

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 34,

AND PORTIONS OF THE METES-AND-BOUNDS SURVEY OF A PORTION OF THE NORTHERLY

RIGHT-OF-WAY OF LAKE MEAD PARKWAY (DRIVE),

AND

METES-AND-BOUNDS SURVEYS OF A PORTION OF THE EASTERLY AND WESTERLY LINES OF

BUREAU OF LAND MANAGEMENT RIGHT-OF-WAY RESERVATION N-73903,

TOWNSHIP 21 SOUTH, RANGE 63 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Lee T. Wilson, Cadastral Surveyor

Under Special Instructions dated April 28, 2016,

and approved April 28, 2016,

which provided for the surveys included under Group No. 962,

and Assignment Instructions dated April 28, 2016.

Survey commenced April 29, 2016

Survey completed June 30, 2017

INDEX DIAGRAM

TOWNSHIP 21 SOUTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34 2	35	36

Dependent Resurvey of a Portion of the Subdivision-of-Section  
 Lines of Section 34..... pp 4 - 6

Dependent Resurvey of Portions of the Metes-and-Bounds Survey  
 of a Portion of The Northerly Right-of-Way of Lake Mead  
 Parkway(Drive)..... pp 7 - 8

Metes-and-Bounds Survey of the Easterly Line of Bureau of Land  
 Management Right-of-Way Reservation N-73903..... pp 8 - 10

Metes-and-Bounds Survey of the Westerly Line of Bureau of Land  
 Management Right-of-Way Reservation N-73903..... pp 10 - 12

## TOWNSHIP 21 SOUTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary, a portion of the subdivision-of-section lines of section 34, and portions of the metes-and-bounds survey of a portion of the northerly right-of-way of Lake Mead Parkway (Drive), and metes-and-bounds surveys of a portion of the easterly and westerly lines of Bureau of Land Management right-of-way reservation N-73903, Township 21 South, Range 63 East, Mount Diablo Meridian, Nevada.

1883 - The south boundary and the subdivisional lines were surveyed by U.S. Deputy Surveyor T.A. Magee, under Contract No. 149.

1931 - The south boundary was dependently resurveyed by U.S. Cadastral Engineers C.S. Swanholm and A. Nelson and U.S. Surveyor R.C. Yundt, under Group No. 169.

1943 - The subdivisional lines were dependently resurveyed by Associate Cadastral Engineer E. Voight and Assistant Cadastral Engineer J.S. Hardison, under Group No. 336.

1991 - 1996 - A portion of the south boundary and a portion of the subdivisional lines were dependently resurveyed, section 34 was subdivided, and a metes-and-bounds survey in section 34 was performed by Cadastral Surveyor, R.E. Williams, under Group No. 713.

The history of other official surveys remote to this area are not included.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the position of the original corners and other calls of the original field note record.

In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 962, dated April 28, 2016.

Measurements were made with Trimble R-8 and R-10 Global Navigation Satellite System (GNSS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only, are entered into the field notes.

The NAD 1983 (2011) (EPOCH:2010.0000) geographic position of the following corners was determined from GNSS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DI1079 NVLM AMS WT FACILITY CORS ARP, DP2494 NVWS WARM SPRINGS CORS ARP, and DI4038 NVPO MT. POTOSI CORS ARP, and carried forward by RTK observations.

The center 1/4 sec. cor. of sec. 34, is as follows:

Latitude: 36°04'43.991" N.      Longitude: 114°55'50.145" W.

## TOWNSHIP 21 SOUTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The cor. of secs. 33 and 34 only, on the S. bdy. of the Tp., is as follows:</p> <p>Latitude: 36°04'17.134" N.      Longitude: 114°56'20.270" W.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor T.A. Magee in 1883, a Portion of the Dependent Resurvey Executed by U.S. Cadastral Engineer C.S. Swanholm in 1931, and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.E. Williams, in 1991 - 1996</p> <hr/> <p>Beginning at the 1/4 sec. cor. of sec. 34 only, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1991 - 1996 dependent resurvey of a portion of the S. bdy., T. 21 S., R. 63 E., executed under Group No. 713, with a mound of stone, 4 1/2 ft. diam., 1 1/2 ft. high, N. of the cor.</p> <p>N. 89°55'00" W., on the S. bdy. of sec. 34.</p> <p>1.30      Bladed access road, 45 lks. wide, bears SE. and NW.</p> <p>1.67      Chain link fence, bears SE. and NW.</p> <p>4.30      Leave dry wash, drains N.</p> <p>8.10      Asphalt recreation path, bears SSE. and NNW.</p> <p>8.497     The 1/4 sec. cor. of sec. 3 only, T. 22 S., R. 63 E., monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the 1991 - 1996 dependent resurvey of a portion of the S. bdy., T. 21 S., R. 63 E., executed under Group No. 713, with a mound of stone, 4 ft. diam., 2 ft. high, S. of the cor.</p> <p>18.555    The point for a witness point at the intersection of the easterly line of Bureau of Land Management right-of-way reservation N-73903 with the S. bdy. of sec. 34, hereinafter described.</p> <p>20.230    The W 1/16 sec. cor. of sec. 34 only, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T21S R63E W 1/16 S34</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1991</p> <hr style="width: 10%; margin: auto;"/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°55'00" W., beginning new measurement.										
11.20	Overhead power line, bears N. and S.										
14.10	Overhead power line, bears N. and S.										
16.30	Overhead power line, bears N. and S.										
18.00	Overhead power line, bears N. and S.										
18.024	Station C966 on the centerline of Bureau of Land Management right-of-way N-10683, determined by Robert L. Carpenter, Nevada Registered Land Surveyor No. 2708, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with brass cap mkd. L.A. D.W.P. SURVEY POINT NO. L42R C966 R.L.S. 2708 POWER SYSTEM, with a steel fence post set alongside. This position, as shown on the record of survey filed in the Clark County Recorder's Office, File 61, Page 69, of Surveys, is accepted as a careful and faithful determination of the intersection point.										
	From this point, station C967 on the centerline of Bureau of Land Management right-of-way N-10683, determined by Robert L. Carpenter, Nevada Registered Land Surveyor No. 2708, monumented with a rebar, 5/8 in. diam., firmly set, flush with the surface of the ground, with illegibly mkd. aluminum cap, as shown on the record of survey filed in the Clark County Recorder's Office, File 61, Page 69, of Surveys, bears N. 0°48'50" W., 81.716 chs. dist.										
19.543	The point for a witness point at the intersection of the westerly line of Bureau of Land Management right-of-way reservation N-73903 with the S. bdy. of sec. 34, hereinafter described.										
19.85	Power line road, 25 lks. wide, bears N. and S.										
20.230	The cor. of secs. 33 and 34 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T21S R63E</td> <td></td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>T22S R63E</td> <td></td> </tr> <tr> <td>S 3</td> <td></td> </tr> </table>	T21S R63E		S33	S34			T22S R63E		S 3	
T21S R63E											
S33	S34										
T22S R63E											
S 3											
	1931										

DEPENDENT RESURVEY OF A PORTION OF THE  
SUBDIVISION-OF-SECTION LINES OF SECTION 34,  
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by Cadastral Surveyor, R.E. Williams, in 1991-1996</p>
	<p>From the center 1/4 sec. cor. of sec. 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713, with a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, W. of the cor.</p>
	<p>S. 89°33'00" W., on a portion of the E-W center line of sec. 34.</p>
12.00	Enter disturbed ground.
14.25	SNWA water line, bears N. and S.
16.153	<p>The point for a witness point at the intersection of the easterly line of Bureau of Land Management right-of-way reservation N-73903 with the E-W center line of sec. 34, hereinafter described.</p>
16.60	Leave disturbed ground.
17.90	Asphalt recreation path, bears NE. and WSW.
20.162	<p>The C-W 1/16 sec. cor. of sec. 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713.</p>
	<p>From this corner, a bent brass rod with no cap (1991 Record, U.S.G.S. Benchmark "HLS 1970", aluminum rod), bears N. 44°00' E., 2.88 chs. dist.</p>
	<p>From this same corner, a Nevada Department of Transportation right-of-way station 182+21.54, monumented with a concrete block, 6 ins. square, firmly set, projecting 5 ins. above the ground, with a nail in the center, and a N. on NNW. side, bears S. 47°37'40" W., 7.494 chs. dist.</p>
	<p>From the C-S 1/16 sec. cor. of sec. 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713, with a mound of stone, 2 ft. diam., 1 ft. high, W. of the cor.</p>
	<p>S. 89°49'00" W., on a portion of the E-W center line of the SW1/4 of sec. 34.</p>
9.10	Enter disturbed ground.
12.05	Bladed road, 20 lks. wide, bears SE. and NW.
16.20	Leave disturbed ground.

DEPENDENT RESURVEY OF A PORTION OF THE  
SUBDIVISION-OF-SECTION LINES OF SECTION 34,  
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
17.356	The point for a witness point at the intersection of the easterly line of Bureau of Land Management right-of-way reservation N-73903 with the E-W center line of the SW1/4 of sec. 34, hereinafter described.
19.11	Chain link fence, bears SE. and NW.
19.35	Gate, bears NE. and SW.
19.60	Access road, 50 lks. wide, bears SE. and NW.
20.03	Chain link fence, bears SE. and NW.
20.199	The SW 1/16 sec. cor. of sec. 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 3 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713.
	<hr/> <p>From the C-W-SW 1/64 sec. cor. of sec. 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713.</p> <p>Cor. is located below overhead power line, bears N. and S.</p> <p>S. 89°49'00" W., on a portion of the E-W center line of the SW1/4 of sec. 34.</p>
2.90	Overhead power line, bears N. and S.
3.75	Power line road, 25 lks. wide, bears SSE. and NNW.
4.80	Overhead power line, bears N. and S.
6.80	Overhead power line, bears N. and S.
8.274	The point for a witness point at the intersection of the westerly line of Bureau of Land Management right-of-way reservation N-73903 and the E-W center line of the SW1/4 of sec. 34, hereinafter described; continue across disturbed area.
10.096	The S 1/16 sec. cor. of secs. 33 and 34, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set, flush with the surface of the ground, in a collar of stone, with an aluminum washer attached, 1 in. diam., mkd. PLS 9833 (no record found). This monument has long standing local usage, is in substantial agreement with the record, and is accepted as the best available evidence of the position of the 1991 - 1996 resurvey corner.
	At the corner point
	Set a magnetic survey nail, 3/16 in. diam., 1 1/4 ins. long, flush with the surface of asphalt in N. First Dawn Street.
	from which

DEPENDENT RESURVEY OF A PORTION OF THE  
 SUBDIVISION-OF-SECTION LINES OF SECTION 34,  
 T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A stainless steel post, 2 1/2 ins. diam., 28 ins. long, set 25 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 45°00'00" E., 2.000 chs. dist., with brass cap mkd. RM T21S R63E S34 132.0 FT. TO COR. 2016 and an arrow pointing to the cor.</p> <p>A brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in westerly curb of N. First Dawn Street, over a magnet, for a reference monument, bears N. 46°56'30" W., 0.550 chs. dist., with top mkd. RM T21S R63E S33 36.3 FT. TO COR. 2017 and an arrow pointing to the cor.</p>
	<p>From the C-W 1/16 sec. cor. of sec. 34.</p>
	<p>N. 4°04'00" W., on a portion of the N-S center line of the NW1/4 of sec. 34.</p>
<p>1.686</p>	<p>Computed centerline of Lake Mead Parkway (Drive), bears N. 59°22'30" E. and S. 59°22'30" W.</p>
<p>5.00</p>	<p>Asphalt recreation path, bears NE. and SW.</p>
<p>5.072</p>	<p>Point for the witness point at the intersection of the N-S center line of the NW1/4 of sec. 34 with the northerly right-of-way of Lake Mead Parkway (Drive), falls in area disturbed by construction of recreational path; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 27 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>W</p> <p> </p> <p>NW1/4   S34</p> <p> </p> <p>W</p> <p>2016</p> </div>
<p>7.40</p>	<p>Asphalt recreation path, bears ESE. and NW.</p>
<p>20.420</p>	<p>The NW 1/16 sec. cor. of sec. 34, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 3 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713.</p>



DEPENDENT RESURVEY OF PORTIONS OF A METES-AND-BOUNDS SURVEY OF  
A PORTION OF THE NORTHERLY RIGHT-OF-WAY OF  
LAKE MEAD PARKWAY (DRIVE),  
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">Reestablishment of Portions of the Survey Executed by Cadastral Surveyor, R.E. Williams, in 1991-1996</p> <hr/>
	<p>From the witness point at the intersection of the N-S center line of sec. 34 with the northerly right-of-way of Lake Mead Parkway (Drive), monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713.</p>
	<p>S. 59°22'30" W., along a portion of the northerly right-of-way of Lake Mead Parkway (Drive).</p>
17.525	<p>The point for a witness point at the intersection of the easterly line of Bureau of Land Management right-of-way reservation N-73903 with the northerly right-of-way of Lake Mead Parkway (Drive), hereinafter described.</p>
22.480	<p>The point for a witness point at the intersection of the N-S center line of the NW1/4 of sec. 34 with the northerly right-of-way of Lake Mead Parkway (Drive), hereinbefore described.</p>
32.086	<p>Beginning of curve, point not monumented.</p> <hr/>
	<p>Along the arc of a circular curve to the right, having a radius of 3,800 ft.; the chord of said arc bears S. 59°36'30" W., 0.469 chs. dist.</p>
0.469	<p>The witness point at the intersection of the E-W center line of sec. 34 with the northerly right-of-way of Lake Mead Parkway (Drive), monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 18 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the 1991 - 1996 subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713, with an iron pipe, 2 1/2 ins. diam., bent over alongside.</p>
	<p>Cor. is located below overhead power line, bears N. and S.</p> <hr/>
	<p>From the witness point at the intersection of the N-S center line of the NW1/4SW1/4 of sec. 34 with the northerly right-of-way of Lake Mead Parkway (Drive), monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 12 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the subdivision of section 34, T. 21 S., R. 63 E., executed under Group No. 713, with a rebar, 5/8 in. diam., 16 ins. long, buried alongside and with a steel pipe, 2 1/2 ins. diam., projecting 30 ins. above the ground, firmly set alongside.</p>
	<p>Cor. is located below overhead power line, bears N. and S.</p>
	<p>Continuing along circular curve to the right, having a radius of 3,800 ft., the chord of said arc bears S. 66°19'20" W., 10.687 chs. dist.</p>

DEPENDENT RESURVEY OF PORTIONS OF A METES-AND-BOUNDS SURVEY OF  
A PORTION OF THE NORTHERLY RIGHT-OF-WAY OF  
LAKE MEAD PARKWAY (DRIVE),  
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
7.854	The point for a witness point at the intersection of the westerly line of Bureau of Land Management right-of-way reservation N-73903 with the northerly right-of-way of Lake Mead Parkway (Drive), hereinafter described.
10.702	<p>The witness point at the intersection of the line bet. secs. 33 and 34 with the northerly right-of-way of Lake Mead Parkway (Drive), monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, 7 ins. below the asphalt surface of Golda Way, with brass cap mkd. as described in the field notes of the 1991 - 1996 dependent resurvey of a portion of the subdivisional lines, T. 21 S., R. 63 E., executed under Group No. 713.</p> <p>From this corner, an aluminum tablet, 2 ins. diam., firmly set, flush with the surface of Golda Way, mkd. J. KLINE RC1 PLS 17827, bears N. 8°30'50" E., 0.010 chs. dist.</p> <p>From this same corner, an aluminum tablet, 2 ins. diam., firmly set, flush with the surface of the easterly curb of Golda Way, mkd. E.G. RADIG INC. 31.78 PLS 7953, bears N. 31°22'00" E., 0.654 chs. dist.</p> <p>From this same corner, an aluminum tablet, 2 ins. diam., firmly set, flush with the surface of the easterly curb of Golda Way, mkd. E.G. RADIG INC. 32.56 PLS 7953, bears S. 81°03'50" E., 0.388 chs. dist.</p> <p>From this same corner, an aluminum tablet, 2 ins. diam., firmly set, flush with the surface of the westerly curb of Golda Way, mkd. E.G. RADIG INC. 33.60 PLS 7953, bears N. 35°42'50" W., 0.709 chs. dist.</p>
<hr/> <p>METES-AND-BOUNDS SURVEY OF A PORTION OF THE EASTERLY LINE OF BUREAU OF LAND MANAGEMENT RIGHT-OF-WAY RESERVATION N-73903, T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p style="text-align: center;">MEMORANDUM</p>	
<p>The following metes-and-bounds survey is of the easterly line of Bureau of Land Management right-of-way reservation N-73903, Corridor A-B (Rainbow Gardens-Eldorado Corridor), as shown on Map 2-7c of the Stateline RMP Supplement. This line was determined at 1400 ft. perpendicular to and parallel with the westerly line of said right-of-way, hereinafter described.</p> <p>All lines described in this metes-and-bounds survey are lines of sight as defined in sections 2-15 and 2-16 of the Manual. Accordingly, these lines are not lines of constant bearing as defined in section 2-13 of the Manual. The following metes-and-bounds survey reports the mean geodetic bearing of these lines of sight.</p>	
<hr/> <p>From the point for a witness point at the intersection of the easterly line of Bureau of Land Management right-of-way reservation N-73903 with the S. bdy. of sec. 34.</p>	

METES-AND-BOUNDS SURVEY OF A PORTION OF THE EASTERLY LINE OF  
BUREAU OF LAND MANAGEMENT RIGHT-OF-WAY RESERVATION N-73903,  
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 27 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">WP T21S R63E SE1/4SW1/4   S34 S 3 T22S</p>
	<p style="text-align: center;">2016</p>
	<p>N. 0°48'40" W., on the easterly line of Bureau of Land Management right-of-way reservation N-73903, in sec. 34.</p>
9.75	Asphalt recreation path, bears SE. and NW.
18.53	Chain link fence, bears SE. and NW.
18.85	Access road, 50 lks. wide, bears SE. and NW.
19.20	Chain link fence, bears SE. and NW.
20.528	<p>The point for a witness point at the intersection of the easterly line of Bureau of Land Management right-of-way reservation N-73903 with the E-W center line of the SW1/4 of sec. 34.</p>
	<p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 25 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">WP T21S R63E S   34 S ——— S E1/2   SW1/4</p>
	<p style="text-align: center;">2016</p>
20.92	Chain link fence, bears ENE. and WSW.
25.30	Overhead power line, bears NE. and SW.
25.60	Power line road, bears NE. and SW.
41.066	<p>The point for a witness point at the intersection of the easterly line of Bureau of Land Management right-of-way reservation N-73903 with the E-W center line of sec. 34.</p>
	<p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 27 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEY OF A PORTION OF THE EASTERLY LINE OF  
 BUREAU OF LAND MANAGEMENT RIGHT-OF-WAY RESERVATION N-73903,  
 T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>WP              T21S R63E              S   34              C ———   ——— C              W   1/2</p> <p>2016</p>
42.75	Asphalt recreation path, bears NE. and SW.
44.46	Southerly edge of asphalt on Lake Mead Parkway (Drive), bears NE. and SW.
46.95	Northerly edge of asphalt on Lake Mead Parkway (Drive), bears NE. and SW.
48.616	<p>The point for a witness point at the intersection of the easterly line of Bureau of Land Management right-of-way reservation N-73903 with the northerly right-of-way of Lake Mead Parkway (Drive).</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 27 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>
	<p>WP              T21S R63E              SE1/4NW1/4   S34</p> <p>2016</p>
	<p>METES-AND-BOUNDS SURVEY OF A PORTION OF THE WESTERLY LINE OF              BUREAU OF LAND MANAGEMENT RIGHT-OF-WAY RESERVATION N-73903,              T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>MEMORANDUM</p> <p>The following metes-and-bounds survey is of a portion of the westerly line of Bureau of Land Management right-of-way reservation N-73903, Corridor A-B (Rainbow Gardens-Eldorado Corridor), as shown on Map 2-7c of the Stateline RMP Supplement. This line was determined at 100 ft. perpendicular to and parallel with the centerline of Bureau of Land Management right-of-way N-10683, for the Intermountain Power Project transmission line. This line is coincident with the westerly line of Bureau of Land Management Right-of-Way N-10683.</p> <p>All lines described in this metes-and-bounds survey are lines of sight as defined in sections 2-15 and 2-16 of the Manual. Accordingly, these lines are not lines of constant bearing as defined in section 2-13 of the Manual. The following metes-and-bounds survey reports the mean geodetic bearing of these lines of sight.</p>

METES-AND-BOUNDS SURVEY OF A PORTION OF THE WESTERLY LINE OF  
 BUREAU OF LAND MANAGEMENT RIGHT-OF-WAY RESERVATION N-73903,  
 T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the point for a witness point at intersection of the westerly line of Bureau of Land Management right-of-way reservation N-73903 with the S. bdy. of sec. 34, determined by Robert L. Carpenter, Nevada Registered Land Surveyor No. 2708, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the surface of the ground, with aluminum cap mkd. L.A. D.W.P. SURVEY POINT NO. L42R R666 R.L.S. 2708 POWER SYSTEM, with a steel fence post set alongside. This position, as shown on the record of survey filed in the Clark County Recorder's Office, File 61, Page 69, of Surveys, is accepted as a careful and faithful determination of the intersection point.</p> <p>At the corner point</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 26 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">WP              T21S R63E              SW1/4SW1/4   S34              S 3              T22S</p> <p style="text-align: center;">2016</p> <p>Retain steel fence post alongside and deposit rebar inside the stainless steel post.</p> <p>N. 0°48'50" W., on the westerly line of Bureau of Land Management right-of-way reservation N-73903, in sec. 34.</p>
20.428	<p>The point for a witness point at the intersection of the westerly line of Bureau of Land Management right-of-way reservation N-73903 with the E-W center line of the SW1/4 of sec. 34.</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 26 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">WP              T21S R63E              S   34              S ——— S              W1/2   SW1/4</p> <p style="text-align: center;">2016</p>
28.280	<p>Station R722, on the westerly line of Bureau of Land Management right-of-way N-10683, coincident with the westerly line of Bureau of Land Management right-of-way reservation N-73903, determined by Robert L. Carpenter, Nevada Registered Land Surveyor No. 2708, monumented with a rebar, 5/8 in. diam., firmly set, 3 ins. below the surface of the ground, with brass cap mkd. L.A. D.W.P. SURVEY POINT NO. L42R R722 R.L.S. 2708 POWER SYSTEM, as shown on the record of survey filed in the Clark County Recorder's Office, File 61, Page 69, of Surveys.</p>

METES-AND-BOUNDS SURVEY OF A PORTION OF THE WESTERLY LINE OF  
BUREAU OF LAND MANAGEMENT RIGHT-OF-WAY RESERVATION N-73903,  
T. 21 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
30.95	Asphalt recreation path, bears ENE. and WSW.
33.22	Southerly edge of asphalt on Lake Mead Parkway (Drive), bears ENE. and WSW.
35.57	Northerly edge of asphalt on Lake Mead Parkway (Drive), bears ENE. and WSW.
37.030	<p>The point for a witness point at the intersection of the westerly line of Bureau of Land Management right-of-way reservation N-73903 with the northerly right-of-way of Lake Mead Parkway (Drive).</p> <p>Set a stainless steel post, 2 1/2 ins. diam., 28 ins. long, 26 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">WP T21S R63E</p> <p style="text-align: center;">NW1/4SW1/4   S34</p> <p style="text-align: center;">2016</p> <p>From this point, Station R720, on the westerly line of Bureau of Land Management right-of-way N-10683, coincident with the westerly line of Bureau of Land Management right-of-way reservation N-73903, determined by Robert L. Carpenter, Nevada Registered Land Surveyor No. 2708, monumented with a rebar, 5/8 in. diam., firmly set, 4 ins. below the surface of the ground, with aluminum cap mkd. L.A. D.W.P. SURVEY POINT NO. L42R R720 R.L.S. 2708 POWER SYSTEM, bears N. 0°48'50" W., 61.257 chs. dist., as shown on the record of survey filed in the Clark County Recorder's Office, File 61, Page 69, of Surveys.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The average elevation of the area surveyed is approximately 1700 feet. General drainage is to the north. Vegetation consists of creosote and cacti.</p> <hr/>

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Carlos Gil-Mendoza

Cadastral Surveyor

CERTIFICATE OF SURVEY

I, Lee T. Wilson, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing the date of April 28th, 2016, I have dependently resurveyed a portion of the south boundary, a portion of the subdivision-of-section lines of section 34, and portions of the metes-and-bounds survey of a portion of the northerly right-of-way of Lake Mead Parkway (Drive), and metes-and-bounds surveys of a portion of the easterly and westerly lines of Bureau of Land Management right-of-way reservation N-73903, Township 21 South, Range 63 East, of the Mount Diablo Meridian, in the state of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

**JUN 15 2022**

(Date)

*Lee T. Wilson*

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary, a portion of the subdivision-of-section lines of section 34, and portions of the metes-and-bounds survey of a portion of the northerly right-of-way of Lake Mead Parkway (Drive), and metes-and-bounds surveys of a portion of the easterly and westerly lines of Bureau of Land Management right-of-way reservation N-73903, Township 21 South, Range 63 East, of the Mount Diablo Meridian, Nevada, executed by Lee T. Wilson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

**AUG 05 2022**

(Date)

*Marshall C. Hammars*

(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 21 South, Range 63 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~