

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY OF TOWNSHIP 22 NORTH, RANGE 19 EAST,

A PORTION OF THE SUBDIVISIONAL LINES,

AND PORTIONS OF THE SEGREGATION SURVEYS OF CERTAIN MINERAL CLAIMS,

AND

THE SUBDIVISION OF SECTIONS 26, 27, 28, 29, 30 AND 35,

TOWNSHIP 22 NORTH, RANGE 20 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Brandon G. Courtright, Cadastral Surveyor

Under Special Instructions dated, June 22, 2017

and approved, June 22, 2017

and Supplemental Special Instructions dated June 1, 2018

and approved June 1, 2018

which provided for the surveys included under Group No. 972,

and Assignment Instructions dated, June 22, 2017.

Survey commenced June 23, 2017

Survey completed July 18, 2017

INDEX DIAGRAM

TOWNSHIP 22 NORTH, RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA

R. 19 E. |

1	6	5	4	3	2	1
12	7	8	9	10	11	12
13	18	17	16	15	14	13
24	19	20	21	22	23	24
4	14				8	
25	30	29	28	27	26	25
2	11				6	
36	31	32	33	34	35	36

SUBDIVISION OF SECTION 26 pp 17 - 18
 SUBDIVISION OF SECTION 27 pp 18 - 20
 SUBDIVISION OF SECTION 28 pp 20 - 21
 SUBDIVISION OF SECTION 29 pp 22 - 24
 SUBDIVISION OF SECTION 30 pp 24 - 25
 SUBDIVISION OF SECTION 35 pp 25 - 29

DEPENDENT RESURVEY OF PORTIONS OF THE SEGREGATION SURVEYS
 OF CERTAIN MINERAL CLAIMS

COPPER KING LODE (ABANDONED AND VOID) pp 29 - 31
 COPPER QUEEN LODE (ABANDONED AND VOID) pp 31 - 32
 JUNIPER LODE (ABANDONED AND VOID) pp 33 - 34
 JUNIPER EXTENSION LODE (ABANDONED AND VOID) pp 34 - 36
 CABIN LODE (ABANDONED AND VOID) pp 36 - 38
 MONARCH NO. 2 LODE (ABANDONED AND VOID) pp 38 - 39

TOWNSHIP 22 NORTH, RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those providing for the dependent resurvey of a portion of the east boundary of Township 22 North, Range 19 East, a portion of the subdivisional lines and portions of the segregation surveys of certain mineral claims, and the subdivision of sections 26, 27, 28, 29, 30 and 35, Township 22 North, Range 20 East, Mount Diablo Meridian, Nevada.

The township boundaries were surveyed by U.S. Deputy Surveyor A.J. Hatch in 1867 under Contract No. 6. A portion of the subdivisional lines were surveyed by U.S. Deputy Surveyors A.J. Hatch and J.C. Smyles in 1872, under Contract No. 50. The west, east (Carson River Guide Meridian), south and north boundaries, and a portion of the subdivisional lines were resurveyed, and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor J.B. Menardi in 1906 under Contract No. 244. Portions of the east and west boundaries were retraced, and a portion of the west boundary was resurveyed by U.S. Transitman A.T. Harris in 1914 under Group No. 13. The boundaries of sections 27, 34 and 35 were dependently resurveyed and segregation surveys of certain mineral claims were conducted by U.S. Cadastral Engineer E. Voigt in 1924 under Group No. 107. A portion of the north boundary of T. 21 N., R. 20 E. was dependently resurveyed by Cadastral Engineer C.S. Swanholm in 1935 under Group No. 156. A portion of the south boundary was dependently resurveyed by Cadastral Surveyor R.A. Pratt in 1987, under Group No. 644.

A dependent resurvey of a portion of the south boundary was executed concurrently under this same Group.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 972, dated June 22, 2017, and the Supplemental Special Instructions dated June 1, 2018.

Measurements were made with Trimble R8 and R10 Global Positioning System (GPS) receivers using the real-time kinematic method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances, only, are entered into the field notes. Measurements to certain topographic features were scaled using rectified aerial imagery.

The NAD 1983 (2011) (Epoch:2010.0000) geographic position, of the following corners were determined by GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS), DG6525 COF1 FERNLEY COOP CORS ARP, DE6254 RNO1 NW RENO COOP CORS ARP, DE6260 STEA STEAD COOP CORS ARP, and carried forward by RTK observations is as follows:

TOWNSHIP 22 NORTH, RANGE 20 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The 1/4 section corner of sections 2 and 35, on the south boundary of the township, is as follows:</p> <p style="margin-left: 40px;">Latitude: 39°43'26.137" N. Longitude: 119°42'20.350" W.</p> <p>The east 1/4 section corner of section 24, Township 22 North, Range 19 East, is as follows:</p> <p style="margin-left: 40px;">Latitude: 39°45'34.304" N. Longitude: 119°47'23.985" W.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 22 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor A.J. Hatch in 1867, a Portion of the Resurvey Executed By U.S. Deputy Surveyor J.B. Menardi in 1906 and a Portion of the Retracement Executed by U.S. Transitman A.T. Harris in 1914</p> <hr/> <p>Beginning at the cor. of secs. 25 and 36, monumented with a granite stone, 18x10x8 ins., firmly set, projecting 7 ins. above the ground, mkd. with 5 notches on N. edge and 1 notch on S. edge, with an embedded mound of stone, 3 ft. diam., W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td colspan="2" style="padding: 0 10px;">T22N R19E</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 10px;">T22N R20E</td> </tr> <tr> <td style="padding: 0 10px;">S25</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 10px;">S31</td> </tr> <tr> <td style="padding: 0 10px;">S36</td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td style="border-left: 1px solid black; padding: 0 5px;"></td> <td></td> </tr> </table> </div> <p style="text-align: center; margin: 10px 0;">2017</p> <p>Bury the mkd. stone alongside the stainless steel post and leave the mound of stone in place.</p> <p>From this cor., a position determined by person(s) unknown, bears S. 76°50'30" W., 0.020 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 12 ins. above an embedded mound of stone, 3 ft. diam. Not utilized during the course of this survey.</p> <p>N. 0°11'30" E., on the E. bdy. of sec. 25.</p> <p>0.07 Barbed wire fence, bears S. 60° E. and N. 60° W.</p>	T22N R19E			T22N R20E	S25			S31	S36			
T22N R19E			T22N R20E										
S25			S31										
S36													

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 22 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
3.479	The closing cor. of secs. 30 and 31, T. 22 N., R. 20 E., hereinafter described.
13.6	Top of ridge, bears E. and W.
24.6	Bottom of drainage, drains S. 80° E.
40.036	The E 1/4 sec. cor. of sec. 25, monumented with a granite stone, 18x12x7 ins. (1906 Record: 20x12x10 ins.), firmly set, flush in the ground, mkd. 1/4 on W. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">T22N R19E T22N R20E 1/4 S25 2017</p>
	Bury the mkd. stone alongside the stainless steel post.
	Cor. is located 10 lks. W. of trail road, 10 lks. wide, bears N. and S., and 45 lks. W. of barbed wire fence, bears N. and S.
	<hr style="width: 20%; margin: auto;"/> N. 0°16'20" W., beginning new measurement.
3.572	The W 1/4 sec. cor. of sec. 30, T. 22 N., R. 20 E., hereinafter described.
15.0	Spur, slopes S. 75° E.
18.5	Ravine, drains N. 70° E.
23.637	The N 1/16 sec. cor. of sec. 30 only, T. 22 N., R. 20 E., hereinafter described.
25.6	Ravine, drains E.
35.6	Top of ridge, bears E. and W.
39.979	The cor. of secs. 24 and 25, monumented with a granite stone, 30x10x8 ins., firmly set, projecting 14 ins. above an embedded mound of stone, 3 ft. diam., mkd. with 2 grooves on E. face and 4 notches on W. edge.
	At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 22 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS										
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>									
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T22N R19E</td> </tr> <tr> <td style="text-align: center;">S24</td> <td style="border-left: 1px solid black; padding-left: 5px;">T22N R20E</td> </tr> <tr> <td style="border-top: 1px solid black; text-align: center;">S25</td> <td style="border-left: 1px solid black; padding-left: 5px; text-align: center;">S30</td> </tr> </table>	T22N R19E		S24	T22N R20E	S25	S30			
T22N R19E										
S24	T22N R20E									
S25	S30									
	2017									
	Bury the mkd. stone alongside the stainless steel post.									
	Cor. is located 53 lks. W. of barbed wire fence, bears N. and S.									
	<hr/> <p>N. 0°05'30" E., on the E. bdy. of sec. 24.</p>									
3.722	The closing cor. of secs. 19 and 30, T. 22 N., R. 20 E., hereinafter described.									
12.7	Ravine, drains E.									
26.9	Head of ravine, drains S. 50° E.									
28.7	Top of westerly end of ridge, extends E.									
38.8	Head of ravine, drains N. 80° E.									
39.956	The E 1/4 sec. cor. of sec. 24, monumented with a basalt stone, 18x11x5 ins. (1906 Record: 18x10x8 ins.), firmly set, projecting 6 ins. above a mound of stone, 3 ft. diam., 1 ft. high, mkd. 1/4 on W. face.									
	At the corner point									
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.									
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T22N R19E</td> <td style="text-align: center;">T22N R20E</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="border-left: 1px solid black;"></td> <td></td> </tr> <tr> <td style="border-top: 1px solid black; text-align: center;">S24</td> <td style="border-left: 1px solid black;"></td> <td></td> </tr> </table>	T22N R19E		T22N R20E	1/4			S24		
T22N R19E		T22N R20E								
1/4										
S24										
	2017									
	Bury the mkd. stone alongside the stainless steel post.									
	Cor. is located 6 lks. E. of barbed wire fence, bears N. and S.									
	<hr/>									

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors A.J. Hatch and J.C. Smyles in 1872, a Portion of the Survey and Resurvey Executed by U.S. Deputy Surveyor J.B. Menardi in 1906 and a Portion of the Dependent Resurvey Executed by U.S. Cadastral Engineer E. Voigt in 1924</p> <hr/> <p>From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 4 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 22 N., R. 20 E., executed concurrently under this same Group.</p> <p>N. 0°00'40" W., bet. secs. 34 and 35.</p>
25.849	<p>Point for the intersection of the S. end line of the Cabin lode (abandoned and void), at a point from which the SW. Cor. of the Cabin lode (abandoned and void), hereinafter described, bears N. 55°30'30" W., 3.619 chs. dist.</p>
32.238	<p>Point for the intersection of the W. side line of the Cabin lode (abandoned and void), at a point from which the SW. Cor. of the Cabin lode (abandoned and void), hereinafter described, bears S. 34°29'30" W., 5.265 chs. dist.</p>
40.035	<p>The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above a mound of stone, 3 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107, with a granite stone, 20x10x6 ins., firmly set alongside, projecting 8 ins. above the ground, mkd. 1/4 on W. face.</p> <p>Bury the mkd. stone alongside the iron post.</p> <hr/> <p>N. 0°04'00" E., beginning new measurement.</p>
11.908	<p>Point for the intersection of the W. side line of the Monarch No. 2 lode (abandoned and void), at a point from which the SW. Cor. of the Monarch No. 2 lode (abandoned and void), hereinafter described, bears S. 40°04'40" E., 9.269 chs. dist.</p>
19.982	<p>Point for the N 1/16 sec. cor. of secs. 34 and 35.</p> <p>POINT NOT MONUMENTED</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.964	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above a mound of stone, 5 ft. diam., 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above a mound of stone, 3 ft. diam., 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107, with an embedded granite boulder, 3x2x1/2 ft. showing alongside, mkd. 1/4 on N. face.</p> <p>S. 89°59'40" W., bet. secs. 26 and 35.</p>
0.6	Spur, slopes S. 20° E.
4.5	Depression, drains N. 5° W.
14.9	Ridge, bears N. and S.
15.68	Trail road, 10 lks. wide, bears N. 15° E. and S. 10° W.
19.859	Point for the W 1/16 sec. cor. of secs. 26 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">S26 W 1/16 — S35</p> <p style="text-align: center;">2017</p>
39.718	The cor. of secs. 26, 27, 34 and 35.
	<hr/> <p>N. 0°36'20" E., bet. secs. 26 and 27.</p>
9.6	Ridge, bears S. 70° E. and N. 70° W.
20.4	Gulch, drains N. 70° W.
22.8	Gulch, drains S. 70° W.
35.0	Top of ridge, bears E. and W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.030	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance by the irregular boundary adjustment method, based on the official record of the 1924 dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E.; there is no remaining evidence of the corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T22N R20E 1/4 S27 S26</p> <p style="text-align: center;">2017</p> <p>Cor. is located 17 lks. W. of a cliff and 75 lks. E. of a ravine, drains N.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°33'50" W., beginning new measurement.</p>
2.2	Spur, slopes N. 60° W.
9.3	Ravine, drains N. 60° W.
19.875	<p>Point for the N 1/16 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S27 S26</p> <p style="text-align: center;">2017</p>
28.2	Ravine, drains N. 80° W.
32.2	Spur, slopes N. 70° W.
39.750	<p>The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107, with a lava stone, 16x12x8 ins., firmly set alongside, mkd. with 2 grooves on E. face and 2 grooves on S. face.</p> <p>Bury the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p>From the cor. of secs. 23, 24, 25 and 26, monumented with a granite stone, 24x12x8 ins., firmly set, projecting 8 ins. above the ground, mkd. with 1 groove on E. face, 2 grooves on S. face and an X on top, with a mound of stone, 3 ft. diam., 1 ft. high, N. of cor.</p>								
	<p>At the corner point</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T22N R20E</td> </tr> <tr> <td style="text-align: center;">S23</td> <td style="text-align: center;">S24</td> </tr> <tr> <td colspan="2" style="text-align: center;">— —</td> </tr> <tr> <td style="text-align: center;">S26</td> <td style="text-align: center;">S25</td> </tr> </table>	T22N R20E		S23	S24	— —		S26	S25
T22N R20E									
S23	S24								
— —									
S26	S25								
	<p style="text-align: center;">2017</p>								
	<p>Bury the mkd. stone in a rebuilt mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>								
	<p>S. 89°24'50" W., bet. secs. 23 and 26.</p>								
12.9	<p>Top of ridge, bears N. 30° E. and S. 30° W.</p>								
20.9	<p>Ravine, drains N. 45° W.</p>								
23.8	<p>Spur, slopes N. 60° W.</p>								
31.2	<p>Ravine, drains N. 20° W.</p>								
41.324	<p>The 1/4 sec. cor. of secs. 23 and 26, monumented with a volcanic stone, 22x10x8 ins., firmly set, projecting 12 ins. above the ground, mkd. 1/4 on N. face, with an embedded mound of stone, 3 ft. diam., N. of cor.</p>								
	<p>At the corner point</p>								
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T22N R20E</td> </tr> <tr> <td colspan="2" style="text-align: center;">S23</td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">—</td> </tr> <tr> <td colspan="2" style="text-align: center;">S26</td> </tr> </table>	T22N R20E		S23		1/4	—	S26	
T22N R20E									
S23									
1/4	—								
S26									
	<p style="text-align: center;">2017</p>								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Bury the mkd. stone alongside the stainless steel post and leave the mound of stone in place.</p> <hr/> <p>S. 89°38'10" W., beginning new measurement.</p>
12.5	Ravine, drains N. 50° W.
25.7	Spur, slopes N. 40° W.
30.0	Ravine, drains N. 25° W.
35.6	Spur, slopes N. 25° W.
39.763	The cor. of secs. 22, 23, 26 and 27.
	<hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107, with a granite stone, 16x10x8 ins., firmly set alongside, projecting 3 ins. above the ground, mkd. 1/4 on W. face, a steel fence post firmly set alongside, and an embedded mound of stone, 3 ft. diam., W. of the cor.</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>N. 0°05'10" E., bet. secs. 27 and 28.</p>
11.0	Low spur, slopes N. 70° E.
16.5	Wash, 15 lks. wide, drains S. 40° E.
19.1	Bottom of drainage, drains S. 70° E.
20.008	Point for the N 1/16 sec. cor. of secs. 27 and 28.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S28 S27</p> <p style="text-align: center;">2017</p>
30.9	Spur, slopes S. 40° E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.016	<p>The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., firmly set, projecting 13 ins. above an embedded mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107, with a granite stone, 22x13x7 ins. (1906 Record 24x10x10 ins.), firmly set alongside, projecting 11 ins. above the ground, mkd. with 3 notches on E. edge and 2 notches on S. edge.</p> <p>Bury the mkd. stone alongside the iron post.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 28 and 29, monumented with a granite stone, 16x10x8 ins., firmly set, projecting 9 ins. above the ground, mkd. 1/4 on W. face, with a scattered mound of stone W. of cor., and a steel fence post firmly set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T22N R20E 1/4 S29 S28</p> <p style="text-align: center;">2017</p> <p>Bury the mkd. stone alongside the stainless steel post and leave the mound of stone in place.</p> <p>N. 0°02'20" W., bet. secs. 28 and 29.</p>
6.7	Spur, slopes E.
11.65	Wash, 5 lks. wide, drains E.
19.999	<p>Point for the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S29 S28</p> <p style="text-align: center;">2017</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
28.0	Spur, slopes N. 60° E.								
33.84	Wash, 5 lks. wide, drains N. 60° E.								
35.9	Spur, slopes N. 70° E.								
39.998	<p>The cor. of secs. 20, 21, 28 and 29, monumented with a quartzite stone, 16x8x6 ins., loosely set, projecting 9 ins. above the ground, mkd. with 4 notches on E. edge and 2 grooves on S. face, with and embedded mound of stone, 3 ft. diam., W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T22N R20E</td> </tr> <tr> <td style="text-align: center;">S20</td> <td style="text-align: center;">S21</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="text-align: center;">S29</td> <td style="text-align: center;">S28</td> </tr> </table> <p style="text-align: center;">2017</p> <p>Bury the mkd. stone alongside the stainless steel post and leave the mound of stone in place.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 30 and 31, monumented with a granite stone, 15x10x8 ins., firmly set, projecting 7 ins. above the ground, faintly mkd. 1/4 on N. face, with an embedded mound of stone, 3 1/2 ft. diam., N. of cor., and a steel fence post firmly set alongside.</p> <p>from which the remaining bearing tree</p> <p style="padding-left: 40px;">The remains of a burnt juniper stump, 10 ins. diam. bears N. 62°10' W., 23 lks. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>	T22N R20E		S20	S21	-----		S29	S28
T22N R20E									
S20	S21								

S29	S28								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS													
	<p style="text-align: center;">T22N R20E S30 1/4 — S31</p> <p style="text-align: center;">2017</p> <p>Bury the mkd. stone alongside the stainless steel post and leave the mound of stone and the steel fence post in place.</p> <p>N. 89°59'50" W., bet. secs. 30 and 31.</p>												
10.8	Ravine, drains S. 35° E.												
26.4	Spur, slopes S. 15° E.												
29.4	Ravine, drains S.												
37.3	Ravine, drains S.												
39.421	The original closing cor. of secs. 30 and 31, monumented with a granite stone, 15x13x6 ins. (Record: 20x14x6 ins.), lying loose in a mound of stone, 3 ft. diam., 1 ft. high, faintly mkd. with 1 groove on a face and 5 grooves on opposite face, with a rebar, 1/2 in. diam., firmly set alongside the mkd. stone, projecting 20 ins. above the mound of stone. Leave the rebar in place and add the marks AM and bury the stone within the mound of stone.												
39.435	Intersect the E. bdy. of T. 22 N., R. 19 E.												
	<p>Point for the closing cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">T22N R19E</td> <td style="border-left: 1px solid black; padding-left: 5px;">T22N R20E</td> <td></td> </tr> <tr> <td style="text-align: center;">S25</td> <td style="border-left: 1px solid black; padding-left: 5px;">S30</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">—</td> <td style="text-align: center;">CC</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">S31</td> <td></td> </tr> </table> <p style="text-align: center;">2017</p> <p>From this point, the cor. of secs. 25 and 36, T. 22 N., R. 19 E., bears S. 0°11'30" W., 3.479 chs. dist., hereinbefore described.</p> <hr style="width: 60%; margin-left: 0;"/>	T22N R19E	T22N R20E		S25	S30			—	CC		S31	
T22N R19E	T22N R20E												
S25	S30												
	—	CC											
	S31												

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 29 and 30, monumented with a granite stone, 18x11x6 ins. (Record: 18x12x10 ins.), firmly set, projecting 9 ins. above the ground, mkd. 1/4 on W. face, with a scattered mound of stone W. of cor., and a steel fence post firmly set alongside.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T22N R20E 1/4 S30 S29</p>
	<p style="text-align: center;">2017</p>
	<p>Bury the mkd. stone alongside the stainless steel post and leave the mound of stone and the steel fence post in place.</p>
	<p>N. 0°05'50" E., bet. secs. 29 and 30.</p>
1.9	<p>Canyon, drains E.</p>
9.1	<p>Top of ridge, bears E. and W.</p>
13.7	<p>Small ravine, drains S. 80° E.</p>
18.1	<p>Ravine, drains S. 45° E.</p>
20.097	<p>Point for the N 1/16 sec. cor. of secs. 29 and 30.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">N 1/16 S30 S29</p>
	<p style="text-align: center;">2017</p>
40.194	<p>The cor. of secs. 19, 20, 29 and 30, monumented with a granite stone, 16x10x8 ins., firmly set, buried in a mound of stone, 3 ft. diam., 2 ft. high, mkd. with 5 notches on E. edge and 2 grooves on S. face.</p>
	<p>from which the bearing trees</p>
	<p style="text-align: center;">A dead juniper, 9 ins. diam., bears N. 15° E., 49 lks. dist., with no visible marks in a charred blaze. (Record: N. 33° E., 52 lks. dist.)</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
	<p>A downed juniper, 8 ins. diam., bears S. 76° E., 46 lks. dist., with no visible marks in a charred blaze. (Record: S. 79°30' E., 56 lks. dist.)</p> <p>A dead juniper, 10 ins. diam., bears S. 70° W., 336 lks. dist., with no visible marks in a charred blaze. (Record: S. 79°35' W., 327 lks. dist.)</p> <p>A downed juniper, 14 ins. diam., bears N. 52° W., 298 lks. dist., with fully healed blaze. (Record: N. 50°45' W., 291 lks. dist.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">T22N R20E</td> </tr> <tr> <td>S19</td> <td>S20</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> </table> <p>2017</p> </div> <p>Bury the mkd. stone alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 89°57'10" W., bet. secs. 19 and 30.</p>	T22N R20E		S19	S20	S30	S29
T22N R20E							
S19	S20						
S30	S29						
6.9	Spur, slopes N. 50° E.						
15.5	Top of ridge, bears S. 70° E. and N. 70° W.						
31.3	Bottom of drainage, drains S. 20° E.						
40.199	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with a granite stone, 16x11x6 ins. (Record: 16x12x10 ins.), firmly set, projecting 8 ins. above the ground, mkd. 1/4 on N. face, with a mound of stone 2 1/2 ft. diam., 2 ft. high, N. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	T22N R20E S19 1/4 — S30 2017								
	Bury the mkd. stone alongside the stainless steel post and leave the mound of stone in place.								
	<hr/> N. 89°56'50" W., beginning new measurement.								
4.4	Ravine, drains S. 70° E.								
16.8	Spur, slopes N. 55° E.								
19.6	Ravine, drains N. 5° W.								
24.5	Spur, slopes N. 20° E.								
27.9	Ravine, drains N. 20° E.								
36.6	Top of ridge, bears S. 30° E. and N. 30° W.								
39.393	Intersect the E. bdy. of T. 22 N., R. 19 E.								
	Point for the closing cor. of secs. 19 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.								
	<table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 5px;">T22N R19E</td> <td style="padding: 5px;">T22N R20E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 5px;">S24</td> <td style="padding: 5px;">S19</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 5px;"></td> <td style="padding: 5px;">— CC</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 5px;"></td> <td style="padding: 5px;">S30</td> </tr> </table>	T22N R19E	T22N R20E	S24	S19		— CC		S30
T22N R19E	T22N R20E								
S24	S19								
	— CC								
	S30								
	2017								
	From this point, the cor. of secs. 24 and 25, T. 22 N., R. 19 E., bears S. 0°05'30" W., 3.722 chs. dist., hereinbefore described.								
39.469	The original closing cor. of secs. 19 and 30, monumented with granite stone, 15x13x8 ins. (1906 Record: 16x12x12 ins.), firmly set, projecting 10 ins. above the ground, mkd. with 4 grooves on N. face and 2 grooves on S. face, with an embedded mound of stone, 3 1/2 ft. diam., E. of cor.								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Add marks AM to the stone and bury in place, destroy the mound of stone.

The point for the 1/4 sec. cor. of sec. 30 only, on the E. bdy. of T. 22 N., R. 19 E., and at midpoint in latitude on the W. bdy. of sec. 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

T22N R19E T22N R20E
| 1/4
| S30

2017

Point located on west edge of trail road, 10 lks. wide, bears N. and S.

From this point, the E 1/4 sec. cor. of sec. 25, T. 22 N., R. 19 E., bears S. 0°16'20" E., 3.572 chs. dist., hereinbefore described.

The point for the N 1/16 sec. cor. of sec. 30 only, on the E. bdy. of T. 22 N., R. 19 E., and at midpoint in latitude bet. the W 1/4 sec. cor. of sec. 30 and the closing cor. of secs. 19 and 30.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

| N 1/16
| S30

2017

Point is located 3 ft. E. of barbed wire fence, bears N. and S.

From this point, the cor. of secs. 24 and 25, T. 22 N., R. 19 E., bears N. 0°16'20" W., 16.342 chs. dist., hereinbefore described.

SUBDIVISION OF SECTION 26,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°03'30" E., on the N-S center line of sec. 26.</p> <p>22.98 Trail road, 10 lks. wide, bears N. 75° E. and S. 35° W.</p> <p>40.174 Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T22N R20E C 1/4 S26</p> <p style="text-align: center;">2017</p> <p>60.098 Point for the C-N 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S26 C</p> <p style="text-align: center;">2017</p> <p>80.022 The 1/4 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26, reestablished by Thomas A. Foote, Nevada Registered Land Surveyor No. 3736, in 1972-1976, monumented with a rebar, 5/8 ins. diam., 12 ins. long, firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. 1/4 25 26 LS3736, as shown on Survey Map No. 985, filed in Washoe County, Nevada, with a stake, 3/4 ins. diam., firmly set alongside, projecting 5 ins. above the ground, and with a granite stone, 16x9x8 ins., lying loose alongside, mkd. 1/4 on a face. This is accepted as a careful and faithful reestablishment of the position of the 1906 corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	--

SUBDIVISION OF SECTION 26,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T22NR20E 1/4 S26 S25</p> <p>2017</p>
	<p>Bury the rebar and the mkd. stone alongside stainless steel post.</p> <p>S. 89°46'50" W., on the E-W center line of sec. 26.</p>
40.732	The center 1/4 sec. cor. of sec. 26.
80.065	The 1/4 sec. cor. of secs. 26 and 27.
	<hr/> <p>From the C-N 1/16 sec. cor. of sec. 26.</p> <p>S. 89°42'30" W., on the E-W center line of the NW1/4 of sec. 26.</p>
39.548	The N 1/16 sec. cor. of secs. 26 and 27.
	<hr/> <p>SUBDIVISION OF SECTION 27, T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above a mound of stone, 5 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107, with a granite stone, 12x12x7 ins. (1906 Record: 16x12x8 ins.), lying loose alongside, mkd. 1/4 on a face.</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>N. 0°07'20" E., on the N-S center line of sec. 27.</p>
39.994	Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E-W center line.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

SUBDIVISION OF SECTION 27,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T22N R20E C 1/4 S27 2017
59.921	Point for the C-N 1/16 sec. cor. of sec. 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> C N 1/16 S27 C </div> 2017
79.71	Trail road, 10 lks. wide, bears N. 50° E. and S. 50° W.
79.849	The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above an embedded mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107, with a granite stone, 13x10x7 ins., embedded in the mound of stone, mkd. 1/4 on a face. <hr/>
	From the 1/4 sec. cor. of secs. 26 and 27. N. 89°56'00" W., on the E-W center line of sec. 27.
40.413	The center 1/4 sec. cor. of sec. 27.
78.41	Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.
80.396	The 1/4 sec. cor. of secs. 27 and 28. <hr/>
	From the N 1/16 sec. cor. of secs. 26 and 27. N. 89°51'20" W., on the E-W center line of the NE1/4 of sec. 27.
40.173	The C-N 1/16 sec. cor. of sec. 27. <hr/>
	N. 89°49'10" W., on the E-W center line of the NW1/4 of sec. 27.
24.13	Dirt road, 15 lks. wide, bears N. 35° E. and S. 10° W.

SUBDIVISION OF SECTION 27,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 39.993</p>	<p>The N 1/16 sec. cor. of secs. 27 and 28.</p>
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 28, T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>From the 1/4 sec. cor. of secs. 28 and 33, monumented with a granite stone, 16x10x8 ins., firmly set, projecting 10 ins. above the ground, mkd. 1/4 on N. face, with an embedded mound of stone, 3 ft. diam., N. of cor., and a steel fence post firmly set alongside.</p>	
<p>At the corner point</p>	
<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>	
<p style="text-align: center;">T22N R20E S28 1/4 — S33</p> <p style="text-align: center;">2017</p>	
<p>Bury the mkd. stone alongside the stainless steel post and leave the mound of stone and the steel fence post in place.</p>	
<p>N. 0°01'40" E., on the N-S center line of sec. 28.</p>	
<p>40.027</p>	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T22N R20E C 1/4 S28</p> <p style="text-align: center;">2017</p>
<p>Raise a mound of stone, 3 ft. base, 2 ft. high, SW. of cor.</p>	
<p>60.043</p>	<p>Point for the C-N 1/16 sec. cor. of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 28,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">C N 1/16 S28 C</p> <p style="text-align: center;">2017</p>
80.059	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with a granite stone, 15x8x6 ins., lying loose in a scattered mound of stone, mkd. 1/4 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T22N R20E S21 1/4 — S28</p> <p style="text-align: center;">2017</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 27 and 28.</p>
	<p>N. 89°56'20" W., on the E-W center line of sec. 28.</p>
40.054	<p>The center 1/4 sec. cor. of sec. 28.</p>
80.092	<p>The 1/4 sec. cor. of secs. 28 and 29.</p> <hr/>
	<p>From the N 1/16 sec. cor. of secs. 27 and 28.</p>
	<p>N. 89°55'40" W., on the E-W center line of the NE1/4 of sec. 28.</p>
31.14	<p>Trail road, 10 lks. wide, bears N. 35° E. and S. 35° W.</p>
40.072	<p>The C-N 1/16 sec. cor. of sec. 28.</p> <hr/>
	<p>N. 89°57'40" W., on the E-W center line of the NW1/4 of sec. 28.</p>
40.059	<p>The N 1/16 sec. cor. of secs. 28 and 29.</p> <hr/>

SUBDIVISION OF SECTION 29,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.017	<p>From the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>N. 89°55'20" W., on the E-W center line of the NE1/4 of sec. 29.</p> <p>The C-N 1/16 sec. cor. of sec. 29.</p>
3.34	<p>N. 89°56'00" W., on the E-W center line of the NW1/4 of sec. 29.</p> <p>Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.</p>
39.954	<p>The N 1/16 sec. cor. of secs. 29 and 30.</p>
<p>SUBDIVISION OF SECTION 30, T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
40.060	<p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 0°04'10" W., on the N-S center line of sec. 30.</p> <p>Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
60.140	<p style="text-align: center;">T22N R20E C 1/4 S30</p> <p style="text-align: center;">2017</p> <p>Point for the C-N 1/16 sec. cor. of secs. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
80.220	<p style="text-align: center;">C N 1/16 S30 C</p> <p style="text-align: center;">2017</p> <p>The 1/4 sec. cor. of secs. 19 and 30.</p>
<p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>N. 89°54'10" W., on the E-W center line of sec. 30.</p>	

SUBDIVISION OF SECTION 30,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.087	The center 1/4 sec. cor. of sec. 30.
79.03	Barbed wire fence, bears N. and S.
79.31	Trail road, 10 lks. wide, bears N. and S.
79.364	The 1/4 sec. cor. of sec. 30, on the E. bdy. of T. 22 N., R. 19 E.
	<hr/>
	From the N 1/16 sec. cor. of secs. 29 and 30.
	N. 89°55'40" W., on the E-W center line of the NE1/4 of sec. 30.
40.143	The C-N 1/16 sec. cor. of sec. 30.
	<hr/>
	N. 89°55'30" W., on the E-W center line of the NW1/4 of sec. 30.
39.347	The N 1/16 sec. cor. of sec. 30, on the E. bdy. of T. 22 N., R. 19 E.
	<hr/>
	SUBDIVISION OF SECTION 35, T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp. monumented with an iron post, 1 in. diam., firmly set, projecting 17 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107.
	N. 0°07'10" W., on the N-S center line of sec. 35.
40.001	Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T22N R20E C 1/4 S35
	2017

SUBDIVISION OF SECTION 35,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
47.949	Point for the intersection of the S. side line of the Copper Queen lode (abandoned and void), at a point from which the SW. Cor. of the Copper Queen lode (abandoned and void), hereinafter described, bears S. 61°39'10" W., 9.836 chs. dist.
58.267	Point for the intersection of the N. side line of the Copper Queen lode (abandoned and void), at a point from which the NE. Cor. of the Copper Queen lode (abandoned and void), hereinafter described, bears N. 61°39'10" E., 8.074 chs. dist.
59.922	The point for the C-N 1/16 sec. cor. of sec. 35. POINT NOT MONUMENTED
79.843	The 1/4 sec. cor. of secs. 26 and 35. From the 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the boundaries of secs. 27, 34 and 35 of T. 22 N., R. 20 E., executed under Group No. 107, with an embedded mound of stone, 4 ft. diam., N. of cor. Cor. is located 4 ft. S. of barbed wire fence, bears E. and W. S. 89°48'50" W., on the E-W center line of sec. 35.
20.633	The C-E 1/16 sec. cor. of the SE1/4 of sec. 35, determined by Thomas A. Foote, Nevada Professional Land Surveyor No. 3736, in 1972-1976, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. C-E 1/16 SEC 35 LS3736, as shown on Survey Map No. 984, filed in Washoe County, Nevada. This is accepted as a careful and faithful determination of the position of the corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. C——C E 1/16 SE1/4 S35 2017 Insert the rebar inside stainless steel post.

SUBDIVISION OF SECTION 35,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S. 89°37'50" W., beginning new measurement.
0.551	The C-E 1/16 sec. cor. of the NE1/4 of sec. 35, determined by Thomas A. Foote, Nevada Professional Land Surveyor No. 3736, monumented with a rebar, 5/8 in. diam., firmly set, flush in the ground, with aluminum cap mkd. S35 SW COR LOT2, as shown on Survey Map No. 984, filed in Washoe County, Nevada. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	E 1/16 NE1/4 S35 C———C
	2017
	Insert the rebar inside stainless steel post.
	—————
	S. 89°49'10" W., beginning new measurement.
20.089	The center 1/4 sec. cor. of sec. 35.
23.197	Intersect the E. side line of the Copper King lode (abandoned and void), at a point from which the NE. Cor. of the Copper King lode (abandoned and void), hereinafter described, bears N. 9°19'40" E., 7.659 chs. dist.
32.433	Intersect the W. side line of the Copper King lode (abandoned and void), at a point from which the NW. Cor. of the Copper King lode (abandoned and void), hereinafter described, bears N. 9°19'40" E., 9.186 chs. dist.
34.716	Intersect the N. side line of the Juniper Extension lode (abandoned and void), at a point from which the SE. Cor. of the Juniper Extension lode (abandoned and void), hereinafter described, bears S. 57°59'20" E., 4.549 chs. dist.
40.015	Point for the C-W 1/16 sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

SUBDIVISION OF SECTION 35,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	W 1/16 C———C S35 2017
43.517	Intersect the E. side line of the Cabin lode (abandoned and void), at a point from which the NE. Cor. of the Cabin lode (abandoned and void), hereinafter described, bears N. 34°29'30" E., 1.667 chs. dist.
51.779	Intersect the S. side line of the Juniper Extension lode (abandoned and void), at a point from which the SW. Cor. of the Juniper Extension lode (abandoned and void), hereinafter described, bears N. 57°59'20" W., 3.737 chs. dist.
54.571	Intersect the W. side line of the Cabin lode (abandoned and void), at a point from which the NW. Cor. of the Cabin lode (abandoned and void), hereinafter described, bears N. 34°29'30" E., 7.956 chs. dist.
59.941	The 1/4 sec. cor. of secs. 34 and 35.
	<hr/> From the W 1/16 sec. cor. of sec. 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 22 N., R. 20 E., executed concurrently under this same Group. N. 0°03'50" W., on the N-S center line of the SW1/4 of sec. 35.
5.128	Point for the intersection of the S. end line of the Juniper lode (abandoned and void), at a point from which the SW. Cor. of the Juniper lode (abandoned and void), hereinafter described, bears N. 70°42'30" W., 3.564 chs. dist.
15.880	Point for the intersection of the W. side line of the Juniper lode (abandoned and void), at a point from which the SW. Cor. of the Juniper lode (abandoned and void), hereinafter described, bears S. 19°17'30" W., 10.144 chs. dist.
32.621	Intersect the S. side line of the Juniper Extension lode (abandoned and void), at a point from which the SE. Cor. of the Juniper Extension lode (abandoned and void), hereinafter described, bears S. 57°59'20" E., 5.105 chs. dist.
40.018	The C-W 1/16 sec. cor. of sec. 35.

SUBDIVISION OF SECTION 35,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 0°01'40" W., on the N-S center line of the NW1/4 of sec. 35.
3.330	Intersect the N. side line of the Juniper Extension lode (abandoned and void), at a point from which the NE. Cor. of the Juniper Extension lode (abandoned and void), hereinafter described, bears S. 57°59'20" E., 10.800 chs. dist.
19.952	Point for the NW1/16 sec. cor. of sec. 35, at intersection with the E-W center line of the NW1/4 of sec. 35.
	POINT NOT MONUMENTED
39.904	The W 1/16 sec. cor. of secs. 26 and 35.
	From the point for the C-N 1/16 sec. cor. of sec. 35.
	S. 89°54'20" W., on the E-W center line of the NW1/4 of sec. 35.
19.892	The point for the NW1/16 sec. cor. of sec. 35.
34.711	Point for the intersection of the E. side line of the Monarch No. 2 lode (abandoned and void), at a point from which the NE. Cor. of the Monarch No. 2 lode (abandoned and void), hereinafter described, bears N. 40°04'40" W., 10.542 chs. dist.
39.785	The point for the N 1/16 sec. cor. of secs. 34 and 35.
	<p style="text-align: center;">DEPENDENT RESURVEY OF PORTIONS OF SEGREGATION SURVEYS OF CERTAIN MINERAL CLAIMS, T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p style="text-align: center;">MEMORANDUM</p>
	<p>Mineral claims segregated by U.S. Cadastral Engineer E. Voigt in 1924 have been determined abandoned and void in memorandum, dated April 25, 2017.</p>
	<p style="text-align: center;">REESTABLISHMENT OF PORTIONS OF THE SEGREGATION SURVEYS EXECUTED BY U.S. CADASTRAL ENGINEER E. VOIGT IN 1924</p>
	<p style="text-align: center;">COPPER KING LODE (ABANDONED AND VOID)</p>
	<p>From the SW. Cor. of the Copper King lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the segregation survey of the Copper King lode, executed under Group No. 107.</p>

DEPENDENT RESURVEY OF PORTIONS OF SEGREGATION SURVEYS
OF CERTAIN MINERAL CLAIMS,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S. 80°40'20" E., on the S. end line of the Copper King lode (abandoned and void).
3.621	Intersect the N. end line of the Juniper lode (abandoned and void), at a point from which the NE. Cor. of the Juniper lode (abandoned and void), bears S. 70°42'30" E., 4.022 chs. dist., hereinafter described.
9.109	SE. Cor. of the Copper King lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above an embedded mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the segregation survey of the Copper King lode, executed under Group No. 107.

	N. 9°19'40" E., on the E. side line of the Copper King lode (abandoned and void).
15.068	Intersect the E-W center line of sec. 35, at a point from which the center 1/4 sec. cor. of sec. 35, bears N. 89°49'10" E., 3.108 chs. dist., hereinbefore described.
22.062	Intersect the S. side line of the Copper Queen lode (abandoned and void), at a point from which the SW. Cor. of the Copper Queen lode (abandoned and void), bears S. 61°39'10" W., 7.612 chs. dist., hereinafter described.
22.727	NE. Cor. of the Copper King lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the segregation survey of the Copper King lode, executed under Group No. 107.

	N. 80°40'20" W., on the N. end line of the Copper King lode (abandoned and void).
9.108	NW. Cor. of the Copper King lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the segregation survey of the Copper King lode, executed under Group No. 107.

	S. 9°19'40" W., on the W. side line of the Copper King lode (abandoned and void).

DEPENDENT RESURVEY OF PORTIONS OF SEGREGATION SURVEYS
OF CERTAIN MINERAL CLAIMS,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.324	Intersect the W. end line of the Copper Queen lode (abandoned and void), at a point from which the NW. Cor. of the Copper Queen lode (abandoned and void), bears N. 28°20'50" W., 4.045 chs. dist., hereinafter described.
9.186	Intersect the E-W center line of sec. 35, at a point from which the C-W 1/16 sec. cor. of sec. 35, bears S. 89°49'10" W., 7.582 chs. dist., hereinbefore described.
10.504	Intersect the N. side line of the Juniper Extension lode (abandoned and void), at a point from which the NE. Cor. of the Juniper Extension lode (abandoned and void), bears S. 57°59'20" E., 2.108 chs. dist., hereinafter described.
15.971	Intersect the E. end line of the Juniper Extension lode (abandoned and void), at a point from which the SE. Cor. of the Juniper Extension lode (abandoned and void), bears S. 32°00'40" W., 4.047 chs. dist., hereinafter described.
22.091	Intersect the N. end line of the Juniper lode (abandoned and void), at a point from which the NW. Cor. of the Juniper lode (abandoned and void), bears N. 70°42'30" W., 1.382 chs. dist., hereinafter described.
22.727	SW. Cor. of the Copper King lode (abandoned and void), and place of beginning.
	<hr/> <p>COPPER QUEEN LODGE (ABANDONED AND VOID)</p>
	From the point for the intersection of the N. end line of the Copper Queen lode (abandoned and void) with the N-S center line of sec. 35.
	POINT NOT MONUMENTED
	From this point, the NE. Cor. of the Copper Queen lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above an embedded mound of stone, 2 1/2 ft. diam., with brass cap mkd. as described in the field notes of the segregation survey of the Copper Queen lode, executed under Group No. 107, bears N. 61°39'10" E., 8.074 chs. dist.
	From this same point, the center 1/4 sec. cor. of sec. 35, bears S. 0°07'10" E., 18.266 chs. dist., hereinbefore described.
	S. 61°39'10" W., on a portion of the N. side line of the Copper Queen lode (abandoned and void).

DEPENDENT RESURVEY OF PORTIONS OF SEGREGATION SURVEYS
OF CERTAIN MINERAL CLAIMS,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.716	<p>NW. Cor. of the Copper Queen lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above an embedded mound of stone, 4 ft. diam., with brass cap mkd. as described in the field notes of the segregation survey of the Copper Queen lode, executed under Group No. 107.</p> <hr/>
	<p>S. 28°20'50" E., on the W. end line of the Copper Queen lode (abandoned and void).</p>
4.045	<p>Intersect the W. side line of the Copper King lode (abandoned and void), at a point from which the NW. Cor. of the Copper King lode (abandoned and void), bears N. 9°19'40" E., 1.324 chs. dist., hereinbefore described.</p>
9.091	<p>SW. Cor. of the Copper Queen lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the segregation survey of the Copper Queen lode, executed under Group No. 107.</p> <hr/>
	<p>N. 61°39'10" E., on a portion of the S. side line of the Copper Queen lode (abandoned and void).</p>
7.612	<p>Intersect the E. side line of the Copper King lode (abandoned and void), at a point from which the NE. Cor. of the Copper King lode (abandoned and void), bears N. 9°19'40" E., 0.665 chs. dist., hereinbefore described.</p>
9.836	<p>Point for the intersection of the S. side line of the Copper Queen lode (abandoned and void) with the N-S center line of sec. 35.</p>
	<p>POINT NOT MONUMENTED</p> <p>From this point, the SE. Cor. of the Copper Queen lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the segregation survey of the Copper Queen lode, executed under Group No. 107, bears N. 61°39'10" E., 12.954 chs. dist.</p> <p>From this same point, the center 1/4 sec. cor. of sec. 35, bears S. 0°07'10" E., 7.948 chs. dist., hereinbefore described.</p> <hr/>

DEPENDENT RESURVEY OF PORTIONS OF SEGREGATION SURVEYS
OF CERTAIN MINERAL CLAIMS,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">JUNIPER LODGE (ABANDONED AND VOID)</p> <p>From the point for the intersection of the S. end line of the Juniper lode (abandoned and void) with the N-S center line of the SW1/4 of sec. 35.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, the W 1/16 sec. cor. of sec. 35, on the S. bdy. of the Tp., bears S. 0°03'50" E., 5.128 chs. dist., hereinbefore described.</p> <p>From this same point, the SW. Cor. of the Juniper lode (abandoned and void), determined at the center of an embedded mound of stone, 3 ft. diam., with an iron post, 1 in. diam., 36 ins. long, lying loose alongside, with brass cap mkd. as described in the field notes of the segregation survey of the Juniper lode, executed under Group No. 107, and with a dilapidated juniper post, 5 ins. diam., 4 ft. long, lying loose alongside, bears N. 70°42'30" W., 3.564 chs. dist. Reset the iron post, 10 ins. in the ground to solid rock, over a plastic encased-magnet, and in a mound of stone, 4 ft. base, 2 1/2 ft. high, and add the marks 2017 to the brass cap. Deposit dilapidated wood post under mound of stone.</p> <p>S. 70°42'30" E., on a portion of the S. end line of the Juniper lode (abandoned and void).</p> <p>5.518 SE. Cor. of the Juniper lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above an embedded mound of stone, 4 ft. diam., with brass cap mkd. as described in the field notes of the segregation survey of the Juniper lode, executed under Group No. 107.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 19°17'30" E., on the E. side line of the Juniper lode (abandoned and void).</p> <p>22.734 NE. Cor. of the Juniper lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above an embedded mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the segregation survey of the Juniper lode, executed under Group No. 107.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 70°42'30" W., on the N. end line of the Juniper lode (abandoned and void).</p> <p>4.022 Intersect the S. end line of the Copper King lode (abandoned and void), at a point from which the SW. Cor. of the Copper King lode (abandoned and void), bears N. 80°40'20" W., 3.621 chs. dist., hereinbefore described.</p>

DEPENDENT RESURVEY OF PORTIONS OF SEGREGATION SURVEYS
OF CERTAIN MINERAL CLAIMS,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
7.699	Intersect the W. side line of the Copper King lode (abandoned and void), at a point from which the SW. Cor. of the Copper King lode (abandoned and void), bears S. 9°19'40" W., 0.636 chs. dist., hereinbefore described.
9.081	<p>NW. Cor. of the Juniper lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd. as described in the field notes of the segregation survey of the Juniper lode (abandoned and void), executed under Group No. 107.</p> <hr/> <p>S. 19°17'30" W., on the W. side line of the Juniper lode (abandoned and void).</p>
12.590	<p>Point for the intersection of the W. side line of the Juniper lode (abandoned and void) with the N-S center line of the SW1/4 of sec. 35.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, the W 1/16 sec. cor. of sec. 35, on the S. bdy. of the Tp., bears S. 0°03'50" E., 15.880 chs. dist., hereinbefore described.</p> <p>From this same point, the SW. Cor. of the Juniper lode (abandoned and void), bears S. 19°17'30" W., 10.144 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">JUNIPER EXTENSION LODGE (ABANDONED AND VOID)</p> <p>From the SW. Cor. of the Juniper Extension lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above an embedded mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the segregation survey of the Juniper Extension lode, executed under Group No. 107.</p> <p>S. 57°59'20" E., on the S. side line of the Juniper Extension lode (abandoned and void).</p>
1.439	Intersect the W. side line of the Cabin lode (abandoned and void), at a point from which the NW. Cor. of the Cabin lode (abandoned and void), bears N. 34°29'30" E., 6.467 chs. dist., hereinafter described.
3.737	Intersect the E-W center line of sec. 35, at a point from which the 1/4 sec. cor. of secs. 34 and 35, bears S. 89°49'10" W., 8.162 chs. dist., hereinbefore described.

DEPENDENT RESURVEY OF PORTIONS OF SEGREGATION SURVEYS
OF CERTAIN MINERAL CLAIMS,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.539	Intersect the E. side line of the Cabin lode (abandoned and void), at a point from which the NE. Cor. of the Cabin lode (abandoned and void), bears N. 34°29'30" E., 6.073 chs. dist., hereinafter described.
17.622	Intersect the N-S center line of the SW1/4 of sec. 35, at a point from which the C-W 1/16 sec. cor. of sec. 35, bears N. 0°03'50" W., 7.397 chs. dist., hereinbefore described.
22.727	SE. Cor. of the Juniper Extension lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the segregation survey of the Juniper Extension lode (abandoned and void), executed under Group No. 107. _____
	N. 32°00'40" E., on the E. end line of the Juniper Extension lode (abandoned and void).
4.047	Intersect the W. side line of the Copper King lode (abandoned and void), at a point from which the SW. Cor. of the Copper King lode (abandoned and void), bears S. 9°19'40" W., 6.756 chs. dist., hereinbefore described.
9.091	NE. Cor. of the Juniper Extension lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above an embedded mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the segregation survey of the Juniper Extension lode, executed under Group No. 107. _____
	N. 57°59'20" W., on the N. side line of the Juniper Extension lode (abandoned and void).
2.108	Intersect the W. side line of the Copper King lode (abandoned and void), at a point from which the NW. Cor. of the Copper King lode (abandoned and void), bears N. 9°19'40" E., 10.504 chs. dist., hereinbefore described.
4.549	Intersect the E-W center line of sec. 35, at a point from which the C-W 1/16 sec. cor. of sec. 35, bears S. 89°49'10" W., 5.299 chs. dist., hereinbefore described.
10.800	Intersect the N-S center line of the NW1/4 of sec. 35, at a point from which the C-W 1/16 sec. cor. of sec. 35, bears S. 0°01'40" E., 3.330 chs. dist., hereinbefore described.

DEPENDENT RESURVEY OF PORTIONS OF SEGREGATION SURVEYS
OF CERTAIN MINERAL CLAIMS,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
21.375	Intersect the S. end line of the Monarch No. 2 lode (abandoned and void), at a point from which the SE. Cor. of the Monarch No. 2 lode (abandoned and void), bears N. 49°56'40" E., 2.592 chs. dist., hereinafter described.
22.727	<p>NW. Cor. of the Juniper Extension lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the segregation survey of the Juniper Extension lode, executed under Group No. 107.</p> <p>Cor. is located in a wash, drains N. 60° W.</p> <hr/> <p>S. 32°00'40" W., on the W. end line of the Juniper Extension lode (abandoned and void).</p>
4.177	Intersect the S. end line of the Monarch No. 2 lode (abandoned and void), at a point from which the SW. Cor. of the Monarch No. 2 lode (abandoned and void), bears S. 49°56'40" W., 2.110 chs. dist., hereinafter described.
9.091	SW. Cor. of the Juniper Extension lode (abandoned and void), and place of beginning.
	<hr/> <p style="text-align: center;">CABIN LODE (ABANDONED AND VOID)</p> <p>From the point for the intersection of the S. end line of the Cabin lode (abandoned and void) with the line bet. secs. 34 and 35.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, the 1/4 sec. cor. of secs. 34 and 35, bears N. 0°00'40" W., 14.186 chs. dist., hereinbefore described.</p> <p>From this same point, the SW. Cor. of the Cabin lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. as described in the field notes of the segregation survey of the Cabin lode, executed under Group No. 107, with an embedded mound of stone, 3 ft. diam., N. of cor., bears N. 55°30'30" W., 3.619 chs. dist.</p> <p>S. 55°30'30" E., on a portion of the S. end line of the Cabin lode (abandoned and void).</p>

DEPENDENT RESURVEY OF PORTIONS OF SEGREGATION SURVEYS
OF CERTAIN MINERAL CLAIMS,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
5.472	SE. Cor. of the Cabin lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the segregation survey of the Cabin lode, executed under Group No. 107, with a mound of stone, 1 ft. diam., 1 ft. high, N. of cor.
	<hr/> N. 34°29'30" E., on the E. side line of the Cabin lode (abandoned and void).
16.628	Intersect the S. side line of the Juniper Extension lode (abandoned and void), at a point from which the SW. Cor. of the Juniper Extension lode (abandoned and void), bears N. 57°59'20" W., 10.539 chs. dist., hereinbefore described.
21.034	Intersect the E-W center line of sec. 35, at a point from which the C-W 1/16 sec. cor. of sec. 35, bears N. 89°49'10" E., 3.502 chs. dist., hereinbefore described.
22.701	NE. Cor. of the Cabin lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. as described in the field notes of the segregation survey of the Cabin lode, executed under Group No. 107, with an embedded mound of stone, 2 ft. diam., W. of cor.
	<hr/> N. 55°30'30" W., on the N. end line of the Cabin lode (abandoned and void).
9.091	NW. Cor. of the Cabin lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above an embedded mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the segregation survey of the Cabin lode, executed under Group No. 107.
	<hr/> S. 34°29'30" W., on a portion of the W. side line of the Cabin lode (abandoned and void).
6.467	Intersect the S. side line of the Juniper Extension lode (abandoned and void), at a point from which the SW. Cor. of the Juniper Extension lode (abandoned and void), bears N. 57°59'20" W., 1.439 chs. dist., hereinbefore described.
7.956	Intersect the E-W center line of sec. 35, at a point from which the 1/4 sec. cor. of secs. 34 and 35, bears S. 89°49'10" W., 5.370 chs. dist., hereinbefore described.

DEPENDENT RESURVEY OF PORTIONS OF SEGREGATION SURVEYS
OF CERTAIN MINERAL CLAIMS,
T. 22 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
17.436	<p>Point for the intersection of the W. side line of the Cabin lode (abandoned and void) with the line bet. secs. 34 and 35.</p> <p>POINT NOT MONUMENTED</p> <p>From this point, the 1/4 sec. cor. of secs. 34 and 35, bears N. 0°00'40" W., 7.797 chs. dist., hereinbefore described.</p> <p>From this same point, the SW. Cor. of the Cabin lode (abandoned and void), bears S. 34°29'30" W., 5.265 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">MONARCH NO. 2 LODE (ABANDONED AND VOID)</p> <p>From the SW. Cor. of the Monarch No. 2 lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. as described in the field notes of the segregation survey of the Monarch No. 2 lode, executed under Group No. 107.</p> <p>Cor. is located on northerly edge of a small wash, 5 lks. wide, drains N. 60° W.</p> <p>N. 49°56'40" E., on the S. end line of the Monarch No. 2 lode (abandoned and void).</p>
2.110	<p>Intersect the W. end line of the Juniper Extension lode (abandoned and void), at a point from which the NW. Cor. of the Juniper Extension lode (abandoned and void), bears N. 32°00'40" E., 4.177 chs. dist., hereinbefore described.</p>
6.501	<p>Intersect the N. side line of the Juniper Extension lode (abandoned and void), at a point from which the NW. Cor. of the Juniper Extension lode (abandoned and void), bears N. 57°59'20" W., 1.352 chs. dist., hereinbefore described.</p>
9.093	<p>SE. Cor. of the Monarch No. 2 lode (abandoned and void), monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above an embedded mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the segregation survey of the Monarch No. 2 lode, executed under Group No. 107.</p> <hr/> <p>N. 40°04'40" W., on a portion of the E. side line of the Monarch No. 2 lode (abandoned and void).</p>
12.185	<p>Point for the intersection of the E. side line of the Monarch No. 2 lode (abandoned and void) with the E-W center line of the NW1/4 of sec. 35.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Brandon K. Grace	Cadastral Surveyor
Justin V. Haddon	Cadastral Surveyor
Steven R. Lambeth	Contractor Employee
Kenneth W. Tynan	Student Trainee
Griffin B. Dekker	Student Trainee

CERTIFICATE OF SURVEY

I, Brandon G. Courtright, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22nd day of June, 2017, and supplemental special instructions bearing date of June 1, 2018, I have dependently resurveyed a portion of the east boundary of Township 22 North, Range 19 East, a portion of the subdivisional lines and portions of the segregation surveys of certain mineral claims, and subdivided sections 26, 27, 28, 29, 30 and 35 of Township 22 North, Range 20 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

APR 23 2019

(Date)

Michael O. Hammon

/For Brandon G. Courtright
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the east boundary of Township 22 North, Range 19 East, a portion of the subdivisional lines and portions of the segregation surveys of certain mineral claims, and the subdivision of sections 26, 27, 28, 29, 30 and 35, of Township 22 North, Range 20 East, Mount Diablo Meridian, Nevada, executed by Brandon G. Courtright, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

APR 23 2019

(Date)

Michael O. Hammon
(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Township 22 North, Range 20 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~