

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
AND A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 32,  
AND THE FURTHER SUBDIVISION OF SECTION 32,  
TOWNSHIP 22 SOUTH, RANGE 60 EAST,  
OF THE MOUNT DIABLO MERIDIAN,  
IN THE STATE OF NEVADA

EXECUTED BY

Jose A. Serna, Cadastral Surveyor

Under Special Instructions dated February 10, 2014,  
and approved February 10, 2014,  
which provided for the surveys included under Group No. 930,  
and Assignment Instructions dated February 10, 2014.

Survey commenced February 27, 2014

Survey completed October 30, 2014

## INDEX DIAGRAM

TOWNSHIP 22 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	<div> <div>5</div> <div>32</div> </div> <div> <div>3</div> <div>2</div> </div>	33	34	35	36

Subdivision of Section 32 ..... pp. 8 - 26

## TOWNSHIP 22 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and a portion of the subdivision-of-section lines of section 32, and the further subdivision of section 32, Township 22 South, Range 60 East, of the Mount Diablo Meridian, Nevada.</p> <p>The exterior township and subdivisional lines were surveyed by U.S. Deputy Surveyors W.H. Proctor and J.M. Brunt, in 1881, under Contract No. 115.</p> <p>The north, south, and west boundaries, a portion of the east boundary and the subdivisional lines, with the establishment of 1/16 section corners on all lines, were dependently resurveyed by Cartographer (Cadastral) W.H. Sylvester, in 1954-55, under Group No. 357.</p> <p>A portion of the west boundary and subdivisional lines were retraced and a portion of the subdivision of section lines were surveyed by Cadastral Surveyor P.K. Russell, in 1957, under Group No. 357.</p> <p>The history of other surveys remote to the area are not included.</p> <p>Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.</p> <p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 930, dated February 10, 2014.</p> <p>Measurements were made with Trimble R8-3 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method. The direction of each line is with reference to the true meridian and are reported as mean bearings. The distances are reported as horizontal measurement at a mean ground elevation of 2,800 feet above sea level.</p> <p>The NAD83 (2011), (EPOCH: 2010.0000) geographic positions for the corners below were determined by GPS static observations processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) NVCA CARLTON SQUARE 2 CORS ARP, NVLM AMS WT FACILITY CORS ARP, NVPO MT. POTOSI CORS ARP, NVTP TROPICANA CORS ARP and carried forward by RTK observations.</p> <p>The cor. of secs. 28, 29, 32 and 33, is as follows:</p> <p>Latitude: 35°59'53.474" N.      Longitude: 115°16'47.824" W.</p>
--------	---

## TOWNSHIP 22 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The 1/4 sec. cor. of secs. 31 and 32, is as follows:</p> <p>Latitude: 35°59'27.022" N.      Longitude: 115°17'50.494" W.</p> <p>The February 27, 2014 mean magnetic declination was determined to be 12°02' E., as obtained from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors W.H. Proctor and J.M. Brunt in 1881 and a Portion of the Dependent Resurvey Executed by Cartographer (Cadastral) W.H. Sylvester in 1954-55</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, with a brass cap mkd. as described in the field notes of the 1954-55 dependent resurvey of the subdivisional lines, executed under Group No. 357, with a scattered mound of stone, 3 ft. base, 8 ins. high, W. of cor.</p> <p>N. 2°57'20" W., bet. secs. 32 and 33.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p> <p>9.654      Point for the S-N 1/64 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S-N 1/64 S32 S33</p> <p>2014</p> </div> <p>16.60      Dirt road, 14 lks. wide, bears N. 72° E. and S. 72° W.</p> <p>19.308      The N 1/16 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., 8 ins. high, projecting 3 ins. above the mound, with brass cap mkd. as described in the field notes of the 1954-55 dependent resurvey of the subdivisional lines, executed under Group No. 357, with a scattered mound of stone, 4 ft. base, 10 ins. high, W. of cor.</p> <hr/> <p>N. 2°55'50" W., beginning new measurement.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.654	<p>Point for the N-N 1/64 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N-N 1/64 S32 S33</p> <p style="text-align: center;">2014</p>
19.308	<p>The cor. of secs. 28, 29, 32 and 33, perpetuated by Vernon C. Little, Nevada Professional Land Surveyor No. 13930, in 2005, monumented with a brass cap, 2 ins. diam., firmly set in a concrete well, with brass cap mkd. S28 S29 S32 S33 PLS 13930, as shown on Plat, Sheet No. 2 of 7 Sheets, recorded in Clark County, Nevada, Book 127, Page 100 of Plats. This corner was accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 33°48'00" W., 162.7 lks. dist., mkd. VTN 107.41 PLS 13930 RM.</p> <p style="padding-left: 40px;">An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 37°22'00" W., 149.0 lks. dist., mkd. VTN 98.42 PLS 13930 RM.</p> <p style="padding-left: 40px;">An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 63°55'20" W., 156.1 lks. dist., mkd. VTN 103.10 PLS 13930 RM.</p> <p style="padding-left: 40px;">An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 66°45'00" W., 171.4 lks. dist., mkd. VTN 113.17 PLS 13930 RM.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with a brass cap mkd. as described in the field notes of the 1954-55 dependent resurvey of the subdivisional lines, executed under Group No. 357, with a mound of stone, 4 ft. diam., 2 ft. high, SW. of cor.</p> <p>N. 5°14'20" W., bet. secs. 31 and 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
9.872	<p>Point for the S-N 1/64 sec. cor. of secs. 31 and 32.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	POINT NOT MONUMENTED
19.50	Center of wash, 23 lks. wide, 10 ft. deep, drains NE.
19.744	<p>The N 1/16 sec. cor. of secs. 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the 1954-55 dependent resurvey of the subdivisional lines, executed under Group No. 357, with a mound of stone, 4 ft. diam., 1 ft. high, W. of cor.</p> <p>From this cor., the SW. cor. of a storage shack, wood construction, 32 ft. x 17 ft., bears N. 11°01'20" W., 5.89 chs. dist.</p> <hr/> <p>N. 5°20'50" W., beginning new measurement.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
9.871	<p>Point for the N-N 1/64 sec. cor. of secs. 31 and 32.</p> <p>Set an aluminum rod with spiral flute, 24 ins. long, 5/8 in. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with a 2 ins. diam. aluminum cap mkd.</p> <div style="text-align: center;"> <p>BLM N-N 1/64 S31 S32 2014</p> </div>
19.742	<p>Point for the cor. of secs. 29, 30, 31 and 32, reestablished by Michael G. Smith, Nevada Professional Land Surveyor No. 16201, in 2007, as shown on Record of Survey, recorded in Clark County, Nevada, File 166, Page 81 of Surveys. The position of this cor., determined from the reference monuments established by Michael G. Smith, has been adopted by local professional land surveyors and is accepted as a careful and faithful reestablishment of the position of the original corner. The point falls on a concrete form surrounding a manhole cover where it is impracticable to establish a permanent monument.</p> <p>from which the only remaining reference monuments</p> <p style="padding-left: 40px;">An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 28°48'00" E., 158.6 lks. dist., mkd. MSG PLS 16201.</p> <p style="padding-left: 40px;">An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 31°44'10" E., 145.1 lks. dist., mkd. MSG PLS 16201.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>and from which new reference monuments</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 49°03'00" W., 150.3 lks. dist., with brass cap mkd. RM T22S R60E S31 99.2 FT. TO COR. 2014 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 74°07'50" W., 163.8 lks. dist., with brass cap mkd. RM T22S R60E S30 108.1 FT. TO COR. 2014 and an arrow pointing to the corner.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 87°08'20" W., bet. secs. 29 and 32.</p> <p>Over nearly level land, along W. Cactus Ave, asphalt surfaced, 73 lks. wide, bears N. 87° E. and S. 87° W.</p> <p>5.107 Point for the E-E-E 1/256 sec. cor. of secs. 29 and 32.</p> <p>Set a standard brass tablet, 3 1/4 ins. diam., flush in asphalt, in W. Cactus Ave, mkd.</p> <p style="text-align: center;">S29</p> <p style="text-align: center;">E-E-E 1/256</p> <p style="text-align: center;">S32</p> <p style="text-align: center;">2014</p> <p>10.214 Point for the E-E 1/64 sec. cor. of secs. 29 and 32.</p> <p>POINT NOT MONUMENTED</p> <p>20.429 The E 1/16 sec. cor. of secs. 29 and 32, perpetuated by William G. Stout, Nevada Professional Land Surveyor No. 14420, in 2010, monumented with a brass tablet, 3 1/4 ins. diam., firmly set flush in asphalt, in W. Cactus Ave., mkd. E 1/16 T22S R60E S29 S32 PLS 14420 2010, as shown on Record of Survey, recorded in Clark County, Nevada, File 182, Page 1 of Surveys. This corner has been adopted by local professional land surveyors and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>from which</p> <p>An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 11°21'20" E., 70.2 lks. dist., mkd. VTN 46.35 PLS 13930 RM.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 23°45'00" E., 76.1 lks. dist., mkd. VTN 60.26 PLS 13930 RM.</p> <p>An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 25°14'50" W., 73.7 lks. dist., mkd. VTN 48.55 PLS 13930 RM.</p> <p>An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 9°57'50" W., 68.5 lks. dist., mkd. VTN 45.16 PLS 13930 RM.</p> <hr/> <p>S. 87°07'50" W., beginning new measurement.</p> <p>Over nearly level land, along W. Cactus Ave, asphalt surfaced, 73 lks. wide, bears N. 87° E. and S. 87° W.</p>
20.448	<p>The 1/4 sec. cor. of secs. 29 and 32, perpetuated by Trent J. Keenan, Nevada Professional Land Surveyor No. 16802, in 2014, monumented with a brass cap, 2 ins. diam., firmly set flush in a concrete form in asphalt, in W. Cactus Ave., mkd. 2014 1/4 S29 S32 PLS 16802, as recorded in Clark County, Nevada, File 193, Page 19 of Surveys. This corner has been adopted by local professional land surveyors and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>from which</p> <p>An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 23°02'40" E., 133.7 lks. dist., mkd. VTN 88.42 PLS 13930 RM.</p> <p>An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 53°55'40" E., 124.0 lks. dist., mkd. VTN 81.99 PLS 13930 RM.</p> <p>An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 56°14'00" W., 125.5 lks. dist., mkd. VTN 82.86 PLS 13930 RM.</p> <p>An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 21°21'40" W., 145.6 lks. dist., mkd. VTN 96.17 PLS 13930 RM.</p> <hr/> <p>N. 88°51'10" W., beginning new measurement.</p> <p>Over nearly level land, along W. Cactus Ave, asphalt surfaced, 73 lks. wide, bears S. 89° E. and N. 89° W.</p>
5.105	<p>Point for the E-E-W 1/256 sec. cor. of secs. 29 and 32.</p>



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a standard brass tablet, 3 1/4 ins. diam., flush in asphalt, in W. Cactus Ave., mkd.</p> <div style="text-align: right;"> S29  E-E-W 1/256 ———  S32 </div> <p style="text-align: center;">2014</p>
10.210	<p>Point for the E-W 1/64 sec. cor. of secs. 29 and 32.</p> <p>Set a standard brass tablet, 3 1/4 ins. diam., flush in asphalt, in W. Cactus Ave., mkd.</p> <div style="text-align: right;"> S29  E-W 1/64 ———  S32 </div> <p style="text-align: center;">2014</p>
15.315	<p>Point for the W-E-W 1/256 sec. cor. of secs. 29 and 32.</p> <p>POINT NOT MONUMENTED</p>
20.20	<p>East edge of S. Quarterhorse Ln., asphalt surfaced, bears S. 4° E. and N. 4° W.</p>
20.420	<p>Point for the W 1/16 sec. cor. of secs. 29 and 32, reestablished by Jerry E. Barnson, Nevada Professional Land Surveyor No. 4046, in 1997, as shown on Record of Survey, recorded in Clark County, Nevada, File 88, Page 19, of Surveys. This corner was later perpetuated by Vernon C. Little, Nevada Professional Land Surveyor No. 13930, in 2008, as shown on Record of Survey, recorded in Clark County, Nevada, File 174, Page 5 of Surveys. The position of this cor., determined from the reference monuments established by Vernon C. Little, has been adopted by local professional land surveyors, and is accepted as a careful and faithful reestablishment of the position of the original corner. The point falls on a manhole cover where it is impractical to establish a permanent monument.</p> <p>from which the only remaining reference monuments</p> <p style="padding-left: 40px;">An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 17°02'20" E., 127.0 lks. dist., mkd. RM 83.77 PLS 14420.</p> <p style="padding-left: 40px;">An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 51°58'10" E., 107.7 lks. dist., mkd. VTN 71.08 PLS 13930 RM.</p> <p style="padding-left: 40px;">An aluminum cap, 1 1/2 ins. diam., firmly set flush in top of curb, for a reference monument, bears N. 18°09'00" W., 122.8 lks. dist., mkd. VTN 81.07 PLS 13930 RM.</p> <hr style="width: 30%; margin-left: auto; margin-right: 0;"/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 88°49'40" W., beginning new measurement.
	Over nearly level land, along W. Cactus Ave, asphalt surfaced, 73 lks. wide, bears S. 89° E. and N. 89° W.
0.20	West edge of S. Quarterhorse Ln., asphalt surfaced, bears S. 4° E. and N. 4° W.
5.110	Point for the E-W-W 1/256 sec. cor. of secs. 29 and 32. Set a standard brass tablet, 3 1/4 ins. diam., flush in asphalt, in W. Cactus Ave., mkd.
	<div style="text-align: right;">S29</div> <div style="text-align: center;">E-W-W 1/256     <u>        </u></div> <div style="text-align: right;">S32</div>
	2014
10.220	Point for the W-W 1/64 sec. cor. of secs. 29 and 32. POINT NOT MONUMENTED
15.330	Point for the W-W-W 1/256 sec. cor. of secs. 29 and 32. POINT NOT MONUMENTED
20.440	The cor. of secs. 29, 30, 31 and 32.
<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 32, T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by Cadastral Surveyor P.K. Russell in 1957</p> <hr/>	
	From the center 1/4 sec. cor. of sec. 32, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, projecting 4 ins. above the mound, with brass cap mkd. as described in the field notes of the 1957 survey of the subdivision of section 32, T. 22 S., R. 60 E., executed under Group No. 357.
	N. 4°25'40" W., on the N-S center line of sec. 32.
	Over gently rolling land, through creosote and scattered yucca plants.
2.20	Center of dirt road, 14 lks. wide, bears N. 41° E. and S. 34° W.
4.70	Center of dirt road, 14 lks. wide, bears N. 78° E. and S. 71° W.
9.410	Point for the C-S-N 1/64 sec. cor. of sec. 32.

DEPENDENT RESURVEY OF A PORTION  
OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p>S32</p> <p>C-S-N</p> <p>1/64</p> <p>2014</p>
18.820	<p>The C-N 1/16 sec. cor. of sec. 32, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, projecting 5 ins. above the mound, with brass cap mkd. as described in the field notes of the 1957 survey of the subdivision of section 32, T. 22 S., R. 60 E., executed under Group No. 357.</p> <hr/> <p>N. 4°26'50" W., beginning new measurement.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
9.399	<p>The C-N-N 1/64 sec. cor. of sec. 32, determined by Trent J. Keenan, Nevada Professional Land Surveyor No. 16802, in 2014, monumented with a rebar, 5/8 in. diam., firmly set, flush with the ground, with an aluminum cap mkd. DIAMONDBACK LAND SURVEYING PLS 16802, and a divot to mark the location of the actual point, as shown on Record of Survey, recorded in Clark County, Nevada, File 193, Page 19 of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 4°27'30" W., beginning new measurement.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
9.397	<p>The 1/4 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>S. 88°36'30" W., on the E-W center line of sec. 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
4.989	<p>Point for the C-E-E-E 1/256 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION  
OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S32
	C-E-E-E
	1/256
	2014
9.978	Point for the C-E-E 1/64 sec. cor. of sec. 32.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S32
	C-E-E
	1/64
	2014
19.956	The C-E 1/16 sec. cor. of sec. 32, monumented with an iron post, 2 1/2 ins. diam. firmly set flush in a mound of stone, 2 1/2 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 1957 survey of the subdivision of section 32, T. 22 S., R. 60 E., executed under Group No. 357.
	<hr/> S. 88°34'30" W., beginning new measurement.  Over gently rolling land, through creosote and scattered yucca plants.
19.957	The center 1/4 sec. cor. of sec. 32.
	<hr/> S. 88°35'30" W., beginning new measurement.  Over gently rolling land, through creosote and scattered yucca plants.
1.00	Center of dirt road, 13 lks. wide, bears S. 37° E. and N. 26° W.
1.70	Center of dirt road, 13 lks. wide, bears N. 33° E. and S. 31° W.
5.023	Point for the C-E-E-W 1/256 sec. cor. of sec. 32.  POINT NOT MONUMENTED
10.046	Point for the C-E-W 1/64 sec. cor. of sec. 32.  POINT NOT MONUMENTED
12.00	Center of dirt road, 11 lks. wide, bears N. 49° E. and S. 51° W.
15.069	Point for the C-W-E-W 1/256 sec. cor. of sec. 32.

DEPENDENT RESURVEY OF A PORTION  
OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	POINT NOT MONUMENTED
20.092	The C-W 1/16 sec. cor. of sec. 32, monumented with an iron post, 2 1/2 ins. diam. firmly set, projecting 8 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 1957 survey of the subdivision of section 32, T. 22 S., R. 60 E., executed under Group No. 357.
	S. 88°35'30" W., beginning new measurement.
3.10	Center of dirt road, 14 lks. wide, bears N. 5° E. and S. 5° W.
5.011	Point for the C-E-W-W 1/256 sec. cor. of sec. 32.
	POINT NOT MONUMENTED
10.022	Point for the C-W-W 1/64 sec. cor. of sec. 32.
	POINT NOT MONUMENTED
20.044	The 1/4 sec. cor. of secs. 31 and 32.
	FURTHER SUBDIVISION OF SECTION 32, T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the C-E 1/16 sec. cor. of sec. 32.
	N. 3°40'10" W., on the N-S center line of the NE1/4 of sec. 32.
	Over gently rolling land, through creosote and scattered yucca plants.
9.528	Point for the C-S-NE 1/64 sec. cor. of sec. 32.
	POINT NOT MONUMENTED
11.40	Center of dirt road, 14 lks. wide, bears N. 72° E. and S. 67° W.
19.056	The NE 1/16 sec. cor. of sec. 32, monumented with a rebar, no record found, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with an aluminum cap, 1 1/2 ins. diam., mkd. PLS 14195. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NE 1/16 S32
	2014

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Insert rebar inside the stainless steel post.
	N. 3°40'10" W., beginning new measurement.
9.526	Point for the C-N-NE 1/64 sec. cor. of sec. 32. POINT NOT MONUMENTED
19.052	The E 1/16 sec. cor. of secs. 29 and 32.
	From the N 1/16 sec. cor. of secs. 32 and 33. S. 87°52'10" W., on the E-W center line of the NE1/4 of sec. 32. Over gently rolling land, through creosote and scattered yucca plants.
5.047	Point for the C-E-E-NE 1/256 sec. cor. of sec. 32. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.  S32  C-E-E-NE  1/256  2014
10.094	Point for the C-E-NE 1/64 sec. cor. of sec. 32. POINT NOT MONUMENTED
20.188	The NE 1/16 sec. cor. of sec. 32.
	N. 87°52'10" W., beginning new measurement.
20.198	The C-N 1/16 sec. cor. of sec. 32.
	From the point for the C-E-NE 1/64 sec. cor. of sec. 32. N. 3°17'50" W., on the N-S center line of the NE1/4NE1/4 of sec. 32. Over gently rolling land, through creosote and scattered yucca plants.
9.590	Point for the NE-NE 1/64 sec. cor. of sec. 32, at the intersection with the E-W center line of the NE1/4NE1/4. POINT NOT MONUMENTED

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 19.180</p>	<p>The point for the E-E 1/64 sec. cor. of secs. 29 and 32.</p>
<p>5.077</p>	<hr/> <p>From the N-N 1/64 sec. cor. of secs. 32 and 33.</p> <p>S. 87°30'10" W., on the E-W center line of the NE1/4NE1/4 of sec. 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p> <p>Point for the C-E-NE-NE 1/256 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S32</p> <p style="text-align: center;">C-E-NE-NE</p> <p style="text-align: center;">1/256</p> <p style="text-align: center;">2014</p>
<p>10.154</p>	<p>The point for the NE-NE 1/64 sec. cor. of sec. 32.</p>
<p>20.308</p>	<p>The point for the C-N-NE 1/64 sec. cor. of sec. 32.</p>
<p>9.622</p>	<hr/> <p>From the C-E-NE-NE 1/256 sec. cor. of sec. 32.</p> <p>N. 3°06'50" W., on the N-S center line of the NE1/4NE1/4NE1/4 of sec. 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
<p>9.591</p>	<hr/> <p>The E-E-E 1/256 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the C-E-E 1/64 sec. cor. of sec. 32.</p> <p>N. 3°18'40" W., on the N-S center line of the SE1/4NE1/4 of sec. 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
<p>9.591</p>	<p>Point for the SE-NE 1/64 sec. cor. of sec. 32, at the intersection with the E-W center line of the SE1/4NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S32
	SE-NE
	1/64
	2014
14.00	Center of dirt road, 14 lks. wide, bears N. 72° E. and S. 67° W.
19.182	The point for the C-E-NE 1/64 sec. cor. of sec. 32.
	From the S-N 1/64 sec. cor. of secs. 32 and 33.
	S. 88°14'20" W., on the E-W center line of the SE1/4NE1/4 of sec. 32.
	Over gently rolling land, through creosote and scattered yucca plants.
5.018	Point for the C-E-SE-NE 1/256 sec. cor. of sec. 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S32
	C-E-SE-NE
	1/256
	2014
10.036	The SE-NE 1/64 sec. cor. of sec. 32.
20.072	The point for the C-S-NE 1/64 sec. cor. of sec. 32.
	From the C-E-SE-NE 1/256 sec. cor. of sec. 32.
	N. 3°08'00" W., on the N-S center line of the NE1/4SE1/4NE1/4 of sec. 32.
	Over gently rolling land, through creosote and scattered yucca plants.
5.50	Center of dirt road, 14 lks. wide, bears N. 72° E. and S. 70° W.
9.623	The C-E-E-NE 1/256 sec. cor. of sec. 32.
	From the C-W 1/16 sec. cor. of sec. 32.
	N. 4°47'10" W., on the N-S center line of the NW1/4 of sec. 32.



FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over gently rolling land, through creosote and scattered yucca plants.
4.70	Southerly edge of bladed dirt cul-de-sac, 152 lks. wide.
9.642	Point for the C-S-NW 1/64 sec. cor. of sec. 32.  POINT NOT MONUMENTED  Point is located near the center of the bladed dirt portion of S. Quarterhorse Ln., 61 lks. wide, bears S. 4° E. and N. 4° W.
12.92	Concrete barricade, extending N. 65° E. and S. 65° W. across S. Quarterhorse Ln.
13.10	From this point, an intersection of a dirt road, 21 lks. wide, with the Westerly edge of S. Quarterhorse Ln., bears WEST, 0.22 chs. dist., with road extending S. 80° W. from the intersection.
18.80	Three wire power transmission line, bears N. 89° E. and S. 89° W.
19.00	Beginning of pavement for S. Quarterhorse Ln., 48 lks. wide, bears S. 4° E., bladed dirt surfaced, and N. 4° W., asphalt surfaced.
19.284	The NW 1/16 sec. cor. of sec. 32, perpetuated by Danny E. Hill, Nevada Professional Land Surveyor No. 9389, in 2010, monumented with an aluminum cap, 3 ins. diam., firmly set, flush in a concrete form, in S. Quarterhorse Ln., mkd. G.C. WALLACE INC. NW 1/16 S32 PLS 9389 2010, as shown on Corner Record PM-10, recorded in Clark County, Nevada, Instrument No. 201010080000502. This corner has been adopted by adjacent land owners and local professional land surveyors, and is accepted as a careful and faithful perpetuation of the position of the corner.  from which  An aluminum cap, 2 ins. diam., firmly set flush in a concrete form, for a reference monument, bears N. 43°17'40" E., 77.9 lks. dist., mkd. RM 51.44 PLS 9389.  An aluminum cap, 2 ins. diam., firmly set flush in a concrete form, for a reference monument, bears S. 61°46'30" E., 70.0 lks. dist., mkd. RM 46.23 PLS 9389.  An aluminum cap, 2 ins. diam., firmly set flush in a concrete form, for a reference monument, bears S. 51°40'00" W., 77.7 lks. dist., mkd. RM 51.27 PLS 9389.  An aluminum cap, 2 ins. diam., firmly set flush in a concrete form, for a reference monument, bears N. 37°46'20" W., 116.7 lks. dist., mkd. RM 77.01 PLS 9389.

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 4°52'00" W., beginning new measurement.
	Over graded land, along S. Quarterhorse Ln., asphalt surfaced, 48 lks. wide, bears S. 4° E. and N. 4° W.
0.20	From this point, an intersection of a dirt road, 21 lks. wide, with the Westerly edge of S. Quarterhorse Ln., bears WEST, 0.21 chs. dist., with road extending S. 50° W. from the intersection.
0.40	From this point, an intersection of a dirt road, 21 lks. wide, with the Westerly edge of S. Quarterhorse Ln., bears West, 0.21 chs. dist., with road extending N. 85° W.
9.629	Point for the C-N-NW 1/64 sec. cor. of sec. 32.  Set a standard brass tablet, 3 1/4 ins. diam., flush in asphalt, near the center of S. Quarterhorse Ln., mkd.  S32  C-N-NW  1/64  2014
10.10	From this point, an intersection of power transmission lines, bears WEST, 0.44 chs. dist., with three wire power transmission lines extending S. 4° E., N. 89° W. and N. 4° W.
11.70	From this point, an intersection of a dirt road, 15 lks. wide, with the Westerly edge of S. Quarterhorse Ln., bears WEST, 0.25 chs. dist., with road extending WSW. from this intersection.
16.60	From this point, an intersection of a dirt road, 15 lks. wide, with the Westerly edge of S. Quarterhorse Ln., bears WEST, 0.22 chs. dist., with road extending SWW. from this intersection.
19.258	The W 1/16 sec. cor. of secs. 29 and 32. <hr/> From the C-N 1/16 sec. cor. of sec. 32. S. 89°53'10" W., on the E-W center line of the NW1/4 of sec. 32. Over gently rolling land, through creosote and scattered yucca plants.
5.061	Point for the C-E-E-NW 1/256 sec. cor. of sec. 32.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S32
	C-E-E-NW
	1/256
	2014
6.70	Center of dirt road, 11 lks. wide, bears NE. and SW.
10.122	Point for the C-E-NW 1/64 sec. cor. of sec. 32.
	POINT NOT MONUMENTED
20.00	East edge of S. Quarterhorse Ln., asphalt surfaced, 48 lks. wide, bears S. 4° E. and N. 4° W.
20.244	The NW 1/16 sec. cor. of sec. 32.
	<hr/>
	S. 89°50'20" W., beginning new measurement.
	Over gently rolling land, through creosote and scattered yucca plants.
0.20	West edge of S. Quarterhorse Ln., asphalt surfaced, 48 lks. wide, bears S. 4° E. and N. 4° W.
5.073	The C-E-W-NW 1/256 sec. cor. of sec. 32, monumented with a rebar, no record found, 5/8 in. diam., firmly set, 1 in. below the surface of the ground, with an aluminum cap, 1 1/2 ins. diam., mkd. BARNSON PLS 4046. This is accepted as a careful and faithful determination of the position of the corner.
	<hr/>
	S. 89°51'50" W., beginning new measurement.
	Over gently rolling land, through creosote and scattered yucca plants.
0.43	Chain-link fence, bears S. 4° E. and N. 4° W. From this point, a corner of chain-link fences bears N. 4°20' W., 0.01 chs. dist., with fences extending S. 4° E. and S. 89° W.
5.04	Chain-link fence, bears S. 5° E. and N. 5° W. From this point, a corner of chain-link fences bears N. 4°58' W., 0.01 chs. dist., with fences extending N. 89° E. and S. 5° E.
5.050	The C-W-NW 1/64 sec. cor. of sec. 32, monumented with a nail and brass tag, no record found, firmly set in concrete, with brass tag stamped PLS 4046. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a standard brass tablet, 3 1/4 ins. diam., flush in concrete form, mkd.

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S32
	C-W-NW
	1/64
	2014
	<hr/>
	S. 89°52'40" W., beginning new measurement.
	Over gently rolling land, through creosote and scattered yucca plants.
5.053	Point for the C-W-W-NW 1/256 sec. cor. of sec. 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	4 ins. in the ground, to bedrock, over a plastic-encased magnet,
	and in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	S32
	C-W-W-NW
	1/256
	2014
10.106	The N 1/16 sec. cor. of secs. 31 and 32.
	<hr/>
	From the point for the C-E-NW 1/64 sec. cor. of sec. 32.
	N. 4°39'50" W., on the N-S center line of the NE1/4NW1/4
	sec. 32.
	Over gently rolling land, through creosote and scattered yucca plants.
9.514	Point for the NE-NW 1/64 sec. cor. of sec. 32, at the
	intersection of the E-W center line of the NE1/4NW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, over a plastic-encased magnet, and in a
	collar of stone, with brass cap mkd.
	S32
	NE-NW 1/64
	2014
19.027	The E-W 1/64 sec. cor. of secs. 29 and 32.
	<hr/>
	From the C-N-N 1/64 sec. cor. of sec. 32.

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 89°29'00" W., on the E-W center line of the NE1/4NW1/4 of sec. 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
2.60	Center of trail road, 11 lks. wide, bears NE. and SW.
5.085	<p>The C-E-NE-NW 1/256 sec. cor. of sec. 32, determined by Trent J. Keenan, Nevada Professional Land Surveyor No. 16802, in 2014, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with an aluminum cap mkd. DIAMONDBACK LAND SURVEYING PLS 16802, and a divot to mark the location of the actual point, as shown on Record of Survey, recorded in Clark County, Nevada, File 193, Page 19 of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>Cor. is located 1 lk. E. of a concrete fence corner, with concrete fences extending NW. and NE.</p> <hr/> <p>N. 89°29'00" W., beginning new measurement.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
5.081	The NE-NW 1/64 sec. cor. of sec. 32.
10.164	<p>Point for the C-W-NE-NW 1/256 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S32</p> <p style="text-align: center;">C-W-NE-NW</p> <p style="text-align: center;">1/256</p> <p style="text-align: center;">2014</p>
15.00	East edge of S. Quarterhorse Ln., asphalt surfaced, 48 lks. wide, bears S. 4° E. and N. 4° W.
15.247	<p>The C-N-NW 1/64 sec. cor. of sec. 32.</p> <hr/> <p>From the C-E-NE-NW 1/256 sec. cor. of sec. 32.</p> <p>N. 4°32'50" W., on the N-S center line of the NE1/4NE1/4NW1/4 of sec. 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.455	The E-E-W 1/256 sec. cor. of secs. 29 and 32.
	From the C-E-E-NW 1/256 sec. cor. of sec. 32.
	N. 4°34'10" W., on the N-S center line of the SE1/4NE1/4NW1/4 of sec. 32.
	Over gently rolling land, through creosote and scattered yucca plants.
2.40	Center of trail road, 11 lks. wide, bears NE. and SW.
9.457	The C-E-NE-NW 1/256 sec. cor. of sec. 32.
	From the point for the C-E-W 1/64 sec. cor. of sec. 32.
	N. 4°36'40" W., on the N-S center line of the SE1/4NW1/4 of sec. 32.
	Over gently rolling land, through creosote and scattered yucca plants.
1.40	Center of dirt road, 13 lks. wide, bears NE. and SW.
2.60	Center of dirt road, 14 lks. wide, bears ENE. and WNW.
9.526	Point for the SE-NW 1/64 sec. cor. of sec. 32, at the intersection of the E-W center line of the SE1/4NW1/4.
	POINT NOT MONUMENTED
12.00	Center of trail road, 11 lks. wide, bears NE. and SW.
19.052	The point for the C-E-NW 1/64 sec. cor. of sec. 32.
	From the C-S-N 1/64 sec. cor. of sec. 32.
	S. 89°14'30" W., on the E-W center line of the SE1/4NW1/4 of sec. 32.
	Over gently rolling land, through creosote and scattered yucca plants.
5.042	Point for the C-E-SE-NW 1/256 sec. cor. of sec. 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S32
	C-E-SE-NW
	1/256
	2014
10.084	The point for the SE-NW 1/64 sec. cor. of sec. 32.
11.30	Center of trail road, 11 lks. wide, bears NE. and SW.
15.126	Point for the C-W-SE-NW 1/256 sec. cor. of sec. 32.
	POINT NOT MONUMENTED
19.80	East edge of S. Quarterhorse Ln., graded dirt surfaced, 48 lks. wide, bears S. 4° E. and N. 4° W.
20.168	The point for the C-S-NW 1/64 sec. cor. of sec. 32.
	From the C-E-SE-NW 1/256 sec. cor. of sec. 32.
	N. 4°31'10" W., on the N-S center line of the NE1/4SE1/4NW1/4 of sec. 32.
	Over gently rolling land, through creosote and scattered yucca plants.
9.468	The C-E-E-NW 1/256 sec. cor. of sec. 32.
	From the point for the C-E-E-W 1/256 sec. cor. of sec. 32.
	N. 4°31'10" W., on the N-S center line of the SE1/4SE1/4NW1/4 of sec. 32.
	Over gently rolling land, through creosote and scattered yucca plants.
2.80	Center of dirt road, 13 lks. wide, bears SE. and NW.
4.00	Center of dirt road, 14 lks. wide, bears ENE. and WSW.
9.468	The C-E-SE-NW 1/256 sec. cor. of sec. 32.
	From the point for the C-W-E-W 1/256 sec. cor. of sec. 32.
	N. 4°42'00" W., on the N-S center line of the SW1/4SE1/4NW1/4 of sec. 32.
	Over gently rolling land, through creosote and scattered yucca plants.
3.90	Center of dirt road, 14 lks. wide, bears SE. and NW.

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 9.584</p>	<p>The point for the C-W-SE-NW 1/256 sec. cor. of sec. 32.</p>
	<hr/> <p>From the point for the C-W-W 1/64 sec. cor. of sec. 32.</p> <p>N. 5°02'20" W., on the N-S center line of the SW1/4NW1/4 of sec. 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
<p>9.757</p>	<p>Point for the SW-NW 1/64 sec. cor. of sec. 32, at the intersection of the E-W center line of the SW1/4NW1/4. The position is presently occupied by a fence post and concrete footing.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 31°46'10" E., 108.5 lks. dist., with brass cap mkd. RM S32 71.6 FT. TO COR. 2014 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 68°53'40" W., 118.8 lks. dist., with brass cap mkd. RM S32 78.4 FT. TO COR. 2014 and an arrow pointing to the corner.</p> <p>Cor. is located 1 lk. S. of a chain-link fence cor., with fences extending E. and N. 5° W.</p>
	<hr/> <p>N. 5°02'20" W., beginning new measurement.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
<p>1.05</p>	<p>From this point, the corner of grid wire fences bears WEST, 0.07 chs. dist., with fences extending N. 85° E. and N. 5° W.</p>
<p>4.90</p>	<p>Grid wire fence, bears N. 80° E. and S. 80° W. From this point, the corner of grid wire fences bears S. 83°30' W., 0.07 chs. dist., with fences extending N. 80° E. and S. 5° E.</p> <p>From this same point, the corner of chain-link and grid wire fences bears N. 83°30' E., 0.01 chs. dist., with fences extending N. 89° E., S. 5° E., S. 80° W., and N. 5° W.</p>
<p>9.755</p>	<p>The C-W-NW 1/64 sec. cor. of sec. 32.</p> <hr/> <p>From the point for the C-S-NW 1/64 sec. cor. of sec. 32. S. 89°13'50" W., on the E-W center line of the SW1/4NW1/4 of sec. 32.</p>



FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over gently rolling land, through creosote and scattered yucca plants.
0.20	West edge of S. Quarterhorse Ln., graded dirt surfaced, bears S. 4° E. and N. 4° W.
2.20	Center of dirt road, 27 lks. wide, bears N. 5° W. and S. 5° E.
4.90	Center of dirt path, 12 lks. wide, bears N. 3° E. and S. 3° W.
5.036	Point for the C-E-SW-NW 1/256 sec. cor. of sec. 32.  Set a magnetic nail, flush with concrete footing of nearby fence post.  from which  A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 64°41'40" E., 75.4 lks. dist., with brass cap mkd. RM S32 49.8 FT. TO COR. 2014 and an arrow pointing to the corner.  A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 33°28'00" W., 128.3 lks. dist., with brass cap mkd. RM S32 84.7 FT. TO COR. 2014 and an arrow pointing to the corner.  Cor. is located 1 lk. SE. of a chain-link fence corner, with fences extending W. and N. 5° W.
10.072	The SW-NW 1/64 sec. cor. of sec. 32.  S. 89°13'50" W., beginning new measurement.
10.064	The point for the S-N 1/64 sec. cor. of secs. 31 and 32.  From the C-E-SW-NW 1/256 sec. cor. of sec. 32.  N. 4°59'30" W., on the N-S center line of the NE1/4SW1/4NW1/4 of sec. 32.  Over gently rolling land, through creosote and scattered yucca plants.
2.70	Center of graveled road, 21 lks. wide, bears N. 80° E.
6.60	Center of dirt road, 21 lks. wide, bears N. 75° E.
9.242	A rebar, 5/8 in. diam., firmly set flush in the ground, with an aluminum cap, 1 1/2 ins. diam., mkd., BARNSON PLS 4046, as recorded in Clark County, Nevada, File 88, Page 19 of Surveys, from which, a square rod, firmly set, projecting 24 ins. above the ground, bears EAST, 1 lk. dist.

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.30	Chain-link fence, bears S. 85° E. and N. 85° W. From this point a cor. of chain-link fences bears E., 0.01 chs. dist., with fences extending N. 85° W. and N. 5° W.
9.699	The C-E-W-NW 1/256 sec. cor. of sec. 32.
	<hr/> <p>From the point for the C-E-W-W 1/256 sec. cor. of sec. 32.</p> <p>N. 4°54'10" W., on the N-S center line of the SE1/4SW1/4NW1/4 of sec. 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
9.20	Center of dirt path, 12 lks. wide, bears N. 59° W.
9.700	The C-E-SW-NW 1/256 sec. cor. of sec. 32.
	<hr/> <p>From the C-W-NW 1/64 sec. cor. of sec. 32.</p> <p>N. 5°05'10" W., on the N-S center line of the NW1/4NW1/4 of sec. 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
9.50	Center of dirt road, 14 lks. wide, bears N. 69° E. and S. 69° W.
9.752	Point for the NW-NW 1/64 sec. cor. of sec. 32, at the intersection of the E-W center line of the NW1/4NW1/4.
	<p>Set an aluminum rod with spiral flute, 24 ins. long, 5/8 in. diam., 26 ins. in the ground, over a plastic-encased magnet, with a 2 ins. aluminum cap mkd.</p> <p style="text-align: center;">BLM S32 NW-NW 1/64  2014</p>
19.501	The point for the W-W 1/64 sec. cor. of secs. 29 and 32.
	<hr/> <p>From the C-N-NW 1/64 sec. cor. of sec. 32.</p> <p>N. 89°28'40" W., on the E-W center line of the NW1/4NW1/4 of sec. 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
0.40	Three wire power transmission line, bears S. 4° E. and N. 4° W.

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
5.085	<p>Point for the C-E-NW-NW 1/256 sec. cor. of sec. 32.</p> <p>Set an aluminum rod with spiral flute, 24 ins. long, 5/8 in. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with 2 ins. aluminum cap mkd.</p> <p style="text-align: center;">BLM S32 C-E-NW-NW 1/256</p> <p style="text-align: center;">2014</p>
9.60	Center of dirt road, 14 lks. wide, bears S. 69° W.
10.170	The NW-NW 1/64 sec. cor. of sec. 32.
14.20	Center of dirt road, 14 lks. wide, bears S. 54° W.
15.251	<p>Point for the C-W-NW-NW 1/256 sec. cor. of sec. 32.</p> <p>Set an aluminum rod with spiral flute, 24 ins. long, 5/8 in. diam., 27 ins. in the ground, over a plastic-encased magnet, with 2 ins. diam. aluminum cap mkd.</p> <p style="text-align: center;">BLM S32 C-W-NW-NW 1/256</p> <p style="text-align: center;">2014</p>
20.332	<p>The N-N 1/64 sec. cor. of secs. 31 and 32.</p> <hr/> <p>From the C-E-NW-NW 1/256 sec. cor. of sec. 32.</p> <p>N. 4°58'30" W., on the N-S center line of the NE1/4NW1/4NW1/4 of sec. 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
0.30	Center of dirt road, 15 lks. wide, bears N. 62° E.
4.50	Center of dirt road, 15 lks. wide, bears NE.
5.00	Center of dirt road, 15 lks. wide, bears SE.
9.689	<p>The E-W-W 1/256 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the C-E-W-NW 1/256 sec. cor. of sec. 32.</p> <p>N. 4°54'40" W., on the N-S center line of the SE1/4NW1/4NW1/4 of sec. 32.</p>

FURTHER SUBDIVISION OF SECTION 32,  
T. 22 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over gently rolling land, through creosote and scattered yucca plants.
9.690	The C-E-NW-NW 1/256 sec. cor. of sec. 32.
	<hr/> <p>From the C-W-W-NW 1/256 sec. cor. of sec. 32.</p> <p>N. 5°13'00" W., on the N-S center line of the SW1/4NW1/4NW1/4 of sec. 32.</p> <p>Over gently rolling land, through creosote and scattered yucca plants.</p>
3.50	Center of dirt road, 14 lks. wide, bears N. 68° E.
9.20	Center of dirt road, 14 lks. wide, bears N. 62° E. and S. 62° W.
9.811	The C-W-NW-NW 1/256 sec. cor. of sec. 32.
	<hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in this survey are located approximately 14 miles southwest of Las Vegas, Nevada. The average elevation of the area surveyed is 2,800 feet above sea level and generally drains to the east. Vegetation consists of creosote and yucca plants as well as other native grasses.</p> <hr/>

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Brock R. Clifford

Cadastral Surveyor

Brandon K. Grace

Cadastral Surveyor

## CERTIFICATE OF SURVEY

I, Jose A. Serna, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 10th day of February, 2014, I have dependently resurveyed a portion of the subdivisional lines and a portion of the subdivision-of-section lines of section 32, and further subdivided section 32, Township 22 South, Range 60 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

AUG 25 2015

(Date)

*Michael O. Hammung*  
For Jose A. Serna  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT

Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and a portion of the subdivision-of-section lines of section 32, and the further subdivision of section 32, Township 22 South, Range 60 East, of the Mount Diablo Meridian, Nevada, executed by Jose A. Serna, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

AUG 25 2015

(Date)

*Michael O. Hammung*  
(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Township 22 South, Range 60 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~~~(Chief Cadastral Surveyor for Nevada)~~