

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT SURVEY OF THE

SIXTH STANDARD PARALLEL SOUTH,

THROUGH A PORTION OF RANGE 57 EAST,

A PORTION OF THE WEST BOUNDARY, THE NORTH BOUNDARY,

THE SUBDIVISIONAL LINES

AND PORTIONS OF CERTAIN MINERAL SURVEYS,

TOWNSHIP 24 SOUTH, RANGE 57 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Brian D. Hatter, Nevada Professional Land Surveyor

Brandon G. Courtright, Cadastral Surveyor

Under Contract No. L06PC05105

and Special Instructions dated February 9, 2010,

and approved February 9, 2010,

which provided for the surveys included under Group No. 892,

and Assignment Instructions dated November 9, 2010,

and Assignment Instructions dated December 14, 2016.

Survey commenced November 28, 2010

Survey completed April 4, 2023

## INDEX DIAGRAM

TOWNSHIP 24 SOUTH, RANGE 57 EAST, MOUNT DIABLO MERIDIAN, NEVADA

17 11 6 58	16 58 5 57	15 47 4 47	15 40 3 39	14 33 2 32	13 25 1 25
10 7 56	57 8 56	46 9 46	39 10 38	32 11 31	24 12 23
10 18 55	55 17 54	45 16 45	38 15 37	31 14 30	22 13 22
8 19 53	53 20 52	44 21 43	37 22 36	29 23 28	21 24 20
8 30 51	51 29 49	42 28 42	35 27 34	27 26 26	19 25 19
31	48 32 7	40 33 6	34 34 5	25 35 4	18 36 3

M.S. No. 1715.....P 59  
M.S. No. 1861...PP 59-60  
M.S. No. 1919...PP 61-64  
M.S. No. 1920...PP 64-69  
M.S. No. 1943...PP 69-72  
M.S. No. 1981.....P 73

M.S. No. 2002...PP 74-76  
M.S. No. 2044...PP 76-78  
M.S. No. 2048...PP 78-80  
M.S. No. 2110...PP 81-85  
M.S. No. 3470...PP 85-87  
M.S. No. 3575...PP 87-90

M.S. No. 3585....PP 91-93  
M.S. No. 4365....PP 93-104  
M.S. No. 4366...PP 104-106  
M.S. No. 4371 A. PP 107-118  
M.S. No. 4373...PP 118-127  
M.S. No. 4546...PP 127-131

## TOWNSHIP 24 SOUTH, RANGE 57 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of the Sixth Standard Parallel South, through a portion of Range 57 East, a portion of the west boundary, the north boundary, the subdivisional lines and portions of certain mineral surveys in Township 24 South, Range 57 East, Mount Diablo Meridian, Nevada.

The south boundary (Sixth Standard Parallel South), the east, west and north boundaries, and the subdivisional lines were surveyed by U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881 under Contract No. 115. A portion of the south boundary (Sixth Standard Parallel South) and a portion of the west boundary were dependently resurveyed by U.S. Transitman R.F. Wilson in 1932 under Group No. 205, California. A portion of the south boundary (Sixth Standard Parallel South), and the east boundary were dependently resurveyed by Nevada Professional Land Surveyor B.D. Hatter, Cadastral Surveyor B.R. Clifford and Surveying Technician M.G. Petrosine in 2010-2021 under Group No. 887.

## HISTORY OF MINERAL SURVEYS PERTAINING TO RESURVEY

Mineral Survey No. 1715, Clementina, Cleveland and Excelsior lodes were surveyed by U.S. Deputy Mineral Surveyor T.K. Stewart in 1895.

Mineral Survey No. 1857, Golden Chariot lode was surveyed by U.S. Deputy Mineral Surveyor H.W. Newby in 1899, and amended in 1900.

Mineral Survey No. 1861, May, John, Black Lime and Desty lodes were surveyed by U.S. Deputy Mineral Surveyor H.W. Newby in 1899.

Mineral Survey No. 1863, Old Timer lode was surveyed by U.S. Deputy Mineral Surveyor H.W. Newby in 1899. This survey was cancelled on September 28, 1901.

Mineral Survey No. 1919, Hillside lode was surveyed by U.S. Deputy Mineral Surveyor H.W. Newby in 1900.

Mineral Survey No. 1920, Last Chance, Shufly, Libie and Hattie A. lodes were surveyed by U.S. Deputy Mineral Surveyor H.W. Newby in 1900.

Mineral Survey No. 1943, Barefoot Annex, Barefoot, Barefoot No. 2 and Mary Anna lodes were surveyed by U.S. Deputy Mineral Surveyor F. Anderson in 1901. The field notes were supplemented in 1904.

Mineral Survey No. 1981, Yellow Jacket lode was surveyed by U.S. Deputy Mineral Surveyor H.W. Newby in 1901.

Mineral Survey No. 2002, Old Timer lode was surveyed by U.S. Deputy Mineral Surveyor H.W. Newby in 1901.

Mineral Survey No. 2044, Copper Chief lode was surveyed by U.S. Deputy Mineral Surveyor J.T. McWilliams in 1902.

Mineral Survey No. 2048, Shenandoah lode was surveyed by U.S. Deputy Mineral Surveyor J.T. McWilliams in 1902.

Mineral Survey Nos. 2110 A and B, Keystone, Honduras, Oversight, What Not, Empire and Bellevue lodes were surveyed by U.S. Deputy Mineral Surveyor H.K. Wheeler in 1903.

## TOWNSHIP 24 SOUTH, RANGE 57 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Mineral Survey No. 3470, Mobile lode was surveyed by U.S. Mineral Surveyor A.D. Knowlton in 1909.

Mineral Survey No. 3575, Lookout lode was surveyed by U.S. Mineral Surveyor A.D. Knowlton in 1908.

Mineral Survey No. 3585, Little Joker lode was surveyed by U.S. Mineral Surveyor A.D. Knowlton in 1908.

Mineral Survey No. 4330, Boss Extension and Saturday lodes were surveyed by U.S. Mineral Surveyor C.E. McCarthy in 1917. This survey was cancelled on December 30, 2016.

Mineral Survey No. 4365, Chances, Red Streak, Highline and Chance lodes were surveyed by U.S. Mineral Surveyor A.H. Black in 1918.

Mineral Survey No. 4366, Eureka lode was surveyed by U.S. Mineral Surveyor A.H. Black in 1918.

Mineral Survey No. 4371 A and B, Boss, Boss No.2, Boss No.3, Campo, and Manse lodes and Boss Mill Site were surveyed by U.S. Mineral Surveyor A.H. Black in 1918.

Mineral Survey No. 4373, Oro Amigo No.1, Oro Amigo No.2, Oro Amigo No.3 and Oro Amigo No.4 lodes were surveyed by U.S. Mineral Surveyor A.H. Black in 1918.

Mineral Survey No. 4546, Rainbow No.1, Rainbow No.2 and Rainbow No.3 lodes were surveyed by U.S. Mineral Surveyor A.H. Black in 1922.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In the resurvey of mineral surveys, record distance, the grant boundary method and methods to preserve parallel end and side lines were applied. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 892, dated February 9, 2010.

Measurements were made with Trimble R7 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 83 (CORS96)(EPOCH:2002.0000) geographic position, of the following corners were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) NVPO MT. POTOSI CORS, NVTP TROPICANA CORS, AND NVBM BERMUDA CORS, and carried forward by RTK observations.

## TOWNSHIP 24 SOUTH, RANGE 57 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The standard 1/4 section corner of section 36, Township 24 South, Range 57 East is as follows:

Latitude: 35°48'33.225" N. Longitude: 115°32'14.391" W.

The corner of Townships 23 and 24 South, Ranges 56 and 57 East is as follows:

Latitude: 35°53'48.542" N. Longitude: 115°38'06.810" W.

The 1980 mean magnetic declination is 14°30' E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "SHENANDOAH PEAK, NEV.-CALIF." provisional edition dated 1985.

---

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL SOUTH,  
THROUGH A PORTION OF RANGE 57 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of a Portion of the Survey Executed by  
U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881

---

Beginning at the standard 1/4 sec. cor. of sec. 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 5 1/2 ft. diam., 2 ft. high, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of the Sixth Standard Parallel South, through a portion of Range 57 East, executed under Group No. 887.

S. 89°51'10" W., on the S. bdy. of sec. 36.

- |        |  |
|--------|--|
| 2.10   | Enter wash, drains S. 40° W. and foot of mountain, bears NE. and SW.   |
| 8.40   | Exit wash.   |
| 9.80   | Trail road, 12 lks. wide, bears NE. and SW.  |
| 14.00  | Wash, 75 lks. wide, drains S.  |
| 17.90  | Wash, 1 1/2 chs. wide, drains SSW.   |
| 23.30  | Trail road, 10 lks. wide, bears ENE. and WSW.  |
| 25.00  | S. edge of wash, drains W.   |
| 33.50  | Exit wash.   |
| 38.00  | Trail road, 10 lks. wide, curving from N. to E.  |
| 40.192 | The standard cor. of secs. 35 and 36, monumented with a limestone, 27x17x9 ins., firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. with 1 notch on the E. edge and 5 notches on the W. edge. |
|        | At the corner point  |

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL SOUTH,  
THROUGH A PORTION OF RANGE 57 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T24S R57E <u>S35   S36</u></p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°52'30" W., on the S. bdy. of sec. 35.</p> <p>4.20 Enter wash, drains WSW.</p> <p>21.30 Exit wash.</p> <p>30.90 Trail road, 10 lks. wide, bears NE. and SW.</p> <p>40.511 The standard 1/4 sec. cor. of sec. 35, monumented with a limestone, 16x10x7 ins., firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SC T24S R57E <u>1/4 S35</u></p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°34'00" W., beginning new measurement.</p> <p>40.419 The standard cor. of secs. 34 and 35, monumented with a limestone, 16x12x7 ins. (Record, 23x17x8 ins.), firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. with 2 notches on the E. edge and 4 notches on the W. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL SOUTH,  
THROUGH A PORTION OF RANGE 57 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">SC T24S R57E <u>S34   S35</u></p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°10'20" W., on the S. bdy. of sec. 34.</p> <p>40.200 The standard 1/4 sec. cor. of sec. 34, monumented with a limestone, 12x8x7 ins. (Record 18x13x9 ins.), firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SC T24S R57E <u>1/4 S34</u></p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 88°55'40" W., beginning new measurement.</p> <p>22.30 Dirt road, 40 lks. wide, bears NNE. and SSW.</p> <p>40.648 The standard cor. of secs. 33 and 34, monumented with a limestone, 18x11x6 ins., firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. with 3 notches on the E. edge and 3 notches on the W. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SC T24S R57E <u>S33   S34</u></p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL SOUTH,  
THROUGH A PORTION OF RANGE 57 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°38'30" W., on the S. bdy. of sec. 33.
5.00	The intersection of Cherokee St. and Quartz Ave., asphalt roads, 40 lks. wide, extending S. and W.
39.95	Overhead powerline, bears N. 30° E. and S. 30° W.
40.477	<p>The standard 1/4 sec. cor. of sec. 33, perpetuated by Wayne M. Hink, Nevada Professional Surveyor No. 2051, in 1972, as recorded in Clark County, Nevada, File 23, Page 12 of Surveys and by Robert Fulstone, Nevada Professional Land Surveyor No. 5269, in 1993, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set 4 ins. below ground, with aluminum cap, 2 ins. diam., mkd. FULSTONE LS5269, as recorded in Clark County, Nevada, File 66, Page 93 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SC T24S R57E 1/4 S33 _____</p> <p style="text-align: center;">2011</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Cor. is located 10 lks. S. of the southerly edge of Quartz Ave., asphalt surface, 40 lks. wide.</p> <p style="text-align: center;">_____</p> <p>N. 89°42'30" W., beginning new measurement.</p>
4.639	A rebar, 5/8 in. diam., firmly set, 6 ins. below the ground, with aluminum cap, 2 ins. diam., mkd. FULSTONE PLS5269, as recorded in Clark County, Nevada, File 66, Page 93 of Surveys.
40.464	<p>The standard cor. of secs. 32 and 33, reestablished by Robert Fulstone, Nevada Professional Land Surveyor No. 5269, in 1993, utilizing the record of Wayne M. Hink, Nevada Professional Land Surveyor No. 2051, as recorded in Clark County, Nevada, File 23, Page 12 of Surveys, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set 4 ins. below ground, with aluminum cap, 2 ins. diam., mkd. FULSTONE LS5269, as recorded in Clark County, Nevada, File 66, Page 93 of Surveys. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p>



DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL SOUTH,  
THROUGH A PORTION OF RANGE 57 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">SC T24S R57E <u>S32 S33</u></p> <p style="text-align: center;">2011</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Cor. is located 10 lks. S. of the southerly edge of Quartz Ave., asphalt surface, 40 lks. wide.</p>
	<hr/>
	<p>S. 89°40'30" W., on the S. bdy. of sec. 32.</p>
4.253	<p>A rebar, 5/8 in. diam., firmly set, 3 ins. below the ground, bears NORTH, 0.037 chs., with aluminum cap, 1 1/2 ins. diam., damaged with illegible markings, as recorded in Clark County, Nevada, File 66, Page 93 of Surveys.</p>
20.330	<p>Point for the standard E 1/16 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">SC <u>E 1/16 S32</u></p>
	<p style="text-align: center;">2022</p>
	<p>From this point, a rebar, 5/8 in. diam., bent, projecting 6 ins. above the ground, bears N. 0°33' E., 0.023 chs. dist. This rebar is not utilized in this survey.</p>
	<p>From this same point, a rebar, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, bears S. 50°17'00" E., 1.122 chs. dist., with plastic cap, mkd. PLS 5269.</p>
40.660	<p>The standard 1/4 sec. cor. of sec. 32, monumented with an iron post, 1 in. diam., firmly set 8 ins. below the ground, with brass cap mkd. as described in the field notes of the 1932 dependent resurvey of the Sixth Standard Parallel South, through a portion of Range 57 East, executed under Group No. 205, California.</p> <p>Cor. is located 5 lks. S. of the southerly edge of Quartz Ave., asphalt surface, 40 lks. wide.</p>
	<hr/>

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881, and a Portion of the Dependent Resurvey Executed by U.S. Transitman R.F. Wilson in 1932</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the 1932 dependent resurvey of a portion of the E. bdy., T. 24 S., R. 56 E., executed under Group No. 205, California.</p>
	<p>N. 0°11'50" E., bet. secs. 25 and 30.</p>
1.40	Trail road, 12 lks. wide, bears irregularly N. and S.
7.80	Trail road, 12 lks. wide, bears NNE. and SSW.
14.50	Trail road, 12 lks. wide, bears NNE. and SSW.
17.40	Trail road, 8 lks. wide, bears ENE. and WSW.
40.392	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T24S R56E R57E 1/4 S25 S30  2011</p>
80.60	Dirt road, 25 lks. wide, bears E. and W.
80.784	<p>The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the 1932 dependent resurvey of a portion of the E. bdy., T. 24 S., R. 56 E., executed under Group No. 205, California.</p> <p>Cor. is located 2 lks. N. of the northerly edge of dirt road.</p>
	<p>N. 0°12'30" E., bet. secs. 19 and 24.</p>
23.90	Trail road, 15 lks. wide, bears NE. and SW.
25.40	Sandy Valley Road, 50 lks. wide, bears SE. and NW.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS  
40.607

The 1/4 sec. cor. of secs. 19 and 24, perpetuated by Robert Fulstone, Nevada Professional Land Surveyor No. 5269, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, with aluminum cap, 2 ins. diam., mkd. FULSTON PLS5269, with a limestone, 8x6x5 ins. (Record, 14x11x8 ins.), lying loose alongside, mkd. 1/4 on a face, as recorded in Clark County, Nevada, File 71, Page 34 of Surveys. This is accepted as a careful and faithful perpetuation of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T24S  
R56E R57E  
1/4  
S24|S19

2011

Insert the rebar inside and deposit the mkd. stone alongside the stainless steel post.

---

N. 0°20'40" E., beginning new measurement.

40.706

The cor. of secs. 13, 18, 19 and 24, perpetuated by Robert Fulstone, Nevada Professional Land Surveyor No. 5269, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, with aluminum cap, 2 ins. diam., mkd. FULSTON PLS5269, with a granite stone, 19x14x9 ins., lying loose alongside, mkd. with 3 notches on an edge and 3 notches on another edge, as recorded in Clark County, Nevada, File 71, Page 34 of Surveys. This is accepted as a careful and faithful perpetuation of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T24S  
R56E|R57E  
S13|S18  
S24|S19

2011

Insert the rebar inside and deposit the mkd. stone alongside the stainless steel post.

---

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 0°03'20" E., bet. secs. 13 and 18.
40.770	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with a lime stone, 15x13x7 ins., lying loose on the ground, mkd. 1/4 on a face. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R56E R57E 1/4 S13 S18 2011</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°03'40" E., beginning new measurement.</p>
40.637	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a limestone, 18x12x9 ins., firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. with 4 notches on the S. edge and 2 notches on the N. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R56E R57E S12 S 7 <hr/>S13 S18 2011</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°49'30" E., bet. secs. 7 and 12.</p>
9.00	Trail road, 15 lks. wide, bears irregularly NE. and SW., in wash, 30 lks. wide, drains SW.
34.60	Confluence of two washes, 1 ch. wide, drains SW.
40.607	The 1/4 sec. cor. of secs. 7 and 12, monumented with a limestone, 14x12x7 ins., firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 1/4 on the W. face.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T24S R56E R57E 1/4 S12 S 7 2011
	Deposit the mkd. stone alongside the stainless steel post.
	<hr/>
	NORTH, beginning new measurement.
17.80	Trail road, 10 lks. wide, bears SE. and NW.
40.466	The cor. of secs. 1, 6, 7 and 12, monumented with a limestone, 22x17x9 ins., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. with 5 notches on the S. edge and 1 notch on the N. edge.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T24S R56E R57E S 1 S 6 S12 S 7 2011
	Deposit the mkd. stone alongside the stainless steel post.
	<hr/>
	N. 2°19'10" E., bet. secs. 1 and 6.
0.50	Wash, 50 lks. wide, drains WSW.
6.40	Wash, 75 lks. wide, drains SW.
12.20	Spur, slopes SW.
16.00	Enter wash, drains SSW.
27.25	Exit wash.
38.00	Foot of mountain, bears SE. and NW.
39.004	Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T24S R56E R57E 1/4 S 1   S 6  2011</p>
43.70	Spur, slopes SE.
50.10	Wash, 50 lks. wide, drains SE.
53.20	Trail road, 10 lks. wide, bears SE. and NW.
55.70	Gulch, 25 lks. wide, drains SE.
61.00	Spur, slopes SW.
63.40	Gulch, 25 lks. wide, drains SW.
74.10	Spur, slopes SE.
78.008	<p>Point for the cor. of Tps. 23 and 24 S., Rs. 56 and 57 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T23S R56E   R57E S36   S31 S 1   S 6 T24S  2011</p> <p>From this point, the cor. of secs. 1, 2, 35 and 36, Tps. 23 and 24 S., R. 56 E., bears N. 88°29'20" W., 84.953 chs. dist., monumented with a granite stone, 14x8x6 ins., firmly set in a mound of stone, 3 1/2 ft. diam., 1 ft. high, mkd. with 1 notch on the E. edge and 5 notches on the W. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T23S R56E  
S35|S36  
S 2|S 1  
T24S

2011

Deposit the mkd. stone alongside the stainless steel post.

This control line was fully retraced and a careful search was made for evidence of the 1/4 sec. cor. of secs. 1 and 36, Tps. 23 and 24 S., R. 56 E., which was not recovered.

From this same point, the 1/4 sec. cor. of secs. 31 and 36, Tps. 23 S., Rs. 56 and 57 E., bears N. 9°41'00" W., 39.535 chs. dist., monumented with a limestone, 18x16x8 ins., firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 1/4 on the W. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T23S  
R56E R57E  
1/4  
S36|S31

2011

Deposit the mkd. stone alongside the stainless steel post.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881

From the cor. of Tps. 23 and 24 S., Rs. 57 and 58 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the 2010-2011 dependent resurvey of the W. bdy., T. 24 S., R. 58 E., executed under Group No. 887.

S. 89°42'30" W., bet. secs. 1 and 36.

42.462

Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T23S R57E S36 1/4 — S 1 T24S  2017</p>
84.924	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T23S R57E S35   S36 —   — S 2   S 1 T24S  2017</p>
	<hr/> <p>S. 89°42'30" W., bet. secs. 2 and 35.</p>
42.462	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T23S R57E S35 1/4 — S 2 T24S  2017</p>
46.40	Gulch, 15 lks. wide, drains SW.
51.60	Overhead powerline, bears S. 30° E. and N. 30° W.
52.00	Dirt road, 20 lks. wide, bears SE. and NW.
79.40	Enter wash, drains WSW.
84.924	<p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>



DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T23S R57E  S34   S35  <hr style="width: 50%; margin: 0 auto;"/> S 3   S 2  T24S    2017 </div>
	S. 89°42'30" W., bet. secs. 3 and 34.
5.00	Trail road, 10 lks. wide, bears NE. and SW.
10.50	Exit wash.
22.00	Gulch, 30 lks. wide, drains SW.
38.30	Trail road, 10 lks. wide, bears NE. and SW.
42.462	Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> T23S R57E  S34  1/4 —  S 3  T24S    2017 </div>
43.80	Wash, 45 lks. wide, drains S.
73.50	Top of hill.
84.924	Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	<div style="text-align: center;"> T23S R57E  S33   S34  <hr style="width: 50%; margin: 0 auto;"/> S 4   S 3  T24S    2017 </div>
	S. 89°42'30" W., bet. secs. 4 and 33.
6.30	Gulch, 50 lks. wide, drains S.
29.80	Ridge, bears N. and S.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 42.462	<p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in a limestone ledge, with top mkd.</p> <div style="text-align: center;"> T23S R57E  S33  1/4 ———  S 4  T24S    2017 </div> <p>From this point, Cor. No. 2, Mineral Survey No. 4546, Rainbow No. 2 lode, hereinafter described, bears S. 18°23'10" E., 19.217 chs. dist.</p>
61.00	Gulch, 15 lks. wide, drains S.
65.30	Low ridge, bears N. and S.
74.50	Gulch, 25 lks. wide, drains SE.
84.924	<p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T23S R57E  S32   S33  ——— ———  S 5   S 4  T24S    2017 </div> <p>Cor. is located on ridge, bears N. and S.</p> <hr/> <p>S. 89°42'30" W., bet. secs. 5 and 32.</p>
16.90	Gulch, 15 lks. wide, drains S.
42.462	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in a quartz ledge, with top mkd.</p> <div style="text-align: center;"> T23S R57E  S32  1/4 ———  S 5  T24S    2017 </div>

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 60.50	Spur, slopes N. from ridge, bears NE. and SW.
84.924	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in limestone, with top mkd.</p> <div style="text-align: center;"> <p>T23S R57E S31   S32 ----- S 6   S 5 T24S</p> <p>2017</p> </div>
	S. 89°42'30" W., bet. secs. 6 and 31.
42.462	True point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner; not monumented, located on cliff face where it is impracticable to establish a permanent monument.
43.614	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T23S R57E S31 1/4 —————&gt; S 6 T24S</p> <p>2011</p> </div>
49.75	Top of ridge, bears N. and S.
63.30	Gulch, 20 lks. wide, drains SW.
76.80	Spur, slopes SE.
84.40	Gulch, 25 lks. wide, drains irregularly SE.
84.797	The cor. of Tps. 23 and 24 S., Rs. 56 and 57 E., hereinbefore described.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881</p>
	<p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 9°55'00" E., bet. secs. 35 and 36.</p>
1.40	Enter wash, drains WSW.
3.80	Trail road, 10 lks. wide, bears irregularly E. and W.
5.60	Exit wash.
41.086	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E 1/4 S35 S36</p> <p>2017</p> </div>
68.00	Spur, slopes SE.
76.90	Gulch, 15 lks. wide, drains SE.
82.172	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E S26 S25 S35 S36</p> <p>2017</p> </div> <p>From this point, Cor. No. 3, Mineral Survey No. 2002, Old Timer lode, hereinafter described, bears N. 24°48'10" E., 36.516 chs. dist.</p> <p>From this same point, Cor. No. 3, Mineral Survey No. 4366, Eureka lode, hereinafter described, bears N. 46°46'20" E., 39.282 chs. dist.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of the W. bdy., T. 24 S., R. 58 E., executed under Group No. 887.</p> <p>S. 83°27'00" W., bet. secs. 25 and 36.</p>
13.653	Intersect line 12-13, Mineral Survey No. 1861, John lode, at a point from which Cor. No. 13, hereinafter described, bears N. 70°05'00" W., 4.393 chs. dist.
46.837	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S25 1/4 — S36</p> <p style="text-align: center;">2017</p> <p>From this point, Cor. No. 1, Mineral Survey No. 4366, Eureka lode, hereinafter described, bears N. 17°59'30" E., 5.557 chs. dist.</p>
93.674	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0°42'40" E., bet. secs. 25 and 26.</p>
17.50	Top of ridge, bears NE. and SW.
31.00	Top of ridge, bears SE. and NW.
40.476	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S26 S25</p> <p style="text-align: center;">2017</p> <p>From this point, Cor. No. 4, Mineral Survey No. 2002, Old Timer lode, hereinafter described, bears N. 86°23'10" E., 14.530 chs. dist.</p>
60.00	Wash, 25 lks. wide, drains irregularly W.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 80.952</p>	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <table border="1" style="margin: auto;"> <tr> <td>S23</td><td>S24</td></tr> <tr> <td>S26</td><td>S25</td></tr> </table> <p>2017</p> </div>	S23	S24	S26	S25
S23	S24				
S26	S25				
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of the W. bdy., T. 24 S., R. 58 E., executed under Group No. 887.</p> <p>S. 84°49'00" W., bet. secs. 24 and 25.</p> <p>2.80 Gulch, 18 lks. wide, drains NW.</p> <p>3.996 Intersect line 3-4, Mineral Survey No. 2110, Bellevue lode, at a point from which Cor. No. 3, hereinafter described, bears S. 39°39'40" E., 0.219 chs. dist.</p> <p>6.75 Dirt road, 15 lks. wide, bears SE. and NW.</p> <p>10.645 Intersect line 1-2, Mineral Survey No. 1981, Yellow Jacket lode, at a point from which Cor. No. 2, Mineral Survey No. 2110, Bellevue lode, identical with Cor. No. 8, Mineral Survey No. 2110, Empire lode, on line 1-2, Mineral Survey No. 1981, Yellow Jacket lode, hereinafter described, bears S. 70°48'20" E., 5.714 chs. dist.</p> <p>17.20 Dirt road, 12 lks. wide, bears NE. and SW.</p> <p>31.397 Intersect line 1-2, Mineral Survey No. 1919, Hillside lode, at a point from which Cor. No. 1, hereinafter described, bears N. 37°16'30" E., 4.096 chs. dist.</p> <p>38.10 Dirt road, 15 lks. wide, bears NE. and SW.</p> <p>40.80 Dirt road, 12 lks. wide, bears SE. and NW.</p> <p>44.775 Intersect line 4-5, Mineral Survey No. 1919, Hillside lode, at a point from which Cor. No. 5, hereinafter described, bears N. 52°18'30" E., 3.632 chs. dist.</p> <p>44.876 Intersect line 2-3, Mineral Survey No. 1920, Hattie A. lode, at a point from which Cor. No. 2, hereinafter described, bears S. 2°19'50" W., 0.570 chs. dist.</p>				

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 46.821</p>	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S24 1/4 — S25</p> <p style="text-align: center;">2017</p> <p>From this point, Cor. No. 2, Mineral Survey No. 3585, Little Joker lode, hereinafter described, bears N. 4°37'40" E., 36.172 chs. dist.</p>
<p>93.642</p>	<p>The cor. of secs. 23, 24, 25 and 26.</p>
	<p>N. 12°41'00" W., bet. secs. 23 and 24.</p>
<p>41.485</p>	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S23 S24</p> <p style="text-align: center;">2016</p> <p>From this point, Cor. No. 3, Mineral Survey No. 4373, Oro Amigo No.1 lode, identical with Cor. No. 4, Oro Amigo No.3 lode, hereinafter described, bears N. 79°34'50" W., 14.129 chs. dist.</p>
<p>46.30</p>	<p>Dirt road, 15 lks. wide, bears E. and W., in gulch, 2 chs. wide, drains W.</p>
<p>53.45</p>	<p>Overhead powerline, bears N. 88° E. and S. 88° W.</p>
<p>82.970</p>	<p>The cor. of secs. 13, 14, 23 and 24, monumented with a limestone, 24x14x7 ins. (Record, 16x12x9 ins.), firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. with 3 notches on the S. edge and 1 notch on the E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> <p>T24S R57E</p> <table border="1"> <tr> <td>S14</td><td>S13</td></tr> <tr> <td>S23</td><td>S24</td></tr> </table> <p>2011</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. diam., 2 ft. high, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of the W. bdy., T. 24 S., R. 58 E., executed under Group No. 887.</p> <p>S. 86°46'50" W., bet. secs. 13 and 24.</p> <p>37.00 Wash, 2 chs. wide, drains NW.</p> <p>55.037 Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <p>S13</p> <p>1/4 ———</p> <p>S24</p> <p>2016</p> </div> <p>From this point, Cor. No. 4, Mineral Survey No. 3585, Little Joker lode, hereinafter described, bears S. 0°30'10" W., 19.416 chs. dist.</p> <p>74.40 Overhead powerline, bears N. 25° E. and S. 25° W.</p> <p>106.10 Wash, 10 lks. wide, drains NW.</p> <p>110.074 The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 21°09'20" E., bet. secs. 13 and 14.</p> <p>1.85 Wash, 10 lks. wide, drains W.</p> <p>27.50 Kingston Road, Nevada State Route 53, gravel surface, 30 lks. wide, bears NE. and SW.</p> <p>39.50 Kingston Road, Nevada State Route 53, gravel surface, 30 lks. wide, bears N. and S.</p> <p>45.343 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p>	S14	S13	S23	S24
S14	S13				
S23	S24				



DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S14 S13</p> <p style="text-align: center;">2011</p>
90.686	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a limestone, 24x18x10 ins. Record, 16x9x7 ins.), firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. with 4 notches on the S. edge and 1 notch on the E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of earth and stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S11 S12 S14 S13</p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p>
	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of the W. bdy., T. 24 S., R. 58 E., executed under Group No. 887.</p> <p>S. 89°51'10" W., bet. secs. 12 and 13.</p>
3.75	Top of ridge, bears N. and S.
39.242	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S12 1/4 — S13</p> <p style="text-align: center;">2017</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 78.484	The cor. of secs. 11, 12, 13 and 14.
	N. 0°40'30" E., bet. secs. 11 and 12.
1.00	Enter wash, drains SW.
19.90	Kingston Road, Nevada State Route 53, gravel surface, 30 lks. wide, bears NE. and SW.
22.60	Trail road, 12 lks. wide, bears ENE. and WSW.
25.50	Exit wash.
36.80	Top of isolated hill.
39.545	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.  T24S R57E 1/4 S11 S12  2011
62.00	Overhead powerline, bears S. 30° E. and N. 30° W.
63.10	Dirt road, 12 lks. wide, bears SE. and NW.
79.090	The cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 19x14x11 ins., firmly set in a mound of stone, 2 1/2 ft. diam., 1/2 ft. high, mkd. with 5 notches on the S. edge and 1 notch on the E. edge.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.  T24S R57E S 2   S 1 S11   S12  2011  Deposit the mkd. stone alongside the stainless steel post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of the W. bdy., T. 24 S., R. 58 E., executed under Group No. 887.</p> <p>S. 88°39'00" W., bet. secs. 1 and 12.</p>
13.00	Top of ridge, bears NNE. and SSW.
38.568	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S 1 1/4 — S12</p> <p style="text-align: center;">2017</p>
49.20	Gulch, 70 lks. wide, drains SW.
77.136	The cor. of secs. 1, 2, 11 and 12.
39.726	<p>N. 3°52'40" W., bet. secs. 1 and 2.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in bedrock, with top mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S 2   S 1</p> <p style="text-align: center;">2017</p>
79.134	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., hereinbefore described.
32.50	<p>From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°13'50" W., bet. secs. 34 and 35.</p> <p>Across alluvial plain of several washes, draining W.</p> <p>Leave alluvial plain.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.00	Foot of mountain, bears NE. and SW.
40.737	<p>The 1/4 sec. cor. of secs. 34 and 35, monumented with a sandstone, 19x12x10 ins., firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, mkd. 1/4 on the W. face,</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S34 S35</p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 4°09'20" E., beginning new measurement.</p>
11.70	Spur, slopes SW.
15.60	Adit, tunnel bears N. 70° E.
24.00	Low sag; ascend.
33.50	Top of spur, slopes WSW.
36.699	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a sandstone, 27x14x12 ins., firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. with 1 notch on the S. edge and 2 notches on the E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S27 S26 S34 S35</p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 88°00'40" W., bet. secs. 26 and 35.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.25	Top of ridge, bears N., curving SW.
32.483	Intersect line 3-4, Mineral Survey No. 2048, Shenandoah lode, at a point from which Cor. No. 4, hereinafter described, bears S. 47°06'00" E., 3.669 chs. dist.
45.349	Intersect line 1-2, Mineral Survey No. 2048, Shenandoah lode, at a point from which Cor. No. 2, hereinafter described, bears N. 45°55'50" W., 5.619 chs. dist.
46.310	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.  Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in a limestone outcrop, with top mkd.  T24S R57E S26 1/4 — S35  2017
77.00	Top of ridge, bears ESE. and WNW.
92.620	The cor. of secs. 26, 27, 34 and 35.
	N. 0°16'50" E., bet. secs. 26 and 27.
8.775	Intersect line 6-1, Mineral Survey No. 4371 A, Manse lode, at a point from which Cor. No. 6, Mineral Survey No. 4371 A, Manse lode, identical with a north side angle Cor. of Rosella lode (unsurveyed), hereinafter described, bears N. 63°12'20" E., 6.067 chs. dist.
18.909	Intersect line 2-3, Mineral Survey No. 4371 A, Manse lode, at a point from which Cor. No. 3, hereinafter described, bears N. 63°10'30" E., 0.324 chs. dist.
26.50	Enter wash, drains W.
27.80	Dirt road, 12 lks. wide, bears SE. and NW.
37.90	Exit wash.
38.604	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.  T24S R57E 1/4 S27 S26  2011

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, Cor. No. 1, Mineral Survey No. 4365, Chance lode, hereinafter described, bears S. 65°51'50" E., 19.593 chs. dist.</p>				
45.80	Top of ridge, bears NE. and SW.				
70.80	Wash, 2 chs. wide, drains SW.				
73.90	Dirt road, 12 lks. wide, bears NE. and SW.				
77.208	<p>The cor. of secs. 22, 23, 26 and 27, perpetuated by James L. Marlett Jr., Nevada Professional Land Surveyor No. 13386, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 3 1/2 ft. diam., 1 ft. high, with aluminum cap, 1 1/2 ins. diam., mkd. PLS13386, with a limestone, 19x10x6 ins. (Record, 20x16x12 ins.), lying loose alongside, with 2 notches on an edge and 2 notches on another edge, as recorded in Clark County, Nevada, Corner Record Instrument No. 20030620.01356. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <table> <tr> <td>S22</td><td>S23</td></tr> <tr> <td>S27</td><td>S26</td></tr> </table> <p>2011</p> </div> <p>Insert the rebar inside and deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 85°44'00" W., bet. secs. 23 and 26.</p>	S22	S23	S27	S26
S22	S23				
S27	S26				
7.30	Top of ridge, bears SE. and WNW.				
43.80	Wash, 2 chs. wide, drains NW.				
46.717	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>				

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T24S R57E S23 1/4 — S26</p> <p>2017</p> <p>From this point, Cor. No. 1, Mineral Survey No. 4365, Red Streak lode, hereinafter described, bears S. 21°54'20" E., 19.956 chs. dist.</p>
91.40	Dirt road, 12 lks. wide, bears NNE. and SSW.
93.434	The cor. of secs. 22, 23, 26 and 27.
	<hr/> <p>NORTH, bet. secs. 22 and 23.</p> <p>Across alluvial plain of several washes draining SW.</p>
8.00	Overhead powerline, bears N. 51° E. and S. 51° W.
30.40	Kingston Road, Nevada State Route 53, gravel surface, 30 lks. wide, bears N. 40° E. and S. 40° W.
40.383	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with a limestone, 18x16x10 ins., firmly set in a mound of stone, 4 1/2 ft. diam., 1/2 ft. high, mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p>T24S R57E 1/4 S22 S23</p> <p>2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>From this corner, Cor. No. 1, Mineral Survey No. 4373, Oro Amigo No.2 lode, hereinafter described, bears S. 76°54'30" E., 31.327 chs. dist.</p> <hr/> <p>N. 6°38'40" W., beginning new measurement.</p>
44.60	Wash, 30 lks. wide, drains W.
49.058	<p>The cor. of secs. 14, 15, 22 and 23, monumented with a limestone, 16x11x7 ins., firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. with 3 notches on the S. edge and 2 notches on the E. edge.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <table style="margin: auto;"> <tr> <td>S15</td><td>S14</td></tr> <tr> <td>S22</td><td>S23</td></tr> </table> <p>2011</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 88°49'30" W., bet. secs. 14 and 23.</p> <p>8.30 Kingston Road, Nevada State Route 53, gravel surface, 30 lks. wide, bears N. 50° E. and S. 50° W.</p> <p>13.60 Enter wash, drains SW.</p> <p>18.30 Exit wash.</p> <p>28.25 Foot of hill, bears NE. and SW.; ascend.</p> <p>40.296 The 1/4 sec. cor. of secs. 14 and 23, monumented with a limestone, 18x14x8 ins., firmly set in a mound of stone, 3 ft. diam., 1/2 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <p>S14</p> <p>1/4 —</p> <p>S23</p> <p>2011</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>Cor. is located on spur, slopes S.</p> <hr/> <p>N. 89°27'00" W., beginning new measurement.</p> <p>17.00 Wash, 30 lks. wide, drains NW., at foot of hill, bears SE. and NW.</p> <p>33.20 Wash, 20 lks. wide, drains SW.</p> <p>40.331 The cor. of secs. 14, 15, 22 and 23.</p> <hr/>	S15	S14	S22	S23
S15	S14				
S22	S23				



DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 20°27'50" E., bet. secs. 14 and 15.
42.918	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.  T24S R57E 1/4 S15 S14  2011
49.80	Top of ridge, bears NE. and SW.
85.836	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.  T24S R57E S10 S11 S15 S14  2022
	From the cor. of secs. 11, 12, 13 and 14. N. 88°37'00" W., bet. secs. 11 and 14.
1.20	Enter wash, drains SW.
10.50	Kingston Road, Nevada State Route 53, gravel surface, 30 lks. wide, bears N. 30° E. and S. 30° W.
15.30	Exit wash.
31.70	Wash, 40 lks. wide, drains SW.
39.798	The 1/4 sec. cor. of secs. 11 and 14, monumented with a granite stone, 10x7x5 ins. (Record, 23x14x7 ins.), firmly set in a mound of stone, 3 ft. diam., 1 ft. high, no marks visible. This is accepted as the best available evidence of the position of the original corner.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T24S R57E S11 1/4 — S14</p> <p>2011</p> <p>Deposit the unmarked stone alongside the stainless steel post.</p> <hr/> <p>S. 84°53'00" W., beginning new measurement.</p>
43.709	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°46'50" E., bet. secs. 10 and 11.</p>
40.214	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
80.428	<p>T24S R57E 1/4 S10 S11</p> <p>2022</p> <p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
9.70	<p>T24S R57E S 3   S 2 S10   S11</p> <p>2017</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°10'50" W., bet. secs. 2 and 11.</p>
10.20	<p>Dirt road, 12 lks. wide, bears SE. and NW.</p>
15.40	<p>Overhead powerline, bears S. 30° E. and N. 30° W.</p>
24.00	<p>Wash, 30 lks. wide, drains SW.</p>
	<p>Wash, 25 lks. wide, drains SE.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
38.00	Wash, 25 lks. wide, drains SW.
39.474	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented with a limestone, 20x12x10 ins. (Record, 17x9x5 ins.), firmly set in a mound of stone, 2 1/2 ft. diam., 1/2 ft. high, no marks visible. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S 2 1/4 — S11</p> <p style="text-align: center;">2011</p> <p>Deposit the unmarked stone alongside the stainless steel post.</p> <hr/> <p>S. 88°38'30" W., beginning new measurement.</p>
9.75	Trail road, 12 lks. wide, bears SE. and WNW.
43.684	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 5°06'00" W., bet. secs. 2 and 3.</p>
8.80	Trail road, 12 lks. wide, bears ESE. and WNW.
13.50	Wash, 40 lks. wide, drains WSW.
40.370	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S 3   S 2</p> <p style="text-align: center;">2017</p>
47.30	Top of hill.
58.60	Trail road, 12 lks. wide, bears SE. and NW., in wash, 1 1/2 chs. wide, drains NW.
80.437	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°05'50" W., bet. secs. 33 and 34.</p>
37.721	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with a limestone, 19x8x6 ins., firmly set in a mound of stone, 2 ft. diam., 1/2 ft. high, mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S33 S34  2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°54'10" E., beginning new measurement.</p> <p>Across alluvial plain of several washes draining SSW.</p>
34.55	Overhead powerline, bears N. 30° E. and S. 30° W.
35.90	Trail road, 10 lks. wide, bears NE. and SW.
40.902	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a limestone, 15x9x7 ins., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. with 1 notch on the S. edge and 2 notches visible on the E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S28 S27 S33 S34  2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°14'30" W., bet. secs. 27 and 34.</p>
8.25	Spur, slopes NW.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.207	Intersect line 1-2, Mineral Survey No. 4371 A, Boss lode, at a point from which Cor. No. 1, hereinafter described, bears N. 55°50'20" E., 9.678 chs. dist.
40.094	Intersect line 3-4, Mineral Survey No. 4371 A, Boss No.3 lode, at a point from which Cor. No. 4, identical with Cor. No. 2, Mineral Survey No. 4371 A, Campo lode, hereinafter described, bears N. 24°33'10" W., 0.020 chs. dist.
41.373	Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.  T24S R57E S27 1/4 — S34  2011
46.50	Dirt road, bears N. and S.
62.80	Enter alluvial plain with several washes draining S.
79.30	Overhead powerline, bears N. 30° E. and S. 30° W.
80.30	Trail road, 10 lks. wide, bears NE. and SW.
82.746	The cor. of secs. 27, 28, 33 and 34. <hr/>
	N. 0°37'00" W., bet. secs. 27 and 28.  Across alluvial plain of several washes draining SW.
11.60	Dirt road, 20 lks. wide, bears ESE. and WNW.
13.80	Kingston Road, Nevada State Route 53, gravel surface, 40 lks. wide, bears N. 40° E. and S. 40° W.
41.118	The 1/4 sec. cor. of secs. 27 and 28, monumented with a limestone, 18x9x7 ins., firmly set 10 ins. in the ground, mkd. 1/4 on the E. face, with a mound of stone, 2 1/2 ft. diam., 1 ft. high, W. of cor.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T24S R57E 1/4 S28 S27  2011

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the mkd. stone alongside the stainless steel post, leave the mound of stone in place.</p> <hr/> <p>N. 0°28'50" W., beginning new measurement.</p>								
8.00	Trail road, 10 lks. wide, bears irregularly E. and W.								
40.782	<p>The cor. of secs. 21, 22, 27 and 28, monumented with a limestone, 17x9x6 ins., firmly set in a mound of stone, 2 ft. diam., 1/2 ft. high, mkd. with 2 notches on the S. edge and 2 notches visible on the E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>T24S</td><td>R57E</td></tr> <tr> <td>S21</td><td>S22</td></tr> <tr> <td>S28</td><td>S27</td></tr> </table> <p>2011</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 86°03'20" W., bet. secs. 22 and 27.</p> <p>Across alluvial plain of several washes draining SW.</p>	T24S	R57E	S21	S22	S28	S27		
T24S	R57E								
S21	S22								
S28	S27								
9.15	Overhead powerline, bears N. 51° E. and S. 51° W.								
25.60	Kingston Road, Nevada State Route 53, gravel surface, 40 lks. wide, bears N. 40° E. and S. 40° W.								
42.043	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>T24S</td><td>R57E</td></tr> <tr> <td></td><td>S22</td></tr> <tr> <td>1/4</td><td>—</td></tr> <tr> <td></td><td>S27</td></tr> </table> <p>2011</p> </div>	T24S	R57E		S22	1/4	—		S27
T24S	R57E								
	S22								
1/4	—								
	S27								
84.086	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/>								

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 1°21'40" W., bet. secs. 21 and 22.
41.124	<p>Across alluvial plain of several washes draining SW. Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S21 S22  2011</p>
82.248	<p>The cor. of secs. 15, 16, 21 and 22, monumented with a limestone, 16x11x7 ins., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. with 3 notches on the S. edge and 3 notches on the E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S16 S15 S21 S22  2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°12'40" W., bet. secs. 15 and 22.</p>
16.90	Foot of spur, bears N. and S.
25.90	Spur, slopes N.
37.50	Foot of spur, bears NE. and SW.
40.078	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T24S R57E S15 1/4 — S22</p> <p>2011</p>
80.156	<p>The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>N. 15°45'40" E., bet. secs. 15 and 16.</p>
41.861	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in a limestone shelf, with top mkd.</p>
	<p>T24S R57E 1/4 S16 S15</p> <p>2017</p>
83.722	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p>T24S R57E S 9 S10 S16 S15</p> <p>2017</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°22'50" W., bet. secs. 10 and 15.</p>
30.25	<p>Top of ridge, bears NE. and S.</p>
43.701	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>



DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T24S R57E S10 1/4 — S15  2017
51.80	Wash, 2 1/2 chs. wide, drains SW.
85.60	Spur, slopes S.
87.402	The cor. of secs. 9, 10, 15 and 16.
	<hr/> N. 0°34'20" E., bet. secs. 9 and 10.
18.75	Spur, slopes SSE.
40.290	Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T24S R57E 1/4 S 9   S10  2017
80.580	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T24S R57E S 4   S 3 S 9   S10  2017
	From this point, Cor. No. 3, Mineral Survey No. 4546, Rainbow No.1 lode, hereinafter described, bears N. 39°19'50" W., 31.898 chs. dist.
	<hr/> From the cor. of secs. 2, 3, 10 and 11. S. 89°29'00" W., bet. secs. 3 and 10.
15.80	Gulch, 30 lks. wide, drains irregularly N.
21.40	Top of hill.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 43.837	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S 3 1/4 — S10</p> <p style="text-align: center;">2017</p>
87.674	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 3°08'30" W., bet. secs. 3 and 4.</p>
23.20	Dirt road, 12 lks. wide, bears NE. and SW.
28.50	Wash, 10 chs. wide, drains SW. at confluence of wash entering from the N.
40.348	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S 4   S 3</p> <p style="text-align: center;">2017</p> <p>From this point, a limestone, 8x10x21 ins., firmly set in a mound of stone, 5 ft. diam., bears S. 81°02'50" W., 31.300 chs. dist., mkd. 1/4 on the W. face. The location of this mkd. stone is determined to be irreconcilable with found and restored original corner positions, is not supported by topographic calls and does not represent an original corner position.</p>
80.605	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°18'00" W., bet. secs. 32 and 33.</p>
0.30	Quartz Ave., asphalt surface, 40 lks. wide, bears E. and W.
1.40	Kingston Road, Nevada State Route 53, gravel surface, 40 lks. wide, bears N. 40° E. and S. 40° W.; across alluvial plain of several washes draining SW.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.208</p>	<p>The 1/4 sec. cor. of secs. 32 and 33, perpetuated by Donald Jaragosky, Nevada Professional Land Surveyor No. 6444, in 2001, monumented with an iron pipe, 1 in. diam., firmly set in a mound of stone, 2 1/2 ft. diam., 1/2 ft. high, with brass cap mkd. 1/4 PLS6444, with a granite stone, 10x7x6 ins. (Record, 16x11x4 ins., lying loose alongside, mkd. 1/4 on a face, as recorded in Clark County, Nevada, File 118, Page 02 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S32 S33  2011</p> <p>Insert the iron pipe inverted inside and deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°18'00" W., beginning new measurement.</p>
<p>20.114</p>	<p>The N 1/16 sec. cor. of secs. 32 and 33, determined by Donald Jaragowsky, Nevada PLS 6444, in 2001, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the ground, with plastic cap mkd. RLS 6444, with a rebar, 1 in. diam., 24 ins. long, firmly set alongside, projecting 6 ins. above the ground, with brass tag mkd. RE1624, as recorded in Clark County, Nevada, File 118, Page 02 of Surveys. This is accepted as a careful and faithful determination of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S32 S33  2011</p> <p>Insert the 5/8 in. diam. rebar inside and deposit the 1 in. diam. rebar alongside the stainless steel post.</p> <hr/> <p>N. 0°18'00" W., beginning new measurement.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 20.114</p>	<p>The cor. of secs. 28, 29, 32 and 33, monumented with a broken limestone, 17x10x8 ins., lying loose in a mound of stone, 3 ft. diam., 1/2 ft. high, with 1 notch visible on an edge, with a rebar, 5/8 in. diam., 18 ins. long, with aluminum cap, 1 1/2 ins. diam., mkd. RLS2051, firmly set alongside, as recorded in Clark County, Corner Record Instrument No. 970711.02260 and Corner Record Instrument No. 970711.02261. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <table border="1"> <tr> <td>S29</td><td>S28</td></tr> <tr> <td>S32</td><td>S33</td></tr> </table> <p>2011</p> </div> <p>Insert the rebar inside and deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 88°45'50" W., bet. secs. 28 and 33.</p> <p>9.80 Kingston Road, Nevada State Route 53, gravel surface, 40 lks. wide, bears N. 60° E. and S. 60° W.; across alluvial plain of several washes draining SW.</p> <p>40.973 Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <p>S28</p> <p>1/4 —</p> <p>S33</p> <p>2011</p> </div> <p>81.946 The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0°42'40" E., bet. secs. 28 and 29.</p> <p>Across alluvial plain of several washes draining SW.</p> <p>0.60 Trail road, 10 lks. wide, bears E. and W.</p>	S29	S28	S32	S33
S29	S28				
S32	S33				

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.444</p>	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with a limestone, 14x9x7 ins., firmly set in a mound of stone, 2 ft. diam., 1/2 ft. high, mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E 1/4 S29 S28</p> <p>2011</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°25'20" W., beginning new measurement.</p>
<p>40.473</p>	<p>The cor. of secs. 20, 21, 28 and 29, monumented with a limestone, 15x11x6 ins., firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. with 2 notches on the S. edge and 4 notches on the E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E S20 S21 S29 S28</p> <p>2011</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°30'50" W., bet. secs. 21 and 28.</p> <p>Across alluvial plain of several washes draining SW.</p>
<p>40.593</p>	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with a limestone, 18x11x7 ins., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T24S R57E S21 1/4 — S28</p> <p>2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°22'20" W., beginning new measurement.</p> <p>7.20 Gulch, 80 lks. wide, drains SW.</p> <p>40.334 The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 0°38'10" E., bet. secs. 20 and 21.</p> <p>Across alluvial plain of several washes draining SW.</p> <p>40.249 Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p>T24S R57E 1/4 S20 S21</p> <p>2011</p> <p>65.50 Foot of mountains, bears E. and W.</p> <p>80.498 The cor. of secs. 16, 17, 20 and 21, monumented with a basalt stone, (Record, limestone) 15x10x6 ins., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. with 3 notches on the S. edge and 4 notches on the E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p>T24S R57E S17 S16 S20 S21</p> <p>2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/>
--------	---

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 88°00'30" W., bet. secs. 16 and 21.</p>
3.90	Wash, 40 lks. wide, drains SW.
11.00	Wash, 60 lks. wide, drains SE.; ascend hill.
18.00	Top of hill.
32.50	Wash, 15 lks. wide, drains SW.
37.00	Foot of hill, bears S. and NW.
38.202	<p>The 1/4 sec. cor. of secs. 16 and 21, monumented with a limestone, 15x12x8 ins., firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S16 1/4 — S21</p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°27'10" W., beginning new measurement.</p>
21.70	Top of hill.
39.885	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 9°45'30" E., bet. secs. 16 and 17.</p>
40.857	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem., cemented in a drill hole in solid rock, with top mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S17 S16</p> <p style="text-align: center;">2011</p>
81.714	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS					
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <table style="margin: auto;"> <tr> <td>S 8</td><td>S 9</td></tr> <tr> <td>S17</td><td>S16</td></tr> </table> <p>2011</p> </div> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°20'50" W., bet. secs. 9 and 16.</p>	S 8	S 9	S17	S16
S 8	S 9				
S17	S16				
27.50	Top of ridge, bears N. and S.				
43.472	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in a sandstone outcrop, with top mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <p>S 9</p> <p>1/4 —</p> <p>S16</p> <p>2017</p> </div>				
67.30	Wash, 5 chs. wide, drains SSE.				
86.944	The cor. of secs. 8, 9, 16 and 17.				
	<hr/> <p>N. 0°17'00" E., bet. secs. 8 and 9.</p>				
16.30	Cross low sag; ascend.				
40.266	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <p>1/4</p> <p>S 8   S 9</p> <p>2011</p> </div>				
48.65	Spur, slopes E.				
80.532	Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.				



DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	<div style="text-align: center;">           T24S R57E            S 5   S 4            S 8   S 9         </div>
	2017
	From the cor. of secs. 3, 4, 9 and 10.
	S. 89°19'20" W., bet. secs. 4 and 9.
5.70	Wash, 30 lks. wide, drains NE.
30.00	Top of ridge, bears NE. and SW.
43.669	Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;">           T24S R57E            S 4            1/4 —            S 9         </div>
	2017
50.00	Spur, slopes NW.
65.00	Gulch, 20 lks. wide, drains NW.
70.10	Gulch, 30 lks. wide, drains N.
87.338	The cor. of secs. 4, 5, 8 and 9.
	N. 1°25'40" W., bet. secs. 4 and 5.
10.90	Gulch, 20 lks. wide, drains irregularly NW.
27.00	Dirt road, 12 lks. wide, bears NE. and SW.
29.00	Wash, 7 chs. wide, drains WSW.
35.50	Foot of mountain, bears E. and W.
40.278	Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S 5   S 4</p> <p style="text-align: center;">2017</p>
81.110	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., set 6 ins. below the ground, with brass cap mkd. as described in the field notes of the 1932 dependent resurvey of the Sixth Standard Parallel South, through a portion of Range 57 East, executed under Group No. 205, California.</p> <p>N. 0°09'00" W., bet. secs. 31 and 32.</p>
0.25	<p>Quartz Ave., asphalt surface, 40 lks. wide, bears E. and W.</p>
19.872	<p>The S 1/16 sec. cor. of secs. 31 and 32, determined by Jay M. Rassler, Nevada Professional Land Surveyor No. 1624, in 1975, monumented with an iron pipe, 1 in. diam., 24 ins. long, firmly set, projecting 10 ins. above the ground, as recorded in Clark County, Nevada, File 17, Page 38 of Plats. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S31   S32</p> <p style="text-align: center;">2011</p> <p>Deposit the iron pipe alongside the stainless steel post.</p> <hr/> <p>N. 0°09'00" W., beginning new measurement.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 19.872</p>	<p>The 1/4 sec. cor. of secs. 31 and 32, determined, reestablished and perpetuated by several local surveyors, including perpetuation by Jerry E. Barnson, Nevada Professional Land Surveyor No. 4046, in 1994, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set 4 ins. below the ground, with aluminum cap mkd. BARNSON RLS4046, with a metal pipe, 1 in. diam., 24 ins. long, set alongside, as recorded in Clark County, Nevada, File 70, Page 34 of Surveys. This position has been adopted by multiple Professional Land Surveyors and is accepted as a careful and faithful determination of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E 1/4 S31 S32  2011</p> </div> <p>Insert the rebar inside and deposit the metal pipe alongside the stainless steel post.</p>
<p>39.744</p>	<p>N. 0°09'00" W., beginning a new measurement.</p> <p>The cor. of secs. 29, 30, 31 and 32, reestablished by Donald Jaragosky, Nevada Professional Land Surveyor No. 6444, in 2001, monumented with a metal pipe, 1 in. diam., 24 ins. long, firmly set flush with the ground, with brass cap mkd. PLS6444, as recorded in Clark County, Nevada, File 118, Page 02 of Surveys. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E S30 S29 S31 S32  2011</p> </div> <p>Insert the metal pipe inside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°51'10" W., bet. secs. 29 and 32.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
18.20	Trail road, 10 lks. wide, bears ENE. and WSW.
20.230	<p>The E 1/16 sec. cor. of secs. 29 and 32, determined by Donald Jaragosky, Nevada Professional Land Surveyor No. 6444, in 2001, monumented with a rebar, 5/8 diam., firmly set, projecting 1 in. above the ground, with plastic cap mkd. PLS 6444, as recorded in Clark County, Nevada, File 118, Page 02 of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S29 E 1/16 ——— S32</p> <p>2022</p> </div> <p>Bury the rebar alongside stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°52'00" W., beginning new measurement.</p>
6.00	Trail road, 10 lks. wide, bears ESE. and WNW.
20.221	<p>The 1/4 sec. cor. of secs. 29 and 32, reestablished by Donald Jaragosky, Nevada Professional Land Surveyor No. 6444, in 2001, monumented with an iron pipe, 1 in. diam., firmly set, 9 ins. below the ground, with brass cap mkd. 1/4 PLS 6444 and a cross, as recorded in Clark County, Nevada, File 118, Page 02 of Surveys. This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E S29 1/4 ——— S32</p> <p>2022</p> </div> <p>Bury the iron pipe alongside the stainless steel post.</p> <p>Cor. is located N. 50° E., 50 lks. dist., from the intersection of Hopi St. and Nickel Ave., asphalt roads, 30 lks. wide, extending S. and W.</p> <hr style="width: 20%; margin: 10px auto;"/>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 88°14'30" W., beginning new measurement.
20.15	Intersection of Nickel Ave. and Inca St., asphalt roads, 30 lks. wide, extending E. and S., and Sandy Valley Road, gravel surface, 40 lks. wide, extending NW.
40.361	The cor. of secs. 29, 30, 31 and 32.
	N. 89°03'10" W., bet. secs. 30 and 31.
20.005	From this point, a galvanized pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground, bears SOUTH, 0.003 chs. dist., with brass cap mkd. RLS 2051.
40.189	The 1/4 sec. cor. of secs. 30 and 31, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set 3 ins. below the ground. This is accepted as a careful and faithful determination of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T24S R57E
	S30
	1/4 —
	S31
	2011
	Deposit the rebar inside the stainless steel post.
	From this cor., a galvanized pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, bears S. 87°03'00" E., 0.187 chs. dist. This position is not utilized in this survey.
	N. 89°03'50" W., beginning new measurement.
40.076	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°06'10" W., bet. secs. 29 and 30.
	Across alluvial plain of several washes draining SW.
18.40	Sandy Valley Road, gravel surface, 40 lks. wide, bears S. 55° E. and N. 55° W.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 39.987</p>	<p>The 1/4 sec. cor. of secs. 29 and 30, determined at the center of a mound of stone, 3 ft. diam., 1 ft. high. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E 1/4 S30 S29</p> <p>2011</p> </div>
<p>41.053</p>	<p>N. 0°52'10" E., beginning new measurement.</p> <p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E S19 S20 S30 S29</p> <p>2016</p> </div>
<p>40.232</p>	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°39'00" W., bet. secs. 20 and 29.</p> <p>Across alluvial plain of several washes draining SW.</p> <p>The 1/4 sec. cor. of secs. 20 and 29, monumented with a limestone, 18x9x8 ins., firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E S20 1/4 — S29</p> <p>2011</p> </div>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 88°54'10" W., beginning new measurement.</p>
40.209	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/> <p>N. 88°50'50" W., bet. secs. 19 and 30.</p>
40.270	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with a limestone, 16x12x9 ins., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <p>S19</p> <p>1/4 —</p> <p>S30</p> <p>2011</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°38'00" W., beginning new measurement.</p>
22.80	<p>Sandy Valley Road, gravel surface, 40 lks. wide, bears S. 50° E. and N. 35° W.</p>
40.251	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 1°13'00" E., bet. secs. 19 and 20.</p> <p>Across alluvial plain of several washes draining SW.</p>
41.057	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with a limestone, 15x10x7 ins., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T24S R57E 1/4 S19 S20  2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°20'40" E., beginning new measurement.</p>
40.388	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a limestone, 14x12x7 ins., firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. with 3 notches on the S. edge and 5 notches on the E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S18 S17 S19 S20  2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°44'50" W., bet. secs. 17 and 20.</p>
1.70	<p>Spur, slopes SW.</p>
19.30	<p>Foot of mountain, bears NE. and SW.; thence across alluvial plain of several washes draining SW.</p>
39.724	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with a limestone, 23x11x7 ins., firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S17 1/4 — S20  2011</p>



DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°39'00" W., beginning new measurement.</p>
40.477	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>N. 89°20'10" W., bet. secs. 18 and 19.</p> <p>Across alluvial plain of several washes draining S.</p>
40.500	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <p>S18</p> <p>1/4 ———</p> <p>S19</p> <p>2011</p> </div>
81.223	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 4°41'10" E., bet. secs. 17 and 18.</p> <p>Across alluvial plain of several washes draining SW.</p>
40.417	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E</p> <p>1/4</p> <p>S18 S17</p> <p>2011</p> </div>
80.834	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T24S R57E  S 7   S 8  S18   S17    2011 </div>
	<hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°58'20" W., bet. secs. 8 and 17.</p>
8.75	Ridge, bears NE. and SW.
37.00	Wash, 1 ch. wide, drains SW.
43.715	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T24S R57E  S 8  1/4 —  S17    2011 </div>
87.430	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>N. 88°50'00" W., bet. secs. 7 and 18.</p> <p>Across alluvial plain of several washes draining W.</p>
43.648	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T24S R57E  S 7  1/4 —  S18    2011 </div>
55.00	Leave alluvial plain.
69.30	Toe of isolated hill; ascend.
74.00	Top of isolated hill; descend.
80.00	Toe of isolated hill.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 87.743	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°14'30" E., bet. secs. 7 and 8.
40.282	Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T24S R57E 1/4 S 7   S 8  2017
64.60	Enter wash, drains SW.
76.30	Dirt road, 12 lks. wide, bears NE. and SW.
78.75	Leave wash.
80.45	Trail road, 10 lks. wide, bears NE. and SW.
80.564	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T24S R57E S 6   S 5 S 7   S 8  2017
	Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.
	From the cor. of secs. 4, 5, 8 and 9.
	S. 89°59'40" W., bet. secs. 5 and 8.
3.30	Wash, 40 lks. wide, drains N.
10.80	Ridge, bears N. and S.
43.737	Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S 5 1/4 — S 8</p> <p style="text-align: center;">2017</p>
62.50	Enter wash, drains SW.
84.10	Dirt road, 12 lks. wide, bears NE. and SW.
85.90	Exit wash.
87.30	Trail road, 10 lks. wide, bears NE. and SW.
87.474	The cor. of secs. 5, 6, 7 and 8.
	<hr/> <p>N. 88°30'00" W., bet. secs. 6 and 7.</p>
22.75	Wash, 1 ch. wide, drains SW.
32.50	Confluence of two gulches, each 20 lks. wide, drains SW.
43.894	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E S 6 1/4 — S 7</p> <p style="text-align: center;">2017</p>
	<hr/> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
64.20	Enter wash, drains SW.
87.481	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.
	<hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°22'00" E., bet. secs. 5 and 6.</p>
12.80	Wash, 75 lks. wide, drains W.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.282</p>	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T24S R57E 1/4 S 6   S 5</p> <p style="text-align: center;">2017</p>
<p>80.665</p>	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1715, TPS. 24 S., RS. 57 AND 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Mineral Surveyor T.K. Stewart in 1895</p> <hr/> <p style="text-align: center;">Excelsior lode</p> <p>From Cor. No. 9, Mineral Survey No. 1715, Excelsior lode, identical with Cor. No. 6, Mineral Survey No. 1715, Cleveland lode, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 5 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of a portion of Mineral Survey No. 1715, executed under Group No. 887.</p> <p>Thence N. 62°48'40" W., on a portion of line 9-10, Mineral Survey No. 1715, Excelsior lode.</p>
<p>1.078</p>	<p>Cor. No. 5, Mineral Survey No. 2110, Honduras lode, hereinafter described.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1861, TPS. 24 S., RS. 57 AND 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Mineral Surveyor H.W. Newby in 1899</p> <hr/> <p style="text-align: center;">John lode</p> <p>From the point of intersection of line 12-13, Mineral Survey No. 1861, John lode, and the line bet. secs. 31 and 36, on the E. bdy. of the Tp.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1861,  
TPS. 24 S., RS. 57 AND 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this point, Cor. No. 12, Mineral Survey No. 1861, John lode, identical with Cor. No. 18, Mineral Survey No. 1861, Black Lime lode, bears S. 70°05'00" E., 5.644 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 6 ft. diam., 2 ft. high, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of portions of Mineral Survey No. 1861, John lode, executed under Group No. 887. Cor. is located on the SE. edge of a gulch, drains NE.</p> <p>From this same point, the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described, bears N. 12°04'10" E., 6.140 chs. dist.</p> <p>From this same point, the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., bears S. 12°04'10" W., 40.810 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of the W. bdy., T. 24 S., R. 58 E., executed under Group No. 887.</p> <p>N. 70°05'00" W., on a portion of line 12-13, Mineral Survey No. 1861, John lode.</p>
13.061	Intersect the line bet. secs. 25 and 36, at a point from which the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described, bears N. 83°27'00" E., 13.653 chs. dist.
17.454	Cor. No. 13, Mineral Survey No. 1861, John lode, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in mound of stone, 5 ft. diam., 2 1/2 ft. high, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of portions of Mineral Survey No. 1861, John lode, executed under Group No. 887.
8.846	<p>Thence N. 18°26'20" E., on line 13-14, Mineral Survey No. 1861, John lode.</p> <p>Cor. No. 14, Mineral Survey No. 1861, John lode, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. diam., 2 ft. high, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of portions of Mineral Survey No. 1861, John lode, executed under Group No. 887.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 1919,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA


## CHAINS

Reestablishment of the Survey Executed by  
U.S. Deputy Mineral Surveyor H.W. Newby in 1900

## Hillside lode

From the point for Cor. No. 1, Mineral Survey No. 1919, Hillside lode, determined by grant boundary adjustment bet. Cor. No. 2, Mineral Survey No. 1919, Hillside lode, and Cor. No. 6, Mineral Survey No. 1919, Hillside lode; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.



2010

Thence S. 37°16'30" W., on line 1-2, Mineral Survey No. 1919, Hillside lode.

0.595

Intersect line 3-4, Mineral Survey No. 1920, Hattie A. lode, at a point from which Cor. No. 4, hereinafter described, on line 2-3, Mineral Survey No. 1981, Yellow Jacket lode, bears S. 86°27'40" E., 7.221 chs. dist.

4.096

Intersect the line bet. secs. 24 and 25, at a point from which the 1/4 sec. cor. of secs. 24 and 25, hereinbefore described, bears S. 84°49'00" W., 15.424 chs. dist.

7.415

Intersect line 4-1, Mineral Survey No. 1920, Libie lode, identical with a portion of line 1-2, Mineral Survey No. 1920, Hattie A. lode, at a point from which Cor. No. 1, Mineral Survey No. 1920, Libie lode, identical with Cor. No. 4, Mineral Survey No. 1920, Shufly lode, on line 1-2, Mineral Survey No. 1920, Hattie A. lode, hereinafter described, bears S. 85°43'40" E., 0.614 chs. dist.

11.371

Cor. No. 2, Mineral Survey No. 1919, Hillside lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 2-1919 H.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 6 1/2 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 1919,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="906 271 1130 472" data-label="Diagram"> </div> <p>Deposit the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence S. 52°19'00" W. on line 2-3, Mineral Survey No. 1919, Hillside lode.</p> <p>7.768 Intersect line 3-4, Mineral Survey No. 1920, Libie lode, at a point from which Cor. No. 4, on line 1-2, Mineral Survey No. 1920, Hattie A. lode, hereinafter described, bears N. 0°43'20" E., 8.527 chs. dist.</p> <p>11.429 Cor. No. 3, Mineral Survey No. 1919, Hillside lode, monumented with a wood post, 4x4 ins., 1 1/2 ft. long, partially burnt, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. 3-1919 H.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="847 1116 1057 1317" data-label="Diagram"> </div> <p>Deposit the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence N. 41°24'20" W. on line 3-4, Mineral Survey No. 1919, Hillside lode.</p> <p>9.094 Cor. No. 4, Mineral Survey No. 1919, Hillside lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 4-1919 H.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in limestone face, with top mkd.</p>



DEPENDENT RESURVEY OF MINERAL SURVEY NO. 1919,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="860 275 1063 439"> <p>T24S R57E S25</p> <p>MS 4 1919 HI</p> <p>2010</p> </div> <p>Leave the mkd. wood post lying loose alongside the brass tablet.</p> <hr/> <p>Thence N. 52°18'30" E. on line 4-5, Mineral Survey No. 1919, Hillside lode.</p> <p>7.631 Intersect line 2-3, Mineral Survey No. 1920, Hattie A. lode, at a point from which Cor. No. 2, hereinafter described, bears S. 2°19'50" W., 0.499 chs. dist.</p> <p>7.762 Intersect the line bet. secs. 24 and 25, at a point from which the 1/4 sec. cor. of secs. 24 and 25, hereinbefore described, bears S. 84°49'00" W., 2.046 chs. dist.</p> <p>11.00 Graded dirt road, 12 lks. wide, bears SE. and NW.</p> <p>11.394 Point for Cor. No. 5, Mineral Survey No. 1919, Hillside lode, determined by grant boundary adjustment bet. Cor. No. 4, Mineral Survey No. 1919, Hillside lode and Cor. No. 6, Mineral Survey No. 1919, Hillside lode; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in a 5x7x8 ft. boulder, with top mkd.</p> <div data-bbox="868 1113 1047 1297"> <p>MS 1920 H A</p> <p>MS 1919 5 HI</p> <p>2010</p> </div> <hr/> <p>Thence N. 37°18'30" E. on line 5-6, Mineral Survey No. 1919, Hillside lode.</p> <p>3.064 Intersect line 3-4, Mineral Survey No. 1920, Hattie A. lode, at a point from which Cor. No. 3, hereinafter described, bears N. 86°27'40" W., 4.638 chs. dist.</p> <p>11.394 Cor. No. 6, Mineral Survey No. 1919, Hillside lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. 6-1919 H.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in rock face, with top mkd.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 1919,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T24S R57E

S24

6

MS

1919

HI

2010

Leave the mkd. wood post lying loose alongside the brass tablet.

Thence S.  $41^{\circ}28'30''$  E. on line 6-1, Mineral Survey No. 1919, Hillside lode.

9.097 Cor. No. 1, Mineral Survey No. 1919, Hillside lode and point of beginning.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 1920,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of Portions of the Survey Executed by  
U.S. Deputy Mineral Surveyor H.W. Newby in 1900

Shufly lode

From Cor. No. 2, Mineral Survey No. 1920, Shufly lode, identical with Cor. No. 3, Mineral Survey No. 1920, Last Chance lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. 2-1920.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

MS1920	MS1920
SH	L C
2	3

BA 2  
MS1943

2011

Deposit the mkd. wood post alongside the stainless steel post.

Thence N.  $85^{\circ}36'50''$  W., on line 2-3, Mineral Survey No. 1920, Shufly lode.

8.408 Intersect line 3-4, Mineral Survey No. 1943, Barefoot No. 2 lode, at a point from which Cor. No. 4, hereinafter described, bears S.  $86^{\circ}18'20''$  W., 2.275 chs. dist.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 1920,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

8.977

Cor. No. 3, Mineral Survey No. 1920, Shufly lode, identical with Cor. No. 2, Mineral Survey No. 1920, Libie lode, determined at the center of a mound of stone, 3 ft. diam., 1 ft. high, with a wood post, 4x4 ins., 3 ft. long, lying loose alongside, mkd. 3-1920. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

MS	MS
1920	1920
LI	SH
2	3

T24S R57E  
S25

2010

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

---

Libie lode

From Cor. No. 2, Mineral Survey No. 1920, Libie lode, identical with Cor. No. 3, Mineral Survey No. 1920, Shufly lode.

Thence N. 86°48'20" W., on line 2-3, Mineral Survey No. 1920, Libie lode.

8.810

Cor. No. 3, Mineral Survey No. 1920, Libie lode, monumented with a wood post, 3 ins. diam., 4 ft. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. 1920.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T24S	MS
R57E	1920
S25	3 LI

2010

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

---

Thence N. 0°43'20" E., on line 3-4, Mineral Survey No. 1920, Libie lode.


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 1920,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
12.648	Intersect line 2-3, Mineral Survey No. 1919, Hillside lode, at a point from which Cor. No. 3, hereinbefore described, bears S. 52°19'00" W., 3.661 chs. dist.								
21.175	<p>Point for Cor. No. 4, Mineral Survey No. 1920, Libie lode, on line 1-2, Mineral Survey No. 1920, Hattie A. lode, determined at proportionate measurement bet. Cor. No. 1, Mineral Survey No. 1920, Libie lode, identical with Cor. No. 4, Mineral Survey No. 1920, Shufly lode, on line 1-2, Mineral Survey No. 1920, Hattie A. lode, and Cor. No. 2, Mineral Survey No. 1920, Hattie A. lode; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>MS1920 H A</p> <table> <tr> <td>MS</td><td>4</td></tr> <tr> <td>1919</td><td>MS</td></tr> <tr> <td>HI</td><td>1920</td></tr> <tr> <td></td><td>LI</td></tr> </table> <p>2022</p> </div> <p>Thence S. 85°43'40" E., on line 4-1, Mineral Survey No. 1920, Libie lode, identical with a portion of line 1-2, Mineral Survey No. 1920, Hattie A. lode.</p>	MS	4	1919	MS	HI	1920		LI
MS	4								
1919	MS								
HI	1920								
	LI								
8.460	Intersect line 1-2, Mineral Survey No. 1919, Hillside lode, at a point from which Cor. No. 2, hereinbefore described, bears S. 37°16'30" W., 3.956 chs. dist.								
9.074	<p>Cor. No. 1, Mineral Survey No. 1920, Libie lode, identical with Cor. No. 4, Mineral Survey No. 1920, Shufly lode, on line 1-2, Mineral Survey No. 1920, Hattie A. lode, monumented with a wood post, 3x2 ins., 30 ins. long, loosely set in a mound of stone, 4 ft. diam., 1 1/2 ft. high, with the marks 19 visible on a shaved faced with illegible markings. Alongside of which is a wood post, 5x4 ins., 5 ft. long, loosely set, mkd. NEVADA on one face, INTERSECTON on an adjacent face and Libie on the opposite face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>								

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 1920,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS																	
	<div data-bbox="868 271 1052 534"> <p>MS1920 H A</p> <table> <tr> <td>1</td><td>4</td></tr> <tr> <td>MS</td><td>MS</td></tr> <tr> <td>1920</td><td>1920</td></tr> <tr> <td>LI</td><td>SH</td></tr> </table> <p>2022</p> </div> <p>Deposit the wood posts, inverted, alongside the stainless steel post.</p> <p>From this corner, Cor. No. 4, Mineral Survey No. 1920, Hattie A. lode, bears S. 87°27'30" E., 9.012 chs. dist.</p> <hr/> <p>Hattie A. lode</p> <p>From Cor. No. 4, Mineral Survey No. 1920, Libie lode, on line 1-2, Mineral Survey No. 1920, Hattie A. lode.</p> <p>Thence N. 85°43'40" W., on a portion of line 1-2, Mineral Survey No. 1920, Hattie A. lode.</p> <p>3.009 Cor. No. 2, Mineral Survey No. 1920, Hattie A. lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, with illegible markings. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in limestone face, with top mkd.</p> <div data-bbox="852 1249 1047 1353"> <table> <tr> <td></td><td>MS</td></tr> <tr> <td>MS</td><td>1920</td></tr> <tr> <td>1919</td><td>2 H A</td></tr> <tr> <td>HI</td><td></td></tr> </table> </div> <p>2010</p> <p>Leave wood post lying alongside brass tablet.</p> <hr/> <p>Thence N. 2°19'50" E., on line 2-3, Mineral Survey No. 1920, Hattie A. lode.</p> <p>0.499 Intersect line 4-5, Mineral Survey No. 1919, Hillside lode, at a point from which Cor. No. 5, hereinbefore described, bears N. 52°18'30" E., 3.763 chs. dist.</p> <p>0.570 Intersect the line bet. secs. 24 and 25, at a point from which the 1/4 sec. cor. of secs. 24 and 25, hereinbefore described, bears S. 84°49'00" W., 1.945 chs. dist.</p>	1	4	MS	MS	1920	1920	LI	SH		MS	MS	1920	1919	2 H A	HI	
1	4																
MS	MS																
1920	1920																
LI	SH																
	MS																
MS	1920																
1919	2 H A																
HI																	

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 1920,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 5.526</p>	<p>Point for Cor. No. 3, Mineral Survey No. 1920, Hattie A. lode, determined by the method of parallel end lines and side lines; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="876 486 1079 694"> <p>T24S R57E S24</p>  <p>2022</p> </div> <p>Thence S. 86°27'40" E., on line 3-4, Mineral Survey No. 1920, Hattie A. lode.</p> <p>4.638 Intersect line 5-6, Mineral Survey No. 1919, Hillside lode, at a point from which Cor. No. 5, hereinbefore described, bears S. 37°18'30" W., 3.064 chs. dist.</p> <p>15.372 Intersect line 1-2, Mineral Survey No. 1919, Hillside lode, at a point from which Cor. No. 1, hereinbefore described, bears N. 37°16'30" E., 0.595 chs. dist.</p> <p>22.593 Cor. No. 4, Mineral Survey No. 1920, Hattie A. lode, on line 2-3, Mineral Survey No. 1981, Yellow Jacket lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, with illegible markings. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="836 1398 1088 1636"> <table> <tr><td>T24S</td><td></td></tr> <tr><td>R57E</td><td></td></tr> <tr><td>S24</td><td>MS1981</td></tr> <tr><td>4</td><td>Y J</td></tr> <tr><td>MS</td><td></td></tr> <tr><td>1920</td><td></td></tr> <tr><td>H A</td><td></td></tr> </table> </div> <p>2011</p> <p>Deposit the wood post, inverted, alongside the stainless steel post.</p>	T24S		R57E		S24	MS1981	4	Y J	MS		1920		H A	
T24S															
R57E															
S24	MS1981														
4	Y J														
MS															
1920															
H A															

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 1920,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

From this corner, Cor. No. 1, Mineral Survey No. 1920, Hattie A. lode, bears S.  $2^{\circ}19'50''$  W., 5.526 chs. dist., determined at the center of a mound of stone, 3 ft. diam., 1 ft. high, with an iron pipe, 1 1/4 ins. diam., 24 ins. long, lying loose alongside. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

MS1920		
L C		
H A 1		MS1920
		L C

2022

Deposit the iron pipe alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1943,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by  
U.S. Deputy Mineral Surveyor F. Anderson in 1901

Barefoot No. 2 lode

From Cor. No. 3, Mineral Survey No. 1943, Barefoot No. 2 lode, determined at the center of a mound of stone, 2 1/2 ft. diam., 1 ft. high. This mound correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.

MS1857
GC

	3	
BA NO2		
MS1943		

2011

Thence S.  $86^{\circ}18'20''$  W., on line 3-4, Mineral Survey No. 1943, Barefoot No. 2 lode.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1943,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 13.485	Intersect line 2-3, Mineral Survey No. 1920, Shufly lode, at a point from which Cor. No. 3, identical with Cor. No. 2, Mineral Survey No. 1920, Libie lode, hereinbefore described, bears N. 85°36'50" W., 0.569 chs. dist.								
15.760	<p>Cor. No. 4, Mineral Survey No. 1943, Barefoot No. 2 lode, monumented with a wood post, 4x4 ins., 2 ft. long, firmly set in a mound of stone, 4 ft. diam., 3 ft. high, mkd. 1943 B.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="860 683 1088 808"> <table> <tr><td>T24S</td><td></td></tr> <tr><td>R57E</td><td>4 MS</td></tr> <tr><td>S25</td><td>1943</td></tr> <tr><td></td><td>BA NO2</td></tr> </table> </div> <p>2011</p> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Thence S. 1°26'10" E., on line 4-5, Mineral Survey No. 1943, Barefoot No. 2 lode.</p>	T24S		R57E	4 MS	S25	1943		BA NO2
T24S									
R57E	4 MS								
S25	1943								
	BA NO2								
3.50	Head of draw, drains SW.								
7.90	Top of ridge, slopes E. and W.								
9.095	<p>Cor. No. 5, Mineral Survey No. 1943, Barefoot No. 2, lode, monumented with the remains of a wood post lying within a mound of stone, 4 ft. diam., 3 ft. high. This evidence correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="860 1522 1088 1667"> <table> <tr><td></td><td>MS</td></tr> <tr><td>T24S</td><td>1943</td></tr> <tr><td>R57E</td><td>BA NO2</td></tr> <tr><td>S25</td><td>5</td></tr> </table> </div> <p>2011</p> <p>Deposit the remains of the wood post alongside the stainless steel post.</p> <hr/>		MS	T24S	1943	R57E	BA NO2	S25	5
	MS								
T24S	1943								
R57E	BA NO2								
S25	5								



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1943,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence N. 81°48'40" E. on a portion of line 5-6, Mineral Survey No. 1943, Barefoot No. 2 lode.
1.80	Top of ridge, bears SE. and NW.
7.902	Cor. No. 4, Mineral Survey No. 1943, Mary Anna lode.
	<p style="text-align: center;">Mary Anna lode</p> <p>From Cor. No. 4, Mineral Survey No. 1943, Mary Anna lode, on line 5-6, Mineral Survey No. 1943, Barefoot No. 2 lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. 1943.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>MS 1943 BA NO2</p> <p style="margin-left: 100px;">4</p> <p>T24S      MS R57E      1943 S25      M A</p> </div> <p style="text-align: center;">2011</p> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <p>Thence S. 19°58'20" W., on line 4-5, Mineral Survey No. 1943, Mary Anna lode.</p>
3.20	Top of ridge, bears E. and W.
10.062	<p>Cor. No. 5, Mineral Survey No. 1943, Mary Anna lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 4 ft. diam., 3 ft. high, mkd. 5 1943 M.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1943,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="857 275 1084 445"> </div> <p data-bbox="922 478 987 507">2011</p> <p data-bbox="435 534 1414 590">Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p data-bbox="435 644 1409 700">Thence N. 72°14'00" E., on line 5-1, Mineral Survey No. 1943, Mary Anna lode.</p> <p data-bbox="305 721 1446 803">0.039 Intersect line 4-5, Mineral Survey No. 3575, Lookout lode, at a point from which the true point for Cor. No. 4, hereinafter described, bears S. 50°46'00" W., 4.544 chs. dist.</p> <p data-bbox="289 824 1446 907">19.709 Intersect line 6-1, Mineral Survey No. 3575, Lookout lode, at a point from which Cor. No. 1, hereinafter described, bears S. 39°45'40" E., 1.620 chs. dist.</p> <p data-bbox="289 928 1463 1011">23.980 Cor. No. 1, Mineral Survey No. 1943, Mary Anna lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 4 ft. diam., 3 ft. high, mkd. 1 1943 MA.</p> <p data-bbox="435 1038 743 1067">At the corner point</p> <p data-bbox="435 1087 1446 1197">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="841 1224 1068 1307"> </div> <p data-bbox="922 1369 987 1398">2011</p> <p data-bbox="435 1425 1463 1481">Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p data-bbox="435 1543 1463 1599">Thence N. 19°04'30" E., on a portion of line 1-2, Mineral Survey No. 1943, Mary Anna lode.</p> <p data-bbox="305 1626 1463 1682">0.458 Cor. No. 7, Mineral Survey No. 2110, Honduras lode, hereinafter described.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1981,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Reestablishment of a Portion of the Survey Executed by  
U.S. Deputy Mineral Surveyor H.W. Newby in 1901

Yellow Jacket lode

From Cor. No. 2, Mineral Survey No. 2110, Bellevue lode,  
identical with Cor. No. 8, Mineral Survey No. 2110, Empire lode,  
hereinafter described, on line 1-2, Mineral Survey No. 1981,  
Yellow Jacket lode.

Thence N. 70°48'20" W., on a portion of line 1-2, Mineral Survey  
No. 1981, Yellow Jacket lode.


5.714 Intersect the line bet. secs. 24 and 25, at a point from which  
the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.,  
hereinbefore described, bears N. 84°49'00" E., 10.645 chs. dist.

17.578 Cor. No. 2, Mineral Survey No. 1981, Yellow Jacket lode,  
monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in  
a mound of stone, 3 ft. diam., 2 ft. high, with the mark 2  
visible.

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented  
in a drill hole in a limestone face, with top mkd.

T24S  
R57E  
S24



2010

Leave the mkd. wood post lying loose alongside the brass tablet.  
from which

A chiseled X followed by the letters BO on a limestone  
bench, 1 ft. high, bears N. 79°36' E.,  
9.2 lks. dist.

A chiseled X followed by the letters BO on face of an  
exposed limestone rib, bears N. 25°51' W.,  
24.3 lks. dist.

Thence S. 2°15'40" W., on a portion of line 2-3, Mineral Survey  
No. 1981, Yellow Jacket lode.

3.438 Cor. No. 4, Mineral Survey No. 1920, Hattie A. lode,  
hereinbefore described.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 2002,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS


Reestablishment of the Survey Executed by  
U.S. Deputy Mineral Surveyor H.W. Newby in 1901

Old Timer lode

From Cor. No. 1, Mineral Survey No. 2002, Old Timer lode, monumented with the remains of a wood post lying within a mound of stone, 2 ft. diam., 1 ft. high. This evidence correlates well with other found corners and the existing improvements on this claim, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



Deposit the remains of the wood post alongside the stainless steel post.


Cor. is located on top of a cliff, 20 ft. high, bears N. and S.

Thence S. 3°49'20" W. on line 1-2, Mineral Survey No. 2002, Old Timer lode.

9.247

Point for Cor. No. 2, Mineral Survey No. 2002, Old Timer lode, determined by grant boundary adjustment bet. Cor. No. 1, Mineral Survey No. 2002, Old Timer lode, and Cor. No. 3, Mineral Survey No. 2002, Old Timer lode; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



from which

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 2002,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A chiseled X followed by the letters BO on the S. face of a limestone outcrop, bears N. 26°32' E., 32.6 lks. dist.</p> <p>A chiseled X followed by the letters BO on the SE. face of a limestone outcrop, bears N. 29°59' W., 14.3 lks. dist.</p> <hr/> <p>Thence N. 86°08'40" W. on line 2-3, Mineral Survey No. 2002, Old Timer lode.</p> <p>18.956 Cor. No. 3, Mineral Survey No. 2002, Old Timer lode, monumented with a cedar post, 4 ins. diam., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. 1863.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="933 858 1088 970"> <p>MS2002 O T 3</p> </div> <p>T24S R57E S25</p> <p>2011</p> <p>Deposit the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence N. 2°11'00" W. on line 3-4, Mineral Survey No. 2002, Old Timer lode.</p> <p>8.247 Cor. No. 4, Mineral Survey No. 2002, Old Timer lode, monumented with a cedar post, 4 ins. diam., 4 ft. long, in a mound of stone, 3 ft. diam., 2 ft. high, mkd. 1863.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="820 1543 1063 1686"> <p>T24S R57E S25 4 MS2002 O T</p> </div> <p>2011</p> <p>Deposit the mkd. wood post alongside the stainless steel post.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 2002,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Thence S. 89°09'50" E. on line 4-1, Mineral Survey No. 2002, Old Timer lode.

19.845

Cor. No. 1, Mineral Survey No. 2002, Old Timer lode and point of beginning.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 2044,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA


Reestablishment of a Portion of the Survey Executed by  
U.S. Deputy Mineral Surveyor J.T. McWilliams in 1902

Copper Chief lode

From Cor. No. 4, Mineral Survey No. 2044, Copper Chief lode, identical with the witness cor. to Cor. No. 1, Mineral Survey No. 3470, Mobile lode, on line 1-2, Mineral Survey No. 3470, Mobile lode, monumented with a wood post, 4x8 ins., 4 ft. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. 4-2044 CC USS WC MOBILE.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.



2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Thence S. 16°23'40" W., on line 4-1, Mineral Survey No. 2044, Copper Chief lode.

9.798

Cor. No. 1, Mineral Survey No. 2044, Copper Chief lode, monumented with a wood post, 4x8 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 3 ft. high, mkd. 1-2044 CC.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 2044,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

MS  
2044  
C C  
1

T24S R57E  
S35

2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Thence N. 75°55'10" W., on line 1-2, Mineral Survey No. 2044, Copper Chief lode.

18.978

Cor. No. 2, Mineral Survey No. 2044, Copper Chief lode, monumented with a wood post, 4x8 ins., 4 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 3 ft. high, mkd. 2-2044 CC.

from which

A cross on the vertical face of a limestone outcrop bears N. 2°00' W., 47.0 lks. dist., with the marks 2-2044 BR chisled alongside.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.

T24S MS  
R57E 2044  
S35 2 C C

2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Thence N. 14°04'40" E., on line 2-3, Mineral Survey No. 2044, Copper Chief lode.

8.553

Cor. No. 3, Mineral Survey No. 2044, Copper Chief lode, monumented with a wood post, 4x8 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 3 ft. high, with illegible markings.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 2044,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T24S  
R57E  
S35 3  
MS  
2044  
C C

2011

Deposit wood post, inverted, alongside stainless steel post.

Thence S. 78°46'30" E., on a portion of line 3-4, Mineral Survey No. 2044, Copper Chief lode.

- 0.048 Intersect line 1-2, Mineral Survey No. 2048, Shenandoah lode, at a point from which Cor. No. 1, hereinafter described, bears S. 45°55'50" E., 6.040 chs. dist.
- 6.707 Intersect line 4-1, Mineral Survey No. 2048, Shenandoah lode, at a point from which Cor. No. 1, hereinafter described, bears S. 37°02'40" W., 3.639 chs. dist.
- 10.233 Cor. No. 2, Mineral Survey No. 3470, Mobile lode, hereinafter described.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 2048,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
U.S. Deputy Mineral Surveyor J.T. McWilliams in 1902

Shenandoah lode

From Cor. No. 1, Mineral Survey No. 2048, Shenandoah lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, mkd. 1-2048 S.

At the corner point



Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

MS  
2048  
SH  
1  
MS  
2044 C C


2011



DEPENDENT RESURVEY OF MINERAL SURVEY NO. 2048,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <p>Thence N. 45°55'50" W., on line 1-2, Mineral Survey No. 2048, Shenandoah lode.</p> <p>6.040 Intersect line 3-4, Mineral Survey No. 2044, Copper Chief lode, at a point from which Cor. No. 3, hereinbefore described, bears N. 78°46'30" W., 0.048 chs. dist.</p> <p>6.60 Top of ridge, bear E. and W.</p> <p>13.747 Intersect the line bet. secs. 26 and 35, at a point from which the 1/4 sec. cor. of. secs. 26 and 35, hereinbefore described, bears S. 88°00'40" W., 0.961 chs. dist.</p> <p>19.366 Cor. No. 2, Mineral Survey No. 2048, Shenandoah lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. 2 2048 U.S.S.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 5 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>T24S MS R57E 2 2048 S26 SH</p> </div> <p style="text-align: center;">2011</p> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Thence N. 43°49'10" E., on line 2-3, Mineral Survey No. 2048, Shenandoah lode.</p> <p>8.967 Cor. No. 3, Mineral Survey No. 2048, Shenandoah lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. 3 2048 S U.S.S.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>T24S R57E 3 MS S26 2048 SH</p> </div> <p style="text-align: center;">2011</p>
--------	---

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 2048,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Thence S. 47°06'00" E., on line 3-4, Mineral Survey No. 2048, Shenandoah lode.</p> <p>14.589 Intersect the line bet. secs. 26 and 35, at a point from which the 1/4 sec. cor. of secs. 26 and 35, hereinbefore described, bears S. 88°00'40" W., 13.827 chs. dist.</p> <p>18.258 Cor. No. 4, Mineral Survey No. 2048, Shenandoah lode, determined at the center of a mound of stone, 3 ft. diam., 1 ft. high, with a wood post, 4x4 ins., 3 ft. long, lying loose alongside, mkd. 4 2048 S. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>MS 2048 4 SH</p> <p>T24S R57E S35</p> <p>2011</p> </div> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Thence S. 37°02'40" W., on line 4-1, Mineral Survey No. 2048, Shenandoah lode.</p> <p>5.771 Intersect line 3-4, Mineral Survey No. 2044, Copper Chief lode, at a point from which Cor. No. 2, Mineral Survey No. 3470, Mobile lode, hereinafter described, bears S. 78°46'30" E., 3.526 chs. dist.</p> <p>9.410 Cor. No. 1, Mineral Survey No. 2048, Shenandoah lode and point of beginning.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 2110,  
TPS. 24 S., RS. 57 AND 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS


Reestablishment of Portions of the Survey Executed by  
U.S. Deputy Mineral Surveyor H.K. Wheeler in 1903

Honduras lode

From Cor. No. 5, Mineral Survey No. 2110, Honduras lode, on line 9-10, Mineral Survey No. 1715, Excelsior lode, monumented with a wood post, 4x4 ins., 2 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, no marks visible. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.



2011

Deposit the wood post, inverted, alongside stainless steel post.


S. 31°34'10" W. on line 5-6, Mineral Survey No. 2110, Honduras lode.

2.332

Cor. No. 6, Mineral Survey No. 2110, Honduras lode, monumented with a wood post, 4x4 ins., 2 ft. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. H 6 2110.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.



2011

Deposit the mkd. wood post, inverted, alongside stainless steel post.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 2110,  
TPS. 24 S., RS. 57 AND 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS


3.391

Thence N. 70°09'00" W. on line 6-7, Mineral Survey No. 2110, Honduras lode.

Cor. No. 7, Mineral Survey No. 2110, Honduras lode, on line 1-2, Mineral Survey No. 1943, Mary Anna lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, no marks visible. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.




2011

Deposit the wood post, inverted, alongside stainless steel post.

## Bellevue lode


From the point for Cor. No. 2, Mineral Survey No. 2110, Bellevue lode, identical with Cor. No. 8, Mineral Survey No. 2110, Empire lode, on line 1-2, Mineral Survey No. 1981, Yellow Jacket lode, determined by grant boundary adjustment bet. Cor. No. 1, Mineral Survey No. 2110, Bellevue lode, identical with Cor. No. 1, Mineral Survey No. 2110, Empire lode, and Cor. No. 3, Mineral Survey No. 2110, Bellevue lode; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



2010


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 2110,  
TPS. 24 S., RS. 57 AND 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this corner, Cor. No. 1, Mineral Survey No. 2110, Bellevue lode, identical with Cor. No. 1, Mineral Survey No. 2110, Empire lode, bears N. 50°51'40" E., 8.968 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of a portion of Mineral Survey No. 2110, executed under Group No. 887, and a wood post, 4 ins. square firmly set alongside.</p> <p>Thence N. 30°34'40" E., on line 2-3, Mineral Survey No. 2110, Bellevue lode.</p> <p>2.684 Cor. No. 3, Mineral Survey No. 2110, Bellevue lode, monumented with a partially burnt wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 5 ft. diam., 2 1/2 ft. high, with illegible markings. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>MS 2110 3 BE</p> <p>2010</p> </div> <p>Deposit the wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Thence N. 39°39'40" W., on line 3-4, Mineral Survey No. 2110, Bellevue lode.</p> <p>0.219 Intersect the line bet. secs. 24 and 25, at a point from which the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described, bears N. 84°49'00" E., 3.996 chs. dist.</p> <p>3.05 Wash, 45 lks. wide, drains W.</p> <p>8.50 Dirt road, 15 lks. wide, bears SSE. and NNW., in wash, 1 ch. wide, drains NNW.</p> <p>11.864 Cor. No. 4, Mineral Survey No. 2110, Bellevue lode, monumented with the remains of a wood post lying within a mound of stone, 2 1/2 ft. diam., 1 ft. high. This evidence correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p>
--------	--

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 2110,  
TPS. 24 S., RS. 57 AND 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.



Deposit the remains of the wood post alongside the stainless steel post.

Thence N. 35°37'10" W., on line 4-5, Mineral Survey No. 2110, Bellevue lode.

1.40 Enter wash, drains WNW.


5.60 Dirt road, 15 lks. wide, bears ESE. and WNW.

6.60 Exit wash.

9.952 Cor. No. 5, Mineral Survey No. 2110, Bellevue lode, monumented with a wood post, 4x4 ins., 2 ft. long, firmly set in a mound of stone, 5 ft. diam., 2 ft. high, with illegible markings. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.



Deposit the wood post, inverted, alongside the stainless steel post.

Thence N. 50°46'10" E., on line 5-6, Mineral Survey No. 2110, Bellevue lode.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 2110,  
TPS. 24 S., RS. 57 AND 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS  
6.490

Cor. No. 6, Mineral Survey No. 2110, Bellevue lode, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 2010-2021 dependent resurvey of a portion of Mineral Survey No. 2110, executed under Group No. 887.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 3470,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA


Reestablishment of a Portion of the Survey Executed by  
U.S. Mineral Surveyor A.D. Knowlton in 1909

Mobile lode

From Cor. No. 2, Mineral Survey No. 3470, Mobile lode, on line 3-4, Mineral Survey No. 2044, Copper Chief lode, determined at the center of a mound of stone, 3 ft. diam., 1 ft. high, with a wood post, 4x4 ins., 3 ft. long, lying loose alongside, mkd. 2 3470. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Thence N. 12°42'50" E., on line 2-3, Mineral Survey No. 3470, Mobile lode.

1.00 Top of ridge, bears E. and W.

6.929 Cor. No. 3, Mineral Survey No. 3470, Mobile lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. 3470.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 3470,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.

T24S  
R57E  
S35  
3  
MS  
3470  
MO

2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Thence S. 75°51'30" E., on line 3-4, Mineral Survey No. 3470, Mobile lode.

10.399

Witness cor. to Cor. No. 4, Mineral Survey No. 3470, Mobile lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, with illegible markings. This is accepted as the best available evidence of the position of the original witness corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

WC  
T24S R57E  
S35  
3470 4  
MO

2011

Deposit the wood post, inverted, alongside the stainless steel post.

Thence S. 75°51'30" E., beginning new measurement.

0.20

Ridge, bears NE. and SW.

12.454



True point for Cor. No. 4, Mineral Survey No. 3470, Mobile lode, determined at record distance from the witness cor. to Cor. No. 4, Mineral Survey No. 3470, Mobile lode on the extension from Cor. No. 3, Mineral Survey No. 3470, Mobile lode.



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 3470,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Point located in extremely adverse terrain.</p> <p>POINT NOT MONUMENTED</p> <hr/> <p>Thence S. 11°42'40" W., on line 4-1, Mineral Survey No. 3470, Mobile lode.</p> <p>6.083 True point for Cor. No. 1, Mineral Survey No. 3470, Mobile lode, determined at record bearing and distance from the witness cor. to Cor. No. 1, Mineral Survey No. 3470, Mobile lode, identical with Cor. No. 4, Mineral Survey No. 2044, Copper Chief lode, hereinbefore described.</p> <p>Point located in extremely adverse terrain.</p> <p>POINT NOT MONUMENTED</p> <hr/> <p>Thence N. 76°20'00' W., on a portion of line 1-2, Mineral Survey No. 3470, Mobile lode.</p> <p>13.788 Witness cor. to Cor. No. 1, Mineral Survey No. 3470, Mobile lode, identical with Cor. No. 4, Mineral Survey No. 2044, Copper Chief lode, hereinbefore described.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 3575, T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Mineral Surveyor A.D. Knowlton in 1908</p> <hr/> <p>Lookout lode</p> <p>From Cor. No. 6, Mineral Survey No. 3575, Lookout lode, monumented with a wood post, 4x4 ins., 2 1/2 ft. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. 3575.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="844 1492 1055 1737"> <p>MS1943</p> <p>M A</p> <p>2011</p> </div> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 3575,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence S. 39°45'40" E., on line 6-1, Mineral Survey No. 3575, Lookout lode.
2.918	Intersect line 5-1, Mineral Survey No. 1943, Mary Anna lode, at a point from which Cor. No. 1, hereinbefore described, bears N. 72°14'00" E., 4.271 chs. dist.
4.538	Cor. No. 1, Mineral Survey No. 3575, Lookout lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 1-3575.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	
	Deposit the mkd. wood post, inverted, alongside the stainless steel post.
	Thence S. 49°58'00" W., on line 1-2 Mineral Survey No. 3575, Lookout lode.
6.110	Cor. No. 2, Mineral Survey No. 3575, Lookout lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 1/2 ft. high, mkd. 2 3575.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	
	Deposit the mkd. wood post, inverted, alongside the stainless steel post.
	Thence S. 50°06'20" W., on line 2-3, Mineral Survey No. 3575, Lookout lode.
6.70	Top of ridge, bears N. and S.


DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 3575,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS  
16.665

Cor. No. 3, Mineral Survey No. 3575, Lookout lode, determined at the center of a mound of stone, 3 ft. diam., 1/2 ft. high, with a wood post, 4x4 ins., 3 ft. long, lying loose, 15 lks. downhill, with illegible marks. This mound correlates well with evidence on the ground and other found corners, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



Deposit the wood post, inverted, alongside the stainless steel post.


Thence N. 39°49'10" W. on line 3-4, Mineral Survey No. 3575, Lookout lode.

9.041

Witness cor. to Cor. No. 4, Mineral Survey No. 3575, Lookout lode, monumented with the remains of a wood post lying within a mound of stone, 3 ft. diam., 2 ft. high. This evidence correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.



Deposit the remains of the wood post alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 3575,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Thence N. 39°49'10" W., beginning new measurement.
0.056	<p>True point for Cor. No. 4, Mineral Survey No. 3575, Lookout lode determined at record distance from the witness cor. to Cor. No. 4, Mineral Survey No. 3575, Lookout lode on the extension from Cor. No. 3, Mineral Survey No. 3575, Lookout lode.</p> <p>Falls on rock ledge where it is impracticable to set a permanent monument.</p> <p>POINT NOT MONUMENTED.</p>
	<p>Thence N. 50°46'00" E., on line 4-5, Mineral Survey No. 3575, Lookout lode.</p>
4.544	Intersect line 5-1, Mineral Survey No. 1943, Mary Anna lode, at a point from which Cor. No. 5, hereinbefore described, bears S. 72°14'00" W., 0.039 chs. dist.
16.679	<p>Cor. No. 5, Mineral Survey No. 3575, Lookout lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. 5 3575.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<div data-bbox="852 1118 1055 1326"> <p>MS 1943 M A</p> <p>5 MS 3575 LO</p> <p>2011</p> </div> <p>Deposit the mkd. wood post, inverted, alongside stainless steel post.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 3585,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Reestablishment of the Survey Executed by  
U.S. Mineral Surveyor A.D. Knowlton in 1908

Little Joker lode

From Cor. No. 1, Mineral Survey No. 3585, Little Joker lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 5 ft. diam., 2 ft. high, with no marks visible. This evidence correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

2010

Deposit the wood post, inverted, alongside the stainless steel post.

Thence S. 22°42'20" W., on line 1-2, Mineral Survey No. 3585, Little Joker lode.

0.10 Enter wash, drains NW.

1.60 Dirt road, 15 lks. wide, bears SE. and NW.

5.60 Exit wash.

9.674 Cor. No. 2, Mineral Survey No. 3585, Little Joker lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 4 ft. diam., 3 ft. high, mkd. 2-3585.  
At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 1/2 ft. base, to top, with brass cap mkd.

2010

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 3585,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Thence N. 47°18'00" W., on line 2-3, Mineral Survey No. 3585, Little Joker lode.</p>
12.40	Enter wash, drains W.
18.70	Dirt road, 15 lks. wide, bears E. and W.
22.50	Exit wash.
22.741	<p>Cor. No. 3, Mineral Survey No. 3585, Little Joker lode, monumented with the remains of a wood post lying loose within a mound of stone, 5 ft. diam., 2 1/2 ft. high. This evidence correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R57E S24</p> <p>MS 3585 3 L J</p> </div> <p>2010</p> <p>Deposit the remains of the wood post alongside the stainless steel post.</p> <hr/> <p>Thence N. 22°43'20" E., on line 3-4, Mineral Survey No. 3585, Little Joker lode.</p>
9.667	<p>Cor. No. 4, Mineral Survey No. 3585, Little Joker lode, monumented with the remains of a wood post lying loose within a mound of stone, 4 ft. diam., 3 ft. high. This evidence correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 3585,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T24S R57E  
S24  
4  
MS  
3585  
L J

2010

Deposit the remains of the wood post alongside the stainless steel post.

Thence S. 47°18'40" E., on line 4-1, Mineral Survey No. 3585, Little Joker lode.

18.00 Enter wash, drains NW.

22.40 Exit wash.

22.736 Cor. No. 1, Mineral Survey No. 3585, Little Joker lode and point of beginning.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4365,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of Portions of the Survey Executed by  
U.S. Mineral Surveyor A.H. Black in 1918

Chances lode

From Cor. No. 2, Mineral Survey No. 4365, Chances lode, identical with Cor. No. 3, Mineral Survey No. 4365, Highline lode, on line 4-1, Mineral Survey No. 4365, Red Streak lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 2 1/2 ft. diam., 2 ft. high, mkd. 4365.


At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.

MS  
4365 MS  
HI 3 4365  
R S  
MS 2  
4365  
CS

2011

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4365,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA



CHAINS	
	<p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <p>Cor. is located 50 lks. N. of ridge, bears SE. and NW.</p> <p>Thence S. <math>35^{\circ}08'10''</math> E., on line 2-3, Mineral Survey No. 4365, Chances lode.</p>
1.25	Ridge, bears SE. and NW.
2.293	Intersect line 3-4, Mineral Survey No. 4365, Red Streak lode, at a point from which Cor. No. 4, bears N. $80^{\circ}32'50''$ W., 1.361 chs. dist.
4.00	Head of gulch, drains SSW.
4.724	Intersect the northerly side line of Eagle lode (unsurveyed), at a point from which the N. Side Center Cor. of Eagle lode (unsurveyed), bears N. $87^{\circ}55'10''$ E., 0.402 chs. dist.
5.071	<p>Cor. No. 3, Mineral Survey No. 4365, Chances lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, mkd. CS 3 4365.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>2011</p> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. <math>79^{\circ}53'10''</math> W., on line 3-4, Mineral Survey No. 4365, Chances lode.</p>
1.65	Gulch, 30 lks. wide, drains SSW.
7.709	The intersection of the westerly end line of Eagle lode (unsurveyed), and line 3-4, Mineral Survey No. 4365, Chances lode.
8.60	Spur, slopes SW.
14.679	Cor. No. 4, Mineral Survey No. 4365, Chances lode, identical with Cor. No. 3, Mineral Survey No. 4365, Chance lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. C 4365, with other illegible marks.



DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4365,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="868 445 1079 694"> </div> <p>2011</p> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Red Streak lode</p> <p>From Cor. No. 2, Mineral Survey No. 4365, Chances lode, identical with Cor. No. 3, Mineral Survey No. 4365, Highline lode, on line 4-1, Mineral Survey No. 4365, Red Streak lode.</p> <p>Thence N. 0°39'30" E., on a portion of line 4-1, Mineral Survey No. 4365, Red Streak lode, identical in part with line 2-3, Mineral Survey No. 4365, Highline lode.</p> <p>9.083 Cor. No. 2, Mineral Survey No. 4365, Highline lode.</p> <p>Continue measurement on line 4-1, Mineral Survey No. 4365, Red Streak lode.</p> <p>9.25 Gulch, 20 lks. wide, drains NE.</p> <p>13.70 Spur, slopes NE.</p> <p>16.90 Gulch, 25 lks. wide, drains NE.</p> <p>20.322 Cor. No. 1, Mineral Survey No. 4365, Red Streak lode, monumented with a wood post, 4x4 ins., 2 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, mkd. RS-1-4365.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4365,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="852 271 1068 445"> <p>T24S R57E</p>  </div> <p>2011</p> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Thence S. 80°38'10" E., on line 1-2, Mineral Survey No. 4365, Red Streak lode.</p>
0.75	Gulch, 25 lks. wide, drains NE.
8.20	Gulch, 40 lks. wide, drains N.
9.244	<p>Cor. No. 2, Mineral Survey No. 4365, Red Streak lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 1/2 ft. high, mkd. 4365.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="852 1120 1052 1295"> <p>T24S R57E</p>  </div> <p>2011</p> <p>Deposit the wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Thence S. 0°36'50" W., on line 2-3, Mineral Survey No. 4365, Red Streak lode.</p>
1.75	Gulch, 25 lks. wide, drains NW.
4.10	Gulch, 25 lks. wide, drains NW.
12.922	<p>Intersect the side line common to the Copper Side lode (unsurveyed) and the Oversight lode (unsurveyed), from which a Cor. common to the Copper Side lode (unsurveyed), and the Oversight lode (unsurveyed), bears N. 88°35'20" E., 21.578 chs. dist.</p>
21.60	Crest of ridge, bears SE. and NW.


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4365,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS  
21.992

Cor. No. 3, Mineral Survey No. 4365, Red Streak lode, identical with the S.W. Cor. of Copper Side lode (unsurveyed), monumented with a wood post, 4x4 ins., 1 1/2 ft. long, firmly set in a mound of stone, 5 ft. diam., 4 ft. high, mkd. RS 3.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.



2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.


Thence N. 80°32'50" W., on line 3-4, Mineral Survey No. 4365, Red Streak lode.

7.908 Intersect line 2-3, Mineral Survey No. 4365, Chances lode, at a point from which Cor. No. 2, identical with Cor. No. 3, Mineral Survey No. 4365, Highline lode, on line 4-1, Mineral Survey No. 4365, Red Streak lode, bears N. 35°08'10" W., 2.293 chs. dist.

9.269 Cor. No. 4, Mineral Survey No. 4365, Red Streak lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 4 ft. diam., 3 ft. high, mkd. RS 4 4365.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4365,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Highline lode</p> <p>From Cor. No. 1, Mineral Survey No. 4365, Chances lode, on line 2-3, Mineral Survey No. 4365, Chance lode, and on line 3-4, Mineral Survey No. 4365, Highline lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. 4365.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="841 665 1114 899" data-label="Diagram"> </div> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <p>Thence N. 87°18'20" W., on a portion of line 3-4, Mineral Survey No. 4365, Highline lode.</p>
0.30	Spur, slopes SW.
1.088	Intersect line 1-2, Mineral Survey No. 4365, Chance lode, at a point from which Cor. No. 2, bears N. 58°17'40" E., 0.888 chs. dist.
5.688	<p>Cor. No. 4, Mineral Survey No. 4365, Highline lode, monumented with a wood post, 4x4 ins., 2 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. 4 4365.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="889 1529 1052 1678" data-label="Diagram"> </div> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4365,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence N. 0°43'40" E., on line 4-1, Mineral Survey No. 4365, Highline lode.
1.80	Gulch, 40 lks. wide, drains W.
4.00	Spur, slopes W.
6.80	Gulch, 30 lks. wide, drains W.
9.066	Cor. No. 1, Mineral Survey No. 4365, Highline lode, identical with the S.W. Cor. North Side lode (unsurveyed), monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 3 ft. high, mkd. HL 1 4365 NS X.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T24S R57E</p> <div style="text-align: center;"> </div> <p style="text-align: center;">2011</p>
	Deposit the mkd. wood post, inverted, alongside the stainless steel post.
	Thence S. 88°52'00" E., on line 1-2, Mineral Survey No. 4365, Highline lode.
4.60	Spur, slopes NW.
9.80	Gulch, 75 lks. wide, drains NW.
18.20	Top of ridge, bears N. and S.
21.95	Gulch, 20 lks. wide, drains NE.
22.096	Point for Cor. No. 2, Mineral Survey No. 4365, Highline lode, identical with the S.E. Cor. North Side lode (unsurveyed), on line 4-1, Mineral Survey No. 4365, Red Streak lode, determined at proportionate distance on line 4-1, Mineral Survey No. 4365, Red Streak lode; there is no remaining evidence of the original corner. Falls on rock face where it is impracticable to set a permanent monument.
	from which
	A chiseled X followed by the letters BO on the NE. face of a limestone outcrop, bears S. 22°16' W., 20.9 lks. dist.


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4365,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

A chiseled X followed by the letters BO on the SE.  
face of a limestone outcrop, bears N.  $58^{\circ}34'$  W., 47.9  
lks. dist.

From the true point, a point selected for a witness corner to  
Cor. No. 2, Mineral Survey No. 4365, Highline lode, on line 4-1,  
Mineral Survey No. 4365, Red Streak lode, bears N.  $13^{\circ}47'00''$  W.,  
0.008 chs. dist.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in drill  
hole at the base of a limestone face, encased in concrete, with  
top mkd.



## Chance lode

From Cor. No. 3, Mineral Survey No. 4365, Chance lode, identical  
with Cor. No. 4, Mineral Survey No. 4365, Chances lode.

Thence S.  $58^{\circ}24'00''$  W., on line 3-4, Mineral Survey No. 4365,  
Chance lode.


1.00 Gulch, 25 lks. wide, drains W.

21.80 Gulch, 30 lks. wide, drains SW.

22.738 Cor. No. 4, Mineral Survey No. 4365, Chance lode, monumented  
with a wood post, 4x4 ins., 2 1/2 ft. long, firmly set in a  
mound of stone, 3 ft. diam., 2 ft. high, mkd. C 4 4365.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
18 ins. in the ground, over a plastic-encased magnet, and in a  
mound of earth and stone, 3 ft. base, to top, with brass cap  
mkd.




DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4365,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Deposit the mkd. wood post, inverted, alongside stainless steel post.
	<hr/> <p>Thence N. 35°13'50" W., on line 4-1, Mineral Survey No. 4365, Chance lode.</p>
0.50	Gulch, 30 lks. wide, drains SW.
2.00	Gulch, 60 lks. wide, drains SW.
9.039	<p>Cor. No. 1, Mineral Survey No. 4365, Chance lode, monumented with a wood post, 4x4 ins., 2 1/2 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. C 1 4365.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
	<div data-bbox="833 851 1050 1009" data-label="Diagram"> </div> <p>2011</p> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <p>Cor. is located in gulch, 50 lks. wide, drains SW.</p> <hr/> <p>Thence N. 58°17'40" E. on line 1-2, Mineral Survey No. 4365, Chance lode.</p>
21.868	Intersect line 3-4, Mineral Survey No. 4365, Highline lode, at a point from which Cor. No. 1, Mineral Survey No. 4365, Chances lode, bears S. 87°18'20" E., 1.088 chs. dist.
22.756	<p>Cor. No. 2, Mineral Survey No. 4365, Chance lode, monumented with the remains of a wood post lying loose within a mound of stone, 3 ft. diam., 2 ft. high. This evidence correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4365,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

MS  
4365 HI



2011

Deposit the remains of the wood post alongside stainless steel post.

Eagle lode (unsurveyed)

From the intersection of the northerly side line of Eagle lode (unsurveyed) and line 2-3, Mineral Survey No. 4365, Chances lode.

From this point, the N. Side Center Cor. of Eagle lode (unsurveyed), bears N.  $87^{\circ}55'10''$  E., 0.402 chs. dist., determined at the center of a mound of stone, 3 ft. diam., 2 ft. high. This is accepted as the best available evidence of the position of the claim corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.

EAGLE

2011

From this same point, Cor. No. 3, Mineral Survey No. 4365, Chances lode, bears S.  $35^{\circ}08'10''$  E., 0.347 chs. dist.

Thence S.  $87^{\circ}55'10''$  W., on a portion of the northerly side line of Eagle lode (unsurveyed).

7.365

The N.W. Cor. of Eagle lode (unsurveyed), determined at the center of a mound of stone, 2 1/2 ft. diam., 2 ft. high. This is accepted as the best available evidence of the position of the claim corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 5 ft. base, to top, with brass cap mkd.





DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4365,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS					
	EAGLE				
	2011				
	<p>Thence S. 1°12'00" W., on a portion of the westerly end line of Eagle lode (unsurveyed).</p>				
1.370	<p>Point for the intersection of the westerly end line of Eagle lode (unsurveyed), and line 3-4, Mineral Survey No. 4365, Chances lode, determined at proportionate dist. on line 3-4, Mineral Survey No. 4365, Chances lode.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in drill hole in S. facing limestone rock, with top mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>MS4365</td><td>T24S</td></tr> <tr> <td>CS</td><td>R57E</td></tr> </table> <p>S26</p> <p>2022</p> </div> <p>From this point, Cor. No. 4, Mineral Survey No. 4365, Chances lode, identical with Cor. No. 3, Mineral Survey No. 4365, Chance lode, bears S. 79°53'10" W., 6.970 chs. dist.</p>	MS4365	T24S	CS	R57E
MS4365	T24S				
CS	R57E				
	Copper Side lode (unsurveyed)				
	<p>From the intersection of the side line common to the Copper Side lode (unsurveyed), and the Oversight lode (unsurveyed), and line 2-3, Mineral Survey No. 4365, Red Streak lode.</p>				
	<p>From this point, a Cor. common to the Copper Side lode (unsurveyed), and the Oversight lode, (unsurveyed), bears N. 88°35'20" E., 21.578 chs. dist., determined at the center of a mound of stone, 5 ft. diam., 3 ft. high, with the remains of a 4x4 wood post, 21 ins. long, split in two, with the marks UU visible on one of the pieces. This is accepted as the best available evidence to the position of the claim corner.</p>				
	At the corner point				
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 5 ft. base, to top, with brass cap mkd.</p>				
	<div style="text-align: center;"> <p>COPPER SIDE</p> </div>				
	2022				
	<p>Deposit the remains of the mkd. wood post alongside the stainless steel post.</p>				

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4365,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same point, Cor. No. 3, Mineral Survey No. 4365, Red Streak lode, identical with the S.W. Cor. of Copper Side lode (unsurveyed), bears S. 0°36'50" W., 9.070 chs. dist.</p> <p>Thence S. 88°35'20" W., on a portion of the side line common to the Copper Side lode (unsurveyed), and the Oversight lode (unsurveyed).</p> <p>1.114 A Cor. common to the Copper Side lode (unsurveyed), and the Oversight lode (unsurveyed), monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 2 1/2 ft. diam., 2 ft. high, mkd. CSx4.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">COPPER SIDE</p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. wood post alongside stainless steel post.</p> <hr/> <p>Thence S. 6°24'50" E., on a portion of the westerly end line of Copper Side lode (unsurveyed).</p> <p>9.099 Cor. No. 3, Mineral Survey No. 4365, Red Streak lode, identical with the S.W. Cor. of Copper Side lode (unsurveyed).</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4366, T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor A.H. Black in 1918</p> <hr/> <p style="text-align: center;">Eureka lode</p> <p>From Cor. No. 1, Mineral Survey No. 4366, Eureka lode, determined at the center of a mound of stone, 3 ft. diam., 1 ft. high, with a wood post, 4x4 ins., 4 ft. long, lying loose, 15 lks. downhill, mkd. 1-4366. This evidence correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4366,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	 <p>MS4366 EU 1 T24S R57E S25</p> <p>2011</p> <p>Deposit the mkd. wood post alongside the stainless steel post.</p> <p>Thence S. 68°53'50" W., on line 1-2, Mineral Survey No. 4366, Eureka lode.</p>
4.80	Gulch, 50 lks. wide, drains SE.
8.20	Gulch, 30 lks. wide, drains SE.
9.368	<p>Cor. No. 2, Mineral Survey No. 4366, Eureka lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, mkd. 2-4366.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
	 <p>MS4366 EU 2 T24S R57E S25</p> <p>2011</p> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Thence N. 28°59'10" W., on line 2-3, Mineral Survey No. 4366, Eureka lode.</p>
22.462	<p>Cor. No. 3, Mineral Survey No. 4366, Eureka lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. 3-4366.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4366,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

T24S R57E

S25

3

MS4366

EU

2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Thence N.  $70^{\circ}14'00''$  E., on line 3-4, Mineral Survey No. 4366, Eureka lode.

4.40 Gulch, 25 lks. wide, drains SE.

9.291 Cor. No. 4, Mineral Survey No. 4366, Eureka lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. 4-4366.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T24S R57E

S25

4

MS4366

EU

2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Thence S.  $29^{\circ}15'50''$  E., on line 4-1, Mineral Survey No. 4366, Eureka lode.

22.258 Cor. No. 1, Mineral Survey No. 4366, Eureka lode and point of beginning.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4371 A,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS


Reestablishment of a Portion of the Survey Executed by  
U.S. Mineral Surveyor A.H. Black in 1918

## Boss lode

From Cor. No. 1, Mineral Survey No. 4371 A, Boss lode, identical with Cor. No. 1, Mineral Survey No. 4371 A, Manse lode, identical with a north side angle Cor. of Rosella lode (unsurveyed), monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 5 ft. diam., 3 1/2 ft. high, mkd. B-1-4371 A M-1-4371 A.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 5 ft. base, to top, with brass cap mkd.



2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Thence S. 55°50'20" W., on line 1-2, Mineral Survey No. 4371 A, Boss lode.

- 0.15 Gulch, 25 lks. wide, drains NW.
- 2.35 Gulch, 40 lks. wide, drains NW.
- 6.00 Top of ridge, bears SE. and NW.
- 9.678 Intersect the line bet. secs. 27 and 34, at a point from which the cor. of secs. 26, 27, 34 and 35, hereinbefore described, bears S. 89°14'30" E., 14.207 chs. dist.
- 20.60 Gulch, 30 lks. wide, drains NW.
- 22.740 Cor. No. 2, Mineral Survey No. 4371 A, Boss lode, identical with Cor. No. 3, cancelled Mineral Survey No. 4330, Boss Extension lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 4 ft. diam., 3 1/2 ft. high, mkd. B-2-4371 A.


At the corner point

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4371 A,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="852 404 1096 590"> </div> <p>2011</p> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Thence N. 34°04'50" W., on a portion of line 2-3, Mineral Survey No. 4371 A, Boss lode.</p> <p>2.90 Gulch, 30 lks. wide, drains NW.</p> <p>4.421 Cor. No. 1, Mineral Survey No. 4371 A, Boss No.2 lode, identical with Cor. No. 5, cancelled Mineral Survey No. 4330, Saturday lode.</p> <hr/> <p>From Cor. No. 1, Mineral Survey No. 4371 A, Boss No.3 lode, on line 3-4, Mineral Survey No. 4371 A, Boss lode, identical with the S.W. Cor. of Sandy No.1 lode (unsurveyed).</p> <p>Thence N. 55°49'10" E., on a portion of line 3-4, Mineral Survey No. 4371 A, Boss lode.</p> <p>7.50 Gulch, 25 lks. wide, drains NW.</p> <p>8.45 Gulch, 30 lks. wide, drains NW.</p> <p>9.561 Cor. No. 4, Mineral Survey No. 4371 A, Boss lode, identical with Cor. No. 2, Mineral Survey No. 4371 A, Manse lode and the south side angle Cor. of Sandy No.1 lode (unsurveyed), monumented with a wood post, 4x4 ins., 2 ft. long, firmly set in a mound of stone, 4 ft. diam., 3 ft. high, mkd. M-2-4371 A.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 1/2 ft. base, to top, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4371 A,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



2011


Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Boss No. 2 lode

From Cor. No. 1, Mineral Survey No. 4371 A, Boss No. 2 lode, identical with Cor. No. 5, cancelled Mineral Survey No. 4330, Saturday lode, on line 2-3, Mineral Survey No. 4371 A, Boss lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, with illegible markings. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.



2011

Deposit the wood post, inverted, alongside the stainless steel post.

Thence S. 28°03'30" W., on line 1-2, Mineral Survey No. 4371 A, Boss No. 2 lode.

0.80 Gulch, 30 lks. wide, drains W.

5.20 Gulch, 25 lks. wide, drains W.

9.90 Gulch, 60 lks. wide, drains W.

22.738 Cor. No. 2, Mineral Survey No. 4371 A, Boss No. 2 lode, identical with the N.E. Cor. of Wallace lode (unsurveyed) and the West side angle Cor. of Bruce lode (unsurveyed), monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, mkd. BNO2-2-4371 A.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4371 A,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="828 455 1071 694" data-label="Diagram"> </div> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p>
<p>2.90</p> <p>7.25</p> <p>8.00</p> <p>9.673</p>	<p>Thence N. 34°04'20" W., on line 2-3, Mineral Survey No. 4371 A, Boss No.2 lode.</p> <p>Spur, slopes SW.</p> <p>Enter wash, drains SW.</p> <p>Dirt road, 15 lks. wide, bears NE. and SW.</p> <p>Cor. No. 3, Mineral Survey No. 4371 A, Boss No.2 lode, identical with the N.W. Cor. of Wallace lode (unsurveyed), the N.E. Cor. of McAlpine lode (unsurveyed) and the S.E. Cor. of Scott lode (unsurveyed), determined at the center of a mound of stone, 3 ft. diam., 2 ft. high. This mound correlates well with other found evidence and is accepted as the best available evidence of the position of the original corner.</p>
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="836 1471 1071 1667" data-label="Diagram"> </div>
<p>4.60</p>	<p>Thence N. 28°04'50" E., on a portion of line 3-4, Mineral Survey No. 4371 A, Boss No.2 lode.</p> <p>Toe of mine tailings, enter mine area.</p>



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4371 A,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS  
12.423

Cor. No. 3, Mineral Survey No. 4371 A, Boss No.3 lode, identical with the N.E. Cor. of Scott lode (unsurveyed).

Boss No.3 lode

From the point for Cor. No. 3, Mineral Survey No. 4371 A, Boss No.3 lode, identical with the N.E. Cor. of Scott lode (unsurveyed), on line 3-4, Mineral Survey No. 4371 A, Boss No.2 lode, determined by grant boundary adjustment bet. Cor. No. 4, Mineral Survey No. 4371 A, Campo lode and Cor. No. 3, Mineral Survey No. 4371 A, Boss No.2 lode, identical with the N.W. Cor. of Wallace lode (unsurveyed), the N.E. Cor. of McAlpine lode (unsurveyed), and the S.E. Cor. of Scott lode (unsurveyed); there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.




2011

Thence N. 24°33'10" W., on line 3-4, Mineral Survey No. 4371 A, Boss No.3 lode.

5.615 Intersect the line bet. secs. 27 and 34, at a point from which the 1/4 sec. cor. of secs. 27 and 34, hereinbefore described, bears N. 89°14'30" W., 1.279 chs. dist.

5.635 Point for Cor. No. 4, Mineral Survey No. 4371 A, Boss No.3 lode, identical with Cor. No. 2, Mineral Survey No. 4371 A, Campo lode, determined at proportionate dist.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.



2011


DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4371 A,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

From Cor. No. 5, Mineral Survey No. 4371 A, Boss No.3 lode, identical with Cor. No. 1, Mineral Survey No. 4371 A, Campo lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, with illegible markings. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.



2011

Deposit the wood post, inverted, alongside the stainless steel post.

Thence S. 24°31'50" E., on line 5-1, Mineral Survey No. 4371 A, Boss No.3 lode.


0.25 Dirt road, 12 lks. wide, bears E. and W., in gulch 25 lks. wide, drains W.

3.15 Dirt road, 12 lks. wide, bears N. and S.

7.780 Cor. No. 1, Mineral Survey No. 4371 A, Boss No.3 lode, identical with the S.W. Cor. of Sandy No.1 lode (unsurveyed), on line 3-4, Mineral Survey No. 4371 A, Boss lode, monumented with a wood post, 4x4 ins., 2 ft. long, firmly set in a mound of stone, 4 ft. diam., 3 ft. high, mkd. B 1-4371 A.


At the corner point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in drill hole in limestone face, encased in concrete, with top mkd.



2011

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4371 A,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Leave the mkd. wood post lying loose alongside the brass tablet.
	<p style="text-align: center;">Campo lode</p>
	<p>From Cor. No. 2, Mineral Survey No. 4371 A, Campo lode, identical with Cor. No. 4, Mineral Survey No. 4371 A, Boss No.3 lode.</p>
	<p>Thence N. 24°33'10" W., on line 2-3, Mineral Survey No. 4371 A, Campo lode.</p>
9.063	<p>Point for Cor. No. 3, Mineral Survey No. 4371 A, Campo lode, determined by grant boundary adjustment bet. Cor. No. 4, Mineral Survey No. 4371 A, Campo lode and Cor. No. 3, Mineral Survey No. 4371 A, Boss No.2 lode, identical with the N.W. Cor. of Wallace lode (unsurveyed), the N.E. Cor. of McAlpine lode (unsurveyed) and the S.E. Cor. of Scott lode (unsurveyed); there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div>
	<p>Thence N. 55°52'50" E., on line 3-4, Mineral Survey No. 4371 A, Campo lode.</p>
9.30	Edge of mine area pit; continue along wash, 5 chs. wide, drains SW.
13.30	Dirt road, 12 lks. wide, bears SE. and NW.
21.069	Intersect the west end line of Sandy No.2 lode (unsurveyed), at a point from which the N.W. Cor. of Sandy No.2 lode (unsurveyed), bears N. 37°23'50" W., 3.531 chs. dist.
22.330	<p>Cor. No. 4, Mineral Survey No. 4371 A, Campo lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set 12 ins. in the ground, mkd. 4-4371 A.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4371 A,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	
	<div data-bbox="868 275 1058 416"> </div> <div data-bbox="920 451 982 478">2011</div> <p data-bbox="436 507 1414 561">Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p data-bbox="436 617 1442 671">Thence S. 24°31'50" E., on line 4-1, Mineral Survey No. 4371 A, Campo lode.</p> <p data-bbox="306 698 1105 725">1.20 Dirt road, 12 lks. wide, bears NE. and SW.</p> <p data-bbox="306 752 610 779">2.10 Leave wash.</p> <p data-bbox="306 806 691 832">5.40 Spur, slopes SW.</p> <p data-bbox="306 859 1365 913">5.652 The S.W. Cor. of Sandy No.2 lode (unsurveyed), hereinafter described.</p> <p data-bbox="306 940 1398 994">7.100 Cor. No. 1, Mineral Survey No. 4371 A, Campo lode, identical with Cor. No. 5, Mineral Survey No. 4371 A, Boss No.3 lode.</p> <hr/> <p data-bbox="872 1042 1032 1069">Manse lode</p> <p data-bbox="436 1096 1446 1176">From Cor. No. 2, Mineral Survey No. 4371 A, Manse lode, identical with Cor. No. 4, Mineral Survey No. 4371 A, Boss lode and the south side angle Cor. of Sandy No.1 lode (unsurveyed).</p> <p data-bbox="436 1203 1442 1257">Thence N. 63°10'30" E., on line 2-3, Mineral Survey No. 4371 A, Manse lode.</p> <p data-bbox="306 1284 932 1311">1.20 Gulch, 40 lks. wide, drains NW.</p> <p data-bbox="306 1338 1057 1365">4.80 Head of gulch, 15 lks. wide, drains NW.</p> <p data-bbox="306 1392 932 1419">8.50 Gulch, 15 lks. wide, drains NW.</p> <p data-bbox="306 1446 932 1473">12.20 Gulch, 30 lks. wide, drains NW.</p> <p data-bbox="306 1500 1430 1580">12.754 Intersect the line bet. secs. 26 and 27, at a point from which the cor. of secs. 26, 27, 34 and 35, hereinbefore described, bears S. 0°16'50" W, 18.909 chs. dist.</p> <p data-bbox="306 1607 1463 1688">13.078 Cor. No. 3, Mineral Survey No. 4371 A, Manse lode, monumented with a wood post, 4x4 ins., 2 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 1/2 ft. high, mkd. 4371.</p> <p data-bbox="436 1715 743 1742">At the corner point</p> <p data-bbox="436 1769 1425 1850">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4371 A,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="873 271 1052 505" data-label="Diagram"> <p>T24S R57E S26 3 MS 4371 A MA 2011</p> </div> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Thence S. 85°45'50" E., on line 3-4, Mineral Survey No. 4371 A, Manse lode.</p>
5.65	<p>Gulch, 50 lks. wide, drains NW.</p>
9.143	<p>Cor. No. 4, Mineral Survey No. 4371 A, Manse lode, monumented with a wood post, 4x4 ins., 2 1/2 ft. long, firmly set in a mound of stone, 5 ft. diam., 3 ft. high, mkd. M-4-4371 A.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="873 1073 1052 1307" data-label="Diagram"> <p>T24S R57E S26 4 MS 4371 A MA 2011</p> </div> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <hr/> <p>Thence S. 34°00'10" E., on line 4-5, Mineral Survey No. 4371 A, Manse lode.</p>
8.903	<p>Witness cor. to Cor. No. 5, Mineral Survey No. 4371 A, Manse lode, monumented with the remains of a wood post lying loose within a mound of stone, 4 ft. diam., 3 ft. high. This evidence correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4371 A,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



T24S R57E  
S26

2011

Deposit the remains of the wood post alongside the stainless steel post.

Thence S. 34°00'10" E., beginning new measurement.

0.196 Cor. No. 5, Mineral Survey No. 4371 A, Manse lode, monumented with a drill steel, 1 in. diam., firmly set, projecting 3 ins. above the ground.

Thence N. 85°46'40" W., on line 5-6, Mineral Survey No. 4371 A, Manse lode.


4.70 Gulch, 50 lks. wide, drains NW.

9.00 Gulch, 30 lks. wide, drains NW.

8.607 Witness cor. to Cor. No. 6, Mineral Survey No. 4371 A, Manse lode, identical with the W.C. for a north side angle Cor. of Rosella lode (unsurveyed), monumented with the remains of a wood post lying loose within a mound of stone, 4 ft. diam., 3 ft. high. This evidence correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.



T25S  
R57E  
S26

2011

Deposit the remains of the wood post alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4371 A,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.548	<p>Thence N. 85°46'40" W., beginning new measurement.</p> <p>Cor. No. 6, Mineral Survey No. 4371 A, Manse lode, identical with a north side angle Cor. of Rosella lode (unsurveyed), marked with an X chiseled on an exposed limestone rib.</p> <p>from which</p> <p>A chiseled X followed by the letters BO on an exposed limestone outcrop, bears S. 63°22' W., 16.0 lks. dist.</p>
	<p>Thence S. 63°12'20" W., on line 6-1, Mineral Survey No. 4371 A, Manse lode.</p>
3.40	Gulch, 30 lks. wide, drains NW.
6.067	Intersect the line bet. secs. 26 and 27, at a point from which the cor. of secs. 26, 27, 34 and 35, hereinbefore described, bears S. 0°16'50" W, 8.775 chs. dist.
8.30	Gulch, 30 lks. wide, drains NW.
13.058	Cor. No. 1, Mineral Survey No. 4371 A, Manse lode, identical with Cor. No. 1, Mineral Survey No 4371 A, Boss lode and a north side angle Cor. of Rosella lode (unsurveyed).
	<p>Sandy No.2 lode (unsurveyed)</p> <p>From the S.W. Cor. of Sandy No.2 lode (unsurveyed), identical with the N.W. Cor. of Sandy No.1 lode (unsurveyed), on line 4-1, Mineral Survey No. 4371 A, Campo, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. S NO 2.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="779 1410 1023 1594"> </div> <p>2011</p> <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <p>Thence N. 37°23'50" W., on a portion of the west end line of Sandy No.2 lode (unsurveyed).</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4371 A,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS  
5.582

Intersect line 3-4, Mineral Survey No. 4371 A, Campo lode, at a point from which Cor. No. 4, bears N.  $55^{\circ}52'50''$  E., 1.261 chs. dist.

From this point, the N.W. Cor. of Sandy No.2 lode (unsurveyed), bears N.  $37^{\circ}23'50''$  W., 3.531 chs. dist., monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 2 ft. diam., 2 ft. high, mkd. S NO 2.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.



2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4373,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of a Portion of the Survey Executed by  
U.S. Mineral Surveyor A.H. Black in 1918

---

Oro Amigo No.1 lode

From Cor. No. 3, Mineral Survey No. 4373, Oro Amigo No.1 lode, identical with Cor. No. 4, Mineral Survey No. 4373, Oro Amigo No.3 lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. OA NO1 3/OA NO3 4 4373.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4373,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="792 271 1036 478"> </div> <div data-bbox="922 509 987 534">2011</div> <p data-bbox="435 565 1414 617">Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <p data-bbox="435 644 1409 696">Thence S. 15°23'40" E., on line 3-4, Mineral Survey No. 4373, Oro Amigo No.1 lode.</p>
9.111	<p data-bbox="435 727 1463 882">Cor. No. 4, Mineral Survey No. 4373, Oro Amigo No.1 lode, identical with Cor. No. 5, Mineral Survey No. 4373, Oro Amigo No.4 lode, determined at the center of a mound of stone, 4 ft. diam., 2 ft. high, with a wood post, 4x4 ins., 1 ft. long, lying loose alongside, mkd. OA NO 4. This is accepted as the best available evidence of the position of the original corner.</p> <p data-bbox="435 909 743 934">At the corner point</p> <p data-bbox="435 961 1425 1065">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="824 1089 1084 1328"> </div> <div data-bbox="922 1359 987 1384">2011</div> <p data-bbox="435 1415 1414 1466">Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p>
	<hr/> <p data-bbox="800 1524 1109 1549">Oro Amigo No.2 lode</p> <p data-bbox="435 1576 1430 1628">From Cor. No. 2, Mineral Survey No. 4373, Oro Amigo No.4 lode, on line 4-1, Mineral Survey No. 4373, Oro Amigo No.2 lode.</p> <p data-bbox="435 1655 1463 1707">Thence S. 74°32'20" W., on a portion of line 4-1, Mineral Survey No. 4373, Oro Amigo No.2 lode.</p> <p data-bbox="313 1734 935 1759">8.50 Gulch, 25 lks. wide, drains NW.</p> <p data-bbox="297 1786 919 1810">18.00 Wash, 50 lks. wide, drains NW.</p>

CHAINS  
20.666

At the corner point

	MS
T24S	4373
R57E	O A 2
S23	1

2011

4.50	Dirt road, 15 lks. wide, bears NE. and SW.
------	--

5.80	Wash, 2 chs. wide, drains SW.
------	-------------------------------

9.094 Cor. No. 2, Mineral Survey No. 4373, Oro Amigo No.2 lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. OA 2 4373.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.

T24S MS  
R57E 2 4373  
S23 O A 2

2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Thence N. 74°33'30" E., on a portion of line 2-3, Mineral Survey No. 4373, Oro Amigo No.2 Lode.

5.30	Gulch, 20 lks. wide, drains SW.
------	---------------------------------

20.301	Cor. No. 1, Mineral Survey No. 4373, Oro Amigo No.3 lode.
--------	---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4373,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS

## Oro Amigo No.3 lode

From Cor. No. 1, Mineral Survey No. 4373, Oro Amigo No.3, on line 2-3, Mineral Survey No. 4373, Oro Amigo No.2 lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. OA NO 3 1 4373.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.



2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.


Thence N. 15°22'40" W., on line 1-2, Mineral Survey No. 4373, Oro Amigo No.3 lode.

8.294

Cor. No. 2, Mineral Survey No. 4373, Oro Amigo No.3 lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. OA NO 3 2 4373.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.



2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Thence N. 83°50'20" E., on line 2-3, Mineral Survey No. 4373, Oro Amigo No.3 lode.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4373,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
15.30	Overhead powerline, bears N. 51° E. and S. 51° W.
22.659	Cor. No. 3, Mineral Survey No. 4373, Oro Amigo No.3 lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. OA NO 3 3 4373.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;"> <p>T24S R57E</p> <p>MS 3 S23 4373 O A 3</p> <p>2011</p> </div>
	Deposit the mkd. wood post, inverted, alongside the stainless steel post.
	Thence S. 15°20'30" E., on line 3-4, Mineral Survey No. 4373, Oro Amigo No.3 lode.
0.508	The intersection of the north side line of Jackson lode (unsurveyed), and line 3-4, Mineral Survey No. 4373, Oro Amigo No.3 lode.
8.201	Cor. No. 4, Mineral Survey No. 4373, Oro Amigo No.3 lode, identical with Cor. No. 3, Mineral Survey No. 4373, Oro Amigo No.1 lode.
	Oro Amigo No.4 lode
	From Cor. No. 5, Mineral Survey No. 4373, Oro Amigo No.4 lode, identical with Cor. No. 4, Mineral Survey No. 4373, Oro Amigo No.1 lode.
	Thence S. 15°22'50" E., on line 5-6, Mineral Survey No. 4373, Oro Amigo No.4 lode.
0.177	Intersect the south side line of Nemaha lode (unsurveyed), at a point from which the S.W. Cor. of Nemaha lode (unsurveyed), bears S. 72°37'00" W., 2.866 chs. dist.
5.773	Intersect the west side line of Poppy lode (unsurveyed), at a point from which the N.W. Cor. of Poppy lode (unsurveyed), bears N. 43°01'00" E., 0.081 chs. dist.
8.024	Cor. No. 6, Mineral Survey No. 4373, Oro Amigo No.4 lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. OA NO 4 6 4373.
	At the corner point

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4373,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.

MS  
4373  
O A 4 6

T24S  
R57E  
S23

2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Thence S. 83°21'10" W., on line 6-1, Mineral Survey No. 4373, Oro Amigo No.4 lode.

2.962 Intersect the west side line of Poppy lode (unsurveyed), at a point from which the S.W. Cor. of Poppy lode (unsurveyed), bears S. 43°01'00" W., 16.437 chs. dist.

22.245 Cor. No. 1, Mineral Survey No. 4373, Oro Amigo No.4 lode, monumented with a wood post, 3x6 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. OA NO 4 1 4373.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.

MS  
4373  
1 O A 4

T24S  
R57E  
S23

2011

Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Cor. is located 40 lks. N. of a wash, drains W.

Thence N. 15°26'00" W., on line 1-2, Mineral Survey No. 4373, Oro Amigo No.4 lode.

5.80 Gulch, 20 lks. wide, drains WSW.

8.208 Cor. No. 2, Mineral Survey No. 4373, Oro Amigo No.4 lode, on line 4-1, Mineral Survey No. 4373, Oro Amigo No.2 lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, mkd. 4373.


At the corner point

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4373,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 3 1/2 ft. base, to top, with brass cap mkd.

MS  
4373  
O A 2



2011


Deposit the mkd. wood post, inverted, alongside the stainless steel post.

Jackson lode (unsurveyed)

From the point for the intersection of the north side line of Jackson lode (unsurveyed), and line 3-4, Mineral Survey No. 4373, Oro Amigo No.3 lode, determined at proportionate dist. on line 3-4, Mineral Survey No. 4373, Oro Amigo No.3 lode.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in limestone rib outcropping, 6x1 ft., 1 ft. high, 1 ft. from N. end mkd.

MS4373  
O A 3



2023

From this point, Cor. No. 3, Mineral Survey No. 4373, Oro Amigo No.3 lode, bears N. 15°20'30" W., 0.508 chs. dist.

Thence S. 72°07'50" W., on a portion of the north side line of Jackson lode (unsurveyed).

0.853


The N.W. Cor. of Jackson lode (unsurveyed), determined at the center of a mound of stone, 3 ft. diam., 3 1/2 ft. high. This is accepted as the best available evidence of the position of the claim corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4373,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



MS  
4373  
O A 3

T24S  
R57E  
S23

2011


Thence S. 4°19'20" E., on the west end line of Jackson lode (unsurveyed).

9.152

A corner common to Jackson lode (unsurveyed), and Nemaha lode (unsurveyed), determined at the center of a mound of stone, 2 1/2 ft. diam., 2 ft. high. This is accepted as the best available evidence of the position of the claim corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.



MS  
4373  
O A 1

T24S  
R57E  
S23

2011

Nemaha lode (unsurveyed)

From a corner common to Jackson lode (unsurveyed), and Nemaha lode (unsurveyed).

Thence S. 13°32'20" E., on the west end line of Nemaha lode (unsurveyed).



8.065

The S.W. Cor. of Nemaha lode (unsurveyed), determined at the center of a mound of stone, 4 ft. diam., 5 ft. high. This is accepted as the best available evidence of the position of the claim corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4373,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	
	
2.866	<p>Thence N. 72°37'00" E. (record bearing), on a portion of the south side line of Nemaha lode (unsurveyed).</p> <p>Intersect line 5-6, Mineral Survey No. 4373, Oro Amigo No.4 lode.</p> <hr/> <p>Poppy lode (unsurveyed)</p> <p>From the intersection of the west side line of Poppy lode (unsurveyed), and line 5-6, Mineral Survey No. 4373, Oro Amigo No.4 lode.</p> <p>From this point, the N.W. Cor. of Poppy lode (unsurveyed), bears N. 43°01'00" E., 0.081 chs. dist., monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 4 ft. diam., 3 ft. high, mkd. 4375.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>  <p>Deposit the mkd. wood post, inverted, alongside the stainless steel post.</p> <p>From this same point of intersection, Cor. No. 6, Mineral Survey No. 4373, Oro Amigo No.4 lode, bears S. 15°22'50" E., 2.251 chs. dist.</p> <p>Thence S. 43°01'00" W., on a portion of the west side line of Poppy lode (unsurveyed).</p>
3.437	<p>Intersect line 6-1, Mineral Survey No. 4373, Oro Amigo No.4 lode, at a point from which Cor. No. 6, Mineral Survey No. 4373, Oro Amigo No.4 lode, bears N. 83°21'10" E., 2.962 chs. dist.</p> <p>From this point, the S.W. Cor. of Poppy lode (unsurveyed), bears S. 43°01'00" W., 16.437 chs. dist., monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 4 1/2 ft. diam., 2 ft. high, mkd. 4 4375.</p> <p>At the corner point</p>



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4373,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.



Deposit the mkd. wood post, inverted, alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4546,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by  
U.S. Mineral Surveyor A.H. Black in 1922

Rainbow No.1 lode

From Cor. No. 2, Mineral Survey No. 4546, Rainbow No.1 lode, identical with Cor. No. 4, Mineral Survey No. 4546, Rainbow No.2 lode, monumented with a limestone, 24x8x6 ins., firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. R1-2-4546 on the S. face and R2-4-4546 on the N. face.

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in drill hole in a 6x8 ft. rock face, with top mkd.

MS4546		
RA 2	4	T24S
		R57E
RA 1	2	S 4
MS4546		

2011

Deposit the mkd. stone in mound of stone 3 ft. base, 2 ft. high, N. of cor.

Thence S. 16°31'40" E., on line 2-3, Mineral Survey No. 4546, Rainbow No.1 lode.

20.942

Cor. No. 3, Mineral Survey No. 4546, Rainbow No.1 lode, monumented with a limestone, 18x14x10 ins. (Record, 26x8x8 ins.), firmly set, 14 ins. in the ground, mkd. R1-3-4546 with chiseled X on top, with a mound of stone, 4 ft. diam., 3 ft. high, alongside.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4546,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

MS  
4546  
RA 1 3

T24S  
R57E  
S 4

2011

Deposit the mkd. stone, inverted, alongside the stainless steel post.

Thence S. 73°29'00" W., on line 3-4, Mineral Survey No. 4546, Rainbow No.1 lode.

9.082

Cor. No. 4, Mineral Survey No. 4546, Rainbow No.1 lode, identical with Cor. No. 2, Mineral Survey No. 4546, Rainbow No.3 lode, monumented with a limestone, 20x8x6 ins., firmly set 10 ins. in the ground, mkd. R1-4-4536 R3-2-4546, with a mound of stone, 2 ft. diam., 1 ft. high, alongside.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

MS  
4546  
RA 3  
2

MS  
4546  
RA 1  
4

T24S R57E  
S 4

2011

Deposit the mkd. stone, inverted, alongside the stainless steel post.

Rainbow No.2 lode

From Cor. No. 1, Mineral Survey No. 4546, Rainbow No.2 lode, identical with Cor. No. 1, Mineral Survey No. 4546, Rainbow No.1 lode and Cor. No. 1, Mineral Survey No. 4546, Rainbow No.3 lode, monumented with a limestone, 24x8x6 ins., firmly set in a rock fissure, mkd. R1-1-4546 R2-1-4546 R3-1-4546.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4546,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in rock face, with top mkd.

T24S	MS4546
R57E	RA 2
S 4	1
1	1
RA 3	RA 1
MS4546	MS4546

2011

Deposit the mkd. stone in mound of stone, 3 ft. base, 2 ft. high, NE. of cor.

Thence N. 16°38'10" W., on line 1-2, Mineral Survey No. 4546, Rainbow No.2 lode.

20.749

Cor. No. 2, Mineral Survey No. 4546, Rainbow No.2 lode, monumented with a chiseled X on a limestone rock face, 10x12x15 ft. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in limestone face, with top mkd.

T24S R57E	
S 4	2 RA 2
	MS4546

2011

Thence N. 73°35'30" E., on line 2-3, Mineral Survey No. 4546, Rainbow No.2 lode.

7.622

Witness cor. to Cor. No. 3, Mineral Survey No. 4546, Rainbow No.2 lode, monumented with a chiseled X on a rock in place, 6x6 ft., rising 10 ft. above surrounding ground, mkd. WC-R2-3-4546.


POINT NOT REMONUMENTED

Thence N. 73°35'30" E., beginning new measurement.

1.456

Point for Cor. No. 3, Mineral Survey No. 4546, Rainbow No.2 lode, determined at record distance from the witness cor. to Cor. No. 3, Mineral Survey No. 4546, Rainbow No.2 lode, on the extension from Cor. No. 2, Mineral Survey No. 4546, Rainbow No.2 lode.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4546,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in boulder, with top mkd.</p> <div data-bbox="844 352 1104 528">  <p>T24S R57E S 4 RA 2 MS4546 2011</p> </div> <p>from which</p> <p>A chiseled X followed with the letters BO, mkd. on exposed SE. limestone face, bears N. 78°04' W., 13.6 lks. dist.</p> <p>A chiseled X followed with the letters BO, mkd. on exposed SE. limestone face, bears N. 42°04' W., 23.9 lks. dist.</p> <hr/> <p>Thence S. 16°39'20" E., on line 3-4, Mineral Survey No. 4546, Rainbow No.2 lode.</p> <p>20.717 Cor. No. 4, Mineral Survey No. 4546, Rainbow No.2 lode, identical with Cor. No. 2, Mineral Survey No. 4546, Rainbow No.1 lode.</p> <hr/> <p>Rainbow No.3 lode</p> <p>From Cor. No. 2, Mineral Survey No. 4546, Rainbow No.3 lode, identical with Cor. No. 4, Mineral Survey No. 4546, Rainbow No.1 lode.</p> <p>Thence S. 73°26'10" W., on line 2-3, Mineral Survey No. 4546, Rainbow No.3 lode.</p> <p>3.80 Enter wash, 1 ch. wide, drains W.</p> <p>7.10 Dirt road, 12 lks. wide, bears E. and W.</p> <p>8.078 Point for Cor. No. 3, Mineral Survey No. 4546, Rainbow No.3 lode, determined by grant boundary adjustment bet. Cor. No. 2, Mineral Survey No. 4546, Rainbow No.3 lode, identical with Cor. No. 4, Mineral Survey No. 4546, Rainbow No.1 lode and Cor. No. 4, Mineral Survey No. 4546, Rainbow No.3 lode; there no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of earth and stone, 3 ft. base, to top, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4546,  
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="857 298 1112 389"> <div>T24S MS4546</div> <div>R57E RA 3</div> <div>S 4 3</div> </div> <div data-bbox="922 416 987 443">2011</div>
	<hr/> <p>Thence N. 16°33'50" W., on line 3-4, Mineral Survey No. 4546, Rainbow No.3 lode.</p>
0.20	Dirt road, 12 lks. wide, bears E. and W.
1.00	Exit wash, 1 ch. wide, drains W.
20.937	<p>Cor. No. 4, Mineral Survey No. 4546, Rainbow No.3 lode, monumented with a chiseled X on a rock face, 20x8 ft., with a limestone, 26x10x8 ins., in a mound of stone, 3 ft. diam., 2 ft. high, over the cor., mkd. R3-4-4546.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <div data-bbox="883 955 1084 1085"> <div>T24S R57E</div> <div>S 4 4 RA 3</div> <div>MS4546</div> </div> <div data-bbox="922 1131 987 1158">2011</div>
	<p>Deposit the mkd. stone in a mound of stone, 4 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>Thence N. 73°30'00" E., on line 4-1, Mineral Survey No. 4546, Rainbow No.3 lode.</p>
8.088	<p>Cor. No. 1, Mineral Survey No. 4546, Rainbow No.3 lode, identical with Cor. No. 1, Mineral Survey No. 4546, Rainbow No.1 lode and Cor. No. 1, Mineral Survey No. 4546, Rainbow No.2 lode.</p> <hr/>
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in this survey are located approximately 7 miles west of the community of Goodsprings, in Clark County, Nevada. Access is provided by Sandy Valley Road, Kingston Road, Nevada State Route 53 and numerous dirt roads. The area is mountainous. Vegetation consists of various grasses, greasewood, sagebrush, Joshua trees, and various cacti. The average elevation of the area is approximately 4,300 ft. above sea level.</p>

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

2010 - 2011

Kelson Hatter	Crew Chief
Josh B. Helmick	Crew Chief
Sean R. Stevens	Crew Chief
Mike Davis	Survey Technician

2016 - 2022

Brandon K. Grace	Cadastral Surveyor
Justin V. Haddon	Cadastral Surveyor
Joseph J. Johnson	Cadastral Surveyor
Carlos Gil Mendoza	Cadastral Surveyor
Mark G. Petrosine	Surveying Technician
Ryan P. Marx	Surveying Technician
Christopher S. Bourgoine	Supervisory Range Technician
Alex J. Yetsko	Geographic Information System Specialist

## CERTIFICATE OF SURVEY

We, Brian D. Hatter, Nevada Professional Land Surveyor, and Brandon G. Courtright, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of February, 2010, We have dependently resurveyed the Sixth Standard Parallel South, through a portion of Range 57 East, a portion of the west boundary, the north boundary, the subdivisional lines and portions of certain mineral surveys, Township 24 South, Range 57 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUN 06 2023

(Date)

*Brian D. Hatter*  
(Nevada Professional Land Surveyor)

JUL 05 2023

(Date)

*Mahmud C. Hammur*  
/For Brandon G. Courtright  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Sixth Standard Parallel South, through a portion of Range 57 East, a portion of the west boundary, the north boundary, the subdivisional lines and portions of certain mineral surveys, Township 24 South, Range 57 East, of the Mount Diablo Meridian, Nevada, executed by Brian D. Hatter, Nevada Professional Land Surveyor, and Brandon G. Courtright, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUL 05 2023

(Date)

*Mahmud C. Hammur*  
(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 24 S., R. 57 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~
~~(Chief Cadastral Surveyor for Nevada)~~