

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SECTIONS 25 AND 26

OF

TOWNSHIP 24 SOUTH, RANGE 58 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Joseph J. Johnson, Cadastral Surveyor

Under Special Instructions dated September 22, 2009,

and approved September 22, 2009,

which provided for the surveys included under Group No. 887,

and Assignment Instructions dated May 22, 2012.

Survey commenced June 7, 2012

Survey completed February 13, 2014

INDEX DIAGRAM

TOWNSHIP 24 SOUTH, RANGE 58 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	11 10 26 8	7 5 25 2 3
31	32	33	34	35	36

SUBDIVISION OF SECTION 25

pp. 12-17

SUBDIVISION OF SECTION 26

pp. 17-24

TOWNSHIP 24 SOUTH, RANGE 58 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following field notes are those of the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines and the subdivision of sections 25 and 26, Township 24 South, Range 58 East, Mount Diablo Meridian.</p> <p>The south boundary (Sixth Standard Parallel South), the north, east and west boundaries, and subdivisional lines were surveyed by U.S. Deputy Surveyors, J.M. Brunt and W.H. Proctor in 1881 under Contract No. 115.</p> <p>The retracement and partial dependent resurvey of the south boundary (Sixth Standard Parallel South), a portion of the subdivisional lines, and the investigation and determination of the actual ground location of Mineral Survey No. 1921, Cresstone Lode was executed by U.S. Surveyor C.S. Swanholm in 1932 under Group No. 166.</p> <p>The history of other surveys remote to the area are not included.</p> <p>Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.</p> <p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the <u>Special Instructions for Group No. 887, dated September 22, 2009</u> and <u>Assignment Instructions for Group No. 887, dated May 22, 2012</u>.</p> <p>Measurements were made with Trimble R8-3 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method. The direction of each line is with reference to the true meridian and are reported as mean bearings. The distances are reported as horizontal measurement at a mean ground elevation of 3,740 feet above sea level.</p> <p>The geographic positions, in NAD83 (2011), (EPOCH:2010.0000) for the corners below were determined by GPS static observations processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS), NVBM BERMUDA CORS ARP, NVTP TROPOCANA CORS ARP, P621 MOUNTPASS_CS2005 CORS ARP and carried forward by RTK observations.</p> <p>The corner of sections 25, 30, 31 and 36 is as follows:</p> <p>Latitude: 35°49'26.252" N. Longitude: 115°24'47.845" W.</p> <p>The corner of sections 22, 23, 26 and 27 is as follows:</p> <p>Latitude: 35°50'18.213" N. Longitude: 115°26'56.782" W.</p>
--------	---

TOWNSHIP 24 SOUTH, RANGE 58 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The June 5, 2012 mean magnetic declination was determined to be 12°14' E. as obtained from the National Oceanic and Atmospheric Administration National Geophysical Data Center declination calculator.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA.</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881 under Contract No. 115.</p> <hr/> <p>Beginning at the cor. of secs. 25, 30, 31 and 36, perpetuated by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393, monumented with an unrecorded rebar, 5/8 in. diam., firmly set flush with the ground, with an aluminum cap, with the original limestone, 19x12x6 ins. (Record: sandstone, 22x14x8 ins.), with 1 notch on the south side, lying alongside rebar. This position was adopted by Joseph P. Fielding, Nevada Professional Land Surveyor No. 6199, in 1991, as recorded in Clark County, Nevada, File 60, Page 95, of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <table border="1" data-bbox="873 1142 1024 1289"> <tr><td colspan="2">T24S</td></tr> <tr><td>R58E</td><td>R59E</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S36</td><td>S31</td></tr> </table> <p>2013</p> <p>Insert the rebar inside the stainless steel post and deposit the mkd. stone alongside.</p> <p>N. 0°20'20" E., bet secs. 25 and 30.</p> <p>Gradual ascent, over rolling land with creosote and cacti.</p> <p>32.10 Power transmission line, bears S. 60 E. and N. 60 W.</p> <p>41.272 The 1/4 sec. cor. of secs. 25 and 30, perpetuated by Joseph P. Fielding, Nevada Professional Land Surveyor No. 6199, monumented with a rebar, 5/8 in. diam., firmly set flush with the ground, with an aluminum cap, with the original limestone, 19x10x5 ins. (Record: sandstone, 21x14x8 ins.) mkd. 1/4 on one face, lying alongside, as recorded in Clark County, Nevada, File 60, Page 95 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p>	T24S		R58E	R59E	S25	S30	<hr/>		S36	S31
T24S											
R58E	R59E										
S25	S30										
<hr/>											
S36	S31										

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S 1/4 R58E R59E S25 S30</p> </div> <p>2013</p> <p>Insert rebar inside stainless steel post and bury mkd. stone alongside.</p> <hr/> <p>N. 0°06'30" W., beginning new measurement.</p> <p>Gradual ascent, over rolling land with creosote and cacti.</p> <p>41.072 The cor. of secs. 19, 24, 25 and 30, monumented with the original sandstone, 22x9x5 ins. (Record: 27x12x10 ins.), lying on the surface of the ground, with 2 notches on the S. side.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R58E R59E S24 S19 <hr/>S25 S30</p> </div> <p>2013</p> <p>Deposit mkd. stone, in mound, alongside stainless steel post.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a portion of the Survey Executed by U.S. Deputy Surveyors J. M. Brunt and W. H. Proctor in 1881 under Contract No. 115.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 88°53'10" W., bet secs. 25 and 36.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over rolling land with creosote and cacti.
9.00	Goodsprings bypass haul road, asphalt surfaced, 45 lks. wide, bears NW. and SE.
18.30	Nevada State Route 161, asphalt surfaced, 40 lks. wide bears S. 60° E. and N. 60° W.
31.20	Wash, 50 lks. wide, drains SE.
41.301	<p>The 1/4 sec. cor. of secs. 25 and 36, perpetuated by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 2 1/2 ft. base, with an aluminum cap mkd. GD BUCK PLS 3393, as recorded in Clark County, Nevada, File 27, Page 75 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R58E</p> <p>S25</p> <p>1/4 —</p> <p>S36</p> <p>2013</p> </div> <p>Insert rebar inside stainless steel post.</p> <hr/> <p>N. 88°55'10" W., beginning new measurement.</p> <p>Over rolling land with creosote and cacti.</p>
20.617	<p>Point for the W 1/16 sec. cor. of secs. 25 and 36.</p> <p>POINT NOT MONUMENTED</p>
41.234	<p>The cor. of secs. 25, 26, 35 and 36, perpetuated by person(s) unknown, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 2 1/2 ft. base, 1 ft. high, with brass tag mkd. PLS 6199 wired to rebar, accepted by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393 in 1974, as recorded in Clark County, Nevada, File 27, Page 75 of surveys, also accepted by Joseph P. Fielding, Nevada Professional Land Surveyor No. 6199, as recorded in Clark County, Nevada, File 60, Page 95 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T24S R58E S26 S25 <hr style="width: 50%; margin: 0 auto;"/> S35 S36 2013 </div> <p>Insert rebar inside stainless steel post.</p> <hr/> <p>N. 0°39'50" E., bet. secs. 25 and 26.</p> <p>Over rolling land with creosote and cacti.</p> <p>11.50 Sandy Valley Road, asphalt surfaced, 30 lks. wide, bears N. 60° E. and S. 60° W.</p> <p>15.90 Ravine, 20 lks. wide, drains East.</p> <p>20.695 The S 1/16 sec. cor. of secs. 25 and 26, determined by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with an aluminum cap, mkd. RLS 3393, as recorded in Clark County, Nevada, File 27, Page 75, of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> S 1/16 S26 S25 2013 </div> <p>Insert rebar inside stainless steel post.</p> <hr/> <p>N. 0°39'50" E., beginning new measurement.</p> <p>Ascend, over SW facing slope, with sparse vegetation.</p> <p>11.90 Top of ridge, bears, east and west.</p> <p>20.695 The 1/4 sec. cor. of secs. 25 and 26, determined by person(s) unknown, monumented with a rebar, 1 1/2 ins. diam., accepted by Clark County Surveyor Ben L. Ortiz, Nevada Professional Land Surveyor No. 735, as recorded in Clark County, Nevada, File 15, Page 45 of Surveys, perpetuated after recordation with a brass disk, 2 ins. diam., firmly set flush in the top of a concrete pad, 7x7 ins., flush with the ground, mkd. CLARK COUNTY 1/4 COR S26 S25 T24S R58E ENG. DEPT., with a steel fence post alongside. This position has long been relied upon by multiple professional</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <hr/> <p>N.0°06'50" E., beginning new measurement.</p> <p>Gradual descent, over rolling land, through the community of Goodsprings.</p>						
2.70	Nevada State Route 161, asphalt surfaced, 40 lks. wide, bears S. 60° E. and N. 70° W.						
19.998	<p>A position determined as the NE cor. of the Goodsprings Townsite by Clark County Surveyor Ben L. Ortiz, Nevada Professional Land Surveyor No. 735, monumented with a brass disk, 2 ins. diam., firmly set flush with the surface and in a concrete pad, 15x12 ins., mkd. CLARK COUNTY ENG DEPT. 1/16 PACIFIC HIGH, as recorded in Clark County, Nevada, File 15, Page 45 of Surveys.</p> <p>From this cor. a limestone, 4x3 ins., mkd. with an "X" on one side, firmly set in a concrete pad, bears N. 89°59'40" E., 0.009 chs. dist.</p>						
20.404	<p>The N 1/16 sec. cor. of secs. 25 and 26, determined by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with an aluminum cap mkd. GD BUCK RLS 3393, as recorded in Clark County, Nevada, File 27, Page 75, of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 0°06'50" E., beginning new measurement.</p>						
20.404	<p>The cor. of secs. 23, 24, 25 and 26, perpetuated by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393, monumented with a rebar, 5/8 in. diam., firmly set, flush with the ground, recorded in Clark County, Nevada, File 27, Page 75, of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R58E</p> <table> <tr> <td>S23</td><td>S24</td></tr> <tr> <td colspan="2"><hr/></td></tr> <tr> <td>S26</td><td>S25</td></tr> </table> <p>2013</p> </div> <p>Bury rebar alongside stainless steel post.</p> <hr/>	S23	S24	<hr/>		S26	S25
S23	S24						
<hr/>							
S26	S25						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 86°59'50" W., bet secs. 24 and 25.</p>
40.974	<p>The 1/4 sec. cor. of secs. 24 and 25, perpetuated by persons unknown, monumented with a rebar, 5/8 in. diam., 18 ins. long, projecting 2 ins. above a mound of stone, 2 1/2 ft. base, 1 ft. high, with the original limestone, 18x9x8 ins. (Record: sandstone, 18x10x6 ins.), lying alongside, mkd. 1/4 on a face. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R58E</p> <p>S24</p> <p>1/4 —</p> <p>S25</p> <p>2013</p> </div> <p>Insert rebar inside stainless steel post and deposit stone alongside.</p> <hr/>
14.90	<p>S. 89°00'20" W., beginning new measurement.</p>
20.599	<p>Goodsprings bypass haul road, asphalt surfaced, 50 lks. wide, bears North and South.</p> <p>The W 1/16 sec. cor. of secs. 24 and 25, determined by Robert Fulstone, Nevada Professional Land Surveyor No. 5269, monumented with an unrecorded rebar, 5/8 in. diam., 18 ins. long, firmly set 2 ins. below the surface of the ground, with an aluminum cap mkd. FULSTONE W 1/16 PLS 5269. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>W 1/16</p> <p>S24</p> <hr/> <p>S25</p> <p>2013</p> </div> <p>Bury rebar alongside stainless steel post.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°00'20" W., beginning new measurement.
16.60	Power transmission line, bears S. 60 E. and N. 60 W.
17.00	Wash, 150 lks. wide, drains S. 15° E.
20.599	The corner of secs. 23, 24, 25 and 26.
	From the cor. of secs. 25, 26, 35, and 36.
	S. 88°34'00" W., bet. secs. 26 and 35.
19.659	Point for the E 1/16 sec. cor. for secs. 26 and 35.
	POINT NOT MONUMENTED
34.403	Point for the W-W-E 1/256 sec. cor. of secs. 26 and 35.
	Set a Cotton Gin Spike, 4 3/4 ins. long, flush with the asphalt surface of Sandy Valley Road.
	from which
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 45°13'40" E., 152.3 lks. dist., with brass cap mkd. RM T24S R58E S 35 W-W-E 1/256 100.5 FT. TO COR. 2013 and an arrow pointing to the corner.
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 45°09'50" W., 151.4 lks. dist., with brass cap mkd. RM T24S R58E S35 W-W-E 1/256 99.9 FT. TO COR. 2013 and an arrow pointing to the corner.
	Point falls on the southerly edge of Sandy Valley Road, 45 lks. wide, bears N. 70 E. and S. 60 W.
35.00	Sandy Valley Road, asphalt surfaced, 45 lks. wide, bears, N. 70 E. and S. 60 W.
39.318	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T24S R58E S26 1/4 — S35 2013

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45°37'50" E., 75.9 lks. dist., with brass cap mkd. RM T24S R58E S35 1/4 50.1 FT. TO COR. 2013 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 44°59'10" W., 75.3 lks. dist., with brass cap mkd. RM T24S R58E S35 1/4 49.7 FT. TO COR. 2013 and an arrow pointing to the corner.</p> <p>Point falls on the southerly shoulder of the Sandy Valley Road and Columbia Mill Road connector road.</p>
44.233	<p>The E-E-W 1/256 cor. of secs. 26 and 35, determined by Michael A. Constable, Nevada Professional Land Surveyor No. 12749, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 3 ins. above the ground, with an aluminum cap mkd. PLS 12749, as recorded in Clark County, Nevada, File 103, Page 48, of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S26 E-E-W 1/256 S35</p> <p style="text-align: center;">2013</p> <p>Bury rebar alongside stainless steel post.</p> <hr/> <p>S. 88°34'00" W., beginning new measurement.</p>
4.90	Columbia Mill Road, asphalt surfaced, 40 lks. wide, bears N. and S.
14.743	<p>Point for the W 1/16 sec. cor. of secs. 26 and 35.</p> <p>POINT NOT MONUMENTED</p>
34.401	<p>The cor. of secs. 26, 27, 34 and 35, monumented with the original limestone 18x14x10 ins. (Record: sandstone, 20x16x10 ins.), firmly set, in a mound of stone, 3 ft. base, 1 1/2 ft. high, with two notches on the E. side and 1 notch on the S. side.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R58E</p> <table> <tr> <td>S27</td><td>S26</td></tr> <tr> <td>S34</td><td>S35</td></tr> </table> <p>2013</p> </div> <p>Bury mkd. stone alongside stainless steel post.</p> <hr/> <p>N. 0°27'20" E., bet. Secs. 26 and 27.</p> <p>20.026 Point for the S 1/16 sec. cor. of secs. 26 and 27.</p> <p>POINT NOT MONUMENTED</p> <p>40.052 The 1/4 sec. cor. of secs. 26 and 27, monumented with the original limestone 13x12x6 ins. (Record: sandstone, 14x10x5 ins.), firmly set, projecting 8 ins. above the ground, with 1/4 mkd. on an exposed face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T24S R58E</p> <p>1/4</p> <table> <tr> <td>S27</td><td>S26</td></tr> </table> <p>2013</p> </div> <p>Bury mkd. stone alongside stainless steel post.</p> <p>From this corner, a position determined as the 1/4 sec. cor. of secs. 26 and 27, by William T. Avery, Nevada Professional Land Surveyor No. 5571, monumented with an unmarked limestone, 19x10x6 ins., loosely set in an eroded mound of stone, with remains of a 2x2 ins. wood hub laying loose alongside, as recorded in Clark County, Nevada File 48, Page 48 of Surveys, bears N. 9°01'00" W., 3.672 chs. dist. This position cannot be reconciled with original corner evidence and is not utilized during the course of this survey.</p> <hr/> <p>N. 0°08'40" W., beginning new measurement.</p> <p>7.90 Wash, 25 lks. wide, bears SE.</p> <p>9.50 Gravel road, 45 lks. wide bears, S. 50 E. and N. 50 W.</p>	S27	S26	S34	S35	S27	S26
S27	S26						
S34	S35						
S27	S26						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
15.20	Wash, 30 lks. wide, drains S. 60 E.						
19.980	Point for the N 1/16 sec. cor. of secs. 26 and 27.						
	POINT NOT MONUMENTED						
31.80	Top of ridge, bears S. 80 E. and N. 60 W.						
39.960	The cor. of secs. 22, 23, 26 and 27, monumented with the original limestone 14x11x6 ins. (Record: sandstone, 14x12x8 ins.), set in the center of a mound of stone, 3 ft. base, 1 ft. high, with two notches on a side and two notches on the adjacent side.						
	At the corner point						
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.						
	<table> <tr> <td>T24S</td><td>R58E</td></tr> <tr> <td>S22</td><td>S23</td></tr> <tr> <td>S27</td><td>S26</td></tr> </table>	T24S	R58E	S22	S23	S27	S26
T24S	R58E						
S22	S23						
S27	S26						
	2013						
	Deposit mkd. stone, in mound of stone, alongside stainless steel post.						
	From this corner, a position determined as the cor. of secs. 22, 23, 26 and 27, by William T. Avery, Nevada Professional Land Surveyor No. 5571, monumented with a rebar, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, with an aluminum cap, 2 ins. diam., mkd. T24S R58E S22 S23 S27 S26 4-22-88 RLS 5571 as recorded in Clark County, Nevada File 48, Page 48 of Surveys, bears N. 23°46'40" W., 4.073 chs. dist. This position cannot be reconciled with original corner evidence and is not utilized during the course of this survey.						
	From the cor. of secs. 23, 24, 25, and 26.						
	S. 89°02'00" W., bet secs 23 and 26.						
15.10	An improved gravel road, 30 lks. wide, bears S. 20 E. and N. 20 W.						
37.50	Trail road, 20 lks. wide, bears S. 50 E. and N. 50 W.						
39.982	The 1/4 sec. cor. of secs. 23 and 26, perpetuated by person(s) unknown, monumented with a miners drill steel, 1 in. diam., 29 ins. long, firmly set, projecting 3 ins. above the ground. This position is accepted on parole evidence submitted by Stephen N. Fleming of Goodsprings, Nevada, dated August 2, 2011, and parole evidence submitted by Donn Blake of Las Vegas, Nevada, dated						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>July 31, 2011. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T24S R58E S23 1/4 — S26</p> <p style="text-align: center;">2013</p> <p>Insert drill steel inside stainless steel post.</p> <p>From this corner, a position determined by person(s) unknown, monumented with a wooden hub, 2x2 ins., firmly set flush with the ground, bears S. 10°22'40" W., 0.141 chs. dist., not utilized during the course of this survey.</p> <p>From this same corner, a position established by person(s) unknown, monumented with a wooden hub, 2x2 ins., firmly set, projecting 2 ins. above the ground, with a stone, 10x9x5 ins., laying loose alongside, mkd. with an X chiseled on the top, bears S. 15°11'50" W., 0.097 chs. dist., not utilized during the course of this survey.</p> <hr/> <p>S. 84°54'00" W., beginning new measurement.</p>
5.90	An improved gravel road, 40 lks. wide, bears, S. 40 E. and N. 40 W.
19.558	Point for the W 1/16 sec. cor. of secs. 23 and 26.
	POINT NOT MONUMENTED
39.116	The sec. cor. of secs. 22, 23, 26 and 27.
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 25, T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 0°22'00" E., on the N-S center line of sec. 25.</p>
11.70	Nevada State Route 161, asphalt surfaced, 40 lks. wide, bears S. 60° E. and N. 60° W.
20.661	Point for the C-S 1/16 sec. cor. of sec. 25.
	POINT NOT MONUMENTED

SUBDIVISION OF SECTION 25,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
41.322	<p>The center 1/4 sec. cor. of sec. 25, determined by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393, monumented with a rebar, 5/8 in. diam., 15 ins. long, firmly set, projecting 2 ins. above the ground with an aluminum cap mkd. GD BUCK RLS 3393, as recorded in Clark County, Nevada, File 27, Page 75, of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T24S R58E C 1/4 S25</p> <p style="text-align: center;">2013</p> <p>Insert rebar inside stainless steel post.</p> <hr/> <p>N. 0°22'00" E., beginning new measurement.</p>
1.60	Goodsprings bypass haul road, asphalt surfaced, 50 lks. wide, bears S. 30° E. and N. 30° W.
17.20	Power transmission line, bears S. 60 E. and N. 60 W.
21.183	Point for the C-N 1/16 sec. cor. of sec. 25.
	POINT NOT MONUMENTED
42.366	<p>The 1/4 sec. cor. of secs. 24 and 25.</p> <hr/> <p>From the 1/4 sec. cor. of sec. 25 and 30, on the E. bdy. of the Tp.</p> <p>N. 88°49'10" W., on the E-W center line of sec. 25.</p>
14.40	Power transmission line, bears N. 60 W. and, S. 60 E.
40.20	Goodsprings bypass haul road, asphalt surfaced, 50 lks. wide, bears N. 30° W. and S. 30° E.
41.279	<p>The center 1/4 sec. cor. of sec. 25.</p> <hr/> <p>N. 88°49'10" W., beginning new measurement.</p>

SUBDIVISION OF SECTION 25,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.508	<p>The C-W 1/16 sec. cor. of sec. 25, determined by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393, monumented with a rebar, 5/8 in. diam., 15 ins. long, firmly set, projecting 4 ins. above the ground, with an aluminum cap mkd. GD BUCK RLS 3393, as recorded in Clark County, Nevada, File 27, Page 75, of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>W 1/16</p> <p>C——C</p> <p>S25</p> <p>2013</p> </div> <p>Insert rebar inside stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88°49'10" W., beginning new measurement.</p>
16.70	Nevada State Route 161, asphalt surfaced, 40 lks. wide bears, S. 60° E. and N. 60° W.
20.508	The 1/4 sec cor. of secs 25 and 26.
	<hr/> <p>From the point for the W 1/16 sec. cor. of secs. 25 and 36.</p> <p>N. 0°31'00" E., on the N-S center line of the SW1/4 of sec 25.</p>
20.678	<p>Point for the SW 1/16 sec. cor. of sec. 25, at intersection with the E-W center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>SW 1/16 S25</p> <p>2013</p> </div>
21.40	Sandy Valley Road, asphalt surfaced, 30 lks. wide, bears N. 75° E. and S. 75° W.
23.40	Nevada State Route 161, asphalt surfaced, 40 lks. wide, bears S. 50° E. and N. 50° W.
31.017	The C-N-SW 1/64 sec. cor. of sec. 25, determined by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with an aluminum cap mkd. G D BUCK RLS 3393, as recorded in Clark County, Nevada, File 27, Page 75, of Surveys.

SUBDIVISION OF SECTION 25,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S25 C-N-SW 1/64</p> <p style="text-align: center;">2014</p> <p>Insert rebar inside stainless steel post.</p> <hr/> <p>N. 0°31'00" E., beginning new measurement.</p>
10.339	<p>The C-W 1/16 sec. cor. of sec. 25.</p> <hr/> <p>From the point for the C-S 1/16 sec. cor. of sec. 25</p> <p>N. 88°52'10" W., on the E-W center line of the SW1/4 of sec. 25.</p>
16.80	Nevada State Route 161, asphalt surfaced, 40 lks. wide, bears S. 60° E. and N. 60° W.
20.561	The SW 1/16 sec. cor. of sec. 25.
22.40	Sandy Valley Road, asphalt surfaced, 30 lks. wide, bears N. 70° E. and S. 70° W.
41.122	The S 1/16 sec. cor. of secs. 25 and 26.
	<hr/> <p>From the C-W 1/16 sec. cor. of sec. 25.</p> <p>N. 0°14'30" E., on the N-S center line of the NW1/4 of sec. 25.</p>
10.396	<p>The C-S-NW 1/64 sec. cor. of sec. 25, determined by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393, monumented with a rebar, 5/8 in. diam., firmly set, flush with the ground and in a collar of stone, with an aluminum cap mkd. G D BUCK RLS 3393, as recorded in Clark County, Nevada, File 27, Page 75, of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

SUBDIVISION OF SECTION 25,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S25 C-S-NW 1/64</p> <p style="text-align: center;">2014</p> <p>Insert rebar inside stainless steel post.</p> <hr/> <p>N. 0°14'30" E., beginning new measurement.</p> <p>10.396 The NW 1/16 sec. cor. of sec. 25, determined by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393, monumented with a rebar, 5/8 in. diam., firmly set, flush with the ground, with an aluminum cap mkd. G D BUCK RLS 3393, as recorded in Clark County, Nevada, File 27, Page 75, of Surveys. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S25</p> <p style="text-align: center;">2014</p> <p>Insert rebar inside stainless steel post.</p> <hr/> <p>N. 0°14'30" E., beginning new measurement.</p> <p>9.20 Power transmission line, bears S. 60° E. and N. 60° W.</p> <p>20.792 The W 1/16 sec. cor. of secs. 24 and 25.</p> <hr/> <p>From the point for the C-N 1/16 sec. cor. of sec. 25.</p> <p>N. 89°54'40" W., on the E-W center line of the NW1/4 of sec. 25.</p> <p>Over gently rolling land with scattered creosote brush.</p> <p>6.10 Power transmission line, bears N. 56° W. and S. 56° E.</p> <p>6.70 Center of unimproved dirt road, 12 lks. wide, bears N. 57° W. and S. 57° E.</p> <p>12.20 Easterly edge of asphalt surfaced road, 45 lks. wide, bears N. 8° W. and S. 32° E.</p> <p>13.40 Power transmission line, bears N. 52° W. and S. 52° E.</p> <p>20.551 The NW 1/16 sec. cor. of sec. 25.</p> <hr/>
--------	--

SUBDIVISION OF SECTION 25,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°54'40" W., beginning new measurement. Over gently rolling land with scattered creosote brush.
17.20	Center of unimproved dirt road, 12 lks. wide, bears N. 28° W. and S. 8° E.
20.551	The N 1/16 sec. cor. of secs. 25 and 26.
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 26, T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	From the 1/4 sec. cor. of sec. 26 and 35. N. 0°05'00" W., on the N-S center line of sec. 26.
0.30	The Sandy Valley Road and the Columbia Mill Road connector road, asphalt surfaced, 40 lks. wide, bears East and West.
5.088	Point for the C-S-S-S 1/256 sec. cor. of sec. 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S26 C-S-S-S 1/256 2014
20.351	Point for the C-S 1/16 sec. cor. of sec. 26. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.
	C S 1/16 S26 C 2013
	From this point, a position determined as the C-S 1/16 sec. cor. of sec. 26, by Michael A. Constable, Nevada Professional Land Surveyor No. 12749, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with an aluminum cap mkd. PLS 12749, as recorded in Clark County, Nevada, File 103, Page 48, of Surveys, bears N. 5°15'30" W., 0.895 chs. dist. This position was determined using improper control at the center 1/4 sec. cor. of sec. 26, and is not utilized during the course of this survey.

SUBDIVISION OF SECTION 26,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
31.860	<p>From this point, a position determined as the C-N-S 1/64 sec. cor. of sec. 26, by Michael A. Constable, Nevada Professional Land Surveyor No. 12749, monumented with a rebar, 5/8 in. diam., firmly set, flush with the ground, with an aluminum cap mkd. PLS 12749, as recorded in Clark County, Nevada, File 103, Page 48, of Surveys, bears WEST, 0.123 chs. dist. This position was determined using improper control at the center 1/4 sec. cor. of sec. 26, and is not utilized during the course of this survey.</p>
35.00	<p>Columbia Mill Road, asphalt surfaced, 40 lks. wide, bears N. 80° E. and S. 80° W.</p>
40.702	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R58E C 1/4 S26</p> <p style="text-align: center;">2013</p>
	<p>From this point, a position accepted as the SW cor. of the Goodsprings Townsite and accepted as center 1/4 sec. cor. of sec. 26, by Clark County Surveyor Ben L. Ortiz, Nevada Professional Land Surveyor No. 735, as recorded in Clark County, Nevada, File 15, Page 45, of Surveys, perpetuated after recordation with a brass disk, 2 ins. diam., firmly set, 3 ins. below the surface and in a concrete pad, 8x8 ins., mkd. CLARK COUNTY ENG. DEPT. CTR 1/4 COR. S 26 5-17-65 T24S R58E, bears N. 5°26'30" W., 1.783 chs. dist. This position cannot be reconciled with proper procedures and is not utilized during the course of this survey as the center 1/4 sec. cor. of sec. 26.</p>
47.475	<p>From this point, a position determined by Clark County Surveyor Ben L. Ortiz, Nevada Professional Land Surveyor No. 735, monumented with a brass disk, 2 ins. diam., firmly set 8 ins. below the surface and in a concrete pad, 8x8 ins., mkd. CLARK COUNTY ENG DEPT C/L BEACON MARKET, as recorded in Clark County, Nevada, File 15, Page 45, of Surveys, bears WEST, 0.149 chs. dist.</p>
52.474	<p>From this point, a position determined by Clark County Surveyor Ben L. Ortiz, Nevada Professional Land Surveyor No. 735, monumented with a brass disk, 2 ins. diam., firmly set 4 ins. below the surface and in a concrete pad, 8x8 ins., mkd. CLARK COUNTY ENG DEPT BEACON MAIN 5-17-65, as recorded in Clark County, Nevada, File 15, Page 45, of Surveys, bears WEST, 0.134 chs. dist.</p>
57.476	<p>From this point, a position determined by Clark County Surveyor Ben L. Ortiz, Nevada Professional Land Surveyor No. 735, monumented with a brass disk, 2 ins. diam., firmly set flush with the surface and in a concrete pad, 8x8 ins., mkd. CLARK COUNTY ENG DEPT BEACON EXCH 5-19-65, as recorded in Clark</p>

SUBDIVISION OF SECTION 26,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	County, Nevada, File 15, Page 45, of Surveys, bears WEST, 0.117 chs. dist.
61.602	<p>Point for the C-N 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>N 1/16 S26</p> <p>C</p> <p>2013</p> </div> <p>From this point, a position determined as the C-N 1/16 sec. cor. of sec. 26, by William T. Avery, Nevada Professional Land Surveyor No. 5571, monumented with a rebar, 5/8 in. diam., firmly set, 1 in. above the ground, with an aluminum cap, mkd. 1/16 5·10·88 RLS 5571, as recorded in Clark County, Nevada, File 48, Page 48, of Surveys, bears N. 6°39'50" W., 0.838 chs. dist. This position was determined using improper control at the 1/4 sec. cor. of secs. 23 and 26, and at the center 1/4 sec. cor. of sec. 26, and is not utilized during the course of this survey as the C-N 1/16 sec. cor. of sec. 26.</p> <p>From this same point, a position accepted as the NW cor. of the Goodsprings Townsite and accepted as C-N 1/16 sec. cor. of sec. 26, by Clark County Surveyor Ben L. Ortiz, Nevada Professional Land Surveyor No. 735, as recorded in Clark County, Nevada, File 15, Page 45, of Surveys, perpetuated after recordation with a brass disk, 2 ins. diam., firmly set in a concrete pad, 7x8 ins., projecting 2 ins. above the ground, mkd. CLARK COUNTY ENG DEPT 1/16 PACIFIC BEACON 5·14·65, in a collar of stone, bears N. 6°37'10" W., 0.900 chs. dist. This position cannot be reconciled with proper procedures and is not utilized during the course of this survey as the C-N 1/16 sec. cor. of sec. 26.</p>
66.30	Intersection of North Beacon Street, 40 lks. wide, bears S. 5° E. and N. 5° W., with an asphalt driveway, 40 lks. wide, bears E. and W.
66.828	<p>Point for the C-S-N-N 1/256 sec. cor. of sec. 26.</p> <p>Set a magnetic nail, flush with the surface of North Beacon Street.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N. 45°03' E., 151.5 lks. dist., with brass cap mkd. RM T24S R58E S 26 C-S-N-N 1/256 100.0 FT. TO COR. 2013 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 44°'56 E., 151.5 lks. dist., with brass cap mkd. RM</p>

SUBDIVISION OF SECTION 26,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T24S R58E S26 C-S-N-N 1/256 100.0 FT. TO COR. 2013 and an arrow pointing to the corner.</p> <p>Point is located on the westerly side of North Beacon Street.</p>
71.00	North Beacon St., gravel surfaced, 50 lks. wide, bears S. 5° E. and N. 25 W.
82.504	The 1/4 sec. cor. of secs. 23 and 26.
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>S. 87°35'50" W., on the E-W center line of sec. 26.</p>
19.937	Point for the C-E 1/16 sec. cor. of sec. 26.
	POINT NOT MONUMENTED
22.40	Reimann Road, asphalt surfaced, 35 lks. wide, bears N. 20 E. and S. 10 W.
39.874	The center 1/4 sec. cor. of sec. 26.
59.353	Point for the C-W 1/16 sec. cor. of sec. 26.
	POINT NOT MONUMENTED
68.30	Gravel road, 40 lks. wide bears S. 50 E. and N. 50 W.
78.832	Point for the 1/4 sec. cor. of secs. 26 and 27.
	<hr/> <p>From the point for the E 1/16 sec. cor. of secs. 26 and 35.</p> <p>N. 0°17'40" E., on the N-S center line the SE1/4 of sec. 26.</p>
4.09	Sandy Valley Road, asphalt surfaced, 30 lks. wide, bears N. 70° E. and S. 70° W.
20.522	Point for the SE 1/16 sec. cor. of sec. 26, at intersection with the E-W center line of the SE1/4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S26</p> <p style="text-align: center;">2014</p> <p>From this point, a position determined as the SE 1/16 sec. cor. of sec. 26 by Gilbert D. Buck, Nevada Professional Land Surveyor No. 3393, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with an aluminum cap mkd. GD Buck RLS 3393, as recorded in Clark County, Nevada, File 27, Page 75, of Surveys, bears N. 7°07'30" W., 0.519 chs. dist. This position was determined using improper control at the</p>

SUBDIVISION OF SECTION 26,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	center 1/4 sec. cor. of sec. 26, and is not utilized during the course of this survey.
41.044	The C-E 1/16 sec. cor. of sec. 26.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 25 and 26.</p> <p>S. 88°05'00" W., on the E-W center line of the SE1/4 of sec. 26.</p>
19.799	The SE 1/16 sec. cor. of sec. 26.
39.598	The C-S 1/16 sec. cor. of sec. 26.
	<hr/> <p>From the W-W-E 1/256 sec. cor. of secs. 26 and 35.</p> <p>N. 0°00'50" E., on the N-S center line of the SW1/4 of the SW1/4 of the SE1/4 of sec. 26.</p>
2.623	From this point, a position determined by Michael A. Constable, Nevada Professional Land Surveyor No. 12749, monumented with a rebar 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with an aluminum cap mkd. PLS 12749 as recorded in Clark County, Nevada, File 103, Page 48, of Surveys, bears EAST, 0.005 chs. dist.
5.098	Point for the SW-SW-SE 1/256 sec. cor. of sec. 26.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S26 SW-SW-SE 1/256 2014</p> <hr/>
	S. 88°26'40" W., on the E-W center line of the SW1/4 of the SW1/4 of the SE1/4 of sec. 26.
4.923	Point for the C-S-S-S 1/256 sec. cor. of sec. 26.
	<hr/> <p>From the point for the W 1/16 sec. cor. of secs. 26 and 35.</p> <p>N. 0°11'10" E., on the N-S center line of the SW1/4 of sec. 26.</p>
15.26	Columbia Mill Road, asphalt surfaced, 40 lks. wide, bears S. 28° E. and N. 28° W.
20.189	Point for the SW 1/16 sec. cor. of sec. 26, at intersection with the E-W center line of the SW1/4.
	POINT NOT MONUMENTED

SUBDIVISION OF SECTION 26,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
32.30	Intersection of Columbia Mill Road, 40 lks. wide, bears N. 54° E. and S. 54° W., with Reimann Road, asphalt surfaced, 35 lks. wide, bears N. 40° W.
40.378	The C-W 1/16 sec. cor. of sec. 26.
	<hr/> <p>From the C-S 1/16 sec. cor. of sec. 26. S. 88°05'00" W., on the E-W center line of the SW1/4 of sec. 26.</p>
19.568	The SW 1/16 sec. cor. of sec. 26.
22.01	Columbia Mill Road, asphalt surfaced, 40 lks. wide, bears S. 28° E. and N. 28° W.
39.136	The S 1/16 sec. cor. of secs. 26 and 27.
	<hr/> <p>From the E-E-W 1/256 sec. cor. of sec. 26 and 35. N. 0°00'40" W., on the N-S center line of the SE1/4 of the SE1/4 of the SW1/4 of sec. 26.</p>
5.078	Point for the SE-SE-SW 1/256 sec. cor. of sec. 26.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S26 SE-SE-SW 1/256 2014</p>
	<p>From this point, a position determined by Michael A. Constable, Nevada Professional Land Surveyor No. 12749, monumented with a rebar, 5/8 in. diam., firmly set, flush with the ground and in a collar of stone, with an aluminum cap mkd. PLS 12749, as recorded in Clark County, Nevada, File 103, Page 48, of Surveys, bears N. 4°38'50" W., 0.259 chs. dist. This position was determined using improper control and is not utilized during the course of this survey.</p>
4.909	<hr/> <p>N. 88°26'30" E., on the E-W center line of the SE1/4 of the SE1/4 of the SW1/4 of sec. 26.</p> <p>The C-S-S-S 1/256 sec. cor. of sec. 26.</p>
	<hr/> <p>From the point for the C-W 1/16 sec. cor. of sec. 26. N. 0°06'50" W., on the N-S center line of the NW1/4 of sec. 26.</p>
20.441	Point for the NW 1/16 sec. cor. of sec. 26, at intersection with the E-W center line of the NW1/4.

SUBDIVISION OF SECTION 26,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	POINT NOT MONUMENTED
40.882	The W 1/16 sec. cor. of secs. 23 and 26.
	<hr/> <p>From the C-N 1/16 sec. cor. of sec. 26.</p> <p>S. 86°14'40" W., on the E-W center line of the NW1/4 of sec. 26.</p>
4.878	Point for the C-E-E-NW 1/256 sec. cor. of sec. 26.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S26 C-E-E-NW 1/256 2013</p>
19.513	The NW 1/16 sec. cor. of sec. 26.
39.026	The N 1/16 sec. cor. of secs. 26 and 27.
	<hr/> <p>From the C-E-E-NW 1/256 sec. cor. of sec. 26.</p> <p>N. 0°05'20" W., on the N-S center line of the SE1/4 of the NE1/4 of the NW1/4 of sec. 26.</p>
1.642	From this point, a position determined by William T. Avery, Nevada Professional Land Surveyor No. 5571, monumented with a rebar, 5/8 in. diam., firmly set, 3 ins. below the ground and in a collar of stone, with an aluminum cap, mkd. RLS 5571, as recorded in Clark County, Nevada, File 48, Page 48, of Surveys, bears WEST, 0.221 chs. dist.
5.197	Point for the SE-NE-NW 1/256 sec. cor. of sec. 26.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S26 SE-NE-NW 1/256 2013</p>
	<hr/> <p>N. 85°54'40" E., on the E-W center line of the SE1/4 of the NE1/4 of the NW1/4 of sec. 26.</p>
3.011	The center of a sewer manhole set in a concrete pad, 4x4 ft., bears NORTH, 0.579 chs. dist.

SUBDIVISION OF SECTION 26,
T. 24 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
3.044	A concrete post, which is the SW. cor. of a single strand steel cable fence enclosure, 15 x 45 ft., bears NORTH 0.542 chs. dist., long side bears S. 88° E.
3.073	Intersect the westerly side of a chain-link storage unit attached to a side of the Goodsprings Fire Station building, 5 x 17 ft., the SW. corner bears S. 1°00' E., 0.129 chs. dist., long side bears N. 1°00' W.
3.154	Intersect a westerly side of the Goodsprings Fire Station building, a northerly corner bears N. 1°00' W., 0.128 chs. dist. From this northerly corner the sides of the building extend EAST, 29 ft., SOUTH, 57 1/2 ft., WEST, 56 1/2 ft., N. 1° W., 33 1/2 ft., EAST, 28 1/2 ft., N. 1° W., 24 ft., to the point of beginning.
3.592	Intersect the easterly side of the Goodsprings Fire Station building.
4.881	The C-S-N-N 1/256 sec. cor. of sec. 26.
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands dependently resurveyed and subdivided within sections 25 and 26, Township 24 South, Range 58 East, consist of low mountains to the west and gently sloping lands to the east. The average elevation of the area is 3700 feet above sea level. Vegetation primarily consists of creosote, yucca, and various species of cacti. The Goodsprings Townsite is located within the area surveyed and has a number of historic buildings. Access to the area is provided by Nevada State Route 161 and numerous unimproved roads.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Jose A. Serna	Cadastral Surveyor
Christopher S. Bourgoine	Range Technician
Joel J. Borwick	Student Trainee
Russell M. Garcia	Student Trainee

CERTIFICATE OF SURVEY

I, Joseph J. Johnson, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22 day of September, 2009, I have dependently resurveyed a portion of the east boundary, a portion of the subdivisional lines and subdivided sections 25 and 26, Township 24 South, Range 58 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUN 25 2014

(Date)



(Cadastral Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines and the subdivision of sections 25 and 26, Township 24 South, Range 58 East, Mount Diablo Meridian, Nevada, executed by Joseph J. Johnson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 25 2014

(Date)



(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 24 S., R. 58 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~