

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE  
DEPENDENT RESURVEY

OF

THE FIFTH STANDARD PARALLEL NORTH THROUGH A PORTION OF RANGE 50 EAST,

A PORTION OF THE SOUTH BOUNDARY

AND A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 25 NORTH, RANGE 50 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Joseph J. Johnson, Cadastral Surveyor

Under Special Instructions dated April 29, 2013,

and approved April 30, 2013,

Supplemental Special Instructions dated June 4, 2013,

and approved June 5, 2013,

and Supplemental Special Instructions dated July 22, 2013,

and approved July 22, 2013,

which provided for the surveys included under Group No. 924,

and Assignment Instructions dated April 30, 2013.

Survey commenced May 23, 2013

Survey completed November 11, 2013

INDEX DIAGRAM

TOWNSHIP 25 NORTH, RANGE 50 EAST, MOUNT DIABLO MERIDIAN, NEVADA

					36
					2
6	5	4	3	2	11 1 10
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24 10
30	29	28	27	26 13	8 25 8
31	32	33	34 5	12 35 4	7 36 3

## TOWNSHIP 25 NORTH, RANGE 50 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of the Fifth Standard Parallel North through a portion of Range 50 East, a portion of the south boundary and a portion of the subdivisional lines of Township 25 North, Range 50 East, Mount Diablo Meridian, Nevada.

The Fifth Standard Parallel North through Range 50 East, the south, east, and west boundaries and the subdivisional lines were surveyed by U.S. Deputy Surveyors D.H. Barker and E.L. Bridges in 1879 under Contract No. 86. A portion of the Fifth Standard Parallel North through Range 51 East was dependently resurveyed and the west boundary was dependently and independently resurveyed by U.S. Surveyor C.S. Swanholm in 1924 under Group No. 92. The Fifth Standard Parallel North through Range 51 East was dependently resurveyed by Cadastral Surveyor B.G. Courtright in 2012 under Group No. 918. The Fifth Standard Parallel North through a portion of Range 51 East and the east boundary were dependently resurveyed concurrently under this same Group.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 924, dated April 29, 2013, Supplemental Special Instructions dated June 4, 2013, and Supplemental Special Instructions dated July 22, 2013.

Measurements were made with Trimble R8-3 Global Positioning System (GPS) receivers using the real-time kinematic method. The direction of each line is with reference to the true meridian. All bearings are mean bearings and the distances are reported as horizontal measurement at a mean ground elevation of 5,750 feet above sea level.

The NAD83 (2011) (EPOCH:2010.0000) geographic position of the following corners were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) AST1 AUSTIN 1 CORS ARP, EGAN EGAN BRGN NV1996 CORS ARP, P013 SPRINGCREKNV2007 CORS ARP and carried forward by RTK observations is as follows:

The corner of Tps. 24 and 25 N., Rs. 50 and 51 E., is as follows:

Latitude: 39°59'50.187" N. Longitude: 116°16'18.880" W.

The standard corner of sections 34 and 35, T. 26 N., R. 50 E., is as follows:

## TOWNSHIP 25 NORTH, RANGE 50 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Latitude: 40°05'04.616" N. Longitude: 116°18'45.898" W.</p> <p>The May 23, 2013 mean magnetic declination was determined to be 13°10' E., as obtained from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.</p> <hr/> <p>DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH THROUGH A PORTION OF RANGE 50 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.L. Bridges in 1879</p> <hr/> <p>Beginning at the standard cor. of Tps. 26 N., Rs. 50 and 51 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fifth Standard Parallel North through Range 51 East, executed under Group No. 918.</p> <p>N. 88°10'00" W., on the S. bdy. of sec. 36.</p> <p>Over rolling land with sagebrush and scattered juniper.</p> <p>4.20 Barbed wire fence, bears N. 50° E. and S. 50° W.</p> <p>13.40 Top of bench, bears NE. and SW.</p> <p>24.100 The N 1/4 sec. cor. of sec. 1, T. 25 N., R. 50 E., hereinafter described.</p> <p>28.180 From this point, the ancient remains of a badly deteriorated wooden post, lying loose on the ground, 2x2 ins., 4 ft. long, bears SOUTH, 1.616 chs. dist. This point is not utilized in this survey.</p> <p>36.90 Improved road, gravel surfaced, 45 lks. wide, bears N. 60° W. and S. 60° E.</p> <p>37.50 Barbed wire fence, bears N. 50° E. and S. 50° W.</p> <p>39.019 Point for the standard 1/4 sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R50E 1/4 S36 <hr/>2013</p>
--------	---

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH  
THROUGH A PORTION OF RANGE 50 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
62.996	The closing cor. of secs. 1 and 2, T. 25 N., R. 50 E., hereinafter described.
78.038	<p>Point for the standard cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">SC T26N R50E S35   S36</p>
	<p style="text-align: center;">2013</p>
	<p>From this point, a juniper, 21 ins. diam., with natural scarring, bears N. 88°11'00" W., 35.633 chs. dist. There is no evidence of this tree being an original bearing tree. It is of unknown origin and is not utilized in the course of this survey.</p>
	<p>From this same point, the standard cor. of secs. 34 and 35, bears N. 88°10'00" W., 78.038 chs. dist., monumented with a squared wooden post, 3x3x48 ins. long, lying loose on the ground, with illegible marks.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">SC T26N R50E S34   S35</p>
	<p style="text-align: center;">2013</p>
	<p>Bury the wooden post alongside the stainless steel post.</p>
	<p>This control line was fully retraced and a careful search was made for evidence of the intervening corner, none of which was found.</p>
	<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.L. Bridges in 1879</p> <hr/>
	<p>From the cor. of Tps. 24 and 25 N., Rs. 50 and 51 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>described in the field notes of T. 25 N., R. 51 E., executed concurrently under this same Group.</p> <p>N. 89°40'00" W., bet. secs. 1 and 36.</p> <p>Over rolling land with sagebrush.</p>						
40.070	<p>The 1/4 sec. cor. of secs. 1 and 36, determined from the decayed, fragmented remains of a wooden post, lying loose on the ground, with no discernible markings. This position is harmoniously related to existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E</p> <p>S36</p> <p>1/4 —</p> <p>S 1</p> <p>T24N</p> <p>2013</p> </div> <p>Bury remains of wooden post alongside the stainless steel post.</p> <hr/> <p>N. 89°42'20" W., beginning new measurement.</p>						
39.537	<p>The cor. of secs. 1, 2, 35 and 36, determined from the decayed, fragmented remains of a wooden post, with no discernible markings, lying loose on the ground. This position is harmoniously related to existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E</p> <table border="1" style="margin: auto;"> <tr> <td>S35</td> <td>S36</td> </tr> <tr> <td>S 2</td> <td>S 1</td> </tr> <tr> <td colspan="2">T24N</td> </tr> </table> <p>2013</p> </div> <p>Insert remains of wooden post inside the stainless steel post.</p> <hr/> <p>N. 89°46'00" W., bet. secs. 2 and 35.</p> <p>Over rolling land with sagebrush.</p>	S35	S36	S 2	S 1	T24N	
S35	S36						
S 2	S 1						
T24N							

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
3.90	Enter Garden Valley, edge bears NE. and SW.
16.20	Barbed wire fence, bears NE. and SW.
40.098	Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  <div style="text-align: center;"> T25N R50E  S35  1/4 —  S 2  T24N    2013 </div>
	Cor. is located at E. edge of meadow.
47.10	Dry bed of Pete Hanson Creek, 5 lks. wide, 2 ft. deep, drains N.
53.00	W. edge of meadow.
54.50	Trail road, 15 lks. wide bears N. and S.
58.50	Leave Garden Valley, edge bears NE. and SW.
60.147	Point for the W 1/16 sec. cor. of secs. 2 and 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  <div style="text-align: center;"> S35  W 1/16 —  S 2    2013 </div>
80.196	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  <div style="text-align: center;"> T25N R50E  S34   S35  —   —  S 3   S 2  T24N    2013 </div>
	N. 89°46'00" W., bet. secs. 3 and 34.  Over rolling land, with sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.10	Barbed wire fence, bears NNE. and SSW.
19.40	Trail road, 15 lks. wide, bears NNE. and SSW.
40.098	<p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E S34 1/4 — S 3 T24N  2013</p> </div>
57.90	Trail road, 15 lks. wide, bears ESE. and WNW.
80.196	<p>The cor. of secs. 3, 4, 33 and 34, perpetuated by person(s) unknown, monumented with the bottom portion of a steel fence post, 1 ft. long, firmly set 3 ins. below the surface, with the top portion of the steel fence post lying loose on the ground, with the decayed remains of a squared wooden post, 1x1x10 ins., no marks visible, wired to the top portion of the steel fence post. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E S33   S34 —   — S 4   S 3 T24N  2013</p> </div> <p>Insert bottom portion of the steel fence post and squared wooden post inside the stainless steel post.</p> <p>Reset top portion of steel fence post alongside stainless steel post.</p> <hr/>



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.L. Bridges in 1879</p>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°13'20" E., bet. secs. 35 and 36.</p> <p>Over rolling land, with sagebrush and rabbit brush.</p>
1.30	Enter Garden Valley, edge bears NE. and SW.
14.30	Barbed wire fence, bears NE. and SW.
19.930	<p>Point for the S 1/16 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16 S35 S36</p> <p>2013</p> </div>
39.860	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E 1/4 S35 S36</p> <p>2013</p> </div>
71.00	Trail road, 15 lks. wide, bears E. and W.
75.30	Enter grassy meadow, bears NE. and SW.
79.720	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E S26 S25 S35 S36</p> <p>2013</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of T. 25 N., R. 51 E., executed concurrently under this same Group.</p> <p>N. 89°14'00" W., bet. secs. 25 and 36.</p> <p>Over rolling land, with rabbit brush.</p>
1.60	Barbed wire fence, and edge of Garden Valley, bears NE. and SW.
20.071	<p>Point for the E 1/16 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S25 E 1/16 — S36</p> <p>2013</p> </div>
40.142	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E S25 1/4 — S36</p> <p>2013</p> </div>
72.10	Trail road, 15 lks. wide, bears NE. and SW.
80.284	The cor. of secs. 25, 26, 35 and 36.
	<hr/> <p>N. 0°56'20" E., bet. secs. 25 and 26.</p> <p>Over rolling land with sagebrush.</p>
1.70	Pete Hanson Creek, 4 lks. wide, 2 ft. deep, course NE.
3.00	Leave meadow, bears NE. and SW.; continue across rolling land with sagebrush.
15.30	Trail road, 20 lks. wide, bears NE. and SW.
19.933	<p>Point for the S 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">S 1/16 S26   S25</p> <p style="text-align: center;">2013</p>
39.866	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T25N R50E 1/4 S26   S25</p> <p style="text-align: center;">2013</p>
79.732	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T25N R50E S23   S24 ----- S26   S25</p> <p style="text-align: center;">2013</p> <p>From this point, the cor. of secs. 21, 22, 27, and 28, bears S. 89°29'40" W., 159.926 chs. dist., monumented with a granite stone, 12x6x5 ins. (Record: 16x14x12 ins.), firmly set, projecting 8 ins. above the ground, with a "T" post alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R50E S21   S22 ----- S28   S27</p> <p style="text-align: center;">2013</p> <p>Bury mkd. stone and reset "T" post alongside stainless steel post.</p> <p>From this same point, the cor. of secs. 1, 2, 11 and 12, bears N. 0°42'30" W., 239.178 chs. dist., hereinafter described.</p> <p>These control lines were fully retraced and a careful search was made for evidence of intervening corners, none of which was found.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of T. 25 N., R. 51 E., executed concurrently under this same Group.</p> <p>N. 88°46'40" W., bet. secs. 24 and 25.</p> <p>Over rolling land, with rabbit brush.</p>
39.979	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E</p> <p>S24</p> <p>1/4 —</p> <p>S25</p> <p>2013</p> </div>
79.968	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with the ground, with brass cap mkd. as described in the field notes of T. 25 N., R. 51 E., executed concurrently under this same Group.</p> <p>N. 88°30'00" W., bet. secs. 1 and 12.</p> <p>Over rolling land, with rabbit brush.</p>
0.40	Improved road, gravel surfaced, 20 lks. wide, bears N. 60° W. and S. 60° E.
3.30	Improved road, gravel surfaced, 20 lks. wide, bears N. 10° W. and S. 10° E.
19.50	Leave Garden Valley, edge bears N. and S.
39.807	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E</p> <p>S 1</p> <p>1/4 —</p> <p>S12</p> <p>2013</p> </div>
71.40	Improved road, gravel surfaced, 30 lks. wide, bears NNE. and SSW.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS					
79.604	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E</p> <table border="1" style="margin: auto;"> <tr> <td>S 2</td><td>S 1</td></tr> <tr> <td>S11</td><td>S12</td></tr> </table> <p>2013</p> </div> <p>From this point, the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., bears N. 89°39'10" W., 397.921 chs. dist., monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 3 ft. base, with brass cap mkd. as described in the field notes of the independent resurvey of a portion of the E. bdy. of T. 25 N., R. 49 E., executed under Group No. 92.</p> <p>This control line was fully retraced and a careful search was made for evidence of intervening corners, none of which was found.</p>	S 2	S 1	S11	S12
S 2	S 1				
S11	S12				
39.862	<p>N. 0°29'40" E., bet. secs. 1 and 2.</p> <p>Over rolling land with sagebrush and bunch grass.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R50E</p> <table border="1" style="margin: auto;"> <tr> <td>1/4</td><td></td></tr> <tr> <td>S 2</td><td>S 1</td></tr> </table> <p>2013</p> </div>	1/4		S 2	S 1
1/4					
S 2	S 1				
80.202	<p>Intersect the Fifth Standard Parallel North.</p> <p>Point for closing cor. of secs. 1 and 2, at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R50E</p> <p>S36</p> <table border="1" style="margin: auto;"> <tr> <td>S 2</td><td>S 1</td></tr> </table> <p>T25N R50E</p> <p>CC</p> <p>2014</p> </div>	S 2	S 1		
S 2	S 1				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, the standard cor. of secs. 35 and 36, T. 26 N., R. 50 E., bears N. 88°10'00" W., 15.042 chs. dist., hereinbefore described.</p> <hr/> <p>The point for the N 1/4 sec. cor. of sec. 1, is on the Fifth Standard Parallel North and at midpoint on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R50E 1/4 S 1 T25N R50E 2013</p> <p>From this point, the standard 1/4 sec. cor. of sec. 36, T. 26 N., R. 50 E., bears N. 88°10'00" W., 14.919 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°09'50" W., bet. secs. 34 and 35.</p> <p>Over rolling land with sagebrush and bunch grass.</p> <p>34.60 Barbed wire fence, bears NNE. and SSW.</p> <p>39.998 Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T25N R50E 1/4 S34 S35 2013</p> <p>79.996 The cor. of secs. 26, 27, 34 and 35, perpetuated by person(s) unknown, monumented with a steel fence post, firmly set, projecting 4 ft. above the ground, with the weathered remains of a squared wooden post, 10x3x2 ins., no marks visible, wired to the base of the steel fence post. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T25N R50E  S27   S26  <hr style="width: 50px; margin: 0 auto;"/> S34   S35 </div>
	2013
	Bury the remains of the wooden post and set steel fence post alongside the stainless steel post.
	<hr/> From the cor. of secs. 25, 26, 35 and 36. N. 89°29'40" W., bet. secs. 26 and 35. Over rolling land with sagebrush and bunch grass.
2.90	Pete Hanson Creek, 4 lks. wide, 2 ft. deep, course NE.
18.30	Leave Garden Valley, edge bears NE. and SW.
18.90	Trail road, 15 lks. wide, bears NE. and SW.
20.035	Point for the E 1/16 sec. cor. of secs. 26 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="display: flex; justify-content: center; align-items: center;"> <div style="margin-right: 10px;">E 1/16</div> <div style="text-align: center;"> S26  <hr style="width: 50px; margin: 0 auto;"/> S35 </div> </div>
	2013
40.070	The 1/4 sec. cor. of secs. 26 and 35, perpetuated by person(s) unknown, monumented with a steel fence post, with the decayed, remains of a wooden post, 2 ins. diam., 1 ft. long, wired to the steel fence post. This is accepted as the best available evidence of the position of the original corner.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> T25N R50E  S26  1/4 ———  S35 </div>
	2013
	Bury the remains of the wooden post and set steel fence post alongside the stainless steel post.
	<hr/> N. 89°39'00" W., beginning new measurement.
15.10	Barbed wire fence, bears NNE. and SSW.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 25 N., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.652	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>GENERAL DESCRIPTION</p> <p>The area resurveyed within T. 25 N., R. 50 E., is about 40 miles north of Eureka, Nevada. Access to the area is by Nevada State Route 278 and numerous desert access roads. The area varies from gently rolling land in the upper elevations to grassy meadows in the bottom lands. The soil is sandy clay loam in the higher elevations and black loam in the meadows. Long term ranching and recent mining facilities are nearby.</p> <hr/>



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS


Brandon G. Courtright	Cadastral Surveyor
Kane M. Hellebust	Cadastral Surveyor
Mark G. Petrosine	Surveying Technician

## CERTIFICATE OF SURVEY

I, Joseph J. Johnson, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of April, 2013, supplemental special instructions bearing date of the 4th day of June, 2013, and supplemental instructions bearing date of the 22nd day of July, 2013, I have dependently resurveyed the Fifth Standard Parallel North through a portion of Range 50 East, a portion of the south boundary and a portion of the subdivisional lines of Township 25 North, Range 50 East, Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

9/24/2014

(Date)



(Cadastral Surveyor)


## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Fifth Standard Parallel North through a portion of Range 50 East, a portion of the south boundary and a portion of the subdivisional lines of Township 25 North, Range 50 East, Mount Diablo Meridian, Nevada, executed by Joseph J. Johnson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

**SEP 29 2014**

(Date)



(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 25 N., R. 50 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~