

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE  
THE SOUTH, EAST AND WEST BOUNDARIES,  
THE SUBDIVISIONAL LINES AND PORTIONS OF CERTAIN MINERAL SURVEYS,  
TOWNSHIP 25 SOUTH, RANGE 58 EAST,  
OF THE MOUNT DIABLO MERIDIAN,  
IN THE STATE OF NEVADA

EXECUTED BY

Brian D. Hatter, Professional Land Surveyor  
Brandon G. Courtright, Cadastral Surveyor

Under Contract No. L06PC05105,  
and Special Instructions dated February 9, 2010,  
and approved February 9, 2010,  
which provided for the surveys included under Group No. 891,  
and Assignment Instructions dated November 9, 2010, and March 9, 2016.

Survey commenced November 18, 2010

Survey completed June 29, 2021

## INDEX DIAGRAM

TOWNSHIP 25 SOUTH, RANGE 58 EAST, MOUNT DIABLO MERIDIAN, NEVADA

18	6	57	5	46	4	39	3	32	2	24	1	12
	56		56		45		38		31		24	
17	7	55	8	44	9	38	10	31	11	23	12	11
	54		53		44		37		30		23	
16	18	52	17	43	16	37	15	30	14	22	13	11
	52		51		43		36		29		22	
15	19	51	20	42	21	36	22	28	23	21	24	10
	50		50		42		35		27		21	
14	30	49	29	41	28	35	27	27	26	20	25	9
	49		48		41		34		26		19	
14	31	47	32	40	33	33	34	26	35	19	36	7
	7		6		5		5		4		3	

Mineral Survey No. 1854....PP 59-61  
 Mineral Survey No. 1856....PP 61-65  
 Mineral Survey No. 1865....PP 66-67  
 Mineral Survey No. 2109....PP 68-70  
 Mineral Survey No. 4168....PP 70-72  
 Mineral Survey No. 4322....PP 72-83  
 Mineral Survey No. 4345....PP 83-93

Mineral Survey No. 4353....PP 93-99  
 Mineral Survey No. 4376....PP 99-103  
 Mineral Survey No. 4441....PP 103-112  
 Mineral Survey No. 4525....PP 112-120  
 Mineral Survey No. 4534....PP 120-124  
 Mineral Survey No. 4551....PP 125-127  
 Mineral Survey No. 4597 A..PP 127-134

## TOWNSHIP 25 SOUTH, RANGE 58 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of the south, east and west boundaries, the subdivisional lines and portions of certain mineral surveys, Township 25 South, Range 58 East, Mount Diablo Meridian, Nevada.

The north boundary (Sixth Standard Parallel South) was surveyed by U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881 under Contract No. 115. The south, east and west boundaries and the subdivisional lines were surveyed by U.S. Deputy Surveyor T.A. Magee in 1883 under Contract No. 149. The retracement and partial dependent resurvey of a portion of the north boundary (Sixth Standard Parallel South), a portion of the west boundary and a portion of the subdivisional lines, and the investigation and determination of the actual ground location of Mineral Survey No. 1921, "Cresstone" lode were executed by U.S. Surveyor C.S. Swanholm in 1932 under Group No. 166. A portion of the west boundary was dependently resurveyed by U.S. Transitman R.F. Wilson in 1932 under Group No. 205, California. The north boundary (Sixth Standard Parallel South) is being concurrently dependently resurveyed by Professional Land Surveyor Brian D. Hatter, Cadastral Surveyor Brock R. Clifford and Surveying Technician Mark G. Petrosine under Group No. 887.

## HISTORY OF MINERAL SURVEYS PERTAINING TO RESURVEY

Mineral Survey No. 1853, Galena and Ruby Silver lodes were surveyed by U.S. Deputy Mineral Surveyor H.W. Newby in 1899, and is being concurrently dependently resurveyed by Professional Land Surveyor Brian D. Hatter, Cadastral Surveyor Brock R. Clifford and Surveying Technician Mark G. Petrosine under Group No. 887.

Mineral Survey No. 1854, Full Moon lode was surveyed by U.S. Deputy Mineral Surveyor H.W. Newby in 1899.

Mineral Survey No. 1856, Mountain Top and Lookout lodes were surveyed by U.S. Deputy Mineral Surveyor H.W. Newby in 1899.

Mineral Survey No. 1864, Chicago lode was surveyed by U.S. Deputy Mineral Surveyor H.W. Newby in 1899, and is being concurrently dependently resurveyed by Professional Land Surveyor Brian D. Hatter, Cadastral Surveyor Brock R. Clifford and Surveying Technician Mark G. Petrosine under Group No. 887.

Mineral Survey No. 1865, Volcano lode was surveyed by U.S. Deputy Mineral Surveyor H.W. Newby in 1899.

Mineral Survey No. 2109, Carbinet No. 2 lode was surveyed by U.S. Deputy Mineral Surveyor H.K. Wheeler in 1903.

Mineral Survey No. 4168, Tiffin lode was surveyed by U.S. Mineral Surveyor C.E. McCarthy in 1913.

Mineral Survey No. 4322, Anchor, Topmast, Anchor No. 2, Anchor No. 3, Anchor No. 4, Monitor and Gulch lodes were surveyed by U.S. Mineral Surveyor C.E. McCarthy in 1917.

Mineral Survey No. 4345, Porter, Prospect, Palace and Promintory lodes were surveyed by U.S. Mineral Surveyor C.H. Fenner in 1917.

## TOWNSHIP 25 SOUTH, RANGE 58 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Mineral Survey No. 4353, Bullion, Bullion No. 2 and Wayward lodes were surveyed by U.S. Mineral Surveyor C.H. Fenner in 1918.

Mineral Survey No. 4376, Evening Star and East Evening Star lodes were surveyed by U.S. Mineral Surveyor A.H. Black in 1918.

Mineral Survey No. 4377, Valentine, Valentine No. 2 and Summit lodes were surveyed by U.S. Mineral Surveyor C.H. Fenner in 1918. Mineral Survey No. 4377 was cancelled on September 20, 2021.

Mineral Survey No. 4441, Mongolia, Producer, Oriental, April Fool and Nellie lodes were surveyed by U.S. Mineral Surveyor A.H. Black in 1920.

Mineral Survey No. 4525, Sultan, Sultana, Turk and Tuffacious lodes were surveyed by U.S. Mineral Surveyor A.H. Black in 1922.

Mineral Survey No. 4534, South Side and Idaho lodes were surveyed by U.S. Mineral Surveyor A.H. Black in 1922.

Mineral Survey No. 4551, Ajax lode was surveyed by U.S. Mineral Surveyor A.H. Black in 1922.

Mineral Survey Nos. 4597 A and B, Hoosier, Oklahoma, East Side, Jupiter, California and Washington lodes and Hoosier mill site were surveyed by U.S. Mineral Surveyor C.D. Baker in 1924.

Mineral Survey No. 4687, Bill Nye and Bill Nye No. 3 lodes were surveyed by U.S. Mineral Surveyor C.D. Baker in 1929, and are being concurrently dependently resurveyed by Professional Land Surveyor Brian D. Hatter, Cadastral Surveyor Brock R. Clifford and Surveying Technician Mark G. Petrosine under Group No. 887.

Mineral Survey No. 4739, Prometheus No. 1 lode was surveyed by U.S. Mineral Surveyor C.D. Baker in 1937, and is being concurrently dependently resurveyed by Professional Land Surveyor Brian D. Hatter, Cadastral Surveyor Brock R. Clifford and Surveying Technician Mark G. Petrosine under Group No. 887.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 891, dated February 9, 2010.

## TOWNSHIP 25 SOUTH, RANGE 58 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Measurements were made with Trimble R7 and R8 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 1983 (CORS96) (EPOCH:2002.0000) geographic position, of the following corners were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) DI4038 NVPO MT. POTOSI CORS, DJ8975 NVTP TROPICANA CORS, AND DJ8973 BERMUDA CORS, and carried forward by RTK observations.

The corner of Townships 25 and 26 South, Ranges 58 and 59 East is as follows:

Latitude: 35°43'17.023" N. Longitude: 115°24'53.898" W.

The standard corner of Townships 24 South, Ranges 57 and 58 East, is as follows:

Latitude: 35°48'33.032" N. Longitude: 115°31'36.414" W.

The mean magnetic declination is 13°30' E. as shown on U.S.G.S. 7 1/2 minute quadrangle map "GOODSPRINGS, NEVADA", provisional edition dated 1989.

---

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of the Survey Executed by  
U.S. Deputy Surveyor T.A. Magee in 1883

---

Beginning at the cor. of Tps. 25 and 26 S., Rs. 58 and 59 E., monumented with a limestone, 21x8x7 ins. (Record, 26x17x12 ins.), firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. with 6 grooves on all 4 faces.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T25S	
R58E	R59E
S36	S31
<hr/>	
S 1	S 6
T26S	

2010

Deposit the mkd. stone alongside the stainless steel post.

S. 89°47'10" W., on the S. bdy. of sec. 36.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 25.70	Wash, 40 lks. wide, drains SE.
42.844	Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to sec. 36 only.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.  T25S R58E 1/4 S36 T26S R58E  2011
73.30	Spur, slopes N. 50° E.
85.688	Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to secs. 35 and 36 only.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.  T25S R58E S35   S36 T26S R58E  2011
27.50	S. 89°47'10" W., on the S. bdy. of sec. 35. Spur, slopes SSE.
42.844	Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to sec. 35 only.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.  T25S R58E 1/4 S35 T26S R58E  2011
48.70	Cross saddle, on ridge, bears NE. and SW.
63.20	Gulch, 25 lks. wide, drains NE.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 85.688	<p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to secs. 34 and 35 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S R58E S34   S35</p> <hr style="width: 50%; margin: 0 auto;"/> <p>T26S R58E</p> <p>2011</p> </div> <hr/> <p>S. 89°47'10" W., on the S. bdy. of sec. 34.</p>
4.18	Top of small peak.
16.80	Gulch, 40 lks. wide, drains N.
38.80	Ridge, bears NE. and SW. at top of spur, slopes NE.
42.844	<p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to sec. 34 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S R58E 1/4 S34</p> <hr style="width: 50%; margin: 0 auto;"/> <p>T26S R58E</p> <p>2011</p> </div>
60.80	Gulch, 20 lks. wide, drains N.
85.688	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to secs. 33 and 34 only.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <div style="text-align: center;"> <p>T25S R58E S33   S34</p> <hr style="width: 50%; margin: 0 auto;"/> <p>T26S R58E</p> <p>2011</p> </div> <hr/> <p>S. 89°47'10" W., on the S. bdy. of sec. 33.</p>
30.70	Top of ridge, bears S. 70° E. and N. 70° W.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 42.844	<p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to sec. 33 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S33 <hr/>T26S R58E</p> <p style="text-align: center;">2011</p>
81.80	Gulch, 15 lks. wide, drains S.
85.688	<p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to secs. 32 and 33 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S32   S33 <hr/>T26S R58E</p> <p style="text-align: center;">2011</p>
	S. 89°47'10" W., on the S. bdy. of sec. 32.
7.7	Top of ridge, bears NE. and SW.
34.30	Gulch, 10 lks. wide, drains N.
42.844	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to sec. 32 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S32 <hr/>T26S R58E</p> <p style="text-align: center;">2011</p>
78.40	Leave mountainous land.



DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
81.60	Trail road, 12 lks. wide, bears NE. and SW.
85.688	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to secs. 31 and 32 only.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T25S R58E S31   S32 T26S R58E  2011
6.00	S. 89°47'10" W., on the S. bdy. of sec. 31.  Wash, 8 chs. wide, drains SW. into alluvial fan.
42.844	Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to sec. 31 only.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T25S R58E 1/4 S31 T26S R58E  2011
84.006	The cor. of Tps. 25 and 26 S., Rs. 57 and 58 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the resurvey of a portion of the W. bdy. of T. 26 S., R. 58 E., executed under Group No. 205, California.
	DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by U.S. Deputy Surveyor T.A. Magee in 1883
	From the cor. of Tps. 25 and 26 S., Rs. 58 and 59 E., hereinbefore described.  N. 0°16'50" W., bet. secs. 31 and 36.
4.10	Spur, slopes SW.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
16.90	Top of ridge, bears S. 65° E. and N. 65° W.
27.10	Spur, slopes NE.
39.668	The 1/4 sec. cor. of secs. 31 and 36, monumented with a limestone, 15x10x9 ins., firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. 1/4 on the W. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;"> T25S  1/4  R58E   R59E  S36   S31 </div>
	2010
	Deposit the mkd. stone alongside the stainless steel post.
	<hr/>
	N. 0°40'30" W., beginning new measurement.
2.10	Trail road, 12 lks. wide, bears WNW. and ESE.
6.50	Wash, 7 chs. wide, drains ESE.
14.70	Wash, 3 1/2 chs. wide, drains E.
31.90	Trail road, 10 lks. wide, bears ENE. and WSW.
39.60	Wash, 20 lks. wide, drains ENE.
40.325	The cor. of secs. 25, 30, 31 and 36, monumented with a limestone, 19x12x7 ins., firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. with 1 groove on the S. face and 5 grooves on the N. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;"> T25S  R58E   R59E  S25   S30  <hr style="width: 50%; margin: 0 auto;"/> S36   S31 </div>
	2010
	Deposit the mkd. stone alongside the stainless steel post.
	<hr/>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°32'00" W., bet. secs. 25 and 30.
10.40	Enter wash, drains N. 80° E.
12.90	Exit wash.
40.186	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with a limestone, 36x20x17 ins. (Record, 15x11x9 ins.), firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <div style="text-align: center;"> <p>T25S 1/4 R58E   R59E S25   S30</p> <p>2010</p> </div> <p>Deposit the mkd. stone in a raised mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, 5 ft. W. of cor.</p> <hr/> <p>N. 0°04'40" W., beginning new measurement.</p>
40.996	<p>The cor. of secs. 19, 24, 25 and 30, perpetuated by James L. Marlett Jr., Nevada Professional Land Surveyor No. 13386, in 2003, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set, projecting 6 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 13386, with a limestone, 23x9x8 ins., loosely set, mkd. with 2 grooves on the S. face and 4 grooves on the N. face alongside, as recorded in Clark County Nevada, Corner Record 20030620.01381.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S R58E   R59E S24   S19 S25   S30</p> <p>2010</p> </div> <p>Insert the rebar inside and deposit the mkd. stone alongside the stainless steel post.</p> <hr/>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°08'40" W., bet. secs. 19 and 24.
40.680	<p>The 1/4 sec. cor. of secs. 19 and 24, perpetuated by James L. Marlett Jr., Nevada Professional Land Surveyor No. 13386, in 2003, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set, projecting 6 ins. above the ground, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 13386, with a limestone, 19x13x10 ins., firmly set, mkd. 1/4 on the W. face alongside, as recorded in Clark County Nevada, Corner Record 20030620.01380.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S 1/4 R58E   R59E S24   S19</p> <p>2010</p> </div> <p>Insert the rebar inside and deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°10'40" W., beginning new measurement.</p>
18.10	Trail road, 12 lks. wide, bears ENE. and WSW.
40.615	<p>The cor. of secs. 13, 18, 19 and 24, monumented with a limestone, 27x19x12 ins. (Record, 16x14x9 ins.), firmly set in a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, mkd. with 3 grooves on the S. face and 3 grooves on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S R58E   R59E S13   S18 <hr/>S24   S19</p> <p>2010</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>From this cor., a rebar, 1/2 in. diam., firmly set, projecting 4 ins. above the ground, and in a collar of stone, with aluminum cap, 1 1/2 ins. diam., mkd. PRUIT J 102395 KING, set by person(s) unknown, bears S. 45°24' W., 0.981 chs. dist., with a 1x1 in. wood post, projecting 3 ft. above the ground, wired to the rebar. This rebar is not utilized in this survey.</p> <hr/>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°35'00" E., bet. secs. 13 and 18.
24.50	Trail road, 12 lks. wide, bears NNE. and SSW.
40.542	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with a limestone, 21x17x11 ins. (Record, 21x9x8 ins.), firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S 1/4 R58E   R59E S13   S18</p> <p>2010</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°06'00" E., beginning new measurement.</p>
31.10	Trail road, 10 lks. wide, bears N. 60° E. and S. 60° W.
40.504	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a limestone, 20x9x6 ins., firmly set on top, in a mound of stone, 2 ft. diam., 1 ft. high, mkd. with 4 grooves on the S. face and 2 grooves on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S R58E   R59E S12   S 7 S13   S18</p> <p>2010</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°46'10" E., bet. secs. 7 and 12.</p>
16.70	Trail road, 10 lks. wide, bears S. 40° E. and N. 40° W.
16.90	Overhead power line, bears S. 40° E. and N. 40° W.
36.60	Trail road, 12 lks. wide, bears ESE. and WNW.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.011</p>	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S. 1/4 R58E R59E S12 S 7</p> <p style="text-align: center;">2010</p>
<p>61.90</p>	<p>Spur, slopes SE.</p>
<p>80.022</p>	<p>The cor. of secs. 1, 6, 7 and 12, perpetuated by Byron E. Johnson, Nevada Professional Land Surveyor No. 9390, in 2002, monumented with a rebar, 5/8 in. diam., 15 ins. long, firmly set, flush with the surface of the ground, with aluminum cap mkd. B JOHNSON PLS 9390, with a limestone, 22x13x7 ins., firmly set on top, in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. with 5 grooves on the S. face and 1 groove on the N. face, as recorded in Clark County, Nevada, File 122, Page 87 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E R59E S 1 S 6 S12 S 7</p> <p style="text-align: center;">2010</p> <p>Insert the rebar inside and deposit the mkd. stone alongside the stainless steel post.</p>
<p>39.947</p>	<p>N. 0°21'50" E., bet. secs. 1 and 6.</p> <p>The 1/4 sec. cor. of secs. 1 and 6, perpetuated by Byron E. Johnson, Nevada Professional Land Surveyor No. 9390, in 2002, monumented with a rebar, 5/8 in. diam., 15 ins. long, firmly set, flush with the surface of the ground, with aluminum cap mkd. B JOHNSON PLS 9390, with a limestone, 16x11x9 ins., firmly set on top, in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 1/4 on the W. face, as recorded in Clark County, Nevada, File 122, Page 87 of Surveys.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S 1/4 R58E   R59E S 1   S 6</p> <p style="text-align: center;">2010</p> <p>Insert the rebar inside and deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°20'50" E., beginning new measurement.</p>
5.80	Trail road, 15 lks. wide, bears S. 20° E. and N. 20° W.
40.505	<p>Intersect the Sixth Standard Parallel South.</p> <p>Point for the closing cor. of Tps. 25 S., Rs. 58 and 59 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T24S R58E S 36 S 1   S 6 R58E   R59E T25S CC</p> <p style="text-align: center;">2011</p> <p>From this point, the standard cor. of Tps. 24 S., Rs. 58 and 59 E., bears S. 89°50'00" E., 6.350 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.</p>
40.600	<p>The original closing cor. of Tps. 25 S., Rs. 58 and 59 E., determined by Joseph P. Fielding, Nevada Professional Land Surveyor No. 6199, in 1991, monumented with a rebar, 5/8 in. diam., firmly set in a collar of stone, with aluminum cap mkd. 36-1-6 CC RLS6199, as recorded in Clark County, Nevada, File 60, Page 95 of Surveys. This is accepted as a careful and faithful determination of the position of the original corner. This monument now becomes an amended monument.</p> <hr/>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyor T.A. Magee in 1883 and the Dependent Resurvey Executed by U.S. Transitman R.F. Wilson in 1932</p> <hr/>
	<p>From the cor. of Tps. 25 and 26 S., Rs. 57 and 58 E., hereinbefore described.</p>
	<p>N. 0°02'50" W., bet. secs. 31 and 36.</p>
40.309	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the resurvey of a portion of the E. bdy. of T. 25 S., R. 57 E., executed under Group No. 205, California.</p> <hr/>
	<p>N. 0°14'10" E., beginning new measurement.</p>
18.20	<p>Wash, 3 chs. wide, drains SW.</p>
28.70	<p>Wash, 6 chs. wide, drains WSW.</p>
40.20	<p>Spur, slopes WSW.</p>
41.074	<p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 3 ft. diam., 2 1/2 ft. high, with brass cap mkd. as described in the field notes of the resurvey of a portion of the E. bdy. of T. 25 S., R. 57 E., executed under Group No. 205, California.</p> <hr/>
	<p>N. 0°13'40" E., bet. secs. 25 and 30.</p>
32.40	<p>Ridge, bears E. and W.</p>
38.561	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with a limestone, 18x15x10 ins. (Record, 16x9x8 ins.), firmly set in a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, mkd. 1/4 on the W. face.</p>
	<p>At the cornerpoint</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T25S 1/4 R57E   R58E S25   S30</p>
	<p style="text-align: center;">2011</p>
	<p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/>



DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°02'30" W., beginning new measurement.								
40.127	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a limestone, 17x16x11 ins., firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. with 1 groove on the S. face and 5 grooves on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <table> <tr><td colspan="2">T25S</td></tr> <tr><td>R57E</td><td>R58E</td></tr> <tr><td>S24</td><td>S19</td></tr> <tr><td>S25</td><td>S30</td></tr> </table> <p>2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p>	T25S		R57E	R58E	S24	S19	S25	S30
T25S									
R57E	R58E								
S24	S19								
S25	S30								
	N. 1°33'10" W., bet. secs. 19 and 24.								
39.40	Spur, slopes WSW.								
41.647	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <table> <tr><td colspan="2">T25S</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R57E</td><td>R58E</td></tr> <tr><td>S24</td><td>S19</td></tr> </table> <p>2011</p>	T25S		1/4		R57E	R58E	S24	S19
T25S									
1/4									
R57E	R58E								
S24	S19								
63.60	Spur, slopes SW.								
83.294	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>								

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> T25S  R57E   R58E  S13   S18  <hr/> S24   S19    2011 </div>
	<hr/>
	<p>N. 1°33'10" W., bet. secs. 13 and 18.</p>
16.10	<p>Top of ridge, bears ESE. and WNW.</p>
23.30	<p>Gulch, 20 lks. wide, drains NW.</p>
29.40	<p>Spur, slopes W.</p>
41.647	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;"> T25S  1/4  R57E   R58E  S13   S18 </div>
	<div style="text-align: center;">2011</div>
	<p>Cor. is located in Singer Wash, 15 chs. wide, drains W.</p>
61.650	<p>Intersect line 3-4, Mineral Survey No. 4168, Tiffin lode, at a point from which Cor. No. 3, hereinafter described, bears S. 41°39'50" E., 7.320 chs. dist.</p>
69.40	<p>Top of small hill.</p>
75.787	<p>Intersect line 1-2, Mineral Survey No. 4168, Tiffin lode, at a point from which Cor. No. 1, hereinafter described, bears N. 41°34'40" W., 0.148 chs. dist.</p>
83.294	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a limestone, 25x15x10 ins. (Record, 17x10x8 ins.), firmly set in a mound of stone, 3 1/2 ft. diam., 1 ft. high, mkd. with 4 grooves on the S. face and 2 grooves on the N. face.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="881 271 1027 399"> <table> <tr><td colspan="2">T25S</td></tr> <tr><td>R57E</td><td>R58E</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S13</td><td>S18</td></tr> </table> </div> <div data-bbox="922 430 987 457">2011</div> <div data-bbox="435 488 1360 515">Deposit the mkd. stone alongside the stainless steel post.</div> <hr/> <div data-bbox="435 567 1008 594">N. 0°37'20" W., bet. secs. 7 and 12.</div> <div data-bbox="285 623 1138 650">12.30 Dirt road, 12 lks. wide, bears WNW. and ESE.</div> <div data-bbox="285 675 1024 702">25.00 Bonanza Wash, 12 chs. wide, drains W.</div> <div data-bbox="285 727 1317 808">40.054 The 1/4 sec. cor. of secs. 7 and 12, monumented with a limestone, 18x9x7 ins., firmly set in a mound of stone, 3 1/2 ft. diam., 1 ft. high, mkd. 1/4 on the W. face.</div> <div data-bbox="435 832 740 859">At the corner point</div> <div data-bbox="435 884 1463 965">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div data-bbox="881 990 1027 1106"> <table> <tr><td colspan="2">T25S</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R57E</td><td>R58E</td></tr> <tr><td>S12</td><td>S 7</td></tr> </table> </div> <div data-bbox="922 1137 987 1164">2011</div> <div data-bbox="435 1195 1360 1222">Deposit the mkd. stone alongside the stainless steel post.</div> <hr/> <div data-bbox="435 1274 1105 1301">N. 0°00'40" E., beginning new measurement.</div> <div data-bbox="302 1330 1105 1357">3.40 Dirt road, 10 lks. wide, bears NE. and SW.</div> <div data-bbox="285 1382 1463 1485">40.123 The cor. of secs. 1, 6, 7 and 12, monumented with a limestone, 16x10x7 ins., firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. with 5 grooves on the S. face and 1 groove on the N. face.</div> <div data-bbox="435 1512 740 1539">At the corner point</div> <div data-bbox="435 1564 1430 1645">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</div> <div data-bbox="881 1670 1027 1796"> <table> <tr><td colspan="2">T25S</td></tr> <tr><td>R57E</td><td>R58E</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S12</td><td>S 7</td></tr> </table> </div> <div data-bbox="922 1827 987 1854">2011</div>	T25S		R57E	R58E	S12	S 7	<hr/>		S13	S18	T25S		1/4		R57E	R58E	S12	S 7	T25S		R57E	R58E	S 1	S 6	<hr/>		S12	S 7
T25S																													
R57E	R58E																												
S12	S 7																												
<hr/>																													
S13	S18																												
T25S																													
1/4																													
R57E	R58E																												
S12	S 7																												
T25S																													
R57E	R58E																												
S 1	S 6																												
<hr/>																													
S12	S 7																												

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/>
	<p>N. 6°30'20" E., bet. secs. 1 and 6.</p>
36.40	<p>Sandy Valley Road, asphalt surface, 50 lks. wide, bears N. 75° E. and S. 75° W.</p>
39.380	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S 1/4 R57E   R58E S 1   S 6</p> <p>2016</p> </div>
79.942	<p>Intersect the Sixth Standard Parallel South.</p> <p>Point for the closing cor. of Tps. 25 S., Rs. 57 and 58 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <div style="text-align: center;"> <p>T24S R57E S36 S 1   S 6 R57E   R58E T25S CC</p> <p>2016</p> </div> <p>From this point, the standard cor. of Tps. 24 S., Rs. 57 and 58 E., bears S. 89°38'50" E., 5.060 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 5 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.</p> <hr/>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyor T.A. Magee in 1883</p>
	<p>From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 1°15'10" E., bet. secs. 35 and 36.</p>
3.70	Top of ridge, bears NE. and SW.
13.80	Wash, 30 lks. wide, drains NE.
39.70	Wash, 20 lks. wide, drains NE.
40.308	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T25S R58E 1/4 S35 S36  2011</p>
54.90	Dirt road, 12 lks. wide, bears ESE. and WNW.
75.40	Wash, 2 chs. wide, drains ESE.
80.616	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T25S R58E S26 S25 S35 S36  2011</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>S. 89°50'10" W., bet. secs. 25 and 36.</p>
17.10	Dirt road, 15 lks. wide, bears N. and S.
40.215	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with a limestone, 21x17x9 ins., firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 1/4 on the S. face.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S25 1/4 — S36</p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°28'00" W., beginning new measurement.</p>
43.026	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 1°41'50" W., bet. secs. 25 and 26.</p>
33.50	Ridge, bears NW. and SE., on spur, slopes SE.
40.316	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S26 S25</p> <p style="text-align: center;">2011</p>
56.60	Top of ridge, bears S. 70° E. and N. 70° W.
70.90	Gulch, 20 lks. wide, drains NE.
80.632	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S23 S24 S26 S25</p> <p style="text-align: center;">2011</p> <hr/>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°48'00" W., bet. secs. 24 and 25.</p>
12.90	Dirt Road, 20 lks. wide, bears S. 15° E. and N. 15° W.
42.592	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <p style="text-align: center;">T25S R58E S24 1/4 — S25</p> <p style="text-align: center;">2011</p>
76.10	Gulch, 20 lks. wide, drains NE.
85.184	The cor. of secs. 23, 24, 25 and 26.
	<hr/> <p>N. 0°15'10" W., bet. secs. 23 and 24.</p>
4.20	Top of ridge, bears N. 40° E. and S. 40° W.
24.60	Dirt road, 15 lks. wide, bears NE. and SW.
39.70	Dirt road, 15 lks. wide, bears NE. and SW.
40.299	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S23 S24</p> <p style="text-align: center;">2011</p> <p>From this point, Cor. No. 1, Mineral Survey No. 4353, Bullion No. 2 lode, bears S. 48°07'00" W., 13.845 chs. dist., hereinafter described.</p>
72.30	Dirt road, 12 lks. wide, bears SE. and NW.
80.598	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T25S R58E  S14 S13  <hr/> S23 S24    2011 </div>
	<hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°20'00" W., bet. secs. 13 and 24.</p>
4.40	Dirt road, 12 lks. wide, bears N. 10° E. and S. 10° W.
42.650	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T25S R58E  S13  1/4 ———  S24    2011 </div>
58.00	Spur, slopes SW.
80.70	Wash, 1 ch. wide, drains SW.
85.300	The cor. of secs. 13, 14, 23 and 24.
	<hr/> <p>N. 1°15'30" W., bet. secs. 13 and 14.</p>
12.00	Wash, 2 chs. wide, drains SSE.
40.308	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T25S R58E  1/4  S14 S13    2016 </div> <p>From this point, Cor. No. 1, Mineral Survey No. 4376, East Evening Star lode, bears S. 59°46'20" W., 44.303 chs. dist., hereinafter described.</p>



DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 80.616	<p>Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T25S</td><td>R58E</td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td>S14</td><td>S13</td></tr> </table> <p>2016</p> </div> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°03'20" W., bet. secs. 12 and 13.</p>	T25S	R58E	S11	S12	S14	S13		
T25S	R58E								
S11	S12								
S14	S13								
27.642	Intersect line 3-4, Mineral Survey No. 4551, Ajax lode, at a point from which Cor. No. 3, hereinafter described, bears N. 20°29'30" W., 6.251 chs. dist.								
37.289	Intersect line 1-2, Mineral Survey No. 4551, Ajax lode, at a point from which Cor. No. 2, hereinafter described, bears N. 20°31'10" W., 3.025 chs. dist.								
43.773	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T25S</td><td>R58E</td></tr> <tr><td>S12</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S13</td><td></td></tr> </table> <p>2016</p> </div>	T25S	R58E	S12		1/4	—	S13	
T25S	R58E								
S12									
1/4	—								
S13									
81.50	Top of ridge, bears NE. and SW.								
87.546	The cor. of secs. 11, 12, 13 and 14.								
	<hr/> <p>N. 2°49'40" E., bet. secs. 11 and 12.</p>								
12.90	Top of ridge, bears SE. and NW.								
40.348	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>								

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T25S R58E 1/4 S11 S12</p> <p>2016</p>
80.696	<p>The cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 18x11x8 ins., firmly set in a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, mkd. with 5 notches on the S. edge and 1 notch on the E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p>T25S R58E S 2 S 1 S11 S12</p> <p>2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°25'10" W., bet. secs. 1 and 12.</p>
42.307	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p>T25S R58E S 1 1/4 — S12</p> <p>2011</p>
55.10	Power line, bears S. 40° E. and N. 40° W.
57.50	Dirt road, 15 lks. wide, bears ESE. and WNW.
66.10	Wash, 15 lks. wide, drains SE.
84.614	The cor. of secs. 1, 2, 11 and 12.
	<hr/> <p>N. 3°22'50" E., bet. secs. 1 and 2.</p>
24.00	Wash, 15 lks. wide, drains SE.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
32.30	Power line, bears S. 40° E. and N. 40° W.
40.542	<p>The point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S 2   S 1</p> <p style="text-align: center;">2016</p>
49.00	Top of ridge, bears WNW. and ESE.
81.675	<p>Intersect the Sixth Standard Parallel South.</p> <p>Point for the closing cor. of secs. 1 and 2.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, on N. side of limestone shelf, 10 ins. high, with top mkd.</p> <p style="text-align: center;">T24S R58E S35 S 2   S 1 T25S R58E CC</p> <p style="text-align: center;">2016</p> <p>From this point, the standard cor. of secs. 35 and 36, T. 24 S., R. 58 E., bears S. 89°43'40" E., 6.224 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.</p>
81.743	<p>The original closing cor. of secs. 1 and 2, monumented with a limestone, 19x14x10 ins., firmly set, projecting 5 ins. above the ground, mkd. CC on the S. face. Add the marks AM and bury the mkd. stone in a mound of stone, 4 ft. base, 2 ft. high.</p> <hr/> <p>The point for the N 1/4 sec. cor. of sec. 1, is on the Sixth Standard Parallel South and at midpoint in departure on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T24S R58E</p> <hr/> <p>1/4 S 1 T25S R58E</p> <p>2016</p> <p>From this point, the standard 1/4 sec. cor. of sec. 36, T. 24 S., R. 58 E., bears S. 89°52'10" E., 6.027 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.</p> <hr/> <p>From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 1°12'00" E., bet. secs. 34 and 35.</p>
39.70	Dirt road, 12 lks. wide, bears NE. and SW., in wash, drains NE.
40.267	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p>T25S R58E 1/4 S34 S35</p> <p>2011</p>
61.60	Wash, 15 lks. wide, drains SE.
80.534	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p>T25S R58E S27 S26 S34 S35</p> <p>2011</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°43'50" W., bet. secs. 26 and 35.</p>
8.00	Wash, 5 chs. wide, drains SE.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 42.874	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S26 1/4 — S35</p> <p style="text-align: center;">2011</p>
85.748	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>N. 1°29'30" W., bet. secs. 26 and 27.</p>
16.00	Top of ridge, bears ESE. and WNW.
25.50	Wash, 25 lks. wide, drains SE.
40.272	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S27 S26</p> <p style="text-align: center;">2011</p>
53.80	Top of ridge, bears SE. and NW.
80.544	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S22 S23 S27 S26</p> <p style="text-align: center;">2011</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°40'40" W., bet. secs. 23 and 26.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
22.031	Intersect line 1-2, Mineral Survey No. 4322, Gulch lode, at a point from which Cor. No. 2, hereinafter described, bears S. $47^{\circ}38'40''$ W., 1.731 chs. dist.
23.658	Intersect line 1-2, Mineral Survey No. 4322, Anchor lode, identical in part with line 2-3, Mineral Survey No. 4322, Gulch lode, at a point from which Cor. No. 2, Mineral Survey No. 4322, Gulch lode, hereinafter described, bears S. $16^{\circ}44'00''$ E., 1.208 chs. dist.
42.567	Intersect line 3-4, Mineral Survey No. 4322, Anchor No. 3 lode, at a point from which Cor. No. 4, hereinafter described, bears N. $16^{\circ}43'10''$ W., 3.545 chs. dist.
42.720	Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.  Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.  T25S R58E S23 1/4 — S26  2011
62.90	Top of ridge, bears ENE. and WSW.
85.440	The cor. of secs. 22, 23, 26 and 27. <hr/>
	N. $0^{\circ}41'40''$ W., bet. secs. 22 and 23.
14.90	Wash, 15 lks. wide, drains S. $76^{\circ}$ E.
23.80	Top of ridge, bears SE. and NW.
33.30	Top of ridge, bears NE. and SW.
40.261	Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T25S R58E 1/4 S22 S23  2016  From this point, Cor. No. 3, Mineral Survey No. 4353, Wayward lode, bears N. $82^{\circ}36'20''$ E., 47.911 chs. dist., hereinafter described.
50.80	Top of ridge, bears N. $70^{\circ}$ E. and S. $70^{\circ}$ W.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 80.522	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T25S R58E  S15   S14  S22   S23    2011 </div>
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°37'30" W., bet. secs. 14 and 23.</p>
9.10	Dirt road, 15 lks. wide, bears SE. and NW.
28.281	Intersect line 1-2, Mineral Survey No. 4345, Promintory lode, at a point from which Cor. No. 1, hereinafter described, bears N. 50°45'30" E., 2.879 chs. dist.
40.316	Intersect line 2-3, Mineral Survey No. 4345, Promintory lode, at a point from which Cor. No. 3, hereinafter described, bears N. 14°58'00" E., 2.616 chs. dist.
43.023	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T25S R58E  S14  1/4 —  S23    2011 </div>
49.425	Intersect line 1-2, Mineral Survey No. 4345, Prospect lode, at a point from which Cor. No. 5, Mineral Survey No. 4345, Palace lode, on line 1-2, Mineral Survey No. 4345, Prospect lode, hereinafter described, bears S. 37°56'10" W., 1.873 chs. dist.
61.050	Intersect line 1-2, Mineral Survey No. 4345, Porter lode, identical with line 3-4, Mineral Survey No. 4345, Prospect lode, at a point from which Cor. No. 2, Mineral Survey No. 4345, Porter lode, identical with Cor. No. 3, Mineral Survey No. 4345, Prospect lode, hereinafter described, bears S. 38°06'50" W., 8.719 chs. dist.
72.508	Intersect line 3-4, Mineral Survey No. 4345, Porter lode, at a point from which Cor. No. 3, hereinafter described, bears S. 37°48'20" W., 2.592 chs. dist.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 86.046	The cor. of secs. 14, 15, 22 and 23.
	N. 2°50'20" W., bet. secs. 14 and 15.
40.308	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T25S R58E 1/4 S15 S14  2016  From this point, Cor. No. 3, Mineral Survey No. 4376, Evening Star lode, bears S. 88°51'10" E., 32.056 chs. dist., hereinafter described.
43.30	Wash, 15 lks. wide, drains irregularly E.
80.616	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.  T25S R58E S10 S11 S15 S14  2016  From the cor. of secs. 11, 12, 13 and 14.  S. 89°35'00" W., bet. secs. 11 and 14.
20.00	Wash, 4 chs. wide, drains S.
44.125	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T25S R58E S11 1/4 — S14</p> <p>2016</p>
88.250	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 9°07'40" E., bet. secs. 10 and 11.</p>
40.774	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p>T25S R58E 1/4 S10 S11</p> <p>2011</p>
53.70	<p>Wash, 2 1/2 chs. wide, drains NE.</p>
81.548	<p>The cor. of secs. 2, 3, 10 and 11, monumented with a limestone, 25x19x12 ins. (Record 16x14x8 ins.), firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. with 5 notches on the S. edge and 2 notches on the E. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p>T25S R58E S 3   S 2 S10   S11</p> <p>2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <p>From this corner, Cor. No. 7, Mineral Survey No. 1856, Mountain Top lode, bears N. 17°46'10" W., 23.807 chs. dist., hereinafter described.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°40'10" W., bet. secs. 2 and 11.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 39.813	<p>The 1/4 sec. cor. of secs. 2 and 11, monumented with a limestone, 22x18x11 ins. (Record, 18x12x8 ins.), firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S 2 1/4 — S11</p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°17'00" W., beginning new measurement.</p>
11.80	Top of ridge, bears SE. and NW.
39.471	The cor. of secs. 2, 3, 10 and 11.
	<hr/> <p>N. 3°25'40" E., bet. secs. 2 and 3.</p>
15.20	Gulch, 50 lks. wide, drains irregularly NE.
41.350	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S 3   S 2</p> <p style="text-align: center;">2011</p>
82.70	Trail road, 12 lks. wide, bears NE. and SW.
82.747	<p>Intersect the Sixth Standard Parallel South.</p> <p>Point for the closing cor. of secs. 2 and 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="889 269 1036 424" data-label="Text"> <p>T24S R58E S34 <hr/>S 3   S 2 T25S R58E CC</p> </div> <div data-bbox="930 462 995 486" data-label="Text"> <p>2016</p> </div> <div data-bbox="438 513 1469 700" data-label="Text"> <p>From this point, the standard cor. of secs. 34 and 35, T. 24 S., R. 58 E., bears N. 89°11'20" E., 5.014 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 5 1/2 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.</p> </div> <div data-bbox="289 725 386 750" data-label="Text"> <p>83.155</p> </div> <div data-bbox="438 725 1469 832" data-label="Text"> <p>The original closing cor. of secs. 2 and 3, monumented with a limestone, 16x13x9 ins., firmly set, projecting 4 ins. above the ground, mkd. CC on the S. face. Add the marks AM and bury the mkd. stone in a mound of stone, 3 ft. base, 1 ft. high.</p> </div> <div data-bbox="438 886 1409 965" data-label="Text"> <p>The point for the N 1/4 sec. cor. of sec. 2, is on the Sixth Standard Parallel South and at midpoint in departure on the N. bdy. of sec. 2.</p> </div> <div data-bbox="438 990 1437 1098" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 5 ft. base, to top, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="889 1123 1036 1239" data-label="Text"> <p>T24S R58E <hr/>1/4 S 2 T25S R58E</p> </div> <div data-bbox="930 1270 995 1295" data-label="Text"> <p>2021</p> </div> <div data-bbox="438 1326 1461 1512" data-label="Text"> <p>From this point, the standard 1/4 sec. cor. of sec. 35, T. 24 S., R. 58 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. diam., bears S. 89°38'10" E., 5.585 chs. dist., with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.</p> </div> <div data-bbox="438 1566 1404 1620" data-label="Text"> <p>From the cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.</p> </div> <div data-bbox="438 1643 1036 1674" data-label="Text"> <p>N. 1°13'50" E., bet. secs. 33 and 34.</p> </div> <div data-bbox="289 1694 386 1719" data-label="Text"> <p>28.50</p> </div> <div data-bbox="438 1694 922 1725" data-label="Text"> <p>Wash, 25 lks. wide, drains NW.</p> </div> <div data-bbox="289 1746 386 1771" data-label="Text"> <p>40.434</p> </div> <div data-bbox="438 1746 1469 1802" data-label="Text"> <p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> </div>
--------	---

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S33 S34</p> <p style="text-align: center;">2011</p>
49.90	Gulch, 2 chs. wide, drains irregularly E.
80.868	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <p style="text-align: center;">T25S R58E S28 S27 S33 S34</p> <p style="text-align: center;">2011</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°59'30" W., bet. secs. 27 and 34.</p>
23.60	Gulch, 30 lks. wide, drains SE.
42.809	Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner; located on face of limestone outcrop where it is impractical to set a permanent monument.
43.489	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">WC T25S R58E S27 1/4 → S34</p> <p style="text-align: center;">2011</p>
64.70	Gulch, 60 lks. wide, drains SE.
85.618	The cor. of secs. 27, 28, 33 and 34.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 1°19'20" W., bet. secs. 27 and 28.
40.436	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S28 S27</p> <p style="text-align: center;">2011</p>
45.30	Top of ridge, bears SE. and NW.
77.00	Wash, 150 lks. wide, drains NW.
80.872	<p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <p style="text-align: center;">T25S R58E S21 S22 S28 S27</p> <p style="text-align: center;">2016</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°46'10" W., bet. secs. 22 and 27.</p>
42.688	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S22 1/4 — S27</p> <p style="text-align: center;">2016</p>
61.40	Gulch, 25 lks. wide, drains irregularly SW.
85.376	The cor. of secs. 21, 22, 27 and 28.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°47'30" W., bet. secs. 21 and 22.
32.50	Top of ridge, bears SE. and NW.
40.428	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.  Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.  T25S R58E 1/4 S21 S22  2011  Cor. is located on top right bank of ravine, 10 ft. wide, 10 ft. deep, drains NW.
52.20	Gulch, 45 lks. wide, drains irregularly W.
80.856	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T25S R58E S16 S15 S21 S22  2011  From this point, Cor. No. 4, Mineral Survey No. 4441, Mongolia lode, bears N. 82°40'10" W., 13.788 chs. dist., hereinafter described.
	From the cor. of secs. 14, 15, 22 and 23.
	N. 89°32'50" W., bet. secs. 15 and 22.
42.750	Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.  T25S R58E S15 1/4 — S22  2011

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Cor. is located on top of ridge, bears S. 50° E. and N. 50° W.
85.500	The cor. of secs. 15, 16, 21 and 22.
	N. 4°18'20" W., bet. secs. 15 and 16.
40.540	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.  Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.  T25S R58E 1/4 S16 S15  2016
81.080	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.  T25S R58E S 9 S10 S16 S15  2016
	From the cor. of secs. 10, 11, 14 and 15.  N. 89°20'20" W., bet. secs. 10 and 15.
39.50	Gulch, 15 lks. wide, drains irregularly NNE.
43.792	Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.  T25S R58E S10 1/4 — S15  2016
87.584	The cor. of secs. 9, 10, 15 and 16.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 14°47'50" E., bet. secs. 9 and 10.
41.811	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S 9 S10</p> <p style="text-align: center;">2016</p>
67.20	Gulch, 15 lks. wide, drains SSE.
83.622	<p>The cor. of secs. 3, 4, 9 and 10, perpetuated by James L. Marlett Jr., Nevada Professional Land Surveyor No. 13386, in 2003, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, with aluminum cap, 1 1/2 ins. diam., mkd. PLS 13386, with a limestone, 16x9x7 ins., lying loose alongside, mkd. with 5 notches on an edge and 3 notches on another edge, as recorded in Clark County Nevada, Corner Record 20030620.01342.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S 4 S 3 S 9 S10</p> <p style="text-align: center;">2011</p> <p>Insert the rebar inside and deposit the mkd. stone alongside the stainless steel post.</p>
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°01'40" W., bet. secs. 3 and 10.</p>
39.575	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>



DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T25S R58E S 3 1/4 — S10</p> <p>2011</p>
79.150	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 3°30'50" E., bet. secs. 3 and 4.</p>
13.20	Dirt road, 12 lks. wide, bears SE. and NW.
40.373	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p>T25S R58E 1/4 S 4   S 3</p> <p>2016</p> <p>From this point, Cor. No. 2, Mineral Survey No. 1865, Volcano lode, bears N. 1°48'30" E., 18.833 chs. dist., hereinafter described.</p> <p>From this same point, Cor. No. 4, Mineral Survey No. 1856, Lookout lode, bears N. 86°55'20" E., 34.530 chs. dist., hereinafter described.</p>
80.686	<p>Intersect the Sixth Standard Parallel South.</p> <p>Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <p>T24S R58E S33 — S 4   S 3 T25S R58E CC</p> <p>2016</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, the standard cor. of secs. 33 and 34, T. 24 S., R. 58 E., bears N. 89°50'10" E., 5.228 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 1/2 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.</p> <hr/> <p>The point for the N 1/4 sec. cor. of sec. 3, is on the Sixth Standard Parallel South and at midpoint in departure on the N. bdy. of sec. 3.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <p style="text-align: center;">T24S R58E</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">1/4 S 3 T25S R58E</p> <p style="text-align: center;">2021</p> <p>From this point, the standard 1/4 sec. cor. of sec. 34, T. 24 S., R. 58 E., bears N. 89°40'50" E., 5.178 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.</p> <hr/> <p>From the cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°52'30" E., bet. secs. 32 and 33.</p> <p>40.367 Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S32 S33</p> <p style="text-align: center;">2016</p> <p>80.734 Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: right;">T25S R58E</div> <div style="text-align: right;">S29 S28</div> <div style="text-align: right;">S32 S33</div> <div style="text-align: center;">2016</div>
	<div style="text-align: right;">From the cor. of secs. 27, 28, 33 and 34.</div> <div style="text-align: right;">S. 89°42'10" W., bet. secs. 28 and 33.</div>
39.50	Wash, 40 lks. wide, drains irregularly SE.
43.089	<div>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div style="text-align: right;">T25S R58E</div> <div style="text-align: right;">S28</div> <div style="text-align: right;">1/4 —</div> <div style="text-align: right;">S33</div> <div style="text-align: center;">2016</div>
86.178	<div>The cor. of secs. 28, 29, 32 and 33.</div> <div style="text-align: right;">N. 0°38'50" W., bet. secs. 28 and 29.</div>
4.90	Shoulder of spurs, sloping S. and E.
12.70	Shoulder of spurs, sloping NE. and N.
40.365	<div>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</div> <div style="text-align: right;">T25S R58E</div> <div style="text-align: right;">1/4</div> <div style="text-align: right;">S29 S28</div> <div style="text-align: center;">2016</div>
53.60	Gulch, 25 lks. wide, drains NE.
80.730	<div>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.</div> <div>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</div>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T25S R58E  S20 S21  <hr style="width: 50%; margin: 0 auto;"/> S29 S28    2016 </div>
	<hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°36'50" W., bet. secs. 21 and 28.</p>
8.90	Wash, 1 ch. wide, drains NW.
22.13	Wash, 1 ch. wide, drains WSW.
35.80	Singer Wash, 2 chs. wide, drains NW.
42.603	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <div style="text-align: center;"> T25S R58E  S21  1/4 ———  S28    2016 </div>
52.20	Top of ridge, bears SE. and NW.
76.50	Wash, 1 1/2 chs. wide, drains NW.
85.206	The cor. of secs. 20, 21, 28 and 29.
	<hr/> <p>N. 0°57'30" W., bet. secs. 20 and 21.</p>
32.40	Wash, 1 ch. wide, drains NNW.
40.368	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T25S R58E  1/4  S20 S21    2016 </div>
80.736	<p>Cor. is located in Singer Wash, 2 chs. wide, drains NW.</p> <p>Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S17 S16 S20 S21 2016</p>
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°31'50" W., bet. secs. 16 and 21.</p>
31.30	Wash, 2 chs. wide, drains NW.
40.50	Spur, slopes NW.
42.713	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S16 1/4 — S21 2016</p>
85.426	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>N. 6°09'30" W., bet. secs. 16 and 17.</p>
33.80	Wash, 3 chs. wide, drains W.
40.596	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S17 S16 2016</p> <p>From this point, Cor. No. 3, Mineral Survey No. 1854, Full Moon lode, bears S. 59°03'30" E., 16.968 chs. dist., hereinafter described.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From this same point, Cor. No. 1, Mineral Survey No. 4534, Idaho lode, bears S. 40°19'30" E., 13.637 chs. dist., hereinafter described.
40.90	Dirt road, 20 lks. wide, bears E. and W.
81.192	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.  <div style="text-align: center;"> T25S R58E  S 8   S 9  <hr style="width: 50%; margin: 0 auto;"/> S17   S16    2016 </div>
	From the cor. of secs. 9, 10, 15 and 16.  S. 89°27'50" W., bet. secs. 9 and 16.
8.80	Top of Table Mountain.
25.00	Top of spur, slopes NE. into saddle bears NE. and SW.
44.016	Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  <div style="text-align: center;"> T25S R58E  S 9  1/4 —  S16    2016 </div>
	From this point, Cor. No. 1, Mineral Survey No. 1854, Full Moon lode, bears S. 9°40'40" W., 34.738 chs. dist., hereinafter described.
88.032	The cor. of secs. 8, 9, 16 and 17.
	N. 13°01'50" E., bet. secs. 8 and 9.
41.429	Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S 8   S 9</p> <p style="text-align: center;">2016</p>
82.858	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S 5   S 4 S 8   S 9</p> <p style="text-align: center;">2016</p>
	<hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°09'00" W., bet. secs. 4 and 9.</p>
11.30	Gulch, 20 lks. wide, drains S.
39.535	<p>The 1/4 sec. cor. of secs. 4 and 9, monumented with a basalt stone (Record, limestone), 17x12x8 ins., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S 4 1/4 — S 9</p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°35'40" W., beginning new measurement.</p>
10.70	Dirt road, 15 lks. wide, bears SSE. and NNW.
18.90	Top of Table Mountain.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
51.158	The cor. of secs. 4, 5, 8 and 9.
	N. 11°08'50" E., bet. secs. 4 and 5.
41.138	Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T25S R58E 1/4 S 5   S 4  2016  Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.  From this point, Cor. No. 4, Mineral Survey No. 1865, Volcano lode, bears N. 65°15'20" E., 69.523 chs. dist., hereinafter described.  From this same point, Cor. No. 3, Mineral Survey No. 4597 A, East Side lode, bears S. 46°31'10" W., 16.794 chs. dist., hereinafter described.
61.70	Top of Table Mountain.
82.323	Intersect the Sixth Standard Parallel South.  Point for the closing cor. of secs. 4 and 5.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  T24S R58E S32  S 5   S 4 T25S R58E CC  2016  From this point, the standard cor. of secs. 32 and 33, T. 24 S., R. 58 E., bears S. 89°38'50" E., 4.689 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.



DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 82.575</p>	<p>The original closing cor. of secs. 4 and 5, monumented with a basalt stone, 27x14x10 ins., firmly set, projecting 10 ins. above the ground, mkd. with 4 notches on the E. edge and 1 notch visible on the W. edge. Add the marks AM and bury the mkd. stone in a mound of stone, 3 ft. base, 2 ft. high.</p> <hr/> <p>The point for the N 1/4 sec. cor. of sec. 4, is on the Sixth Standard Parallel South and is at midpoint in departure on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, and in a mound of stone, 3 ft. base, to top, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T24S R58E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 4 T25S R58E</p> <p style="text-align: center;">2021</p> <p>From this point, the standard 1/4 sec. cor. of sec. 33, T. 24 S., R. 58 E., bears N. 89°05'00" E., 5.020 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.</p> <p>from which accessories established by James L. Marlett Jr., Nevada Professional Land Surveyor No. 13386, in 2003, all monumented with rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground with aluminum cap, 1 1/2 ins. diam., mkd. RM PLS 13386, as recorded in Clark County Nevada, Corner Record 20030620.01341, each bears</p> <p style="margin-left: 40px;">N. 52°56' E., 153.4 lks. dist. N. 52°56' E., 302.9 lks. dist. S. 37°12' E., 148.2 lks. dist. S. 37°12' E., 305.2 lks. dist. S. 52°49' W., 151.6 lks. dist. S. 52°49' W., 302.6 lks. dist. N. 37°10' W., 152.5 lks. dist. N. 37°10' W., 301.1 lks. dist.</p> <hr/> <p>From the cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°28'10" E., bet. secs. 31 and 32.</p> <p>5.20 Wash, 2 chs. wide, drains SW.</p> <p>40.834 Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p>
--------------------------	--

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S31 S32</p> <p style="text-align: center;">2011</p>
48.30	Ridge, bears ENE. and WSW.
81.668	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S30 S29 S31 S32</p> <p style="text-align: center;">2011</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°35'20" W., bet. secs. 29 and 32.</p>
36.40	Gulch, 20 lks. wide, drains WSW.
43.117	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S29 1/4 — S32</p> <p style="text-align: center;">2016</p>
68.00	Wash, 4 chs. wide, drains SW.
82.80	Wash, 3 chs. wide, drains NNW.
86.234	The cor. of secs. 29, 30, 31 and 32.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°35'40" W., bet. secs. 30 and 31.
6.90	Wash, 2 chs. wide, drains WSW., broadening into alluvial fan, sloping W.
42.955	Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T25S R58E S30 1/4 — S31  2011
	Cor. is located in alluvial fan, sloping W.
84.525	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 29, 30, 31 and 32. N. 0°07'40" W., bet. secs. 29 and 30.
4.50	Wash, 3 chs. wide, drains W.
32.30	Top of ridge, bears NE. and SW.
40.532	Point selected for the witness cor. to the 1/4 sec. cor. of secs. 29 and 30.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.  WC T25S R58E 1/4 ↑ S30   S29  2011
40.833	Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner; located on face of large boulder where it is impractical to set a permanent monument.
62.80	Spur, slopes WSW.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
81.666	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original corner; located on face of rock ledge where it is impractical to set a permanent monument.
	From the cor. of secs. 20, 21, 28 and 29.
	N. 88°57'10" W., bet. secs. 20 and 29.
31.339	Intersect line 1-2, Mineral Survey No. 4525, Turk lode, at a point from which Cor. No. 1, hereinafter described, bears N. 52°08'20" W., 2.636 chs. dist.
42.753	Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.
	<div style="text-align: center;"> T25S R58E  S20  1/4 ———  S29    2016 </div>
43.280	Intersect line 3-4, Mineral Survey No. 4525, Sultan lode, at a point from which Cor. No. 3, hereinafter described, bears S. 32°07'40" E., 4.135 chs. dist.
85.506	The cor. of secs. 19, 20, 29 and 30.
	S. 87°34'10" W., bet. secs. 19 and 30.
0.756	Point selected for the witness cor. to the cor. of secs. 19, 20, 29 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;"> WC  T25S R58E  S19   S20  ——— ———  S30   S29    2011 </div>
38.00	Ridge, bears ENE. and WSW.
42.290	Point selected for the witness cor. to the 1/4 sec. cor. of secs. 19 and 30.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>WC T25S R58E S19 1/4 ← S30</p> <p>2011</p>
42.672	Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner; located on face of rock outcrop where it is impractical to set a permanent monument.
84.278	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.
	<hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 1°07'40" W., bet. secs. 19 and 20.</p>
31.00	Head of ravine, drains WSW.
40.841	<p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p>T25S R58E 1/4 S19 S20</p> <p>2011</p>
71.00	Ridge, bears ESE. and WNW.
81.682	<p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p>T25S R58E S18 S17 S19 S20</p> <p>2011</p>
	<hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 88°19'40" W., bet. secs. 17 and 20.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 22.20	Low spur, slopes N.
42.885	<p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S R58E S17 1/4 — S20</p> <p>2016</p> </div>
47.40	Wash, 8 chs. wide, drains NW.
51.80	Dirt road, 15 lks. wide, bears SSE. and NNW.
85.770	The cor. of secs. 17, 18, 19 and 20.
	<hr/>
	S. 88°39'50" W., bet. secs. 18 and 19.
38.20	Spur, slopes S. off top of mountain.
42.824	Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner; located on face of rock ledge, where it is impractical to set a permanent monument.
43.003	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T25S R58E S18 1/4 —→ S19</p> <p>2011</p> </div>
84.856	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 9°56'40" W., bet. secs. 17 and 18.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 41.456</p>	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with a limestone, 15x9x6 ins. (Record, 23x11x9 ins.), firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S18 S17</p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p>
<p>17.60</p>	<p>N. 0°28'30" E., beginning new measurement.</p>
<p>32.00</p>	<p>Singer Wash, 17 chs. wide, drains W.</p>
<p>40.136</p>	<p>Dirt road, 20 lks. wide, bears SE. and NW.</p> <p>The cor. of secs. 7, 8, 17 and 18, perpetuated by James L. Marlett Jr., Nevada Professional Land Surveyor No. 13386, in 2003, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, with aluminum cap, 1 1/2 ins. diam., mkd. 2003 PLS 13386, with a limestone, 15x8x6 ins., lying loose alongside, mkd. with 4 notches on an edge and 5 notches on another edge, as recorded in Clark County Nevada, Corner Record 20030620.01368.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S 7 S 8 S18 S17</p> <p style="text-align: center;">2011</p> <p>Insert the rebar inside and deposit the mkd. stone alongside the stainless steel post.</p>
<p>From the cor. of secs. 8, 9, 16 and 17.</p>	<p>N. 86°47'30" W., bet. secs. 8 and 17.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 43.962</p>	<p>The 1/4 sec. cor. of secs. 8 and 17, perpetuated by James L. Marlett Jr., Nevada Professional Land Surveyor No. 13386, in 2003, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, with aluminum cap, 1 1/2 ins. diam., mkd. 2003 PLS 13386, with a limestone, 14x12x5 ins. (Record, 18x9x5 ins.), lying loose alongside, mkd. 1/4 on a face, as recorded in Clark County Nevada, Corner Record 20030620.01369.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S R58E S 8 1/4 — S17</p> <p>2011</p> </div> <p>Insert the rebar inside and deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°35'10" W., beginning new measurement.</p>
<p>39.940</p>	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/>
	<p>N. 89°43'10" W., bet. secs. 7 and 18.</p>
<p>7.50</p>	<p>Dirt road, 20 lks. wide, bears SE. and NW.</p>
<p>40.026</p>	<p>The 1/4 sec. cor. of secs. 7 and 18, monumented with a limestone, 17x11x6 ins., firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. 1/4 on the N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S R58E S 7 1/4 — S18</p> <p>2011</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 89°49'40" W., beginning new measurement.</p>
<p>13.50</p>	<p>Dirt road, 12 lks. wide, bears ESE. and WNW.</p>



DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 40.223	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°09'00" E., bet. secs. 7 and 8.</p>
14.40	Enter wash, and S. channel, drains WNW.
40.456	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with a limestone, 26x9x8 ins., firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, mkd. 1/4 on the W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S 7   S 8</p> <p style="text-align: center;">2011</p> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°01'00" W., beginning new measurement.</p>
0.50	Leave wash, and N. channel, drains WSW.
40.303	<p>The cor. of secs. 5, 6, 7 and 8, perpetuated by James L. Marlett Jr., Nevada Professional Land Surveyor No. 13386, in 2003, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set in a mound of stone, 4 ft. diam., 1 ft. high, with aluminum cap, 1 1/2 ins. diam., mkd. 2003 PLS 13386, with a limestone, 27x10x6 ins. (Record, 28x15x9 ins.), lying loose alongside, mkd. with 5 notches on an edge and 5 notches on another edge, as recorded in Clark County Nevada, Corner Record 20030620.01370.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S 6   S 5 S 7   S 8</p> <p style="text-align: center;">2011</p> <p>Insert the rebar inside and deposit the mkd. stone alongside the stainless steel post.</p> <hr/>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the cor. of secs. 4, 5, 8 and 9. N. 88°26'40" W., bet. secs. 5 and 8.
49.00	Gulch, 20 lks. wide, drains WSW.
51.220	Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T25S R58E S 5 1/4 — S 8  2016
70.30	Dirt road, 12 lks. wide, bears SE. and NW.
87.00	Dirt road, 15 lks. wide, bears NE. and SW.
99.10	Dirt road, 15 lks. wide, bears SE. and NW.
102.440	The cor. of secs. 5, 6, 7 and 8.
	S. 89°09'00" W., bet. secs. 6 and 7.
23.60	Dirt road, 20 lks. wide, bears N. and S.
40.350	The 1/4 sec. cor. of secs. 6 and 7, monumented with a limestone, 27x15x11 ins., firmly set in a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, mkd. 1/4 on the N. face.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.  T25S R58E S 6 1/4 — S 7  2011  Deposit the mkd. stone alongside the stainless steel post.  N. 89°31'50" W., beginning new measurement.
40.411	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 15°55'10" E., bet. secs. 5 and 6.</p>
1.70	Dirt road, 15 lks. wide, bears ESE. and WNW.
40.442	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E 1/4 S 6   S 5  2016</p> <p>From this point, Cor. No. 4, Mineral Survey No. 4597 A, Washington lode, bears N. 86°19'40" E., 37.614 chs. dist., hereinafter described.</p>
56.40	Spur, slopes SE.
74.50	Ridge, bears E. and W.
81.713	<p>Intersect the Sixth Standard Parallel South.</p> <p>Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T24S R58E S31 S 6   S 5 T25S R58E CC  2016</p> <p>From this point, the standard cor. of secs. 31 and 32, T. 24 S., R. 58 E., bears S. 89°38'50" E., 5.771 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.</p>

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The point for the N 1/4 sec. cor. of sec. 5, is on the Sixth Standard Parallel South and at midpoint on the N. bdy. of sec. 5.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T24S R58E

1/4 S 5  
T25S R58E

2021

From this point, the standard 1/4 sec. cor. of sec. 32, T. 24 S., R. 58 E., bears S. 89°38'50" E., 5.230 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 5 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.

The point for the N 1/4 sec. cor. of sec. 6 is on the Sixth Standard Parallel South and at proportionate distance on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

T24S R58E

1/4 S 6  
T25S R58E

2016

From this point, the standard 1/4 sec. cor. of sec. 31, T. 24 S., R. 58 E., bears S. 89°38'50" E., 5.771 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 1/2 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of the Sixth Standard Parallel South, through Range 58 East, executed concurrently under Group No. 887.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 1854,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of the Survey Executed by  
U.S. Deputy Mineral Surveyor H.W. Newby in 1899


Full Moon lode

From Cor. No. 1, Mineral Survey No. 1854, Full Moon lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, with aluminum cap mkd. MS1854 1-FULL MOON OWENS PLS 2884, with a wood post, 3x3 ins., 3 ft. long, lying loose alongside, no marks visible, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T25S R58E  
S16



2011

Deposit the rebar and invert and reset the wood post alongside the stainless steel post.

Thence S. 16°21'20" E., on line 1-2, Mineral Survey No. 1854, Full Moon lode.

9.644

Cor. No. 2, Mineral Survey No. 1854, Full Moon lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, with aluminum cap mkd. MS1854 2-FULL MOON OWENS PLS 2884, with a wood post, 3x3 ins., 4 ft. long, lying loose alongside, mkd. 1854-2, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 1854,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="841 229 1094 435"> </div> <p data-bbox="922 469 987 489">2011</p> <p data-bbox="435 524 1352 576">Deposit the rebar and invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p data-bbox="435 631 1409 683">Thence S. 74°44'10" W., on line 2-3, Mineral Survey No. 1854, Full Moon lode.</p> <p data-bbox="302 707 367 727">8.00</p> <p data-bbox="435 707 1458 760">Dirt road, 20 lks. wide, bears SE. and NW. in wash, 2 chs. wide, drains NW.</p> <p data-bbox="285 786 383 806">22.793</p> <p data-bbox="435 786 1466 995">Cor. No. 3, Mineral Survey No. 1854, Full Moon lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 1/2 in. diam., 18 ins. long, firmly set in mound of stone, 3 ft. diam., 1 ft. high, with a wood post, 4x4 ins., 4 ft. long, lying loose alongside, no marks visible, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p data-bbox="435 1022 740 1042">At the corner point</p> <p data-bbox="435 1074 1450 1175">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="841 1201 1094 1292"> </div> <p data-bbox="922 1318 987 1338">2011</p> <p data-bbox="435 1372 1433 1425">Deposit the rebar and invert and reset the wood post alongside the stainless steel post.</p> <hr/> <p data-bbox="435 1479 1409 1532">Thence N. 16°10'00" W., on line 3-4, Mineral Survey No. 1854, Full Moon lode.</p> <p data-bbox="302 1558 367 1578">3.90</p> <p data-bbox="435 1558 1092 1578">Dirt road, 12 lks. wide, bears E. and NW.</p> <p data-bbox="302 1610 367 1630">5.80</p> <p data-bbox="435 1610 1385 1663">Dirt road, 40 lks. wide, bears NE. and SW., in wash, 2 chs. wide, drains SW.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 1854,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 9.167</p>	<p>Cor. No. 4, Mineral Survey No. 1854, Full Moon lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, with aluminum cap mkd. MS1854 4-FULL MOON OWENS PLS 2884, with a wood post, 3x3 ins., 4 ft. long, lying loose alongside, no marks visible, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="812 674 1088 899"> </div> <p>Deposit the rebar and invert and reset the wood post alongside the stainless steel post.</p>
<p>22.758</p>	<p>Thence N. 73°32'00" E., on line 4-1, Mineral Survey No. 1854, Full Moon lode.</p> <p>Cor. No. 1, Mineral Survey No. 1854, Full Moon lode, and point of beginning.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1856, T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Mineral Surveyor H.W. Newby 1899</p> <hr/> <p>Lookout lode</p> <p>From Cor. No. 5, Mineral Survey No. 1856, Mountain Top lode, on line 3-4, Mineral Survey No. 1856, Lookout lode.</p> <p>Thence N. 72°26'50" W., on a portion of line 3-4, Mineral Survey No. 1856, Lookout lode.</p>
<p>16.710</p>	<p>Cor. No. 4, Mineral Survey No. 1856, Lookout lode, determined at the center of a mound of stone, 3 ft. diam., 1 ft. high, with a wood post, 4x4 ins., 4 ft. long, lying loose alongside, mkd. 4 1856.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1856,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="857 329 1065 461"> <p>T25S / MS1856 R58E / LO S 3 / 4</p> </div> <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence N. 17°54'50" E., on line 4-1, Mineral Survey No. 1856, Lookout lode.</p> <p>2.50 Dirt road, 12 lks. wide, bears SE. and NW.</p> <p>4.20 Dirt road, 12 lks. wide, bears E. and W.</p> <p>9.00 Gulch, 30 lks. wide, drains SE.</p> <p>9.449 Cor. No. 1, Mineral Survey No. 1856, Lookout lode, determined at the center of a mound of stone, 3 ft. diam., 1 ft. high, with a wood post, 4x4 ins., 4 ft. long, lying loose alongside, mkd. 1 1865.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="886 1208 1102 1381"> <p>T25S R58E S 3 1 LO MS1856</p> </div> <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence S. 71°34'30" E., on line 1-2, Mineral Survey No. 1856, Lookout lode.</p> <p>7.00 Gulch, 25 lks. wide, drains ENE.</p> <p>22.40 Dirt road, 12 lks. wide, bears S. 20° E. and N. 20° W.</p>
--------	--




DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1856,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS  
23.101

Cor. No. 2, Mineral Survey No. 1856, Lookout lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. 2 1865.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



2011

Invert and reset the mkd. wood post alongside the stainless steel post.

Thence S. 17°39'00" W., on line 2-3, Mineral Survey No. 1856, Lookout lode.


1.00 Dirt road, 12 lks. wide, bears SE. and NW.

8.30 Dirt road, 12 lks. wide, bears SE. and NW.

9.158 Cor. No. 3, Mineral Survey No. 1856, Lookout lode, on line 5-6, Mineral Survey 1856, Mountain Top lode, determined at the center of a mound of stone, 4 ft. diam., 2 ft. high, with a wood post, 4x4 ins., 4 ft. long, lying loose alongside, mkd. 3 1865.

At the corner point



Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



2011

Invert and reset the mkd. wood post alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1856,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Mountain Top lode
	From Cor. No. 3, Mineral Survey No. 1856, Lookout lode.
	Thence S. 72°28'30" E., on a portion of line 5-6, Mineral Survey No. 1856, Mountain Top lode.
0.60	Dirt road, 12 lks. wide, bears SE. and NW.
16.462	Cor. No. 6, Mineral Survey No. 1856, Mountain Top lode, determined at the center of a mound of stone, 2 1/2 ft. diam., 1 ft. high, with a wood post, 4x4 ins., 3 ft. long, lying loose alongside, mkd. 6 1856.
	At the corner point
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.
	 <p>A diagram showing a corner point labeled '6'. A line segment labeled 'MS1856' runs from the bottom left towards the corner. Another line segment runs from the corner towards the top right, labeled 'T25S' and 'R58E'. The corner itself is labeled '6' and 'S 3'.</p>
	2011
	Deposit the mkd. wood post in a mound of stone, 3 ft. base, 1 ft. high, N. of cor.
	Thence S. 17°46'50" W., on line 6-7, Mineral Survey No. 1856, Mountain Top lode.
9.274	Cor. No. 7, Mineral Survey No. 1856, Mountain Top lode, determined at the center of a mound of stone, 3 ft. diam., 1 1/2 ft. high. This mound of stone correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	 <p>A diagram showing a corner point labeled '7'. A line segment labeled 'MS1856' runs from the bottom left towards the corner. Another line segment runs from the corner towards the top right, labeled 'T25S' and 'R58E'. The corner itself is labeled '7' and 'S 3'.</p>
	2011
	Thence N. 72°31'40" W., on line 7-8, Mineral Survey No. 1856, Mountain Top lode.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 1856,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

2.60

Gulch, 50 lks. wide, drains SE.

22.886

Cor. No. 8, Mineral Survey No. 1856, Mountain Top lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, set in a mound of stone, 3 ft. diam., 1 ft. high, no marks visible. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T25S  
R58E  
S 3

M T  
MS1856  
8

2011

Invert and reset the wood post alongside the stainless steel post.

Thence N. 17°43'30" E., on line 8-5, Mineral Survey No. 1856, Mountain Top lode.

9.358

Cor. No. 5, Mineral Survey No. 1856, Mountain Top lode, on line 3-4, Mineral Survey No. 1856, Lookout lode, determined at the center of a mound of stone, 3 ft. diam., 1 1/2 ft. high, with a wood post, 4x4 ins., 4 ft. long, lying loose alongside, mkd. 5 1856.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

MS1856  
LO

T25S  
R58E  
S 3

5  
M T  
MS1856

2011

Invert and reset the mkd. post alongside the stainless steel post.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 1865,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Reestablishment of the Survey Executed by  
U.S. Deputy Mineral Surveyor H.W. Newby 1899

Volcano lode

From Cor. No. 1, Mineral Survey No. 1865, Volcano lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, with no marks visible. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T25S R58E

S 4

1  
VO  
MS1865

2011

Invert and reset the wood post alongside the stainless steel post.

Thence S. 0°02'50" E., on line 1-2, Mineral Survey No. 1865, Volcano lode.

3.60 Gulch, 60 lks. wide, drains irregularly SE.

9.425 Point for Cor. No. 2, Mineral Survey No. 1865, Volcano lode, determined by parallel end lines and sidelines; there is no remaining evidence of the original corner.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.

MS1865 T25S  
VO R58E  
2 S 4

2021

Thence S. 89°54'50" W., on line 2-3, Mineral Survey No. 1865, Volcano lode.

22.646 Cor. No. 3, Mineral Survey No. 1865, Volcano lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. 3-1865.

At the corner point

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 1865,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T25S	MS1865
R58E	VO
S 4	3

2011

Invert and reset the mkd. wood post alongside the stainless steel post.

Thence N. 0°02'50" W., on line 3-4, Mineral Survey No. 1865, Volcano lode.

9.425

Cor. No. 4, Mineral Survey No. 1865, Volcano lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, mkd. 4-1865.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T25S	
R58E	4
S 4	VO
	MS1865

2011

Invert and reset the mkd. wood post alongside the stainless steel post.

Thence N. 89°54'50" E., on line 4-1, Mineral Survey No. 1865, Volcano lode.

22.646

Cor. No. 1, Mineral Survey No. 1865, Volcano lode, and point of beginning.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 2109,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS


Reestablishment of the Survey Executed by  
U.S. Deputy Mineral Surveyor H.K. Wheeler in 1903

Carbinet No. 2 lode

From Cor. No. 1, Mineral Survey No. 2109, Carbinet No. 2 lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, no marks visible. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 1/2 ft. base, to top, with brass cap mkd.




Invert and reset the wood post alongside the stainless steel post.

Thence S. 41°33'30" E., on line 1-2, Mineral Survey No. 2109, Carbinet No. 2 lode.

- 9.60 Top of ridge, bears NE. and SW.
- 21.60 Dirt road, 12 lks. wide, bears NE. and SW.
- 22.102 Point for Cor. No. 2, Mineral Survey No. 2109, Carbinet No. 2 lode, determined by Grant Boundary adjustment bet. Cor. Nos. 1 and 3; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.



Thence S. 48°26'30" W., on line 2-3, Mineral Survey No. 2109, Carbinet No. 2 lode.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 2109,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 9.092</p>	<p>Point for Cor. No. 3, Mineral Survey No. 2109, Carbinet No. 2 lode, determined at the extension of the line bet. Cor. No. 4, Mineral Survey No. 2109, Carbinet No. 2 lode and Cor. No. 2, Mineral Survey No. 4168, Tiffin lode, hereinafter described, and at record distance from Cor. No. 2, Mineral Survey No. 4168, Tiffin lode; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="861 564 1069 665"> </div> <div data-bbox="861 685 1021 745"> <p>T25S R58E S18</p> </div> <div data-bbox="909 766 973 806"> <p>2011</p> </div> <hr/> <p>Thence N. 41°34'40" W., on line 3-4, Mineral Survey No. 2109, Carbinet No. 2 lode.</p> <p>2.480 Cor. No. 2, Mineral Survey No. 4168, Tiffin lode, hereinafter described.</p> <p>Continue on line 3-4, Mineral Survey No. 2109, Carbinet No. 2 lode, identical with a portion of line 1-2, Mineral Survey No. 4168, Tiffin lode.</p> <p>22.099 Cor. No. 4, Mineral Survey No. 2109, Carbinet No. 2 lode, monumented with a wood post, 4x4 ins., 2 ft. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, no marks visible. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="813 1451 1117 1632"> </div> <div data-bbox="909 1653 973 1693"> <p>2011</p> </div> <p>Invert and reset the wood post alongside the stainless steel post.</p>
-------------------------	--


DEPENDENT RESURVEY OF MINERAL SURVEY NO. 2109,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Thence N. 48°24'50" E., on line 4-1, Mineral Survey No. 2109, Carbinet No. 2 lode.</p>
9.101	<p>Cor. No. 1, Mineral Survey No. 2109, Carbinet No. 2 lode, and point of beginning.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4168, TPS. 25 S., RS. 57 AND 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a portion of the Survey Executed by U.S. Mineral Surveyor C.E. McCarthy in 1913</p> <hr/> <p>Tiffin lode</p> <p>From Cor. No. 2, Mineral Survey No. 4168, Tiffin lode, on line 3-4, Mineral Survey No. 2109, Carbinet No. 2 lode, monumented with the remains of a wood post, 4x4 ins., 12 ins. long, firmly set, 12 ins. in the ground, no marks visible. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="795 1042 1088 1205"> </div> <p>2011</p> <p>Deposit the wood post remains alongside the stainless steel post.</p> <p>Thence S. 74°26'10" W., on line 2-3, Mineral Survey No. 4168, Tiffin lode.</p> <p>0.60 Dirt road, 12 lks. wide, bears NE. and SW.</p> <p>3.20 Northerly edge of wash, 20 chs. wide, drains SW.</p> <p>10.106 Cor. No. 3, Mineral Survey No. 4168, Tiffin lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. T 3 4168.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4168,  
TPS. 25 S., RS. 57 AND 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS



T25S R58E  
S18

2011

Invert and reset the mkd. wood post alongside the stainless steel post.


Thence N.  $41^{\circ}39'50''$  W., on line 3-4, Mineral Survey No. 4168, Tiffin lode.

7.320 Intersect the line bet. secs. 13 and 18 on the W. bdy. of the Tp., at a point from which the  $1/4$  sec. cor. of secs. 13 and 18, hereinbefore described, bears S.  $1^{\circ}33'10''$  E., 20.003 chs. dist.

22.772 Cor. No. 4, Mineral Survey No. 4168, Tiffin lode, determined at the center of a mound of stone, 3 ft. diam., 2 ft. high, with a wood post, 4x4 ins., 4 ft. long, lying loose alongside, mkd. T 4 4168.

At the corner point

Set a stainless steel post, 28 ins. long, 2  $1/2$  ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4  $1/2$  ft. base, to top, with brass cap mkd.



2011

Invert and reset the mkd. wood post alongside the stainless steel post.

Thence N.  $74^{\circ}34'50''$  E., on line 4-1, Mineral Survey No. 4168, Tiffin lode.


10.156 Point for Cor. No. 1, Mineral Survey No. 4168, Tiffin lode, determined at the extension of the line bet. Cor. No. 2, Mineral Survey No. 4168, Tiffin lode and Cor. No. 4, Mineral Survey No. 2109, Carbinet No. 2 lode, hereinbefore described, and at record distance from Cor. No. 4, Mineral Survey No. 2109, Carbinet No. 2 lode; a wood post, 4x4 ins., 4 ft. long, was found lying loose on the ground, no marks visible, original position indeterminate.

Set a brass tablet, 3  $1/4$  ins. diam., 3  $1/2$ -in. stem, cemented in a drill hole in solid rock, with top mkd.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4168,  
TPS. 25 S., RS. 57 AND 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T25S R57E  
S13



2011

Bury the wood post in a mound of stone, 3 ft. base, 1 ft. high,  
N. of cor.

Thence S.  $41^{\circ}34'40''$  E., on a portion of line 1-2, Mineral Survey  
No. 4168, Tiffin lode.

0.148 Intersect the W. bdy. of the Tp., at a point from which the cor.  
of secs. 7, 12, 13 and 18, hereinbefore described, bears  
N.  $1^{\circ}33'10''$  W., 7.507 chs. dist.

3.109 Cor. No. 4, Mineral Survey No. 2109, Carbinet No. 2 lode,  
hereinbefore described.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4322,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA


Reestablishment of Portions of the Survey Executed by  
U.S. Mineral Surveyor C.E. McCarthy in 1917

Anchor lode

From Cor. No. 1, Mineral Survey No. 4322, Anchor lode, identical  
with Cor. No. 3, Mineral Survey No. 4322, Gulch lode, monumented  
with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a  
mound of stone, 2 ft. diam., 1 ft. high, mkd. A 1 4322 G 3 4322.

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented  
in a drill hole in solid rock, with top mkd.



2011

Reset the mkd. wood post in a mound of stone, 3 ft. base, 1 ft.  
high, S. of cor.

Thence S.  $16^{\circ}44'00''$  E., on a portion of line 1-2, Mineral Survey  
No. 4322, Anchor lode, identical in part with line 2-3, Mineral  
Survey No. 4322, Gulch lode.


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4322,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
4.341	The N.W. Cor. of Santa Clara lode (unsurveyed).
8.863	Intersect the line bet. secs. 23 and 26, at a point from which the 1/4 sec. cor. of secs. 23 and 26, hereinbefore described, bears S. 89°40'40" W., 19.062 chs. dist.
10.071	Cor. No. 2, Mineral Survey No. 4322, Gulch lode.  Continue measurement on a portion of line 1-2, Mineral Survey No. 4322, Anchor lode.
13.583	Cor. No. 4, Mineral Survey No. 4322, Anchor No. 2 lode.  From Cor. No. 4, Mineral Survey No. 4322, Anchor lode, identical with Cor. No. 1, Mineral Survey No. 4322, Anchor No. 3 lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 4 ft. high, mkd. A 4 4322 A3 1 4322.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.  <div data-bbox="812 956 1104 1205" data-label="Diagram"> </div> Invert and reset the mkd. wood post alongside the stainless steel post.  Thence N. 75°37'40" E., on a portion of line 4-1, Mineral Survey No. 4322, Anchor lode.
0.250	Cor. No. 2, Mineral Survey No. 4322, Monitor lode.  Topmast lode  From Cor. No. 3, Mineral Survey No. 4322, Anchor No. 2 lode, on line 1-2, Mineral Survey No. 4322, Topmast lode.  Thence S. 16°43'30" E., on a portion of line 1-2, Mineral Survey No. 4322, Topmast lode.
9.085	Cor. No. 2, Mineral Survey No. 4322, Topmast lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, mkd. TM 2 4322.  At the corner point

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4322,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.



MS4322 TO 2 T25S R58E S26

2011

Invert and reset the mkd. wood post alongside the stainless steel post.


Thence S. 73°18'50" W., on line 2-3, Mineral Survey No. 4322, Topmast lode.

6.40 Gulch, 45 lks. wide, drains SE.

9.072 Cor. No. 3, Mineral Survey No. 4322, Topmast lode, identical with Cor. No. 2, Mineral Survey No. 4322, Anchor No. 4 lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. TM 3 4322 A4 2 4322.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



MS4322 AN 4 TO 2 MS4322 TO 3 T25S R58E S26

2011



Invert and reset the mkd. wood post alongside the stainless steel post.

Anchor No. 2 lode

From Cor. No. 4, Mineral Survey No. 4322, Anchor No. 2 lode, on line 1-2, Mineral Survey No. 4322, Anchor lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, mkd. A2 4 4322.

At the corner point


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4322,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>  <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <p>Thence N. 84°03'10" E., on line 4-1, Mineral Survey No. 4322, Anchor No. 2 lode.</p>
9.140	<p>Cor. No. 1, Mineral Survey No. 4322, Anchor No. 2 lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. A2 1 4322.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>  <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <p>Thence S. 16°35'40" E., on line 1-2, Mineral Survey No. 4322, Anchor No. 2 lode.</p>
10.80	<p>Gulch, 30 lks. wide, drains NE.</p>
22.700	<p>Cor. No. 2, Mineral Survey No. 4322, Anchor No. 2 lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, mkd. A2 2 4322.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4322,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.



MS4322  
AN 2  
2

T25S  
R58E  
S26

2011

Invert and reset the mkd. wood post alongside the stainless steel post.


Thence S. 83°46'50" W., on line 2-3, Mineral Survey No. 4322, Anchor No. 2 lode.

9.121

Cor. No. 3, Mineral Survey No. 4322, Anchor No. 2 lode, on line 1-2, Mineral Survey No. 4322, Topmast lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. A2 3 4322.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.



MS4322  
AN 2  
3

TO  
MS4322

T25S  
R58E  
S26

2011

Invert and reset the mkd. wood post alongside the stainless steel post.



Anchor No. 3 lode

From Cor. No. 3, Mineral Survey No. 4322, Anchor No. 3 lode, identical with Cor. No. 4, Mineral Survey No. 4322, Anchor No. 4 lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. A3 3 4322 A4 4 4322.


At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4322,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	 <p style="text-align: center;">2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <p>Thence N. 16°43'10" W., on line 3-4, Mineral Survey No. 4322, Anchor No. 3 lode.</p> <p>7.00 Gulch, 30 lks. wide, drains NNE.</p> <p>19.162 Intersect the line bet. secs. 23 and 26, at a point from which the 1/4 sec. cor. of secs. 23 and 26, hereinbefore described, bears S. 89°40'40" W., 0.153 chs. dist.</p> <p>21.00 Gulch, 25 lks. wide, drains ENE.</p> <p>22.707 Cor. No. 4, Mineral Survey No. 4322, Anchor No. 3 lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. A3 4 4322.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p>  <p style="text-align: center;">2011</p> <p>Deposit the mkd. wood post alongside the stainless steel post.</p> <p>Thence N. 73°20'00" E., on line 4-1, Mineral Survey No. 4322, Anchor No. 3 lode.</p>
9.090	<p>Cor. No. 1, Mineral Survey No. 4322, Anchor No. 3 lode, identical with Cor. No. 4, Mineral Survey No. 4322, Anchor lode.</p>


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4322,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">Anchor No. 4 lode</p> <p>From Cor. No. 2, Mineral Survey No. 4322, Anchor No. 4 lode, identical with Cor. No. 3, Mineral Survey No. 4322, Topmast lode.</p> <p>Thence S. 73°18'50" W., on line 2-3, Mineral Survey No. 4322, Anchor No. 4 lode.</p> <p>9.059 Cor. No. 3, Mineral Survey No. 4322, Anchor No. 4 lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, mkd. A4 3 4322.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p>2011</p> </div> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p>
	<p>Thence N. 16°39'20" W., on line 3-4, Mineral Survey No. 4322, Anchor No. 4 lode.</p>
11.50	Gulch, 25 lks. wide, drains SSW.
22.716	<p>Cor. No. 4, Mineral Survey No. 4322, Anchor No. 4 lode, identical with Cor. No. 3, Mineral Survey No. 4322, Anchor No. 3 lode.</p>
	<p style="text-align: center;">Monitor lode</p> <p>From Cor. No. 2, Mineral Survey No. 4322, Monitor lode, on line 4-1, Mineral Survey No. 4322, Anchor lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. M 4 4322.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>



DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4322,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS



T25S MS4322  
R58E MO  
S23 2

AN  
MS4322

2011

Invert and reset the mkd. wood post alongside the stainless steel post.

Thence N. 15°14'40" W., on line 2-3, Mineral Survey No. 4322, Monitor lode.

17.065

Cor. No. 3, Mineral Survey No. 4322, Monitor lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. M 3 4322.

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.



T25S  
R58E MO  
S23 MS4322

2011

Deposit the mkd. wood post in a mound of stone, 3 ft. base, 1 ft. high, S. of cor.

Thence N. 73°14'20" E., on line 3-4, Mineral Survey No. 4322, Monitor lode.


9.085

Cor. No. 4, Mineral Survey No. 4322, Monitor lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. M 4 4322.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.


T25S R58E  
S23





4  
MO  
MS4322

2011

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4322,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Invert and reset the mkd. wood post alongside the stainless steel post.</p>
	<hr/>
	<p>Thence S. 15°10'20" E., on line 4-1, Mineral Survey No. 4322, Monitor lode.</p>
16.943	<p>Intersect line 3-4, Mineral Survey No. 4322, Gulch lode, at a point from which Cor. No. 3, identical with Cor. No. 1, Mineral Survey No. 4322, Anchor lode, bears S. 47°32'20" W., 0.299 chs. dist.</p>
17.081	<p>Cor. No. 1, Mineral Survey No. 4322, Monitor lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 4 1/2 ft. diam., 3 ft. high, mkd. M 1 4322.</p>
	<p>At the corner point</p>
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p>
	
	<p>2011</p>
	<p>Invert and reset the mkd. wood post in a mound of stone, 5 ft. base, 2 ft. high, N. of cor.</p>
	<hr/>
	<p>Gulch lode</p>
	<p>From Cor. No. 3, Mineral Survey No. 4322, Gulch lode, identical with Cor. No. 1, Mineral Survey No. 4322, Anchor lode.</p>
	<p>Thence N. 47°32'20" E., on line 3-4, Mineral Survey No. 4322, Gulch lode.</p>
0.299	<p>Intersect line 4-1, Mineral Survey No. 4322, Monitor lode, at a point from which Cor. No. 1 bears S. 15°10'20" E., 0.138 chs. dist.</p>
22.744	<p>Cor. No. 4, Mineral Survey No. 4322, Gulch lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. G 4 4322.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4322,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="852 241 1031 449"> <p>T25S R58E S23</p>  <p>2011</p> </div> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence S. 16°40'20" E., on line 4-1, Mineral Survey No. 4322, Gulch lode.</p> <p>4.40 North side of wash, drains NE. and S., edge of mine tailings.</p> <p>5.50 South side of wash.</p> <p>6.40 Dirt road, 12 lks. wide, bears ENE. and WSW.</p> <p>10.122 Cor. No. 1, Mineral Survey No. 4322, Gulch lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, set in a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, mkd. G 1 4322.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="820 1113 1079 1318">  <p>2011</p> </div> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence S. 47°38'40" W., on line 1-2, Mineral Survey No. 4322, Gulch lode.</p> <p>13.241 Intersect the north side line of Santa Clara lode (unsurveyed), at a point from which the N.E. Cor. of Santa Clara lode (unsurveyed), bears N. 84°06'00" E., 6.670 chs. dist.</p> <p>20.981 Intersect the line bet. secs. 23 and 26, at a point from which the cor. of secs. 23, 24, 25 and 26, hereinbefore described, bears N. 89°40'40" E., 22.031 chs. dist.</p> <p>22.712 Point for Cor. No. 2, Mineral Survey No. 4322, Gulch lode, on line 1-2, Mineral Survey No. 4322, Anchor lode, at proportionate distance; there is no remaining evidence of the original corner.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4322,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.



2011

from which

A chiseled X followed by the letters BO, mkd. on a W. facing rock wall, bears S. 50°38' E., 37.1 lks. dist.

Santa Clara lode (unsurveyed)


The location of Santa Clara lode (unsurveyed) is based on the 1917 survey executed by C.E. McCarthy as shown on the official plat of Mineral Survey No. 4322, approved August 24, 1917.

From the intersection of the north side line of Santa Clara lode (unsurveyed) and line 1-2, Mineral Survey No. 4322, Gulch lode.

From this point, the N.E. Cor., Santa Clara lode (unsurveyed), bears N. 84°06'00" E., 6.670 chs. dist., monumented with a 4x4 wood post, 3 1/2 ft. long, loosely set in a mound of stone, no marks visible. This is accepted as the best available evidence of the position of the claim corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



2011

Deposit the wood post inverted alongside stainless steel post.

From this same point, Cor. No. 2, Mineral Survey No. 4322, Gulch lode, bears S. 47°38'40" W., 9.471 chs. dist.


Thence S. 84°06'00" W., on the north side line of Santa Clara lode (unsurveyed).

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4322,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS  
8.694

Point for the N.W. Cor. of Santa Clara lode (unsurveyed), on line 2-3, Mineral Survey No. 4322, Gulch lode, identical with a portion of line 1-2, Mineral Survey No. 4322, Anchor lode, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.



2021

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4345,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by  
U.S. Mineral Surveyor C.H. Fenner in 1917

Porter lode

From the true point for Cor. No. 1, Mineral Survey 4345, Porter lode, identical with Cor. No. 4, Mineral Survey No. 4345, Prospect lode, determined at intersection of the extension of the line bet. Cor. No. 4 and the witness cor. on line 4-1, Mineral Survey No. 4345, Porter lode, and the line bet. Cor. No. 2 and the witness cor. on line 1-2, Mineral Survey No. 4345, Porter lode, identical with Cor. No. 3 and line 3-4, Mineral Survey No. 4345, Prospect lode.

Point is located on cliff face.

Thence S. 38°06'50" W., on line 1-2, Mineral Survey No. 4345, Porter lode, identical with line 3-4, Mineral Survey No. 4345, Prospect lode.

0.669

The witness cor. to Cor. No. 1, Mineral Survey No. 4345, Porter lode, identical with Cor. No. 4, Mineral Survey No. 4345, Prospect lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, no marks visible. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4345,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="841 237 1117 499"> <p>WC T25S R58E S14 POR 1 MS4345 PROS MS4345 2011</p> </div> <p>Deposit the wood post alongside the stainless steel post.</p> <hr/> <p>Thence S. 38°06'50" W., continuing on line 1-2, Mineral Survey No. 4345, Porter lode, identical with line 3-4, Mineral Survey No. 4345, Prospect lode, beginning new measurement.</p> <p>11.00 N. edge of gulch, 30 lks. wide, drains NE.</p> <p>13.386 Intersect the line bet. secs. 14 and 23, at a point from which the 1/4 sec. cor. of secs. 14 and 23, hereinbefore described, bears N. 89°37'30" E., 18.027 chs. dist.</p> <p>17.20 Gulch, 30 lks. wide, drains NE.</p> <p>22.105 Cor. No. 2, Mineral Survey No. 4345, Porter lode, identical with Cor. No. 3, Mineral Survey No. 4345, Prospect lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 1/2 ft. high, mkd. P 2 4345.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="841 1225 1133 1518"> <p>PO MS4345 2 PROS 3 MS4345 T25S R58E S23 2011</p> </div>
<p>1.50</p>	<p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence N. 58°17'00" W., on line 2-3, Mineral Survey No. 4345, Porter lode.</p> <p>Gulch, 40 lks. wide, drains irregularly NE.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4345,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA



<p>CHAINS 9.011</p>	<p>Cor. No. 3, Mineral Survey No. 4345, Porter lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. P 3 4345.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <div data-bbox="836 480 1096 623"> <p>T25S R58E S23</p> <p>PO 3 MS4345</p> </div> <p>2011</p> <p>Invert and reset the mkd. wood post in a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p> <hr/> <p>Thence N. 37°48'20" E., on line 3-4, Mineral Survey No. 4345, Porter lode.</p> <p>0.50 Gulch, 30 lks. wide, drains E.</p> <p>2.592 Intersect the line bet. secs. 14 and 23, at a point from which the cor. of secs. 14, 15, 22 and 23, hereinbefore described, bears S. 89°37'30" W., 13.538 chs. dist.</p> <p>22.719 Cor. No. 4, Mineral Survey No. 4345, Porter lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 3 ft. high, mkd. P 4 4345.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="860 1318 1063 1481"> <p>T25S R58E S14</p> <p>4 PO MS4345</p> </div> <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence S. 58°32'20" E., on line 4-1, Mineral Survey No. 4345, Porter lode.</p>
-------------------------	---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4345,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 8.809</p>	<p>The witness cor. to Cor. No. 1, Mineral Survey No. 4345, Porter lode, identical with Cor. No. 4, Mineral Survey No. 4345, Prospect lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 4 ft. base, 2 1/2 ft. high, no marks visible. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="828 584 1088 846"> </div> <p>Invert and reset the original wood post alongside the stainless steel post.</p> <hr/> <p>Thence S. 58°32'20" E., continuing on line 4-1, Mineral Survey No. 4345, Porter lode, beginning new measurement.</p> <p>0.329 True Point for Cor. No. 1, Mineral Survey No. 4345, Porter lode, identical with Cor. No. 4, Mineral Survey No. 4345, Prospect lode, and point of beginning.</p> <hr/> <p style="text-align: center;">Prospect lode</p> <p>From the true point for Cor. No. 4, Mineral Survey No. 4345, Prospect lode, identical with Cor. No. 1, Mineral Survey No. 4345, Porter lode.</p> <p>Thence S. 58°30'40" E., on line 4-1, Mineral Survey No. 4345, Prospect lode.</p> <p>6.70 Gulch, 30 lks. wide, drains irregularly E.</p> <p>9.136 Cor. No. 1, Mineral Survey No. 4345, Prospect lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, mkd. P 1 4345.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
-------------------------	---



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4345,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	 <p>PROS MS4345</p> <p>1</p> <p>T25S R58E S14</p> <p>2011</p>
	<p>Invert and reset the mkd. wood post alongside the stainless steel post.</p>
	<hr/> <p>Thence S. 37°56'10" W., on line 1-2, Mineral Survey No. 4345, Prospect lode.</p>
7.874	<p>Intersect the line bet. secs. 14 and 23, at a point from which the 1/4 sec. cor. of secs. 14 and 23, hereinbefore described, bears N. 89°37'30" E., 6.402 chs. dist.</p>
9.747	<p>Cor. No. 5, Mineral Survey No. 4345, Palace lode.</p>
19.117	<p>Intersect line 3-4, Mineral Survey No. 4345, Palace lode, at a point from which Cor. No. 4, bears N. 35°15'10" W., 4.484 chs. dist.</p>
22.733	<p>Cor. No. 2, Mineral Survey No. 4345, Prospect lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 1/2 ft. high, mkd. P 2 4345.</p>
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 1/2 ft. base, to top, with brass cap mkd.</p>
	 <p>MS4345 PROS</p> <p>2</p> <p>T25S R58E S23</p> <p>2011</p>
	<p>Invert and reset the mkd. wood post alongside the stainless steel post.</p>
	<hr/> <p>Thence N. 58°43'00" W., on line 2-3, Mineral Survey No. 4345, Prospect lode.</p>
9.210	<p>Cor. No. 3, Mineral Survey No. 4345, Prospect lode, identical with Cor. No. 2, Mineral Survey No. 4345, Porter lode.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4345,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA


## CHAINS

## Palace lode

From Cor. No. 5, Mineral Survey No. 4345, Palace lode, on line 1-2, Mineral Survey No. 4345, Prospect lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 2 1/2 ft. diam., 2 ft. high, mkd. PA 5 4345.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.



Invert and reset the mkd. wood post alongside the stainless steel post.

Thence S. 35°58'40" E., on line 5-6, Mineral Survey No. 4345, Palace lode.


12.253 Intersect line 2-3, Mineral Survey No. 4345, Promintory lode, at a point from which Cor. No. 2, bears S. 14°58'00" W., 1.059 chs. dist.

12.873 Intersect line 1-2, Mineral Survey No. 4345, Promintory lode, at a point from which Cor. No. 2, bears S. 50°45'30" W., 0.824 chs. dist.

14.766 Cor. No. 6, Mineral Survey No. 4345, Palace lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 2 ft. diam., 2 ft. high, mkd. PA 6 4345.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.



2011

Invert and reset the mkd. wood post alongside the stainless steel post.



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4345,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Thence S. 32°03'10" E., on line 6-1, Mineral Survey No. 4345, Palace lode.</p> <p>4.80 Top of ridge, bears N. 70° E. and S. 70° W.</p> <p>7.868 Cor. No. 1, Mineral Survey No. 4345, Palace lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. PAL 1 4345.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="824 641 1071 856"> </div> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence S. 65°51'40" W., on line 1-2, Mineral Survey No. 4345, Palace lode.</p> <p>9.039 The witness cor. to Cor. No. 2, Mineral Survey No. 4345, Palace lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 4 ft. diam., 1 1/2 ft. high, mkd. WC P 2 4345.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="812 1374 1091 1608"> </div> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/>
--------	--



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4345,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence S. 65°51'40" W., continuing on line 1-2, Mineral Survey No. 4345, Palace lode, beginning new measurement.
0.127	<p>True point for Cor. No. 2, Mineral Survey No. 4345, Palace lode, at the extension of the line bet. Cor. No. 1, Mineral Survey No. 4345, Palace lode, and the witness cor. for Cor. No. 2, Mineral Survey No. 4345, Palace lode and at record distance; there is no remaining evidence of the original corner; located on E. facing rock face where it is impractical to set a permanent monument.</p> <hr/> <p>Thence N. 33°14'30" W., on line 2-3, Mineral Survey No. 4345, Palace lode.</p>
7.882	<p>Cor. No. 3, Mineral Survey No. 4345, Palace lode, monumented with a wood post, 4x4 ins., 2 1/2 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. PAL 3 4345.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="836 889 1063 1042" data-label="Diagram"> </div> <p style="text-align: center;">2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence N. 35°15'10" W., on line 3-4, Mineral Survey No. 4345, Palace lode.</p>
10.267	Intersect line 1-2, Mineral Survey No. 4345, Prospect lode, at a point from which Cor. No. 2 bears S. 37°56'10" W., 3.616 chs. dist.
14.751	<p>Cor. No. 4, Mineral Survey No. 4345, Palace lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 2 1/2 ft. diam., 2 ft. high, mkd. PA 4 4345.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4345,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	 <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Promintory lode</p> <p>From Cor. No. 1, Mineral Survey No. 4345, Promintory lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. P 1 4345.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>  <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <p>Thence S. 50°45'30" W., on line 1-2, Mineral Survey No. 4345, Promintory lode.</p> <p>2.879 Intersect the line bet. secs. 14 and 23, at a point from which the 1/4 sec. cor. of secs. 14 and 23, hereinbefore described, bears S. 89°37'30" W., 14.742 chs. dist.</p> <p>21.901 Intersect line 5-6, Mineral Survey No. 4345, Palace lode, at a point from which Cor. No. 6 bears S. 35°58'40" E., 1.893 chs. dist.</p> <p>22.725 Cor. No. 2, Mineral Survey No. 4345, Promintory lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, mkd. P 2 4345.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4345,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	 <p>MS4345 PA</p> <p>MS4345 PROM</p> <p>2</p> <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence N. 14°58'00" E., on line 2-3, Mineral Survey No. 4345, Promintory lode.</p> <p>1.059 Intersect line 5-6, Mineral Survey No. 4345, Palace lode, at a point from which Cor. No. 6 bears S. 35°58'40" E., 2.513 chs. dist.</p> <p>12.913 Intersect the line bet. secs. 14 and 23, at a point from which the 1/4 sec. cor. of secs. 14 and 23, hereinbefore described, bears S. 89°37'30" W., 2.707 chs. dist.</p> <p>15.529 Cor. No. 3, Mineral Survey No. 4345, Promintory lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 4 ft. diam., 4 ft. high, mkd. P 3 4345.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>  <p>T25S R58E S14</p> <p>3 PROM MS4345</p> <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence N. 50°47'30" E., on line 3-4, Mineral Survey No. 4345, Promintory lode.</p> <p>1.30 Enter wash, drains irregularly E.</p> <p>9.00 Exit wash.</p> <p>16.50 Dirt road, 12 lks. wide, bears NE. and SW.</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4345,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 22.716</p>	<p>Cor. No. 4, Mineral Survey No. 4345, Promintory lode, determined at the center of a mound of stone, 4 ft. diam., 2 ft. high. This mound of stone correlates well with other existing corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="873 553 1036 764" data-label="Diagram"> </div> <p>Thence S. 14°59'30" W., on line 4-1, Mineral Survey No. 4345, Promintory lode.</p> <p>3.50 Dirt road, 12 lks. wide, bears ESE. and WNW.</p> <p>5.10 Enter wash, drains irregularly E.</p> <p>7.60 Exit wash.</p> <p>15.515 Cor. No. 1, Mineral Survey No. 4345, Promintory lode, and point of beginning.</p> <hr/> <p>DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4353, T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of Portions of the Survey Executed by U.S. Mineral Surveyor C.H. Fenner in 1918</p> <hr/> <p>Bullion lode</p> <p>From Cor. No. 1, Mineral Survey No. 4353, Bullion lode, identical with Cor. No. 2, Mineral Survey No. 4353, Bullion No. 2 lode, determined at the center of a mound of stone, 3 ft. diam., 1 ft. high, with the remains of a wood post lying loose within, no marks visible. This mound of stone correlates well with other existing corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
--------------------------	---

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4353,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

MS4353	MS4353
BU	BU 2
1	2

T25S R58E  
S23

2011

Deposit the wood post remains alongside the stainless steel post.

Thence S. 87°38'30" W., on line 1-2, Mineral Survey No. 4353, Bullion lode.

3.50 Wash, 45 lks. wide, drains E.; thence along wash.

9.087 Cor. No. 2, Mineral Survey No. 4353, Bullion lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 1/2 ft. high, no marks visible. This is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

MS4353
BU
2

T25S R58E  
S23

2010

Invert and reset the mkd. wood post alongside the stainless steel post.

Cor. is located in wash, 30 lks. wide, drains E.

Thence N 2°27'10" W., on a portion of line 2-3, Mineral Survey No. 4353, Bullion lode.

4.118 Cor. No. 1, Mineral Survey No. 4353, Wayward lode.

From Cor. No. 3, Mineral Survey No. 4353, Bullion lode, on line 5-1, Mineral Survey No. 4353, Wayward lode, monumented with a wood post, 4x4 ins., firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. B 3 4353.



At the corner point



DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4353,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td data-bbox="818 435 915 482">WA MS4353</td><td data-bbox="932 378 1101 537">T25S R58E S23 3 BU MS4353</td></tr> </table> <p>2011</p> </div> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <p>Thence N. 87°37'10" E., on line 3-4, Mineral Survey No. 4353, Bullion lode.</p> <p>9.092 Cor. No. 4, Mineral Survey No. 4353, Bullion lode, identical with Cor. No. 3, Mineral Survey No. 4353, Bullion No. 2 lode, monumented with a wood post, 4x4 ins., firmly set in a mound of stone, 4 ft. diam., 3 ft. high, mkd. 4353.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2" data-bbox="880 1087 1029 1136">T25S R58E S23</td></tr> <tr> <td data-bbox="844 1160 941 1242">4 BU MS4353</td><td data-bbox="964 1160 1062 1242">3 BU 2 MS4353</td></tr> </table> <p>2010</p> </div> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p style="text-align: center;">Bullion No. 2 lode</p> <p>From Cor. No. 3, Mineral Survey No. 4353, Bullion No. 2 lode, identical with Cor. No. 4, Mineral Survey No. 4353, Bullion lode.</p> <p>Thence N. 87°36'20" E., on line 3-4, Mineral Survey No. 4353 Bullion No. 2.</p> <p>9.089 Cor. No. 4, Mineral Survey No. 4353, Bullion No. 2 lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 5 ft. diam., 4 ft. high, mkd. B2 4 4353.</p> <p>At the corner point</p>	WA MS4353	T25S R58E S23 3 BU MS4353	T25S R58E S23		4 BU MS4353	3 BU 2 MS4353
WA MS4353	T25S R58E S23 3 BU MS4353						
T25S R58E S23							
4 BU MS4353	3 BU 2 MS4353						

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4353,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T25S R58E S23</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2010</p>
	<p>Invert and reset the mkd. wood post alongside the stainless steel post.</p>
	<p>Thence S. 2°25'20" E., on line 4-1, Mineral Survey No. 4353, Bullion No. 2 lode.</p>
20.00	<p>Dirt road, 15 lks. wide, bears NE. and SW.</p>
21.90	<p>Wash, 1 ch. wide, drains NE.</p>
22.727	<p>Cor. No. 1, Mineral Survey No. 4353, Bullion No. 2 lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, mkd. B2 1 4353.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	<div style="text-align: center;">  </div> <p style="text-align: center;">T25S R58E S23</p> <p style="text-align: center;">2010</p>
	<p>Invert and reset the mkd. wood post alongside the stainless steel post.</p>
	<p>Cor. is located at S. edge of wash, 2 chs. wide, drains E.</p>
	<p>Thence S. 87°37'00 W., on line 1-2, Mineral Survey No. 4353, Bullion No. 2 lode.</p>
6.00	<p>N. edge of wash, 1 ch. wide, drains E.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4353,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

9.094


Cor. No. 2, Mineral Survey No. 4353, Bullion No. 2 lode, identical with Cor. No. 1, Mineral Survey No. 4353, Bullion lode.

## Wayward lode

From Cor. No. 1, Mineral Survey No. 4353, Wayward lode, on line 2-3, Mineral Survey No. 4353, Bullion lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, mkd. W 1 4353.

## At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of earth and stone, 4 ft. base, to top, with brass cap mkd.



2011

Invert and reset the mkd. wood post alongside the stainless steel post.


Thence N. 62°37'00" W., on line 1-2, Mineral Survey No. 4353, Wayward lode.

10.473

Cor. No. 2, Mineral Survey No. 4353, Wayward lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, mkd. W 2 4353.

## At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



2011

Invert and reset the mkd. wood post alongside the stainless steel post.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4353,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Thence N. 2°23'20" W., on line 2-3, Mineral Survey No. 4353, Wayward lode.</p> <p>6.714 Cor. No. 3, Mineral Survey No. 4353, Wayward lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, mkd. W 3 4353.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="771 613 1055 797"> </div> <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence N. 4°31'30" E., on line 3-4, Mineral Survey No. 4353, Wayward lode.</p> <p>14.642 Cor. No. 4, Mineral Survey No. 4353, Wayward lode, monumented with a wood post, 4x4 ins., 3 1/2 ft. long, firmly set in a mound of stone, 2 1/2 ft. diam., 2 ft. high, mkd. W 4 4353.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="885 1369 1088 1543"> </div> <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <p>From this corner, Cor. No. 1, Mineral Survey No. 4345, Palace lode bears S. 66°45'00" W., 0.909 chs. dist., hereinbefore described.</p> <hr/>
--------	---



DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4353,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>Thence S. <math>62^{\circ}44'40''</math> E., on line 4-5, Mineral Survey No. 4353, Wayward lode.</p> <p>8.410 Cor. No. 5, Mineral Survey No. 4353, Wayward lode, determined at the center of a mound of stone, 2 ft. diam., 1 ft. high, with a wood post, 4x4 ins., 2 ft. long, lying loose alongside, mkd. W 5 4353.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="826 620 1024 826" data-label="Diagram"> </div> <p>Deposit the mkd. wood post alongside the stainless steel post.</p> <p>Thence S. <math>2^{\circ}32'20''</math> E., on a portion of line 5-1, Mineral Survey No. 4353, Wayward lode.</p> <p>3.686 Cor. No. 3, Mineral Survey No. 4353, Bullion lode.</p> <hr/> <p>DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4376, T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the Survey Executed by U.S. Mineral Surveyor A.H. Black in 1918</p> <hr/> <p>Evening Star lode</p> <p>From Cor. No. 1, Mineral Survey No. 4376, Evening Star lode, identical with Cor. No. 2, Mineral Survey No. 4376, East Evening Star lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 4 ft. diam., 1 ft. high, mkd. ES 1 4376 EES 2 4376.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
---------------	--

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4376,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
	<table border="1" data-bbox="841 229 1065 350"> <tr> <td>MS4376</td><td>MS4376</td></tr> <tr> <td>E S</td><td>E E S</td></tr> <tr> <td>1</td><td>2</td></tr> </table> <p data-bbox="878 374 1024 429">T25S R58E S14</p> <p data-bbox="919 463 984 485">2011</p> <p data-bbox="435 518 1382 570">Invert and reset the mkd. wood post alongside the stainless steel post.</p> <p data-bbox="435 596 1409 649">Thence S. 85°22'30" W., on line 1-2, Mineral Survey No. 4376, Evening Star lode.</p>	MS4376	MS4376	E S	E E S	1	2
MS4376	MS4376						
E S	E E S						
1	2						
8.962	<p data-bbox="435 675 1414 778">Cor. No. 2, Mineral Survey No. 4376, Evening Star lode, monumented with a wood post, 4x4 ins., 2 1/2 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. ES 2 4376.</p> <p data-bbox="435 806 740 832">At the corner point</p> <p data-bbox="435 856 1446 959">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="881 989 1078 1110"> <tr> <td>T25S</td><td>MS4376</td></tr> <tr> <td>R58E</td><td>E S</td></tr> <tr> <td>S14</td><td>2</td></tr> </table> <p data-bbox="922 1139 987 1161">2011</p> <p data-bbox="435 1193 1382 1245">Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr data-bbox="688 1270 1219 1274"/> <p data-bbox="435 1304 1393 1356">Thence N. 0°11'00" E., on line 2-3, Mineral Survey No. 4376, Evening Star lode.</p>	T25S	MS4376	R58E	E S	S14	2
T25S	MS4376						
R58E	E S						
S14	2						
6.30	<p data-bbox="435 1382 914 1409">Gulch, 25 lks. wide, drains E.</p>						
22.400	<p data-bbox="435 1437 1414 1540">Cor. No. 3, Mineral Survey No. 4376, Evening Star lode, monumented with a wood post, 4x4 ins., 2 1/2 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. ES 3 4376.</p> <p data-bbox="435 1566 740 1592">At the corner point</p> <p data-bbox="435 1616 1446 1719">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>						

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4376,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	
	<p style="text-align: center;">T25S R58E S14</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2011</p>
	<p>Invert and reset the mkd. wood post alongside the stainless steel post.</p>
	<hr/> <p>Thence N. 85°27'40" E., on line 3-4, Mineral Survey No. 4376, Evening Star lode.</p>
3.40	<p>Gulch, 50 lks. wide, drains S.</p>
8.670	<p>The witness cor. to Cor. No. 4, Mineral Survey No. 4376, Evening Star lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. WC ES 4 4376.</p>
	<hr/> <p>Thence N. 85°27'40" E., continuing on line 3-4, Mineral Survey No. 4376, Evening Star lode, beginning new measurement.</p>
0.151	<p>Point for Cor. No. 4, Mineral Survey No. 4376, Evening Star lode, identical with Cor. No. 3, Mineral Survey No. 4376, East Evening Star lode, determined at intersection of the extension of the line bet. Cor. No. 3 and the witness cor. on line 3-4, Mineral Survey No. 4376, Evening Star lode, and the line bet. Cor. No. 1 and the witness cor. on line 4-1, Mineral Survey No. 4376, Evening Star lode, identical with Cor. No. 2 and line 2-3, Mineral Survey No. 4376, East Evening Star lode; there is no remaining evidence of the marks from the 1918 survey.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p>
	<p style="text-align: center;">T25S R58E S14</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2011</p>
	<hr/> <p>Thence S. 0°10'20" E., on line 4-1, Mineral Survey No. 4376, Evening Star lode, identical with line 2-3, Mineral Survey No. 4376, East Evening Star lode.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4376,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA



CHAINS	
0.534	The witness cor. to Cor. No. 3, Mineral Survey No. 4376, East Evening Star lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 3 ft. diam., 2 ft. high, mkd. WC EES 3 4376.
	Thence S. 0°10'20" E., continuing on line 4-1, Mineral Survey No. 4376, Evening Star lode, identical with line 2-3, Mineral Survey No. 4376, East Evening Star lode, beginning new measurement.
2.20	Gulch, 50 lks. wide, drains E.
15.60	Gulch, 40 lks. wide, drains NE.
21.841	Cor. No. 1, Mineral Survey No. 4376, Evening Star lode, identical with Cor. No. 2, Mineral Survey No. 4376, East Evening Star lode, and point of beginning.
	East Evening Star lode
	From Cor. No. 3, Mineral Survey No. 4376, East Evening Star lode, identical with Cor. No. 4, Mineral Survey No. 4376, Evening Star lode.
	Thence N. 85°29'10" E., on line 3-4, Mineral Survey No. 4376, East Evening Star lode.
7.968	Point selected for the witness cor. to Cor. No. 4, Mineral Survey No. 4376, East Evening Star lode.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.
	WC
	T25S R58E
	S14
	4
	E E S
	MS4376
	2011
7.998	True point for Cor. 4, Mineral Survey No. 4376, East Evening Star lode, determined by Grant Boundary adjustment bet. Cor. Nos. 1 and 3. A wood post, 4x4 ins., 2 1/2 ft. long, mkd. ES 4 4376, was found at the base of the cliff, original position indeterminate; located on face of limestone outcrop where it is impractical to set a permanent monument.
	Thence S. 0°07'40" E., on line 4-1, Mineral Survey No. 4376, East Evening Star lode.
6.90	Gulch, 1 ch. wide, drains SE.
8.20	Remains of old wagon road, 10 lks. wide, bears SE. and NW.



DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4376,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.00	Gulch, 20 lks. wide, drains SE.
12.30	Dirt road, 12 lks. wide, bears E. and W.
22.387	<p>Cor. No. 1, Mineral Survey No. 4376, East Evening Star lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, mkd. EES 1 4376.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence S. 85°33'40" W., on line 1-2, Mineral Survey No. 4376, Evening Star lode.</p>
7.981	<p>Cor. No. 2, Mineral Survey No. 4376, East Evening Star lode, identical with Cor. No. 1, Mineral Survey No. 4376, Evening Star lode.</p> <hr/> <p>DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4441, T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of Portions of the Survey Executed by U.S. Mineral Surveyor A.H. Black in 1920</p> <hr/> <p>Mongolia lode</p> <p>From Cor. No. 3, Mineral Survey No. 4441, April Fool lode, on line 1-2, Mineral Survey No. 4441, Mongolia lode.</p> <p>Thence N. 30°11'50" E., on a portion of line 1-2, Mineral Survey No. 4441, Mongolia lode.</p>
2.40	Wash, 20 lks. wide, drains SW.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4441,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA


<p>CHAINS 4.020</p>	<p>Cor. No. 2, Mineral Survey No. 4441, Mongolia lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, with aluminum cap mkd. MS4441 2-MONGOLIA OWENS PLS 2884, with a wood post, 4x4 ins., 3 ft. long, lying loose alongside, mkd. M 2 4441, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="861 635 1029 856"> <p>T25S R58E S16</p>  </div> <p>Insert the rebar inside and invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence S. 35°27'00" E., on line 2-3, Mineral Survey No. 4441, Mongolia lode.</p> <p>0.50 Wash, 30 lks. wide, drains SW.</p> <p>9.367 Cor. No. 3, Mineral Survey No. 4441, Mongolia lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set in a mound of stone, 3 1/2 ft. diam., 3 1/2 ft. high, with aluminum cap mkd. MS4441 3-MONGOLIA OWENS PLS 2884, with a wood post, 4x4 ins., 2 ft. long, lying loose alongside, no marks visible, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="798 1562 1125 1764"> <p>T25S R58E S16</p>  </div>
-------------------------	---

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4441,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Insert the rebar inside and invert and reset the wood post alongside the stainless steel post.</p>
	<p>Thence S. 30°07'10" W., on line 3-4, Mineral Survey No. 4441, Mongolia lode.</p>
21.10	<p>Gulch, 30 lks. wide, drains SW.</p>
22.659	<p>Cor. No. 4, Mineral Survey No. 4441, Mongolia lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 3 1/2 ft. diam., 1 ft. high, with aluminum cap mkd. MS4441 4-MONGOLIA OWENS PLS 2884, with a wood post, 4x4 ins., 3 ft. long, lying loose alongside, mkd. M 4-4441, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="873 891 1042 1112" data-label="Diagram"> </div> <p>Insert the rebar inside and invert and reset the mkd. wood post alongside the stainless steel post.</p>
	<p>Thence N. 35°29'00" W., on line 4-1, Mineral Survey No. 4441, Mongolia lode.</p>
9.395	<p>Cor. No. 1, Mineral Survey No. 4441, Mongolia lode, on line 3-4, Mineral Survey No. 4441, Oriental lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the surface of the ground, with aluminum cap mkd. MS4441 1-MONGOLIA OWENS PLS 2884, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4441,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



2011


Insert the rebar inside the stainless steel post.

Producer lode

From Cor. No. 2, Mineral Survey No. 4441, Producer lode, identical with Cor. No. 4, Mineral Survey No. 4441, Oriental lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the surface of the ground, with aluminum cap mkd. MS4441 2-PRODUCER 4-ORIENTAL OWENS PLS 2884, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.



2011

Insert the rebar inside the stainless steel post.

Thence S. 30°02'50" W., on line 2-3, Mineral Survey No. 4441, Producer lode.

9.086

Cor. No. 3, Mineral Survey No. 4441, Producer lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, with aluminum cap mkd. MS4441 3-PRODUCER OWENS PLS 2884, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

CHAINS

MS4441  
PR  
3  
T25S R58E  
S16

2011

Insert the rebar inside the stainless steel post.

Thence N.  $36^{\circ}12'10''$  W., on line 3-4, Mineral Survey No. 4441, Producer lode.

22.730

Cor. No. 4, Mineral Survey No. 4441, Producer lode, identical with Cor. No. 3, Mineral Survey No. 4534, South Side lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, with aluminum cap mkd. SS 3-4534 P 4-4441 OWENS PLS 2884, with a wood post, 4x4 ins., 4 ft. long, lying loose alongside, mkd. SS 3-4534 P 4-4411, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T25S R58E  
S16  
3 4  
S S PR  
MS4534 S16 MS4441  
T25S R58E

2011

Deposit the rebar and invert and reset the wood post alongside the stainless steel post.

Thence N.  $30^{\circ}11'30''$  E., on line 4-1, Mineral Survey No. 4441, Producer lode.

6.00

Wash, 70 lks. wide, drains NW.

9.076


Cor. No. 1, Mineral Survey No. 4441, Producer lode, identical with Cor. No. 1, Mineral Survey No. 4441, Oriental lode, recovered by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a chiseled X in bedrock, with the marks P-1-4441 O-1-4441 chiseled alongside, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.

At the corner point

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4441,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.



2011

From this cor., the witness cor. to Cor. No. 1, Mineral Survey No. 4441, Producer lode, bears S. 36°12'10" E., 0.356 chs. dist., monumented with a limestone, 36x24x24 ins., mkd. WC P-1-4441 O-1-4441, set in a mound of stone, 4 ft. diam., 1 ft. high.

## Oriental lode

From Cor. No. 1, Mineral Survey No. 4441, Oriental lode, identical with Cor. No. 1, Mineral Survey No. 4441, Producer lode.


Thence N. 30°11'30" E., on line 1-2, Mineral Survey No. 4441, Oriental lode.

9.921

Cor. No. 2, Mineral Survey No. 4441, Oriental lode, identical with Cor. No. 1, Mineral Survey No. 4441, April Fool lode, recovered by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a limestone, 21x16x8 ins., set in a mound of stone 4 ft. diam., 2 ft. high, mkd. X on top and O-2 AF-1 4441 on the S. face, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.




2011

Deposit the mkd. stone alongside the stainless steel post.

From Cor. No. 1, Mineral Survey No. 4441, Mongolia lode, on line 3-4, Mineral Survey No. 4441, Oriental lode.


Thence S. 32°58'40" W., on a portion of line 3-4, Mineral Survey No. 4441, Oriental lode.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4441,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 0.527</p>	<p>Cor. No. 4, Mineral Survey No. 4441, Oriental lode, identical with Cor. No. 2, Mineral Survey No. 4441, Producer lode.</p> <hr/> <p>April Fool lode</p> <p>From Cor. No. 1, Mineral Survey No. 4441, April Fool lode, identical with Cor. No. 2, Mineral Survey No. 4441, Oriental lode.</p> <p>Thence N. 30°11'30" E., on a portion of line 1-2, Mineral Survey No. 4441, April Fool lode.</p>
<p>0.557</p>	<p>Cor. No. 4, Mineral Survey No. 4441, Nellie lode.</p> <hr/> <p>From Cor. No. 2, Mineral Survey No. 4441, April Fool lode, identical with Cor. No. 3, Mineral Survey No. 4441, Nellie lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 1/2 ft. high, with aluminum cap mkd. MS4441 3-NELLIE OWENS PLS 2884, with a wood post, 4x4 ins., 18 ins. long, lying loose alongside, mkd. AF 2 4441 N 3-4441, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>  <p>Insert the rebar inside and deposit the mkd. wood post alongside the stainless steel post.</p> <p>Thence S. 35°00'10" E., on line 2-3, Mineral Survey No. 4441, April Fool lode.</p>
<p>22.948</p>	<p>Point for Cor. No. 3, Mineral Survey No. 4441, April Fool lode, on line 1-2, Mineral Survey No. 4441, Mongolia lode, at proportionate distance bet. Cor. No. 2, Mineral Survey No. 4441, Mongolia lode and Cor. No. 4, Mineral Survey No. 4441, April Fool lode, identical with Cor. No. 3, Mineral Survey No. 4441, Oriental lode; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4441,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS



2011


From this point, a position determined by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, bears S. 24°25'30" W., 0.288 chs. dist., monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. MS4441 3-APRIL FOOL OWENS PLS 2884, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys. This is not utilized in this survey.

Thence S. 30°11'50" W., on line 3-4, Mineral Survey No. 4441, April Fool lode, identical with a portion of line 1-2, Mineral Survey No. 4441, Mongolia lode.

9.246 Cor. No. 4, Mineral Survey No. 4441, April Fool lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 4 1/2 ft. diam., 2 ft. high, with aluminum cap mkd. MS4441 4-APRIL FOOL 3-ORIENTAL OWENS PLS 2884, with a wood post, 4x4 ins., 3 1/2 ft. long, lying loose alongside, mkd. O 3-4441 AF 4-4441, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.



2011


Deposit the rebar inside and invert and reset the mkd. wood post alongside the stainless steel post.



DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4441,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p style="text-align: center;">Nellie lode</p> <p>From Cor. No. 4, Mineral Survey No. 4441, Nellie lode, on line 1-2, Mineral Survey No. 4441, April Fool lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 4 1/2 ft. diam., 3 1/2 ft. high, with aluminum cap mkd. MS4441 4-NELLIE OWENS PLS 2884, with a wood post, 4x4 ins., 3 1/2 ft. long, lying loose alongside, mkd. N 4-4441, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="737 717 1065 903" data-label="Diagram"> </div> <p>Insert the rebar inside and invert and reset the mkd. wood post alongside the stainless steel post.</p> <p>Thence N. 60°49'40" W., on line 4-1, Mineral Survey No. 4441, Nellie lode.</p> <p>20.687 Cor. No. 1, Mineral Survey No. 4441, Nellie lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, with aluminum cap mkd. MS4441 1-NELLIE OWENS PLS 2884, with a wood post, 4x4 ins., 4 ft. long, lying loose alongside, mkd. N 1-4441, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="740 1507 1062 1705" data-label="Diagram"> </div> <p>Insert the rebar inside and invert and reset the mkd. wood post alongside the stainless steel post.</p>
---------------	---

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4441,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence N. 30°12'50" E., on line 1-2, Mineral Survey No. 4441, Nellie lode.
4.40	Gulch, 30 lks. wide, drains irregularly W.
8.679	Cor. No. 2, Mineral Survey No. 4441, Nellie lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, with aluminum cap mkd. MS4441 2-NELLIE OWENS PLS 2884, with a wood post, 4x4 ins., 2 ft. long, lying loose alongside, mkd. N 2-4441, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;"> <p>T25S R58E S16</p>  <p>2011</p> </div>
	Insert the rebar inside and invert and reset the wood post alongside the stainless steel post.
	Thence S. 62°19'00" E., on line 2-3, Mineral Survey No. 4441, Nellie lode.
4.30	Gulch, 45 lks. wide, drains irregularly W.
20.695	Cor. No. 3, Mineral Survey No. 4441, Nellie lode, identical with Cor. No. 2, Mineral Survey No. 4441, April Fool lode.
<p>DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4525, T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p>Reestablishment of a Portion of the Survey Executed by U.S. Mineral Surveyor A.H. Black in 1922</p>	
<p>Sultan lode</p>	
<p>From Cor. No. 3, Mineral Survey No. 4525, Sultan lode, identical with Cor. No. 4, Mineral Survey No. 4525, Turk lode, perpetuated by Craig A. Givant, Nevada Professional Land Surveyor No. 14348, in 2007, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, mkd. S 3 4525 T 4 4525, with a brass tag on the top of wood post</p>	


DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4525,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

mkd. GIVANT PLS 14348, as recorded in Clark County, Nevada, File 166, Page 47 of Surveys.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.



2011

Invert and reset the mkd. wood post alongside the stainless steel post.


Thence N. 32°07'40" W., on line 3-4, Mineral Survey No. 4525, Sultan lode.

4.135 Intersect the line bet. secs. 20 and 29, at a point from which the 1/4 sec. cor. of secs. 20 and 29, hereinbefore described, bears S. 88°57'10" E., 0.527 chs. dist.

22.731 Cor. No. 4, Mineral Survey No. 4525, Sultan lode, perpetuated by Craig A. Givant, Nevada Professional Land Surveyor No. 14348, in 2007, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set in a mound of earth and stone, 3 1/2 ft. diam., 1 1/2 ft. high, with aluminum cap mkd. GIVANT PLS 14348, with a wood post, 4x4 ins., 2 ft. long, lying loose alongside, mkd. S 4 4525, as recorded in Clark County, Nevada, File 166, Page 47 of Surveys.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.





2011

Insert the rebar inside and deposit the mkd. wood post alongside the stainless steel post.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4525,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence N. 57°36'50" E., on a portion of line 4-1, Mineral Survey No. 4525, Sultan lode
0.901	Cor. No. 3, Mineral Survey No. 4525, Sultana lode.
	<p style="text-align: center;">Sultana lode</p> <p>From Cor. No. 3, Mineral Survey No. 4525, Sultana lode, on line 4-1, Mineral Survey No. 4525, Sultan lode, perpetuated by Craig A. Givant, Nevada Professional Land Surveyor No. 14348, in 2007, monumented with a rebar, 1/2 in. diam., 14 ins. long, firmly set in a mound of stone, 2 1/2 ft. diam., 1 ft. high, with aluminum cap mkd. GIVANT PLS 14348, with a wood post, 4x4 ins., 3 1/2 ft. long, lying loose alongside, mkd. S 3 4525, as recorded in Clark County, Nevada, File 166, Page 47 of Surveys.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <div data-bbox="833 852 1079 1040" data-label="Diagram"> </div> <p style="text-align: center;">2011</p> <p>Deposit the rebar and invert and reset the mkd. wood post in a mound of stone, 3 ft. base, 2 ft. high, SE. of cor.</p> <p>Thence N. 14°51'20" W., on line 3-4, Mineral Survey No. 4525, Sultana lode.</p>
22.626	Cor. No. 4, Mineral Survey No. 4525, Sultana lode, perpetuated by Craig A. Givant, Nevada Professional Land Surveyor No. 14348, in 2007, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 4 1/2 ft. diam., 2 1/2 ft. high, mkd. S 4 4525, with a brass tag on the top of the wood post mkd. GIVANT PLS 14348, as recorded in Clark County, Nevada, File 166, Page 47 of Surveys.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4525,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	
	 <p style="text-align: center;">2011</p>
	<p>Deposit the mkd. wood post alongside the stainless steel post.</p>
	<p>Thence N. 57°21'40" E., on line 4-1, Mineral Survey No. 4525, Sultana lode.</p>
9.173	<p>Cor. No. 1, Mineral Survey No. 4525, Sultana lode, perpetuated by Craig A. Givant, Nevada Professional Land Surveyor No. 14348, in 2007, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set in a mound of stone, 3 ft. diam., 3 ft. high, with aluminum cap mkd. GIVANT PLS 14348, with a wood post, 4x4 ins., 2 ft. long, lying loose alongside, mkd. S 1 4525, as recorded in Clark County, Nevada, File 166, Page 47 of Surveys.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	 <p style="text-align: center;">2011</p>
	<p>Insert the rebar inside and invert and reset the mkd. wood post alongside the stainless steel post.</p>
	<p>Thence S. 14°21'00" E., on line 1-2, Mineral Survey No. 4525, Sultana lode.</p>
21.938	<p>Intersect line 1-2, Mineral Survey No. 4525, Tuffacious lode, at a point from which Cor. No. 1, identical with Cor. No. 1, Mineral Survey No. 4525, Sultan lode, bears S. 26°04'20" W., 1.391 chs. dist.</p>
22.698	<p>Cor. No. 2, Mineral Survey No. 4525, Sultana lode, perpetuated by Craig A. Givant, Nevada Professional Land Surveyor No. 14348, in 2007, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set in a mound of stone, 3 1/2 ft. diam., 1 ft. high, with aluminum cap mkd. GIVANT PLS 14348, with a wood post, 4x4 ins., 2 ft. long, lying loose alongside, mkd. S 2 4525, as recorded in Clark County, Nevada, File 166, Page 47 of Surveys.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4525,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.




Insert the rebar inside and deposit the mkd. wood post alongside the stainless steel post.

Turk lode

From Cor. No. 1, Mineral Survey No. 4525, Turk lode, identical with Cor. No. 4, Mineral Survey No. 4525, Tuffacious lode, and Cor. No. 2, Mineral Survey No. 4525, Sultan lode, perpetuated by Craig A. Givant, Nevada Professional Land Surveyor No. 14348, in 2007, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, with aluminum cap mkd. GIVANT PLS 14348, with a wood post, 4x4 ins., 3 ft. long, lying loose alongside, mkd. T 1 4525 T 4 4525 S 2 4525, as recorded in Clark County, Nevada, File 166, Page 47 of Surveys.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.



2011

Insert the rebar inside and invert and reset the mkd. wood post alongside the stainless steel post.

Thence S. 52°08'20" E., on line 1-2, Mineral Survey No. 4525, Turk lode.


2.636

Intersect the line bet. secs. 20 and 29, at a point from which the 1/4 sec. cor. of secs. 20 and 29, hereinbefore described, bears N. 88°57'10" W., 11.414 chs. dist.

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4525,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA



<p>CHAINS 5.20</p>	<p>Wash, 30 lks. wide, drains N. 10° E.</p>
<p>22.692</p>	<p>Cor. No. 2, Mineral Survey No. 4525, Turk lode, perpetuated by Craig A. Givant, Nevada Professional Land Surveyor No. 14348, in 2007, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set in a mound of earth and stone, 3 ft. diam., 2 ft. high, with aluminum cap mkd. GIVANT PLS 14348, with a wood post, 4x4 ins., 2 ft. long, lying loose alongside, mkd. T 2 4525, as recorded in Clark County, Nevada, File 166, Page 47 of Surveys.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p> <div data-bbox="812 604 1136 776" data-label="Diagram"> </div> <p>Deposit the rebar and the mkd. wood post in a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <hr/> <p>Thence S. 57°23'50" W., on line 2-3, Mineral Survey No. 4525, Turk lode.</p>
<p>9.095</p>	<p>Cor. No. 3, Mineral Survey No. 4525, Turk lode, perpetuated by Craig A. Givant, Nevada Professional Land Surveyor No. 14348, in 2007, monumented with a rebar, 1/2 in. diam., 20 ins. long, firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, with aluminum cap mkd. GIVANT PLS 14348, with a wood post, 4x4 ins., 2 ft. long, lying loose alongside, mkd. T 3 4525, as recorded in Clark County, Nevada, File 166, Page 47 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="836 1370 1079 1582" data-label="Diagram"> </div> <p>Insert the rebar inside and invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence N. 52°08'10" W., on line 3-4, Mineral Survey No. 4525, Turk lode.</p>

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4525,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.20	Wash, 20 lks. wide, drains NNE.
20.20	Wash, 30 lks. wide, drains NE.
22.688	Cor. No. 4, Mineral Survey No. 4525, Turk lode, identical with Cor. No. 3, Mineral Survey No. 4525, Sultan lode.
	<p style="text-align: center;">Tuffacious lode</p> <p>From Cor. No. 1, Mineral Survey No. 4525, Tuffacious lode, identical with Cor. No. 1, Mineral Survey No. 4525, Sultan lode, perpetuated by Craig A. Givant, Nevada Professional Land Surveyor No. 14348, in 2007, monumented with a rebar, 1/2 in. diam., 12 ins. long, firmly set in a mound of stone, 4 ft. diam., 3 1/2 ft. high, with aluminum cap mkd. GIVANT PLS 14348, with a wood post, 4x4 ins., 2 ft. long, lying loose alongside, mkd. S 1 4525, as recorded in Clark County, Nevada, File 166, Page 47 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  <p style="text-align: center;">2011</p> </div> <p>Insert the rebar inside and deposit the mkd. wood post alongside the stainless steel post.</p> <p>Thence N. 26°04'20" E., on line 1-2, Mineral Survey No. 4525, Tuffacious lode.</p>
1.391	Intersect line 1-2, Mineral Survey No. 4525, Sultana lode, at a point from which Cor. No. 2 bears S. 14°21'00" E., 0.760 chs. dist.
8.90	Dirt road, 12 lks. wide, bears SSE. and NNW.
10.583	Cor. No. 2, Mineral Survey No. 4525, Tuffacious lode, perpetuated by Craig A. Givant, Nevada Professional Land Surveyor No. 14348, in 2007, monumented with a rebar, 1/2 in. diam., 12 ins. long, firmly set in a mound of earth and stone, 4 ft. diam., 3 1/2 ft. high, with aluminum cap mkd. GIVANT PLS 14348, with a wood post, 4x4 ins., 3 ft. long, lying loose alongside, mkd. T 2 4525, as recorded in Clark County, Nevada, File 166, Page 47 of Surveys.
	At the corner point



DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4525,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="885 367 1047 531"> <p>T25S R58E S20</p>  <p>2011</p> </div> <p>Insert the rebar inside and invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence S. 32°37'10" E., on line 2-3, Mineral Survey No. 4525, Tuffaceous lode.</p> <p>4.40 Dirt road, 12 lks. wide, bears SE. and NW.</p> <p>7.20 Dirt road, 12 lks. wide, bears NE. and SW.</p> <p>8.50 Remains of old wagon road, 10 lks. wide, bears N. and S.</p> <p>11.60 Gulch, 40 lks. wide, drains irregularly N.</p> <p>22.727 Cor. No. 3, Mineral Survey No. 4525, Tuffaceous lode, perpetuated by Craig A. Givant, Nevada Professional Land Surveyor No. 14348, in 2007, monumented with a basalt stone, 36x12x6 ins., firmly set in a mound of stone, 4 1/2 ft. diam., 2 1/2 ft. high, mkd. T 4 4525, with a brass tag mkd. PLS 14348, at the center of a chiseled X on top, as recorded in Clark County, Nevada, File 166, Page 47 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="836 1369 1071 1533">  <p>2011</p> </div> <p>Deposit the mkd. stone alongside the stainless steel post.</p> <hr/> <p>Thence S. 26°08'40" W., on line 3-4, Mineral Survey No. 4525, Tuffaceous lode.</p> <p>8.70 Gulch, 30 lks. wide, drains irregularly N.</p>
--------	---

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 4525,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS  
10.592

Cor. No. 4, Mineral Survey No. 4525, Tuffacious lode, identical with Cor. No. 1, Mineral Survey No. 4525, Turk lode, and Cor. No. 2, Mineral Survey No. 4525, Sultan lode.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4534,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA


Reestablishment of the Survey Executed by  
U.S. Mineral Surveyor A.H. Black in 1922

South Side lode

From Cor. No. 1, Mineral Survey No. 4534, South Side lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 3 1/2 ft. diam., 2 ft. high, with aluminum cap mkd. MS4534 1-SOUTH SIDE OWENS PLS 2884, with a wood post, 4x4 ins., 2 ft. long, lying loose alongside, no marks visible, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



Insert the rebar inside and deposit the wood post alongside the stainless steel post.

Thence N. 30°15'20" E., on line 1-2, Mineral Survey No. 4534, South Side lode.

0.026 Intersect line 2-3, Mineral Survey No. 4534, Idaho lode, at a point from which Cor. No. 3, bears S. 14°51'20" E., 3.111 chs. dist.


8.989 Cor. No. 2, Mineral Survey No. 4534, South Side lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of stone, 4 ft. diam., 2 ft. high, with aluminum cap mkd. MS4534 2-SOUTH SIDE OWENS PLS 2884, with a wood post, 4x4 ins., 4 ft. long, lying loose alongside, mkd. SS 2 4534, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4534,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="857 425 1047 664" data-label="Diagram"> <p>T25S R58E S16</p> <p>2011</p> </div> <p>Insert the rebar inside and invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/> <p>Thence S. 35°28'40" E., on line 2-3, Mineral Survey No. 4534, South Side lode.</p>
8.30	Gulch, 20 lks. wide, drains SW.
17.40	Dirt road, 20 lks. wide, bears ENE. and WSW., in wash, 75 lks. wide, drains WSW.
22.694	Cor. No. 3, Mineral Survey No. 4534, South Side lode, identical with Cor. No. 4, Mineral Survey No. 4441, Producer lode, hereinbefore described.
	<hr/> <p>Thence S. 30°19'40" W., on line 3-4, Mineral Survey No. 4534, South Side lode.</p>
8.996	<p>Cor. No. 4, Mineral Survey No. 4534, South Side lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the surface of the ground, with aluminum cap mkd. SS 4-4534 OWENS PLS 2884, with a wood post, 4x4 ins., 4 ft. long, lying loose alongside, mkd. SS 4 4534, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.</p>
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4534,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS



T25S R58E  
S16

2011

Insert the rebar inside and invert and reset the wood post  
alongside the stainless steel post.

Thence N. 35°27'00" W., on line 4-1, Mineral Survey No. 4534,  
South Side lode.


- 11.30 Dirt road, 20 lks. wide, bears E. and W., in wash, 1 ch. wide,  
drains W.
- 19.30 Gulch, 60 lks. wide, drains W.
- 22.636 Intersect line 2-3, Mineral Survey No. 4534, Idaho lode, at a  
point from which Cor. No. 3, bears S. 14°51'20" E., 3.044 chs.  
dist.
- 22.688 Cor. No. 1, Mineral Survey No. 4534, South Side lode, and point  
of beginning.

## Idaho lode

From Cor. No. 1, Mineral Survey No. 4534, Idaho lode,  
perpetuated by James J. Owens, Nevada Professional Land Surveyor  
No. 2884, in 1998, monumented with a rebar, 5/8 in. diam.,  
18 ins. long, firmly set in a mound of stone, 3 ft. diam., 2 ft.  
high, with aluminum cap mkd. MS4534 4-IDAHO OWENS PLS 2884, with  
a wood post, 4x4 ins., 4 ft. long, lying loose alongside, mkd. I  
1 4534, as recorded in Clark County, Nevada, File 94, Page 40 of  
Surveys.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
9 ins. in the ground, to solid rock, over a plastic-encased  
magnet, and in a mound of stone, 3 1/2 ft. base, to top, with  
brass cap mkd.





2011

Insert the rebar and deposit the mkd. wood post alongside the  
stainless steel post.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4534,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence N. 74°37'10" E., on line 1-2, Mineral Survey No. 4534, Idaho lode.
20.90	Dirt road, 20 lks. wide, bears SE. and NW., in wash, 2 chs. wide, drains NW.
25.240	<p>Cor. No. 2, Mineral Survey No. 4534, Idaho lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of earth and stone, 2 1/2 ft. diam., 1 ft. high, with aluminum cap mkd. MS4534 2-IDAHO OWENS PLS 2884, with a wood post, 4x4 ins., 2 ft. long, lying loose alongside, mkd. I 2 4534, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="820 813 1039 1026" data-label="Diagram"> </div> <p>Insert the rebar inside and deposit the mkd. wood post alongside the stainless steel post.</p>
	Thence S. 14°51'20" E., on line 2-3, Mineral Survey No. 4534, Idaho lode.
5.978	Intersect line 1-2, Mineral Survey No. 4534, South Side lode, at a point from which Cor. No. 1 bears S. 30°15'20" W., 0.026 chs. dist.
6.045	Intersect line 4-1, Mineral Survey No. 4534, South Side lode, at a point from which Cor. No. 1 bears N. 35°27'00" W., 0.052 chs. dist.
9.089	<p>Cor. No. 3, Mineral Survey No. 4534, Idaho lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, with aluminum cap mkd. MS4534 3-IDAHO OWENS PLS 2884, set in a mound of stone, 2 ft. diam., 1 ft. high, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4534,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	 <p>2011</p> <p>Insert the rebar inside the stainless steel post.</p>
	<p>Thence S. 74°36'30" W., on line 3-4, Mineral Survey No. 4534, Idaho lode.</p>
2.00	<p>Dirt road, 20 lks. wide, bears SE. and NW., in wash, 1 ch. wide, drains NW.</p>
25.242	<p>Cor. No. 4, Mineral Survey No. 4534, Idaho lode, perpetuated by James J. Owens, Nevada Professional Land Surveyor No. 2884, in 1998, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set in a mound of earth and stone, 3 ft. diam., 3 ft. high, with aluminum cap mkd. MS4534 1-IDAHO OWENS PLS 2884, with a wood post, 4x4 ins., 3 ft. long, lying loose alongside, mkd. I 4 4534, as recorded in Clark County, Nevada, File 94, Page 40 of Surveys.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock, with top mkd.</p>  <p>2011</p> <p>Deposit the mkd. wood post and the rebar in a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p>
9.094	<p>Thence N. 14°50'40" W., on line 4-1, Mineral Survey No. 4534, Idaho lode.</p> <p>Cor. No. 1, Mineral Survey No. 4534, Idaho lode, and point of beginning.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4551,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	<p>Reestablishment of the Survey Executed by U.S. Mineral Surveyor A.H. Black in 1922</p> <hr/> <p>Ajax lode</p> <p>From Cor. No. 1, Mineral Survey No. 4551, Ajax lode, monumented with the remains of a wood post at the center of a mound of stone, 3 ft. diam., 1 ft. high. This evidence correlates well with other found corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="876 694 1055 858"> <p>MS4551 AJ 1 T25S R58E S13</p> </div> <p>2010</p> <p>Deposit the remains of the wood post alongside the stainless steel post.</p> <p>Thence N. 20°31'10" W., on line 1-2, Mineral Survey No. 4551, Ajax lode.</p>
19.691	<p>Intersect the line bet. secs. 12 and 13, at a point from which the 1/4 sec. cor. of secs. 12 and 13, hereinbefore described, bears S. 89°03'20" W., 6.484 chs. dist.</p>
22.716	<p>Cor. No. 2, Mineral Survey No. 4551, Ajax lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 5 ft. diam., 4 ft. high, mkd. A-2-4551.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="747 1492 1071 1655"> <p>T25S R58E S12 2 AJ MS4551 2010</p> </div> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <hr/>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4551,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence N. 69°31'10" E., on line 2-3, Mineral Survey No. 4551, Ajax lode.
9.092	<p>Cor. No. 3, Mineral Survey No. 4551, Ajax lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of earth and stone, 3 ft. diam., 3 ft. high, mkd. A-3-4551.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="865 594 1068 803" data-label="Diagram"> </div> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p>
6.251	<p>Thence S. 20°29'30" E., on line 3-4, Mineral Survey No. 4551, Ajax lode.</p> <p>Intersect the line bet. secs. 12 and 13, at a point from which the 1/4 sec. cor. of secs. 12 and 13, hereinbefore described, bears S. 89°03'20" W., 16.131 chs. dist.</p>
22.50	Dirt road, 12 lks. wide, bears NE. and SW.
22.707	<p>Cor. No. 4, Mineral Survey No. 4551, Ajax lode, determined at the center of a post hole in a mound of stone, 5 ft. diam., 2 ft. high, with a wood post, 4x4 ins., 3 ft. long, lying loose alongside, mkd. A-4-4551.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="820 1492 1120 1700" data-label="Diagram"> </div> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p>



DEPENDENT RESURVEY OF MINERAL SURVEY NO. 4551,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA


CHAINS	Thence S. 69°28'00" W., on line 4-1, Mineral Survey No. 4551, Ajax lode.
8.30	Dry wash, 60 lks. wide, drains S. 40° E.
9.081	Cor. No. 1, Mineral Survey No. 4551, Ajax lode, and point of beginning.
<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4597 A, T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Mineral Surveyor C.D. Baker in 1924</p> <hr/> <p>East Side lode</p> <p>From Cor. No. 2, Mineral Survey No. 4597 A, East Side lode, identical with Cor. No. 3, Mineral Survey No. 4597 A, Hoosier lode, monumented with a wood post, 4x4 ins., 2 1/2 ft. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. ES 2 4597 H 3 4597.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p> <p>Thence N. 69°04'30" E., on line 2-3, Mineral Survey No. 4597 A, East Side lode.</p>	
5.10	Gulch, 50 lks. wide, drains NW.
12.50	Gulch, 75 lks. wide, drains NW.
22.641	Cor. No. 3, Mineral Survey No. 4597 A, East Side lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 ft. high, no marks visible.
	from which
	<p>A + on a limestone boulder, 2 1/2 x 1 3/4 x 2 ft. high, mkd. E.S.2.S.1. + .. S.W. Cor. on top surface, bears N. 3°26' E., 114.8 lks. dist. (Record, N. 7°40' E., 87.5 ft.)</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4597 A,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 7 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



Invert and reset the wood post alongside the stainless steel post.

Thence N. 21°10'20" W., on line 3-4, Mineral Survey No. 4597 A, East Side lode.

0.70 Gulch, 45 lks. wide, drains W.


9.114 Cor. No. 4, Mineral Survey No. 4597 A, East Side lode, identical with Cor. No. 2, Mineral Survey No. 4597 A, Oklahoma lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. O 2 4597A.

from which

A + chiseled on the NE. face of cliff, 3 ft. above base, bears S. 61°48' W., 29.4 lks. dist.  
(Record, S. 64° W., 17 ft.)

At the corner point


Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.



2011

Invert and reset the mkd. wood post alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4597 A,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Oklahoma lode
	From Cor. No. 2, Mineral Survey No. 4597 A, Oklahoma lode, identical with Cor. No. 4, Mineral Survey No. 4597 A, East Side lode.
	Thence N. 20°57'00" W., on line 2-3, Mineral Survey No. 4597 A, Oklahoma lode.
0.20	Gulch, 50 lks. wide, drains NW.
2.30	Gulch, 30 lks. wide, drains SW.
3.80	Intersect ledge of outcropping bedrock on N. side of wide gulch or canyon.
6.10	S. edge of wash, 1 ch. wide, at drop off into wash, drains SW.
9.066	Cor. No. 3, Mineral Survey No. 4597 A, Oklahoma lode, identical with Cor. No. 2, Mineral Survey No. 4597 A, California lode, monumented with a wood post, 4x4 ins., 3 ft. long, firmly set in a mound of stone, 2 ft. in diam., 1 ft. high, mkd. O 3 4597.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	 <p>2011</p>
	Invert and reset the mkd. wood post alongside the stainless steel post.
	<hr/>
	Hoosier lode
	From Cor. No. 1, Mineral Survey No. 4597 A, Washington lode, on line 4-1, Mineral Survey No. 4597 A, Hoosier lode.
	Thence S. 68°58'10" W., on a portion of line 4-1, Mineral Survey No. 4597 A, Hoosier lode.
4.552	Point for Cor. No. 1, Mineral Survey No. 4597 A, Hoosier lode, determined by Grant Boundary adjustment bet. Cor. No. 1, Mineral Survey No. 4597 A, Washington lode, and Cor. No. 2, Mineral Survey No. 4597 A, Hoosier lode; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4597 A,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="771 357 1079 562"> <p>T25S R58E S 5 1 HO MS4597A 2011</p> </div>
	<p>Thence S. 21°01'50" E., on line 1-2, Mineral Survey No. 4597 A, Hoosier lode.</p>
1.90	S. edge of wash, 8 chs. wide, drains SW.
3.30	Dirt road, 15 lks. wide, bears NE. and SW.
9.105	<p>Cor. No. 2, Mineral Survey No. 4597 A, Hoosier lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. H 2 4597A.</p>
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="876 1083 1104 1318"> <p>MS4597A HO 2 T25S R58E S 5 2011</p> </div>
	<p>Invert and reset the mkd. wood post alongside the stainless steel post.</p>
	<p>Thence N. 68°58'50" E., on line 2-3, Mineral Survey No. 4597 A, Hoosier lode.</p>
22.695	<p>Cor. No. 3, Mineral Survey No. 4597 A, Hoosier lode, identical with Cor. No. 2, Mineral Survey No. 4597 A, East Side lode.</p>
	<p>Jupiter lode</p> <p>From Cor. No. 4, Mineral Survey No. 4597 A, California lode, on line 2-3, Mineral Survey No. 4597 A, Jupiter lode.</p> <p>Thence N. 20°49'40" W., on a portion of line 2-3, Mineral Survey No. 4597 A, Jupiter lode.</p>



DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4597 A,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 2.00</p> <p>4.658</p> <p>5.30</p> <p>9.053</p>	<p>Wash, 20 lks. wide, drains SW.</p> <p>Cor. No. 3, Mineral Survey No. 4597 A, Jupiter lode, determined at the center of a mound of stone, 2 ft. diam., 1/2 ft. high. This mound of stone correlates well with the other existing corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div data-bbox="771 618 1037 850" data-label="Diagram"> </div> <p>Thence S. 69°04'00" W., on line 3-4, Mineral Survey No. 4597 A, Jupiter lode.</p> <p>Top of ridge, bears NE. and SW.</p> <p>Cor. No. 4, Mineral Survey No. 4597 A, Jupiter lode, identical with Cor. No. 3, Mineral Survey No. 4597 A, Washington lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. J 4 4597A W 3 4597A.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="828 1391 1131 1632" data-label="Diagram"> </div> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p>
--	---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4597 A,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Washington lode</p> <p>From Cor. No. 3, Mineral Survey No. 4597 A, Washington lode, identical with Cor. No. 4, Mineral Survey No. 4597 A, Jupiter lode.</p> <p>Thence S. 69°08'20" W., on line 3-4, Mineral Survey No. 4597 A, Washington lode.</p>
7.10	Wash, 25 lks. wide, drains SW.
9.120	<p>Cor. No. 4, Mineral Survey No. 4597 A, Washington lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 2 ft. diam., 1/2 ft. high, no marks visible. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div data-bbox="787 868 1104 1022"> </div> <p>2011</p> <p>Invert and reset the wood post alongside the stainless steel post.</p>
	<p>Thence S. 20°56'30" E., on line 4-1, Mineral Survey No. 4597 A, Washington lode.</p>
1.20	Wash, 50 lks. wide, drains SW.
8.90	High ridge, bears NE. and SW.
19.00	Wash, 1 ch. wide, drains W.
22.30	Dirt road, 12 lks. wide, bears E. and W.
22.882	<p>Cor. No. 1, Mineral Survey No. 4597 A, Washington lode, on line 4-1, Mineral Survey No. 4597 A, Hoosier lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 1/2 ft. diam., 1 ft. high, mkd. W 1 4597A.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>


DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4597 A,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	 <p>2011</p> <p>Invert and reset the mkd. wood post alongside the stainless steel post.</p>
	<p>California lode</p> <p>From Cor. No. 2, Mineral Survey No. 4597 A, California lode, identical with Cor. No. 3, Mineral Survey No. 4597 A, Oklahoma lode.</p> <p>Thence N. 20°57'00" W., on line 2-3, Mineral Survey No. 4597 A, California lode.</p> <p>4.60 Top of ridge, bears NE. and SW.</p> <p>8.20 Steep cliff, bears NE. and SW.</p> <p>9.130 Cor. No. 3, Mineral Survey No. 4597 A, California lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 2 ft. diam., 1 ft. high, mkd. C 3 4597.</p>
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>  <p>2011</p> <p>Invert and reset the wood post alongside the stainless steel post.</p>
	<p>Thence S. 69°01'40"W., on line 3-4, Mineral Survey No. 4597 A, California lode.</p> <p>22.592 Cor. No. 4, Mineral Survey No. 4597 A, California lode, on line 2-3, Mineral Survey No. 4597 A, Jupiter lode, monumented with a wood post, 4x4 ins., 4 ft. long, firmly set in a mound of stone, 3 ft. diam., 1 1/2 ft. high, mkd. C 4 4597A.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4597 A,  
T. 25 S., R. 58 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.



2011

Invert and reset the mkd. wood post alongside the stainless steel post.

GENERAL DESCRIPTION

The lands included in the survey are located approximately 2 miles south of the community of Goodsprings, in Clark County, Nevada. Access is provided by Sandy Valley Road and numerous dirt roads. The area is mountainous. Vegetation consists of various grasses, greasewood, sagebrush, Joshua trees, and various cacti. The average elevation of the area is approximately 4,000 ft. above sea level.



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

2010 - 2011

Micky J. Denison	Crew Chief
Josh B. Helmick	Crew Chief
Sean R. Stevens	Crew Chief
Taylor J. Carmack	Surveying Technician
Alex M. Blair	Survey Aid
Jacob I. Davigon	Survey Aid
Wayne G. Dubbs	Survey Aid
Huston Powell	Survey Aid
Zack A. Ruble	Survey Aid
Patrick S. Stevens	Survey Aid
Cody R. Suckow	Survey Aid
Kenneth M. Thomas	Survey Aid

2016 - 2021

Brandon K. Grace	Cadastral Surveyor
Joseph J. Johnson	Cadastral Surveyor
Carlos Gil Mendoza	Cadastral Surveyor
Mark G. Petrosine	Surveying Technician
Ryan P. Marx	Cartographic Technician

## CERTIFICATE OF SURVEY

We, Brian D. Hatter, Professional Land Surveyor, and Brandon G. Courtright, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of February, 2010, We have dependently resurveyed the south, east and west boundaries, the subdivisional lines and portions of certain mineral surveys, Township 25 South, Range 58 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

1/3/22

(Date)

JUL 27 2022

(Date)

Brian D. Hatter

(Nevada Professional Land Surveyor)

Muhamed O. Hammurij

/For Brandon G. Courtright  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of the south, east and west boundaries, the subdivisional lines and portions of certain mineral surveys, Township 25 South, Range 58 East, Mount Diablo Meridian, Nevada, executed by Brian D. Hatter, Professional Land Surveyor, and Brandon G. Courtright, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUL 27 2022

(Date)

Muhamed O. Hammurij

(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 25 South, Range 58 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~