

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF

THE NORTH BOUNDARY AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF SECTIONS 6, 8 AND 18,

TOWNSHIP 26 NORTH, RANGE 31 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Thomas E. Casinger, Cadastral Surveyor

Under Special Instructions dated May 17, 1999,

and approved May 17, 1999,

which provided for the surveys included under Group No. 783,

and Assignment Instructions dated May 17, 1999.

Survey commenced May 17, 1999

Survey completed June 24, 1999

## INDEX DIAGRAM

TOWNSHIP 26 NORTH, RANGE 31 EAST

2					
<b>6</b>	18 <b>5</b>	<b>4</b>	<b>3</b>	<b>2</b>	<b>1</b>
16	15				
<b>7</b>	14 <b>8</b>	3 <b>9</b>	<b>10</b>	<b>11</b>	<b>12</b>
13	11				
<b>18</b>	9 <b>17</b>	<b>16</b>	<b>15</b>	<b>14</b>	<b>13</b>
6					
<b>19</b>	<b>20</b>	<b>21</b>	<b>22</b>	<b>23</b>	<b>24</b>
<b>30</b>	<b>29</b>	<b>28</b>	<b>27</b>	<b>26</b>	<b>25</b>
<b>31</b>	<b>32</b>	<b>33</b>	<b>34</b>	<b>35</b>	<b>36</b>

Subdivision of Section 6 ..... pp. 18 - 21  
 Subdivision of Section 8 ..... pp. 21 - 22  
 Subdivision of Section 18 ..... pp. 22 - 25

## TOWNSHIP 26 NORTH, RANGE 31 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary and a portion of the subdivisional lines, and the subdivision of sections 6, 8 and 18, Township 26 North, Range 31 East, Mount Diablo Meridian, Nevada.

The Fifth Standard Parallel North (south boundary), the north, east and west boundaries, and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor A.J. Hatch in 1868 under Contract No. 12. A portion of the subdivisional lines were surveyed by U.S. Deputy Surveyors A.J. Hatch and J.H. Eaton in 1878 under Contract No. 77. The south boundary was resurveyed by U.S. Deputy Surveyor F.L. Gould in 1892 under Contract No. 196. The northeast township corner was reestablished by U.S. Deputy Surveyor H.B. Maxson in 1893 under Contract No. 199. The west boundary was resurveyed by U.S. Surveyor T.A. Haigh and U.S. Transitman H.W. Reppert in 1912 under Group No. 14. A portion of the subdivisional lines were surveyed and dependently resurveyed by U.S. Surveyor T.A. Haigh in 1912 under Group No. 14.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 17, 1999.

The direction of the lines of this survey refer to the true meridian as determined by use of Global Positioning System satellite data, using the real-time kinematic survey process.

The geographic position for the northwest corner of section 18 is at Lat. 40°07'45.191" N., Long. 118°33'07.589" W., NAD 83 (1994), as determined from National Geodetic Survey control (formerly U.S.C. & G.S. triangulation) station "RING", located in sec. 14, T. 26 N., R. 30 E.

The mean magnetic declination is 16° E., as shown on U.S.G.S. quadrangle map "WEST OF LOVELOCK, NEVADA", provisional edition dated 1987.

---

## 140

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the survey executed by A. J. Hatch, U.S. Deputy Surveyor, in 1868</p>
	<p>From the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., determined by John H. Milton III, Nevada Professional Land Surveyor No. 5271, at the corner of fences extending N. and W. monumented with a rebar, 5/8 in. diam., 22 ins. long, firmly set 20 ins. in the ground, with aluminum cap mkd., JOHN H. MILTON III RLS 5271, as shown on Parcel Map recorded as File No. 143502, Pershing County, Nevada. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R31E S31   S32 ----- S 6   S 5 T26N</p> <p>1999</p> </div> <p>Place rebar inside the stainless steel post.</p> <p>S. 89°49'30" W., bet. secs. 6 and 31.</p> <p>Over nearly level terrain, along fence.</p>
1.70	Corner of fences extending E. and S. 2° E.
20.659	Point for the E 1/16 sec. cor. of secs. 6 and 31. Point not monumented.
41.318	<p>The 1/4 sec. cor. of secs. 6 and 31, remonumented by John H. Milton III, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 in. diam., 24 ins. long, firmly set 16 ins. in the ground, with aluminum cap mkd., JOHN H. MILTON III RLS 5271, as shown on Parcel Map recorded as File No. 143502, Pershing County, Nevada, with a wooden post, 6x4 ins., 4 ft. long, firmly set alongside, 24 ins. in the ground, mkd. illegibly. This is accepted as a careful and best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R31E S31 1/4 ——— S 6 T26N</p> <p>1999</p> </div>

141

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>40.892</p>	<p>Bury wooden post, inverted, alongside and place rebar inside stainless steel post.</p> <hr/> <p>S. 89°55'10" W., beginning new measurement.</p> <p>Over nearly level terrain.</p> <p>The cor. of Tps. 26 and 27 N., R. 31 E., monumented with a granite stone, 16x12x8 ins., loosely set 4 ins. in the ground, in a collar of stone, with no mks. visible. There is no remaining evidence of the iron post set in the 1912 resurvey of the N. bdy. of T. 26 N., R. 30 E.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td></td><td>T27N</td></tr> <tr><td></td><td>R31E</td></tr> <tr><td>T26N</td><td>S31</td></tr> <tr><td>S 1</td><td></td></tr> <tr><td>R30E</td><td>S 6</td></tr> <tr><td></td><td>T26N</td></tr> </table> </div> <p>1999</p> <p>Deposit the unmkd. stone alongside the stainless steel post and rebuild mound of stone, 2 1/2 ft. base, 2 ft. high, W. of the cor.</p> <p>From this point, a granite boulder, 8 ft. high, bears N. 15° E., 0.96 chs. dist.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the surveys executed by A.J. Hatch, U.S. Deputy Surveyor, in 1868, A.J. Hatch and J.H. Eaton, U.S. Deputy Surveyors, in 1878, and T.A. Haigh, U. S. Surveyor, in 1912</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17, determined by Robert F. Myers, Nevada Professional Civil Engineer and Land Surveyor No. 519, monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T26N</td><td>R31E</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td>S17</td><td>S16</td></tr> <tr><td>10-22-47</td><td></td></tr> <tr><td>LS 519</td><td></td></tr> </table> </div>		T27N		R31E	T26N	S31	S 1		R30E	S 6		T26N	T26N	R31E	S 8	S 9	S17	S16	10-22-47		LS 519	
	T27N																						
	R31E																						
T26N	S31																						
S 1																							
R30E	S 6																						
	T26N																						
T26N	R31E																						
S 8	S 9																						
S17	S16																						
10-22-47																							
LS 519																							

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>This position has been adopted and recorded by various other professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>Cor. is located 3.00 chs. N. of Toulon Drain, course S. 57° W. N. 0°14'30" W., bet. secs. 8 and 9.</p> <p>Over nearly level terrain.</p>
0.50	Power line, bears N. 50° E. and S. 50° W.
1.40	Union Pacific Railroad track, bears N. 53°32' E. and S. 53°32' W.
20.45	Frontage road, asphalt surfaced, 40 lks. wide, bears N. 50° E. and S. 50° W.
22.446	<p>Centerline of the east bound lane of Interstate Highway No. 80, bears N. 49°39'30" E. and S. 49°39'30" W.</p> <p>From this point, the east bound centerline at Sta. "OE" 712+72.52 POT bears N. 49°39'30" E., 4.313 chs. dist.</p> <p>from which</p> <p>A reference monument, bears S. 40°20'30" E., 0.546 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, with top mkd. OE 712+72.52 POT DIST 36.04 ANGLE 90.</p> <p>A reference monument, bears N. 40°20'30" W., 0.643 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, with top mkd. OE 712+72.52 POT DIST 42.47 ANGLE 90.</p>
25.061	<p>Centerline of the west bound lane of Interstate Highway No. 80, bears N. 49°39'30" E. and S. 49°39'30" W.</p> <p>From this point, the west bound centerline at Sta. "OW" 712+72.52 POT bears N. 49°39'30" E., 2.629 chs. dist.</p> <p>from which</p> <p>A reference monument, bears S. 40°20'30" E., 0.588 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, with top mkd. OW 712+72.52 POT DIST 38.83 ANGLE 90 .</p> <p>A reference monument, bears N. 40°20'30" W., 1.635 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post alongside, with top mkd. OW 712+72.52 POT DIST 107.90 ANGLE 90 .</p>
31.72	Power line, bears N. 51° E. and S. 51° W.

## 143

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.071	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R31E</p> <p>1/4</p> <p>S 8   S 9</p> <p>1999</p> </div> <p>Set a steel fence post alongside.</p> <p>From this point, a squared wooden post monumented by person(s) unknown, 4x4 ins., firmly set, projecting 2 ft. above the ground, plainly mkd. 1/4 on the E. face, with an iron post, 1 1/4 ins. diam., firmly set alongside, projecting 6 ins. above the ground, bears N. 39°01' W., 1.46 chs. dist. This post does not have the characteristics of an original monument set in 1878 and its appearance indicates that it was set and mkd. subsequent to the original survey and it is not utilized during the course of this survey.</p>
78.65	Wire fence, bears E. and W.
80.142	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R31E</p> <p>S 5   S 4</p> <hr/> <p>S 8   S 9</p> <p>1999</p> </div> <p>Cor. is located on S. edge of slough, 0.35 chs. wide, bears E. and W.</p> <p>From this point, the cor. of secs. 3, 4, 9 and 10, bears S. 89°41'40" E., 79.902 chs. dist., determined by John H. Milton III, Nevada Professional Land Surveyor No. 5271, as shown on Parcel Map recorded as File No. 193884, Pershing County, Nevada, monumented with a PK nail set flush with the surface of asphalt. This is accepted as the best available evidence of the position of the original corner.</p> <p>from which</p> <p style="padding-left: 40px;">A rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, at the intersection of a right-of-way fence, bears E. and W. and a fence, extending S., bears S. 0°10' W., 0.535 chs. dist.</p> <p>and new reference monuments</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 41°29' E., 69 1/2 lks. dist., with brass cap mkd. RM T26NR31E S10 45.8 FT 1999 and an arrow pointing to the corner.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 57°50' W., 103 1/2 lks. dist., with brass cap mkd. RM T26NR31E S9 68.3 FT 1999 and an arrow pointing to the corner.

Cor. is located at the intersection of Big Meadow Road, asphalt surfaced, 36 lks. wide, bears E. and W. and the projection of a fence, bears S.

This control line was fully retraced and no evidence of the intervening cor. was found.

From this same point, the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., bears N. 0°21'30" E., 79.932 chs. dist., determined latitudinally by the extension of a unimproved gravel road bearing E. and W. and longitudinally by the extension of a canal bearing N. This position is harmoniously related to surrounding corners and is accepted as the best available evidence of the position of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.

T27N	R31E
S32	S33
S 5	S 4
T26N	

1999

Cor. is located on S. edge of a wandering gravel road, bears E. and W.

This control line was fully retraced and no evidence of the intervening cor. was found.

From the cor. of secs. 17, 18, 19 and 20, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., firmly set 21 ins. in the ground, imbedded in a concrete post, 8 ins. diam., 26 ins. long. This position has been adopted by adjacent land owners and professional land surveyors and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T26N R31E S18   S17 ----- S19   S20</p> <p>1999</p> <p>Bury rebar with concrete post and set a steel fence post alongside stainless steel post.</p> <p>Cor. is located 5 lks. S. of the remnants of a fence bearing E. and W.</p> <p>From this point, a well casing, 6 ins. diam., projecting 12 ins. above the ground, bears N. 89°49' W., 0.28 chs. dist.</p> <p>S. 89°43'50" W., bet. secs. 18 and 19.</p> <p>Over nearly level terrain, along fence remnants.</p>
10.40	Toulon Drain, course S. 20° W.
28.65	Power line, bears N. 52° E. and S. 52° W.
29.90	Union Pacific Railroad track, bears N. 52°32' E. and S. 52°32' W.
39.796	<p>The 1/4 sec. cor. of secs. 18 and 19, determined by person(s) unknown, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above the ground, with iron cap laying alongside, mkd. illegibly. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T26N R31E S18 1/4 ——— S19</p> <p>1999</p> <p>Deposit iron cap and pipe and set a steel fence post alongside stainless steel post.</p> <hr/> <p>S. 89°50'10" W., beginning new measurement.</p> <p>Over nearly level terrain.</p>
2.553	The reference monument for the easterly right-of-way, frontage road, monumented with a concrete post, 8 ins. square, firmly set, projecting 4 ins. above the ground, mkd. N. on the W. face, with a wooden post set alongside.
7.55	Frontage road, asphalt surfaced, 40 lks. wide, bears N. 52 1/4° E. and S. 52 1/4° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.039	<p>Centerline of the east bound lane of Interstate Highway No. 80, asphalt surfaced, 40 lks. wide, bears N. 52°21'20" E. and S. 52°21'20" W.</p> <p>From this point, the east bound centerline at Sta. "OE" 597+30.84 POT, as shown on Property Schedule Sheet No. 12, Project No. I-080-2(7)98, obtained from the Nevada Highway Department, bears S. 52°21'20" W., 3.844 chs. dist.</p> <p>from which</p> <p>A reference monument, bears S. 37°38'40" E., 2.887 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post alongside, with top mkd. OE 597+30.84 POT DIST 190.56 ANGLE 90.</p>
13.326	<p>Centerline of the west bound lane of Interstate Highway No. 80, asphalt surfaced, 40 lks. wide, bears N. 52°21'20" E. and S. 52°21'20" W.</p> <p>From this point, the west bound centerline at Sta. "OW" 597+30.84 POT, as shown on Property Schedule Sheet No. 12, Project No. I-080-2(7)98, obtained from the Nevada Highway Department, bears S. 52°21'20" W., 1.238 chs. dist.</p> <p>from which</p> <p>A reference monument, bears N. 37°38'40" W., 1.061 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, with top mkd. OW 597+30.84 POT DIST 70.00 ANGLE 90.</p> <p>A reference monument, bears N. 37°38'40" W., 2.946 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post alongside, with top mkd. OW 597+30.84 POT DIST 194.44 ANGLE 90.</p>
21.50	Power line, bears N. 52° E. and S. 52° W.
39.948	<p>The cor. of secs. 18 and 19 only, on the W. bdy. of the Tp., monumented with a trapstone, 16x12x14 ins., firmly set 8 ins. in the ground, plainly mkd. with 3 notches on the N. and S. edges and 6 grooves on the E. and W. faces, with a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

147

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div>T26N R30E R31E S 24   S18           S19</div> <div>1999</div> <div>Deposit the original cornerstone and set a steel fence post alongside the stainless steel post.</div> <hr/> <div>From the cor. of secs. 17, 18, 19 and 20.</div> <div>N. 0°08'40" E., bet. secs. 17 and 18.</div> <div>Over nearly level terrain.</div> <div>17.50 Toulon Drain, course S. 50° W.</div> <div>19.956 Point for the S 1/16 sec. cor. of secs. 17 and 18.</div> <div>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div><div>S 1/16 S18   S17</div><div>1999</div><div>Set a steel fence post alongside stainless steel post.</div></div> <div>21.10 Power line, bears N. 52° E. and S. 52° W.</div> <div>22.05 Union Pacific Railroad track, bears N. 52°32' E. and S. 52°32' W.</div> <div>29.934 Point for the N-S 1/64 sec. cor. of secs. 17 and 18.</div> <div>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div><div>N-S 1/64 S18   S17</div><div>1999</div><div>Set a steel fence post alongside stainless steel post.</div></div> <div>32.396 From this point, a reference monument for the easterly right-of-way, frontage road, monumented with a concrete post, 8 ins. square, firmly set, projecting 10 ins. above the ground, mkd. N. on the W. face, with a wooden post set alongside, bears West, 0.164 chs. dist.</div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
34.319	<p>From this point, a reference monument for the easterly right-of-way, frontage road, monumented with a concrete post, 8 ins. square, firmly set, projecting 12 ins. above the ground, mkd. N. on the W. face, with a wooden post set alongside, bears West, 0.154 chs. dist.</p>
36.35	<p>Frontage road, asphalt surfaced, 40 lks. wide, bears N. 52 1/4° E. and S. 52 1/4° W.</p>
38.304	<p>Centerline of the east bound lane of Interstate Highway No. 80, asphalt surfaced, 40 lks. wide, bears N. 52°21'40" E. and S. 52°21'20" W.</p> <p>From this point, the east bound centerline at Sta. "OE" 641+21.79 POT, as shown on Property Schedule Sheet No. 12, Project No. I-080-2(7)98, obtained from the Nevada Highway Department, bears S. 52°21'20" W., 0.371 chs. dist.</p> <p>from which</p> <p>A reference monument, bears S. 37°38'40" E., 0.707 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, with top mkd. OE 641+21.79 POT DIST 46.64 ANGLE 90.</p> <p>A reference monument, bears N. 37°38'40" W., 0.730 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, with top mkd. OE 641+21.79 POT DIST 48.20 ANGLE 90.</p>
39.912	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the corner reestablished in the 1912 resurvey.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R31E 1/4 S18 S17 1999</p> <p>Set a steel fence post alongside.</p>
40.835	<p>Centerline of the west bound lane of Interstate Highway No. 80, asphalt surfaced, 40 lks. wide, bears N. 52°21'40" E. and S. 52°21'20" W.</p> <p>From this point, the west bound centerline at Sta. "OW" 641+21.79 POT, as shown on Property Schedule Sheet No. 12, Project No. I-080-2(7)98, obtained from the Nevada Highway Department, bears S. 52°21'20" W., 1.921 chs. dist.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A reference monument, bears S. 37°38'40" E., 0.620 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, with top mkd. OW 641+21.79 POT DIST 40.92 ANGLE 90.</p> <p>A reference monument, bears N. 37°38'40" W., 1.435 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, with top mkd. OW 641+21.79 POT DIST 94.70 ANGLE 90.</p>
47.70	Power line, bears N. 52° E. and S. 52° W.
49.890	<p>Point for the S-N 1/64 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S-N 1/64 S18 S17 1999</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p>
79.824	<p>Point for the cor. of secs. 7, 8, 17 and 18, determined longitudinally at record distance from the 1/4 sec. cor. of secs. 7 and 18 and latitudinally by proportionate measurement; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R31E S 7   S 8 S18   S17 1999</p> </div> <p>Set a steel fence post alongside stainless steel post.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°27'20" W., bet. secs. 8 and 17.</p> <p>Over nearly level terrain.</p>
0.60	Power line, bears N. 51° E. and S. 51° W.
1.92	Union Pacific Railroad track, bears N. 54°12' E. and S. 54°12' W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
24.50	Frontage road, asphalt surfaced, 40 lks. wide, bears N. 50° E. and S. 50° W.
26.826	Centerline of the east bound lane of Interstate Highway No. 80, bears N. 49°39'30" E. and S. 49°39'30" W.
	<p>From this point, the east bound centerline at Sta. "OE" 686+44.49 POT ("OE" 686+38.25 PT), as shown on Property Schedule Sheet No. 13, Project No. I-080-2(7)98, obtained from the Nevada Highway Department, bears S. 49°39'30" W., 0.446 chs. dist.</p>
	from which
	<p>A reference monument, bears S. 40°20'30" E., 0.509 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, with top mkd. OE 686+44.49 PT DIST 33.61 ANGLE 90.</p>
	<p>A reference monument, bears N. 40°20'30" W., 0.677 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, with top mkd. OE 686+44.49 PT DIST 44.71 ANGLE 90.</p>
29.972	Centerline of the west bound lane of Interstate Highway No. 80, in a curve, concave to the NW.
	<p>From this point, the west bound centerline at Sta. "OW" 686+44.49 POT ("OW" 686+38.25 PT), as shown on Property Schedule Sheet No. 13, Project No. I-080-2(7)98, obtained from the Nevada Highway Department, is on the arc of a circular curve to the left having a radius of 9768 feet, the chord of said arc bears N. 50°03'10" E., 1.972 chs. dist.</p>
	from which
	<p>A reference monument, bears S. 40°20'30" E., 0.757 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set flush with the surface of the ground, with a steel fence post alongside, with top mkd. OW 686+38.25 PT OW 686+44.49 POT DIST 49.94 ANGLE 90.</p>
	<p>A reference monument, bears N. 40°20'30" W., 0.820 chs. dist., monumented with a brass disk, 3 1/4 ins. diam., seated in a concrete post, 18 ins. diam., firmly set, projecting 4 ins. above the ground, with a steel fence post alongside, with top mkd. OW 686+38.25 PT OW 686+44.94 POT DIST 54.11 ANGLE 90.</p>
40.30	Power line, bears N. 51 1/4° E. and S. 51 1/4° W.
40.461	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

## 151

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T26N R31E S 8 1/4 — S17 1999</p> <p>Set a steel fence post alongside stainless steel post.</p> <p>From this point, the corner of fences extending S. 5 1/2° W. and S. 80° W. bears N. 29 3/4° E., 3.40 chs. dist.</p>
80.922	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>S. 89°54'30" W., bet. secs. 7 and 18.</p> <p>Over nearly level terrain.</p>
20.000	<p>Point for the E 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
40.000	<p>E 1/16 — S 7 S18 1999</p> <p>Set a steel fence post alongside stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., firmly set 20 ins. in the ground, with top broken off and missing.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
39.85	<p>T26N R31E S 7 1/4 — S18 1999</p> <p>Deposit iron post and set a steel fence post alongside stainless steel post.</p> <hr/> <p>N. 89°39'10" W., beginning new measurement.</p> <p>Over nearly level terrain.</p> <p>Wash, 5 lks. wide, drains N. 15° W.</p>

## 152

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.148	<p>The cor. of secs. 7 and 18 only, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above the ground, with a mound of stone, 2 1/2 ft. base, 2 ft. high, E. of the cor., with brass cap mkd.</p> <div><div>T26N R31E S 7</div><div>S18</div></div> <p>1912</p> <p>Remark brass cap</p> <div><div>T26N R30E   R31E S 7</div><div>S13   S18</div></div> <p>1912 1999</p> <p>From this corner, National Geodetic Survey control (formerly U.S.C. &amp; G.S. triangulation) station "RING", monumented with a standard brass tablet, firmly cemented in a concrete cylinder, 8 ins. diam., mkd. RING 1957, bears S. 72°15'20" W. (mean bearing), 128.766 chs. dist.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°06'10" W., bet. secs. 7 and 8.</p> <p>Over nearly level terrain.</p> <p>19.976 Point for the S 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div><div>S 1/16 S 7   S 8</div><p>1999</p></div> <p>Set a steel fence post alongside stainless steel post.</p> <p>From this point, a wooden post, 4 ins. square, firmly set, projecting 4 ft. above the ground, mkd. RIGHT OF WAY on the E. face, bears S. 66°14' W., 0.047 chs.</p> <p>39.952 The 1/4 sec. cor. of secs. 7 and 8, determined by person(s) unknown, monumented with an iron pipe, 3/4 in. diam., firmly set 10 ins. in the ground, with a cedar post, 2 ins. square, 14 ins. long, laying alongside, no mks. visible, with a steel fence post alongside. This is accepted as the best available evidence of the position of the original corner.</p>



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R31E 1/4 S 7   S 8 1999</p> </div> <p>Deposit iron pipe and cedar post alongside stainless steel post.</p> <hr/> <p>N. 0°01'00" E., beginning new measurement.</p> <p>Over nearly level terrain.</p> <p>39.976 The cor. of secs. 5, 6, 7 and 8, determined by person(s) unknown, subsequently remonumented by Keith N. Meador, Nevada Professional Land Surveyor No. 1004, as shown on a plat recorded as File No. 65758, Pershing County, Nevada, with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, encased in concrete, with pipe cap mkd.</p> <div style="text-align: center;"> <p>1967 T26N R31E S 6   S 5 S 7   S 8 RLS 1004</p> </div> <p>This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R31E S 6   S 5 S 7   S 8 1999</p> </div> <p>Deposit iron post and set a steel fence post alongside stainless steel post.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°18'10" W., bet. secs. 5 and 8.</p> <p>Over nearly level terrain.</p> <p>40.314 Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p>
---------------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R31E S 5 1/4 — S 8  1999</p> <p>Set a steel fence post alongside stainless steel post.</p> <p>Cor. is located in a wash, 1 ch. wide, bears S. 60° E. and N. 60° W., 4.5 chs. N. of a wire fence extending N. 70° E. and S. 70° W.</p> <p>60.471 Point for the W 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 5 W 1/16 — S 8  1999</p> <p>Set a steel fence post alongside stainless steel post.</p> <p>80.628 The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <p>N. 89°37'20" W., bet. secs. 6 and 7.</p> <p>Over gently rolling terrain.</p> <p>10.768 Intersect the northerly boundary of the Indian Cemetery as shown on Drawing No. 65758, Records of Pershing County, Nevada. Fence bears S. 64° E. and N. 64° W.</p> <p>From this point, the southeast corner of the Indian Cemetery, established by Keith N. Meador, Nevada Professional Land Surveyor No. 1004, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, bears S. 64°24'10" E., 2.108 chs. dist.</p> <p>From this same point, the northwest corner of the Indian Cemetery, established by Keith N. Meador, Nevada Professional Land Surveyor No. 1004, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, bears N. 64°24'10" W., 2.681 chs. dist.</p> <p>Continue between secs. 6 and 7, across Indian Cemetery.</p> <p>13.716 Intersect the westerly boundary of the Indian Cemetery as shown on Drawing No. 65758, Records of Pershing County, Nevada. Fence bears N. 25° E. and S. 25° W.</p>
--------	--

## 155

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, the northwest corner of the Indian Cemetery, established by Keith N. Meador, Nevada Professional Land Surveyor No. 1004, hereinbefore described, bears N. 24°58'40" E., 1.256 chs. dist.</p> <p>From this same point, the southwest corner of the Indian Cemetery, established by Keith N. Meador, Nevada Professional Land Surveyor No. 1004, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, bears S. 24°58'40" W., 1.559 chs. dist.</p> <p>Continue between secs. 6 and 7.</p> <p>20.093 Point for the E 1/16 sec. cor. of secs. 6 and 7. Point not monumented.</p> <p>40.186 Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate distance by the method of irregular boundary adjustment; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R31E S 6 1/4 — S 7</p> <p>1999</p> </div> <p>Set a steel fence post alongside stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°43'20" W., beginning new measurement.</p> <p>Over gently rolling terrain.</p> <p>39.786 The cor. of secs. 6 and 7 only, on the W. bdy. of the Tp., monumented with a granite stone, 10x10x5 ins., loosely set 2 ins. in the ground, plainly mkd. 1/4 and 6 grooves on the E. face, 5 grooves on the S. face and 1 groove on the N. face, with a steel post, projecting 3 ft. above the ground, set alongside, with a mound of stone, 6 ft. base, 4 ft. high, W. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E R31E S 6 S12 — S 7</p> <p>1999</p> </div> <p>Deposit original corner stone alongside stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>
--------	---

## 156

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 1°07'00" E., bet. secs. 5 and 6.</p> <p>Over gently rolling terrain.</p>
20.092	<p>Point for the S 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 6   S 5  1999</p>
40.184	<p>Cor. is located 1.5 chs. W. of a wire fence bearing S. 2° E. and N. 2° W.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R31E 1/4 S 6   S 5  1999</p> <p>Set a steel fence post alongside stainless steel post.</p> <p>Cor. is located 0.40 chs. W. of wire fence bearing S. 2° E. and N. 2° W.</p>
60.276	Point for the N 1/16 sec. cor. of secs. 5 and 6. Point not monumented.
81.031	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., hereinbefore described.
<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 6, T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N. 0°18'40" E., on the N-S center line of sec. 6.</p> <p>Over gently rolling terrain.</p>
20.086	Point for the C-S 1/16 sec. cor. of sec. 6. Point not monumented.
40.00	Wash, 4 lks. wide, drains E.
40.172	Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E-W center line.

SUBDIVISION OF SECTION 6,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R31E C 1/4 S 6</p> <p style="text-align: center;">1999</p> <p>Set a steel fence post alongside stainless steel post.</p> <p>60.230 Point for the C-N 1/16 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} C \\ N \ 1/16 \   \ S \ 6 \\ C \end{array}</math> </p> <p style="text-align: center;">1999</p> <p>Set a steel fence post alongside stainless steel post.</p> <p>80.619 The 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6.</p> <p>N. 89°37'50" W., on the E-W center line of sec. 6.</p> <p>Over gently rolling terrain.</p> <p>20.373 Point for the C-E 1/16 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} E \ 1/16 \\ C \ \hline S \ 6 \end{array} C</math> </p> <p style="text-align: center;">1999</p> <p>Set a steel fence post alongside stainless steel post.</p> <p>40.746 The center 1/4 sec. cor.</p> <p>81.191 The 1/4 sec. cor. of sec. 6 only, on the W. bdy. of the Tp., monumented with a granite stone, 16x14x8 ins., laying loose, dimly mkd. 1/4, with a mound of stone, 2 ft. base, 1 ft. high, E. of cor. Accepted base of stone as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

## 158

SUBDIVISION OF SECTION 6,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T26N R30E R31E   1/4   S 6</p> <p style="text-align: center;">1999</p> <p>Deposit the original cornerstone and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/>
20.075	<p>From the C-E 1/16 sec. cor. of sec. 6.</p> <p>N. 0°42'50" E., on the N-S center line of the NE1/4 of sec. 6.</p> <p>Over nearly level terrain.</p> <p>Point for the NE 1/16 sec. cor. of sec. 6, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 6</p> <p style="text-align: center;">1999</p>
40.647	<p>The point for the E 1/16 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp.</p> <hr/> <p>From the point for the N 1/16 sec. cor. of secs. 5 and 6.</p> <p>N. 89°40'20" W., on the E-W center line of the NE1/4 of sec. 6.</p> <p>Over nearly level terrain.</p>
0.60	Wire fence bearing S. 2° E. and N. 2° W.
20.513	The NE 1/16 sec. cor.
41.026	The C-N 1/16 sec. cor. of sec. 6.
20.088	<hr/> <p>From the point for the E 1/16 sec. cor. of secs. 6 and 7.</p> <p>N. 0°42'50" E., on the N-S center line of the SE1/4 of sec. 6.</p> <p>Over nearly level terrain.</p> <p>Point for the SE 1/16 sec. cor. of sec. 6, at intersection with the E-W center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 6</p> <p style="text-align: center;">1999</p>

SUBDIVISION OF SECTION 6,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a steel fence post alongside stainless steel post.
40.176	The C-E 1/16 sec. cor of sec. 6.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 5 and 6. N. 89°37'20" W., on the E-W center line of the SE1/4 of sec. 6. Over gently rolling terrain.</p>
20.233	The SE 1/16 sec. cor.
40.466	The point for the C-S 1/16 sec. cor. of sec. 6.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 8, T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 8 and 17. N. 0°08'30" W., on the N-S center line of sec. 8. Over nearly level terrain.</p>
2.65	Wire fence, bears N. 80° E. and S. 80° W.
20.006	Point for the C-S 1/16 sec. cor. of sec. 8.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;"> <math display="block">\begin{array}{c} C \\ S\ 1/16\   \ S\ 8 \\ C \end{array}</math> 1999 </p>
	<p>Set a steel fence post alongside stainless steel post. Cor. falls in a trail road, 30 lks. wide, bears S. 10° E. and N. 40° W.</p>
40.012	Point for the center 1/4 sec. cor. of sec. 8, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">T26N R31E C 1/4 S 8 1999</p>
	Set a steel fence post alongside stainless steel post.

SUBDIVISION OF SECTION 8,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, a squared wooden post established by person(s) unknown, 4x4 ins., firmly set, projecting 2 ft. above the ground, plainly mkd. 1/4 on the E. face, bears N. 14°14' E., 2.72 chs. dist. This position is not utilized during the course of this survey.</p>
80.036	<p>The 1/4 sec. cor. of secs. 5 and 8.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 8 and 9. S. 89°22'20" W., on the E-W center line of sec. 8. Over gently rolling terrain.</p>
40.388	<p>The center 1/4 sec. cor.</p>
60.603	<p>Point for the C-W 1/16 sec. cor. of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} W \ 1/16 \\ C \ \frac{\quad}{\quad} \ C \\ S \ 8 \\ 1999 \end{array}</math> </div>
80.818	<p>Set a steel fence post alongside stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 7 and 8.</p> <hr/>
	<p>From the C-S 1/16 sec. cor. of sec. 8. Over nearly level terrain. S. 89°24'50" W., on the E-W center line of the SW1/4 of sec. 8.</p>
40.444	<p>The S 1/16 sec. cor. of secs. 7 and 8.</p> <hr/>
	<p>From the C-W 1/16 sec. cor. of sec. 8. Over gently rolling terrain. N. 0°03'40" W., on the N-S center line of the NW1/4 of sec. 8.</p>
40.000	<p>The W 1/16 sec. cor. of secs. 5 and 8.</p> <hr/>
	<p style="text-align: center;">SUBDIVISION OF SECTION 18, T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 18 and 19. N. 0°00'10" W., on the N-S center line of sec. 18. Over nearly level terrain.</p>



## 161

SUBDIVISION OF SECTION 18,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
5.80	Frontage road, asphalt surfaced, 40 lks. wide, bears N. 52° E. and S. 52° W.
7.716	<p>Centerline of the east bound lane of Interstate Highway No. 80, asphalt surfaced, 40 lks. wide, bears N. 52°21'20" E. and S. 52°21'20" W.</p> <p>From this point, the east bound centerline at Sta. "OE" 597+30.84 POT, as shown on Property Schedule Sheet No. 12, Project No. I-080-2(7)98, obtained from the Nevada Highway Department, bears S. 52°21'20" W., 16.524 chs. dist., hereinbefore described.</p>
10.242	<p>Centerline of the west bound lane of Interstate Highway No. 80, asphalt surfaced, 40 lks. wide, bears N. 52°21'20" E. and S. 52°21'20" W.</p> <p>From this point, the west bound centerline at Sta. "OW" 597+30.84 POT, as shown on Property Schedule Sheet No. 12, Project No. I-080-2(7)98, obtained from the Nevada Highway Department, bears S. 52°21'20" W., 18.068 chs. dist., hereinbefore described.</p>
16.00	Power line, bears N. 52° E. and S. 52° W.
20.047	<p>Point for the C-S 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} C \\ S\ 1/16 \left  S18 \\ C \end{array}</math> <p>1999</p> </div> <p>Set a steel fence post alongside stainless steel post.</p> <p>Over mountainous terrain.</p>
40.094	<p>Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} T26N\ R31E \\ C\ 1/4\ S18 \end{array}</math> <p>1999</p> </div> <p>Set a steel fence post alongside stainless steel post.</p>
79.945	<p>The 1/4 sec. cor. of secs. 7 and 18.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>S. 89°59'40" W., on the E-W center line of sec. 18.</p> <p>Over mountainous terrain.</p>

162

SUBDIVISION OF SECTION 18,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.192	Centerline of the west bound lane of Interstate Highway No. 80, asphalt surfaced, 40 lks. wide, bears N. 52°21'20" E. and S. 52°21'20" W.
	From this point, the west bound centerline at Sta. "OW" 641+21.79 POT, as shown on Property Schedule Sheet No. 12, Project No. I-080-2(7)98, obtained from the Nevada Highway Department, bears S. 52°21'20" W., 0.412 chs. dist., hereinbefore described.
9.70	Power line, bears N. 52° E. and S. 52° W.
39.895	The center 1/4 sec. cor.
80.473	The 1/4 sec. cor. of sec. 18 only, on the W. bdy. of the Tp., monumented with a trapstone, 24x14x10 ins., loosely set, 3 ins. in the ground, plainly mkd. 1/4 on the E. face, with a mound of stone, 3 ft. base, 2 ft. high, E. of cor.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> T26N  R30E R31E    1/4 S18     1999 </div>
	Deposit the original cornerstone and set a steel fence post, 5 ft. long, alongside the stainless steel post.
	From the S 1/16 sec. cor. of secs. 17 and 18.
	S. 89°51'40" W., on the E-W center line of the SE1/4 of sec. 18.
	Over nearly level terrain.
1.55	Power line, bears N. 52° E. and S. 52° W.
2.80	Union Pacific Railroad track, bears N. 52°32' E. and S. 52°32' W.
21.30	Frontage road, asphalt surfaced, 40 lks. wide, bears N. 52° E. and S. 52° W.
23.810	Centerline of the east bound lane of Interstate Highway No. 80, asphalt surfaced, 40 lks. wide, bears N. 52°21'20" E. and S. 52°21'20" W.
	From this point, the east bound centerline at Sta. "OE" 641+21.79 POT, as shown on Property Schedule Sheet No. 12, Project No. I-080-2(7)98, obtained from the Nevada Highway Department, bears N. 52°21'20" E., 29.760 chs. dist., hereinbefore described.
27.095	Centerline of the west bound lane of Interstate Highway No. 80, asphalt surfaced, 40 lks. wide, bears N. 52°21'20" E. and S. 52°21'20" W.

SUBDIVISION OF SECTION 18,  
T. 26 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From this point, the west bound centerline at Sta. "OW" 641+21.79 POT, as shown on Property Schedule Sheet No. 12, Project No. I-080-2(7)98, obtained from the Nevada Highway Department, bears N. 52°21'20" E., 32.366 chs. dist., hereinbefore described.
34.70	Power line, bears N. 52° E. and S. 52° W.
39.846	The C-S 1/16 sec. cor. of sec. 18.
	<hr/>
	GENERAL DESCRIPTION
	The area resurveyed and subdivided within Township 26 North, Range 31 East, varies in terrain from nearly level to mountainous. The elevation from about 3,935 to 4,100 feet above sea level. The soil is sandy clay loam and gravel. Numerous gravel pits are scattered throughout the area. The vegetation consists of sagebrush and native grass.
	Access is by Interstate Highway No. 80, improved gravel roads and trail roads.
	<hr/>

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Clay W. Morrow .....Surveying Technician

Michael McCain .....Survey Aid

## CERTIFICATE OF SURVEY

I, Thomas E. Casinger, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 17th day of May, 1999, I have dependently resurveyed a portion of the north boundary and a portion of the subdivisional lines, and subdivided sections 6, 8 and 18, Township 26 North, Range 31 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 4, 2002  
(Date)

Thomas E. Casinger  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the north boundary and a portion of the subdivisional lines, and the subdivision of sections 6, 8 and 18, Township 26 North, Range 31 East, Mount Diablo Meridian, Nevada, executed by Thomas E. Casinger, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

September 24, 2002  
(Date)

R. M. Scurry  
(Chief Cadastral Surveyor, Nevada)

## CERTIFICATE OF TRANSCRIPT

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 26 N., R. 31 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
(Date)~~

~~\_\_\_\_\_  
(Chief Cadastral Surveyor, Nevada)~~