

BUREAU OF LAND MANAGEMENT
Original
FIELD NOTES
OF THE
DEPENDENT RESURVEY OF THE EAST BOUNDARY,
A PORTION OF THE WEST BOUNDARY,
THE NORTH BOUNDARY
AND A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 26 NORTH, RANGE 49 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY
Michael E. Swope, Cadastral Surveyor

Under Special Instructions dated November 13, 2012,
and approved November 13, 2012,
and Supplemental Special Instructions dated December 18, 2012,
and approved December 18, 2012,
which provided for the surveys included under Group No. 919,
and Assignment Instructions dated November 13, 2012.

Survey commenced November 16, 2012

Survey completed October 9, 2014

INDEX DIAGRAM

TOWNSHIP 26 NORTH, RANGE 49 EAST, MOUNT DIABLO MERIDIAN, NEVADA

14	12	11	11	10	9
8 6	25 5	18 4	14 3	2	1 6
	24	17			
7	8	9	10	11	12 5
18	17	16	15	14	13 4
	23				
19	22 20	15 21	22	23	24 4
21	20				
7					
30	19 29	28	27	26	25 3
19					
31	32	33	34	35	36 2

TOWNSHIP 26 NORTH, RANGE 49 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following field notes are those of the dependent resurvey of the east boundary, a portion of the west boundary, the north boundary and a portion of the subdivisional lines, Township 26 North, Range 49 East, Mount Diablo Meridian, Nevada.</p> <p>The east boundary of T. 26 N., R. 48 E. was surveyed by U.S. Deputy Surveyors A.J. Hatch and J.H Eaton in 1869 under Contract No. 30. The south boundary (Fifth Standard Parallel North) and the subdivisional lines were surveyed by U.S. Deputy Surveyor E.L. Bridges in 1879 under Contract No. 86. The east, west and north boundaries were surveyed by U.S Deputy Surveyor D.H. Barker in 1879 under Contract No. 86. The south boundary (Fifth Standard Parallel North) was dependently resurveyed by U.S. Surveyor C.S. Swanholm in 1922 under Group No. 92. The corner of Townships 26 and 27 North, Ranges 49 and 50 East was remonumented by U.S. Surveyor C.S. Swanholm in 1930 under Group No. 145. A portion of the west boundary was dependently resurveyed by Cadastral Surveyor L.H Godwin in 1957 under Group No. 316.</p> <p>Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.</p> <p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 919, dated November 13, 2012.</p> <p>Measurements were made with Trimble R8 Global Positioning System (GPS) receivers using the real-time kinematic method. The direction of each line is with reference to the true meridian. All bearings are mean bearings and the distances are reported as horizontal measurements at a mean ground elevation of 6000 feet above sea level.</p> <p>The NAD 83 (2011)(EPOCH:2010.0000) geographic position of the corners below were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) LKN1 ELKO CORS ARP, AST2 AUSTIN 2 CORS ARP and TUNG TUNGSTEN CORS ARP and carried forward by RTK observations is as follows:</p> <p>The standard cor. of T. 26 N., R. 49 E. and R. 50 E., is as follows:</p> <p>Latitude: 40°05'05.953" N. Longitude: 116°23'19.031" W.</p> <p>The NW. cor. of T. 26 N., R. 49 E., is as follows:</p> <p>Latitude: 40°10'20.484" N. Longitude: 116°30'13.824" W.</p>
--------	--

TOWNSHIP 26 NORTH, RANGE 49 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The mean magnetic declination is 16° E, as shown on U.S.G.S. 7 1/2 minute quadrangle map "BUCKHORN MINE" dated 1986.</p>
	<p>DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor D.H. Barker in 1879</p>
	<p>Beginning at the standard cor. of T. 26 N., Rs. 49 and 50 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fifth Standard Parallel North through Ranges 48 1/2 and 49 East, executed under Group No. 92.</p>
	<p>N. 1°07'30" W., bet. secs. 31 and 36.</p>
	<p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
24.10	<p>Trail road, 10 lks. wide, bears N. 60° E. and S. 60° W.</p>
38.981	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>T26N 1/4 R49E R50E S36 S31 2013</p>
43.70	<p>Pine Creek, 15 lks. wide, 1/2 ft. deep, course N. 75° E.</p>
57.00	<p>Trail road, 10 lks. wide, bears E. and W.</p>
77.962	<p>The cor. of secs. 25, 30, 31 and 36, monumented with an unmarked squared wooden post, 4x4 ins., 4 ft. long, lying loose on the ground. The base of the wooden post is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T26N R49E R50E S25 S30 <hr style="width: 50%; margin: 0 auto;"/> S36 S31 2013 </div> <p>Bury the wooden post alongside the stainless steel post.</p> <hr/> <p>N. 0°12'10" E., bet. secs. 25 and 30.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
8.40	Barbed wire fence, 4 strand, parallels Cortez Beowawe Road.
9.70	Cortez Beowawe Road, improved gravel, 50 lks. wide, bears N. 80° E. and S. 80° W.
40.715	<p>The 1/4 sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26N 1/4 R49E R50E S25 S30 2013 </div> <p>From this point, the decayed remains of a wooden post, 3 ins. diam., 7 ft. long, no visible scribe marks, lying loose on the ground, bears N. 25°56'20" E., 3.405 chs. dist.</p>
80.30	Buckhorn Road, improved gravel, 50 lks. wide, bears S. 50° E. and N. 50° W.
81.430	<p>The cor. of secs. 19, 24, 25 and 30, monumented with the unmarked bottom portion of a broken and squared wooden post, 2x2 ins., 18 ins. long, lying loose on the ground, with the upper portion of the squared wooden post, 2x2 ins., 16 ins. long, lying loose on the ground alongside the bottom portion of the wooden post, mkd. with illegible scribe marks. The base of the bottom portion of the wooden post is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T26N R49E R50E S24 S19 <hr style="width: 50%; margin: 0 auto;"/> S25 S30 </div> <div style="text-align: center;">2013</div> <p>Bury both portions of the original wooden post alongside the stainless steel post.</p> <hr/> <p>N. 0°00'30" E., bet. secs. 19 and 24.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>32.80 Willow Creek, 10 lks. wide, 1/2 ft. deep, course S. 85° E.</p> <p>40.624 Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26N 1/4 R49E R50E S24 S19 <hr style="width: 50%; margin: 0 auto;"/> </div> <div style="text-align: center;">2013</div> <p>75.50 Barbed wire fence, 4 strand, bears N. 85° E. and S. 85° W.</p> <p>81.248 The cor. of secs. 13, 18, 19 and 24, determined by person(s) unknown, monumented with an unrecorded General Land Office iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with steel fence post set alongside, projecting 4 ft. above the ground, with brass cap mkd. T26N R49E R50E S13 S18 S24 S19 1930. This position is accepted as the best available evidence of the position of the original corner.</p> <hr/> <p>N. 0°44'20" W., bet. secs. 13 and 18.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>40.829 The 1/4 sec. cor. of secs. 13 and 18, monumented with a squared wooden post, 2x2 ins., 12 ins. long, (Record, 3 ins. wide, 4 ft. long), wired to a steel fence post, firmly set, projecting 4 ft. above the ground, no visible scribe marks.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N 1/4 R49E R50E S13 S18</p> <p>2013</p> </div> <p>Insert the squared wooden post in the stainless steel post. Reset the steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°44'30" E., beginning new measurement.</p>
40.714	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a wooden post, 2 ins. diam., 20 ins. long, (Record, 4x4 ins., 4 1/2 ft. long), with illegible scribe marks visible, wired to a steel fence post, loosely set, projecting 4 ft. above the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R49E R50E S12 S 7 <hr/>S13 S18</p> <p>2013</p> </div> <p>Bury the wooden post alongside the stainless steel post. Reset the steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°25'30" E., bet. secs. 7 and 12.</p>
40.323	<p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>The 1/4 sec. cor. of secs. 7 and 12, monumented with the bottom portion of a broken wooden post, 1 in. diam., 8 ins. long, (Record, 3 ins. wide, 4 ft. long), with no legible marks visible, wired to a steel fence post, firmly set, projecting 4 ft. above the ground, with the upper portion of a wooden post, 2 ins. diam., 10 ins. long, lying loose on the ground alongside the steel fence post.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N 1/4 R49E R50E S12 S 7</p> <p style="text-align: center;">2013</p> <p>Insert both portions of the wooden post in the stainless steel post. Reset the steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°09'10" E., beginning new measurement.</p>
40.756	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an embedded mound of stone (Record, charred post 4 1/2 ft. long, 4x4 ins., in a mound, 2 1/2 ft. high), 4 ft. diam., with a steel fence post, firmly set, S. of cor. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T26N R49E R50E S 1 S 6 <hr/>S12 S 7</p> <p style="text-align: center;">2013</p> <p>Reset the steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°03'30" E., bet. secs. 1 and 6.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
2.20	Trail road, 15 lks. wide, bears S. 50° E. and N. 50° W.
30.20	Quartz Road, improved gravel, 50 lks. wide, bears S. 50° E. and N. 50° W.
40.199	<p>The 1/4 sec. cor. of secs. 1 and 6, perpetuated with an unrecorded General Land Office iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. 1/4 S1 S6 1930, with a wooden post, 2 ins diam., (Record, 3 ins. wide, 4 ft. long), firmly set alongside the iron post, projecting 6 ins. above the ground, with a steel fence post,</p>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	loosely set, projecting 4 ft. above the ground, alongside iron post, with a mound of stone, 4 ft. base, 8 ins. high, W. of cor. This corner is accepted as a careful and faithful perpetuation of the position of the original corner.
	N. 0°22'40" E., beginning new measurement.
40.281	The cor. of Tps. 26 and 27 N., Rs. 49 and 50 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy., T. 27 N., R. 50 E., executed under Group No. 145, with a mound of stone, 3 ft. base, 1 ft. high, S. of cor.
	DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor D.H. Barker in 1879, and a Portion of the Dependent Resurvey Executed By Cadastral Surveyor L.H. Godwin in 1957
	From the 1/4 sec. cor. of sec. 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy., T. 26 N., R. 49 E., executed under Group No. 316.
	from which the 1957 bearing tree
	A dead and standing juniper, 10 ins. diam., bears N. 5° E., 8 lks. dist., with illegible scribe marks visible on a fire scared blaze.
	From this cor. an unrecorded Bureau of Land Management iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with an embedded mound of stone, 3 ft. base, with brass cap mkd. T26N R48E 1/4 S24 1957, bears N. 0°00'28" W., 7.568 chs. dist.
	N. 0°29'20" W., on W. bdy. of sec. 30.
	Over rolling terrain, through bunch grass and scattered sagebrush.
0.60	Wash, 20 lks. wide, 3 ft. deep, drains E.
11.70	Crest of spur, slopes S. 55° E.
17.80	Draw, drains S. 60° E.
19.990	Point for the N 1/16 sec. cor. of sec. 30.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S30</p> <p style="text-align: center;">2013</p>
26.90	Trail road, 15 lks. wide, bears S. 70° E. and N. 70° W.; Road is located on top of a spur, bears SE. and NW.
39.980	<p>The cor. of secs. 19 and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy., T. 26 N., R. 49 E., executed under Group No. 316.</p> <p>from which the 1957 bearing trees</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears N. 56° E., 26 lks. dist., mkd. T26N R49E S19 BT on a partially healed blaze.</p> <p style="padding-left: 40px;">A juniper 12 ins. diam., bears S. 44° E., 7 lks. dist., mkd. T26N R49E S30 BT on a partially healed blaze.</p> <hr/> <p>From the cor. of secs. 6 and 7, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the top of a mound of stone, 4 ft. base, 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy., T. 26 N., R. 49 E., executed under Group No. 316.</p> <p>From this cor., the closing cor. of Tps. 26 and 27 N., R. 48 E., bears N. 0°18'10" E., 2.198 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the independent resurvey of a portion of the N. bdy., T. 26 N., R. 48 E., executed under Group No. 316.</p> <p>N. 3°19'00" E., on the W. bdy. of sec. 6.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
1.90	Draw, drains S. 45° E.
40.068	<p>Point for the 1/4 sec. cor. of sec. 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="border-left: 1px solid black; padding-left: 5px; margin-left: 400px;"> T26N R49E 1/4 S 6 </div> <p style="text-align: center;">2013</p>
60.102	<p>Point for the N 1/16 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="border-left: 1px solid black; padding-left: 5px; margin-left: 400px;"> N 1/16 S 6 </div> <p style="text-align: center;">2013</p>
61.70	<p>Willow Creek, 5 lks. wide, 4 ins. deep, course S. 50° E.,</p>
80.136	<p>Point for the cor. of Tps. 26 and 27 N., Rs. 48 and 49 E., established at record latitude from the cor. of secs. 6 and 7 on the W. bdy. of the Tp., hereinbefore described, and at record departure from the 1/4 sec. cor. of secs. 5 and 32 on the N. bdy. of the Tp., hereinafter described; there is no remaining evidence of the original corner. This cor. will now refer to the NW. cor. of T. 26 N., R. 49 E. only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="border-left: 1px solid black; padding-left: 5px; margin-left: 400px;"> T26N R49E S6 </div> <p style="text-align: center;">2013</p>
<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor D.H. Barker in 1879</p> <hr/> <p>From the cor. of Tps. 26 and 27 N., Rs. 49 and 50 E., hereinbefore described.</p> <p>S. 89°11'20" W., on the N. bdy. of sec. 1.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>	
26.50	<p>Trail road, 15 lks. wide, bears S. 30° E. and N. 30° W.</p>

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.038	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now refer to the 1/4 sec. cor. of sec. 1 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <hr/> <p>T26N R49E 1/4 S1</p> <p>2013</p>
44.90	Trail road, 15 lks. wide, bears N. and S. 5° W.
48.40	Wash, 5 lks. wide, course S. 30° E.
80.076	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now refer to cor. of secs. 1 and 2 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <hr/> <p>S 2 S 1 T26N R49E</p> <p>2013</p> <hr/> <p>S. 89°11'20" W., on the N. bdy. of sec. 2.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
0.10	Trail road, 15 lks. wide, bears S. 20° E. and N. 20° W.
40.038	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now refer to the 1/4 sec. cor. of sec. 2 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <hr/> <p>T26N R49E 1/4 S2</p> <p>2013</p>
66.00	Trail road, 15 lks. wide, bears N. 10° E. and S.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS					
80.076	<p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now refer to cor. of secs. 2 and 3 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <hr style="width: 100px; margin: 0 auto;"/> <table style="margin: 0 auto;"> <tr> <td style="padding: 0 5px;">S 3</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 2</td> </tr> <tr> <td style="padding: 0 5px;">T26N</td> <td style="border-left: 1px solid black; padding: 0 5px;">R49E</td> </tr> </table> <p>2013</p> </div>	S 3	S 2	T26N	R49E
S 3	S 2				
T26N	R49E				
40.038	<p>S. 89°11'20" W., on the N. bdy. of sec. 3.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now refer to the 1/4 sec. cor. of sec. 3 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <hr style="width: 100px; margin: 0 auto;"/> <p>T26N R49E 1/4 S3</p> <p>2013</p> </div>				
80.076	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now refer to cor. of secs. 3 and 4 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <hr style="width: 100px; margin: 0 auto;"/> <table style="margin: 0 auto;"> <tr> <td style="padding: 0 5px;">S 4</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 3</td> </tr> <tr> <td style="padding: 0 5px;">T26N</td> <td style="border-left: 1px solid black; padding: 0 5px;">R49E</td> </tr> </table> <p>2013</p> </div> <p>S. 89°11'20" W., on the N. bdy. of sec. 4.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>	S 4	S 3	T26N	R49E
S 4	S 3				
T26N	R49E				

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS					
40.038	<p>Point for the 1/4 sec. cor. of secs. 4 and 35, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now refer to the 1/4 sec. cor. of sec. 4 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <hr/> <p>T26N R49E 1/4 S4</p> <p>2013</p>				
51.30	Buckhorn Road, improved gravel, 50 lks. wide, bears S. 48° E. and N. 38° W.				
59.90	Barbed wire fence, 4 strand, bears S. 68° E. and N. 68° W.				
60.057	<p>Point for the W 1/16 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <hr/> <p>W 1/16 S 4</p> <p>2013</p>				
80.076	<p>The cor. of secs. 4, 5, 32 and 33, monumented with a porphyry stone, 15x12x7 ins. (Record, 22x14x12 ins.), firmly set, projecting 10 ins. above an embedded mound of stone, 3 ft. diam., mkd. with 2 grooves on W. face and 4 grooves on E. face. This cor. will now refer to the cor. of secs. 4 and 5 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <hr/> <table border="1"> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td>T26N</td> <td>R49E</td> </tr> </table> <p>2013</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>N. 89°37'10" W., on the N. bdy. of sec. 5.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>	S 5	S 4	T26N	R49E
S 5	S 4				
T26N	R49E				

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
5.20	Trail road, 15 lks. wide, bears S. 65° E. and N. 65° W. Thence over rolling terrain, through an active mining area.
20.131	Point for the E 1/16 sec. cor. of sec. 5 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> <hr style="width: 20%; margin: 10px auto;"/> E 1/16 S 5 2013 </div>
40.262	The 1/4 sec. cor. of secs. 5 and 32, monumented with an unmarked flint stone, 19x11x10 ins., firmly set, projecting 10 ins. above the ground. This is accepted as the best available evidence of the position of the original corner. This cor. will now refer to the 1/4 sec. cor. of sec. 5 only. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> <hr style="width: 20%; margin: 10px auto;"/> T26N R49E 1/4 S5 2013 </div> Bury the flint stone alongside the stainless steel post. <div style="text-align: center;"> <hr style="width: 20%; margin: 10px auto;"/> N. 88°40'20" W., beginning new measurement. </div>
40.010	Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now refer to cor. of secs. 5 and 6 only. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> <hr style="width: 20%; margin: 10px auto;"/> <div style="display: inline-block; text-align: center; vertical-align: middle;"> <div style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 6</div> <div style="padding: 0 5px;">S 5</div> </div> T26N R49E 2013 </div>

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>From this point, a rebar, 1/4 in. diam., firmly set, projecting 8 ins. above the ground, bears S. 67°51'20" E., 3.286 chs. dist., with a squared wooden post, 4x4 ins., 4 1/2 ft. long, lying loose on the ground alongside the rebar.</p> <p>From this same point, a scattered mound of stone, bears S. 21°17'00" E., 3.235 chs. dist.</p> <p>From this same point, a scattered mound of stone, bears S. 17°39'30" E., 3.429 chs. dist.</p> <hr/> <p>N. 88°40'20" W., on the N. bdy. of sec. 6.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>40.010 Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now refer to the 1/4 sec. cor. of sec. 6 only.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <hr/> <p style="text-align: center;">T26N R49E 1/4 S6</p> <p style="text-align: center;">2013</p> <p>Thence over rolling terrain, with numerous historic bladed roads, through bunch grass and scattered sagebrush.</p> <p>42.40 Stream, 3 lks. wide, 5 ins. deep, course S. 15° E.</p> <p>86.762 The NW. cor. of T. 26 N., R. 49 E., hereinbefore described.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.L. Bridges in 1879</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10, monumented with a basalt stone, 12x10x8 ins. (Record, red granite, 17x14x12 ins.), loosely set, projecting 10 ins. above an embedded mound of stone, 2 1/2 ft. diam., 4 ins. high, mkd. with 5 grooves on a face and 3 grooves on an adjacent face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
---------------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T26N R49E S 4 S 3 —+— S 9 S10</p> <p style="text-align: center;">2012</p>
	<p>Bury the original stone alongside the stainless steel post.</p> <p>N. 0°59'00" W., bet. secs. 3 and 4.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
24.30	<p>Buckhorn road, improved gravel, 50 lks. wide, S. 45° E. and N. 45° W.</p>
39.789	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R49E 1/4 S 4 S 3</p> <p style="text-align: center;">2013</p>
	<p>From this point, a stone, 16x8x6 ins., firmly set, projecting 6 ins. above the ground, no visible markings, with a lathe, lying loose alongside the stone, mkd. E 1/4 4, in black ink, bears N. 72°21'50" E., 5.332 chs. dist.</p>
79.976	<p>The cor. of secs. 3 and 4 on the N. bdy.</p> <hr/> <p>From the point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R49E S20 S21 —+— S29 S28</p> <p style="text-align: center;">2013</p>
	<p>From this point, the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., bears S. 89°44'50" E., 318.798 chs. dist., hereinbefore described.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this same point, the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., bears S. 0°41'20" W., 158.956 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fifth Standard Parallel North, through Range 49 East, executed under Group No. 92, with a steel fence post, firmly set alongside the iron post, projecting 4 ft. above the ground.</p> <p>The control lines were fully retraced and a careful search was made for evidence of intervening corners, none of which were recovered.</p> <p>N. 2°24'20" W., bet. secs. 20 and 21.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
39.771	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R49E 1/4 S20 S21 2013</p>
79.542	<p>Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R49E S17 S16 — — S20 S21 2013</p> <p>From this point, the point for the cor. of secs. 4, 5, 8 and 9, bears N. 0°19'50" E., 158.947 chs. dist., hereinafter described.</p> <p>From this same point, the cor. of secs. 13, 14, 23 and 24, bears S. 89°54'40" E., 241.705 chs. dist., monumented with a badly decayed wooden post, 3 ins. diam., 8 ins. long, (Record, 3x3 ins., 4 ft. long), lying loose on the ground. The base of the wooden post is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R49E</p> <table border="1"> <tr> <td>S14</td><td>S13</td></tr> <tr> <td>S23</td><td>S24</td></tr> </table> <p>2013</p> </div> <p>Bury the wood post alongside the stainless steel post.</p> <p>The control lines were fully retraced and a careful search was made for evidence of intervening corners, none of which were recovered.</p> <p>From this same point, a deeply embedded mound of stone of unknown origins, 3 ft. diam., bears N. 1°39'20" W., 79.649 chs. dist.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°11'50" W., bet. secs. 4 and 9.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>7.10 Willow Creek, 5 lks. wide, 4 ins. deep, course S. 25° W.</p> <p>41.324 Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R49E</p> <p>S 4</p> <p>1/4 —</p> <p>S 9</p> <p>2013</p> </div> <p>82.648 Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>	S14	S13	S23	S24
S14	S13				
S23	S24				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="878 291 1024 407"> <p>T26N R49E S 5 S 4 — — S 8 S 9</p> </div> <div data-bbox="920 441 984 464">2013</div> <hr/> <p data-bbox="440 527 992 550">N. 0°50'40" E., bet. secs. 4 and 5.</p> <p data-bbox="440 579 1463 632">Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p data-bbox="293 659 1463 711">39.740 Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p data-bbox="440 739 1463 816">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div data-bbox="878 848 1024 932"> <p>T26N R49E 1/4 S 5 S 4</p> </div> <div data-bbox="920 968 984 991">2013</div> <p data-bbox="440 1022 1463 1075">From this point, a deeply embedded mound of stone, 3 1/2 ft. diam., bears N. 53°58'00" W., 4.820 chs. dist.</p> <p data-bbox="440 1102 1463 1155">From this same point, a deeply embedded mound of stone, 4 ft. diam., bears N. 73°20'50" W., 4.254 chs. dist.</p> <p data-bbox="293 1182 1308 1205">57.90 Trail road, 15 lks. wide, bears S. 72° E. and N. 72° W.</p> <p data-bbox="293 1234 1200 1257">59.610 Point for the N 1/16 sec. cor. of secs. 4 and 5.</p> <p data-bbox="440 1287 1463 1365">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div data-bbox="894 1396 1008 1457"> <p>N 1/16 S 5 S 4</p> </div> <div data-bbox="920 1488 984 1512">2013</div> <p data-bbox="293 1541 1341 1564">65.10 Willow Creek, 5 lks. wide, 1/2 ft. deep, course S. 30° E.</p> <p data-bbox="293 1593 1308 1617">76.20 Trail road, 15 lks. wide, bears N. 73° E. and S. 73° W.</p> <p data-bbox="293 1646 1308 1669">77.30 Trail road, 15 lks. wide, bears S. 57° E. and N. 57° W.</p> <p data-bbox="293 1698 1053 1722">79.997 The cor. of sec. 4 and 5 on the N. bdy.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 29, 30, 31 and 32, perpetuated by person(s) unknown, monumented with a rebar, 5/8 in. diam., 18 ins. long (Record, charred post, 3x3 ins., 4 ft. long), firmly set, projecting 3 ins. above a deeply embedded collar of stone, with a cedar fence post, 3 ins. diam., 8 ft. long, lying loose on the ground alongside the rebar. This evidence is consistent with what Lloyd E. Toland found on August 22, 1962, on file with the Bureau of Land Management, Nevada State office, under reports of found corners, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R49E</p> <table style="margin: auto;"> <tr> <td>S30</td><td>S29</td></tr> <tr> <td colspan="2">—</td></tr> <tr> <td>S31</td><td>S32</td></tr> </table> <p>2013</p> </div> <p>Insert the rebar inside the stainless steel post. Deposit the loose cedar fence post N. of the cor. and on top of the mound of stone.</p> <p>N. 89°45'40" W., bet. secs. 30 and 31.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>41.40 Trail road, 15 lks. wide, bears S. 65° E. and N. 65° W.</p> <p>41.660 Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R49E</p> <p>S30</p> <p>1/4 —</p> <p>S31</p> <p>2013</p> </div> <p>90.506 The cor. of secs. 30 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the West bdy. of T. 26 N., R. 49 E., executed under Group No. 316.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p>	S30	S29	—		S31	S32
S30	S29						
—							
S31	S32						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°16'40" E., bet. secs. 29 and 30. Over rolling terrain, through bunch grass and scattered sagebrush.
38.90	Trail road, 30 lks. wide, bears S. 65° E. and N. 65° W.
40.209	Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T26N R49E 1/4 S30 S29 2013
45.40	Horse Canyon road, improved gravel, 50 lks. wide, bears S. 46° E. and N. 46° W.
48.60	Horse Creek, 5 lks. wide, 1/2 ft. deep, course S. 55° E.
80.418	The cor. of secs. 19, 20, 29 and 30, monumented with a deeply embedded mound of stone (Record, charred post, 3x3 ins., 4 ft. long), 2 1/2 ft. diam., 1/2 ft. high, with a 60d nail, firmly set in the center of the embedded mound of stone. The center of the mound of stone is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. T26N R49E S19 S20 S30 S29 2013 Deposit 60d nail alongside the stainless steel post. From the cor. of secs. 20, 21, 28 and 29. N. 88°53'10" W., bet. secs. 20 and 29. Over rolling terrain, through bunch grass and scattered sagebrush.
3.00	Trail road, 15 lks. wide, bears S. 60° E. and N. 60° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.661	<p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R49E S20 1/4 — S29</p> <p style="text-align: center;">2013</p>
51.40	Trail road, 25 lks. wide, bears N. 6° E. and S. 11° W.
79.322	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/> <p>S. 89°58'20" W., bet. secs. 19 and 30.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
42.124	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R49E S19 1/4 — S30</p> <p style="text-align: center;">2013</p>
63.186	<p>Point for the W 1/16 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S19 W 1/16 — S30</p> <p style="text-align: center;">2013</p>
66.80	Horse Canyon road, improved dirt, 30 lks. wide, bears S. 45° E. and N. 45° W.
74.50	Horse Creek, 5 lks. wide, 1/2 ft. deep, course S. 66° E.
84.248	Point for the 80 1/16 sec. cor. of secs. 19 and 30.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S19 1/16 — 80 S30 2013</p>
91.567	<p>The cor. of secs. 19 and 30 on the W. bdy.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30. N. 3°22'40" W., bet. secs. 19 and 20. Over rolling terrain, through bunch grass and scattered sagebrush.</p>
39.779	<p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R49E 1/4 S19 S20 2013</p>
79.558	<p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R49E S18 S17 — S19 S20 2013</p> <p>From this point the cor. of secs. 18 and 19 on the W. bdy of the Tp., bears N. 89°36'50" W., 87.570 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the West bdy. of T. 26 N., R. 49 E., executed under Group No. 316.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same point, the point for the cor. of secs. 5, 6, 7 and 8, bears N. 0°02'50" W., 158.841 chs. dist., hereinafter described.</p> <p>The control lines were fully retraced and a careful search was made for evidence of intervening corners, none of which were recovered.</p> <p>From this same point, a deeply embedded mound of stone, 4 ft. diam., bears N. 2°40'50" E., 42.843 chs. dist.</p> <p>From this same point, a deeply embedded mound of stone, 5 ft. diam., bears N. 0°58'19" W., 79.060 chs. dist.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 88°56'30" W., bet. secs. 17 and 20.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
20.163	<p>Point for the E 1/16 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S17 E 1/16 — S20</p> <p>2013</p> </div>
40.326	<p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R49E S17 1/4 — S20</p> <p>2013</p> </div>
46.00	Trail road, 15 lks. wide, bears, S. 44° E. and N. 10° W.
60.489	<p>Point for the W 1/16 sec. cor. of secs. 17 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.652	<p style="text-align: center;">S17 W 1/16 — S20</p> <p style="text-align: center;">2013</p> <p>The cor. of secs. 17, 18, 19 and 20.</p>
40.832	<hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°01'40" W., bet. secs. 5 and 8.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R49E S 5 1/4 — S 8</p> <p style="text-align: center;">2013</p>
44.20	Trail road, 15 lks. wide, bears S. 25° E. and N. 25° W.
81.664	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R49E S 6 S 5 — — S 7 S 8</p> <p style="text-align: center;">2013</p> <p>From this point, the cor. of secs. 6 and 7, on the W. bdy. of the Tp., bears N. 88°50'10" W., 88.859 chs. dist., hereinbefore described.</p> <p>The control line was fully retraced and a careful search was made for evidence of intervening corners, none of which were recovered.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same point, a red granite stone, 17x14x12 ins., firmly set, projecting 10 ins. above a mound of stone, 4 ft. base, 1 ft. high, bears N. 22°18'30" E., 1.462 chs. dist. An examination revealed no visible marks and the mound of stone appeared to be recently constructed and was not congruent with the other original mounds of stones recovered during the course of this survey. This position was not utilized during the course of this survey.</p> <p>From this same point, a mound of stone, 3 ft. base, 1 ft. high, bears N. 89°05'50" W., 2.272 chs. dist.</p> <hr/> <p>N. 1°50'00" W., bet. secs. 5 and 6.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>39.730 Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26N R49E 1/4 S 6 S 5 2013</p> <p>68.70 Trail road, 15 lks. wide, bears S. 50° E. and N. 50° W.</p> <p>72.80 Willow Creek, 5 lks. wide, 4 ins. deep, course East.</p> <p>79.837 The cor. of secs. 5 and 6 on the N. bdy.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands contained within the scope of this survey are located in Eureka County, Nevada, about 45 miles south of the community of Carlin, Nevada. The area is generally rolling, at an average elevation of about 6000 ft. above sea level. The vegetation is generally sagebrush and grasses. Access is provided by numerous dirt roads and by way of Nevada Highway No. 278. There is evidence of grazing and mineral exploration throughout.</p> <hr/>
--------	---

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Brock R. Clifford	Cadastral Surveyor
Brandon G. Courtright	Cadastral Surveyor
Paul L. Moss	Principle Analyst (Contractor)
Josephina M. Campbell	Surveying Technician
Mark G. Petrosine	Surveying Technician
Chris S. Bourgoine	Lead Range Technician

CERTIFICATE OF SURVEY

I, Michael E. Swope, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 13th day of November, 2012, and supplemental special instructions bearing the date of the 18th day of December, 2012. I have dependently resurveyed the east boundary, a portion of the west boundary, the north boundary and a portion of the subdivisional lines, Township 26 North, Range 49 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

OCT 10 2014

(Date)

Michael E. Swope

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the east boundary, a portion of the west boundary, the north boundary and a portion of the subdivisional lines, Township 26 North, Range 49 East, Mount Diablo Meridian, Nevada, executed by Michael E. Swope, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

OCT 10 2014

(Date)

David P. Moran

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 26 N., R. 49 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~