

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE FIFTH STANDARD PARALLEL NORTH

THROUGH RANGE 51 EAST,

THE WEST BOUNDARY

AND A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 26 NORTH, RANGE 51 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Brandon G. Courtright, Cadastral Surveyor

Under Special Instructions dated October 2, 2012,

and approved October 2, 2012,

and Supplemental Special Instructions dated

November 1, 2012, and approved November 1, 2012,

which provided for the surveys included under Group No. 918,

and Assignment Instructions dated October 2, 2012.

Survey commenced October 10, 2012

Survey completed November 14, 2012

INDEX DIAGRAM

TOWNSHIP 26 NORTH, RANGE 51 EAST, MOUNT DIABLO MERIDIAN, NEVADA

10 6	5	4	3	2	1
9 7	8	9	10	11	12
9 18	17	16	15	14	13
8 19	20	21	22	23	24
7 30 12	29	28	27	26	25
6 31 5	11 32 5	33 4	34 3	35 2	36 2

TOWNSHIP 26 NORTH, RANGE 51 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following field notes are those of the dependent resurvey of the Fifth Standard Parallel North through Range 51 East, the west boundary and a portion of the subdivisional lines of Township 26 North, Range 51 East, Mount Diablo Meridian, Nevada.</p> <p>The east boundary was surveyed by U.S. Deputy Surveyor O.A. Palmer in 1869 under Contract No. 33. The Fifth Standard Parallel North through Range 51 East (south boundary), the west and north boundaries and the subdivisional lines were surveyed by D.H. Barker and E.L. Bridges in 1879 under Contract No. 86. The east boundary was dependently resurveyed by Cadastral Engineer P.L. Inch in 1939 under Group No. 201. The north boundary was dependently resurveyed by Cadastral Surveyors J.A. Farmer and S.R. Lambeth in 1984-85 under Group No. 619.</p> <p>Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.</p> <p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 2009</u>, and the <u>Special Instructions for Group No. 918</u>, dated October 2, 2012, and <u>Supplemental Special Instructions</u> dated November 1, 2012.</p> <p>Measurements were made with Trimble R8 Global Positioning System (GPS) receivers using the real-time kinematic method. The direction of each line is with reference to the true meridian. All bearings are mean bearings and the distances are reported as horizontal measurement at a mean ground elevation of 5,600 feet above sea level.</p> <p>The NAD 1983 (2011)(EPOCH:2010.0000) geographic position, of the following corners were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) EGAN EGAN BRGN NV1996 CORS ARP, AST1 AUSTIN 1 CORS ARP, and LKN1 ELKO CORS ARP and carried forward by RTK observations.</p> <p>The standard corner of Tps. 26 N., Rs. 51 and 52 E., is as follows:</p> <p>Latitude: 40°05'01.818" N. Longitude: 116°09'43.445" W.</p> <p>The corner of Tps. 26 and 27 N., Rs. 50 and 51 E., is as follows:</p> <p>Latitude: 40°10'15.980" N. Longitude: 116°16'27.752" W.</p> <p>The October 2, 2012 mean magnetic declination was determined to be 13°15' E., as obtained from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH
THROUGH RANGE 51 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of the Survey Executed by E.L. Bridges in 1879</p>
	<p>Beginning at the standard cor. of Tps. 26 N., Rs. 51 and 52 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Fifth Standard Parallel North, through Range 51 East, executed under Group No. 201.</p> <p>N. 89°43'20" W., on the S. bdy. of sec. 36.</p>
19.50	Crest of hill, bears N. and S.
39.841	<p>Point for the standard 1/4 sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top with brass cap mkd.</p> <p style="text-align: center;">SC T26N R51E 1/4 S36</p> <p style="text-align: center;">2012</p>
75.80	Barbed wire fence, bears S. 30° E. and N. 30° W.
79.682	<p>The standard cor. of secs. 35 and 36, determined by person(s) unknown, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, 14 ins. in the ground, in a partially embedded mound of stone, 4 ft. base. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R51E S35 S36</p> <p style="text-align: center;">2012</p> <p>Bury rebar alongside the stainless steel post.</p>
39.466	<p>N. 89°38'30" W., on S. bdy. of sec. 35.</p> <p>The standard 1/4 sec. cor. of sec. 35, perpetuated by person(s) unknown, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, 14 ins. in the ground, with a volcanic stone, 12x8x4 ins., mkd. 1/4 on a face, loosely set alongside, within an embedded mound of stone, 3 ft. base.</p>

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH
THROUGH RANGE 51 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R51E <u>1/4 S35</u></p> <p style="text-align: center;">2012</p> <p>Insert rebar inside, and bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°47'20" W., beginning new measurement.</p>
40.430	<p>Point for the standard cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R51E <u>S34 S35</u></p> <p style="text-align: center;">2012</p> <hr/> <p>S. 89°47'20" W., on the S. bdy. of sec. 34.</p>
0.20	Dry creek, 15 lks. wide, drains N. 5° W.
1.90	Eureka-Palisade Railroad bed, abandoned, bears N. 10° E., S. 10° W.
5.90	Leave meadows, enter bench, bears N. and S.
15.90	Barbed wire fence, bears N. and S.
18.10	Power transmission line, bears N. 5° E. and S. 5° W.
20.50	Nevada State Route 278, asphalt surface, 30 lks. wide, bears N. and S.
23.50	Barbed wire fence, bears N. and S.
40.430	<p>Point for the standard 1/4 sec. cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH
THROUGH RANGE 51 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">SC T26N R51E <u>1/4 S34</u></p> <p style="text-align: center;">2012</p>
70.80	Power transmission line, bears N. and S.
77.50	Barbed wire fence, bears S. 20° E. and N. 20° W.
80.860	<p>Point for the standard cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R51E <u>S33 S34</u></p> <p style="text-align: center;">2012</p>
40.430	<p>S. 89°47'20" W., on the S. bdy. of sec. 33.</p> <p>Point for the standard 1/4 sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R51E <u>1/4 S33</u></p> <p style="text-align: center;">2012</p>
49.70	J.D. Ranch Road, improved dirt surface, 30 lks. wide, bears S. 70° E. and N. 70° W.
51.70	Power transmission line, bears S. 70° E. and N. 70° W.
80.860	<p>Point for the standard cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SC T26N R51E <u>S32 S33</u></p> <p style="text-align: center;">2012</p>

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH
THROUGH RANGE 51 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°47'20" W., on the S. bdy. of sec. 32.
8.70	Barbed wire fence, bears S. 60° E. and N. 60° W.
40.430	Point for the standard 1/4 sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. SC T26N R51E 1/4 S32 2012
80.860	Point for the standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. SC T26N R51E S31 S32 2012
	S. 89°47'20" W., on the S. bdy. of sec. 31.
16.80	Dirt road, 30 lks. wide, bears S. 10° E. and N. 5° W.
20.215	Point for the standard E 1/16 sec. cor. of sec. 31. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. SC E 1/16 S31 2012
26.90	Barbed wire fence, bears N. and S.
40.10	Creek, 10 lks. wide, 1/2 ft. deep, course N.
40.430	Point for the standard 1/4 sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH
THROUGH RANGE 51 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">SC T26N R51E <u>1/4 S31</u></p>
	<p style="text-align: center;">2012</p>
51.40	Dry creek, 10 lks. wide, drains N.
60.10	Barbed wire fence, bears N. 10° E. and S. 10° W.
66.061	From this point, a wood post, 5x4 ins., firmly set, projecting 20 ins. above ground, no mks. visible, bears South, 0.170 chs. dist., with a steel fence post alongside the wood post, firmly set, projecting 3 ft. above ground.
70.20	Dirt road, 20 lks. wide, bears N. 5° E. and S. 5° W.
77.50	Barbed wire fence, bears S. 60° E. and N. 60° W.
80.860	<p>The standard cor. of Tps. 26 N., Rs. 50 and 51 E., determined by person(s) unknown, monumented with a milled wood post, 5x4 ins., 36 ins. long, lying loose on the ground, no mks. visible. This position has been adopted by a professional land surveyor as shown on map filed with the Nevada State Engineer's Office under application number 13966, dated January 2, 1952, and is accepted as the best available evidence of the position of the original corner.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">SC T26N R50E R51E <u>S36 S31</u></p>
	<p style="text-align: center;">2012</p>
	<p>Bury the wood post alongside the stainless steel post.</p>
	<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 26 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p style="text-align: center;">Reestablishment of the Survey Executed by D.H. Barker in 1879</p> <hr/>
	<p>From the standard cor. of Tps. 26 N., Rs. 50 and 51 E., hereinbefore described.</p>
	<p>N. 0°48'00" E., bet. secs. 31 and 36.</p>
2.20	Barbed wire fence, bears S. 60° E. and N. 60° W.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 26 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 20.107	<p>Point for the S 1/16 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S36 S31</p> <p style="text-align: center;">2012</p>
21.50	Improved dirt road, 15 lks. wide, bears S. 70° E. and N. 85° W.
39.60	J.D. Ranch Road, improved dirt surface, 30 lks. wide, bears N. 70° E. and S. 70° W.
40.214	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N 1/4 R50E R51E S36 S31</p> <p style="text-align: center;">2012</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 23 ins. in the ground, for a reference monument, bears N. 29°54" E., 152.4 lks. dist., with brass cap mkd. RM 1/4 S31 100.6 FT TO COR 2012, and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 60°07" W., 152.0 lks. dist., with brass cap mkd. RM 1/4 S36 100.3 FT TO COR 2012, and an arrow pointing to the corner.</p>
80.428	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R50E R51E S25 S30 S36 S31</p> <p style="text-align: center;">2012</p> <hr/> <p>N. 0°48'00" E., bet. secs. 25 and 30.</p>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 26 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.214	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26N 1/4 R50E R51E S25 S30 2012 </div>
44.10	Dirt road, 20 lks. wide, bears S. 20° E. and N. 15° W.
44.90	Barbed wire fence, bears S. 15° E. and N. 20° W.
51.40	Dirt road, partially overgrown with brush, 15 lks. wide, bears S. 35° E. and N. 30° W.
70.40	Barbed wire fence, bears N. 75° E. and S. 75° W.
80.428	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26N R50E R51E S24 S19 S25 S30 2012 </div>
	N. 0°48'00" E., bet. secs. 19 and 24.
40.214	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26N 1/4 R50E R51E S24 S19 2012 </div>
48.30	Barbed wire fence, bears E. and W.
64.00	Irrigation ditch, 5 lks. wide, 1 ft. deep, bears S. 20° E. and N. 20° W.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 26 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS 71.70	Barbed wire fence, bears E. and W.										
80.428	<p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td colspan="2">T26N</td></tr> <tr><td>R50E</td><td>R51E</td></tr> <tr><td>S13</td><td>S18</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S24</td><td>S19</td></tr> </table> <p>2012</p> </div>	T26N		R50E	R51E	S13	S18	<hr/>		S24	S19
T26N											
R50E	R51E										
S13	S18										
<hr/>											
S24	S19										
40.214	<p>N. 0°48'00" E., bet. secs. 13 and 18.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td colspan="2">T26N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td>R50E</td><td>R51E</td></tr> <tr><td>S13</td><td>S18</td></tr> </table> <p>2012</p> </div>	T26N		1/4		R50E	R51E	S13	S18		
T26N											
1/4											
R50E	R51E										
S13	S18										
80.428	<p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td colspan="2">T26N</td></tr> <tr><td>R50E</td><td>R51E</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S13</td><td>S18</td></tr> </table> <p>2012</p> </div>	T26N		R50E	R51E	S12	S 7	<hr/>		S13	S18
T26N											
R50E	R51E										
S12	S 7										
<hr/>											
S13	S18										
20.107	<p>N. 0°48'00" E., bet. secs. 7 and 12.</p> <p>Point for the S 1/16 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td colspan="2">S 1/16</td></tr> <tr><td>S12</td><td>S 7</td></tr> </table> <p>2012</p> </div>	S 1/16		S12	S 7						
S 1/16											
S12	S 7										

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 26 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.214</p>	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N 1/4 R50E R51E S12 S 7</p> <p>2012</p> </div> <p>From this point, the center of the remains of a circular corral, approximately 100 ft. diam., bears S. 82°37' W., 14.80 chs. dist.</p> <p>From this same point, the center of a leveled pad, 30x30 ft., with disturbed vegetation, bears N. 57°41' W., 18.60 chs. dist.</p>
<p>80.428</p>	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R50E R51E S 1 S 6 S12 S 7</p> <p>2012</p> </div> <p>From this point, the center of a spring, approximately 30 ft. diam., bears S. 7°58'30" E., 1.61 chs. dist.</p>
<p>40.214</p>	<p>N. 0°48'00" E., bet. secs. 1 and 6.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N 1/4 R50E R51E S 1 S 6</p> <p>2012</p> </div>
<p>60.321</p>	<p>Point for the N 1/16 sec. cor. of secs. 1 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 26 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N 1/16 S 1 S 6</p> <p>2012</p>
80.428	<p>The cor. of Tps. 26 and 27 N., Rs. 50 and 51 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 27 N., R. 50 E., executed under Group No. 145.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 26 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by E.L. Bridges in 1879</p> <hr/> <p>From the standard cor. of secs. 31 and 32, hereinbefore described.</p> <p>N. 0°38'50" E., bet. secs. 31 and 32.</p>
37.30	Barbed wire fence, bears S. 70° E. and N. 70° W.
37.80	Power transmission line, bears S. 75° E. and N. 75° W.
38.90	J.D. Ranch Road, improved dirt surface, 30 lks. wide, bears S. 80° E. and N. 75° W.
40.095	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a nail, 12 ins. long, 1/4 in. diam. shank, 1/2 in. diam. head, 24 ins. below the surface of the ground.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, for a reference monument, bears S. 43°50" E., 410.3 lks. dist., with brass cap mkd. RM 1/4 S32 270.8 FT TO COR 2012, and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 46°25" W., 285.3 lks. dist., with brass cap mkd. RM 1/4 S31 188.3 FT TO COR 2012, and an arrow pointing to the corner.</p>
74.90	Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.
80.190	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="883 262 1026 359"> <p>T26N R51E S30 S29 S31 S32</p> </div> <div data-bbox="922 386 984 411">2012</div> <div data-bbox="436 438 1451 598"> <p>From this point, the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., bears N. 0°33'10" E., 401.344 chs. dist., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the S. bdy. of T. 27 N., R. 51 E., executed under Group No. 619.</p> </div> <div data-bbox="436 625 1451 701"> <p>This control line was fully retraced and careful search was made for evidence of intervening corners, none of which was recovered.</p> </div> <div data-bbox="436 728 1451 915"> <p>From this same point, the cor. of secs. 26, 27, 34 and 35, perpetuated by person(s) unknown, bears N. 89°56'10" E., 241.072 chs. dist., monumented with a rebar, 5/8 ins. diam., 18 ins. long, firmly set, 16 ins. in the ground, with a squared wood post, 2x2x18 ins., with illegible scribe marks, lying loose alongside. This is accepted as the best available evidence of the position of the original corner.</p> </div> <div data-bbox="436 942 740 968"> <p>At the corner point</p> </div> <div data-bbox="436 995 1451 1071"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="883 1100 1026 1197"> <p>T26N R51E S27 S26 S34 S35</p> </div> <div data-bbox="922 1224 984 1249">2012</div> <div data-bbox="436 1276 1406 1329"> <p>Insert the rebar inside, and bury the wood post alongside the stainless steel post.</p> </div> <div data-bbox="436 1356 1451 1432"> <p>This control line was fully retraced and careful search was made for evidence of intervening corners, none of which was recovered.</p> </div> <hr/> <div data-bbox="436 1493 1037 1518"> <p>S. 89°57'20" W., bet. secs. 30 and 31.</p> </div> <div data-bbox="290 1545 386 1570">20.126</div> <div data-bbox="436 1545 1229 1570"> <p>Point for the E 1/16 sec. cor. of secs. 30 and 31.</p> </div> <div data-bbox="436 1598 1451 1673"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="873 1680 1032 1755"> <p>S30 E 1/16 — S31</p> </div> <div data-bbox="922 1785 984 1810">2012</div> <div data-bbox="290 1837 386 1862">30.189</div> <div data-bbox="436 1837 1260 1862"> <p>Point for the W-E 1/64 sec. cor. of secs. 30 and 31.</p> </div>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S30 W-E 1/64 S31 2012</p>
31.60	Dirt road, 20 lks. wide, bears N. and S.
32.20	Barbed wire fence, bears N. and S.
40.252	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26N R51E S30 1/4 ——— S31 2012</p>
57.20	Creek, 5 lks. wide, 2 ft. deep, course N.
57.70	Barbed wire fence, bears N. and S.
58.80	Improved dirt road, 120 lks. wide, bears S. 5° E. and N. 5° W.
60.378	<p>Point for the W 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S30 W 1/16 ——— S31 2012</p>
64.60	Improved dirt road, 30 lks. wide, bears S. 10° E. and N. 5° W.
80.625	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy of the Tp., hereinbefore described.</p> <hr/>

TOWNSHIP 26 NORTH, RANGE 51 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

GENERAL DESCRIPTION

The lands included in the survey are located in Eureka County, Nevada, about 45 miles south of the community of Carlin, Nevada. Access is gained by way of J.D. Ranch Road, which can be accessed off of Nevada State Route 278.

The area is mostly level ground. There are two valleys, Garden and Pine, bearing north and south, with a bench between them. Drainage in the valleys is to the north. Rolling hills begin to appear along the east boundary.

The average elevation of the area is 5600 feet.

Vegetation is grass and sagebrush, though large areas on the bench land have been burned. Juniper and scattered pinion pine are present in the hills to the southeast.

There is evidence of grazing in both Garden and Pine Valleys, and the beginnings of mineral exploration in Garden Valley.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Brock R. Clifford	Cadastral Surveyor
Joseph J. Johnson	Cadastral Surveyor
Christopher S. Bourgoine	Surveying Technician

CERTIFICATE OF SURVEY

I, Brandon G. Courtright, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 2nd day of October, 2012, and supplemental special instructions bearing the date of the 1st day of November, 2012, I have dependently resurveyed the Fifth Standard Parallel North through Range 51 East, the west boundary and a portion of the subdivisional lines of Township 26 North, Range 51 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 12, 2013

(Date)

Brandon G. Courtright
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Fifth Standard Parallel North through Range 51 East, the west boundary and a portion of the subdivisional lines of Township 26 North, Range 51 East, of the Mount Diablo Meridian, Nevada, executed by Brandon G. Courtright, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

February 14, 2013

(Date)

Daniel D. Hoffman
(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 26 North, Range 51 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~