

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE EAST BOUNDARY,

A PORTION OF THE SOUTH BOUNDARY

AND A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 33 AND 34,

AND METES-AND-BOUNDS SURVEYS OF

THE RIGHT-OF-WAY LINES OF INTERSTATE HIGHWAY NO. 15

AND A PORTION OF THE WESTERLY RIGHT-OF-WAY LINE OF

THE UNION PACIFIC RAILROAD,

TOWNSHIP 26 SOUTH, RANGE 59 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Richard A. Zaninovich, Cadastral Surveyor

Under Special Instructions dated January 5, 2001,

and approved January 5, 2001,

which provided for the surveys included under Group No. 797,

and Assignment Instructions dated January 5, 2001.

Survey commenced January 9, 2001

Survey completed April 12, 2001

INDEX DIAGRAM

TOWNSHIP 26 SOUTH, RANGE 59 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	42 4 41	32 3 32	24 2 24	18 1 12 18
7	8	40 9 39	31 10 30	23 11 23	17 12 11 16
18	17	38 16 47	30 15 29	22 14 21	16 13 10 15
19	46 20 45	36 21 35	28 22 27	21 23 20	15 24 9 14
30	44 29 43	34 28 34	27 27 26	20 26 19	13 25 8 13
31	42 32 6	33 33 5	25 34 4	18 35 3	12 36 7 2

Subdivision of Section 33 pp. 47 - 48
 Subdivision of Section 34 pp. 48 - 50
 Metes-and-bounds survey of the westerly right-of-way line of Interstate
 Highway No. 15 pp. 50 - 55
 Metes-and-bounds survey of the easterly right-of-way line of Interstate
 Highway No. 15 pp. 56 - 61
 Metes-and-bounds survey of a portion of the westerly right-of-way line
 of the Union Pacific Railroad pp. 61 - 62

073

TOWNSHIP 26 SOUTH, RANGE 59 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of the east boundary, a portion of the south boundary and a portion of the subdivisional lines, the subdivision of sections 33 and 34, and metes-and-bounds surveys of the right-of-way lines of Interstate Highway No. 15 and a portion of the westerly right-of-way line of the Union Pacific Railroad, Township 26 South, Range 59 East, Mount Diablo Meridian, Nevada.

The exterior boundaries and subdivisional lines were surveyed by T.A. Magee in 1883 under Contract No. 149. The west one mile of the south boundary was resurveyed by R.F. Wilson in 1932 under Group No. 205, California. Portions of the north boundary were resurveyed by R.E. Williams in 1992-96 under Group No. 702 and R.A. Zaninovich concurrently under Group No. 797.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated for Group No. 797 dated January 5, 2001.

Measurements were made with Trimble 4400 and 4700 GPS receivers. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The intersections of section lines with right-of-way lines of Interstate Highway No. 15 were determined from ties made to Nevada Department of Transportation monuments as described in the field notes of the metes-and-bounds surveys; the intersections with the right-of-way of the Union Pacific Railroad were determined from ties made to the center of railroad tracks along the tangents and calculations through curves utilizing right-of-way data.

The geographic position NAD83 (1994) of the corner of sections 2, 3, 34 and 35 on the north boundary of the township, as determined by a tie made to National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "CONCH" is as follows:

Latitude 35°43'18.587" N. Longitude 115°20'35.763" W.

The mean magnetic declination is 14° E., as shown on U.S.G.S. quadrangle map "ROACH, NEV." dated 1985.

074

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of the Survey Executed by
T.A. Magee in 1883

Beginning at the cor. of Tps. 26 and 27 S., Rs. 59 and 60 E., monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY T26S T27S R59E R60E RLS 6199, set in a mound of stone under a granite stone, 20x12x8 ins., mkd. with 6 notches on the north, south, east and west edges. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T26S	
R59E R60E	
S36	S31
<hr/>	
S 1	S 6
T27S	

2001

Deposit the rebar inside and the original corner monument alongside the stainless steel post.

N. 89°40'30" W., bet. secs. 1 and 36.

40.525

The 1/4 sec. cor. of secs. 1 and 36, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 1/4 1 36 RLS 6199, set in a mound of stone under a granite stone, 12x10x8 ins., mkd. 1/4 on the north face. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T26S R59E	
S36	
1/4	—
S 1	
T27S	

2001

Deposit the rebar inside and the original corner monument alongside the stainless steel post.

Raise a mound of stone north of the corner.

075

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°51'30" W., beginning new measurement.										
40.685	<p>The cor. of secs. 1, 2, 35 and 36, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 1 2 35 36 RLS 6199, set in a mound of stone under a granite stone, 12x10x8 ins., mkd. with notches, 1 on the east and 5 on the west edges. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T26S</td><td>R59E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td colspan="2">T27S</td></tr> </table> <p>2001</p> </div> <p>Deposit the rebar inside and the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p>	T26S	R59E	S35	S36	<hr/>		S 2	S 1	T27S	
T26S	R59E										
S35	S36										
<hr/>											
S 2	S 1										
T27S											
40.744	<p>S. 89°51'00" W., bet. secs. 2 and 35.</p> <p>The 1/4 sec. cor. of secs. 2 and 35, monumented with a granite stone, 20x8x6 ins., mkd. 1/4 on the north face, set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T26S</td><td>R59E</td></tr> <tr><td>S35</td><td></td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>1/4</td><td>S 2</td></tr> <tr><td colspan="2">T27S</td></tr> </table> <p>2001</p> </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone north of the corner.</p> <hr/> <p>N. 89°31'40" W., beginning new measurement.</p>	T26S	R59E	S35		<hr/>		1/4	S 2	T27S	
T26S	R59E										
S35											
<hr/>											
1/4	S 2										
T27S											

076

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS											
40.876	<p>The cor. of secs. 2, 3, 34 and 35, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 2 3 34 35 RLS 6199, set in a collar of stone under a granite stone, 14x8x6 ins., mkd. with notches, 2 on the east and 4 on the west edges. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td colspan="2">T26S R59E</td></tr> <tr><td>S34</td><td>S35</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td colspan="2">T27S</td></tr> </table> <p>2001</p> </div> <p>Deposit the rebar inside and the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p>	T26S R59E		S34	S35	<hr/>		S 3	S 2	T27S	
T26S R59E											
S34	S35										
<hr/>											
S 3	S 2										
T27S											
	<hr/> <p>N. 89°45'10" W., bet. secs. 3 and 34.</p>										
1.80	Power transmission line, NE-SW.										
25.40	Power transmission line, NE-SW.										
31.80	Power transmission line, NE-SW.										
37.40	Power transmission line, NNE-SSW.										
40.762	<p>Point for the 1/4 sec. cor. of secs. 3 and 34 at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td colspan="2">T26S R59E</td></tr> <tr><td colspan="2">S34</td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td colspan="2">S 3</td></tr> <tr><td colspan="2">T27S</td></tr> </table> <p>2001</p> </div>	T26S R59E		S34		1/4	<hr/>	S 3		T27S	
T26S R59E											
S34											
1/4	<hr/>										
S 3											
T27S											
62.90	Power transmission line, NE-SW.										

077

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>81.524</p>	<p>The cor. of secs. 3, 4, 33 and 34, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 3 4 33 34 RLS 6199, set in a collar of stone. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful reestablishment of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T26S</td><td>R59E</td></tr> <tr><td>S33</td><td>S34</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>T27S</td><td></td></tr> </table> <p>2001</p> </div> <p>Deposit the rebar inside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <p>From this corner a rebar, 1/2 in. diam., with plastic cap, illegible, set in a collar of stone, bears S. 1°08'20" E., 1.869 chs. dist.; no map record of the establishment of this monument was found.</p> <hr/> <p>N. 89°45'10" W., bet. secs. 4 and 33.</p> <p>1.048 Intersect the center of tracks of the Union Pacific Railroad, bears N. 10°24'50" E. and S. 10°24'50" W.</p> <p>6.50 Underground petroleum pipelines, NE-SW.</p> <p>20.353 Point for the E 1/16 sec. cor. of secs. 4 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>E 1/16</td><td>S33</td></tr> <tr><td></td><td>S 4</td></tr> </table> <p>2001</p> </div> <p>Raise a mound of stone north of the corner.</p> <p>40.706 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>	T26S	R59E	S33	S34	S 4	S 3	T27S		E 1/16	S33		S 4
T26S	R59E												
S33	S34												
S 4	S 3												
T27S													
E 1/16	S33												
	S 4												

078

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T26S R59E S33 1/4 — S 4 T27S</p> <p>2001</p> <p>Raise a mound of stone north of the corner.</p>
49.20	Power transmission line, NE-SW.
81.412	<p>The cor. of secs. 4, 5, 32 and 33, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 4 3 32 33 RLS 6199, set flush with the surface of the ground. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T26S R59E S32 S33 — — S 5 S 4 T27S</p> <p>2001</p> <p>Deposit the rebar inside the stainless steel post.</p> <hr/> <p>N. 89°30'20" W., bet. secs. 5 and 32.</p>
13.70	Power transmission lines, NE-SW.
18.00	Underground telephone cables, NE-SW.
18.228	<p>Intersect the easterly right-of-way line of Interstate Highway No. 15 and right-of-way fence.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T26S R59E S32 ROW / — S 5 T27S</p> <p>2001</p>
26.035	Intersect the westerly right-of-way line of Interstate Highway No. 15 and right-of-way fence.

079

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E S32 — / ROW S 5 T27S</p> <p style="text-align: center;">2001</p>
26.20	Underground telephone cable, NE-SW.
40.483	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 1/4 5 32 RLS 6199, set flush with the surface of the ground. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E S32 1/4 — S 5 T27S</p> <p style="text-align: center;">2001</p> <p>Deposit the rebar inside the stainless steel post.</p> <hr/> <p>S. 89°52'10" W., beginning new measurement.</p>
40.580	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2 ins. diam., projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the 1932 resurvey executed by R.F. Wilson under Group No. 205, California, and a mound of stone west of the corner.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by T.A. Magee in 1883</p> <hr/> <p>From the cor. of Tps. 26 and 27 S., Rs. 59 and 60 E., hereinbefore described.</p> <p>N. 0°02'30" E., bet. secs. 31 and 36.</p>

080

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>40.138</p>	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with a granite stone, 20x14x10 ins., mkd. 1/4 on the west face, set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E R60E 1/4 S31 S36</p> <p>2001</p> </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>N. 0°05'10" E., beginning new measurement.</p> <p>40.434</p> <p>The cor. of secs. 25, 30, 31 and 36, monumented with a granite stone, 14x14x12 ins., mkd. with notches, 1 on the south and 5 on the north edges, set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E R60E S25 S30 <hr/>S36 S31</p> <p>2001</p> </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>N. 0°07'10" E., bet. secs. 25 and 30.</p> <p>40.533</p> <p>The 1/4 sec. cor. of secs. 25 and 30, monumented with a granite stone, 12x10x10 ins., mkd. 1/4 on the west face, set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
-----------------------------	--

CHAINS	<div data-bbox="878 260 1024 369" data-label="Text"> <p>T26S R59E R60E 1/4 S25 S30</p> </div> <div data-bbox="915 394 980 417" data-label="Text"> <p>2001</p> </div> <div data-bbox="433 447 1463 499" data-label="Text"> <p>Deposit the original corner monument alongside the stainless steel post.</p> </div> <div data-bbox="433 527 1091 550" data-label="Text"> <p>Raise a mound of stone west of the corner.</p> </div> <hr data-bbox="688 575 1208 579"/> <div data-bbox="433 606 1089 630" data-label="Text"> <p>N. 0°54'20" E., beginning new measurement.</p> </div> <div data-bbox="280 657 375 680" data-label="Text"> <p>40.285</p> </div> <div data-bbox="433 657 1463 735" data-label="Text"> <p>The cor. of secs. 19, 24, 25 and 30, monumented with a granite stone, 14x12x6 ins., mkd. with notches, 2 on the south and 4 on the north edges, set in a mound of stone.</p> </div> <div data-bbox="433 762 732 787" data-label="Text"> <p>At the corner point</p> </div> <div data-bbox="433 814 1463 892" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="873 921 1019 1054" data-label="Text"> <p>T26S R59E R60E S24 S19 S25 S30</p> </div> <div data-bbox="912 1081 977 1104" data-label="Text"> <p>2001</p> </div> <div data-bbox="433 1134 1463 1184" data-label="Text"> <p>Deposit the original corner monument alongside the stainless steel post.</p> </div> <div data-bbox="433 1213 1088 1236" data-label="Text"> <p>Raise a mound of stone west of the corner.</p> </div> <div data-bbox="433 1264 1463 1369" data-label="Text"> <p>From this corner National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "BEER", monumented with a standard brass tablet set in bedrock, mkd. BEER 1958, bears S. 77°09'20" W., 5.577 chs. dist.</p> </div> <hr data-bbox="431 1394 1451 1398"/> <div data-bbox="433 1423 1006 1446" data-label="Text"> <p>N. 0°16'40" W., bet. secs. 19 and 24.</p> </div> <div data-bbox="276 1474 370 1497" data-label="Text"> <p>40.281</p> </div> <div data-bbox="433 1474 1463 1551" data-label="Text"> <p>The 1/4 sec. cor. of secs. 19 and 24, monumented with a granite stone, 20x16x6 ins., mkd. 1/4 on the west face, set in a mound of stone.</p> </div> <div data-bbox="433 1579 729 1604" data-label="Text"> <p>At the corner point</p> </div> <div data-bbox="433 1631 1463 1709" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="870 1738 1016 1845" data-label="Text"> <p>T26S R59E R60E 1/4 S24 S19</p> </div> <div data-bbox="909 1873 974 1896" data-label="Text"> <p>2001</p> </div>
--------	---

082

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>N. 0°07'50" E., beginning new measurement.</p>
5.10	Power transmission line, NE-SW.
12.70	Power transmission line, NE-SW.
40.286	<p>The cor. of secs. 13, 18, 19 and 24, monumented with a rebar, 5/8 in. diam., no cap, set in a mound of stone; this is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E R60E S13 S18 <hr/>S24 S19</p> <p>2001</p> </div> <p>Deposit the rebar inside the stainless steel post.</p> <hr/> <p>N. 0°24'20" W., bet. secs. 13 and 18.</p>
40.390	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with a granite stone, 18x14x8 ins., mkd. 1/4 on the west face, set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E R60E 1/4 S13 S18</p> <p>2001</p> </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>N. 1°01'30" E., beginning new measurement.</p>
40.297	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a granite stone, 18x12x10 ins., mkd. with notches, 4 on the south and 2 on the north edges, set in a mound of stone.</p>

083

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E R60E S12 S 7 ----- S13 S18</p> </div> <p style="text-align: center;">2001</p> <p>Deposit the original corner monument alongside the stainless steel post.</p> <hr/> <p>N. 0°39'30" W., bet. secs. 7 and 12.</p>
10.00	Power transmission line, NE-SW.
40.162	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with a granite stone, 14x12x6 ins., mkd. 1/4 on the west face, set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E R60E 1/4 S12 S 7</p> </div> <p style="text-align: center;">2001</p> <p>Deposit the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>N. 0°09'20" E., beginning new measurement.</p>
1.50	Power transmission line, NE-SW.
5.90	Power transmission line, NE-SW.
20.60	Power transmission line, NE-SW.
40.906	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a granite stone, 10x8x8 ins., mkd. with notches, 5 on the south and 1 on the north edges, set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

084

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T26S R59E R60E S 1 S 6 <hr/>S12 S 7 2001</p> <p>Deposit the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>N. 0°16'10" E., bet. secs. 1 and 6.</p>
40.218	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T26S R59E R60E 1/4 S 1 S 6 2001</p> <p>Raise a mound of stone west of the corner.</p>
44.90	Power transmission line, NW-SE.
50.20	Power transmission line, NW-SE.
80.436	<p>The cor. of Tps. 25 and 26 S., Rs. 59 and 60 E., monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1992-96 resurvey executed by R.E. Williams under Group No. 702, and a mound of stone south of the corner.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by T.A. Magee in 1883</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36 on the south boundary of the Tp., hereinbefore described.</p> <p>N. 0°17'20" W., bet. secs. 35 and 36.</p>
40.595	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

085

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T26S R59E 1/4 S35 S36 2001</p> <p>Raise a mound of stone west of the corner.</p> <p>81.190 The cor. of secs. 25, 26, 35 and 36, monumented with a rebar, 5/8 in. diam., no cap, set alongside a granite stone, 18x6x6 ins., mkd. with notches, 1 on the south and 1 on the east edges.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E S26 S25 ----- S35 S36 2001</p> <p>Deposit the rebar inside and the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p>
	<hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the east boundary of the Tp., hereinbefore described.</p> <p>N. 89°28'30" W., bet. secs. 25 and 36.</p> <p>40.848 Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T26S R59E S25 1/4 ——— S36 2001</p> <p>Raise a mound of stone north of the corner.</p> <p>81.696 The cor. of secs. 25, 26, 35 and 36.</p>
	<hr/> <p>N. 0°48'20" W., bet. secs. 25 and 26.</p>
	<p>36.70 Power transmission line, NE-SW.</p>
	<p>39.664 Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p>

086

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E 1/4 S26 S25</p> <p style="text-align: center;">2001</p> <p>Raise a mound of stone west of the corner.</p>
42.40	Power transmission line, NE-SW.
79.328	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a wooden hub, no tag, set in a mound of earth; this is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E S23 S24 ----- S26 S25</p> <p style="text-align: center;">2001</p> <p>Deposit the wooden hub inside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the east boundary of the Tp., hereinbefore described.</p> <p>S. 89°29'20" W., bet. secs. 24 and 25.</p>
41.759	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E S24 1/4 ——— S25</p> <p style="text-align: center;">2001</p> <p>Raise a mound of stone north of the corner.</p>
43.10	Power transmission line, NE-SW.
48.70	Power transmission line, NE-SW.

087

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
83.518	The cor. of secs. 23, 24, 25 and 26.
	<hr/>
	N. 0°10'30" E., bet. secs. 23 and 24.
6.50	Power transmission line, NE-SW.
40.683	Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T26S R59E 1/4 S23 S24
	2001
	Raise a mound of stone west of the corner.
63.50	Power transmission line, NE-SW.
72.00	Power transmission line, NE-SW.
81.366	The cor. of secs. 13, 14, 23 and 24, monumented with a rebar, 5/8 in diam., with aluminum cap mkd. LAPS E208 L66S RLS 2708, set alongside an unmarked granite stone, 16x10x8 ins.; this is accepted as the best available evidence of the original corner position.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T26S R59E S13 S14 S23 S24
	2001
	Deposit the rebar inside and unmarked stone alongside the stainless steel post.
	<hr/>
	From the cor. of secs. 13, 18, 19 and 24, on the east boundary of the Tp., hereinbefore described.
	N. 89°57'40" W., bet. secs. 13 and 24.
41.575	Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

088

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T26S R59E S13 1/4 — S24</p> <p>2001</p> <p>Raise a mound of stone north of the corner.</p>
48.70	Power transmission line, NE-SW.
75.40	Power transmission line, NE-SW.
80.20	Power transmission line, NE-SW.
83.150	The cor. of secs. 13, 14, 23 and 24.
	<hr/>
	N. 0°07'40" E., bet. secs. 13 and 14.
40.512	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>T26S R59E 1/4 S14 S13</p> <p>2001</p> <p>Raise a mound of stone west of the corner.</p>
53.40	Power transmission line, NE-SW.
81.024	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. LAPS E211 L66S RLS 2708, set in a mound of earth; this is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>T26S R59E S11 S12 — S14 S13</p> <p>2001</p> <p>Deposit the rebar inside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p>
	<hr/>
	From the cor. of secs. 7, 12, 13 and 18, on the east boundary of the Tp., hereinbefore described.

089

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 89°43'30" W., bet. secs. 12 and 13.
11.00	Power transmission line, NE-SW.
37.70	Power transmission line, NE-SW.
40.90	Power transmission line, NE-SW.
41.694	Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T26S R59E S12 1/4 — S13 2001 </div>
	Raise a mound of stone north of the corner.
64.10	Power transmission line, NE-SW.
83.388	The cor. of secs. 11, 12, 13 and 14.
	<hr/>
	N. 1°14'50" E., bet. secs. 11 and 12.
40.353	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T26S R59E 1/4 S11 S12 2001 </div>
	Raise a mound of stone west of the corner.
80.706	The cor. of secs. 1, 2, 11 and 12, monumented with a granite stone, 12x8x6 ins., mkd. with notches, 5 on the south and 1 on the east edges, set in a collar of stone. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T26S R59E S 2 S 1 — — S11 S12 2001 </div>

090

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the east boundary of the Tp., hereinbefore described.</p> <p>N. 89°59'00" W., bet. secs. 1 and 12.</p>
40.634	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E S 1 1/4 — S12 2001</p> <p>Raise a mound of stone north of the corner.</p>
81.268	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0°15'20" E., bet. secs. 1 and 2.</p>
40.504	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E 1/4 S 2 S 1 2001</p> <p>Raise a mound of stone west of the corner.</p>
80.796	<p>The cor. of secs. 1, 2, 35 and 36, on the north boundary of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1992-96 resurvey executed by R.E. Williams under Group No. 702, and a mound of stone west of the corner.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the south boundary of the Tp., hereinbefore described.</p> <p>N. 0°20'50" W., bet. secs. 34 and 35.</p>
2.60	Power transmission line, NE-SW.
30.60	Power transmission line, NE-SW.

091

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
36.10	Power transmission line, NE-SW.
40.116	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E 1/4 S34 S35 2001</p> <p>Raise a mound of stone west of the corner.</p>
51.20	Power transmission line, NE-SW.
59.50	Power transmission line, NE-SW.
80.232	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 26 27 34 35 RLS 6199, set alongside a 4x4 post, 3 ft. long, no marks. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E S27 S26 S34 S35 2001</p> <p>Deposit the rebar inside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°29'20" W., bet. secs. 26 and 35.</p>
30.20	Power transmission line, NE-SW.
34.10	Power transmission line, NE-SW.
40.00	Power transmission line, NE-SW.
40.842	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

092

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T26S R59E S26 1/4 — S35 2001</p> <p>Raise a mound of stone north of the corner.</p>
68.40	Power transmission line, NE-SW.
75.30	Power transmission line, NE-SW.
81.684	The cor. of secs. 26, 27, 34 and 35.
	<hr/>
	N. 0°29'10" W., bet. secs. 26 and 27.
40.421	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>T26S R59E 1/4 S27 S26 2001</p> <p>Raise a mound of stone west of the corner.</p>
80.842	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>T26S R59E S22 S23 — — S27 S26 2001</p> <p>Raise a mound of stone west of the corner.</p>
	<hr/>
	From the cor. of secs. 23, 24, 25 and 26.
	N. 89°26'30" W., bet. secs. 23 and 26.
3.40	Power transmission line, NE-SW.
29.80	Power transmission line, NE-SW.
34.40	Power transmission line, NE-SW.
40.620	Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

093

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E S23 1/4 — S26 2001</p> <p>Raise a mound of stone north of the corner.</p>
81.240	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0°03'50" E., bet. secs. 22 and 23.</p>
23.60	Power transmission line, NE-SW.
40.420	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E 1/4 S22 S23 2001</p> <p>Raise a mound of stone west of the corner.</p>
80.840	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E S15 S14 <hr/>S22 S23 2001</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°33'20" W., bet. secs. 14 and 23.</p>
38.00	Power transmission line, NE-SW.

094

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.305	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 1/4 14 23 RLS 6199, set flush with the surface of the ground; a granite stone, 12x8x6 ins., mkd. 1/4, was found lying loosely on the ground a short distance west of the rebar. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E</p> <p>S14</p> <p>1/4 —</p> <p>S23</p> <p>2001</p> </div> <p>Deposit the rebar inside and the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone north of the corner.</p> <hr style="width: 20%; margin-left: 0;"/> <p>S. 89°56'00" W., beginning new measurement.</p>
41.074	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr style="width: 60%; margin-left: 0;"/> <p>N. 0°15'00" E., bet. secs. 14 and 15.</p>
40.420	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E</p> <p>1/4</p> <p>S15 S14</p> <p>2001</p> </div> <p>Raise a mound of stone west of the corner.</p>
80.840	<p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>


095

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div data-bbox="878 268 1024 373"> T26S R59E S10 S11 <hr/> S15 S14 </div> <div data-bbox="919 394 984 422">2001</div> <div data-bbox="435 449 1089 476">Raise a mound of stone west of the corner.</div>
	<div data-bbox="435 527 1073 554">From the cor. of secs. 11, 12, 13 and 14.</div> <div data-bbox="435 581 1024 609">N. 89°56'40" W., bet. secs. 11 and 14.</div>
40.595	<div data-bbox="435 638 1463 688">Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.</div> <div data-bbox="435 716 1463 793">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div data-bbox="857 821 1019 926"> T26S R59E S11 1/4 <hr/> S14 </div> <div data-bbox="919 953 984 980">2001</div> <div data-bbox="435 1008 1101 1035">Raise a mound of stone north of the corner.</div>
81.190	<div data-bbox="435 1058 992 1085">The cor. of secs. 10, 11, 14 and 15.</div>
	<div data-bbox="435 1136 1008 1163">N. 1°00'50" E., bet. secs. 10 and 11.</div>
40.426	<div data-bbox="435 1190 1463 1241">Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</div> <div data-bbox="435 1268 1463 1346">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div data-bbox="873 1373 1019 1478"> T26S R59E 1/4 S10 S11 </div> <div data-bbox="919 1484 984 1512">2001</div> <div data-bbox="435 1539 1084 1566">Raise a mound of stone west of the corner.</div>
80.852	<div data-bbox="435 1589 1463 1640">Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</div> <div data-bbox="435 1667 1463 1745">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div>

096

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> T26S R59E S 3 S 2 <hr style="width: 50%; margin: 0 auto;"/> S10 S11 2001 </div> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°50'10" W., bet. secs. 2 and 11.</p>
40.751	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26S R59E S 2 1/4 — S11 2001 </div> <p>Raise a mound of stone north of the corner.</p>
81.502	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>N. 0°20'40" E., bet. secs. 2 and 3.</p>
22.303	<p>Intersect the center of tracks of the Union Pacific Railroad, bears N. 20°24'30" E. and S. 20°24'20" W.</p>
26.719	<p>Intersect the westerly right-of-way line of the Union Pacific Railroad.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26S R59E S 3 S 2  ROW 2001 </div> <p>Raise a mound of stone west of the corner.</p>
40.420	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

097

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T26S R59E 1/4 S 3 S 2 2001</p> <p>Raise a mound of stone west of the corner.</p>
43.60	Underground petroleum pipelines, NE-SW.
80.931	<p>The cor. of secs. 2, 3, 34 and 35, on the north boundary of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1992-96 resurvey executed by R.E. Williams under Group No. 702, and a mound of stone west of the corner.</p> <p>From this corner National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "CONCH", monumented with a standard brass tablet set in bedrock, mkd. CONCH 1958, bears N. 17°23'30" W., 61.304 chs. dist.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the south boundary of the Tp., hereinbefore described.</p> <p>N. 0°26'30" W., bet. secs. 33 and 34.</p>
5.500	Intersect the center of tracks of the Union Pacific Railroad, bears N. 10°24'50" E. and S. 10°24'50" W.
19.40	Underground petroleum pipelines, NE-SW.
40.166	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T26S R59E 1/4 S33 S34 2001</p> <p>Raise a mound of stone west of the corner.</p> <p>From this corner National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "ROACH", monumented with a standard brass tablet set in a concrete post, mkd. ROACH 1935, bears S. 39°22'40" E., 7.520 chs. dist.</p>
60.249	<p>Point for the N 1/16 sec. cor. of secs. 33 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>N 1/16 S33 S34 2001</p>

098

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Raise a mound of stone west of the corner.								
68.30	Power transmission line, NE-SW.								
80.332	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. BK JEFFERSON PLS 8421, set flush with the surface of the ground. This monument was set by Brett K. Jefferson, Professional Land Surveyor 8421, in 1997, as shown on Record of Survey File 87 Page 67, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful reestablishment of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>T26S R59E</td><td></td></tr> <tr> <td>S28</td><td>S27</td></tr> <tr> <td>S33</td><td>S34</td></tr> </table> <p>2001</p> </div> <p>Deposit the rebar inside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°41'00" W., bet. secs. 27 and 34.</p>	T26S R59E		S28	S27	S33	S34		
T26S R59E									
S28	S27								
S33	S34								
40.821	<p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>T26S R59E</td><td></td></tr> <tr> <td>S27</td><td></td></tr> <tr> <td>1/4</td><td>—</td></tr> <tr> <td>S34</td><td></td></tr> </table> <p>2001</p> </div> <p>Raise a mound of stone north of the corner.</p>	T26S R59E		S27		1/4	—	S34	
T26S R59E									
S27									
1/4	—								
S34									
67.324	Intersect the center of tracks of the Union Pacific Railroad, bears N. 10°25'00" E. and S. 10°25'00" W.								
68.863	<p>Intersect the westerly right-of-way line of the Union Pacific Railroad.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>								

099

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: right;">T26S R59E</div> <div style="text-align: center;"> $\begin{array}{r} S27 \\ \hline S34 \end{array} \bigg/ \text{ROW}$ </div> <div style="text-align: center;">2001</div> <p>Raise a mound of stone west of the corner.</p> <p>69.10 Underground petroleum pipelines, NE-SW.</p> <p>73.50 Power transmission line, NE-SW.</p> <p>81.642 The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0°24'50" W., bet. secs. 27 and 28.</p> <p>40.220 Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: right;">T26S R59E</div> <div style="text-align: center;"> $\begin{array}{r} 1/4 \\ S28 \end{array} \bigg S27$ </div> <div style="text-align: center;">2001</div> <p>Raise a mound of stone west of the corner.</p> <p>80.440 The cor. of secs. 21, 22, 27 and 28, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. BK JEFFERSON PLS 8421, set flush with the surface of the ground. This monument was set by Brett K. Jefferson, Professional Land Surveyor 8421, in 1997, as shown on Record of Survey File 87 Page 67, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful reestablishment of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: right;">T26S R59E</div> <div style="text-align: center;"> $\begin{array}{r} S21 \end{array} \bigg \begin{array}{r} S22 \\ \hline S28 \end{array} \bigg S27$ </div> <div style="text-align: center;">2001</div> <p>Deposit the rebar inside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°58'00" W., bet. secs. 22 and 27.</p>
--------	---

100

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.40	Power transmission line, NE-SW.
40.761	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26S R59E S22 1/4 <u> </u> S27 2001 </div> <p>Raise a mound of stone north of the corner.</p>
51.827	Intersect the center of tracks of the Union Pacific Railroad, bears N. 10°25'10" E. and S. 10°25'00" W.
53.367	<p>Intersect the westerly right-of-way line of the Union Pacific Railroad.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26S R59E S22 <u> </u> / ROW S27 2001 </div> <p>Raise a mound of stone west of the corner.</p>
54.00	Underground petroleum pipelines, NE-SW.
81.522	The cor. of secs. 21, 22, 27 and 28.
	<hr/>
	N. 0°25'20" W., bet. secs. 21 and 22.
40.124	<p>Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26S R59E 1/4 S21 S22 2001 </div> <p>Raise a mound of stone west of the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS					
80.248	<p>The cor. of secs. 15, 16, 21 and 22, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 15 16 21 22 RLS 6199, set flush with the surface of the ground. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful reestablishment of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E</p> <table border="1" style="margin: auto;"> <tr> <td>S16</td><td>S15</td></tr> <tr> <td>S21</td><td>S22</td></tr> </table> <p>2001</p> </div> <p>Deposit the rebar inside the stainless steel post.</p>	S16	S15	S21	S22
S16	S15				
S21	S22				
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°37'10" W., bet. secs. 15 and 22.</p>				
37.096	<p>Intersect the center of tracks of the Union Pacific Railroad, bears N. 10°25'20" E. and S. 10°25'10" W.</p>				
38.638	<p>Intersect the westerly right-of-way line of the Union Pacific Railroad.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E</p> <table border="1" style="margin: auto;"> <tr> <td>S15</td><td rowspan="2">ROW</td></tr> <tr> <td>S22</td></tr> </table> <p>2001</p> </div> <p>Raise a mound of stone west of the corner.</p>	S15	ROW	S22	
S15	ROW				
S22					
39.00	<p>Underground petroleum pipelines, NE-SW.</p>				
41.096	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>				

102

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T26S R59E S15 1/4 — S22</p> <p style="text-align: center;">2001</p> <p>Raise a mound of stone north of the corner.</p> <p>82.192 The cor. of secs. 15, 16, 21 and 22.</p>
	<hr/> <p>N. 0°51'40" E., bet. secs. 15 and 16.</p> <p>40.591 Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E 1/4 S16 S15</p> <p style="text-align: center;">2001</p>
	<p>81.182 The cor. of secs. 9, 10, 15 and 16, monumented with a iron post, 2 ins. diam., with brass cap mkd. N. P. CO. 9 10 15 16 RLS 6199, set in a collar of stone. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as the best available evidence of the original corner position.</p> <p>Not remonumented.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°51'00" W., bet. secs. 10 and 15.</p>
	<p>22.541 Intersect the center of tracks of the Union Pacific Railroad, bears N. 10°25'20" E. and S. 10°25'20" W.</p> <p>24.082 Intersect the westerly right-of-way line of the Union Pacific Railroad.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E S10 — / ROW S15</p> <p style="text-align: center;">2001</p> <p>Raise a mound of stone west of the corner.</p> <p>25.00 Underground petroleum pipelines, NE-SW.</p>

103

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.656	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26S R59E S10 1/4 ——— S15 2001 </div>
81.312	<p>Raise a mound north of the corner.</p> <p>The cor. of secs. 9, 10, 15 and 16.</p>
40.512	<hr/> <p>N. 0°53'00" E., bet. secs. 9 and 10.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26S R59E 1/4 S 9 S10 2001 </div>
81.024	<p>Raise a mound of stone west of the corner.</p> <p>The cor. of secs. 3, 4, 9 and 10, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 3 4 9 10 RLS 6199, set in a collar of stone under a granite stone, 12x8x6 ins., mkd. with notches, 3 on the east and 5 on the south edges. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26S R59E S 4 S 3 ——— S 9 S10 2001 </div> <p>Deposit the rebar inside and the original corner monument alongside the stainless steel post.</p>

104

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Raise a mound of stone west of the corner.</p> <p>From this corner National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "EYAS", monumented with a standard brass tablet set in a concrete post, mkd. EYAS 1958, bears N. 49°57'20" W., 28.600 chs. dist.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°58'30" W., bet. secs. 3 and 10.</p> <p>7.867 Intersect the center of tracks of the Union Pacific Railroad, on curve concave southeast.</p> <p>9.452 Intersect the westerly right-of-way line of the Union Pacific Railroad.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E</p> <p>S 3</p> <hr style="width: 50px; margin: 0 auto;"/> <p>S10 / ROW</p> <p>2001</p> </div> <p>Raise a mound of stone west of the corner.</p> <p>10.80 Underground petroleum pipelines, NE-SW.</p> <p>40.740 Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E</p> <p>S 3</p> <p>1/4 <hr style="width: 50px; margin: 0 auto;"/></p> <p>S10</p> <p>2001</p> </div> <p>Raise a mound of stone north of the corner.</p> <p>81.480 The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>N. 0°22'20" E., bet. secs. 3 and 4.</p> <p>40.763 Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

105

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T26S R59E 1/4 S 4 S 3 2001</p> <p>Raise a mound of stone west of the corner.</p>
81.189	<p>The cor. of secs. 3, 4, 33 and 34, on the north boundary of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1992-96 resurvey executed by R.E. Williams under Group No. 702, and a mound of stone west of the corner.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the south boundary of the Tp., hereinbefore described.</p> <p>N. 0°52'00" E., bet. secs. 32 and 33.</p>
40.246	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T26S R59E 1/4 S32 S33 2001</p> <p>Raise a mound of stone west of the corner.</p>
80.492	<p>From this corner National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "DOLLY", monumented with a standard brass tablet set in a concrete post, mkd. DOLLY 1958, bears N. 48°38'00" W., 28.475 chs. dist.</p> <p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T26S R59E S29 S28 S32 S33 2001</p> <p>Raise a mound of stone west of the corner.</p> <p>From this corner a rebar, 5/8 in. diam., with aluminum cap mkd. BK JEFFERSON PLS 8421, set flush with the surface of the ground, bears N. 2°05'20" W., 0.234 chs. dist. This monument was set by Brett K. Jefferson, Professional Land Surveyor 8421, in 1997, as shown on Record of Survey File 87 Page 67, on file in the office of the Clark County Recorder, using incorrect control and is not utilized in the course of this resurvey.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this same corner an iron pipe, 3/4 in. diam., no cap, projecting 4 ins. above the ground, bears S. 67°38'30" W., 2.667 chs. dist.; no map record of the establishment of this monument was found.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°38'20" W., bet. secs. 28 and 33.</p>
39.780	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E</p> <p>S28</p> <p>1/4 —</p> <p>S33</p> <p>2001</p> </div> <p>Raise a mound of stone north of the corner.</p>
79.560	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0°22'00" W., bet. secs. 28 and 29.</p>
26.00	Power transmission lines, NE-SW.
40.242	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E</p> <p>1/4</p> <p>S29 S28</p> <p>2001</p> </div> <p>Raise a mound of stone west of the corner.</p>
56.20	Underground telephone cables, NE-SW.
57.288	<p>Intersect the easterly right-of-way line of Interstate Highway No. 15 and right-of-way fence.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

107

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.484	<div data-bbox="868 262 1015 525"> <p>T26S R59E ROW S29 S28 2001</p> </div> <p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="868 735 1015 892"> <p>T26S R59E S20 S21 S29 S28 2001</p> </div> <p>Corner is located in the median of Interstate Highway No. 15, 2 lks. west of the edge of pavement.</p>
39.738	<hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°36'20" W., bet. secs. 21 and 28.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="844 1312 1015 1470"> <p>T26S R59E S21 1/4 — S28 2001</p> </div>
71.70	Raise a mound of stone north of the corner.
76.00	Power transmission lines, NE-SW.
76.114	Underground telephone cables, NE-SW.
76.114	<p>Intersect the easterly right-of-way line of Interstate Highway No. 15 and right-of-way fence.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T26S R59E <div style="display: flex; align-items: center; justify-content: center;"> <div style="margin-right: 5px;">ROW</div> <div style="border-left: 1px solid black; padding-left: 5px; text-align: center;"> S21 <hr style="width: 100%;"/> S28 </div> </div> 2001</p>
79.476	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/>
	<p>N. 1°47'20" W., bet. secs. 20 and 21.</p>
26.211	<p>Intersect the westerly right-of-way line of Interstate Highway No. 15 and right-of-way fence.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T26S R59E <div style="display: flex; align-items: center; justify-content: center;"> <div style="margin-right: 5px;">S20</div> <div style="border-left: 1px solid black; padding-left: 5px; text-align: center;"> S21 <div style="border-left: 1px solid black; height: 100px; margin: 0 auto; width: 2px;"></div> </div> </div> <div style="display: flex; align-items: center; justify-content: center;"> <div style="margin-right: 5px;">/</div> <div style="border-left: 1px solid black; padding-left: 5px; text-align: center;"> ROW <div style="border-left: 1px solid black; height: 100px; margin: 0 auto; width: 2px;"></div> </div> </div> 2001</p>
27.10	<p>Underground telephone cable, NE-SW.</p>
40.260	<p>The 1/4 sec. cor. of secs. 20 and 21, monumented with a limestone, 15x10x10 ins., mkd. 1/4 on the west face, set in a mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T26S R59E 1/4 S20 S21 2001</p> <p>Deposit the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>N. 0°35'30" E., beginning new measurement.</p>
40.634	<p>Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="867 260 1013 365"> <p>T26S R59E S17 S16 — — S20 S21</p> </div> <div data-bbox="906 394 971 415">2001</div> <p>Raise a mound of stone west of the corner.</p> <p>From this corner a rebar, 5/8 in. diam., with aluminum cap mkd. BK JEFFERSON PLS 8421, set flush with the surface of the ground, bears N. 1°39'00" W., 0.280 chs. dist. This monument was set by Brett K. Jefferson, Professional Land Surveyor 8421, in 1997, as shown on Record of Survey File 87 Page 67, on file in the office of the Clark County Recorder, using incorrect control and is not utilized in the course of this resurvey.</p> <p>From this same corner a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 16 17 20 21 RLS 6199, set flush with the surface of the ground, bears N. 7°12'10" W., 0.303 chs. dist. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder, using incorrect control and is not utilized in the course of this resurvey.</p> <p>From this same corner National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "HEAP", monumented with a standard brass tablet set in a concrete post, mkd. HEAP 1958, bears S. 20°12'20" E., 13.732 chs. dist.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°09'20" W., bet. secs. 16 and 21.</p> <p>39.858 Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="847 1394 1013 1499"> <p>T26S R59E S16 1/4 — S21</p> </div> <div data-bbox="906 1528 971 1549">2001</div> <p>From this corner a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 1/4 16 21 RLS 6199, set flush with the surface of the ground, bears N. 2°16'40" W., 0.146 chs. dist. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder, using incorrect control and is not utilized in the course of this resurvey.</p> <p>52.20 Power transmission lines, NE-SW.</p> <p>59.70 Underground telephone cables, NE-SW.</p>
--------	---

110

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
59.748	<p>Intersect the easterly right-of-way line of Interstate Highway No. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E</p> <p>ROW / S16</p> <p> S21</p> <p>2001</p> </div>
59.90	Right-of-way fence.
76.70	Right-of-way fence.
76.90	Underground telephone cable, NE-SW.
77.855	<p>Intersect the westerly right-of-way line of Interstate Highway No. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E</p> <p>S16 /</p> <p> ROW</p> <p>S21</p> <p>2001</p> </div>
79.716	The cor. of secs. 16, 17, 20 and 21.
40.633	<p>N. 0°19'40" W., bet. secs. 16 and 17.</p> <hr/> <p>The 1/4 sec. cor. of secs. 16 and 17, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 1/4 16 17 RLS 6199, set under a limestone, 18x8x8 ins., mkd. 1/4 on the west face. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E</p> <p>1/4</p> <p>S17 S16</p> <p>2001</p> </div> <p>Deposit the rebar inside and the original corner monument alongside the stainless steel post.</p>

111

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Corner is located 1 lk. east of a fence which bears N-S.</p> <hr/>								
40.338	<p>N. 1°24'20" E., beginning new measurement.</p> <p>The cor. of secs. 8, 9, 16 and 17, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 8 9 16 17 RLS 6199, set in a collar of stone under a limestone, 14x8x6 ins., mkd. with 4 grooves on the south and east faces. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T26S</td><td>R59E</td></tr> <tr><td>S 8</td><td>S 9</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S17</td><td>S16</td></tr> </table> <p>2001</p> </div> <p>Deposit the rebar inside and the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/>	T26S	R59E	S 8	S 9	<hr/>		S17	S16
T26S	R59E								
S 8	S 9								
<hr/>									
S17	S16								
40.080	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°18'50" W., bet. secs. 9 and 16.</p> <p>The 1/4 sec. cor. of secs. 9 and 16, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 1/4 9 16 RLS 6199. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful reestablishment of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T26S</td><td>R59E</td></tr> <tr><td>S 9</td><td></td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td>S16</td><td></td></tr> </table> <p>2001</p> </div> <p>Deposit the rebar inside the stainless steel post.</p> <p>Raise a mound of stone north of the corner.</p> <hr/>	T26S	R59E	S 9		1/4	<hr/>	S16	
T26S	R59E								
S 9									
1/4	<hr/>								
S16									

112

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°18'50" W., beginning new measurement.
2.70	Power transmission lines, NE-SW.
4.50	Underground telephone cables, NE-SW.
6.846	Intersect the easterly right-of-way line of Interstate Highway No. 15 and right-of-way fence. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T26S R59E S 9 ROW / S16 2001 </div>
14.875	Intersect the westerly right-of-way line of Interstate Highway No. 15 and right-of-way fence. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T26S R59E S 9 — / ROW S16 / 2001 </div>
15.00	Underground telephone cable, NE-SW.
40.080	The cor. of secs. 8, 9, 16 and 17.
	<hr/>
	N. 0°24'40" E., bet. secs. 8 and 9.
40.283	Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T26S R59E 1/4 S 8 S 9 2001 </div>
	Raise a mound of stone west of the corner.

113

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
80.566	<p>The cor. of secs. 4, 5, 8 and 9, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 4 5 8 9 RLS 6199, set in a mound of stone under a limestone, 14x8x6 ins., mkd. with notches, 5 on the south and 4 on the east edges. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26S R59E</p> <table style="margin: auto;"> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> </table> <p>2001</p> </div> <p>Deposit the rebar inside and the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/>	S 5	S 4	<hr/>		S 8	S 9
S 5	S 4						
<hr/>							
S 8	S 9						
	<p>From the cor. of secs. 3, 4, 9 and 10.</p>						
	<p>N. 89°38'20" W., bet. secs. 4 and 9.</p>						
21.60	<p>Power transmission lines, NE-SW.</p>						
23.60	<p>Underground telephone cables, NE-SW.</p>						
24.995	<p>Intersect the easterly right-of-way line of Interstate Highway No. 15 and right-of-way fence.</p>						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>						
	<div style="text-align: center;"> <p>T26S R59E</p> <table style="margin: auto;"> <tr> <td>ROW</td> <td>S 4</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td></td> <td>S 9</td> </tr> </table> <p>2001</p> </div>	ROW	S 4	<hr/>			S 9
ROW	S 4						
<hr/>							
	S 9						
33.036	<p>Intersect the westerly right-of-way line of Interstate Highway No. 15 and right-of-way fence.</p>						
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T26S R59E $\begin{array}{r} S\ 4 \\ \hline S\ 9 \end{array} \bigg/ \text{ROW}$ 2001</p>
33.20	Underground telephone cable, NE-SW.
40.407	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E $\begin{array}{r} S\ 4 \\ 1/4 \text{ ---} \\ S\ 9 \end{array}$ 2001</p> <p>Raise a mound of stone north of the corner.</p>
80.814	The cor. of secs. 4, 5, 8 and 9.
40.636	<p>N. 0°34'10" E., bet. secs. 4 and 5.</p> <p>The 1/4 sec. cor. of secs. 4 and 5, monumented with a limestone, 16x8x6 ins., mkd. 1/4 on the west face, set in a collar of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T26S R59E $\begin{array}{r} 1/4 \\ S\ 5 \big S\ 4 \end{array}$ 2001</p> <p>Deposit the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p>
40.523	<p>N. 0°02'20" W., beginning new measurement.</p> <p>The cor. of secs. 4, 5, 32 and 33, on the north boundary of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the 1992-96 resurvey executed by R.E. Williams under Group No. 702, and a mound of stone west of the corner.</p> <p>From the cor. of secs. 5, 6, 31 and 32, on the south boundary of the Tp., hereinbefore described.</p>

115

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 1°42'20" E., bet. secs. 31 and 32.
13.00	Underground gas pipeline, NNE-SSW.
39.439	Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T26S R59E 1/4 S31 S32 2001 Raise a mound of stone west of the corner.
78.878	The cor. of secs. 29, 30, 31 and 32, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 29 30 31 32 RLS 6199, set in a mound of stone under a limestone, 14x12x8 ins., mkd. with notches, 1 on the south and 5 on the east edges. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T26S R59E S30 S29 S31 S32 2001 Deposit the rebar inside and the original corner monument alongside the stainless steel post. Raise a mound of stone west of the corner. <hr/>
	From the cor. of secs. 28, 29, 32 and 33. S. 89°00'30" W., bet. secs. 29 and 32.
3.60	Power transmission lines, NE-SW.
8.20	Underground telephone cables, NE-SW.
8.329	Intersect the easterly right-of-way line of Interstate Highway No. 15 and right-of-way fence. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

116

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T26S R59E <div style="display: flex; align-items: center; justify-content: center;"> <div style="text-align: right; margin-right: 5px;">ROW</div> <div style="border-left: 1px solid black; padding-left: 5px; text-align: center;"> S29 <hr style="width: 50%; margin: 0;"/> S32 </div> </div> 2001</p>
16.166	<p>Intersect the westerly right-of-way line of Interstate Highway No. 15 and right-of-way fence.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T26S R59E <div style="display: flex; align-items: center; justify-content: center;"> <div style="border-left: 1px solid black; padding-left: 5px; text-align: center;"> S29 <hr style="width: 50%; margin: 0;"/> S32 </div> <div style="margin-left: 5px;">ROW</div> </div> 2001</p>
16.30	Underground telephone cable, NE-SW.
39.965	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T26S R59E S29 <div style="display: flex; align-items: center; justify-content: center;"> <div style="text-align: right; margin-right: 5px;">1/4</div> <div style="border-left: 1px solid black; padding-left: 5px; text-align: center;"> <hr style="width: 50%; margin: 0;"/> S32 </div> </div> 2001</p> <p>Raise a mound of stone north of the corner.</p> <p>From this corner an iron pipe, 3/4 in. diam., no cap, set in a mound of stone, bears S. 6°45'40" E., 2.219 chs. dist.; no map record of the establishment of this monument was found.</p>
79.00	Underground gas pipeline, N-S.
79.930	The cor. of secs. 29, 30, 31 and 32.
	<hr style="border: 0.5px solid black;"/> <p>N. 0°03'50" W., bet. secs. 29 and 30.</p>
29.00	Underground gas pipeline, NNW-SSE.
40.441	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 1/4 29 30 RLS 6199, set in a mound of stone under a limestone, 12x10x4 ins., mkd. 1/4 on the west face. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.</p> <p>At the corner point</p>

117

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E 1/4 S30 S29</p> <p style="text-align: center;">2001</p> <p>Deposit the rebar inside and the original corner monument alongside the stainless steel post.</p> <hr/> <p>N. 0°17'20" E., beginning new measurement.</p>
40.772	<p>The cor. of secs. 19, 20, 29 and 30, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 19 20 29 30 RLS 6199, set in a mound of stone under a limestone, 14x8x6 ins., mkd. with grooves, 2 on the south and 5 on the east faces. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E S19 S20 S30 S29</p> <p style="text-align: center;">2001</p> <p>Deposit the rebar inside and the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°31'40" W., bet. secs. 20 and 29.</p>
4.457	<p>Intersect the westerly right-of-way line of Interstate Highway No. 15 and right-of-way fence.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T26S R59E S20 S29 ROW</p> <p style="text-align: center;">2001</p>

118

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
4.60	Underground telephone cable, NE-SW
39.615	<p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26S R59E S20 1/4 — S29 2001 </div> <p>Raise a mound of stone north of the corner.</p>
79.230	The cor. of secs. 19, 20, 29 and 30.
40.584	<hr/> <p>N. 1°02'30" W., bet. secs. 19 and 20.</p> <p>The 1/4 sec. cor. of secs. 19 and 20, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 1/4 19 20 RLS 6199, set in a mound of stone under a limestone, 14x10x6 ins., mkd. 1/4 on the west face. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T26S R59E 1/4 S19 S20 2001 </div> <p>Deposit the rebar inside and the original corner monument alongside the stainless steel post.</p> <p>Raise a mound of stone west of the corner.</p> <hr/>
40.407	<p>N. 0°18'20" W., beginning new measurement.</p> <p>The cor. of secs. 17, 18, 19 and 20, monumented with a rebar, 5/8 in. diam., with aluminum cap mkd. NEVADA POWER COMPANY 17 18 19 20 RLS 6199, set in a mound of stone alongside a mesquite post, 3 ins. square, 3 ft. long, mkd. with notches, 3 on the south and 5 on the east edges. This monument was set by Joseph P. Fielding, Professional Land Surveyor 6199, in 1988, as shown on Record of Survey File 50 Page 69, on file in the office of the Clark County Recorder; it is accepted as a careful and faithful remonumentation of the original corner position.</p>

119

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div><div>T26S R59E</div><div>S18 S17</div><div><div></div><div>S19 S20</div></div></div>
	2001
	Deposit the rebar inside and the original corner monument alongside the stainless steel post.
	Raise a mound of stone west of the corner.
	<hr/>
	From the cor. of secs. 16, 17, 20 and 21.
	S. 89°36'30" W., bet. secs. 17 and 20.
39.665	Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div><div>T26S R59E</div><div>S17</div><div>1/4 —</div><div>S20</div></div>
	2001
	Raise a mound of stone north of the corner.
79.330	The cor. of secs. 17, 18, 19 and 20.
	<hr/>
	<div>SUBDIVISION OF SECTION 33, T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</div>
	<hr/>
	From the 1/4 sec. cor. of secs. 4 and 33, on the south boundary of the Tp. hereinbefore described.
	N. 0°12'50" E., on the N-S center line of sec. 33.
12.00	Power transmission line, NE-SW.
40.203	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

120

SUBDIVISION OF SECTION 33,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T26S R59E C 1/4 S33</p>
	<p style="text-align: center;">2001</p>
	<p>Raise a mound of stone west of the corner.</p>
80.406	<p>The 1/4 sec. cor. of secs. 28 and 33.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 33 and 34.</p>
	<p>N. 89°41'50" W., on the E-W center line of sec. 33.</p>
20.122	<p>Point for the center E 1/16 sec. cor. of sec. 33.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">E 1/16 C $\frac{\quad}{\quad}$ C S33</p>
	<p style="text-align: center;">2001</p>
	<p>Raise a mound of stone north of the corner.</p>
21.30	<p>Power transmission line, NE-SW.</p>
40.244	<p>The center 1/4 sec. cor.</p>
80.488	<p>The 1/4 sec. cor. of secs. 32 and 33.</p> <hr/>
	<p>From the E 1/16 sec. cor. of secs. 4 and 33, on the south boundary of the Tp., hereinbefore described.</p>
	<p>N. 0°06'50" W., on the N-S center line of the SE1/4 of sec. 33.</p>
40.182	<p>The center E 1/16 sec. cor. of sec. 33.</p> <hr/>
	<p style="text-align: center;">SUBDIVISION OF SECTION 34, T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 3 and 34, on the south boundary of the Tp., hereinbefore described.</p>
	<p>N. 0°23'50" W., on the N-S center line of sec. 34.</p>
14.70	<p>Power transmission line, NE-SW.</p>
40.142	<p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E-W center line.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

121

SUBDIVISION OF SECTION 34,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T26S R59E C 1/4 S34</p> <p style="text-align: center;">2001</p> <p>Raise a mound of stone west of the corner.</p>
60.213	<p>Point for the center N 1/16 sec. cor of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16\ S34 \\ C \end{array}$ </p> <p style="text-align: center;">2001</p> <p>Raise a mound of stone west of the corner.</p>
80.284	<p>The 1/4 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>N. 89°43'10" W., on the E-W center line of sec. 34.</p>
6.50	Power transmission line, NE-SW.
11.40	Power transmission line, NE-SW.
40.792	The center 1/4 sec. cor.
74.950	Intersect the center of tracks of the Union Pacific Railroad, bears N. 10°25'00" E. and S. 10°24'50" W.
77.80	Underground petroleum pipelines, NE-SW.
81.584	<p>The 1/4 sec. cor. of secs. 33 and 34.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec 34.</p> <p>N. 89°42'10" W., on the E-W center line of the NW1/4 of sec. 34.</p>
30.329	Intersect the center of tracks of the Union Pacific Railroad, bears N. 10°25'00" E. and S. 10°25'00" W.
31.868	<p>Intersect the westerly right-of-way line of the Union Pacific Railroad.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} T26S\ R59E \\ S \\ N\ \hline 34\ \diagup\ N \\ \quad \quad \quad ROW \end{array}$ </p> <p style="text-align: center;">2001</p>

SUBDIVISION OF SECTION 34,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Raise a mound of stone west of the corner.
32.60	Underground petroleum pipelines, NE-SW.
40.805	The N 1/16 sec. cor. of secs. 33 and 34.
<hr/> <p style="text-align: center;">METES-AND-BOUNDS SURVEY OF THE WESTERLY RIGHT-OF-WAY LINE OF INTERSTATE HIGHWAY NO. 15, T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	<p>From the point of intersection of the line bet. secs. 5 and 32, on the south boundary of the Tp. with the westerly right-of-way line of Interstate Highway No. 15, hereinbefore described.</p> <p>from which</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 96+53.24 DIST 60.00, bears S. 12°51'10" E., 6.118 chs. dist.</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 96+53.24 DIST OE 54.00 OW 54.00, bears S. 26°21'10" E., 6.920 chs. dist.</p> <p>N. 7°53'30" E., on the westerly right-of-way line of Interstate Highway No. 15 through sec. 32.</p> <p>Along right-of-way fence.</p>
18.951	<p>Point from which centerline station OW 112+81.54 bears S. 82°06'30" E., 3.076 chs. dist.</p> <p>from which</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 112+81.54 DIST 75.00, bears S. 82°06'30" E., 1.939 chs. dist.</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 112+81.54 DIST OE 54.00 OW 54.00, bears S. 82°06'30" E., 3.894 chs. dist.</p>
44.751	<p>Point from which centerline station OW 129+84.33 bears S. 82°06'30" E., 3.076 chs. dist.</p> <p>from which</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 129+84.33 DIST 75.00, bears S. 82°06'30" E., 1.939 chs. dist.</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 129+84.33 DIST OE 54.00 OW 54.00, bears S. 82°06'30" E., 3.894 chs. dist.</p>
75.124	<p>Point from which centerline station OW 149+88.70 bears S. 82°06'30" E., 3.076 chs. dist.</p>

123

METES-AND-BOUNDS SURVEY OF
THE WESTERLY RIGHT-OF-WAY LINE OF INTERSTATE HIGHWAY NO. 15,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 149+88.70 DIST 75.00, bears S. 82°06'30" E., 1.939 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 149+88.70 DIST OE 54.00 OW 54.00, bears S. 82°06'30" E., 3.894 chs. dist.</p> <p>80.742 The point of intersection of the line bet. secs. 29 and 32 with the westerly right-of-way line of Interstate Highway No. 15, hereinbefore described.</p> <hr/> <p>N. 7°53'40" E., on the westerly right-of-way line of Interstate Highway No. 15 through sec. 29.</p> <p>Along right-of-way fence.</p> <p>9.597 Point from which centerline station OW 159+92.67 bears S. 82°06'20" E., 3.076 chs. dist.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 159+92.67 DIST 75.00, bears S. 82°06'20" E., 1.939 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 159+92.67 DIST OE 54.00 OW 54.00, bears S. 82°06'20" E., 3.894 chs. dist.</p> <p>39.687 Point from which centerline station OW 179+78.50 bears S. 82°06'20" E., 3.076 chs. dist.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 179+78.50 DIST 65.00, bears S. 82°06'20" E., 2.091 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 179+78.50 DIST OE 54.00 OW 54.00, bears S. 82°06'20" E., 3.894 chs. dist.</p> <p>70.049 Point from which centerline station OW 199+82.64 bears S. 82°06'20" E., 3.076 chs. dist.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 199+82.64 DIST 60.00, bears S. 82°06'20" E., 2.167 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 199+82.64 DIST OE 54.00 OW 54.00, bears S. 82°06'20" E., 3.894 chs. dist.</p>
--------	--

124

METES-AND-BOUNDS SURVEY OF
THE WESTERLY RIGHT-OF-WAY LINE OF INTERSTATE HIGHWAY NO. 15,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
81.496	<p>The point of intersection of the line bet. secs. 20 and 29 with the westerly right-of-way line of Interstate Highway No. 15, hereinbefore described.</p> <hr/> <p>N. 7°53'40" E., on the westerly right-of-way line of Interstate Highway No. 15 through sec. 20.</p> <p>Along right-of-way fence.</p>
18.900	<p>Point from which centerline station OW 219+85.30 bears S. 82°06'20" E., 3.076 chs. dist.</p> <p>from which</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 219+85.30 DIST 70.00, bears S. 82°06'20" E., 2.015 chs. dist.</p>
26.487	<p>The point of intersection of the line bet. secs. 20 and 21 with the westerly right-of-way line of Interstate Highway No. 15, hereinbefore described.</p> <hr/> <p>N. 7°53'40" E., on the westerly right-of-way line of Interstate Highway No. 15 through sec. 21.</p> <p>Along right-of-way fence.</p>
22.117	<p>Point from which centerline station OW 239+45.77 bears S. 82°06'20" E., 3.076 chs. dist.</p> <p>from which</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 239+45.77 DIST 60.00, bears S. 82°06'20" E., 2.167 chs. dist.</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 239+45.77 DIST OE 54.00 OW 54.00, bears S. 82°06'20" E., 3.894 chs. dist.</p>
33.545	<p>Point from which centerline station OW 247+00.00 bears S. 82°06'20" E., 3.076 chs. dist.</p> <hr/> <p>N. 82°06'20" W., beginning new measurement.</p>
4.545	<p>Point from which centerline station OW 247+00.00 bears S. 82°06'20" E., 7.621 chs. dist.</p> <hr/> <p>N. 7°53'40" E., beginning new measurement.</p>
12.121	<p>Point from which centerline station OW 255+00.00 bears S. 82°06'20" E., 7.621 chs. dist.</p> <hr/> <p>N. 82°06'20" W., beginning new measurement.</p> <p>Leave right-of-way fence.</p>

125

METES-AND-BOUNDS SURVEY OF
THE WESTERLY RIGHT-OF-WAY LINE OF INTERSTATE HIGHWAY NO. 15,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.136	Point from which centerline station OW 255+00.00 bears S. 82°06'20" E., 8.758 chs. dist. <hr/>
	N. 7°53'40" E., beginning new measurement.
8.716	The point of intersection of the line bet. secs. 16 and 21 with the westerly right-of-way line of Interstate Highway No. 15, hereinbefore described. <hr/>
	N. 7°53'45" E., on the westerly right-of-way line of Interstate Highway No. 15 through sec. 16.
3.405	Point from which centerline station OW 263+00.00 bears S. 82°06'15" E., 8.758 chs. dist. <hr/>
	S. 82°06'15" E., beginning new measurement.
1.136	Point from which centerline station OW 263+00.00 bears S. 82°06'15" E., 7.621 chs. dist. <hr/>
	N. 7°53'45" E., beginning new measurement.
	Along right-of-way fence.
18.980	Point from which centerline station OW 275+52.67 bears S. 82°06'15" E., 7.621 chs. dist. <hr/>
	S. 82°06'15" E., beginning new measurement.
4.545	Point from which centerline station OW 275+52.67 bears S. 82°06'15" E., 3.076 chs. dist. and Point of Curvature. from which
	<p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 275+52.67 DIST 175.50, bears S. 82°06'15" E., 0.417 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 275+52.67 DIST 60.00, bears S. 82°06'15" E., 2.167 chs. dist.</p> <hr/>
	Continue on curve to the right with a Radius of 10,311 ft. and a Delta Angle of 8°08'05"; begin new measurement.
22.181	Point from which centerline station OW 289+76.30 bears S. 73°58'10" E., 3.076 chs. dist. and Point of Tangency. from which
	<p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 289+76.30 POT STA OW 289+87.78 PT DIST 150.00, bears S. 73°58'10" E., 0.803 chs. dist.</p>

126

METES-AND-BOUNDS SURVEY OF
THE WESTERLY RIGHT-OF-WAY LINE OF INTERSTATE HIGHWAY NO. 15,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 289+76.30 POT STA OW 289+87.78 PT DIST 60.00, bears S. 73°58'10" E., 2.167 chs. dist.</p>
	<p>N. 16°01'50" E., beginning new measurement.</p>
26.858	<p>Point from which centerline station OW 307+48.76 bears S. 73°58'10" E., 3.076 chs. dist.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 307+48.76 DIST 60.00, bears S. 73°58'10" E., 2.167 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 307+48.76 DIST OE 54.00 OW 54.00, bears S. 73°58'10" E., 3.894 chs. dist.</p>
39.127	<p>The point of intersection of the line bet. secs. 9 and 16 with the westerly right-of-way line of Interstate Highway No. 15, hereinbefore described.</p>
	<p>N. 16°02'00" E., on the westerly right-of-way line of Interstate Highway No. 15 through sec. 9.</p> <p>Along right-of-way fence.</p>
20.406	<p>Point from which centerline station OW 329+05.21 bears S. 73°58'00" E., 3.076 chs. dist.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 329+05.21 DIST 175.50, bears S. 73°58'00" E., 0.417 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 329+05.21 DIST 125.50, bears S. 73°58'00" E., 1.174 chs. dist.</p>
49.039	<p>Point from which centerline station OW 347+94.88 bears S. 73°58'00" E., 3.076 chs. dist.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 347+94.88 DIST OE 54.00 OW 54.00, bears S. 73°58'00" E., 3.894 chs. dist.</p>
81.564	<p>Point from which centerline station OW 369+41.49 bears S. 73°58'00" E., 3.076 chs. dist.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 369+41.49 DIST 200.30, bears S. 73°58'00" E., 0.041 chs. dist.</p>

127

METES-AND-BOUNDS SURVEY OF
THE WESTERLY RIGHT-OF-WAY LINE OF INTERSTATE HIGHWAY NO. 15,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 369+41.49 DIST 150.00, bears S. 73°58'00" E., 0.803 chs. dist.</p>
83.828	<p>The point of intersection of the line bet. secs. 4 and 9 with the westerly right-of-way line of Interstate Highway No. 15, hereinbefore described.</p> <hr/>
	<p>N. 16°02'10" E., on the westerly right-of-way line of Interstate Highway No. 15 through sec. 4.</p> <p>Along right-of-way fence.</p>
26.127	<p>Point from which centerline station OW 388+15.35 bears S. 73°57'50" E., 3.076 chs. dist.</p> <p>from which</p>
	<p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 388+15.35 DIST 150.10, bears S. 73°57'50" E., 0.802 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 388+15.35 DIST OE 54.00 OW 54.00, bears S. 73°57'50" E., 3.894 chs. dist.</p>
53.482	<p>Point from which centerline station OW 406+20.82 bears S. 73°57'50" E., 3.076 chs. dist.</p> <p>from which</p>
	<p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 406+20.82 DIST OE 54.00 OW 54.00, bears S. 73°57'50" E., 3.894 chs. dist.</p>
81.662	<p>Point from which centerline station OW 424+80.72 bears S. 73°57'50" E., 3.076 chs. dist.</p> <p>from which</p>
	<p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OW 424+80.72 DIST 150.00, bears S. 73°57'50" E., 0.803 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 424+80.72 DIST OE 54.00 OW 54.00, bears S. 73°57'50" E., 3.894 chs. dist.</p>
84.295	<p>The point of intersection of the line bet. secs. 4 and 33 with the westerly right-of-way line of Interstate Highway No. 15, monumented with a stainless steel post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the concurrent resurvey of a portion of the south boundary of T. 25 S., R. 59 E., executed by R.A. Zaninovich under this same group.</p> <hr/>

128

METES-AND-BOUNDS SURVEY OF
THE EASTERLY RIGHT-OF-WAY LINE OF INTERSTATE HIGHWAY NO. 15,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the point of intersection of the line bet. secs. 5 and 32, on the south boundary of the Tp. with the easterly right-of-way line of Interstate Highway No. 15, hereinbefore described.</p> <p>from which</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 96+53.24 DIST 100.30, bears S. 20°32'50" W., 6.894 chs. dist.</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 96+53.24 DIST OE 54.00 OW 54.00, bears S. 37°39'50" W., 7.749 chs. dist.</p> <p>N. 7°53'30" E., on the easterly right-of-way line of Interstate Highway No. 15 through sec. 32.</p> <p>Along right-of-way fence.</p>
17.945	<p>Point from which centerline station OE 112+81.54 bears N. 82°06'30" W., 3.030 chs. dist.</p> <p>from which</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 112+81.54 DIST 100.00, bears N. 82°06'30" W., 1.515 chs. dist.</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 112+81.54 DIST OE 54.00 OW 54.00, bears N. 82°06'30" W., 3.848 chs. dist.</p>
43.745	<p>Point from which centerline station OE 129+84.33 bears N. 82°06'30" W., 3.030 chs. dist.</p> <p>from which</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 129+84.33 DIST 100.00, bears N. 82°06'30" W., 1.515 chs. dist.</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 129+84.33 DIST OE 54.00 OW 54.00, bears N. 82°06'30" W., 3.848 chs. dist.</p>
74.118	<p>Point from which centerline station OE 149+88.70 bears N. 82°06'30" W., 3.030 chs. dist.</p> <p>from which</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 149+88.70 DIST 100.00, bears N. 82°06'30" W., 1.515 chs. dist.</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 149+88.70 DIST OE 54.00 OW 54.00, bears N. 82°06'30" W., 3.848 chs. dist.</p>

129

METES-AND-BOUNDS SURVEY OF
THE EASTERLY RIGHT-OF-WAY LINE OF INTERSTATE HIGHWAY NO. 15,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.946	<p>The point of intersection of the line bet. secs. 29 and 32 with the easterly right-of-way line of Interstate Highway No. 15, hereinbefore described.</p> <hr/> <p>N. 7°53'40" E., on the easterly right-of-way line of Interstate Highway No. 15 through sec. 29.</p> <p>Along right-of-way fence.</p>
8.387	<p>Point from which centerline station OE 159+92.67 bears N. 82°06'20" W., 3.030 chs. dist.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 159+92.67 DIST 100.00, bears N. 82°06'20" W., 1.515 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 159+92.67 DIST OE 54.00 OW 54.00, bears N. 82°06'20" W., 3.848 chs. dist.</p>
38.477	<p>Point from which centerline station OE 179+78.50 bears N. 82°06'20" W., 3.030 chs. dist.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 179+78.50 DIST 100.00, bears N. 82°06'20" W., 1.515 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 179+78.50 DIST OE 54.00 OW 54.00, bears N. 82°06'20" W., 3.848 chs. dist.</p>
57.978	<p>The point of intersection of the line bet. secs. 28 and 29 with the easterly right-of-way line of Interstate Highway No. 15, hereinbefore described.</p> <hr/> <p>N. 7°53'40" E., on the easterly right-of-way line of Interstate Highway No. 15 through sec. 28.</p> <p>Along right-of-way fence.</p>
10.861	<p>Point from which centerline station OE 199+82.64 bears N. 82°06'20" W., 3.030 chs. dist.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 199+82.64 DIST 100.00, bears N. 82°06'20" W., 1.515 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 199+82.64 DIST OE 54.00 OW 54.00, bears N. 82°06'20" W., 3.848 chs. dist.</p>

130

METES-AND-BOUNDS SURVEY OF
THE EASTERLY RIGHT-OF-WAY LINE OF INTERSTATE HIGHWAY NO. 15,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
23.396	<p>The point of intersection of the line bet. secs. 21 and 28 with the easterly right-of-way line of Interstate Highway No. 15, hereinbefore described.</p> <hr/>
	<p>N. 7°53'40" E., on the easterly right-of-way line of Interstate Highway No. 15 through sec. 21.</p> <p>Along right-of-way fence.</p>
17.812	<p>Point from which centerline station OE 219+85.30 bears N. 82°06'20" W., 3.030 chs. dist.</p> <p>from which</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 219+85.30 DIST 100.00, bears N. 82°06'20" W., 1.515 chs. dist.</p>
47.516	<p>Point from which centerline station OE 239+45.77 bears N. 82°06'20" W., 3.030 chs. dist.</p> <p>from which</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 239+45.77 DIST 100.00, bears N. 82°06'20" W., 1.515 chs. dist.</p> <p style="padding-left: 40px;">A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 239+45.77 DIST OE 54.00 OW 54.00, bears N. 82°06'20" W., 3.848 chs. dist.</p>
58.944	<p>Point from which centerline station OE 247+00.00 bears N. 82°06'20" W., 3.030 chs. dist.</p> <hr/> <p>S. 82°06'20" E., beginning new measurement.</p>
4.39	<p>Leave right-of-way fence.</p>
4.545	<p>Point from which centerline station OE 247+00.00 bears N. 82°06'20" W., 7.576 chs. dist.</p> <hr/> <p>N. 7°53'40" E., beginning new measurement.</p>
23.060	<p>The point of intersection of the line bet. secs. 16 and 21 with the easterly right-of-way line of Interstate Highway No. 15, hereinbefore described.</p> <hr/>
20.162	<p>N. 7°53'45" E., on the easterly right-of-way line of Interstate Highway No. 15 through sec. 16.</p> <p>Point from which centerline station OE 275+52.67 bears N. 82°06'15" W., 7.576 chs. dist.</p> <hr/>
0.15	<p>N. 82°06'15" W., beginning new measurement.</p> <p>Along right-of-way fence.</p>

131

METES-AND-BOUNDS SURVEY OF
THE EASTERLY RIGHT-OF-WAY LINE OF INTERSTATE HIGHWAY NO. 15,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
4.545	<p>Point from which centerline station OE 275+52.67 bears N. 82°06'15" W., 3.030 chs. dist. and Point of Curvature.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 275+52.67 DIST 100.00, bears N. 82°06'15" W., 1.515 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 275+52.67 DIST 150.00, bears N. 82°06'15" W., 0.758 chs. dist.</p> <hr/> <p>Continue on curve to the right with a Radius of 9,800 ft. and a Delta Angle of 8°08'05"; begin new measurement.</p>
21.082	<p>Point from which centerline station OE 289+76.30 bears N. 73°58'10" W., 3.030 chs. dist. and Point of Tangency.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 289+76.30 POT STA OE 289+72.45 PT DIST 100.00, bears N. 73°58'10" W., 1.515 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 289+76.30 POT STA OE 289+72.45 PT DIST 150.60, bears N. 73°58'10" W., 0.748 chs. dist.</p> <hr/> <p>N. 16°01'50" E., beginning new measurement.</p>
26.858	<p>Point from which centerline station OE 307+48.76 bears N. 73°58'10" W., 3.030 chs. dist.</p> <p>from which</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 307+48.76 DIST 100.00, bears N. 73°58'10" W., 1.515 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 307+48.76 DIST OE 54.00 OW 54.00, bears N. 73°58'10" W., 3.848 chs. dist.</p>
41.251	<p>The point of intersection of the line bet. secs. 9 and 16 with the easterly right-of-way line of Interstate Highway No. 15, hereinbefore described.</p> <hr/> <p>N. 16°02'00" E., on the easterly right-of-way line of Interstate Highway No. 15 through sec. 9.</p> <p>Along right-of-way fence.</p>
18.282	<p>Point from which centerline station OE 329+05.21 bears N. 73°58'00" W., 3.030 chs. dist.</p>

132

METES-AND-BOUNDS SURVEY OF
THE EASTERLY RIGHT-OF-WAY LINE OF INTERSTATE HIGHWAY NO. 15,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	from which
	A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 329+05.21 DIST 88.37, bears N. 73°58'00" W., 1.691 chs. dist.
46.915	Point from which centerline station OE 347+94.88 bears N. 73°58'00" W., 3.030 chs. dist.
	from which
	A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 347+94.88 DIST 60.00, bears N. 73°58'00" W., 2.121 chs. dist.
	A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 347+94.88 DIST 100.00, bears N. 73°58'00" W., 1.515 chs. dist.
79.440	Point from which centerline station OE 369+41.49 bears N. 73°58'00" W., 3.030 chs. dist.
83.876	The point of intersection of the line bet. secs. 4 and 9 with the easterly right-of-way line of Interstate Highway No. 15, hereinbefore described.
	N. 16°02'10" E., on the easterly right-of-way line of Interstate Highway No. 15 through sec. 4.
	Along right-of-way fence.
23.955	Point from which centerline station OE 388+15.35 bears N. 73°57'50" W., 3.030 chs. dist.
	from which
	A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 388+15.35 DIST 100.00, bears N. 73°57'50" W., 1.515 chs. dist.
	A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 388+15.35 DIST OE 54.00 OW 54.00, bears N. 73°57'50" W., 3.848 chs. dist.
37.60	Leave right-of-way fence.
51.310	Point from which centerline station OE 406+20.82 bears N. 73°57'50" W., 3.030 chs. dist.
	from which
	A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 406+20.82 DIST 60.00, bears N. 73°57'50" W., 2.121 chs. dist.
	A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 406+20.82 DIST 100.00, bears N. 73°57'50" W., 1.515 chs. dist.
79.490	Point from which centerline station OE 424+80.72 bears N. 73°57'50" W., 3.030 chs. dist.

133

METES-AND-BOUNDS SURVEY OF
THE EASTERLY RIGHT-OF-WAY LINE OF INTERSTATE HIGHWAY NO. 15,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	from which
	<p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE 424+80.72 DIST 100.00, bears N. 73°57'50" W., 1.515 chs. dist.</p> <p>A standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA OE OW 424+80.72 DIST OE 54.00 OW 54.00, bears N. 73°57'50" W., 3.848 chs. dist.</p>
84.318	<p>The point of intersection of the line bet. secs. 4 and 33 with the easterly right-of-way line of Interstate Highway No. 15, monumented with a stainless steel post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the concurrent resurvey of a portion of the south boundary of T. 25 S., R. 59 E., executed by R.A. Zaninovich under this same group.</p>
	<p style="text-align: center;">METES-AND-BOUNDS SURVEY OF A PORTION OF THE WESTERLY RIGHT-OF-WAY LINE OF THE UNION PACIFIC RAILROAD, T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>From the point of intersection of the E-W center line of the NW1/4 of sec. 34 with the westerly right-of-way line of the Union Pacific Railroad, hereinbefore described.</p> <p>N. 10°25'00" E., on the westerly right-of-way line of the Union Pacific Railroad through sec. 34.</p>
20.394	<p>The point of intersection of the line bet. secs. 27 and 34 with the westerly right-of-way line of the Union Pacific Railroad, hereinbefore described.</p>
	<p>N. 10°25'00" E., on the westerly right-of-way line of the Union Pacific Railroad through sec. 27.</p>
81.841	<p>The point of intersection of the line bet. secs. 22 and 27 with the westerly right-of-way line of the Union Pacific Railroad, hereinbefore described.</p>
	<p>N. 10°25'10" E., on the westerly right-of-way line of the Union Pacific Railroad through sec. 22.</p>
81.901	<p>The point of intersection of the line bet. secs. 15 and 22 with the westerly right-of-way line of the Union Pacific Railroad, hereinbefore described.</p>
	<p>N. 10°25'20" E., on the westerly right-of-way line of the Union Pacific Railroad through sec. 15.</p>
82.392	<p>The point of intersection of the line bet. secs. 10 and 15 with the westerly right-of-way line of the Union Pacific Railroad, hereinbefore described.</p>
	<p>N. 10°25'20" E., on the westerly right-of-way line of the Union Pacific Railroad through sec. 10.</p>

134

METES-AND-BOUNDS SURVEY OF A PORTION OF
THE WESTERLY RIGHT-OF-WAY LINE OF THE UNION PACIFIC RAILROAD,
T. 26 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
62.356	<p>Point of Curvature of a curve to the right with a Radius of 11,559.30 ft. and a Delta Angle of 9°59'00".</p> <hr/>
	<p>Continue on curve; begin new measurement.</p>
20.153	<p>The point of intersection of the line bet. secs. 3 and 10 with the westerly right-of-way line of the Union Pacific Railroad, hereinbefore described.</p> <hr/>
	<p>Continue on curve on the westerly right-of-way line of the Union Pacific Railroad through sec. 3.</p>
10.364	<p>Point of Tangency.</p> <hr/>
	<p>N. 20°24'20" E., begin new measurement</p>
18.043	<p>The point of intersection of the line bet. secs. 2 and 3 with the westerly right-of-way line of the Union Pacific Railroad, hereinbefore described.</p> <hr/>
	<p>N. 20°24'30" E., on the westerly right-of-way line of the Union Pacific Railroad through sec. 2.</p>
57.747	<p>The point of intersection of the line bet. secs. 2 and 35 with the westerly right-of-way line of the Union Pacific Railroad, monumented with a stainless steel post, 2 1/2 ins. diam., projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the concurrent resurvey of a portion of the south boundary of T. 25 S., R. 59 E., executed by R.A. Zaninovich under this same group, and a mound of stone west of the corner.</p> <hr/>
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The average elevation of the area surveyed is about 800 meters. General drainage is to the middle. Vegetation consists of creosote and cacti.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Richard L. Jones..... Cadastral Surveyor
Clay W. Morrow..... Surveying Technician
Sean C. Whelan..... Survey Aid
John M. Conner..... Survey Aid


136

CERTIFICATE OF SURVEY

I, Richard A. Zaninovich, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 5th day of January, 2001, I have dependently resurveyed the east boundary, a portion of the south boundary and a portion of the subdivisional lines, subdivided sections 33 and 34, and executed metes-and-bounds surveys of the right-of-way lines of Interstate Highway No. 15 and a portion of the westerly right-of-way line of the Union Pacific Railroad, Township 26 South, Range 59 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 16, 2002

(Date)


(Cadastral Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the east boundary, a portion of the south boundary and a portion of the subdivisional lines, the subdivision sections 33 and 34, and metes-and-bounds surveys of the right-of-way lines of Interstate Highway No. 15 and a portion of the westerly right-of-way line of the Union Pacific Railroad, Township 26 South, Range 59 East, Mount Diablo Meridian, Nevada, executed by Richard A. Zaninovich, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

September 10, 2002

(Date)


(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 26 S., R. 59 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~