UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

MINERAL SURVEY NO. 38,

TOWNSHIP 28 NORTH, RANGE 66 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Michael O. Jones, Cadastral Surveyor

Under Special Instructions dated April 26, 2021,

and approved April 26, 2021,

which provided for the surveys included under Group No. 998,

and Assignment Instructions dated April 26, 2021.

Survey commenced May 3, 2021
Survey completed October 27, 2022

INDEX DIAGRAM

TOWNSHIP 28 NORTH, RANGE 66 EAST, MOUNT DIABLO MERIDIAN, NEVADA

| 6 | 5 | 4 | 3 | 2 | 1 |
|----|----|----|----|----|----|
| 7 | 8 | 9 | 10 | 11 | 12 |
| 18 | 17 | 16 | 15 | 14 | 13 |
| 19 | 20 | 21 | 22 | 23 | 24 |
| 30 | 29 | 28 | 27 | 26 | 25 |
| 31 | 32 | 33 | 34 | 35 | 36 |

Dependent Resurvey of M.S. No. 38, Office No. 1618, Eugenia lode pp 2-9

CHAINS

The following field notes are those of the dependent resurvey of Mineral Survey No. 38, Township 28 North, Range 66 East, Mount Diablo Meridian, Nevada.

The Township Boundaries were surveyed by U.S. Deputy Surveyors C.S. Preble and J. Thorburn in 1881, under Contract No. 130.

The subdivisional lines of Township 28 North, Range 66 East, were surveyed by U.S. Deputy Surveyor E.B. Monroe in 1882, under Contract No. 157.

Mineral Survey No. 37, Office No. 1617, Victoria lode was surveyed by U.S. Deputy Mineral Surveyor A.D. Rock in 1883.

Mineral Survey No. 38, Office No. 1618, Eugenia lode was surveyed by U.S. Deputy Mineral Surveyor A.D. Rock in 1883.

Mineral Survey No. 4869, Jordan lode, Trinity lode (Cancelled), Starless lode (Cancelled), Kempton lode (Cancelled), Midas lode (Cancelled), Victoria Extension lode, Vic No. 3 lode, Vic No. 4 lode (Cancelled), Vic No. 9 lode (Cancelled), Vic No. 10 lode (Cancelled), Vic No. 11 lode (Cancelled), Vic No. 12 lode (Cancelled), Vic No. 13 lode (Cancelled), Vic No. 15 lode (Cancelled), Starless No. 2 lode (Cancelled), Black Hawk lode (Cancelled), Rough Wrestler No. 3 lode (Cancelled), Rough Wrestler No. 4 lode (Cancelled), Rough Wrestler No. 5 lode (Cancelled), Rough Wrestler No. 7 lode (Cancelled), Corinne No. 1 lode (Cancelled), Gibby No. 2 lode (Cancelled), Lutie No. 1 lode (Cancelled), Lutie No. 2 lode (Cancelled), Lutie No. 3 lode (Cancelled), Skippy No. 1 lode (Cancelled), Skippy No. 3 lode (Cancelled), were surveyed by Mineral Surveyor Robert W. Millard in 1961-1963.

The East boundary of Township 28 North, Range 66 East, was dependently resurveyed by Cadastral Surveyor Robert A. Pratt in 1976 under Group No. 534.

Before restoring the corners, the lines of the original survey were retraced, and a diligent search made for any evidence of the position of the original corners and other calls of the original field note records.

In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 998, dated April 26, 2021.

Measurements were made with Trimble R-10 Global Navigation Satellite System (GNSS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

TOWNSHIP 28 NORTH, RANGE 66 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The NAD 1983 (2011) (EPOCH:2010.0000) geographic position, of the following corners were determined by Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) AI0950 EGAN EGAN_BRGN_NV1996 CORS ARP, DL7692 GOSH GOSH_BRGN_UT1996 CORS ARP and DL7710 P007 SALMONFALLNV2007 CORS ARP, and carried forward by RTK observations.

The corner of sections 3, 4, 33 and 34, on the N. bdy. of the Tp., is as follows:

Latitude: 40°20′14.116″ N. Longitude: 114°31′20.742″ W.

The corner of sections 5, 6, 31 and 32, on the N. bdy. of the Tp., is as follows:

Latitude: 40°20'15.259" N. Longitude: 114°33'36.532" W.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 38 (1618), T. 28 N., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA.

Reestablishment of the Survey executed by U.S. Deputy Mineral Surveyor A.D. Rock in 1883

Eugenia lode

Beginning at Cor. No. 1, Mineral Survey No. 38, Eugenia lode, determined by Richard W. Forman, Nevada Registered Land Surveyor No. 2898, in 1974, monumented with an iron post, 2 1/2 ins. diam., 36 ins. long, loosely set, projecting 24 ins. above a mound of stone, 3 ft. diam., 1 1/2 ft. high, with a rectangular copper cap, 2x4 ins., mkd. CORNER NO. 1 EUGENIA SUR. NO. 38 RLS 2898 7-25-74, as recorded in Elko County, Nevada, File No. 84994. This is accepted as a careful and faithful determination of the position of the original corner. Reset the iron post, 16 ins. in the ground to sold rock, over a plastic encased magnet, and in a mound of stone 3 ft. base., 1 ft. high.

from which

A pinyon pine, 4 ins. diam., bears S. 62 1/2° E., 34 lks. dist., mkd. XBT at base.

Cor. is located on the southerly side of old road, and 40 lks. S. of a dry creek bed.

From this cor., the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., bears N. $59^{\circ}19'00''$ E., 38.722 chs. dist., (Record: N. $32^{\circ}20'$ E., 1990 ft. (30.152 chs.)), monumented with a wood post, 35 ins. long, 6 ins. at base, firmly set, projecting 24 ins. above a scattered mound of stone, hewed on 4 sides, mkd. TXXIXN RLXVIE on north side, XXXIV III on east side, TXXVIIIN RLXVI on south side, XXXIII IV on west side.

from which the original bearing trees


T. 28 N., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA CHAINS A pinyon pine, 13 ins. diam., bears N. 59° E., 37.6 lks. dist. (1882 Record: nut pine, 12 ins. diam, N. 66° E., 35 lks. dist.), no visible mks. A pinyon pine, 16 ins. diam., bears S. 11° W, 47.3 lks. dist. (1882 Record: nut pine, 18 ins. diam, S. 2° E., 41 lks. dist.), with illegible mks. on a partially healed blaze at breast height. A juniper, 21 ins. diam. at base, bears S. 63° W., 55.8 lks. dist. (1882 Record: cedar 16 ins. diam., S. 31° W., 62 lks. dist.), with illegible mks. on a partially healed blaze at base. A pinyon pine, 12 ins. diam., bears N. 43° W., 24.8 lks. dist. (1882 Record: nut pine, 20 ins. diam., N. 34° W., 20 lks. dist.), no mks. visible on mostly healed blaze at breast height. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic encased magnet, and in a collar of stone, with brass cap mkd. T29N R66E S33 | S34 S 4 S 3 T28N 2021 Deposit the original wood post, horizontally alongside the collar of stone. S. 23°00′00″ E., on line 1-2, Mineral Survey No. 38, Eugenia 8.80 Approximate position of underground water line, bears NE. and SW. 22.727 Point for Cor. No. 2, Mineral Survey No. 38, Eugenia lode, determined at the original 1883 record bearing and distance, from Cor. No. 1, Mineral Survey No. 38, Eugenia lode. This position also agrees with the survey plat by Richard W. Forman, Nevada Registered Land Surveyor No. 2898, recorded in 1974 in Elko County, Nevada, as File No. 84994. There is no remaining evidence of the original corner. At the corner point Set stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, with brass

cap mkd.

| | 1. Zo N., IX. OO E., HOOM DINDE HEREDING NEVIDE |
|--------|---|
| CHAINS | MS 38 \ |
| | EU T28N |
| | 2 \ R66E |
| | S 4 |
| | 2022 |
| | from which |
| | A mountain mahogany, 6 ins. diam., bears S. 66° W., 32.9 lks. dist., mkd. XBT at base. |
| | A pinyon pine, 7 ins. diam., bears N. 37° W., 42.4 lks. dist., mkd. MS38C2XBT at base. |
| | From this cor., a position monumented as Cor. No. 2, Mineral Survey No. 38, Eugenia lode, by Richard W. Forman, Nevada Registered Land Surveyor No. 2898, in 1974, with an iron post, 2 1/2 ins. diam., firmly set, projecting 19 ins. above the ground, in a collar of stone, with a rectangular copper cap, 2x4 ins., mkd. CORNER NO. 2 EUGENIA SUR. NO. 38 RLS 2898 7-25-74, as recorded in Elko County, Nevada, as File No. 84994, bears N. 20°03'20" W., 42.3 lks. dist. The position of this monument on the ground does not correlate well with the original record measurements nor with the measurements on Forman's plat, and is not utilized during the course of this survey. |
| | S. 67°00'00" W., on line 2-3, Mineral Survey No. 38, Eugenia lode. |
| 0.90 | Elko County Road No. 795, graded surface, 50 lks. wide, bears SW. and NW. |
| 4.545 | From this point, a position established by Richard W. Forman, Nevada Registered Land Surveyor No. 2898, in 1974, bears N. 23°00'00" W., 11.364 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 29 ins. above the ground, in a collar of stone, with a rectangular copper cap, 2x5 ins., mkd. LOC. MON. EUGENIA SUR. NO. 38 RLS 2829 7-25-74, as recorded in Elko County, Nevada, File No. 84994. |
| 9.091 | Point for Cor. No. 3, Mineral Survey No. 38, Eugenia lode, determined at the original 1883 record bearing and distance, from Cor. No. 2, Mineral Survey No. 38, Eugenia lode. This position also agrees with the survey plat by Richard W. Forman, Nevada Registered Land Surveyor No. 2898, recorded in 1974 in Elko County, Nevada, as File No. 84994. There is no remaining evidence of the original corner. |
| | At the corner point |
| | Set stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd. |
| | |
| | |
| | |
| | |
| | |
| | |
| 1 | |

| CHAINS | MS 38 EU |
|--------|---|
| | |
| | T28N R66E S 4 |
| | 2022 |
| | from which |
| | A pinyon pine, 8 ins. diam., bears S. 53° W., 27.4 lks. dist., mkd. MS38C3XBT at base. |
| | A pinyon pine, 7 ins. diam., bears N. 77 1/2° W., 32.1 lks. dist., mkd. XBT at base. |
| | From this cor., a position monumented as Cor. No. 3, Mineral Survey No. 38, Eugenia lode, by Richard W. Forman, Nevada Registered Land Surveyor No. 2898, in 1974, with an iron post, 2 1/2 ins. diam., firmly set, projecting 20 ins. above the ground, in a collar of stone, with a rectangular copper cap, 2x3 ins., mkd. CORNER NO. 3 EUGENIA SUR. NO. 38 RLS 2898 7-25-74, as recorded in Elko County, Nevada, as File No. 84994, bears S. 31°53′00″ W., 48.5 lks. dist. The position of this monument on the ground does not correlate well with the original record measurements nor with the measurements on Forman's plat, and is not utilized during the course of this survey. |
| | N. 23°00'00" W., on line 3-4, Mineral Survey No. 38, Eugenia lode. |
| 4.40 | Elko County Road No. 795, graded surface, 50 lks. wide, bears NE. and SW. |
| 16.70 | Approximate position of underground water line, bears SE. and NW. |
| 22.727 | Point for Cor. No. 4, Mineral Survey No. 38, Eugenia lode, determined at the original 1883 record bearing and distance, from Cor. No. 3, Mineral Survey No. 38, Eugenia lode. This position also agrees with the survey plat by Richard W. Forman, Nevada Registered Land Surveyor No. 2898, recorded in 1974 in Elko County, Nevada, as File No. 84994. There is no remaining evidence of the original corner. |
| | At the corner point |
| · | Set stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd. |
| | |
| | |
| | |
| | |
| | |

CHAINS



2022

from which

A pinyon pine, 11 ins. diam., bears S. 37 1/2° W., 33.9 lks. dist., mkd. MS38C4XBT at base.

A pinyon pine, 7 ins. diam., bears N. 45° W., 33.3 lks. dist., mkd. MS38C4 at waist height and XBT at base.

From this cor., a position monumented as Cor. No. 4, Mineral Survey No. 38, Eugenia lode, by Richard W. Forman, Nevada Registered Land Surveyor No. 2898, in 1974, with an iron post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above a mound of stone, 3 1/2 ft. diam., 1 1/2 ft. high, with a rectangular copper cap, 2x4 ins., mkd. CORNER NO. 4 EUGENIA SUR. NO. 38 RLS 2898 7-25-74, as recorded in Elko County, Nevada, as File No. 84994, bears N. 15°50′00″ W., 16.1 lks. dist. The position of this monument on the ground does not correlate well with the original record measurements nor with the measurements on Forman's plat, and is not utilized during the course of this survey.

From this same cor., a position established by Richard W. Forman, Nevada Registered Land Surveyor No. 2898, in 1974, as recorded in Elko County, Nevada, File No. 84994, mkd. LOC. MON. EUGENIA SUR. NO. 38 RLS 2829 7-25-74, as hereinbefore described, bears S. 44°48′00″ E., 12.239 chs. dist., (Forman's Record: S. 44°48′06″ E., 807.77 ft. dist. (12.227 chs. dist.)) From this monument, a rock cropping bears N. 23° W., 1 ch. dist.

From this same cor., the locatable record improvements are as follows: Shaft A, 15 ft. diam., 5 ft. deep, bears S. $44^{\circ}49'20''$ E., 12.40 chs. dist.; Cut B, 5x7 ft., 5 ft. deep, bears S. $50^{\circ}25'40''$ E., 12.50 chs. dist.; and Cut C, 25 ft. diam., 6 ft. deep, with partially buried notched wood timbers, bears S. $47^{\circ}50'50''$ E., 13.00 chs. dist.

From this same cor., Cor. No. 1, Mineral Survey No. 4869, Lutie No. 1 lode (cancelled), identical with Cor. No. 2, Mineral Survey No. 4869, Lutie No. 2 lode (cancelled), on line 3-4, Mineral Survey No. 4869, Corinne No. 1 lode (cancelled), bears N. 49°42′00″ E., 13.068 chs. dist., (Forman's Record: N. 49°50′17″ E., 864.60 ft. dist. (13.100 chs. dist.)), monumented with an iron post, 2 ins. diam., firmly set, projecting 21 ins. above mound of earth and stone, 3 ft. diam., 1 ft. high, with a galvanized pipe cap, mkd. P 2.

CHAINS

From this same cor., Cor. No. 1, Mineral Survey No. 4869, Lutie No. 2 lode (cancelled), on line 3-4, Mineral Survey No. 4869, Corinne No. 1 lode (cancelled), bears S. 88°30′00″ E., 7.131 chs. dist. (Forman's Record: S. 88°32′51″ E., 472.34 ft. dist. (7.157 chs. dist.)), monumented with an iron post, 2 ins. diam., firmly set, projecting 21 ins. above the ground, in a scattered mound of stone, with a galvanized pipe cap, mkd. L2-1-4869 P 2.

from which the original bearing tree

A pinyon pine, 13 ins. diam., bears N. 85° E., 2.7 lks. dist., mkd. L2-1 4869; on a partially healed blaze.

From this same cor., Cor. No. 2, Mineral Survey No. 4869, Black Hawk lode (cancelled), bears S. 71°39′30″ E., 6.464 chs. dist. Forman's Record: S. 71°48′10″ E., 427.97 ft. dist. (6.484 chs. dist.)), monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above the ground, with a rectangular copper cap, 2x3 ins., mkd. BH-2 4869 V16-1.

From this same cor., Cor. No. 4, Mineral Survey No. 4869, Corinne No. 1 lode (cancelled), bears S. 25°57′00″ E., 9.815 chs. dist. (Forman's Record: S. 25°59′53″ E., 647.05 ft. dist. (9.804 chs. dist.)), monumented with an iron post, 2 ins. diam., firmly set, projecting 22 ins. above a mound of stone, 4 1/2 ft. diam., 1 1/2 ft. high, with a galvanized pipe cap, mkd. C1-4 4869.

from which the original bearing tree

A pinyon pine, 22 ins. diam., bears S. 43° W., 48.6 lks. dist., mkd. 1-4 4869; on a partially healed blaze.

From this same cor., Cor. No. 1, Mineral Survey No. 4869, Corinne No. 1 lode (cancelled), bears S. 35°58′40″ W., 7.394 chs. dist. (Forman's Record: S. 36°02′28″ W., 486.04 ft. dist. (7.364 chs. dist.)), monumented with an iron post, 2 ins. diam., firmly set, projecting 21 ins. above the ground, in a collar of stone, with a galvanized pipe cap, mkd. C1-1-4869.

From this same cor., Cor. No. 2, Mineral Survey No. 37, Victoria lode, identical with Cor. No. 4, Mineral Survey No. 4869, Trinity lode (cancelled), Cor. No. 1, Mineral Survey No. 4869, Midas lode (cancelled), and Cor. No. 1, Mineral Survey No. 4869, Kempton lode (cancelled), bears S. 66°10′00″ W., 71.478 chs. dist., monumented with a galvanized iron post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above a mound of earth and stone, 3 ft. diam., 1 ft. high, with a rectangular copper cap 2 1/4x2 3/4 ins., with no marks. Mark the cap as follows: MS37 VI 2, MS4869 TR 4, MS4869 MI 1, MS4869 KE 1 2022. Cor. is located NE., 60 lks. dist. of switchback of road, bearing SE. and SW. From this cor., the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., bears N. 27°11′10″ E., 60.561 chs. dist., hereinafter described.

CHAINS

From this same cor., the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., bears N. $56^{\circ}28'10''$ W., 45.240 chs. dist., determined at record bearing and distance from the only remaining original bearing tree

A pinyon pine, 13 ins. diam. (1882 Record: nut pine 14 ins. diam), bears S. 65° W., 200 lks. dist., with visible mks. TXXVIIINR BT on a previously opened, partially healed blaze at breast height.

At the corner point

Set a stainless steel post, 28 ins. long, $2\ 1/2$ ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

2021

from which a new bearing tree

A pinyon pine, 6 ins. diam., bears N. 31° E., 12 lks. dist., mkd. X at breast high and BT at base.

From this same cor., Cor. No. 4, Mineral Survey No. 4869, Victoria Extension lode, identical with Cor. No. 2, Mineral Survey No. 4869, Vic No. 4 lode (cancelled), bears S. 88°15′50″ W., 102.888 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 17 ins. above a mound of earth and stone, 4 1/2 ft. diam., 1 1/2 ft. high, with a rectangular copper cap, 3x2 1/2 ins., mkd. 4 V EXT S 4 NO 4869. From this cor., the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., bears N. 27°49′40″ W., 31.867 chs. dist., monumented with a rebar, 3/4 in. diam., firmly set, projecting 2 ins. above the ground, with a tag, 3/4 in. diam., wired to the top, mkd. RLS 3720, with a steel fence post alongside, no record found.

from which a remaining original bearing tree

A juniper, 16 ins. diam. at base, bears S. 68° E., 180 lks. dist., mkd. R L X VII BT VII on a partially healed blaze at base.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic encased magnet, and in a collar of stone, with brass cap mkd.

| | | | T29N R66E | | | | |
|-------|---|--------------------------|-----------------------------------|-----------------|----------|--|--|
| | S31 S32 | | | | | | |
| | | | S 6 S 5 | | | | |
| | | | T28N | | | | |
| | | | 2022 | | | | |
| | Deposit the reb | oar inside th | ne stainless stee | l post. | | | |
| | Cor. is located and SW. | d SE., 50 lks | s. dist., from je | ep trail, bears | s NE. | | |
| | N. 67°00'00" E. lode. | , on line 4- | -1, Mineral Surve | y No. 38, Euger | nia | | |
| 9.091 | Cor. No. 1, Mineral Survey No. 38, Eugenia lode and the place of beginning. | | | | | | |
| | GENERAL DESCRIPTION | | | | | | |
| | | SISIS OF HIM | rbers, prnon prne | and mountain | | | |
| | Vegetation cons mahogany. Joe M portion of sec. | Moore Spring | is located in the water sources w | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring | is located in th | e north easter! | Ly i. | | |
| | mahogany. Joe M | Moore Spring | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring 4, no other | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring 4, no other | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring 4, no other | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring 4, no other | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring 4, no other | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring 4, no other | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring 4, no other | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring 4, no other | is located in th | e north easter! | Ly d. | | |
| | mahogany. Joe M | Moore Spring 4, no other | is located in th | e north easter! | Ly d. | | |

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Kelly R. Totten

Alex J. Yetsko

Nathan D. Mersino

Cadastral Surveyor

Survey Technician

Student trainee (Survey)

CERTIFICATE OF SURVEY

I, Michael O. Jones, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 26th day of April, 2021, I have dependently resurveyed Mineral Survey No. 38, Township 28 North, Range 66 East, of the Mount Diablo Meridian, in the State of Nevada, which is represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUL 1 1 2023

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Reno, Nevada

The foregoing field notes of the dependent resurvey of Mineral Survey No. 38, Township 28 North, Range 66 East, of the Mount Diablo Meridian, Nevada, executed by Michael O. Jones, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUL 1 8 2023

(Date)

(Chief Cadastral Surveyor for Neyada)

CERTIFICATE OF TRANSCRIP

I CERTIFY that the foregoing transcript of the field notes of the above described survey in Township 28 North Range 66 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor for Nevada)