

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original
FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF
A PORTION OF THE SUBDIVISIONAL LINES,
AND
THE SUBDIVISION OF SECTIONS 16 AND 17,
TOWNSHIP 30 NORTH, RANGE 19 EAST,
OF THE MOUNT DIALBO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY
Don R. Aschenbach, Cadastral Surveyor

Under Special Instructions dated July 21, 2004,
and approved July 21, 2004,
which provided for the surveys included under Group No. 819,
and Assignment Instructions dated July 21, 2004.

Survey commenced July 26, 2004
Survey completed August 15, 2006

INDEX DIAGRAM

TOWNSHIP 30 NORTH, RANGE 19 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
	8	5			
18	7 17	4 16	2 15	14	13
	6	3			
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 16 pp. 9 - 11
 Subdivision of Section 17 pp. 11 - 12

TOWNSHIP 30 NORTH, RANGE 19 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 16 and 17, T. 30 N., R. 19 E., Mount Diablo Meridian, Nevada.</p> <p>The north (Sixth Standard Parallel North) and east boundaries, the east 4 miles of the south boundary, and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor G.W. Garside in 1872 under Contract No. 52.</p> <p>Portions of the south boundary were retraced and resurveyed, and surveyed by U.S. Deputy Surveyor M. Santee in 1880 under Contract No. 95.</p> <p>Portions of the north boundary (Sixth Standard Parallel North) were retraced and resurveyed, and surveyed; the west boundary was surveyed; and portions of the subdivisional lines were retraced and resurveyed, and surveyed by U.S. Deputy Surveyor C.S. Alverson in 1880-1881 under Contract No. 100.</p> <p>A portion of the north boundary (Sixth Standard Parallel North) through R. 20 E., was resurveyed by U.S. Surveyor Winfred A. Pray in 1912 under Group No. 18.</p> <p>The south 2 miles of the west boundary were resurveyed by Cadastral Surveyor Neil R. Forsyth in 1973 under Group No. 502.</p> <p>Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.</p> <p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 819 dated July 21, 2004.</p> <p>Measurements were made with Trimble 4700 and 5700 Global Positioning System (GPS) receivers using real-time kinematic methods and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.</p> <p>Geodetic control was derived from Global Positioning System (GPS) static observations post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) GARL GARLIC COR ARP, NFLN FALLON NAVAL AIR CORS ARP, AND TUNG OREANA CORS ARP. The NAD 83(CORS96) (EPOCH:2002) geographic position of the SE corner of section 16, is as follows:</p> <p>Latitude: 40°27'57.864" N. Longitude: 119°50'37.030" W.</p> <p>The mean magnetic declination is 16 1/2° E., as shown on U.S.G.S. quadrangle map SHEEPSHEAD SPRING, NEV., dated 1981.</p>
--------	--

081

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div>Reestablishment of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1872 and the Resurvey and Survey Executed by U.S. Deputy Surveyor C.S. Alverson in 1880-1881</div> <div>Beginning at the cor. of secs. 15, 16, 21 and 22, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 4 ft. base, 6 ins. high, with the remains of a cottonwood post, 6x1 1/2x3/4 ins., no visible marks laying alongside.</div> <div>At the corner point</div> <div>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</div> <div><div>T30N R19E S16 S15 S21 S22</div><div>2004</div></div> <div>Deposit the local pipe and the remains of the original wood post alongside the stainless steel post.</div> <div>N. 1°07'30" W., bet. secs. 15 and 16.</div> <div>Over nearly level land, covered with sagebrush and greasewood.</div> <div>10.90 Mine road, 30 lks. wide, bears E. and W.</div> <div>20.232 Point for the S 1/16 sec. cor. of secs. 15 and 16.</div> <div>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</div> <div><div>S 1/16 S16 S15</div><div>2004</div></div> <div>40.464 The 1/4 sec. cor. of secs. 15 and 16, monumented with a deeply embedded mound of stone, 3 ft. base, 1 ft. high. This mound of stone correlates well with other existing corners and is accepted as the best available evidence of the position of the original corner.</div> <div>At the corner point</div> <div>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</div>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T30N R19E 1/4 S16 S15 2004</p> <hr/> <p>N. 1°05'30" W., beginning new measurement.</p> <p>6.50 Jeep trail, 20 lks. wide, bears SE. and NW.</p> <p>20.385 Point for the N 1/16 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p>N 1/16 S16 S15 2006</p> <p>40.770 The cor. of secs. 9, 10, 15 and 16, monumented with the remains of a cottonwood post, 11x1 1/2x1 1/2 ins., no visible marks, loosely set in a small mound of stone.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p>T30N R19E S 9 S10 S16 S15 2004</p> <p>Deposit the remains of the original wood post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°17'20" W., bet. secs. 16 and 21.</p> <p>Over nearly level land, covered with sagebrush and greasewood.</p> <p>20.274 Point for the E 1/16 sec. cor. of secs. 16 and 21. Not monumented.</p> <p>26.80 Wash, 20 lks. wide, drains SE.</p> <p>27.70 Jeep trail, 20 lks. wide, bears SE. and NW.</p> <p>40.548 Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
--------	---

083

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T30N R19E $\frac{1}{4}$ $\frac{S16}{S21}$ 2004</p>
81.096	<p>The cor. of secs. 16, 17, 20 and 21, monumented with a galvanized pipe, 1 1/2 ins. diam., with a galvanized cap, 2 ins. diam., mkd. 16 17 20 21, firmly set, projecting 12 ins. above the ground, in mound of stone, 4 ft. base, 1 ft. high, with a volcanic stone, 14x9x9 ins., loosely set alongside, mkd. with 3 grooves on one face and 4 grooves on adjoining face, and the decayed remains of a cottonwood post, 5x3/4x1/2 ins., laying alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T30N R19E $\frac{S17}{S20}$ $\frac{S16}{S21}$ 2004</p> <p>Deposit the marked stone, remains of the original wood post and the local pipe alongside the stainless steel post.</p> <p>From this cor., a windmill bears N. 18°00' E., 17.3 chs. dist.</p>
	N. 0°23'30" W., bet. secs. 16 and 17.
	Over nearly level land, covered with sagebrush and greasewood.
8.50	Wash, 20 lks. wide, drains E.
14.70	Jeep trail, 20 lks. wide, bears SE. and NW.
39.90	Mine road, 30 lks. wide, bears E. and W.
40.169	<p>The 1/4 sec. cor. of secs. 16 and 17, determined by person(s) unknown, monumented with a galvanized pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above the ground and in mound of stone 3 ft. base, 1 ft. high., with a galvanized cap, 2 ins. diam., mkd. 1/4. This position has been adopted by adjacent landowners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

084

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T30N R19E 1/4 S17 S16 2004</p> <p>Deposit the local pipe alongside the stainless steel post.</p> <hr/> <p>N. 0°20'10" W., beginning new measurement.</p> <p>18.50 Jeep trail, 20 lks. wide, bears SE. and N.</p> <p>19.10 Jeep trail, 20 lks. wide, bears S. and W.</p> <p>40.112 The cor. of secs. 8, 9, 16 and 17, monumented with a galvanized pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground and in a mound of stone, 4 ft. base, 1 ft. high, with a galvanized cap, 2 ins. diam., mkd. 8 9 16 17, with a volcanic rock, 16x9x6 ins., loosely set alongside, mkd. with 4 grooves on one face and 4 grooves on adjoining face, and a cottonwood post 28 ins. long, 1 1/2 ins. diam., no visible marks, wired to a steel fence post, firmly set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p>T30N R19E S 8 S 9 S17 S16 2004</p> <p>Deposit the marked stone, the original wood post and the local pipe alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°57'00" W., bet. secs. 9 and 16.</p> <p>Over nearly level land, covered with sagebrush and greasewood.</p> <p>20.002 Point for the E 1/16 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p>E 1/16 $\frac{S 9}{S16}$ 2004</p> <p>From this cor., an iron pipe, 1/2 in. diam., firmly set, projecting 8 ins. above the ground, unknown origin, at corner of fences, extending S. and W., bears S. 32°25' E., 0.596 chs. dist., and was not utilized during the course of this survey.</p>
--------	--

085

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.004	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T30N R19E S 9 1/4 <u> </u> S16 2004 </div>
59.90	<p>Corner of fences bears S., 17 lks. dist.; fences extending E. and S.</p>
80.008	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 88°00'30" W., bet. secs. 17 and 20.</p> <p>Over nearly level land and rolling hills, covered with sagebrush and greasewood.</p> <p>Ridge, bears N. and S.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T30N R19E S17 1/4 <u> </u> S20 2004 </div>
49.10	<p>Wash, 15 lks. wide, drains NE.</p>
50.40	<p>Same wash, 15 lks. wide, drains SE.</p>
78.856	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a volcanic stone, 13x10x4 ins., firmly set in a mound of stone, 3 ft. base, 6 ins. high., mkd. with 5 grooves on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top with brass cap mkd.</p>

086

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS																	
	<div data-bbox="873 306 1024 401"> <table> <tr> <td>T30N</td><td>R19E</td></tr> <tr> <td>S18</td><td>S17</td></tr> <tr> <td>S19</td><td>S20</td></tr> </table> </div> <div data-bbox="915 422 982 449">2004</div> <div data-bbox="446 476 1455 531">Deposit the original corner stone alongside the stainless steel post.</div> <hr/> <div data-bbox="446 585 1036 613">N. 0°14'10" E., bet. secs. 17 and 18.</div> <div data-bbox="446 638 1354 665">Over rolling hills, covered with sagebrush and shadscale.</div> <div data-bbox="303 690 909 718">12.10 Wash, 20 lks. wide, drains E.</div> <div data-bbox="303 743 703 770">22.40 Spur, slopes SE.</div> <div data-bbox="303 795 829 823">35.80 Ridge, bears SE. and NW.</div> <div data-bbox="303 848 1455 930">40.056 The 1/4 sec. cor. of secs. 17 and 18, monumented with a volcanic stone, 18x10x7 ins., firmly set in a mound of stone, 4 ft. base, 1 ft. high, mkd. 1/4 on E. face.</div> <div data-bbox="446 955 756 982">At the corner point</div> <div data-bbox="446 1008 1442 1089">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</div> <div data-bbox="873 1115 1024 1197"> <table> <tr> <td>T30N</td><td>R19E</td></tr> <tr> <td>1/4</td><td></td></tr> <tr> <td>S18</td><td>S17</td></tr> </table> </div> <div data-bbox="915 1222 982 1249">2004</div> <div data-bbox="446 1274 1455 1329">Deposit the original corner stone alongside the stainless steel post.</div> <hr/> <div data-bbox="446 1383 1117 1411">N. 0°12'40" E., beginning new measurement.</div> <div data-bbox="319 1436 1117 1463">8.60 Mine road, 30 lks. wide, bears SE. and NW.</div> <div data-bbox="303 1488 1245 1516">20.174 Point for the N 1/16 sec. cor. of secs. 17 and 18.</div> <div data-bbox="446 1541 1442 1623">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</div> <div data-bbox="891 1648 1008 1705"> <table> <tr> <td>N</td><td>1/16</td></tr> <tr> <td>S18</td><td>S17</td></tr> </table> </div> <div data-bbox="915 1728 982 1755">2004</div> <div data-bbox="303 1780 1102 1808">27.10 Jeep trail, 20 lks. wide, bears E. and W.</div> <div data-bbox="303 1833 802 1860">35.70 Ridge, bears E. and W.</div>	T30N	R19E	S18	S17	S19	S20	T30N	R19E	1/4		S18	S17	N	1/16	S18	S17
T30N	R19E																
S18	S17																
S19	S20																
T30N	R19E																
1/4																	
S18	S17																
N	1/16																
S18	S17																

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
40.348	<p>The cor. of secs. 7, 8, 17 and 18, monumented with a volcanic stone, 16x9x5 ins., firmly set in a mound of stone, 4 ft. base, 1 ft. high, mkd. with 5 grooves on E. face and 4 grooves on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T30N</td><td>R19E</td></tr> <tr><td>S 7</td><td>S 8</td></tr> <tr><td>S18</td><td>S17</td></tr> </table> <p>2004</p> </div> <p>Deposit the original corner stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 87°53'50" W., bet. secs. 8 and 17.</p> <p>Over nearly level land and rolling hills, covered with sagebrush and shadscale.</p>	T30N	R19E	S 7	S 8	S18	S17
T30N	R19E						
S 7	S 8						
S18	S17						
19.506	<p>Point for the E 1/16 sec. cor. of secs. 8 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>E 1/16</td><td>S 8</td></tr> <tr><td></td><td>S17</td></tr> </table> <p>2004</p> </div> <p>From this cor., a galvanized pipe, 1 1/2 ins. diam., firmly set, unknown origin, with a galvanized cap, 2 ins. diam., mkd. PW, bears S. 20°52' W., 0.563 chs. dist., and was not utilized during the course of this survey.</p>	E 1/16	S 8		S17		
E 1/16	S 8						
	S17						
35.00	<p>Mine road, 30 lks. wide, bears SE. and NW.</p>						
39.012	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T30N</td><td>R19E</td></tr> <tr><td>1/4</td><td>S 8</td></tr> <tr><td></td><td>S17</td></tr> </table> <p>2004</p> </div>	T30N	R19E	1/4	S 8		S17
T30N	R19E						
1/4	S 8						
	S17						

088

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
42.60	Jeep trail, 20 lks. wide, bears NE. and SW.
51.10	Jeep trail, 20 lks. wide, bears NE. and SW.
54.40	Mine road, 30 lks. wide, bears SE. and NW.
58.518	Point for the W 1/16 sec. cor. of secs. 8 and 17. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. $\begin{array}{r} \text{W } 1/16 \quad \text{S } 8 \\ \hline \text{S } 17 \end{array}$ 2004
62.70	Ridge, bears N. and S.
78.024	The cor. of secs. 7, 8, 17 and 18.
<hr/>	
SUBDIVISION OF SECTION 16, T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA	
<hr/>	
	From the 1/4 sec. cor. of secs. 16 and 21. N. 0°44'20" W., on the N-S center line of sec. 16. Over nearly level land, covered with sagebrush and greasewood.
6.50	Wash, 20 lks. wide, drains SE.
20.158	Point for the C-S 1/16 sec. cor. of sec. 16. Not monumented.
22.60	Mine road, 30 lks. wide, bears SE. and NW.
40.20	Barbed wire fence, bears E. and W.
40.316	Point for the center 1/4 sec. cor. of sec. 16, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, over a plastic-encased magnet, with brass cap mkd. $\begin{array}{r} \text{T30N R19E} \\ \text{C } 1/4 \text{ S16} \end{array}$ 2004
80.40	Barbed wire fence, bears E. and W.
80.759	The 1/4 sec. cor. of secs. 9 and 16.
<hr/>	
	From the 1/4 sec. cor. of secs. 15 and 16. N. 89°29'20" W., on the E-W center line of sec. 16.

SUBDIVISION OF SECTION 16,
T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over nearly level land, covered with sagebrush and greasewood.
20.00	Barbed wire fence, bears N. and S.
20.134	Point for the C-E 1/16 sec. cor. of sec. 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. $\begin{array}{c} \text{E } 1/16 \\ \text{C } \frac{\quad}{\text{S16}} \text{ C} \end{array}$ 2004 From this cor., an iron pipe, 1/2 in. diam., firmly set, unknown origin, at corner of fences, extending N. and W., bears S. 43°34' E., 0.194 chs. dist., and was not utilized during the course of this survey.
40.268	The center 1/4 sec. cor. of sec. 16.
60.40	Barbed wire fence, bears N. and S., 6 lks. dist. to corner of fences, extending N. and E.
60.60	Jeep trail, 20 lks. wide, bears SE. and NW.
80.564	The 1/4 sec. cor. of secs. 16 and 17. <hr/>
	From the C-E 1/16 sec. cor. of sec. 16. N. 0°55'00" W., on the N-S center line of the NE1/4 of sec. 16. Over nearly level land, covered with sagebrush and greasewood.
40.10	Barbed wire fence, bears E. and W.
40.606	The E 1/16 sec. cor. of secs. 9 and 16. <hr/>
	From the point for the E 1/16 sec. cor. of secs. 16 and 21. N. 0°56'00" W., on the N-S center line of the SE1/4 of sec. 16. Over nearly level land, covered with sagebrush and greasewood.
12.70	Mine road, 30 lks. wide, bears E. and W.
20.195	Point for the SE 1/16 sec. cor. of sec. 16, at intersection with the E-W center line of the SE1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. $\text{SE } 1/16 \text{ S16}$ 2004
40.25	Barbed wire fence, bears E. and W.

SUBDIVISION OF SECTION 16,
T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.390	The C-E 1/16 sec. cor. of sec. 16.
	From the S 1/16 sec. cor. of secs. 15 and 16.
	N. 89°23'20" W., on the E-W center line of the SE1/4 of sec. 16.
	Over nearly level land, covered with sagebrush and greasewood.
20.206	The SE 1/16 sec. cor. of sec. 16.
37.60	Mine road, 30 lks. wide, bears SE. and NW.
40.412	The point for the C-S 1/16 sec. cor. of sec. 16.
	SUBDIVISION OF SECTION 17, T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 17 and 20.
	N. 0°04'10" W., on the N-S center line of sec. 17.
	Over gently rolling hills covered with sagebrush and shadscale.
2.00	Wash, 20 lks. wide, drains NE.
7.40	Spur, slopes SE.
31.00	Ridge, bears E. and W.
40.112	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T30N R19E C 1/4 S17 2004
44.80	Draw, drains irregularly NE.
49.70	Spur, slopes NE.
80.344	The 1/4 sec. cor. of secs. 8 and 17.
	From the 1/4 sec. cor. of secs. 16 and 17.
	N. 88°04'50" W., on the E-W center line of sec. 17.
	Over gently rolling hills, covered with sagebrush and shadscale.
19.599	Point for the C-E 1/16 sec. cor. of sec. 17.

SUBDIVISION OF SECTION 17,
T. 30 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.
	$C \frac{E \ 1/16}{S17} C$
	2004
20.80	Mine road, 30 lks. wide, bears SE. and NW.
39.198	The center 1/4 sec. cor. of sec. 17.
69.90	Ridge, bears NE. and SW.
78.405	The 1/4 sec. cor. of secs. 17 and 18.
	<hr/>
	From the C-E 1/16 sec. cor. of sec. 17.
	N. 0°12'10" W., on the N-S center line of the NE1/4 of sec. 17.
	Over nearly level land, covered with sagebrush and greasewood.
19.50	Jeep trail, 20 lks. wide, bears E. and W.
19.60	Barbed wire fence, bears E. and W., 15 lks. dist. to corner of fences extending E. and N.
19.640	A galvanized pipe, 1 1/2 ins. diam., firmly set, unknown origin, with 1 1/2 in. galvanized cap mkd. PW, bears WEST, 0.152 chs. dist., and was not utilized during the course of this survey.
22.59	Intersect the south side of a wood frame building, 10.5x12 ft., the SW cor. bears W., 7 lks. dist., the long side bears N.
22.78	Intersect the south side of a wood frame building, 8x8 ft. the SW cor. bears W., 10 lks. dist., the long side bears N.
24.00	Intersect the south side of a wood frame building, 16x10 ft. the SW cor. bears W., 12 lks. dist., the long side bears N.
28.00	Barbed wire fence, bears E. and W., 18 lks. dist. to corner of fences, extending E. and S.
40.173	The E 1/16 sec. cor. of secs. 8 and 17.
	<hr/>
	GENERAL DESCRIPTION
	The lands included in this survey are located in Washoe County, Nevada, about 40 miles west of the community of Gerlach, Nevada. The area drains easterly into the Smoke Creek Desert. The average elevation is about 4000 feet above sea level.
	<hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Joseph J. Johnson

Surveying Technician

Jeremiah J. Lee

Surveying Technician

093

CERTIFICATE OF SURVEY

I, Don R. Aschenbach, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing date of the 21st Day of July, 2004, I have dependently resurveyed a portion of the subdivisional lines, and subdivided sections 16 and 17, Township 30 North, Range 19 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 16, 2006

(Date)

Don R. Aschenbach
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 16 and 17, Township 30 North, Range 19 East, of the Mount Diablo Meridian, Nevada, executed by Don R. Aschenbach, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

August 22, 2006

(Date)

David W. Morlan
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 30 N., R. 19 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~