

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

PORTIONS OF THE EAST AND NORTH BOUNDARIES
AND A PORTION OF THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF SECTIONS 14 AND 24,

AND

THE SURVEY OF THE MEANDERS
OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
TOWNSHIP 32 NORTH, RANGE 32 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Don R. Aschenbach, Cadastral Surveyor

Under Special Instructions dated August 28, 2009,
and approved August 28, 2009,
which provided for the surveys included under Group No. 884,
and Assignment Instructions dated August 28, 2009.

Survey commenced September 2, 2009

Survey completed October 5, 2011

INDEX DIAGRAM

TOWNSHIP 32 NORTH, RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

					6	5	
6	5	4	3	2	11	1	5
				17		10	
7	8	9	10	15	11	10	12
				19	15		9
18	17	16	15	15	14	8	13
				18	14		7
19	20	21	22	12	23	6	2
				17			24
30	29	28	27	12	26		25
				11			
31	32	33	34	35			36

Subdivision of Section 14.....pp. 20-21
 Subdivision of Section 24.....pp. 21-23
 Meanders of portions of the 4144 foot contour.....pp. 23-41

TOWNSHIP 32 NORTH, RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of portions of the east and north boundaries and a portion of the subdivisional lines, the subdivision of sections 14 and 24, and the survey of the meanders of portions of the 4144 foot contour line, Township 32 North, Range 32 East, Mount Diablo Meridian, Nevada.

The exterior boundaries and subdivisional lines were surveyed by U.S. Deputy Surveyor E.H. Dyer in 1863 under Contract "E". A portion of the south boundary was retraced and the west boundary was dependently resurveyed by U.S. Surveyor W.H. Craigue and G.L.O. Transitman N.E. Potter in 1912 under Group No. 14. A portion of the east boundary was dependently resurveyed by Cadastral Engineer E. Voigt in 1939 under Group No. 258. The north and east boundaries and a portion of the south boundary were dependently resurveyed by Cadastral Surveyor J.R. Munson in 1974 under Group No. 498. A portion of the south boundary and the subdivisional lines were dependently resurveyed by Cadastral Surveyor D.R. Garoutte in 1974 under Group No. 510.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 884, dated August 28, 2009.

Measurements were made with Trimble 5700 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes. The 4144 foot contour line was determined utilizing survey grade global positional system receivers and was based on the National Geodetic Vertical Datum of 1929.

The NAD 1983 (CORS 96) geographic position of the corner of sections 1, 6, 7 and 12, on the east boundary of the township, as determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) GARL GARLIC CORS ARP, UPSA UPSAL HOGBACK CORS ARP AND TUNG TUNGSTEN CORS ARP, and carried forward by RTK observations is as follows:

Latitude: 40°39'38.165" N. Longitude: 118°18'49.381" W.

The NAD 1983 (CORS 96) geographic position of the corner of sections 26, 27, 34 and 35, as determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) GARL GARLIC CORS ARP, UPSA UPSAL HOGBACK CORS ARP AND TUNG TUNGSTEN CORS ARP and carried forward by RTK observations is as follows:

TOWNSHIP 32 NORTH, RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Latitude: 40°36'08.541" N. Longitude: 118°21'05.680" W.</p> <p>The 1971 mean magnetic declination is 18° E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "RYE PATCH RES. NORTH, NEVADA", dated 1971.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.H. Dyer in 1863, and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor J.R. Munson in 1973</p> <hr/> <p>Beginning at the 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. Bdy., T. 32 N., R. 33 E., executed under Group No. 498, with a steel fence post set alongside.</p> <p>N. 0°18'20" W., bet. secs. 19 and 24.</p> <p>Over nearly level ground, through medium growth of shadscale, greasewood and sagebrush.</p> <p>20.047 Point for the N 1/16 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S24 S19</p> <p style="text-align: center;">2009</p> <p>20.80 Jeep trail, 20 lks wide, bears SE. and NW.</p> <p>40.094 The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy., T. 32 N., R. 33 E., executed under Group No. 498, with a steel fence post set alongside.</p> <hr/> <p>N. 0°17'40" W., bet. secs. 13 and 18.</p> <p>Over nearly level ground, through medium growth of shadscale, greasewood and sagebrush.</p> <p>16.70 Waters edge, Rye Patch Reservoir, bears NE. and SW.; enter reservoir.</p>
--------	--




DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
31.80	Waters edge, Rye Patch Reservoir, bears NE. and SW., enter nearly level land.
40.092	The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. Bdy., T. 32 N., R. 33 E., executed under Group No. 498, with a steel fence post set alongside.

	N. 0°19'50" W., beginning new measurement.
	Over nearly level ground, through medium growth of shadscale, greasewood and sagebrush.
7.308	Point for a witness point, at intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<pre> WP T32N R32E R33E S18 / 4144 FT S13 </pre>
	2010
40.098	The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. Bdy., T. 32 N., R. 33 E., executed under Group No. 498, with a steel fence post set alongside.

	N. 0°19'00" W., on the line bet. secs. 7 and 12.
	Over nearly level land, through sparse vegetation.
38.021	Point for a witness point, at intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> <p>WP T32N R32E R33E</p>  <p>2010</p> </div>
40.093	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes the dependent resurvey of the W. Bdy., T. 32 N., R. 33 E., executed under Group No. 498, with a steel fence post set alongside.</p> <hr/> <p>N. 0°18'40" W., beginning new measurement.</p>
3.453	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>WP T32N R32E R33E</p>  <p>2010</p> </div>
36.491	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
40.091	<div style="text-align: center;"> <p>WP T32N R32E R33E</p>  <p>2010</p> </div> <p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. Bdy., T. 32 N., R. 33 E., executed under Group No. 498, with a steel fence post set alongside.</p> <hr/>



DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°18'20" W., bet. secs. 1 and 6.</p> <p>Over nearly level land, through sparse vegetation.</p> <p>0.40 Waters edge, Rye Patch Reservoir, bears E. and W., enter reservoir.</p> <p>40.102 Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance, falls in Rye Patch Reservoir; no permanent monument established.</p> <p>80.204 Point for the cor. of Tps. 32 and 33 N., Rs. 32 and 33 E., at proportionate distance, there is no remaining evidence of the position of the original corner, falls in Rye Patch Reservoir; no permanent monument established.</p> <p>From this point, the witness point on the line bet. secs. 31 and 36, Tps. 33 N., Rs. 32 and 33 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the West Bdy., T. 33 N., R. 33 E., executed under Group No. 498, with a steel fence post set alongside, bears N. 0°06'00" W., 52.265 chs. dist.</p> <p>From this same point, the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of T. 33 N., R. 33 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the N. bdy., T. 32 N., R. 33 E., executed under Group No. 258, with a steel fence post set alongside, bears N. 89°39'40" E., 79.736 chs. dist. All intervening corners were searched for and no evidence was found.</p>
<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyor E.H. Dyer in 1863, and the Dependent Resurvey Executed by Cadastral Surveyor J.R. Munson in 1973</p> <hr/>	
	<p>From the point for the cor. of Tps. 32 and 33 N., Rs. 32 and 33 E., hereinbefore described.</p> <p>S. 89°53'30" W., bet. secs. 1 and 36.</p> <p>Across Rye Patch Reservoir.</p> <p>40.058 Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance, falls in Rye Patch Reservoir; no permanent monument established.</p> <p>80.116 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance, falls in Rye Patch Reservoir; no permanent monument established.</p>

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°53'30" W., bet. secs. 2 and 35.
	Across Rye Patch Reservoir.
10.00	Waters edge, Rye Patch Reservoir, bears NE. and SW; over nearly level ground.
10.25	Record distance for the 1974 witness point; there is no remaining evidence of the position of the corner. This point serves no further function.
13.893	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">WP T33N R32E S35</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 4144 FT / 2 T32N</p> <p style="text-align: center;">2010</p>
40.058	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the N. bdy., T. 32 N., R. 32 E., executed under Group No. 498.</p>
<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.H. Dyer in 1863, and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor D.R. Garoutte in 1974</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p>
	N. 0°07'30" W., bet. secs. 23 and 24.
	Over nearly level land, through greasewood.
20.033	Point for the N 1/16 sec. cor. of secs. 23 and 24.
	POINT NOT MONUMENTED

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
23.032	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;">  <p>T32N R32E S S23 4144 FT 24 2010</p> </div>
40.066	<p>The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p>
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy of the Tp., hereinbefore described.</p>
	<p>S. 89°51'40" W., bet. secs. 13 and 24.</p>
	<p>Over nearly level land, through greasewood.</p>
5.00	<p>Jeep trail, 20 lks. wide, bears SE. and NW.</p>
36.022	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;">  <p>WP T32N R32E S13 S 4144 FT 24 2010</p> </div>
40.119	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p>
	<p>S. 89°52'00" W., beginning new measurement.</p>
13.50	<p>Jeep trail, 20 lks. wide, SE. and NW.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
21.599	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP T32N R32E S13</p> <hr style="width: 10%; margin: 0 auto;"/> <p>S 4144 FT 24</p> <p>2010</p> </div>
40.116	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°15'00" W., bet. secs. 13 and 14.</p> <p>Over nearly level land, through greasewood.</p>
2.00	<p>Waters edge, Rye Patch Reservoir, bears irregularly E. and W., soon irregularly N.; along W. edge and intermittently crossing reservoir.</p>
40.062	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°16'10" W., beginning new measurement.</p>
8.405	<p>Point selected for a witness point, on the line bet. secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP T32N R32E S13 S14 2010</p> </div>
10.13	<p>Record distance for the 1974 witness post; found an iron post, 28 ins. long, 2 1/2 ins. diam., laying loose and out of position, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510. This point serves no further function.</p> <p>Removed and destroyed the iron post.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.60	Waters edge, Rye Patch Reservoir, bears irregularly NE. and SW.; across reservoir.
40.070	Point for the sec. cor. of secs. 11 and 12, 13 and 14, at proportionate distance, falls in Rye Patch Reservoir; no permanent monument established.
	<hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°48'20" W., bet. secs. 12 and 13.</p> <p>Over nearly level land, through greasewood.</p>
15.545	Point for a witness point, at intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">WP T32N R32E</p> <p style="text-align: center;">S 4144 FT 12 ————— S13 2010</p>
27.00	Waters edge, Rye Patch Reservoir, bears irregularly N. and S.; across reservoir.
39.00	Waters edge, Rye Patch Reservoir, bears irregularly N. and S.; over nearly level land.
40.075	The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional line, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.
	<hr/> <p>S. 89°50'30" W., beginning new measurement.</p>
6.631	Point selected for a witness point on the line bet. secs. 12 and 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	WP T32N R32E S12 <hr style="width: 10%; margin: 0 auto;"/> S13 2009
7.37	<p>Record distance for the 1974 witness post; found a iron post, 28 ins. long, 2 1/2 ins. diam., laying loose and out of position, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510. This point serves no further function.</p> <p>Removed and destroyed the iron post.</p>
9.40	<p>Waters edge, Rye Patch Reservoir, bears irregularly SE. and NW.; across reservoir.</p>
40.068	<p>The point for the cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0°03'30" W., bet. secs. 11 and 12.</p> <p>Across Rye Patch Reservoir.</p>
40.070	<p>Point for the 1/4 cor. of secs. 11 and 12, at proportionate dist., falls in reservoir; no permanent monument established.</p>
80.140	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist., falls in reservoir; no permanent monument established.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°47'40" W., bet. secs. 1 and 12.</p> <p>Over nearly level land.</p>
2.325	<p>Point selected for a witness point, on the line bet. secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	WP T32N R32E S 1 <hr style="width: 10%; margin: 0 auto;"/> S12 2010



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
2.58	Record distance for the 1974 witness post; found a iron post, 28 ins. long, 2 1/2 ins. diam., laying loose and out of position, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510. This point serves no further function. Removed and destroyed the iron post.
3.50	Waters edge, Rye Patch Reservoir, bears N. and S.; enter reservoir.
39.885	Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist., falls in reservoir; no permanent monument established.
79.770	The point for the cor. of secs. 1, 2, 11 and 12. <hr/>
	N. 0°34'00" W., bet. secs. 1 and 2. Across Rye Patch Reservoir.
40.072	Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist., falls in reservoir; no permanent monument established.
80.345	The point for the cor. of secs. 1, 2, 35 and 36, on the N. bdy of the Tp., hereinbefore described. <hr/>
	From the witness 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside. S. 89°31'50" W., bet. secs. 26 and 35. Over gently rolling land, through budsage, shadscale and greasewood.
7.678	Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p>WP T32N R32E</p> <p>S 4144 FT 26</p> <hr style="width: 10%; margin: auto;"/> <p>S35 2010</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
33.789	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p> <hr/> <p>N. 0°00'40" E., bet. secs. 26 and 27.</p> <p>Over gently rolling land, through budsage, shadscale and greasewood.</p>
40.055	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p> <hr/> <p>N. 0°00'30" E., beginning new measurement.</p>
33.691	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="873 1094 1024 1331" style="text-align: center;"> <p>WP T32N R32E</p> <p>S27 S26 4144 FT</p> <p>2010</p> </div>
40.053	<p>The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p> <hr/> <p>N. 0°13'20" W., bet. secs. 22 and 23.</p> <p>Over gently rolling land, sloping generally E., through budsage, shadscale and greasewood.</p>
14.116	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;">  </div>
22.615	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div style="text-align: center;">  </div>
40.211	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510.</p> <p>From this corner, a well casing, 6 ins. diam., projecting 2 1/2 ft. above ground, bears S. 7°10' W., 2.33 chs. dist.</p>
	<hr style="width: 30%; margin: auto;"/> <p>N. 0°16'10" W., beginning new measurement.</p>
3.241	<p>The 1974 witness point bet. secs. 22 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510.</p>
	<hr style="width: 30%; margin: auto;"/> <p>N. 0°14'00" W., beginning new measurement.</p>
2.00	<p>Waters edge, Rye patch Reservoir, bears irregularly SE. and NW.; across reservoir.</p>
36.955	<p>Point for the cor. of secs. 14, 15, 22 and 23, determined latitudinally on the extension of the line bet. secs. 15 and 22 and longitudinally at record dist. from the witness cor. of secs. 14, 15, 22 and 23, hereinafter described, falls in reservoir; no permanent monument established.</p> <hr style="width: 30%; margin: auto;"/>




DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the cor. of secs. 13, 14, 23 and 24.
	S. 89°42'10" W., bet. secs. 14 and 23.
	Over nearly level ground, through greasewood.
11.438	Point for a witness point, at intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">WP T32N R32E S <u>4144 FT</u> 14 S23</p>
	2010
20.052	Point for the E 1/16 sec. cor. of secs. 14 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">S14 E 1/16 <u> </u> S23</p>
	2009
28.066	Point selected for a witness point, on the line bet. secs. 14 and 23.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">WP T32N R32E S14 <u> </u> S23</p>
	2010
28.74	Record distance for the 1974 witness point; there is no remaining evidence of the iron post. This point serves no further function.
29.20	Waters edge, Rye Patch Reservoir, bears irregularly SE. and NW.; across Reservoir.
40.104	Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance, falls in reservoir; no permanent monument established.
80.208	The point for the cor. of secs. 14, 15, 22 and 23.


DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°20'10" W., bet. secs. 14 and 15. Across Rye Patch Reservoir.
40.212	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance, falls in Rye Patch Reservoir; no permanent monument established.
60.00	Waters edge, Rye Patch Reservoir, bears irregularly E. and W.; over nearly level ground.
65.844	The 1974 witness point bet. secs. 14 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510.
	—————
	N. 0°19'10" W., beginning new measurement.
3.70	Waters edge, Rye Patch Reservoir, bears irregularly E. and W.; across reservoir.
14.559	Point for the cor. of secs. 10, 11, 14 and 15, determined latitudinally on the extension of the line bet. secs. 10 and 15 and longitudinally at record dist. from the witness cor. of secs. 10, 11, 14 and 15, hereinafter described, falls in reservoir; no permanent monument established.
	—————
	From the point for the cor. of secs. 11, 12, 13 and 14. S. 89°53'40" W., bet. secs. 11 and 14. Across Rye Patch Reservoir.
40.147	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance, falls in reservoir; no permanent monument established.
80.294	The point for the cor. of secs. 10, 11, 14 and 15.
	—————
	N. 0°12'10" E., bet. secs. 10 and 11. Across Rye Patch Reservoir.
7.50	Waters edge, Rye Patch Reservoir, bears irregularly NE. and SW.; over gently rolling land, slopes generally E., through greasewood.
13.185	The 1974 witness point bet. secs. 10 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510.
	—————

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°14'00" E., beginning new measurement.
10.462	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div>
20.473	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div>
27.046	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510.</p>
	<p style="text-align: center;">—————</p> <p>N. 0°13'10" E., beginning new measurement.</p>
16.848	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.202	<p>The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p> <hr/> <p>From the point for the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°54'30" W., bet. secs. 2 and 11.</p> <p>Across Rye Patch Reservoir.</p>
39.945	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance, falls in reservoir; no permanent monument established.</p>
66.50	<p>Waters edge, Rye Patch Reservoir, bears irregularly NNE. and SSW.; over gradual slope.</p>
67.018	<p>The 1974 witness point bet. secs. 2 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. as described in the field notes of dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p> <hr/> <p>N. 89°50'50" W., beginning new measurement.</p>
6.402	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  <p>WP T32N R32E 4144 Ft S11 2010</p> </div>
12.866	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°58'40" W., bet. secs. 22 and 27.</p> <p>Over gently rolling land, sloping generally E., through budsage, shadscale and greasewood.</p>
0.772	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>20.80</p> <p>39.946</p> <p>5.50</p> <p>5.970</p> <p>5.001</p>	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> WP T32N R32E $\frac{4144 \text{ FT}}{S}$ S27 2010 </p> <p>Dry wash, 20 lks. wide, drains NE.</p> <p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p> <hr/> <p>From the true point for the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°56'40" W., bet. secs. 15 and 22.</p> <p>Across Rye Patch Reservoir.</p> <p>Waters edge, Rye Patch Reservoir, bears irregularly N. and S.; over gently rolling land, through budsage, shadscale and greasewood.</p> <p>The 1974 witness cor. to the cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p> <hr/> <p>S. 89°56'40" W., beginning new measurement.</p> <p>Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> WP T32N R32E S15 $\frac{4144 \text{ FT}}{S}$ 2010 </p>
--	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
34.110	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p> <hr/> <p>From the true point for the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°51'40" W., bet. secs. 10 and 15.</p> <p>Across Rye Patch Reservoir.</p>
4.50	<p>Waters edge, Rye Patch Reservoir, bears irregularly NE. and SW.; over gently rolling land, through budsage, shadscale and greasewood.</p>
5.340	<p>The 1974 witness cor. to the cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510.</p> <hr/> <p>S. 89°51'40" W., beginning new measurement.</p>
7.257	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the west side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP T32N R32E</p> <p>S15</p> <p>2010</p> </div>
34.875	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.</p> <hr/>



SUBDIVISION OF SECTION 14
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the point for the 1/4 sec. cor. of secs. 14 and 23.
	N. 0°17'50" W., on the N-S center line of sec. 14.
	Across Rye Patch Reservoir.
40.137	Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W center line, falls in reservoir; no permanent monument established.
80.268	The point for the 1/4 sec. cor. of secs. 11 and 14.
<hr/>	
	From the 1/4 sec. cor. of secs. 13 and 14.
	S. 89°48'30" W., on the E-W center line of sec. 14.
	Over gently rolling land, through greasewood.
2.570	Intersect the 4144 foot contour line, on the east side of Rye Patch Reservoir.
9.521	Intersect the 4144 foot contour line, on the east side of Rye Patch Reservoir.
9.70	Waters edge, Rye Patch Reservoir, bears irregularly NE. and SW.; across Rye patch Reservoir.
20.066	Point for the C-E 1/16 sec. cor. of sec. 14, falls in reservoir; no permanent monument established.
40.132	The point for the C 1/4 sec. cor. of sec. 14.
80.258	The point for the 1/4 sec. cor. of secs. 14 and 15.
<hr/>	
	From the E 1/16 sec. cor. of secs. 14 and 23.
	N. 0°16'30" W., on the N-S center line of the SE1/4 of sec. 14.
28.025	Point selected for a witness point on the N-S center line of the SE1/4 of sec. 14.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<pre> WP E S 14 E 2009 </pre>
28.120	Point of intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir, falls on steep slope.

SUBDIVISION OF SECTION 14
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
28.80	Waters edge, Rye Patch Reservoir, bears irregularly NE. and SW; across Rye patch Reservoir.
40.100	The point for the C-E 1/16 sec. cor. of sec. 14.
<hr/> SUBDIVISION OF SECTION 24 T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA	
	From the 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines, T. 32 N., R. 32 E., executed under Group No. 510, with a steel fence post set alongside.
	N. 0°16'50" E., on the N-S center line of sec. 24.
	Over gently rolling land, through greasewood.
9.80	Jeep trail, 20 lks. wide, bears E. and W.
40.874	Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T32N R32E C 1/4 S24 2010
60.913	Point for the C-N 1/16 sec. cor. of sec. 24.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	C N 1/16 S24 C 2009
64.860	Intersect the 4144 foot contour line, on the east side of Rye Patch Reservoir.
66.30	Jeep trail, 20 lks. wide, bears NW. and SE.
80.952	The 1/4 sec. cor. of secs. 13 and 24.

SUBDIVISION OF SECTION 24
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>40.533</p> <p>80.371</p>	<p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°53'00" W., on the E-W center line of sec. 24.</p> <p>Over gently rolling land, through budsage, shadscale and greasewood.</p> <p>The C 1/4 sec. cor. of sec. 24.</p> <p>The 1/4 sec. cor. of secs. 23 and 24.</p>
<p>10.599</p>	<p>From the N 1/16 sec. cor. of secs. 19 and 24 on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°52'20" W., on the E-W center line of the NE1/4 of sec. 24.</p> <p>Over gently rolling land, through budsage, shadscale and greasewood.</p> <p>Point for a witness point, at intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>T32N R32E</p>  <p>2010</p> </div>
<p>28.264</p>	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p> <p>T32N R32E</p>  <p>2010</p> </div>
<p>40.325</p>	<p>The C-N 1/16 sec. cor. of sec. 24.</p>

SUBDIVISION OF SECTION 24
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S. 89°52'30" W., on the E-W center line of the NW1/4 of sec. 24.</p> <p>Over gently rolling land, through budsage, shadscale and greasewood.</p>
2.705	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the east side of Rye Patch Reservoir.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div>
39.976	<p>The N 1/16 sec. cor. of secs. 23 and 24.</p> <hr/> <p style="text-align: center;">MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR, T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">MEMORANDUM</p> <p>The survey of the meanders along the 4144 foot contour line in Township 32 North, Range 32 East, is to identify certain boundaries of Reclamation withdrawn lands to be conveyed to the Pershing County Water Conservation District and the State of Nevada pursuant to P.L. 107-282. The 4144 foot contour line was determined utilizing survey grade global positional system receivers and was based on the National Geodetic Vertical Datum of 1929.</p> <hr/> <p style="text-align: center;">West side of Rye Patch Reservoir</p> <p>From the witness point on the line bet. secs. 2 and 35, N. 89°53'30" E., 26.165 chs. dist. from the 1/4 sec. cor. of secs. 2 and 35, both on the N. bdy of the Tp. and hereinbefore described.</p> <p>Thence with meanders along the 4144 foot contour line, on the west side of Rye Patch Reservoir, through sec. 2.</p> <p>S. 29°23'40" W., 1.945 chs. dist.</p> <p>S. 27°36'20" W., 3.360 chs. dist.</p> <p>S. 37°02'30" E., 2.479 chs. dist.</p> <p>S. 30°12'10" W., 2.347 chs. dist.</p>

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS			
	N. 27°49'40" W.,	3.447 chs. dist.	
	S. 42°34'30" W.,	1.173 chs. dist.	
	S. 34°55'00" E.,	1.939 chs. dist.	
	S. 15°30'40" W.,	1.623 chs. dist.	
	S. 20°11'00" E.,	2.103 chs. dist.	
	S. 18°24'10" W.,	2.630 chs. dist.	
	N. 31°38'00" W.,	1.517 chs. dist.	
	S. 29°43'00" W.,	2.111 chs. dist.	
	S. 6°56'20" W.,	4.503 chs. dist.	
	N. 70°53'50" W.,	3.870 chs. dist.	
	N. 26°52'20" W.,	1.335 chs. dist.	
	S. 42°50'40" W.,	2.438 chs. dist.	
	S. 28°12'00" E.,	4.887 chs. dist.	
	S. 46°24'10" W.,	3.093 chs. dist.	
	S. 60°13'50" W.,	3.521 chs. dist.	At end of course, Spur, slopes S.
	N. 19°03'30" W.,	3.318 chs. dist.	
	N. 85°42'00" W.,	1.432 chs. dist.	
	S. 7°39'10" W.,	3.174 chs. dist.	At end of course, Spur, slopes S.
	N. 75°49'50" W.,	1.992 chs. dist.	
	N. 65°34'50" W.,	3.119 chs. dist.	
	N. 39°12'20" W.,	2.942 chs. dist.	
	N. 18°47'10" W.,	3.340 chs. dist.	
	N. 13°54'30" W.,	5.530 chs. dist.	
	N. 32°35'20" E.,	3.857 chs. dist.	
	N. 66°20'30" E.,	2.610 chs. dist.	
	N. 15°52'50" W.,	0.620 chs. dist.	

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS			
	N. 75°30'40" W.,	1.809 chs. dist.	
	S. 54°57'10" W.,	1.780 chs. dist.	
	N. 35°54'50" W.,	1.207 chs. dist.	
	N. 8°29'00" W.,	2.797 chs. dist.	
	N. 28°18'50" E.,	0.571 chs. dist.	
	N. 24°55'10" E.,	1.382 chs. dist.	
	S. 60°50'30" W.,	2.706 chs. dist.	At 1.20 chs., dry wash, 30 lks. wide, drains S.
	S. 25°24'10" W.,	1.951 chs. dist.	
	S. 5°28'10" W.,	2.679 chs. dist.	
	S. 2°01'00" W.,	1.848 chs. dist.	
	S. 1°15'30" E.,	2.111 chs. dist.	
	S. 48°36'50" W.,	2.124 chs. dist.	
	S. 50°55'30" W.,	2.012 chs. dist.	
	S. 55°25'50" W.,	2.462 chs. dist.	At 1.50 chs., dry wash, 20 lks. wide, drains S.
	S. 30°13'40" W.,	3.146 chs. dist.	
	S. 40°03'10" W.,	2.977 chs. dist.	
	S. 9°55'10" W.,	2.417 chs. dist.	
	S. 12°52'10" W.,	2.237 chs. dist.	
	S. 77°05'00" E.,	2.138 chs. dist.	
	S. 31°11'20" E.,	1.657 chs. dist.	
	S. 15°35'00" E.,	1.772 chs. dist.	
	S. 40°50'50" W.,	1.791 chs. dist.	
	S. 41°08'00" E.,	2.485 chs. dist.	
	S. 50°15'40" W.,	2.377 chs. dist.	
	S. 72°53'40" W.,	1.988 chs. dist.	
	S. 7°44'30" E.,	2.113 chs. dist.	

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS			
	S. 22°04'50" W.,	1.891 chs. dist.	
	S. 17°55'30" W.,	2.757 chs. dist.	
	S. 16°13'40" W.,	2.579 chs. dist.	
	S. 3°48'10" E.,	1.053 chs. dist.	
	N. 77°43'50" E.,	2.036 chs. dist.	At 1.30 chs., dry wash, 20 lks. wide, drains NE.
	N. 45°42'50" E.,	3.309 chs. dist.	
	N. 46°30'20" E.,	2.461 chs. dist.	
	N. 45°23'40" E.,	3.011 chs. dist.	
	N. 42°08'30" E.,	2.419 chs. dist.	
	N. 45°06'10" E.,	2.789 chs. dist.	
	N. 68°21'50" E.,	2.596 chs. dist.	
	N. 82°59'10" E.,	3.887 chs. dist.	
	S. 89°06'50" E.,	1.931 chs. dist.	
	S. 66°52'20" E.,	2.898 chs. dist.	
	N. 62°33'30" E.,	1.650 chs. dist.	At end of course, Spur, slopes NE.
	S. 66°06'20" E.,	0.667 chs. dist.	
	S. 3°40'50" W.,	3.418 chs. dist.	
	N. 79°24'10" W.,	3.391 chs. dist.	
	S. 10°08'00" W.,	1.007 chs. dist.	
	S. 23°04'50" E.,	2.947 chs. dist.	
	S. 42°56'00" W.,	1.798 chs. dist.	
	S. 87°54'40" W.,	1.621 chs. dist.	
	S. 36°47'20" W.,	1.390 chs. dist.	
	S. 82°09'40" W.,	1.899 chs. dist.	
	N. 38°55'40" W.,	1.656 chs. dist.	
	S. 34°10'00" W.,	1.075 chs. dist.	

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS		
	S. 6°48'40" E.,	2.964 chs. dist.
	S. 22°17'20" W.,	2.636 chs. dist.
	S. 52°53'20" W.,	2.130 chs. dist.
	N. 36°59'20" W.,	2.035 chs. dist.
	S. 36°47'20" W.,	1.852 chs. dist.
	S. 6°33'00" E.,	2.860 chs. dist.
	S. 62°16'00" W.,	1.222 chs. dist.
	S. 20°37'30" W.,	1.986 chs. dist.
	S. 72°17'50" W.,	1.609 chs. dist.
	N. 72°51'20" W.,	2.289 chs. dist.
	S. 23°04'10" W.,	3.600 chs. dist.
	N. 82°17'30" W.,	1.440 chs. dist.
	S. 7°46'40" E.,	2.104 chs. dist.
	S. 33°41'50" W.,	1.630 chs. dist.
	S. 61°13'00" W.,	0.931 chs. dist.
	S. 4°00'10" W.,	0.936 chs. dist.
	S. 35°33'30" W.,	1.366 chs. dist.
	N. 44°46'20" W.,	3.046 chs. dist.
	S. 51°53'30" W.,	1.772 chs. dist.
	S. 15°57'40" W.,	2.768 chs. dist.
	N. 69°42'40" W.,	3.387 chs. dist.
	S. 15°07'50" E.,	2.135 chs. dist.
	S. 30°38'10" W.,	1.428 chs. dist.
	N. 67°41'30" W.,	1.197 chs. dist.
	S. 28°56'40" W.,	2.472 chs. dist.
	S. 33°28'10" W.,	3.164 chs. dist.
	S. 33°59'40" W.,	2.055 chs. dist.

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS		
	N. 88°48'00" W.,	2.233 chs. dist.
	S. 38°13'10" W.,	2.329 chs. dist.
	S. 87°21'20" W.,	1.969 chs. dist.
	S. 8°11'30" W.,	0.987 chs. dist.
		At 0.50 chs., dry wash,
		20 lks. wide, drains SE.
	S. 51°51'40" E.,	1.567 chs. dist.
	S. 2°33'00" W.,	1.775 chs. dist.
		At end of course, the
		witness point on the
		line bet. secs. 2 and
		11, S. 89°50'50" E.,
		6.464 chs. dist. from
		the cor. of secs. 2, 3,
		10 and 11, hereinbefore
		described.
	<hr/>	
	From the most northerly witness point on the line bet. secs. 10	
	and 11, S. 0°13'10" W., 23.354 chs. dist. from the cor. of secs.	
	2, 3, 10 and 11, both hereinbefore described.	
	Thence with the meanders along the 4144 foot contour line, on	
	the west side of Rye Patch Reservoir, through a portion of the	
	E1/2 of the E1/2 of sec. 10.	
	N. 1°12'20" W.,	0.168 chs. dist.
	S. 38°49'20" W.,	2.404 chs. dist.
	S. 29°40'10" W.,	2.023 chs. dist.
	S. 8°25'40" E.,	0.725 chs. dist.
	N. 68°44'40" W.,	0.432 chs. dist.
	S. 25°20'50" E.,	2.830 chs. dist.
	S. 23°49'30" E.,	2.295 chs. dist.
	S. 7°54'50" W.,	2.680 chs. dist.
	S. 5°28'30" E.,	2.439 chs. dist.
	S. 20°31'10" W.,	2.208 chs. dist.
	S. 74°21'40" W.,	2.047 chs. dist.
	S. 9°17'30" W.,	3.290 chs. dist.
	S. 42°46'10" E.,	3.073 chs. dist.

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS		
	S. 51°08'40" E., 2.447 chs. dist.	At end of course, the third most southerly witness point on the line bet. secs. 10 and 11, S. 0°14'00" W., 6.573 chs. dist. from the 1/4 sec. cor. of secs. 10 and 11, both hereinbefore described.
	<p>From the second most southerly witness point on the line bet. secs. 10 and 11, N. 0°14'00" E., 10.462 chs. dist. from the 1974 witness point on the line bet. secs. 10 and 11, both hereinbefore described.</p>	
	<p>Thence with the meanders along the 4144 foot contour line, on the west side of Rye Patch Reservoir, continuing through a portion of the E1/2E1/2 of sec. 10.</p>	
	S. 50°41'10" W., 1.289 chs. dist.	
	S. 61°11'40" W., 2.091 chs. dist.	
	S. 40°39'50" W., 1.852 chs. dist.	
	N. 82°13'20" W., 2.383 chs. dist.	
	S. 54°23'00" W., 3.151 chs. dist.	At end of course, dry wash, 30 lks. wide, drains SE.
	S. 5°59'50" E., 2.253 chs. dist.	
	S. 11°51'40" E., 3.642 chs. dist.	
	S. 30°29'10" W., 2.994 chs dist.	
	S. 17°16'30" W., 3.320 chs. dist.	
	S. 21°52'30" E., 3.251 chs. dist.	
	S. 18°06'00" W., 3.243 chs. dist.	
	S. 62°03'10" W., 2.730 chs. dist.	At end of course, the witness point on the line bet. secs. 10 and 15, S. 89°51'40" W., 7.257 chs. dist. from the 1974 witness cor. for the cor. of secs. 10, 11, 14 and 15, both hereinbefore described.

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS		
	From the witness point on the line bet. secs. 15 and 22, S. 89°56'40" W., 5.001 chs. dist. from the 1974 witness corner for the cor. of secs. 14, 15, 22 and 23, both hereinbefore described.	
	Thence with the meanders along the 4144 foot contour line, on the west side of Rye Patch Reservoir, through a portion of the E1/2 of the NE 1/4 of sec. 22 and through a portion of the NE1/4 of the SE1/4 of sec. 22.	
	S. 1°38'50" E.,	0.640 chs. dist.
	S. 16°00'40" W.,	1.725 chs. dist.
	S. 4°57'50" W.,	1.231 chs. dist.
	S. 35°10'00" E.,	1.836 chs. dist.
	S. 68°31'20" E.,	1.629 chs. dist.
	S. 67°23'10" E.,	2.234 chs. dist.
	S. 50°39'00" W.,	3.274 chs. dist.
	S. 73°53'10" W.,	2.425 chs. dist.
	S. 37°19'10" W.,	3.139 chs. dist. At 1.10 chs., dry wash, 20 lks. wide, drains SE.
	S. 5°07'00" E.,	2.858 chs. dist.
	S. 51°30'40" E.,	2.422 chs. dist.
	S. 29°54'20" E.,	3.339 chs. dist.
	S. 18°59'40" W.,	3.430 chs. dist.
	S. 9°22'10" W.,	1.687 chs. dist. At 1.30 chs., dry wash, 20 lks. wide, drains NE.
	N. 87°37'40" E.,	2.439 chs. dist.
	S. 85°11'40" E.,	1.648 chs. dist.
	S. 44°27'10" E.,	1.301 chs. dist.
	S. 34°19'40" E.,	1.852 chs. dist.
	N. 46°39'10" E.,	2.524 chs. dist.
	S. 77°45'50" E.,	0.959 chs. dist.
	S. 13°59'20" W.,	2.520 chs. dist.

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS			
	S. 40°48'20" W.,	1.544 chs. dist.	
	S. 20°57'40" W.,	1.743 chs. dist.	
	S. 64°33'40" W.,	3.171 chs. dist.	
	S. 23°49'30" E.,	1.467 chs. dist.	
	S. 40°10'40" E.,	2.654 chs. dist.	
	S. 10°37'40" W.,	2.398 chs. dist.	
	S. 1°36'10" E.,	3.028 chs. dist.	
	S. 14°30'00" E.,	3.577 chs. dist.	At end of course, jeep trail, 20 lks. wide, bears NE. and SW.
	S. 2°34'00" E.,	3.311 chs. dist.	
	S. 8°15'30" W.,	2.353 chs. dist.	
	S. 9°56'40" W.,	2.896 chs. dist.	
	S. 4°23'30" W.,	2.465 chs. dist.	
	S. 9°17'40" E.,	2.400 chs. dist.	At 1.90 chs., dry wash, 30 lks. wide, drains NE.
	S. 85°36'30" E.,	2.410 chs. dist.	
	S. 87°31'20" E.,	2.454 chs. dist.	
	S. 48°13'00" E.,	0.761 chs. dist.	At end of course, the second most southerly witness point on the line bet. secs. 22 and 23, S. 0°13'20" E., 17.596 chs. dist. from the 1/4 sec. cor. of secs. 22 and 23, both hereinbefore described.
<p>From the most southerly witness point on the line bet. secs. 22 and 23, N. 0°13'20" W., 14.116 chs. dist. from the cor. of secs. 22, 23, 26 and 27, both hereinbefore described.</p>			
<p>Thence with the meanders along the 4144 foot contour line, on the west side of Rye Patch Reservoir, continuing through a portion of the E1/2 of the E1/2 of sec. 22.</p>			
	S. 37°33'10" W.,	1.246 chs. dist.	

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS		
	S. 37°21'30" W.,	2.435 chs. dist.
	S. 20°42'20" E.,	2.989 chs. dist.
	S. 32°21'30" W.,	2.429 chs. dist.
	S. 63°56'10" W.,	3.054 chs. dist.
	S. 4°06'30" W.,	2.130 chs. dist.
	S. 55°05'20" E.,	2.721 chs. dist.
	S. 64°40'40" E.,	1.828 chs. dist.
	S. 55°18'00" E.,	0.944 chs. dist.
		At 1.30 chs., dry wash, 20 lks. wide, drains E.
		At end of course, the witness point on the line bet. 22 and 27, N. 89°54'40" W., 0.772 chs. dist. from the cor. of secs. 22, 23, 26 and 27, both hereinbefore described.
<p>From the witness point on the line bet. secs. 26 and 27, S. 0°00'30" W., 6.362 chs. dist. from the cor. of secs. 22, 23, 26 and 27, both hereinbefore described.</p> <p>Thence with the meanders along the 4144 foot contour line, on the west side of Rye Patch Reservoir, through a portion of the W1/2 of sec. 26.</p>		
	N. 48°09'00" E.,	0.664 chs. dist.
	S. 62°37'00" E.,	1.668 chs. dist.
	S. 28°39'00" W.,	2.309 chs. dist.
	S. 26°57'20" E.,	1.202 chs. dist.
	S. 60°59'30" E.,	2.005 chs. dist.
	N. 67°01'10" E.,	1.985 chs. dist.
	S. 41°51'30" E.,	2.218 chs. dist.
	S. 30°17'50" W.,	2.502 chs. dist.
	S. 6°19'20" E.,	1.102 chs. dist.
	S. 4°00'10" W.,	1.825 chs. dist.
	S. 75°23'30" E.,	0.977 chs. dist.

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS			
	S. 21°56'00" W.,	1.214 chs. dist.	
	N. 89°38'10" W.,	1.297 chs. dist.	
	N. 58°58'20" W.,	1.747 chs. dist.	
	S. 52°06'50" W.,	2.416 chs. dist.	
	S. 0°08'00" W.,	3.287 chs. dist.	
	S. 19°10'20" W.,	2.518 chs. dist.	
	S. 9°20'30" E.,	2.531 chs. dist.	At 1.70 chs., dry wash, 30 lks. wide, drains NE.
	N. 51°27'30" E.,	2.010 chs. dist.	
	N. 77°07'30" E.,	2.274 chs. dist.	
	S. 79°57'10" E.,	2.481 chs. dist.	
	N. 79°49'20" E.,	2.209 chs. dist.	
	S. 84°46'20" E.,	1.456 chs. dist.	At end of course, Spur, slopes NE.
	S. 25°11'10" W.,	0.786 chs. dist.	
	S. 62°35'50" W.,	3.474 chs. dist.	
	S. 51°00'30" W.,	2.834 chs. dist.	
	S. 14°29'30" W.,	3.834 chs. dist.	
	S. 17°39'40" E.,	2.552 chs. dist.	
	S. 37°42'40" E.,	2.355 chs. dist.	
	S. 66°56'10" W.,	1.724 chs. dist.	
	S. 52°23'50" W.,	1.910 chs. dist.	
	S. 12°47'00" E.,	2.286 chs. dist.	
	S. 28°55'50" E.,	2.419 chs. dist.	
	S. 66°48'30" E.,	2.245 chs. dist.	
	N. 89°04'40" E.,	2.715 chs. dist.	
	S. 29°38'10" E.,	2.026 chs. dist.	
	S. 16°21'30" E.,	2.980 chs. dist.	

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS		
	S. 27°44'50" W.,	2.748 chs. dist.
	S. 40°28'00" W.,	2.572 chs. dist.
	S. 11°46'00" W.,	2.453 chs. dist.
	S. 30°25'50" E.,	1.958 chs. dist.
	S. 12°12'20" W.,	2.335 chs. dist.
	S. 12°41'50" E.,	2.560 chs. dist.
	S. 2°03'30" E.,	1.463 chs. dist.
	S. 9°14'40" W.,	3.124 chs. dist.
	S. 27°05'20" W.,	3.840 chs. dist.
	S. 39°26'00" W.,	2.058 chs. dist.
	S. 64°19'50" E.,	2.865 chs. dist.
		At 0.30 chs., dry wash, 30 lks. wide, drains NE.
	S. 22°42'00" E.,	3.332 chs. dist.
	S. 34°59'10" E.,	2.558 chs. dist.
	S. 75°03'50" E.,	2.260 chs. dist.
	N. 74°06'30" E.,	2.760 chs. dist.
	N. 18°37'50" E.,	3.125 chs. dist.
	N. 53°02'00" E.,	2.348 chs. dist.
	N. 21°58'50" E.,	1.943 chs. dist.
	S. 74°28'00" E.,	1.907 chs. dist.
	S. 63°08'40" E.,	1.810 chs. dist.
	N. 49°55'30" E.,	1.861 chs. dist.
	N. 57°37'20" E.,	2.635 chs. dist.
	N. 45°23'30" E.,	2.872 chs. dist.
	N. 52°47'50" E.,	2.437 chs. dist.
	N. 85°09'50" E.,	1.631 chs. dist.
		At end of course, Spur, slopes NE.
	S. 25°12'00" E.,	2.027 chs. dist.

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS		
	S. 4°26'50" E.,	2.316 chs. dist.
	S. 28°18'10" W.,	3.585 chs. dist.
	S. 7°16'20" W.,	2.312 chs. dist.
	S. 49°40'40" W.,	3.085 chs. dist.
	S. 61°06'10" W.,	2.806 chs. dist.
		At end of course, the witness point on the line bet. secs. 26 and 35, S. 89°31'50" W., 7.678 chs. dist. from the 1974 witness 1/4 cor. of secs. 26 and 35, both hereinbefore described.
East side of Rye Patch Reservoir		
From the most northerly witness point on the line bet. secs. 7 and 12, S. 0°18'40" E., 3.600 chs. dist. from the cor. of secs 1, 6, 7 and 12, both on the E. bdy. of the Tp. and hereinbefore described.		
Thence with the meanders along the 4144 foot contour line, on the east side of Rye Patch Reservoir, through a portion of the E1/2 of the NE1/4 of sec. 12.		
	N. 36°10'20" W.,	1.035 chs. dist.
	N. 12°12'50" W.,	1.153 chs. dist.
	N. 55°23'40" W.,	0.607 chs. dist.
		At end of course, Spur, slopes N.
	S. 26°47'20" W.,	0.800 chs. dist.
	S. 16°05'10" W.,	2.753 chs. dist.
	S. 36°14'40" E.,	3.043 chs. dist.
	S. 24°37'20" W.,	2.304 chs. dist.
	S. 76°56'10" W.,	0.944 chs. dist.
	S. 60°10'40" W.,	1.843 chs. dist.
	S. 42°31'30" W.,	2.970 chs. dist.
	S. 2°13'20" E.,	1.969 chs. dist.
	N. 64°39'30" E.,	4.062 chs. dist.

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS		
	S. 26°49'00" E.,	2.661 chs. dist.
	S. 12°27'40" W.,	2.794 chs. dist.
	S. 9°44'10" W.,	1.353 chs. dist.
	S. 29°54'10" E.,	2.459 chs. dist.
	S. 16°21'00" E.,	2.754 chs. dist.
	S. 28°17'40" W.,	1.716 chs. dist.
	S. 21°20'10" W.,	2.743 chs. dist.
	S. 31°36'20" W.,	3.968 chs. dist.
	S. 33°39'40" W.,	4.534 chs. dist.
	S. 0°29'10" W.,	2.358 chs. dist.
	S. 78°01'30" E.,	1.932 chs. dist.
	N. 19°50'30" E.,	2.307 chs. dist.
	N. 73°44'20" E.,	2.943 chs. dist.
	S. 14°00'50" W.,	2.174 chs. dist.
	N. 76°08'00" E.,	1.729 chs. dist.
	<p>At end of course, the middle witness point on the line bet. 7 and 12, N. 0°18'40" W., 3.453 chs. dist. from the 1/4 sec. cor. of secs. 7 and 12, both on the E. side of the Tp. and hereinbefore described.</p> <hr/> <p>From the most southerly witness point on the line bet. secs. 7 and 12, S. 0°19'00" E., 2.072 chs. dist. from the 1/4 cor. of secs 7 and 12, both on the E. bdy. of the Tp. and hereinbefore described.</p> <p>Thence with the meanders along the 4144 foot contour line, on the east side of Rye Patch Reservoir, through a portion of the SE1/4 of sec. 12.</p>	
	N. 62°50'10" W.,	1.641 chs. dist.
	S. 65°40'40" W.,	3.352 chs. dist.
	S. 61°06'20" W.,	8.761 chs. dist.

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS		
	S. 37°15'10" W.,	2.177 chs. dist.
	N. 28°56'30" W.,	2.256 chs. dist.
	N. 14°36'40" E.,	2.386 chs. dist.
	N. 84°50'00" W.,	2.861 chs. dist.
	S. 85°30'20" W.,	2.735 chs. dist.
	S. 28°47'20" W.,	0.850 chs. dist.
	S. 4°42'10" W.,	2.903 chs. dist.
	S. 9°15'30" W.,	2.873 chs. dist.
	S. 15°07'50" W.,	3.854 chs. dist.
	S. 10°34'00" W.,	2.413 chs. dist.
	S. 0°02'20" E.,	3.217 chs. dist.
	S. 10°00'10" W.,	4.182 chs. dist.
	S. 9°24'20" E.,	4.754 chs. dist.
	S. 18°08'00" E.,	2.375 chs. dist.
	S. 20°53'40" E.,	4.166 chs. dist.
	S. 63°15'00" E.,	2.884 chs. dist.
	S. 12°37'00" E.,	1.852 chs. dist.
	S. 38°09'20" E.,	2.484 chs. dist.
		At end of course, the witness point on the line bet. 12 and 13, S. 89°48'20" W., 15.545 chs. dist. from the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., both hereinbefore described.
	From the most easterly witness point on the E-W center line of the NE1/4 of sec. 24, S. 89°52'20" W., 10.599 chs. dist. from the N 1/16 cor. of secs 19 and 24, on the E. bdy. of the Tp., both hereinbefore described.	
	Thence with the meanders along the 4144 foot contour line, on the east side of Rye Patch Reservoir, through a portion of the N1/2 of the NE1/4 of sec. 24.	

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS		
	N. 78°39'40" W.,	2.053 chs. dist.
	N. 50°20'40" E.,	1.576 chs. dist.
	N. 54°08'50" E.,	1.642 chs. dist.
	N. 7°37'40" W.,	1.744 chs. dist.
	N. 2°52'30" W.,	2.756 chs. dist.
	S. 88°56'30" W.,	3.300 chs. dist.
	N. 9°16'40" W.,	2.760 chs. dist.
	N. 26°35'00" E.,	2.458 chs. dist.
	N. 68°15'00" W.,	4.431 chs. dist.
	S. 66°03'00" W.,	3.360 chs. dist.
	S. 60°00'40" W.,	2.482 chs. dist.
	S. 87°38'40" W.,	2.953 chs. dist.
	S. 57°20'00" W.,	3.828 chs. dist.
	S. 59°16'30" W.,	3.323 chs. dist.
	S. 43°56'40" E.,	4.247 chs. dist.
	S. 24°18'40" W.,	3.343 chs. dist.
	S. 63°39'10" E.,	1.800 chs. dist.
		At end of course, the most westerly witness point on the E-W center line of the NE1/4 of sec. 24, N. 89°52'20" E., 12.061 chs. dist. from the C-N 1/16 sec. cor. of sec. 24, both hereinbefore described.
	From the witness point on the E-W center line of the NW1/4 of sec. 24, S. 89°52'30" W., 2.705 chs. dist. from the C-N 1/16 sec. cor. of sec. 24, both hereinbefore described.	
	Thence with the meanders along the 4144 foot contour line, on the east side of Rye Patch Reservoir, through a portion of the NE1/4 of the NW1/4 of sec. 24.	
	N. 8°25'00" E.,	2.459 chs. dist.

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS		
	N. 63°40'10" E.,	2.080 chs. dist.
	N. 39°56'10" E.,	2.398 chs. dist. At 0.780 chs. dist., intersect the N-S center line of sec. 24, continue through a portion of the NW1/4 of the NE1/4 of sec. 24
	N. 4°11'50" E.,	2.525 chs. dist.
	N. 3°59'50" W.,	3.625 chs. dist.
	N. 64°15'20" E.,	2.906 chs. dist.
	N. 1°23'20" W.,	4.030 chs. dist.
	N. 34°35'50" E.,	2.744 chs. dist.
	N. 36°35'40" W.,	1.466 chs. dist. At end of course, the easterly witness point on the line bet. secs. 13 and 24, N. 89°51'40" E., 4.097 chs. dist. from the 1/4 sec. cor. of secs. 13 and 24, both hereinbefore described.
<p>From the most westerly witness point on the line bet. secs. 13 and 24, S. 89°52'00" W., 21.599 chs. dist. from the 1/4 sec. cor. of secs. 13 and 24, both hereinbefore described.</p>		
<p>Thence with the meanders along the 4144 foot contour line, on the east side of Rye Patch Reservoir, through a portion of the NW1/4 of the NW1/4 of sec. 24.</p>		
	S. 19°24'10" E.,	1.838 chs. dist.
	S. 44°02'20" W.,	5.179 chs. dist.
	S. 41°37'20" E.,	2.606 chs. dist.
	S. 33°58'00" W.,	3.588 chs. dist.
	S. 76°25'40" W.,	4.096 chs. dist.
	S. 69°45'30" W.,	5.769 chs. dist.
	S. 51°31'10" W.,	3.522 chs. dist.
	S. 15°19'50" W.,	2.386 chs. dist.

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 72°48'10" W., 2.548 chs. dist. At end of course, the witness point on the line bet. secs. 23 and 24, S. 0°07'30" E., 17.034 chs. dist. from the cor. of secs. 13, 14, 23 and 24, both hereinbefore described.</p> <hr/> <p>From the witness point on the line bet. secs. 14 and 23, S. 89°42'10" W., 11.438 chs. dist. from the cor. of secs. 13, 14, 23 and 24, both hereinbefore described.</p> <p>Thence with the meanders along the 4144 foot contour line, on the east side of Rye Patch Reservoir, through a portion of the E1/2 of the SE1/4 of sec. 14.</p> <p>N. 7°36'50" E., 2.512 chs. dist.</p> <p>S. 57°10'50" E., 2.564 chs. dist.</p> <p>N. 70°27'30" E., 2.308 chs. dist.</p> <p>N. 27°57'20" W., 2.667 chs. dist.</p> <p>N. 36°10'00" E., 2.722 chs. dist.</p> <p>N. 34°21'40" W., 4.486 chs. dist.</p> <p>N. 6°00'20" E., 2.210 chs. dist.</p> <p>N. 50°53'10" E., 2.673 chs. dist.</p> <p>N. 41°53'30" W., 4.202 chs. dist.</p> <p>N. 25°25'20" E., 3.533 chs. dist.</p> <p>N. 36°29'40" W., 3.162 chs. dist.</p> <p>N. 72°59'20" W., 3.411 chs. dist.</p> <p>N. 49°54'20" E., 3.257 chs. dist.</p> <p>N. 41°39'50" E., 3.729 chs. dist.</p> <p>N. 30°09'00" E., 3.567 chs. dist.</p> <p>N. 76°21'30" E., 2.326 chs. dist.</p> <p>N. 3°58'20" E., 4.252 chs. dist.</p> <p>N. 13°33'00" E., 2.817 chs. dist.</p>
--------	--

MEANDERS OF PORTIONS OF THE 4144 FOOT CONTOUR LINE,
T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS		
	N. 25°24'00" E., 2.996 chs. dist.	At 0.824 chs. dist. intersect the E-W center line of sec. 14, continue through a portion of the SE1/4 of the NE1/4 of sec. 14.
	N. 29°19'00" W., 1.821 chs. dist.	
	N. 0°34'20" E., 2.097 chs. dist.	
	N. 29°43'20" E., 1.415 chs. dist.	At end of course, Spur, slopes NE.
	S. 59°10'50" W., 2.941 chs. dist.	
	S. 38°17'50" W., 2.616 chs. dist.	
	S. 48°31'00" W., 1.890 chs. dist.	
	S. 45°51'30" W., 3.097 chs. dist.	At 2.999 chs. dist., intersect the E-W center line of sec. 14., continue through a portion of the NE1/4 of the SE1/4 of sec. 14.
	S. 50°13'40" W., 3.369 chs. dist.	
	S. 48°28'20" E., 0.940 chs. dist.	
	S. 24°06'40" E., 1.249 chs. dist.	
	N. 70°31'00" W., 1.797 chs. dist.	
	S. 9°14'00" E., 2.550 chs. dist.	
	S. 20°52'10" W., 1.903 chs. dist.	
	S. 32°31'00" W., 1.843 chs. dist.	
	S. 53°49'00" W., 2.954 chs. dist.	
	S. 67°58'10" W., 1.560 chs. dist.	
	S. 78°45'50" W., 2.301 chs. dist.	At end of course, intersect the N-S center line of the SE1/4 of sec. 14, N. 0°16'30" W., 0.095 chs. dist. from the witness point on the N-S center line of the SE1/4 of sec. 14, hereinbefore described.

T. 32 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	GENERAL DESCRIPTION
	<p>The lands within the survey border Rye Patch Reservoir. The average elevation of approximately 4150 ft. above sea level. The land is nearly level to rolling. The soil consists of mostly sandy clay to fine gravel.</p> <p>The vegetation consists of budsage, shadscale and greasewood. The land drains toward Rye Patch Reservoir, which flows in a southerly direction.</p> <p>The principal use of this area is for livestock grazing, camping, boating and fishing. Access into the township is provided by an improved dirt road and numerous trail roads.</p> <p>No minerals were noted along the lines surveyed.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Steven E. Dagitz

Land Surveyor

Michelle E. Martin

Supervisory Range Technician

Jonathan Grayson

Surveying Technician

CERTIFICATE OF SURVEY

I, Don R. Aschenbach, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 28th day of August, 2009, I have dependently resurveyed portions of the east and north boundaries and a portion of the subdivisional lines, subdivided sections 14 and 24, and surveyed the meanders of portions of the 4144 foot contour line, Township 32 North, Range 32 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 24, 2012

(Date)

Don R. Aschenbach
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of dependent resurvey of portions of the east and north boundaries and a portion of the subdivisional lines, the subdivision of sections 14 and 24, and the survey of the meanders of portions of the 4144 foot contour line, Township 32 North, Range 32 East, Mount Diablo Meridian, Nevada, executed by Don R. Aschenbach, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

May 3, 2012

(Date)

David P. York
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 32 N., R. 32 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~