

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 3 AND 4,

TOWNSHIP 34 NORTH, RANGE 55 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Michael E. Swope, Cadastral Surveyor

Under Special Instructions dated March 9, 2015,

and approved March 9, 2015,

which provided for the surveys included under Group No. 942,

and Assignment Instructions dated March 9, 2015.

Survey commenced March 11, 2015

Survey completed June 3, 2015

INDEX DIAGRAM

TOWNSHIP 34 NORTH, RANGE 55 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	3 4 7	2 5 3 5	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

SUBDIVISION OF SECTION 3	pp 8 - 16
SUBDIVISION OF SECTION 4	pp 16 - 22

TOWNSHIP 34 NORTH, RANGE 55 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and the subdivision of sections 3 and 4, Township 34 North, Range 55 East, Mount Diablo Meridian, Nevada.

The east boundary was surveyed by U.S. Deputy Surveyor C.C. Tracey in 1868 under Contract No. 13. The south, west, and north boundaries and the subdivisional lines were surveyed by U.S. Deputy Surveyor C.C. Tracey, in 1869 under Contract No. 21. The north boundary was dependently resurveyed by U.S. Deputy Surveyor H.B. Maxon in 1894 under Contract No. 204. The east boundary (Ruby Valley Guide Meridian) was dependently resurveyed by U.S. Surveyor W.A. Pray in 1915 under Group No. 28. Portions of the east and west boundaries and a portion of the subdivisional lines were dependently resurveyed by Cadastral surveyor A.D. Griffin in 1969 under Group No. 462. A portion of the subdivisional lines were dependently resurveyed, section 10 was subdivided and a metes-and-bounds survey in section 10 was surveyed by Cadastral Surveyor M.E. Collie in 1974 under Group No. 507. Portions of the south and west boundaries and a portion of the subdivisional lines were dependently resurveyed by Cadastral Surveyor R.A. Pratt in 1983-84 under Group No. 609.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the original field note record.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 942, dated March 9, 2015.

Measurements were made with Trimble R8 Global Positioning System (GPS) receivers using the real-time kinematic method. The direction of each line is with reference to the true meridian. All bearings are mean bearings and the distances are reported as horizontal measurement at a mean ground elevation of 5,300 feet above sea level.

The NAD 1983 (2011) (EPOCH:2010.0000) geographic position, of the following corners were determined from GPS static observations processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) SPRINGCREKNV2007 CORS ARP, MCDERMITT_OR2008 CORS ARP, SALMONFALLNV2007 CORS ARP and carried forward by RTK observations is as follows:

The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., is as follows:

Latitude: 40°52'10.271" N. Longitude: 115°47'45.133" W.

TOWNSHIP 34 NORTH, RANGE 55 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The 1/4 sec. cor. of secs. 3 and 10 is as follows:

Latitude: 40°51'15.521" N. Longitude: 115°46'00.263" W.

The mean magnetic declination is 17° E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "ELKO WEST, NEV" dated 1962.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
U.S. Deputy Surveyor C.C. Tracey in 1869,
and a Portion of the Dependent Resurvey Executed by
U.S. Deputy Surveyor H.B. Maxon in 1894

Beginning at the 1/4 sec. cor. of secs. 3 and 34, perpetuated by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, in 1991, monumented with a rebar, 5/8 in. diam., 17 ins. long, firmly set, projecting 1 in. above the ground, with a plastic cap mkd. PLS 6203, with a redwood post, 2x2 ins., 27 ins. long, mkd. x with other illegible markings on a face, wired to a steel fence post, 5 ft. long, lying loose on the ground alongside the rebar, as recorded in Elko County, Nevada, Record of Survey, File No. 302100. This is accepted as a careful and faithful perpetuation of the position of the original corner.

At corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T35N R55E

S34

1/4 —

S 3

T34N

2015

Insert rebar inside, bury redwood post and drive steel fence post alongside stainless steel post.

N. 89°48'30" W., bet. secs. 3 and 34.

Over rolling terrain, through bunch grass and scattered sagebrush.

20.154 Point for the W 1/16 sec. cor. of secs. 3 and 34.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: right;">S34</div> <div style="text-align: center;">W 1/16 ———</div> <div style="text-align: right;">S 3</div> <div style="text-align: center;">2015</div>
23.60	Dirt road, 12 lks. wide, bears SE. and NW.
25.30	Top of bluff, bears SE. and NW.
30.231	<p>Point for the W-W 1/64 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: right;">S34</div> <div style="text-align: center;">W-W 1/64 ———</div> <div style="text-align: right;">S 3</div> <div style="text-align: center;">2015</div>
40.308	<p>The cor. of secs. 3, 4, 33 and 34, monumented with a granite stone, 14x7x6 ins., firmly set, projecting 6 ins. above the ground, mkd. with 3 notches on the E. edge and 4 grooves on the W. face, and with a redwood post, 3x3 ins square, 31 ins. long, wired to a fence corner, set alongside mkd. stone, also monumented by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, in 1991, with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above the ground, with a plastic cap mkd. PLS 6203, set alongside mkd. stone, as recorded in Elko County, Nevada, Record of Survey, File No. 302100.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T35N R55E S33 S34 ——— S 4 S 3 T34N </div> <div style="text-align: center;">2015</div> <p>Insert rebar inside and bury redwood post and mkd. stone alongside stainless steel post.</p> <p>Cor. is located at the corner of barbed wire fences, extending N. and W.</p> <hr/> <p>N. 89°30'00" W., bet. secs. 4 and 33.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
23.20	Drain, course SE.
35.40	Drain, course NE.
40.119	<p>The 1/4 sec. cor. of secs. 4 and 33, determined at the center of a mound of stone, 4 ft. base, with a granite stone, 10x7x5 ins., mkd. 1/4 on a face, found disturbed, lying loose alongside mound.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T35N R55E S33 1/4 — S 4 T34N 2015</p> <p>Bury mkd. stone alongside stainless steel post.</p> <p>From this cor., a rebar, no record found, 5/8 in. diam., firmly set flush with the surface of the ground, with a plastic cap mkd. RLS 11194 SUMMIT, bears N. 68°12'20" W., 0.018 chs. dist. This rebar has been disturbed and is not utilized during the course of this survey.</p> <p>From this same cor., the cor. of secs. 4, 5, 32 and 33, bears N. 89°51'00" W., 40.451 chs. dist., monumented with a wood post, 6x8 ins. square, firmly set, projecting 4 ft. above the ground.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 52°16'30" E., 107.4 lks. dist., with brass cap mkd. RM T34NR55E S4 70.9 FT TO COR 2015 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 43°14'00" W., 216.7 lks. dist., with brass cap. mkd. RM T34NR55E S5 143.0 FT TO COR 2015 and an arrow pointing to the cor.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor C.C. Tracey in 1869 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor M.E. Collie in 1974</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10, monumented with a General Land Office iron post, 1 in. diam., firmly set, projecting 17 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 34 N., R. 55 E., executed under Group No. 507.</p> <p>S. 89°05'10" W., bet. secs. 3 and 10.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
19.528	<p>Point for the W 1/16 sec. cor. of secs. 3 and 10.</p> <p>POINT NOT MONUMENTED</p>
29.292	<p>Point for the W-W 1/64 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 3</p> <p>W-W 1/64 ———</p> <p>S10</p> <p>2015</p> </div>
39.056	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a General Land Office iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 34 N., R. 55 E., executed under Group No. 507, with a steel fence post set alongside, projecting 2 1/2 ft. above the ground.</p> <hr/> <p>N. 2°07'10" W., bet. secs. 3 and 4.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
0.40	<p>Dirt road, 35 lks. wide, bears E. and SW.</p>
3.20	<p>Dirt road, 15 lks. wide, bears NE. and SW.</p>
20.040	<p>Point for the S 1/16 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S 1/16 S 4 S 3</p> <p>2015</p>
26.70	Dirt road, 25 lks. wide, bears NE. and SW.
36.40	Dirt road, 12 lks. wide, bears NE. and SW.
40.080	<p>The 1/4 sec. cor. of secs. 3 and 4, perpetuated by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, in 1991, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, in an embedded mound of stone, 3 ft. base, with a square wooden post, 4x4 ins., 40 ins. long, and a granite stone, 9x7x3 ins., both lying loose on the ground alongside the rebar, and a steel fence post, projecting 4 ft. above the ground, alongside the mound of stone, as recorded in Elko County, Nevada, Record of Survey, File No. 302100. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p>T34N R55E 1/4 S 4 S 3</p> <p>2015</p> <p>Insert rebar inside and bury wooden post and granite stone alongside stainless steel post.</p> <p>Re-set steel fence post alongside collar of stone.</p> <hr/> <p>N. 1°18'50" W., beginning new measurement.</p>
16.80	Dirt road, 12 lks. wide, bears SE. and NW.
20.951	<p>Point for the N 1/16 sec. cor. of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>N 1/16 S 4 S 3</p> <p>2015</p>
44.102	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy of the Tp., hereinbefore described.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°53'10" W., bet. secs. 4 and 9.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
0.20	Dirt road, 35 lks. wide, bears NE. and SW.
2.98	Dirt road, 15 lks. wide, bears N. and S.
6.60	Dirt road, 30 lks. wide, bears SE. and NW.
10.084	<p>Point for the E-E 1/64 sec. cor. of secs. 4 and 9, position falls in dirt road, 20 lks. wide, bears W. and SE.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 4</p> <p>E-E 1/64 ———</p> <p>S 9</p> <p>2015</p> </div>
17.10	Dirt road, 18 lks. wide, bears NNE. and SSW.
20.168	<p>Point for the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 4</p> <p>E 1/16 ———</p> <p>S 9</p> <p>2015</p> </div>
30.252	<p>Point for the W-E 1/64 sec. cor. of secs. 4 and 9.</p> <p>POINT NOT MONUMENTED</p>
40.336	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34N R55E</p> <p>S 4</p> <p>1/4 ———</p> <p>S 9</p> <p>2015</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, a rebar, no record found, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with unreadable plastic cap, bears S. 20°19'50" E., 0.264 chs. dist.</p> <p>From this same point, the cor. of secs. 4, 5, 8 and 9, bears N. 89°53'10" W., 40.336 chs. dist., point falls in a construction site, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above the ground. This position has been adopted and record by various professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. below the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34N R55E</p> <table border="1"> <tr> <td>S 5</td><td>S 4</td></tr> <tr> <td>S 8</td><td>S 9</td></tr> </table> <p>2015</p> </div> <p>Insert rebar inside stainless steel post.</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 46°03'30" W., 154.4 lks. dist., with brass cap. mkd. RM T34NR55E S8 101.9 FT TO COR 2015 and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, for a reference monument, bears N. 15°10'20" W., 458.3 lks. dist., with brass cap. mkd. RM T34NR55E S5 302.5 FT TO COR 2015 and an arrow pointing to the cor.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 3, T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 0°50'40" W., on the N-S center line of sec. 3.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>0.20 Dirt road, 12 lks. wide, bears E. and W.</p>	S 5	S 4	S 8	S 9
S 5	S 4				
S 8	S 9				

SUBDIVISION OF SECTION 3,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 10.047</p>	<p>The C-S-S 1/64 sec. cor. of sec. 3, determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, in 1991, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, with a plastic cap mkd. PLS 6203, as recorded in Elko County, Nevada, Record of Survey, File No. 302100, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>C S-S 1/64 S 3 C 2015</p> </div> <p>Insert rebar inside stainless steel post.</p> <hr/> <p>N. 0°50'40" W., beginning new measurement.</p> <p>2.70 Dirt road, 18 lks. wide, bears SE. and NW.</p> <p>4.50 Barbed wire fence, bears S. 67° E. and N. 67° W.</p> <p>Continue across golf course.</p> <p>10.047 Point for the C-S 1/16 sec. cor. of sec. 3, point falls in a golf course where it is impractical to establish a permanent monument.</p> <p>29.50 Leave golf course, barbed wire fence, bears S. 37° W. and N. 37° E.</p> <p>30.141 Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E-W center line. This point falls in a dirt road, 25 lks. wide, bears NE. and SW.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. below the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T34N R55E C 1/4 S 3 2015</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 56°20'50" W., 189.2 lks. dist., with brass cap. mkd. RM C 1/4 S3 124.9 FT TO COR 2015 and an arrow pointing to the cor.</p>
--------------------------	---

SUBDIVISION OF SECTION 3,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, over a plastic-encased magnet, with a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 24°44'20" W., 197.6 lks. dist., with brass cap. mkd. RM C 1/4 S3 130.4 FT TO COR 2015 and an arrow pointing to the cor.</p>
50.839	<p>Point for the C-N 1/16 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \quad \quad S\ 3 \\ C \end{array}$ <p>2015</p> </div>
51.90	Dirt road, 12 lks. wide, bears SE. and NW.
73.349	<p>The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 3, determined by Mark Chilton, Nevada Professional Land Surveyor No. 1404, in 1975, monumented with an iron post, no record found, 2 1/2 ins. diam., 24 ins. long, loosely set, projecting 18 ins. above the ground, with a brass cap mkd. CORNER T34N R55E 1/4 S3 S2 1975 RLS 1404, with a rebar inside the iron post, 1/2 in. diam., 18 ins. long. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} T34N\ R55E \\ 1/4 \\ S\ 3 \quad \quad S\ 2 \end{array}$ <p>2015</p> </div> <p>Insert rebar inside and bury iron post alongside stainless steel post.</p> <p>Cor. is located at the cor. of barbed wire fences, extending E. and S.</p> <p>S. 88°55'20" W., on the E-W center line of sec. 3.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
0.20	Dirt road, 15 lks. wide, bears NE. and S.

SUBDIVISION OF SECTION 3,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
11.30	Dirt road, 15 lks. wide, bears NE. and SW.
13.50	Dirt road, 15 lks. wide, bears SE. and NW.
20.092	<p>The C-E 1/16 sec. cor. of sec. 3, determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, in 1991, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 1 in. above the ground, with a plastic cap mkd. PLS 6203, with a steel fence post alongside rebar, 4 ft. high, as recorded in Elko County, Nevada, Record of Survey, File No. 302100. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16</p> <p>C———C</p> <p>S 3</p> <p>2015</p> </div> <p>Insert rebar inside and re-set steel fence post alongside stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88°55'20" W., beginning new measurement.</p>
18.00	Dirt road, 15 lks. wide, bears NW. and SE.
20.092	The center 1/4 sec. cor. of sec. 3.
22.10	Dirt road, 12 lks. wide, bears ENE. and WSW.
30.078	<p>The C-E-W 1/64 sec. cor. of sec. 3, determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, in 1991, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 3 ins. above the ground, with plastic cap mkd. PLS 6203, as recorded in Elko County, Nevada, Record of Survey, File No. 302100. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>E-W 1/64</p> <p>C———C</p> <p>S 3</p> <p>2015</p> </div> <p>Insert rebar inside stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>

SUBDIVISION OF SECTION 3,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 88°55'20" W., beginning new measurement.
3.10	Dirt road, 12 lks. wide, bears NE. and SW.
9.986	Point for the C-W 1/16 sec. cor. of sec. 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> W 1/16 C——C S 3 2015 </div>
19.972	The C-W-W 1/64 sec. cor. of sec. 3, determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, in 1991, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 3 ins. above the ground, with a plastic cap mkd. PLS 6203, as recorded in Elko County, Nevada, Record of Survey, File No. 302100. This is accepted as a careful and faithful determination of the position of the corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> W-W 1/64 C——C S 3 2015 </div> Insert rebar inside stainless steel post. <div style="text-align: center;"> <hr style="width: 30%; margin: 0 auto;"/> </div> S. 88°55'20" W., beginning new measurement.
9.986	The 1/4 sec. cor. of secs. 3 and 4. <div style="text-align: center;"> <hr style="width: 60%; margin: 0 auto;"/> </div> From the point for the W 1/16 sec. cor. of secs. 3 and 10. N. 1°28'50" W., on the N-S center line of the SW1/4 of sec. 3. Over rolling terrain, through bunch grass and scattered sagebrush.
0.20	Barbed wire fence, bears E. and W.
0.60	Dirt road, 12 lks. wide, bears E. and W.
9.70	Dirt road, 12 lks. wide, bears NE. and SW.
20.065	Point for the SW 1/16 sec. cor. of sec. 3, at intersection with the E-W center line of the SW 1/4.

SUBDIVISION OF SECTION 3,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 3</p> <p style="text-align: center;">2015</p>
27.40	Dirt road, 12 lks. wide, bears SE. and NW.
34.10	Dirt road, 12 lks. wide, bears NE. and SW.
34.80	Dirt road, 12 lks. wide, bears NE. an SW.
35.40	Dirt road, 12 lks. wide, bears SE. and NW.
40.130	The C-W 1/16 sec. cor. of sec. 3.
	<hr/> <p>From the point for the C-S 1/16 sec. cor. of sec. 3.</p> <p>S. 89°00'10" W., on the E-W center line of the SW1/4 of sec. 3.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
5.10	Dirt road, 18 lks. wide, bears SE. and NW.
9.875	<p>The C-E-SW 1/64 sec. cor. of sec. 3, determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, in 1991, monumented with a rebar, 5/8 in. diam., 18 ins. long, loosely set, projecting 3 ins. above the ground, as recorded in Elko County, Nevada, Record of Survey, File No. 302100. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 3</p> <p style="text-align: center;">C-E-SW</p> <p style="text-align: center;">1/64</p> <p style="text-align: center;">2015</p> <p>Insert rebar inside stainless steel post.</p> <hr/> <p>S. 89°00'10' W., beginning new measurement.</p>
9.875	The SW 1/16 sec. cor. of sec. 3.
17.60	Dirt road, 12 lks. wide, bears NE. and SW.

SUBDIVISION OF SECTION 3,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.750	<p>The C-W-SW 1/64 sec. cor. of sec. 3, determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, in 1991, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, as recorded in Elko County, Nevada, Record of Survey, File No. 302100. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 3 C-W-SW 1/64 2015</p> <p>Insert rebar inside stainless steel post.</p> <hr/> <p>S. 89°00'10" W., beginning new measurement.</p>
9.875	<p>The S 1/16 sec. cor. of secs. 3 and 4.</p> <hr/> <p>From the W-W 1/64 sec. cor. of secs. 3 and 10.</p> <p>N. 1°48'00" W., on the N-S center line of the SW1/4SW1/4 of sec. 3.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
0.10	Barbed wire fence, bears E. and W.
0.40	Dirt road, 12 lks. wide, bears E. and W.
7.50	Dirt road, 12 lks. wide, bears E. and SW.
10.50	Dirt road, 12 lks. wide, bears NNE. and SSW.
20.052	<p>The C-W-SW 1/64 sec. cor. of sec. 3.</p> <hr/> <p>N. 1°48'00" W., on the N-S center line of the NW1/4SW1/4 of sec. 3.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
10.60	Dirt road, 12 lks. wide, bears NE. and SW.
20.052	<p>The C-W-W 1/64 sec. cor. of sec. 3.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 3.</p>

SUBDIVISION OF SECTION 3,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 1°04'50" W., on the N-S center line of the NW1/4 of sec. 3. Over rolling terrain, through bunch grass and scattered sagebrush.
18.00	Dirt road, 12 lks. wide, bears SE. and NW.
20.825	Point for the NW 1/16 sec. cor. of sec. 3, at intersection with the E-W center line of the NW1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. NW 1/16 S 3 2015
22.20	Dirt road, 12 lks. wide, bears ESE. and WNW.
40.00	Dirt road, 12 lks. wide, bears SE. and NW.
43.655	The W 1/16 sec. cor. of secs. 3 and 34, on the N. bdy. of the TP. <hr/>
	From the C-N 1/16 sec. cor. of sec. 3. S. 89°16'50" W., on the E-W center line of the NW1/4 of sec. 3. Over rolling terrain, through bunch grass and scattered sagebrush.
16.20	Dirt road, 12 lks. wide, bears SE. and NW.
20.056	The NW 1/16 sec. cor. of sec. 3.
24.70	Dirt road, 12 lks. wide, bears SE. and NNW.
30.084	Point for the C-W-NW 1/64 sec. cor. of sec. 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. S 3 C-W-NW 1/64 2015
40.112	The N 1/16 sec. cor. of secs. 3 and 4. <hr/>
	From the C-W-W 1/64 sec. cor. of sec. 3. N. 1°11'50" W., on the N-S center line of the SW1/4NW1/4 of sec. 3.

SUBDIVISION OF SECTION 3,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over rolling terrain, through bunch grass and scattered sagebrush.
10.444	The SW-NW 1/64 sec. cor. of sec. 3, determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, in 1991, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, as recorded in Elko County, Nevada, Record of Survey, File No. 302100. This is accepted as a careful and faithful determination of the position of the corner.

	N. 0°11'50" W., beginning new measurement.
9.60	Dirt road, 12 lks. wide, bears NE. and SW.
10.444	The C-W-NW 1/64 sec. cor. of sec. 3.

	N. 1°11'50" W., on the N-S center line of the NW1/4NW1/4 of sec. 3.
	Over rolling terrain, through bunch grass and scattered sagebrush.
9.30	Dirt road, 12 lks. wide, bears SSE. and NNW.
15.40	Dirt road, 12 lks. wide, bears SSE. and NNW.
22.990	The W-W 1/64 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.

	SUBDIVISION OF SECTION 4, T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

	From the 1/4 sec. cor. of secs. 4 and 9.
	N. 1°33'00" W., on the N-S center line of sec. 4.
	Over rolling terrain, through bunch grass and scattered sagebrush.
4.30	Levee, bears N. 40° E. and S. 40° W.
20.158	Point for the C-S 1/16 sec. cor. of sec. 4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="display: flex; align-items: center; justify-content: center;"> <div style="margin-right: 10px;">C</div> <div style="display: flex; flex-direction: column; align-items: center;"> <div style="margin-bottom: 5px;">S 1/16</div> <div style="margin-bottom: 5px;"> </div> <div style="margin-bottom: 5px;">S 4</div> </div> <div style="margin-left: 10px;">C</div> </div>
	2015
27.50	Dirt road, 15 lks. wide, bears SE. and NW.

SUBDIVISION OF SECTION 4,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
28.20	Dirt road, 15 lks. wide, bears SE. and NNW.
30.237	Point for the C-N-S 1/64 sec. cor. of sec. 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> C N-S 1/64 S 4 C 2015 </div>
31.90	Dirt road, 15 lks. wide, bears SE. and NW.
40.316	Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T34N R55E C 1/4 S 4 2015 </div>
50.50	Dirt road, 12 lks. wide, bears NE. and SW.
84.444	The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp. <hr/>
	From the 1/4 sec. cor. of secs. 3 and 4. N. 89°31'40" W., on the E-W center line of sec. 4. Over rolling terrain, through bunch grass and scattered sagebrush.
19.971	Point for the C-E 1/16 sec. cor. of sec. 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> E 1/16 C ——— C S 4 2015 </div>
39.942	The center 1/4 sec. cor. of sec. 4.
41.80	Dirt road, 50 lks. wide, bears S. and NNW.
51.50	Dirt road, 12 lks. wide, bears SSE. and NNW.
67.10	Dirt road, 12 lks. wide, bears NE. and SW.

SUBDIVISION OF SECTION 4,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 80.388</p>	<p>The 1/4 sec. cor. of secs. 4 and 5, monumented with an igneous rock (Record: charred wooden post), 12x9x5 ins., firmly set, projecting 8 ins. above the ground, mkd. 1/4 on W. face, with a wooden post, 4x4 ins. square, 45 ins. long, lying loose alongside, also monumented by Duane V. Merrill, Nevada Professional Land Surveyor No. 7000, in 1996, with a rebar, 5/8 in. diam., 18 ins. long, firmly set alongside mkd. stone, projecting 2 ins. above the ground, with a damaged plastic cap, as recorded in Elko County, Nevada, Parcel Map, File No. 384998. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T34N R55E 1/4 S 5 S 4 2015</p> <p>Insert rebar inside and bury mkd. stone alongside stainless steel post.</p> <p>Deposit wood post, loose on the ground, alongside stainless steel post.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>N. 1°50'00" W., on the N-S center line of the SE1/4 of sec. 4.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>0.10 Dirt road, 12 lks. wide, bears E. and W.</p> <p>5.025 Point for the C-S-S-SE 1/256 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 4 C-S-S-SE 1/256 2015</p> <p>7.30 Dirt road, 30 lks. wide, bears SE. and NW.</p> <p>15.075 Point for the C-N-S-SE 1/256 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------------------------	---

SUBDIVISION OF SECTION 4,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">S 4 C-N-S-SE 1/256 2015</p>
15.40	Dirt road, 30 lks. wide, bears NE. and SW.
20.100	<p>Point for the SE 1/16 sec. cor. of sec. 4, at intersection with the E-W center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 4 2015</p>
28.60	Dirt road, 30 lks. wide, bears ENE. and WSW.
40.198	<p>The C-E 1/16 sec. cor. of sec. 4.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 3 and 4.</p> <p>N. 89°42'30" W., on the E-W center line of the SE1/4 of sec. 4.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
10.90	Dirt road, 12 lks. wide, bears NE. and SW.
15.20	Dirt road, 12 lks. wide, bears ENE. and WSW.
20.070	The SE 1/16 sec. cor. of sec. 4.
30.105	<p>Point for the C-W-SE 1/64 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 4 C-W-SE 1/64 2015</p>
33.40	Dirt road, 50 lks. wide, bears SSE. and NNW.
40.140	<p>The C-S 1/16 sec. cor. of sec. 4.</p> <hr/> <p>From the E-E 1/64 sec. cor. of secs. 4 and 9.</p> <p>N. 1°58'30" W., on a portion of the computed N-S center line of the SE1/4SE1/4 of sec. 4.</p>

SUBDIVISION OF SECTION 4,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over rolling terrain, through bunch grass and scattered sagebrush.
2.00	Dirt road, 23 lks. wide, bears SE. and NW.
5.017	Point for the C-S-SE-SE 1/256 sec. cor. of sec. 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S 4 C-S-SE-SE 1/256 2015
	N. 89°50'30" W., on a portion of the computed E-W center line of the SW1/4SE1/4SE1/4 of sec. 4. Over rolling terrain, through bunch grass and scattered sagebrush.
6.30	Intersection of dirt roads, 12 lks. wide, bears NNE., SE., S. and NW.
10.071	The C-S-S-SE 1/256 sec. cor. of sec. 4. From the point for the C-N-SW-SE 1/256 sec. cor. of sec. 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. S 4 C-N-SW-SE 1/256 2015
	N. 1°41'30" W., on a portion of the computed N-S center line of the SW1/4SE1/4 of sec. 4. Over rolling terrain, through bunch grass and scattered sagebrush.
0.40	Dirt road, 30 lks. wide, bears SE. and NW.
5.032	The C-W-SE 1/64 sec. cor. of sec. 4. From the C-N-S-SE 1/256 sec. cor. of sec. 4. N. 89°45'10" W., on a portion of the computed E-W center line of the NE1/4SW1/4SE1/4 of sec. 4.

SUBDIVISION OF SECTION 4,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over rolling terrain, through bunch grass and scattered sagebrush.
9.40	Dirt road, 30 lks. wide, bears SE. and NW.
10.047	The C-N-SW-SE 1/256 sec. cor. of sec. 4.
	<hr/> <p>From the C-W-SE 1/64 sec. cor. of sec. 4.</p> <p>N. 1°41'30" W., on a portion of the computed N-S center line of the NW1/4SE1/4 of sec. 4.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
4.40	Dirt road, 12 lks. wide, bears NE. and SW.
5.032	Point for the C-S-NW-SE 1/256 sec. cor. of sec. 4.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 4 C-S-NW-SE 1/256 2015</p> <hr/> <p>From the point for the C-W-NW-SE 1/256 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 4 C-W-NW-SE 1/256 2015</p> <p>N. 89°37'10" W., on a portion of the computed E-W center line of the NW1/4SE1/4 of sec. 4.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p>
5.005	The C-N-S 1/64 sec. cor. of sec. 4.
	<hr/> <p>From the point for the SW-NW-SE 1/256 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 4,
T. 34 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> <p>S 4 SW-NW-SE 1/256</p> <p>2015</p> </div> <p>N. 1°37'20" W., on a portion of the computed N-S center line of the SW1/4NW1/4SE1/4 of sec. 4.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>5.036 The C-W-NW-SE 1/256 sec. cor. of sec. 4.</p> <hr/> <p>From the C-S-NW-SE 1/256 sec. cor. of sec. 4.</p> <p>N. 89°39'50" W., on a portion of the computed E-W center line of the SW1/4NW1/4SE1/4 of sec. 4.</p> <p>Over rolling terrain, through bunch grass and scattered sagebrush.</p> <p>5.011 The SW-NW-SE 1/256 sec. cor. of sec. 4.</p> <hr/> <div style="text-align: center;"> <p>GENERAL DESCRIPTION</p> </div> <p>The lands contained within the scope of this survey are located in Elko County, Nevada, in the community of Elko, Nevada.</p> <p>The area is generally rolling with an average elevation of approximately 5,300 ft. above sea level. The vegetation is generally sagebrush and grasses.</p> <p>Access is provided by numerous paved and dirt roads by way of Interstate No. 80.</p> <p>The use of the land is for recreational activities.</p> <p>No mineral formations of any consequence were noted during the course of this survey.</p> <hr/>
--------	--

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Brock R. Clifford

Cadastral Surveyor

Mark G. Petrosine

Surveying Technician

CERTIFICATE OF SURVEY

I, Michael E. Swope, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of March, 2015, I have dependently resurveyed a portion of the north boundary, a portion of the subdivisional lines, and subdivided sections 3 and 4, Township 34 North, Range 55 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUN 29 2015

(Date)

Michael E. Swope

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and the subdivision of sections 3 and 4, Township 34 North, Range 55 East, of the Mount Diablo Meridian, Nevada, executed by Michael E. Swope, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 29 2015

(Date)

Michael O. Hammer

(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 34 North, Range 55 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~~~(Chief Cadastral Surveyor for Nevada)~~