

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF
THE SEVENTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 32 EAST;

AND THE

DEPENDENT RESURVEY OF
A PORTION OF THE WEST BOUNDARY OF
TOWNSHIP 36 NORTH, RANGE 33 EAST;

AND THE SURVEY OF

A PORTION OF THE SOUTH BOUNDARY OF
TOWNSHIP 37 NORTH, RANGE 33 EAST;

AND THE SURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 36 NORTH, RANGE 32 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Ronald E. Williams, Cadastral Surveyor

David L. Dupleth, Cadastral Surveyor

Under Special Instructions dated August 7, 2001,

and approved August 7, 2001,

and Supplemental Special Instructions dated July 16, 2004,

and approved July 16, 2004,

which provided for the surveys included under Group No. 803,
and Assignment Instructions dated August 7, 2001 and July 16, 2004.

Survey commenced August 7, 2001

Survey completed May 12, 2005

INDEX DIAGRAM

TOWNSHIP 36 NORTH, RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

						R32E	R33E	T37N
							10	T36N
6	5	4	26 3	18 2	13 1			8
			25	18	11			
7	8	9	25 10	17 11	10 12			7
			24	16				
18	17	16	23 15	16 14	13			6
			23	15				
19	20	21	22 22	14 23	24			
			22					
30	29	29 28	21 27	26	25			
		28	20					
31	32	27 33	19 34	35	36			
		4	2					

003

TOWNSHIP 36 NORTH, RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of the Seventh Standard Parallel North, through a portion of Range 32 East; and the dependent resurvey of a portion of the west boundary of Township 36 North, Range 33 East; and the survey of a portion of the south boundary of Township 37 North, Range 33 East; and the survey of a portion of the subdivisional lines of Township 36 North, Range 32 East, Mount Diablo Meridian, Nevada.

The north boundary was surveyed by U.S. Deputy Surveyor G.W. Garside in 1874 under Contract No. 65.

The Seventh Standard Parallel North, through Range 32 East, the west boundary of Township 36 North, Range 33 East, and the subdivisional lines of Township 35 North, Range 32 East, were surveyed by U.S. Deputy Surveyor H.B. Maxson in 1888 under Contract No. 189.

A portion of the Seventh Standard Parallel North, through a portion of Range 32 East, was retraced and resurveyed, the east boundary was retraced and partially resurveyed, and a portion of the subdivisional lines were surveyed by U.S. Transitman N.E. Potter in 1912 under Group No. 14.

A portion of the north boundary was retraced, and the west boundary was surveyed by U.S. Transitman J.R. English in 1918 under Group No. 62.

Field investigations were conducted in 1960 under Group No. 389, in order to prepare Nevada Protraction Diagram No. 147, Unit Nos. 18 and 19.

A portion of the south boundary of T. 37 N., R. 32 E., was independently resurveyed concurrently under this same group.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated August 7, 2001, and the Supplemental Special Instructions, dated July 16, 2004, for Group No. 803.

Measurements were made with Trimble 4400 and 4700 Global Positioning System (GPS) receivers using real-time kinematic method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in these field notes.

004

TOWNSHIP 36 NORTH, RANGE 32 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	The geographic position (NAD 1983) of the corner of sections 32 and 33 only, on the south boundary of the township, as determined by survey grade GPS receivers, in 2001, from National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "WESTERN", located in T. 35 N., R. 32 E., is as follows: Latitude 40°56'38.544" N. Longitude 118°24'30.144" W. The mean magnetic declination is 18° E., as shown on U.S.G.S. quadrangle map "JUNGO, NEV." dated 1971. DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH, THROUGH A PORTION OF RANGE 32 EAST, T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of the Survey Executed by U.S. Deputy Surveyor H.B. Maxson in 1888 From the standard cor. of secs. 34 and 35, monumented with the rusted remains of an iron post, 3 ins. diam., filled with concrete, firmly set in the ground, the top 6 ins. of the iron post is broken off and laying loosely on the ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 32 E., executed under Group No. 14. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. SC T36N R32E <u>S34 S35</u> 2001 Deposit the remains of the 1912 iron post and set a carsonite post, 6 ft. long, alongside the stainless steel post. S. 89°53'10" W., on the S. bdy. of the Tp. Across alkali flat. 27.35 Graveled road, 20 lks. wide, bears NNE and SSW in curve; leave alkali flat, enter mountainous land, covered with native grass and shadscale. 40.000 Point for the 1/4 sec. cor. of sec. 34 only, at 40.00 chs. in departure from the standard cor. of secs. 34 and 35.
--------	---

005

DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 32 EAST,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T36N R32E <u>1/4 S34</u>
	2001
	Raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.
42.218	The standard 1/4 sec. cor. of sec. 34, monumented with a scattered mound of stone. This agrees closely with the 1912 retracement, executed by N.E. Potter, under Group No. 14, and is accepted as the best available evidence of the position of the original corner. This cor. will now function as an angle point.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	AP T36N R32E <u>S34</u>
	2001
	Raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.
	S. 89°37'20" W., beginning new measurement.
	Over mountainous land.
22.30	Top of spur, slopes NE.
37.782	Point for the cor. of secs. 33 and 34 only, at 80.00 chs. in departure from the standard cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T36N R32E <u>S33 S34</u>
	2001
40.390	Point for the standard cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now function as an angle point.

006

DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 32 EAST,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. AP T36N R32E <u>S33</u> 2001 S. 89°37'20" W., on the S. bdy. of the Tp. Over mountainous land. 37.392 Point for the 1/4 sec. cor. of sec. 33 only, at 120.00 chs. in departure from the standard cor. of secs. 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E <u>1/4 S33</u> 2001 Set a carsonite post, 6 ft. long, alongside the stainless steel post. 40.390 Point for the standard 1/4 sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now function as an angle point. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. AP T36N R32E <u>S33</u> 2001 68.40 Top of ridge, bears N. and S. 77.392 Point for the cor. of secs. 32 and 33 only, at 160.00 chs. in departure from the standard cor. of secs. 34 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T36N R32E <u>S32 S33</u> 2001
--------	--

CHAINS	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	From this corner, National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "WESTERN", monumented with a brass disc, firmly cemented flush with rock outcropping, mkd. WESTERN 1958 and a triangle, bears S. 7°41'55" W., 250.348 chs. dist.
80.780	Point for the standard cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now function as an angle point. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. AP T36N R32E S32 2001 From this point, the standard cor. of Tps. 36 N., Rs. 31 and 32 E., monumented with a trapstone, 8x6x6 ins., mkd. SC and 6 notches on the N. and 6 notches on both E. and W. edges, firmly set in a mound of stone, 2 ft. diam., alongside of which is the iron post, 3 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the 1918 dependent resurvey of T. 36 N., R. 31 E., executed by J.R. English, under Group No. 62, bears S. 89°37'20" W., 161.560 chs. dist., from which the remaining bearing tree mkd. by English A juniper, 11 ins. diam., bears N. 33° E., 28 lks. dist., with scribe marks T36N R32E S31 SC BT visible on open blaze. (Record, 30 lks.) Reset the iron post, 36 ins. long, 3 ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, and add marks 2004 to the brass cap. Deposit the original corner monument alongside the iron post. This control line was fully retraced and a careful search was made for evidence of intervening corners, none of which were recovered.

008

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 36 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of the Survey Executed by U.S. Deputy Surveyor H.B. Maxson in 1888, and the Resurvey Executed by U.S. Transitman N.E. Potter in 1912 From the 1/4 sec. cor. of sec. 18 only, on the W. bdy. of the Tp., monumented with a granite stone, 24x8x5 ins., (Record 20x6x4 ins.) firmly set, projecting 12 ins. above ground, no marks visible, alongside of which is an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. JOHN H. MILTON PLS 5271, set by John H. Milton, III, Nevada Professional Land Surveyor No. 5271, not of record. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <table> <tr><td colspan="2">T36N</td></tr> <tr><td>R32E</td><td>R33E</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td></td><td>S18</td></tr> </table> 2004 Deposit the 1912 stone alongside the stainless steel post. N. 0°36'20" E., on the W. bdy. of sec. 18. Over alkali flat.	T36N		R32E	R33E		1/4		S18
T36N									
R32E	R33E								
	1/4								
	S18								
38.212	The cor. of secs. 12 and 13 only, T. 36 N., R. 32 E., monumented with the rusted remains of an iron post, 2 ins. diam., filled with concrete, firmly set in the ground, 4 ins. below the surface, the top 16 ins. of the iron post is broken off and laying loosely on the ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 32 E., executed under Group No. 14. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. <table> <tr><td>T36N</td><td>T36N</td></tr> <tr><td>R32E</td><td>R33E</td></tr> <tr><td>S12</td><td>S18</td></tr> <tr><td>S13</td><td></td></tr> </table> 2004	T36N	T36N	R32E	R33E	S12	S18	S13	
T36N	T36N								
R32E	R33E								
S12	S18								
S13									

009

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 36 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Deposit the remains of the original iron post alongside the stainless steel post.								
40.290	The cor. of secs. 7 and 18 only, monumented with a granite stone, 21x10x7 ins., (Record, 16x9x6 ins.) firmly set, projecting 12 ins. above ground, with 4 notches on the S. edge and 2 notches on the N. edge, alongside of which is an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. JOHN H. MILTON PLS 5271, set by John H. Milton, III, Nevada Professional Land Surveyor No. 5271, not of record, and a steel fence post laying alongside. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <table border="1"> <tr><td>T36N</td><td>T36N</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td>R32E</td><td>S18</td></tr> <tr><td></td><td>R33E</td></tr> </table> 2004 Deposit the 1912 stone and iron rod and set the steel fence post alongside the stainless steel post.	T36N	T36N	S12	S 7	R32E	S18		R33E
T36N	T36N								
S12	S 7								
R32E	S18								
	R33E								
	N. 0°14'10" E., on the W. bdy. of sec. 7. Over alkali flat.								
37.820	The 1/4 sec. cor. of sec. 12 only, T. 36 N., R. 32 E., hereinafter described.								
40.169	The 1/4 sec. cor. of sec. 7 only, monumented with an unmarked granite stone, 12x7x7 ins., loosely set, and is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <table border="1"> <tr><td>T36N</td><td></td></tr> <tr><td>R32E</td><td>R33E</td></tr> <tr><td></td><td>1/4</td></tr> <tr><td></td><td>S 7</td></tr> </table> 2004 Deposit the granite stone alongside the stainless steel post.	T36N		R32E	R33E		1/4		S 7
T36N									
R32E	R33E								
	1/4								
	S 7								

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 36 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From this corner, an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, bears N. 76°08'00" E., 1.193 chs. dist., with plastic cap mkd. JOHN H. MILTON PLS 5271, alongside of which is laying a steel fence post, onto which a wood post, 1 1/2x3x24 ins. long, is fastened by wire, dimly mkd. with scribe marks 1/4 S. The wood post has been displaced from its original position by the prevailing westerly winds during times of standing water on the alkali flat and therefore this position is not utilized in this survey. N. 0°11'40" E., beginning new measurement. Over alkali flat.								
37.549	The closing cor. of secs. 1 and 12, T. 36 N., R. 32 E., hereinafter described.								
39.50	Jeep trail, 10 lks. wide, bears N. 80° E. and S. 80° W.								
39.981	The cor. of secs. 6 and 7 only, perpetuated by John H. Milton, III, Nevada Professional Land Surveyor No. 5271, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with plastic cap mkd. JOHN H. MILTON PLS 5271, with a steel fence post set alongside onto which a redwood post 2x3 1/2x21 ins. long is fastened by wire, no marks visible. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <table> <tr> <td>T36N</td><td>T36N</td></tr> <tr> <td>S 1</td><td>S 6</td></tr> <tr> <td></td><td>S 7</td></tr> <tr> <td>R32E</td><td>R32E</td></tr> </table> 2004 Deposit the iron rod inside and the original wood post alongside and reset the steel fence post alongside the stainless steel post.	T36N	T36N	S 1	S 6		S 7	R32E	R32E
T36N	T36N								
S 1	S 6								
	S 7								
R32E	R32E								
	N. 1°19'00" E., on the W. bdy. of sec. 6. Over alkali flat.								
15.70	Jeep trail, 10 lks. wide, bears N. 85° E. and S. 85° W.								
17.00	Ascend broken S. slope; enter mountainous land.								
35.00	Ravine, drains SE.								
37.578	The 1/4 sec. cor. of sec. 1 only, T. 36 N., R. 32 E., hereinafter described.								

011

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 36 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.510	Point for the 1/4 sec. cor. of sec. 6 only, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. T36N R32E R33E 1/4 S 6 2004 The cor. is located on a steep, rocky S. slope.
46.50	Ravine, drains SE.
55.324	The closing cor. of Tps. 36 and 37 N., Rs. 32 and 33 E., hereinafter described.
58.50	Top of ridge, bears NE. and SW.
63.50	Ravine, drains W.
79.020	The Maxson cor. of Tps. 36 and 37 N., Rs. 32 and 33 E., monumented with a volcanic stone, 12x8x6 ins., firmly set, with 6 notches on N. and 6 notches on S. edges, and in a mound of stone, 4 ft. diam., with a metal post laying alongside. This cor. will now refer to the NW. cor. of T. 36 N., R. 33 E., only. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T37N R33E S31 S 6 T36N R33E 2004 Deposit the original stone and set the metal post alongside the stainless steel post. The cor. is located on small rocky spur, slopes S. 20° E.

012

SURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 37 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the cor. of Tps. 37 N., Rs. 32 and 33 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. as described in the field notes of the independent resurvey of a portion of the south boundary of T. 37 N., R. 32 E., executed concurrently under this same group. EAST, on a portion of the S. bdy. of sec. 31. Over mountainous land. 22.311 Intersect the W. bdy. of sec. 6, T. 36 N., R. 33 E. Point for the closing cor. of Tps. 36 and 37 N., Rs. 32 and 33 E. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <table> <tr><td>T37N</td><td></td></tr> <tr><td>R33E</td><td>T36N</td></tr> <tr><td>S31</td><td>R33E</td></tr> <tr><td>CC</td><td></td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td>T36N</td><td></td></tr> <tr><td>R32E</td><td></td></tr> </table> 2004 From this corner, the NW. cor. of T. 36 N., R. 33 E., hereinbefore described, bears N. 1°19'00" E., 23.696 chs. dist. Land, mountainous. Soil, rocky. Vegetation, native grass and shadscale. SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA From the cor. of secs. 11, 12, 13 and 14, established by N.E. Potter in 1912, under Group No. 14, monumented with the rusted remains of an iron post, 2 ins. diam., filled with concrete, firmly set in the ground, 4 ins. below the surface, the brass cap is missing. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. <table> <tr><td>T36N</td><td>R32E</td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td>S14</td><td>S13</td></tr> </table> 2004	T37N		R33E	T36N	S31	R33E	CC		S 1	S 6	T36N		R32E		T36N	R32E	S11	S12	S14	S13
T37N																					
R33E	T36N																				
S31	R33E																				
CC																					
S 1	S 6																				
T36N																					
R32E																					
T36N	R32E																				
S11	S12																				
S14	S13																				

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Deposit the remains of the original iron post alongside the stainless steel post. N. 0°14'00" E., bet. secs. 11 and 12. Over alkali flat, through scattered vegetation.
40.000	Point for the 1/4 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E 1/4 S11 S12 2004 The cor. is located on alkali flat with scattered vegetation.
56.40	Jeep trail, 10 lks. wide, bears N. 80° W. and S. 80° E.
76.50	Jeep trail, 10 lks. wide, bears N. 25° E. and S. 25° W.
77.00	Leave alkali flat, begin ascent.
80.000	Point for the cor. of secs. 1, 2, 11 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd. T36N R32E S 2 S 1 S11 S12 2004 Land, level. Soil, alkali and silt. Vegetation, native grass, creosote, and shadscale. EAST, bet. secs. 1 and 12. Over nearly level land, with scattered vegetation.
1.90	Jeep trail, 10 lks. wide, bears N. 25° E. and S. 25° W.
2.00	Enter alkali flat.
40.000	Point for the 1/4 sec. cor. of secs. 1 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

014

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T36N R32E S 1 1/4 S12 2004 The cor. is located on alkali flat with scattered vegetation. 79.030 Intersect the W. bdy. of sec. 7, T. 36 N., R. 33 E. Point for the closing cor. of secs. 1 and 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <table border="0"> <tr> <td>T36N</td><td style="border-left: 1px solid black;">T36N</td></tr> <tr> <td>R32E</td><td style="border-left: 1px solid black;">R33E</td></tr> <tr> <td>S 1</td><td style="border-left: 1px solid black;">S 7</td></tr> <tr> <td>CC S12</td><td style="border-left: 1px solid black;"></td></tr> </table> 2004 From this corner, the cor. of secs. 6 and 7, T. 36 N., R. 33 E., hereinbefore described, bears N. 0°11'40" E., 2.432 chs. dist. Land, level. Soil, alkali and silt. Vegetation, native grass, creosote, and shadscale. The point for the 1/4 sec. cor. of sec. 12 only, T. 36 N., R. 32 E., is at midpoint in latitude on the E. bdy. of sec. 12. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <table border="0"> <tr> <td>T36N</td><td style="border-left: 1px solid black;"></td></tr> <tr> <td>R32E</td><td style="border-left: 1px solid black;">R33E</td></tr> <tr> <td>1/4</td><td style="border-left: 1px solid black;"></td></tr> <tr> <td>S12</td><td style="border-left: 1px solid black;"></td></tr> </table> 2004 The cor. is located on alkali flat with scattered creosote. From this point, the 1/4 sec. cor. of sec. 7 only, T. 36 N., R. 33 E., bears N. 0°14'10" E., 2.349 chs. dist., hereinbefore described. The point for the 1/4 sec. cor. of sec. 1 only, T. 36 N., R. 32 E., is at 40.000 chs. N. in latitude from the closing cor. of secs. 1 and 12, and on the E. bdy. of sec. 1.	T36N	T36N	R32E	R33E	S 1	S 7	CC S12		T36N		R32E	R33E	1/4		S12	
T36N	T36N																
R32E	R33E																
S 1	S 7																
CC S12																	
T36N																	
R32E	R33E																
1/4																	
S12																	

015

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T36N R32E R33E 1/4 S 1 2004 The cor. is located on a steep rocky S. slope. From this point, the 1/4 sec. cor. of sec. 6 only, T. 36 N., R. 33 E., bears N. 1°19'00" E., 1.932 chs. dist., hereinbefore described. From the cor. of secs. 1, 2, 11 and 12. N. 0°14'00" E., bet. secs. 1 and 2. Ascend, through scattered vegetation. 40.000 Point for the 1/4 sec. cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T36N R32E 1/4 S 2 S 1 2004 The cor. is located on a gradual SE. slope with scattered vegetation. 57.742 Intersect the S. bdy. of sec. 36, T. 37 N., R. 32 E. Point for the closing cor. of secs. 1 and 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd. T37N R32E S36 S 2 S 1 C C T36N 2004 The cor. is located on a steep W. slope with scattered vegetation.
--------	--

016

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From this corner, the 1/4 sec. cor. of sec. 36 only, on the S. bdy. of T. 37 N., R. 32 E., bears EAST, 17.751 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the field notes of the independent resurvey of a portion of the south boundary of T. 37 N., R. 32 E., executed concurrently under this same group. Land, southern slopes of Jungo Hills. Soil, alkali and silt. Vegetation, native grass, creosote, and shadscale. The point for the 1/4 sec. cor. of sec. 1 only, T. 36 N., R. 32 E., is at 40.000 chs. E. in departure from the closing cor. of secs. 1 and 2, and on the N. bdy. of sec. 1. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T37N R32E 1/4 S 1 T36N 2004 The cor. is located on a steep W. slope with scattered vegetation. From this point, the cor. of Tps. 37 N., Rs. 32 and 33 E., bears EAST, 17.751 chs. dist., hereinbefore described. From the cor. of secs. 22, 23, 26 and 27, established by N.E. Potter in 1912, under Group No. 14, monumented with the rusted remains of an iron post, 2 ins. diam., filled with concrete, firmly set in the ground, the brass cap is missing. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E <table border="1" style="margin: auto;"> <tr> <td>S22</td><td>S23</td></tr> <tr> <td>S27</td><td>S26</td></tr> </table> 2004 Deposit the remains of the original iron post and set a carsonite post, 6 ft. long, alongside the stainless steel post. N. 0°13'00" E., bet. secs. 22 and 23. Over alkali flat. 40.000 Point for the 1/4 sec. cor. of secs. 22 and 23.	S22	S23	S27	S26
S22	S23				
S27	S26				

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T36N R32E
1/4
S22 | S23

2004

The cor. is located on level land with scattered vegetation.

80.000

Point for the cor. of secs. 14, 15, 22 and 23.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T36N R32E
S15 | S14
S22 | S23

2004

The cor. is located on level land with sagebrush.

Land, level.

Soil, alkali and silt.

Vegetation, native grass, creosote, and shadscale.

From the cor. of secs. 13, 14, 23 and 24, monumented with the rusted remains of an iron post, 2 ins. diam., filled with concrete, firmly set in the ground, the top 18 ins. of the iron post is broken off and laying loosely on the ground, with brass cap mkd. as described in the field notes of T. 36 N., R. 32 E., executed under Group No. 14.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T36N R32E
S14 | S13
S23 | S24

2004

Deposit the remains of the original iron post alongside the stainless steel post.

The cor. is located on alkali flat.

S. 89°55'30" W., bet. secs. 14 and 23.

Over alkali flat.

39.940

Point for the 1/4 sec. cor. of secs. 14 and 23.

018

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T36N R32E S14 1/4 <u> </u> S23 2004
79.880	The cor. of secs. 14, 15, 22 and 23. Land, level. Soil, alkali and silt. Vegetation, native grass, creosote, and shadscale.
	N. 0°13'00" E., bet. secs. 14 and 15. Over alkali flat.
40.000	Point for the 1/4 sec. cor. of secs. 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T36N R32E 1/4 S15 S14 2004
	The cor. is located on alkali flat with scattered vegetation.
64.20	Jeep trail, 10 lks. wide, bears NW. and SE.
80.000	Point for the cor. of secs. 10, 11, 14 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T36N R32E S10 S11 <u> </u> S15 S14 2004
	Cor. is located on level land with scattered vegetation. Land, level. Soil, alkali and silt. Vegetation, native grass, creosote, and shadscale.
	From the cor. of secs. 11, 12, 13 and 14.
	S. 89°55'50" W., bet. secs. 11 and 14.
	Over alkali flat.

019

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.947	Point for the 1/4 sec. cor. of secs. 11 and 14. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E S11 1/4 <u> </u> S14 2004 The cor. is located on alkali flat.
79.894	The cor. of secs. 10, 11, 14 and 15. Land, level. Soil, alkali and silt. Vegetation, native grass and shadscale. N. 0°13'00" E., bet. secs. 10 and 11. Over alkali flat.
21.60	Jeep trail, 10 lks. wide, bears NE. and SW.
40.000	Point for the 1/4 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E 1/4 S10 S11 2004 The cor. is located on level land with scattered vegetation.
80.000	Point for the cor. of secs. 2, 3, 10 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E S 3 S 2 S10 S11 2004 The cor. is located on level land with scattered vegetation. Land, level. Soil, alkali and silt. Vegetation, native grass and shadscale.

020

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the cor. of secs. 1, 2, 11 and 12. S. 89°55'50" W., bet. secs. 2 and 11. Over isolated rocky hill.
24.50	Top of ascent, slopes NE.
39.950	Point for the 1/4 sec. cor. of secs. 2 and 11. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. T36N R32E S 2 1/4 $\frac{\quad}{S11}$ 2004 The cor. is located on a rocky NW. slope with scattered vegetation.
79.900	The cor. of secs. 2, 3, 10 and 11. Land, hills, nearly level. Soil, alkali and silt. Vegetation, native grass and shadscale. N. 0°13'00" E., bet. secs. 2 and 3. Over nearly level land.
40.000	Point for the 1/4 sec. cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. T36N R32E 1/4 S 3 S 2 2004 The cor. is located on a gentle SW. slope with scattered vegetation.
57.840	Intersect the S. bdy. of sec. 35, T. 37 N., R. 32 E. Point for the closing cor. of secs. 2 and 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

021

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T37N R32E S35 S 3 S 2 C C T36N 2004 The cor. is located on a gentle SW. slope with scattered vegetation. From this corner, the 1/4 sec. cor. of sec. 35 only, on the S. bdy. of T. 37 N., R. 32 E., bears EAST, 17.653 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. as described in the field notes of the independent resurvey of a portion of the south boundary of T. 37 N., R. 32 E., executed concurrently under this same group. Land, nearly level. Soil, alkali and silt. Vegetation, native grass and shadscale. The point for the 1/4 sec. cor. of sec. 2 only, T. 36 N., R. 32 E., is at midpoint on the N. bdy. of sec. 2. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. T37N R32E 1/4 S 2 T36N 2004 The cor. is located on a gradual SW. slope with scattered vegetation. From this point, the cor. of secs. 35 and 36 only, T. 37 N., R. 32 E., bears EAST, 17.702 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the field notes of the independent resurvey of a portion of the south boundary of T. 37 N., R. 32 E., executed concurrently under this same group. From the cor. of secs. 33 and 34 only, on the S. bdy. of the Tp., hereinbefore described. N. 0°12'20" E., bet. secs. 33 and 34. Over mountainous land. 40.322 Point for the 1/4 sec. cor. of secs. 33 and 34, determined at 40.000 chs. in latitude from the cor. of secs. 27, 28, 33 and 34, hereinafter described.
--------	---

022

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E 1/4 S33 S34 2001 Set a carsonite post, 6 ft. long, alongside the stainless steel post. Descend over a NE. slope. 80.322 Intersect the sectional correction line. Point for the cor. of secs. 27, 28, 33 and 34, established WEST from the cor. of secs. 26, 27, 34 and 35, hereinafter described. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E S28 S27 S33 S34 2001 Set a carsonite post, 6 ft. long, alongside the stainless steel post. Land, mountainous. Soil, rocky. Vegetation, native grass and shadscale. From the cor. of secs. 26, 27, 34 and 35, established by N.E. Potter in 1912, under Group No. 14, monumented with the rusted remains of an iron post, 2 ins. diam., filled with concrete, firmly set in the ground, the brass cap is missing. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E S27 S26 S34 S35 2001 Deposit the remains of the original iron post and set a carsonite post, 6 ft. long, alongside the stainless steel post. WEST, bet. secs. 27 and 34, on a sectional correction line.
--------	--

023

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across alkali flat.
34.40	Graveled road, 20 lks. wide, bears NNW and SSE; enter gently rolling land.
40.046	Point for the 1/4 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E S27 1/4 <u> </u> S34 2001 Set a carsonite post, 6 ft. long, alongside the stainless steel post.
80.092	The cor. of secs. 27, 28, 33 and 34. Land, level, gently rolling. Soil, sandy, alkali, silt. Vegetation, grease wood, native grass, and shadscale. N. 0°12'20" E., bet. secs. 27 and 28. Over gently rolling land.
40.000	Point for the 1/4 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E 1/4 S28 S27 2001 Set a carsonite post, 6 ft. long, alongside the stainless steel post.
80.000	Point for the cor. of secs. 21, 22, 27 and 28. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E S21 S22 S28 S27 2001

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T: 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a carsonite post, 6 ft. long, alongside the stainless steel post. Land, gently rolling. Soil, sandy, alkali and silt. Vegetation, native grass and shadscale. From the cor. of secs. 22, 23, 26 and 27. N. 89°59'40" W., bet. secs. 22 and 27. Across alkali flat. 40.118 Point for the 1/4 sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E S22 1/4 <u> </u> S27 2001 Set a carsonite post, 6 ft. long, alongside the stainless steel post. From this corner, a windmill bears S. 78°29' W., 20.02 chs. dist. 52.20 Graveled road, 20 lks. wide, bears NNW and SSE. 80.236 The cor. of secs. 21, 22, 27 and 28. Land, level. Soil, sandy, alkali, and silt. Vegetation, greasewood, native grass, and shadscale. N. 0°12'20" E., bet. secs. 21 and 22. Over level land. 40.000 Point for the 1/4 sec. cor. of secs. 21 and 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E 1/4 S21 S22 2004 The cor. is located on level land with scattered vegetation.
--------	---

025

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.000	Point for the cor. of secs. 15, 16, 21 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T36N R32E S16 S15 S21 S22
	2004
	The cor. is located on level land with scattered vegetation.
	Land, level. Soil, alkali and silt. Vegetation, native grass and shadscale.
	From the cor. of secs. 14, 15, 22 and 23.
	N. 89°59'40" W., bet. secs. 15 and 22.
	Over alkali flat.
40.116	Point for the 1/4 sec. cor. of secs. 15 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T36N R32E S15 1/4 ——— S22
	2004
	The cor. is located on alkali flat with scattered vegetation.
58.60	Jeep trail, bears N. 15° E. and S. 15° W.
69.60	Graveled road, 20 lks. wide, bears NNW and SSE.
80.232	The cor. of secs. 15, 16, 21 and 22.
	Land, level. Soil, alkali and silt. Vegetation, native grass and shadscale.
	N. 0°12'20" E., bet. secs. 15 and 16.
	Over nearly level land.
40.000	Point for the 1/4 sec. cor. of secs. 15 and 16.

026

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. T36N R32E 1/4 S16 S15 2004
46.00	Graveled road, 20 lks. wide, bears NNW and SSE.
67.90	Jeep trail, bears N. 80° E. and S. 80° W.
80.000	Point for the cor. of secs. 9, 10, 15 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E S 9 S10 S16 S15 2004 The cor. is located on level land with scattered vegetation. Land, nearly level. Soil, alkali and silt. Vegetation, native grass and shadscale. From the cor. of secs. 10, 11, 14 and 15. N. 89°59'40" W., bet. secs. 10 and 15. Over alkali flat.
21.00	Jeep trail, bears N. 60° W. and S. 60° E.
32.00	Jeep trail, bears N. 60° E. and S. 60° W.
40.116	Point for the 1/4 sec. cor. of secs. 10 and 15. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E S10 1/4 — S15 2004 The cor. is located on level land with scattered vegetation.

027

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.232	The cor. of secs. 9, 10, 15 and 16. Land, level. Soil, alkali and silt. Vegetation, native grass and shadscale. N. 0°12'20" E., bet. secs. 9 and 10. Over nearly level land.
40.000	Point for the 1/4 sec. cor. of secs. 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E 1/4 S 9 S10 2004 The cor. is located on level land with scattered vegetation.
44.50	Jeep trail, bears N. 60° W. and S. 60° E.
67.00	Ascend rolling hills.
80.000	Point for the cor. of secs. 3, 4, 9 and 10. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T36N R32E S 4 S 3 S 9 S10 2004 The cor. is located on a steep rocky E. slope, in shale. Land, level, rolling. Soil, alkali and silt to rocky. Vegetation, native grass and shadscale. From the cor. of secs. 2, 3, 10 and 11. N. 89°59'40" W., bet. secs. 3 and 10. Over level land.
40.116	Point for the 1/4 sec. cor. of secs. 3 and 10.

028

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E S 3 1/4 <u> </u> S10 2004 The cor. is located on level land with scattered vegetation.
52.00	Ascend rolling hills.
80.232	The cor. of secs. 3, 4, 9 and 10. Land, level, rolling. Soil, alkali and silt. Vegetation, native grass and shadscale. N. 0°12'20" E., bet. secs. 3 and 4. Over rolling land.
20.00	Enter nearly level land.
40.000	Point for the 1/4 sec. cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E 1/4 S 4 S 3 2004 The cor. is located on level land with scattered vegetation.
57.830	Intersect the S. bdy. of sec. 34, T. 37 N., R. 32 E. Point for the closing cor. of secs. 3 and 4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T37N R32E S34 <u> </u> S 4 S 3 C C T36N 2004 The cor. is located on level land with scattered vegetation.

CHAINS	From this corner, the 1/4 sec. cor. of sec. 34 only, on the S. bdy. of T. 37 N., R. 32 E., bears EAST, 17.887 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the field notes of the independent resurvey of a portion of the south boundary of T. 37 N., R. 32 E., executed concurrently under this same group. Land, rolling, level. Soil, alkali to silt. Vegetation, native grass and shadscale.
	The point for the 1/4 sec. cor. of sec. 3 only, T. 36 N., R. 32 E., is at midpoint on the N. bdy. of sec. 3. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. T37N R32E 1/4 S 3 T36N 2004
	The cor. is located on a gradual SW. slope with scattered vegetation. From this point, the cor. of secs. 34 and 35 only, T. 37 N., R. 32 E., bears EAST, 17.770 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the the ground, and in a collar of stone, with brass cap mkd. as described in the field notes of the independent resurvey of a portion of the south boundary of T. 37 N., R. 32 E., executed concurrently under this same group.
	From the cor. of secs. 32 and 33 only, on the S. bdy. of the Tp., hereinbefore described. N. 0°11'40" E., bet. secs. 32 and 33. Over mountainous land.
40.850	Point for the 1/4 sec. cor. of secs. 32 and 33, at 40.000 chs. in latitude from the cor. of secs. 28, 29, 32 and 33, hereinafter described. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

030

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T36N R32E 1/4 S32 S33 2001 Set a carsonite post, 6 ft. long, alongside the stainless steel post. 80.850 Intersect the sectional correction line. Point for the cor. of secs. 28, 29, 32 and 33, established WEST from the cor. of secs. 27, 28, 33 and 34. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E S29 S28 S32 S33 2001 Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor. Land, mountainous. Soil, rocky. Vegetation, native grass and shadscale. From the cor. of secs. 27, 28, 33 and 34. WEST, bet. secs. 28 and 33, on a sectional correction line. Ascend over a NE. slope. 39.998 Point for the 1/4 sec. cor. of secs. 28 and 33. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T36N R32E S28 1/4 ——— S33 2001 Set a carsonite post, 6 ft. long, alongside the stainless steel post. 50.00 Enter mountainous land. 79.996 The cor. of secs. 28, 29, 32 and 33. Land, mountainous. Soil, rocky. Vegetation, native grasses and shadscale.
--------	--

031

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°11'40" E., bet. secs. 28 and 29.
	Over mountainous land.
13.00	Top of ridge, bears ENE and WSW.
40.000	Point for the 1/4 sec. cor. of secs. 28 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T36N R32E 1/4 S29 S28 2001
	The cor. is located on a spur, slopes ENE.
72.00	Ravine, drains ESE.
80.000	Point for the cor. of secs. 20, 21, 28 and 29.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T36N R32E S20 S21 S29 S28 2001
	Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.
	Land, mountainous.
	Soil, rocky.
	Vegetation, native grass and shadscale.
	From the cor. of secs. 21, 22, 27 and 28.
	WEST, bet. secs. 21 and 28.
	Over gently rolling land.
39.997	Point for the 1/4 sec. cor. of secs. 21 and 28.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T36N R32E S21 1/4 — S28 2001

032

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 32 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a carsonite post, 6 ft. long, alongside the stainless steel post.
55.00	Enter mountainous land.
69.00	Top of ridge, bears N. and S.
79.994	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling, mountainous. Soil, rocky. Vegetation, native grass and shadscale.
GENERAL DESCRIPTION	
The lands included in the survey are located in the south-central portion of Humboldt County, Nevada, about 40 miles westerly of the City of Winnemucca, Nevada. Access is gained by way of Nevada State Route No. 49 (Jungo Road). The majority of the township can be accessed from a rural road, extending northerly from the Jungo railroad siding on Jungo Road.	
The lowest portion of the survey area is at 4160 feet above sea level in the southwestern portion of Desert Valley. The southwestern portion of the area surveyed rises to 5350 feet above sea level. Jungo Hills borders the surveyed area on the north.	
Presently the lands are used for cattle grazing and off-road vehicle recreation. Limited mining activity has occurred in past years in the Jungo Hills. Vegetation in the alkali soil consists of native grass, shadscale and other vegetation.	

033UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFIELD ASSISTANTS

Brian L. Mikkelsen	Cadastral Surveyor
Donald R. Parke	Cadastral Surveyor
Jonathan H. Miller II	Land Surveyor-in-Training (Student)
Matthew D. Norman	Land Surveyor-in-Training (Student)
David J. Roderiques	Land Surveyor-in-Training (Student)
Ronald M. Schulz	Land Surveyor-in-Training (Student)
Clay W. Morrow	Surveying Technician
Wayne E. Chubb	Survey Aid
Jeremiah J. Lee	Survey Aid

034

CERTIFICATE OF SURVEY

We, Ronald E. Williams and David L. Dukleth, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 7th day of August, 2001, and Supplemental Special Instructions bearing date of the 16th day of July, 2004, we have dependently resurveyed the Seventh Standard Parallel North, through a portion of Range 32 East; and dependently resurveyed a portion of the west boundary of Township 36 North, Range 33 East; and surveyed a portion of the south boundary of Township 37 North, Range 33 East; and surveyed a portion of the subdivisional lines of Township 36 North, Range 32 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special and supplemental special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 27, 2005

(Date)

David D. Morlan

/ For Ronald E. Williams
(Cadastral Surveyor)

September 19, 2005

(Date)

David L. Dukleth

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Seventh Standard Parallel North, through a portion of Range 32 East; and the dependent resurvey of a portion of the west boundary of Township 36 North, Range 33 East; and the survey of a portion of the south boundary of Township 37 North, Range 33 East; and the survey of a portion of the subdivisional lines of Township 36 North, Range 32 East, Mount Diablo Meridian, Nevada, executed by Ronald E. Williams and David L. Dukleth, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

September 27, 2005

(Date)

David D. Morlan

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 36 N., R. 32 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~