

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

CORRECTIVE DEPENDENT RESURVEY

OF

A PORTION OF THE EAST BOUNDARY

OF

TOWNSHIP 37 NORTH, RANGE 62 EAST;

AND

A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 37 NORTH, RANGE 63 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Ronald E. Williams, Cadastral Surveyor

Under Special Instructions dated May 29, 1998,

and approved May 29, 1998,

which provided for the surveys included under Group No. 773,

and Assignment Instructions dated May 29, 1998.

Survey commenced June 2, 1998

Survey completed June 3, 1998

INDEX DIAGRAM

TOWNSHIP 37 NORTH, RANGE 63 EAST

	6	5	4	3	2
					1
4	9	7	8	9	10
—		8		11	12
3	9	18	7	17	16
—		6		15	14
2	7	19	5	20	21
—		5	5	22	23
	30	4	29	28	27
				26	25
	31	32	33	34	35
					36

TOWNSHIP 37 NORTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the corrective dependent resurvey of a portion of the east boundary of Township 37 North, Range 62 East; and a portion of the subdivisional lines of Township 37 North, Range 63 East, Mount Diablo Meridian, Nevada.

The north four miles of the west boundary were surveyed by U.S. Deputy Surveyors C.C. Tracy in 1868 under Contract No. 21. The southwest corner of the township was established by U.S. Deputy Surveyors A.J. Hatch and J.H. Eaton in 1870 under Contract No. 40. The east boundary was surveyed by U.S. Deputy Surveyors D.H. Barker and J.H. Eaton in 1879 under Contract No. 92. The north and south boundaries, the south two miles of the west boundary, and the subdivisional lines were surveyed by U.S. Deputy Surveyor T.K. Stewart in 1883 under Contract No. 168. The south four miles of the west boundary were dependently resurveyed by U.S. Surveyor N.E. Potter in 1915 under Group No. 29. The east boundary was dependently resurveyed by Cadastral Surveyors N.R. Forsyth and M.R. Collie in 1976 under Group No. 533. The west, south and north boundaries, and the subdivisional lines were dependently resurveyed by Cadastral Surveyors M.R. Collie and J.R. Munson in 1976-1977 under Group No. 533.

Registered Land Surveyor Robert E. Morley, in a letter dated July 18, 1994, reported that the reestablished corners of sections 19, 20, 29 and 30 and the $\frac{1}{4}$ section corner of sections 29 and 30, T. 37 N., R. 63 E., as being monumented in different locations than the proportioned positions described in the 1976-1977 resurvey field notes and plat approved April 1, 1980. This corrective dependent resurvey verified Mr. Morley's findings, as well as discovering additional errors during investigations conducted in 1996 and 1998, and reflects the changes.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 29, 1998.

The direction of the lines of this survey was determined by use of Global Positioning System satellite data, using the real-time kinematic survey process, and refer to the true meridian.

The geographic position for the corner of sections 29, 30, 31 and 32, is at Lat. 41°03'12.217" N. and Long. 114°53'18.129" W.- NAD 83 (1994) as determined by survey-grade GPS receivers in 1998, from NGS stations "CEDAR" and "KAW", located in sec. 10, T. 37 N., R. 63 E., and sec. 12, T. 37 N., R. 62 E., respectively.

TOWNSHIP 37 NORTH, RANGE 63 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The mean magnetic declination is $17\frac{1}{2}^{\circ}$ E., as shown on U.S.G.S. quadrangle map "WELLS, NEV." dated 1968.

CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE EAST BOUNDARY,
T. 37 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
C.C. Tracy, U.S. Deputy Surveyor, in 1868,
the Survey Executed by
T.K. Stewart, U.S. Deputy Surveyor, in 1883,
the Resurvey Executed by
N.E. Potter, U.S. Surveyor, in 1915,
and Correction of the Resurvey Executed by
M.R. Collie and J.R. Munson, Cadastral Surveyors, in 1976-1977

From the cor. of secs. 24 and 25, monumented with an iron post, 3 ins. diam., firmly set, showing 11 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 63 E., executed under Group No. 533.

From this corner, the closing cor. of secs. 19 and 30, T. 37 N., R. 63 E., bears S. $0^{\circ}05'$ W., 1.95 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 5 ins. above ground, with brass cap mkd.

```

      T37N
    R62E R63E
      |  S19
    S24 |-----CC
      |  S30
  
```

1977

N. $0^{\circ}04'$ E., on the E. bdy. of sec. 24.

Over mountainous land, covered with scattered juniper, pinon pine, sagebrush, cacti and native grass.

37.50 The $\frac{1}{4}$ sec. cor. of sec. 19, T. 37 N., R. 63 E., hereinafter described.

39.97 The $\frac{1}{4}$ sec. cor. of sec. 24, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 63 E., executed under Group No. 533, from which the original bearing tree

A pinon pine, 8 ins. diam., bears S. 11° W., 24 lks. dist., mkd. $\frac{1}{4}$ S 24 BT, on open blaze.

N. $0^{\circ}06'$ E., beginning new measurement.

Over rolling land.

36.98 The closing cor. of secs. 18 and 19, T. 37 N., R. 63 E., hereinafter described.

CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE EAST BOUNDARY,
T. 37 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 39.98</p>	<p>The cor. of secs. 13 and 24, monumented with an iron post, 3 ins. diam., firmly set, showing 9 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 63 E., executed under Group No. 533, from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. $24\frac{1}{4}^{\circ}$ W., 34 lks. dist., with illegible scribe marks visible on open blaze.</p> <p style="padding-left: 40px;">A pinon pine, 11 ins. diam., bears N. 87° W., 68 lks. dist., with illegible scribe marks visible on open blaze.</p> <hr/> <p>N. $0^{\circ}04'$ W., on the E. bdy. of sec. 13.</p> <p>Over rolling land, covered with medium sagebrush and scattered native grass.</p> <p>4.49 The angle point on the E. bdy. of sec. 13, monumented with an iron post, 3 ins. diam., firmly set, showing 10 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 62 E., executed under Group No. 29.</p> <hr/> <p>N. $0^{\circ}16'$ E., beginning new measurement.</p> <p>32.535 The $\frac{1}{4}$ sec. cor. of sec. 18, T. 37 N., R. 63 E., hereinafter described.</p> <p>40.14 Point for the $\frac{1}{4}$ sec. cor. of sec. 13, at proportionate distance by irregular boundary adjustment; there is no remaining evidence of the original corner found and perpetuated in the 1915 resurvey.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T37N R62E R63E $\frac{1}{4}$ S13 </p> <p>1998</p> </div> <p>Set a steel fence post, 6 ft. long, alongside the stainless steel post.</p> <p>From this corner, the $\frac{1}{4}$ sec. cor. of sec. 13, established in the 1976-1977 resurvey, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, bears N. $0^{\circ}15'$ E., 8.421 chs. dist. This corner now becomes an amended monument, obliterate the marks except for the date on the brass cap and add the marks AM 1998.</p> <hr/> <p>N. $0^{\circ}14'$ E., beginning new measurement.</p> <p>Over rolling land.</p> <p>32.42 The closing cor. of secs. 7 and 18, T. 37 N., R. 63 E., hereinafter described.</p>
-------------------------	--

168

CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE EAST BOUNDARY,
T. 37 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.28</p>	<p>The cor. of secs. 12 and 13, monumented with an iron post, 3 ins. diam., firmly set, showing 8 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 63 E., executed under Group No. 533.</p>
	<p>N. 0°16' E., on the E. bdy. of sec. 12.</p> <p>Over gently rolling land, covered with medium sagebrush, scattered cacti and native grass.</p>
<p>32.42</p>	<p>The $\frac{1}{4}$ sec. cor. of sec. 7, T. 37 N., R. 63 E., hereinafter described.</p>
<p>40.28</p>	<p>The $\frac{1}{4}$ sec. cor. of sec. 12, monumented with an iron post, 2$\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 39 N., R. 63 E., executed under Group No. 533.</p> <p>From this corner, the closing cor. of secs. 6 and 7, T. 37 N., R. 63 E., monumented with an iron post, 2$\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 63 E., executed under Group No. 533, bears N. 0°16' E., 32.42 chs. dist.</p>
<p style="text-align: center;">CORRECTIVE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 37 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p style="text-align: center;">Reestablishment of the Survey Executed by T.K. Stewart, U.S. Deputy Surveyor, in 1883, and Correction of the Resurvey Executed by M.R. Collie and J.R. Munson, Cadastral Surveyors, in 1976-1977</p>	
	<p>From the cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2$\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 63 E., executed under Group No. 533.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over mountainous land, covered with medium pinon pine, juniper, scattered mountain mahogany, sagebrush, cacti and native grass.</p>
<p>40.01</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T37N R63E</p> <p>$\frac{1}{4}$</p> <p>S30 S29</p> <p>1998</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>

CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
	<p>From this corner, the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, established in the 1976-1977 resurvey, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, bears N. $88^{\circ}50'$ E., 2.096 chs. dist. This corner now becomes an amended monument, obliterate the marks except for the date on the brass cap and add the marks AM 1998.</p>						
80.02	<p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance, falls on quartz outcropping; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, $3\frac{1}{4}$ ins. diam., $3\frac{1}{2}$-in. stem, in drill hole, with top mkd.</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td>T37N</td><td>R63E</td></tr> <tr> <td>S19</td><td>S20</td></tr> <tr> <td>S30</td><td>S29</td></tr> </table> <p>1998</p> </div> <p>From this corner, the cor. of secs. 19, 20, 29 and 30, established in the 1976-1977 resurvey, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 6 ins. above ground, bears N. $45^{\circ}01'$ E., 3.999 chs. dist. This corner now becomes an amended monument, obliterate the marks except for the date on the brass cap and add the marks AM 1998.</p>	T37N	R63E	S19	S20	S30	S29
T37N	R63E						
S19	S20						
S30	S29						
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented with an iron post, $2\frac{1}{2}$ ins. diam, firmly set, showing 3 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 63 E., executed under Group No. 533.</p> <p>N. $89^{\circ}43'$ W., bet. secs. 20 and 29.</p> <p>Over mountainous land, covered with medium pinon pine, juniper, sagebrush and scattered native grass.</p>						
40.09	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>S. $89^{\circ}16'$ W., bet. secs. 19 and 30.</p> <p>Over mountainous land, covered with medium pinon pine, juniper, scattered mountain mahogany, sagebrush and native grass.</p>						
40.16	<p>The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 63 E., executed under Group No. 533.</p> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. $0^{\circ}02'$ E., bet. secs. 19 and 20.</p> <p>Over mountainous land, covered with medium pinon pine, juniper, scattered mountain mahogany, sagebrush and native grass.</p>						

170

CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 40.01</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T37N R63E $\frac{1}{4}$ S19 S20 1998</p> <p>Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.</p> <p>From this corner, the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, established in the 1976-1977 resurvey, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, bears N. $0^{\circ}12'$ W., 1.030 chs. dist. This corner now becomes an amended monument, obliterate the marks except for the date on the brass cap and add the marks AM 1998.</p>
<p>80.02</p>	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 63 E., executed under Group No. 533.</p>
	<p>S. $88^{\circ}25'$ W., bet. secs. 18 and 19.</p> <p>Over mountainous land, covered with medium pinon pine, juniper, scattered sagebrush and native grass.</p>
<p>40.17</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T37N R63E S18 $\frac{1}{4}$ ——— S19</p>
	<p style="text-align: center;">1998</p>
	<p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor.</p>
	<p>From this corner, the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, established in the 1976-1977 resurvey, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 6 ins. above ground, bears S. $17^{\circ}00'$ E., 0.054 chs. dist. This corner now becomes an amended monument, obliterate the marks except for the date on the brass cap and add the marks AM 1998.</p>
<p>79.07</p>	<p>Intersect the E. bdy. of sec. 24, T. 37 N., R. 62 E.</p> <p>Point for the closing cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

171

CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="873 260 1058 392" data-label="Text"> <p style="text-align: center;">T37N R62E R63E S24 S18 S19 — CC</p> </div> <div data-bbox="917 417 987 443" data-label="Text"> <p style="text-align: center;">1998</p> </div> <div data-bbox="443 468 1417 501" data-label="Text"> <p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, E. of cor.</p> </div> <div data-bbox="443 520 1466 579" data-label="Text"> <p>From this corner, the cor. of secs. 13 and 24, T. 37 N., R. 62 E., hereinbefore described, bears N. $0^{\circ}06'$ E., 3.00 chs. dist.</p> </div> <div data-bbox="443 598 1471 764" data-label="Text"> <p>From this same corner, the closing cor. of secs. 18 and 19, established in the 1976-1977 resurvey, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, bears S. $1^{\circ}42'$ E., 0.134 chs. dist. This corner now becomes an amended monument, obliterate the marks except for the date on the brass cap and add the marks AM 1998.</p> </div> <hr/> <div data-bbox="443 810 1471 869" data-label="Text"> <p>The point for the W $\frac{1}{4}$ sec. cor. of sec. 19, on the E. bdy. of sec. 24, T. 37 N., R. 62 E., and at midpoint between the closing cors.</p> </div> <div data-bbox="443 888 1471 949" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="878 972 1032 1075" data-label="Text"> <p style="text-align: center;">T37N R62E R63E $\frac{1}{4}$ S19</p> </div> <div data-bbox="920 1100 993 1125" data-label="Text"> <p style="text-align: center;">1998</p> </div> <div data-bbox="443 1150 1425 1186" data-label="Text"> <p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, E. of cor.</p> </div> <div data-bbox="443 1203 1474 1289" data-label="Text"> <p>From this corner, the E $\frac{1}{4}$ sec. cor. of sec. 24, T. 37 N., R. 62 E., hereinbefore described, bears N. $0^{\circ}04'$ E., 2.47 chs. dist.</p> </div> <div data-bbox="443 1310 1481 1476" data-label="Text"> <p>From this same corner, the W $\frac{1}{4}$ sec. cor. of sec. 19, established in the 1976-1977 resurvey, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, bears S. $0^{\circ}57'$ E., 0.067 chs. dist. This corner now becomes an amended monument, obliterate the marks except for the date on the brass cap and add the marks AM 1998.</p> </div> <hr/> <div data-bbox="443 1524 1104 1556" data-label="Text"> <p>From the cor. of secs. 17, 18, 19 and 20.</p> </div> <div data-bbox="443 1577 993 1608" data-label="Text"> <p>N. $0^{\circ}25'$ E., bet. secs. 17 and 18.</p> </div> <div data-bbox="443 1627 1477 1688" data-label="Text"> <p>Over mountainous land, covered with medium pinon pine, juniper, scattered sagebrush and native grass.</p> </div> <div data-bbox="293 1713 381 1743" data-label="Text"> <p>40.04</p> </div> <div data-bbox="443 1705 1482 1770" data-label="Text"> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> </div> <div data-bbox="443 1785 1481 1848" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div>
--------	---

172

CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T37N R63E $\frac{1}{4}$ S18 S17 1998</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>From this corner, the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, established in the 1976-1977 resurvey, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a collar of stone, bears N. $0^{\circ}44'$ W., 0.500 chs. dist. This corner now becomes an amended monument, obliterate the marks except for the date on the brass cap and add the marks AM 1998.</p>
80.08	<p>The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 63 E., executed under Group No. 533.</p> <hr/> <p>S. $88^{\circ}23'$ W., bet. secs. 7 and 18.</p> <p>Over rolling land, covered with medium sagebrush, scattered pinon pine and native grass.</p>
40.20	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T37N R63E S 7 $\frac{1}{4}$ ——— S18 1998</p> <p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor.</p> <p>From this corner, the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, established in the 1976-1977 resurvey, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 8 ins. above ground, bears N. $36^{\circ}57'$ E., 0.029 chs. dist. This corner now becomes an amended monument, obliterate the marks except for the date on the brass cap and add the marks AM 1998.</p>
79.32	<p>Intersect the E. bdy. of sec. 13, T. 37 N., R. 62 E.</p> <p>Point for the closing cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

173

CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T37N
R62E R63E
S 7
S13 — CC
S18

1998

Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, E. of cor.

From this corner, the cor. of secs. 12 and 13, T. 37 N., R. 62 E., hereinbefore described, bears N. $0^{\circ}14'$ E., 7.86 chs. dist.

From this same corner, the closing cor. of secs. 7 and 18, established in the 1976-1977 resurvey, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 6 ins. above ground, bears N. $1^{\circ}10'$ W., 0.044 chs. dist. This corner now becomes an amended monument, obliterate the marks except for the date on the brass cap and add the marks AM 1998.

The point for the W $\frac{1}{4}$ sec. cor. of sec. 18, on the E. bdy. of sec. 13, T. 37 N., R. 62 E., and at midpoint between the closing cors.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T37N
R62E R63E
S $\frac{1}{4}$
S18

1998

Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, E. of cor.

From this corner, the E $\frac{1}{4}$ sec. cor. of sec. 13, T. 37 N., R. 62 E., hereinbefore described, bears N. $0^{\circ}16'$ E., 7.605 chs. dist.

From this same corner, the W $\frac{1}{4}$ sec. cor. of sec. 18, established in the 1976-1977 resurvey, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, bears N. $0^{\circ}17'$ E., 5.596 chs. dist. This corner now becomes an amended monument, obliterate the marks except for the date on the brass cap and add the marks AM 1998.

The point for the W $\frac{1}{4}$ sec. cor. of sec. 7, on the E. bdy. of sec. 12, T. 37 N., R. 62 E., and at midpoint between the closing cors.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

174

CORRECTIVE DEPENDENT RESURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 37 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T37N
R62E R63E
|¹/₄
S 7

1998

Raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, E. of cor.

From this corner, the E $\frac{1}{4}$ sec. cor. of sec. 12, T. 37 N., R. 62 E., hereinbefore described, bears N. $0^{\circ}16'$ E., 7.86 chs. dist.

From this same corner, the W $\frac{1}{4}$ sec. cor. of sec. 7, established in the 1976-1977 resurvey, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 4 ins. above ground, bears N. $2^{\circ}16'$ W., 0.023 chs. dist. This corner now becomes an amended monument, obliterate the marks except for the date on the brass cap and add the marks AM 1998.

GENERAL DESCRIPTION

The land within the confines of this corrective resurvey in Township 37 North, Range 63 East, is located in the Wood Hills area a few miles south and east of Wells, Nevada, varying in elevation from about 5800 to 7000 ft. above sea level, and is rolling to mountainous land. The soil consists of sandy clay loam to rocky in the mountains with timber of mountain mahogany, pinon pine and juniper and vegetation of sagebrush, cacti and native grass.

There are ravines and washes scattered throughout the area. Access is by numerous trail roads running principally alongside the drainages. The principal users of the area are prospectors, cattle grazers and hunters. There is a ranch with various structures located in the southeast quarter of section 30.

There are prospect holes in the area of the corners of sections 19, 20, 29 and 30 and sections 7, 8, 17 and 18.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Clay W. Morrow Surveying Technician

CERTIFICATE OF SURVEY

I, Ronald E. Williams, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 29th day of May, 1998, I have correctively dependently resurveyed a portion of the east boundary of Township 37 North, Range 62 East; and a portion of the subdivisional lines of Township 37 North, Range 63 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 25, 1999
(Date)

Ronald E. Williams
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the corrective dependent resurvey of a portion of the east boundary of Township 37 North, Range 62 East; and a portion of the subdivisional lines of Township 37 North, Range 63 East, Mount Diablo Meridian, Nevada, executed by Ronald E. Williams, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

February 2, 1999
(Date)

David J. Clark
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 37 N., R. 63 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief Cadastral Surveyor, Nevada)~~