

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SOUTH BOUNDARY OF TOWNSHIP 40 NORTH, RANGE 31 EAST;

AND

THE DEPENDENT RESURVEY

OF THE

EAST BOUNDARY,

A PORTION OF THE NORTH BOUNDARY

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF CERTAIN SECTIONS,

TOWNSHIP 39 NORTH, RANGE 31 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Don R. Aschenbach, Cadastral Surveyor


Under Special Instructions dated July 17, 2002, and approved July 17, 2002,  
and Supplemental Special Instructions dated November 12, 2002,  
and approved November 12, 2002,  
which provided for the surveys included under Group No. 807,  
and Assignment Instructions dated July 17, 2002.

Survey commenced July 24, 2002

Survey completed August 26, 2004

INDEX DIAGRAM

TOWNSHIP 39 NORTH, RANGE 31 EAST, MOUNT DIABLO MERIDIAN, NEVADA



						20	10
6	5	4	3	2		1	
						20	
7	8	9	10	11	19	12	9
				28		18	
18	17	16	15	27	14	17	13
				26		17	
19	20	21	22	25	23	16	24
				24		15	
30	29	28	27	23	26	14	25
			30		22		13
31	32	33	29	34	21	35	12
							36
							4

Subdivision of Sec. 1...p. 30-31  
 Subdivision of Sec. 11..pp. 31-33  
 Subdivision of Sec. 13..pp. 33-34  
 Subdivision of Sec. 14..p. 34  
 Subdivision of Sec. 23..pp. 34-37

Subdivision of Sec. 24..p. 37  
 Subdivision of Sec. 25..p. 37  
 Subdivision of Sec. 26..pp. 37-39  
 Subdivision of Sec. 36..pp. 39-42

## TOWNSHIP 39 NORTH, RANGE 31 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary of Township 40 North, Range 31 East; and the dependent resurvey of the east boundary, a portion of the north boundary and a portion of the subdivisional lines, and the subdivision of certain sections, Township 39 North, Range 31 East, Mount Diablo Meridian, Nevada.

The north and east boundaries, portions of the south and west boundaries and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor G.W. Garside in 1874 under Contract No. 65.

A portion of the north boundary was purportedly resurveyed by U.S. Surveyor W.E. Hoffman in 1913 under Group No. 7.

The corner of Townships 38 and 39 North, Ranges 31 and 32 East, was remonumented by Cadastral Surveyor W.H. Sylvester in 1959 under Group No. 376.

A portion of the south boundary was resurveyed concurrently by Cadastral Surveyors T.E. Casinger and D.R. Aschenbach in 2001-04 under Group No. 802.

During the course of this survey, retracements revealed corners set by Garside in the east one and one-half miles of the north boundary were not recovered in the Hoffman resurvey. Also, the evidence utilized by Hoffman as the northeast township corner was not the same corner that was set in the Garside survey, resulting in an overlap between the survey and resurvey from the 1/4 section corner of section 2 only to the Garside township corner which is located approximately 32 chs. northerly and 25 chs. westerly of the Hoffman township corner. That portion of the plat of T. 39 N., R. 31 E., approved December 23, 1874, representing lots 1 to 4 inclusive, the S1/2NE1/4, and the S1/2NW1/4 of section 1; lots 1 and 2, and the S1/2NE1/4 of section 2; the SE1/4 of section 22; the E1/2 of section 27; and the SE1/4 of section 33 was suspended by the Director's memo dated July 16, 2003.

The Hoffman line was reestablished as the controlling boundary between Tps. 39 and 40 N., R. 31 E.

Garside's corner points for the north boundary of T. 39 N., R. 31 E. are employed for alignment and for determining proportionate measurements of the subdivisional lines within T. 39 N., R. 31 E. These subdivisional lines are terminated on the Hoffman's line with closing corners.

The one-quarter section corner of section 1 was established on the Hoffman line at the intersection with the original north-south center line of section 1.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

TOWNSHIP 39 NORTH, RANGE 31 EAST, MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated July 17, 2002, and the Supplemental Special Instructions dated November 12, 2002, for Group No. 807.</p> <p>The direction and distances of the lines of this survey were obtained by Trimble 4400 and 4700 Global Positioning System (GPS) receivers using the real-time kinematic method and refer to the true meridian, based on geodetic methods.</p> <p>The geographic position NAD 83 (1994) of the corner of Townships 38 and 39 North, Ranges 31 and 32 East, as determined by survey grade GPS receivers, in 2001, from National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "ROBERTS", located in section 25, T. 38 N., R. 32 E., is as follows:</p> <p>Latitude 41°12'18.765" N.    Longitude 118°27'07.499" W.</p> <p>The mean magnetic declination is 16°30' E., as shown on U.S. Geological Survey 7 1/2 minute quadrangle map "PARROT PEAK, NEVADA", provisional edition, dated 1990.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 40 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Resurvey Executed by U.S. Surveyor W.E. Hoffman in 1913</p> <hr/> <p>Beginning at the cor. of Tps. 39 and 40 N., R. 31 E., purportedly recovered in the course of the survey of the S. bdy. of T. 40 N., R. 32 E. executed by W.A. Pray in 1913 and utilized by Hoffman, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the 1913 fractional resurvey of the S. bdy. of T. 40 N., R. 31 E., executed under Group No. 7, with a mound of stone W. of cor. This cor. will now refer to the SE cor. of T. 40 N., R. 31 E. only.</p> <p>Remark the brass cap to read as follows:</p> <div style="text-align: center;"> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>T40N</td></tr> <tr><td>R31E</td></tr> <tr><td>S36</td></tr> </table> <p style="margin-left: 100px;">S 6</p> <p style="margin-left: 100px;">T39N R32E</p> <p style="margin-left: 100px;">2002</p> <p style="margin-left: 100px;">1913</p> </div>	T40N	R31E	S36
T40N				
R31E				
S36				

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 40 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°43'40" W., on the S. bdy. of sec. 36.  Over hills, through sagebrush and native grasses.
24.70	Ravine, drains SW.
25.487	The closing cor. of Tps. 39 N., Rs. 31 and 32 E., hereinafter described.
40.126	The 1/4 sec. cor. of secs. 1 and 36, purportedly recovered by Hoffman, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the 1913 fractional resurvey of the S. bdy. of T. 40 N., R. 31 E., executed under Group No. 7, with a mound of stone N. of cor. This cor. will now refer to the 1/4 sec. cor. of sec. 36 only.  Remark the brass cap to read as follows:  <div style="text-align: center;"> <p>T40N R31E 1/4 S36</p> <hr style="width: 10%; margin: 0 auto;"/> <p>T39N R31E</p> <p>2002 1913</p> </div> <p>From this cor., a fresh water spring bears S. 7°30' E., 5.85 chs. dist.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°45'40" W., beginning new measurement.</p>
18.70	Graveled road, 30 lks. wide, bears N. 40° E. and S. 40° W.
22.40	Graveled road, 30 lks. wide, bears N. 20° W. and S. 40° E., in curve.
26.062	The 1/4 sec. cor. of sec. 1 only, T. 39 N., R. 31 E., hereinafter described.
26.15	Trail road, bears irregularly N. and S.
29.00	Trout Creek Road, 30 lks. wide, bears N. 40° E. and S. 40° W.
39.978	The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 3 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. as described in the field notes of the 1913 fractional resurvey of the S. bdy. of T. 40 N., R. 31 E., executed under Group No. 7, with a mound of stone W. of cor. This cor. will now refer to the cor. of secs. 35 and 36 only.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 40 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Remark the brass cap to read as follows:								
	<table border="0"> <tr><td>T40N R31E</td></tr> <tr><td>S35   S36</td></tr> <tr><td>-----</td></tr> <tr><td>S 1</td></tr> <tr><td>T39N R31E</td></tr> <tr><td> </td></tr> <tr><td>2002</td></tr> <tr><td>1913</td></tr> </table>	T40N R31E	S35   S36	-----	S 1	T39N R31E		2002	1913
T40N R31E									
S35   S36									
-----									
S 1									
T39N R31E									
2002									
1913									
	<hr/> <p>S. 89°47'10" W., on the S. bdy. of sec. 35.</p> <p>Over hills, through sagebrush and native grasses.</p>								
11.50	Ravine, drains SE.								
26.780	The closing cor. of secs. 1 and 2, T. 39 N., R. 31 E., hereinafter described.								
38.00	Ravine, drains NW.								
40.078	The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. as described in the field notes of the 1913 fractional resurvey of the S. bdy. of T. 40 N., R. 31 E., executed under Group No. 7, with a mound of stone N. of cor. This cor. will now refer to the 1/4 sec. cor. of sec. 35 only.								
	<p>Remark the brass cap to read as follows:</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td>T40N R31E</td></tr> <tr><td>1/4 S35</td></tr> <tr><td>-----</td></tr> <tr><td>T39N R31E</td></tr> <tr><td> </td></tr> <tr><td>2002</td></tr> <tr><td>1913</td></tr> </table>	T40N R31E	1/4 S35	-----	T39N R31E		2002	1913	
T40N R31E									
1/4 S35									
-----									
T39N R31E									
2002									
1913									
	<hr/> <p>DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1874</p> <hr/>								
	<p>From the cor. of Tps. 38 and 39 N., Rs. 31 and 32 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above the ground, and in a mound of stone, 2 1/2 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the 1959 dependent resurvey of T. 38 N., R. 32 E., executed under Group No. 376.</p> <p>From this cor., National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "ROBERTS", bears S. 46°45'50" E. (mean bearing), 580.500 chs. dist., monumented with a standard brass tablet cemented in solid rock, mkd. ROBERTS 1965.</p>								

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 1°02'10" E., bet. secs. 31 and 36.</p> <p>Over flats, through sagebrush and native grasses.</p>										
20.423	<p>Point for the S 1/16 sec. cor. of secs. 31 and 36.</p> <p>POINT NOT MONUMENTED</p>										
40.846	<p>The 1/4 sec. cor. of secs. 31 and 36, perpetuated by Robert N. Caldwell, Nevada Professional Land Surveyor No. 4223, monumented with a rebar, 5/8 in. diam., firmly set in a mound of stone, with aluminum cap mkd. ROBERT N CALDWELL RLS 4233, alongside of which is laying a trap stone, 14x12x6 ins., mkd. 1/4 on a face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T39N</td></tr> <tr><td colspan="2">1/4</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">R31E</td><td style="padding: 0 5px;">R32E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S36</td><td style="padding: 0 5px;">S31</td></tr> </table> <p>2002</p> </div> <p>Insert the rebar inside and bury the original stone alongside the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, bears N. 35° W. and S. 35° E.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0°43'10" E., beginning new measurement.</p>	T39N		1/4		R31E	R32E	S36	S31		
T39N											
1/4											
R31E	R32E										
S36	S31										
41.537	<p>The cor. of secs. 25, 30, 31 and 36, perpetuated by Robert N. Caldwell, Nevada Professional Land Surveyor No. 4223, monumented with a rebar, 5/8 in. diam., firmly set in a mound of stone, with an aluminum cap mkd. ROBERT N CALDWELL RLS 4233, alongside of which is laying a trap stone, 13x8x8 ins., mkd. with 4 grooves on one face and 1 groove on opposite face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2">T39N</td></tr> <tr><td colspan="2">R31E R32E</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S25</td><td style="padding: 0 5px;">S30</td></tr> <tr><td colspan="2" style="border-top: 1px solid black;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S36</td><td style="padding: 0 5px;">S31</td></tr> </table> <p>2002</p> </div> <p>Insert the rebar inside and bury the original stone alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/>	T39N		R31E R32E		S25	S30			S36	S31
T39N											
R31E R32E											
S25	S30										
S36	S31										

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 1°33'10" E., bet. secs. 25 and 30.</p> <p>Over flats, through sagebrush and native grasses.</p> <p>14.90 Trail road, bears NE. and SW.</p> <p>27.00 Dry channel, 6 lks. wide, drains SW.</p> <p>31.60 Small stream, course SW.</p> <p>40.664 The 1/4 sec. cor. of secs. 25 and 30, monumented with a steel fence post of unknown origin, 5 1/2 ft. long, firmly set in an embedded mound of stone, 3 ft. diam., and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T39N 1/4 R31E   R32E S25   S30</p> <p>2002</p> </div> <p>Reset the steel fence post alongside the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°42'10" E., beginning new measurement.</p> <p>11.10 Dry channel, 10 lks. wide, drains SW.</p> <p>32.10 Dry channel, 10 lks. wide, drains SW.</p> <p>40.894 The cor. of secs. 19, 24, 25 and 30, perpetuated by John H. Milton, III, Nevada Professional Land Surveyor No. 5271, in 1994, monumented with a rebar, 5/8 in. diam., firmly set in a mound of stone, with a metal tag mkd. PLS 5271, as recorded in Humboldt County, Nevada, Book 340, Page 153, File No. 353669, alongside of which is laying a trap stone, 18x10x10 ins., mkd. with 6 grooves on one face and 2 grooves on opposite face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T39N R31E   R32E S24   S19 <hr style="width: 10%; margin: 0 auto;"/>S25   S30</p> <p>2002</p> </div>
--------	---

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Insert the rebar inside and bury the original stone alongside the stainless steel post.</p> <hr/> <p>N. 1°40'20" E., bet. secs. 19 and 24.</p> <p>Over flats, through sagebrush and native grasses.</p> <p>40.138 The 1/4 sec. cor. of secs. 19 and 24, monumented with a trap stone, 14x8x5 ins., firmly set 6 ins. in the ground, mkd. 1/4 on W. face, with a mound of stone W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T39N 1/4 R31E   R32E S24   S19</p> <p>2002</p> </div> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>N. 1°51'10" E., beginning new measurement.</p> <p>6.30 Dry creek, 10 lks. wide, drains SW.</p> <p>40.866 The cor. of secs. 13, 18, 19 and 24, monumented with a trap stone, 10x8x7 ins., laying loose in a small mound of stone, mkd. with 3 grooves on each of two opposite faces, with a steel fence post 5 1/2 ft. long, firmly set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T39N R31E R32E S13   S18 <hr/>S24   S19</p> <p>2002</p> </div> <p>Bury the original stone and reset steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 1°08'50" E., bet. secs. 13 and 18.</p> <p>Over flats, through sagebrush and native grasses.</p> <p>2.00 Dry channel, 10 lks. wide, drains SW.</p> <p>14.00 Dry channel, 10 lks. wide, drains SW.</p>
--------	--

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS											
41.311	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with a trap stone, 10x7x4 ins., laying loose on the ground, mkd. 1/4 on a face, with a steel fence post, 5 1/2 ft. long, firmly set in the ground alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T39N</td><td></td></tr> <tr><td>1/4</td><td></td></tr> <tr><td>R31E</td><td>R32E</td></tr> <tr><td>S13</td><td>S18</td></tr> </table> <p>2002</p> </div> <p>Bury the original stone and reset the steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>	T39N		1/4		R31E	R32E	S13	S18		
T39N											
1/4											
R31E	R32E										
S13	S18										
	<p>N. 0°05'00" W., beginning new measurement.</p>										
1.30	<p>Dry channel, 10 lks. wide, drains SW.</p>										
20.079	<p>Point for the N 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>N 1/16</td><td></td></tr> <tr><td>S13</td><td>S18</td></tr> </table> <p>2002</p> </div>	N 1/16		S13	S18						
N 1/16											
S13	S18										
40.158	<p>The cor. of secs. 7, 12, 13 and 18, monumented with an unmarked trap stone, 10x5x4 ins., firmly set 4 ins. in the ground, with a steel fence post, 5 1/2 ft. long, firmly set in a small mound of stone alongside, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T39N</td><td></td></tr> <tr><td>R31E</td><td>R32E</td></tr> <tr><td>S12</td><td>S 7</td></tr> <tr><td colspan="2"><hr style="width: 20%; margin: 0 auto;"/></td></tr> <tr><td>S13</td><td>S18</td></tr> </table> <p>2002</p> </div> <p>Bury the unmarked stone and reset the steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>	T39N		R31E	R32E	S12	S 7	<hr style="width: 20%; margin: 0 auto;"/>		S13	S18
T39N											
R31E	R32E										
S12	S 7										
<hr style="width: 20%; margin: 0 auto;"/>											
S13	S18										

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 1°02'20" E., bet. secs. 7 and 12.</p> <p>Over hills, through sagebrush and native grasses.</p> <p>6.74 Barbed wire fence, bears N. 65° E. and S. 65° W.</p> <p>27.50 Dry wash, 5 lks. wide, drains SW.</p> <p>40.854 The 1/4 sec. cor. of secs. 7 and 12, monumented with an unrecorded rebar, 5/8 ins. diam., firmly set flush with the ground, with aluminum cap mkd. ROBERT N CALDWELL RLS 4233, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T39N 1/4 R31E   R32E S12   S 7</p> <p>2002</p> </div> <p>Insert the rebar inside, and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>Cor. is located in a barbed wire fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°54'40" E., beginning new measurement.</p> <p>0.85 From this point, a spring bears EAST, 11.75 chs. dist.</p> <p>20.431 The N 1/16 sec. cor. of secs. 7 and 12, monumented with an unrecorded rebar, 5/8 in. diam., firmly set, projecting 8 ins. above the ground, with an aluminum cap mkd. ROBERT N CALDWELL RLS 4233, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16 S12   S 7</p> <p>2002</p> </div> <p>Insert the rebar inside the stainless steel post.</p> <p>Cor. is located at the intersection of barbed wire fences, extending N., S. and E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°59'40" E., beginning new measurement.</p>
--------	---

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
2.60	Trout Creek, 8 lks. wide, course SW.
3.40	Trail road, bears NE. and SW.
18.50	Dry channel, 10 lks. wide, drains SW.
20.426	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a trap stone, 18x15x12 ins., firmly set 8 ins. in the ground, mkd. with 5 grooves on S. face and 1 groove on N. face, with a steel fence post, 5 1/2 ft. long, firmly set alongside, and a mound of stone, 3 ft. diam., S. of cor. At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T39N R31E R32E S 1   S 6 ----- S12   S 7</p> <p>2002</p> </div> <p>Bury the original stone and reset the steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°54'00" E., bet. secs. 1 and 6. Over hills, through sagebrush and native grasses.</p>
37.00	Ridge, bears E. and W.
39.207	<p>Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T39N 1/4 R31E   R32E S 1   S 6</p> <p>2002</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
45.90	Ravine, drains SW.
46.562	<p>Intersect the S. bdy. of sec. 36, T. 40 N., R. 31 E.</p> <p>Point for the closing cor. of Tps. 39 N., Rs. 31 and 32 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p>T40N R31E S36</p> <hr/> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T39N</td> <td style="padding: 0 5px;">T39N</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R31E</td> <td style="padding: 0 5px;">R32E</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">CC</td> </tr> </table> <p>2002</p>	S 1	S 6	T39N	T39N	R31E	R32E	CC	
S 1	S 6								
T39N	T39N								
R31E	R32E								
CC									
	<p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this point, the 1/4 sec. cor. of sec. 36 only, T. 40 N., R. 31 E., bears N. 89°43'40" W., 14.639 chs. dist., hereinbefore described.</p> <p>Continue measurement across sec. 36, T. 40 N., R. 31 E., on a blank line.</p>								
54.00	Summit, bears E. and W.								
73.70	Graded road, 30 lks. wide, bears NE. and SW.								
78.414	The Garside cor. of Tps. 39 and 40 N., Rs. 31 and 32 E., monumented with a trap stone, 14x8x5 ins., firmly set in a mound of stone, 3 ft. diam., 6 ins. high, mkd. with 6 grooves on S. face and 6 grooves on W. face. I add the marks AM and bury the stone flush with ground with AM marks on top face.								
<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>									
<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1874</p> <hr/>									
	<p>From the Garside cor. of Tps. 39 and 40 N., Rs. 31 and 32 E., now an amended monument, hereinbefore described.</p> <p>N. 89°46'50" W., across secs. 36 and 35, T. 40 N., R. 31 E., on a blank line.</p> <p>Over hills, through sagebrush and native grasses.</p>								
24.45	From this point, a spring bears SOUTH, 3.35 chs. dist.								
32.60	Graveled road, 30 lks. wide, bears N. 25° W. and S. 25° E.								
40.928	Point for the Garside 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. This point now becomes an amended position.								
	POINT NOT MONUMENTED								
48.30	Ravine, drains N.								
57.60	Ravine, drains N.								

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
81.856	<p>Point for the Garside cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. This point now becomes an amended position.</p>
	<p>POINT NOT MONUMENTED</p> <hr/>
	<p>N. 89°46'50" W., across sec. 35, T. 40 N., R. 31 E., on a blank line.</p>
	<p>Over hills, through sagebrush and native grasses.</p>
6.00	<p>Ridge, bears N. and S.</p>
40.928	<p>The Garside 1/4 sec. cor. of secs. 2 and 35, monumented with a trap stone, 12x8x5 ins., firmly set flush with the surface of the ground, mkd. 1/4 on N. face. I add the marks AM and bury the stone flush with ground with AM marks on top face.</p>
	<p>Set a steel fence post, 5 1/2 ft. long, alongside the original stone.</p> <hr/>
	<p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1874</p> <hr/>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a brass tablet, 3 1/4 ins. diam., firmly set in a boulder, 36 ins. x 12 ins., projecting 18 ins. above the ground, with top mkd. as described in the field notes of the 2001-04 dependent resurvey of the N. bdy. of T. 38 N., R. 31 E., executed concurrently under Group No. 802.</p>
	<p>N. 2°09'10" E., bet. secs. 35 and 36.</p>
	<p>Over flats, through sagebrush and native grasses.</p>
3.00	<p>Louse Creek, 20 lks. wide, course SE.</p>
31.80	<p>Dry creek, 10 lks. wide, drains SE.</p>
36.227	<p>The 1/4 sec. cor. of secs. 35 and 36, monumented with a trap stone, 10x9x5 ins., firmly set 6 ins. in the ground, mkd. 1/4 on W. face.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>T39N R31E 1/4 S35 S36</p>
	<p>2002</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>8.90</p> <p>20.424</p> <p>39.10</p> <p>40.848</p> <p>13.00</p>	<p>Bury the original stone and set a steel fence post, 5 1/2 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 1°14'20" E., beginning new measurement.</p> <p>Dry creek, 10 lks. wide, drains SE.</p> <p>Point for the N 1/16 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S35   S36</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>Trout Creek Road, 30 lks. wide, bears N. 30° W. and S. 30° E.</p> <p>The cor. of secs. 25, 26, 35 and 36, monumented with a trap stone, 12x8x8 ins., firmly set in a mound of stone, 2 1/2 ft. diam., mkd. with 1 groove on S. face and 1 groove on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T39N R31E S26   S25 S35   S36</p> <p style="text-align: center;">2002</p> <p>Bury the original stone and set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>From this cor., a point determined by John H. Milton, III, Nevada Professional Land Surveyor No. 5271, in 1994, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, and in a mound of stone, 2 1/2 ft. diam., with a plastic cap mkd. PLS 5271, as recorded in Humboldt County, Nevada, Book 340, Page 153, File No. 353669, bears N. 5°09'30" W., 11.580 chs. dist. This point is not utilized in this survey.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 83°23'30" W., bet. secs. 25 and 36. Over flats, through sagebrush and native grasses.</p> <p>Trail road, bears NE. and SW.</p>
---	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
32.60	Dry creek, 10 lks. wide, drains SW.
40.00	Dry wash, 15 lks. wide, drains SW.
40.286	Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T39N R31E S25 1/4 ——— S36  2002
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
60.429	Point for the W 1/16 sec. cor. of secs. 25 and 36.  POINT NOT MONUMENTED
64.00	Dry wash, 10 lks. wide, drains SW.
67.60	Trout Creek, 8 lks. wide, course S. 10° E.
72.90	Ditch, 10 lks. wide, 2 ft. deep, drains SE.
80.572	The cor. of secs. 25, 26, 35 and 36.
	N. 0°58'40" E., bet. secs. 25 and 26.  Over flats, changing to rolling hills, through sagebrush and native grasses.
15.80	Ditch, 10 lks. wide, 2 ft. deep, drains SE.
17.80	Trout Creek, 8 lks. wide, course S. 5° E.
40.625	The 1/4 sec. cor. of secs. 25 and 26, monumented with a trap stone, 14x10x8 ins., firmly set 6 ins. in the ground, mkd. 1/4 on W. face, with a lone stone alongside.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.
	T39N R31E 1/4 S26   S25  2002
	Bury the original stone alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°50'10" E., beginning new measurement.								
27.50	Ravine, drains SW.								
30.85	Barbed wire fence, bears N. 30° W. and S. 30° E.								
41.435	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a trap stone, 14x10x8 ins., firmly set 6 ins. in the ground, mkd. with 2 grooves on S. face and 1 groove on E. face, with a mound of stone, 2 1/2 ft. diam., 1 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T39N R31E</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> <tr> <td colspan="2"><hr style="width: 50%; margin: 0 auto;"/></td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> </table> <p>2002</p> </div> <p>Bury the original stone alongside the stainless steel post.</p> <p>Rebuild the mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>From this cor., a point determined by John H. Milton, III, Nevada Professional Land Surveyor No. 5271, in 1994, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, and in a mound of stone, 2 1/2 ft. diam., with a metal tag mkd. PLS 5271, alongside of which is laying a stone, 10x8x8 ins., mkd. with 2 grooves on one face, as recorded in Humboldt County, Nevada, Book 340, Page 153, File No. 353669, bears N. 0°08'30" E., 11.435 chs. dist. This point is not utilized in this survey.</p>	T39N R31E		S23	S24	<hr style="width: 50%; margin: 0 auto;"/>		S26	S25
T39N R31E									
S23	S24								
<hr style="width: 50%; margin: 0 auto;"/>									
S26	S25								
	<hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 83°46'30" W., bet. secs. 24 and 25.</p> <p>Over flats, through sagebrush and native grasses.</p>								
40.400	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T39N R31E</td> </tr> <tr> <td></td> <td>S24</td> </tr> <tr> <td>1/4</td> <td><hr style="width: 50%; margin: 0 auto;"/></td> </tr> <tr> <td></td> <td>S25</td> </tr> </table> <p>2002</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> </div>	T39N R31E			S24	1/4	<hr style="width: 50%; margin: 0 auto;"/>		S25
T39N R31E									
	S24								
1/4	<hr style="width: 50%; margin: 0 auto;"/>								
	S25								
46.10	Dry wash, 10 lks. wide, drains SW.								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
62.10	Dry wash, drains S.
71.30	Ravine, drains SW.
80.800	The cor. of secs. 23, 24, 25 and 26.
	<hr/> <p>N. 0°33'40" E., bet. secs. 23 and 24.</p> <p>Over flats, changing to rolling hills, through sagebrush and native grasses.</p>
22.00	Dry channel, 10 lks. wide, drains SW.
40.30	Dry wash, 10 lks. wide, drains SW.
40.954	Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">T39N R31E 1/4 S23   S24</p> <p style="text-align: center;">2002</p>
	Set a steel fence post, 5 1/2 ft. long, alongside the stainless steel post.
55.40	Dry wash, 20 lks. wide, drains SW.
61.431	Point for the N 1/16 sec. cor. of secs. 23 and 24.
	POINT NOT MONUMENTED
74.90	Trail road, bears NE. and SW.
81.908	The cor. of secs. 13, 14, 23 and 24, monumented with a trap stone, 18x8x7 ins., firmly set in a mound of stone, 2 1/2 ft. diam., mkd. with 3 grooves on S. face and 1 groove on E. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T39N R31E S14   S13 S23   S24</p> <p style="text-align: center;">2002</p>
	Bury the original stone alongside the stainless steel post.
	From this cor., a point determined by John H. Milton, III, Nevada Professional Land Surveyor No. 5271, in 1994, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>above the ground, and in a mound of stone, 3 ft. diam., with a metal tag mkd. PLS 5271, alongside of which is laying a stone, mkd. with 3 grooves on one face, as recorded in Humboldt County, Nevada, Book 340, Page 153, File No. 353669, bears N. 7°11'20" E., 11.572 chs. dist. This point is not utilized in this survey.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 84°33'10" W., bet. secs. 13 and 24.</p> <p>Over hills, through sagebrush and native grasses.</p> <p>3.30 Dry wash, 20 lks. wide, drains SW.</p> <p>7.50 Dry wash, 20 lks. wide, drains NW.</p> <p>15.10 Dry wash, 20 lks. wide, drains SW.</p> <p>25.40 Dry wash, 10 lks. wide, drains SW.</p> <p>30.10 Dry wash, 10 lks. wide, drains SW.</p> <p>41.184 Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T39N R31E</p> <p>S13</p> <p>1/4 <math>\frac{\quad}{\quad}</math></p> <p>S24</p> <p>2002</p> </div> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p> <p>72.40 Dry wash, 20 lks. wide, drains SW.</p> <p>78.80 Trail road, bears NE. and SW.</p> <p>82.368 The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 1°20'40" E., bet. secs. 13 and 14.</p> <p>Over rolling hills, through sagebrush and native grasses.</p> <p>7.10 Dry wash, 20 lks. wide, drains SW.</p> <p>45.520 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T39N R31E 1/4 S14   S13</p>
	<p style="text-align: center;">2002</p>
91.040	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a trap stone, 13x11x5 ins., firmly set in a mound of stone, 2 1/2 ft. diam., mkd. with 4 grooves on S. face and 1 groove on E. face, alongside of which is set a rebar, 5/8 in. diam., with aluminum cap mkd. RLS 4233.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T39N R31E S11   S12 S14   S13</p> <p style="text-align: center;">2002</p> <p>Insert the rebar inside, bury the original stone alongside, and set a steel fence post, 5 1/2 ft. long alongside, the stainless steel post.</p> <p>Raise a small mound of stone, 2 ft. base, N. of cor.</p>
13.18	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 88°46'00" W., bet. secs. 12 and 13.</p>
	<p>Over low hills, through sagebrush and native grasses.</p>
32.40	<p>Barbed wire fence, bears N. 65° E. and S. 65° W.</p>
40.315	<p>Dry channel, drains SW.</p>
	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T39N R31E S12 1/4 ——— S13</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p>
53.60	<p>Trail road, bears NW. and SE.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.630	The cor. of secs. 11, 12, 13 and 14.
	N. 0°55'50" E., bet. secs. 11 and 12.
	Over low hills, through sagebrush and native grasses.
8.40	Dry creek, 15 lks. wide, drains SW.
20.269	Point for the S 1/16 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S 1/16 S11 S12
	2002
	Set a carsonite post, 5 ft. long, alongside the stainless steel post.
	Cor. is located at the intersection of barbed wire fences, extending N., E. and W.
25.00	Trout Creek, 10 lks. wide, course S. 45° W.
40.538	The 1/4 sec. cor. of secs. 11 and 12, perpetuated by Robert N. Caldwell, Nevada Professional Land Surveyor No. 4233, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with an aluminum cap mkd. ROBERT N CALDWELL RLS 4233, alongside of which is laying a trap stone, 22x12x10 ins., mkd. 1/4 on a face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T39N R31E 1/4 S11 S12
	2002
	Bury the rebar inside and the original stone alongside the stainless steel post.
	Cor. is located at the intersection of barbed wire fences, extending E. and S.
	N. 0°53'40" E., beginning new measurement.
3.10	Dry creek, 10 lks. wide, drains S. 25° W.
5.20	Trout Creek Road, 30 lks. wide, bears N. 20° E. and S. 20° W.
40.550	The cor. of secs. 1, 2, 11 and 12, determined by Robert N. Caldwell, Nevada Professional Land Surveyor No. 4233,

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>monumented with a rebar, 5/8 in. diam., firmly set in a mound of stone, with an aluminum cap mkd. ROBERT N CALDWELL RLS 4233, and adopted by John H. Milton, III, Nevada Professional Land Surveyor No. 5271, in 1987, as recorded in Humboldt County, Nevada, File No. 284765, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T39N</td><td>R31E</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td>S11</td><td>S12</td></tr> </table> <p>2002</p> </div> <p>Bury the rebar alongside the stainless steel post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°12'30" W., bet. secs. 1 and 12.</p> <p>Over gentle slope, through sagebrush and native grasses.</p> <p>30.90 Trail road, bears NW. and SE.</p> <p>40.364 Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T39N</td><td>R31E</td></tr> <tr><td>S 1</td><td></td></tr> <tr><td>1/4</td><td>S12</td></tr> </table> <p>2002</p> </div> <p>Set a steel fence post, 5 ft. long, alongside the stainless steel post.</p> <p>70.20 Dry creek, 10 lks. wide, drains S.</p> <p>71.20 Trout Creek Road, 30 lks. wide, bears N. and S.</p> <p>80.728 The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0°03'30" E., bet. secs. 1 and 2.</p> <p>Over rolling hills, through sagebrush and native grasses.</p> <p>38.922 Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate</p>	T39N	R31E	S 2	S 1	S11	S12	T39N	R31E	S 1		1/4	S12
T39N	R31E												
S 2	S 1												
S11	S12												
T39N	R31E												
S 1													
1/4	S12												

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T39N R31E 1/4 S 2   S 1</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>45.242 Intersect the S. bdy. of sec. 35, T. 40 N., R. 31 E.</p> <p>Point for the closing cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T40N R31E S35 ----- S 2   S 1 T39N R31E CC</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this point, the 1/4 sec. cor. of sec. 35 only, T. 40 N., R. 31 E., bears S. 89°47'10" W., 13.298 chs. dist., hereinbefore described.</p> <p>Continue measurement across sec. 35, T. 40 N., R. 31 E., on a blank line.</p> <p>68.50 Ridge, bears NW. and SE.</p> <p>77.601 The point for the Garside cor. of secs. 1, 2, 35 and 36, now an amended position, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 2001-04 dependent resurvey of the N. bdy. of T. 38 N., R. 31 E., executed concurrently under Group No. 802.</p> <p>N. 0°08'10" W., bet. secs. 34 and 35.</p> <p>Over rolling hills, through sagebrush and native grasses.</p> <p>11.70 Dry channel, drains E.</p> <p>13.50 Trail road, bears NW. and SE.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.00	Dry channel, drains SE.
34.40	Spur, slopes E.
39.715	The 1/4 sec. cor. of secs. 34 and 35, monumented with a trap stone, 13x7x6 ins., firmly set in a mound of stone, 2 1/2 ft. diam., mkd. 1/4 on W. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T39N R31E 1/4 S34 S35  2002
	Bury the original stone alongside the stainless steel post.
	-----
	N. 0°02'00" E., beginning new measurement.
3.90	Dry wash, 20 lks. wide, drains SE.
20.10	Ridge, bears E. and W.
35.30	Louse Creek, 10 lks. wide, course E.
36.90	Trail road, bears NW. and SE.
42.218	The cor. of secs. 26, 27, 34 and 35, monumented with a trap stone, 19x6x6 ins., firmly set in a mound of stone, 4 ft. diam., 1 ft. high, mkd. with 1 groove on S. face and 2 grooves on E. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T39N R31E S27 S26 ----- S34 S35  2002
	Bury the original stone alongside the stainless steel post.
	-----
	From the cor. of secs. 25, 26, 35 and 36.
	N. 87°40'50" W., bet. secs. 26 and 35.
	Over rolling hills, through sagebrush and native grasses.
0.90	Trout Creek Road, 30 lks. wide, bears N. 30° W. and S. 30° E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.929	<p>Point for the E 1/16 sec. cor. of secs. 26 and 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 <math>\frac{S26}{S35}</math></p> <p style="text-align: center;">2002</p>
	<p>Set a carsonite post, 5 ft. long, alongside stainless steel post.</p>
24.30	Creek, 10 lks. wide, course SE.
26.50	Trail road, bears NW. and SE.
35.00	Trail road, bears NE. and SW.
36.10	Trail road, bears NW. and SE.
38.80	Trail road, bears NE. and SW.
41.858	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T39N R31E 1/4 <math>\frac{S26}{S35}</math></p> <p style="text-align: center;">2002</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
83.716	The cor. of secs. 26, 27, 34 and 35.
	<p>N. 1°10'00" E., bet. secs. 26 and 27.</p> <p>Over rolling hills, through sagebrush and native grasses.</p>
15.80	Ridge, bears NW. and SE.
41.685	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with a trap stone, 9x7x6 ins., firmly set 4 ins. in the ground, mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T39N R31E 1/4 S27 S26 2002</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>N. 0°55'30" E., beginning new measurement.</p> <p>2.80 Trail road, bears NW. and SE.</p> <p>11.50 Clover Creek, 10 lks. wide, course SE.</p> <p>26.60 Ravine, drains SE.</p> <p>40.393 The cor. of secs. 22, 23, 26 and 27, monumented with a trap stone, 12x10x6 ins., firmly set 6 ins. in the ground, mkd. with 2 grooves on S. face and 2 grooves on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T39N R31E S22 S23 S27 S26 2002</p> <p>Bury the original stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 84°47'40" W., bet. secs. 23 and 26.</p> <p>Over hills, through sagebrush and native grasses.</p> <p>1.60 Barbed wire fence, bears N. and S.</p> <p>9.10 Trout Creek, 10 lks. wide, course S.</p> <p>13.80 Trout Creek Road, 30 lks. wide, bears N. and S.</p> <p>20.50 Dry wash, 15 lks. wide, drains SE.</p> <p>20.60 Barbed wire fence, bears N. and S.</p> <p>21.235 Point for the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	$E \frac{1}{16} \frac{S23}{S26}$ <p style="text-align: center;">2002</p>
42.470	<p>The 1/4 sec. cor. of secs. 23 and 26, monumented with a mound of stone, 3 ft. diam., 1 ft. high, no mkd. stone found and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $T39N R31E$ $\frac{1}{4} \frac{S23}{S26}$ <p style="text-align: center;">2002</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89°22'10" W., beginning new measurement.</p>
4.40	Dry creek, 20 lks. wide, drains SE.
41.135	The cor. of secs. 22, 23, 26 and 27.
	<hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°28'00" E., bet. secs. 22 and 23.</p> <p>Over hills, through sagebrush and native grasses.</p>
6.10	Ravine, drains E.
36.70	Ravine, 20 lks. wide, drains SE.
42.082	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $T39N R31E$ $\frac{1}{4} \frac{S22}{S23}$ <p style="text-align: center;">2002</p>
53.50	Ravine, drains SE.
66.70	Spur, slopes SE.
70.80	Ravine, drains SE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
84.164	<p>The cor. of secs. 14, 15, 22 and 23, monumented with a small mound of stone, 1 1/2 ft. diam., 6 ins. high, no mkd. stone found and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T39N</td><td>R31E</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td>S22</td><td>S23</td></tr> </table> <p>2002</p> </div> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p> <hr/>	T39N	R31E	S15	S14	S22	S23
T39N	R31E						
S15	S14						
S22	S23						
	<p>From the cor. of secs. 13, 14, 23 and 24.</p>						
	<p>N. 86°07'30" W., bet. secs. 14 and 23.</p>						
	<p>Over hills, through sagebrush and native grasses.</p>						
2.40	<p>Ravine, drains SW.</p>						
20.930	<p>Point for the E 1/16 sec. cor. of secs. 14 and 23.</p>						
	<p>POINT NOT MONUMENTED</p>						
21.10	<p>Trout Creek, 10 lks. wide, course SSW.</p>						
21.90	<p>Trout Creek Road, 30 lks. wide, bears N. 20° E. and S. 25° W.</p>						
29.40	<p>Dry wash, 20 lks. wide, drains SE.</p>						
41.860	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T39N</td><td>R31E</td></tr> <tr><td>1/4</td><td>S14</td></tr> <tr><td></td><td>S23</td></tr> </table> <p>2002</p> </div>	T39N	R31E	1/4	S14		S23
T39N	R31E						
1/4	S14						
	S23						
	<p>Set a steel fence post, 5 1/2 ft. long, alongside the stainless steel post.</p>						
	<p>From this point, a point adopted by John H. Milton III, Nevada Professional Land Surveyor No. 5271, in 1994, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above the ground, and in a mound of stone, 3 ft. diam., as recorded in Humboldt County, Nevada, Book 340, Page 153, File No. 353669, bears N. 18°43'50" E., 10.205 chs. dist. This point is</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	not utilized in this survey.
70.50	Spur, slopes S.
80.40	Ravine, drains S.
83.720	The cor. of secs. 14, 15, 22 and 23.
	<hr/>
	N. 0°30'30" E., bet. secs. 14 and 15.
	Over hills, through sagebrush and native grasses.
26.10	Ridge, bears NW. and SE.
41.90	Ravine, drains E.
43.404	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.
	T39N R31E 1/4 S15 S14  2002
46.10	Ravine, drains E.
60.50	Ridge, bears NE. and SW.
69.30	Creek, 4 lks. wide, course E.
76.50	Rock cliff, bears E. and W.
86.808	The cor. of secs. 10, 11, 14 and 15, monumented with a trap stone, 16x10x10 ins., firmly set in a small mound of stone, mkd. with 2 grooves on N. face and 2 grooves on E. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T39N R31E S10 S11 S15 S14  2002
	Bury the original stone alongside the stainless steel post.
	<hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 88°53'30" W., bet. secs. 11 and 14.</p> <p>Over hills, through sagebrush and native grasses.</p>
6.80	Dry channel, 15 lks. wide, drains SW.
18.90	Trout Creek, 10 lks. wide, course S. 10° W.
20.247	<p>The E 1/16 sec. cor. of secs. 11 and 14, determined by John H. Milton, III, Nevada Professional Land Surveyor No. 5271, in 1994, monumented with a rebar, 5/8 in. diam., firmly set flush with the surface of the ground, with a plastic cap mkd. JOHN H MILTON PLS 5271, as recorded in Humboldt County, Nevada, Book 340, Page 153, File No. 353669, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">E \frac{1}{16} \frac{S11}{S14}</math> <p>2002</p> </div> <p>Insert the rebar inside the stainless steel post.</p> <p>Cor. is located at the corner of barbed wire fences extending N. and W.</p> <p>From this cor., an iron pipe, 1 1/4 ins. diam., firmly set, projecting 10 ins. above the ground, mkd. 1/XVI on the S. side, set by person(s) unknown, bears S. 49°36'30" E., 0.495 chs. dist., and is not utilized in this survey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88°53'30" W., beginning new measurement.</p>
0.20	Trout Creek Road, 30 lks. wide, bears N. 15° E. and S. 15° W.
5.70	Dry channel, drains SE.
20.247	<p>The 1/4 sec. cor. of secs. 11 and 14, perpetuated by John H. Milton, III, Nevada Professional Land Surveyor No. 5271, in 1994, from original evidence no longer in existence, monumented with a rebar, 5/8 in. diam., firmly set flush with the surface of the ground, with a plastic cap mkd. JOHN H MILTON PLS 5271, as recorded in Humboldt County, Nevada, Book 340, Page 153, File No. 353669, and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T39N R31E S11 1/4 <u>      </u> S14</p> <p style="text-align: center;">2002</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Cor. is located at the corner of barbed wire fences, extending E. and S.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°08'50" W., beginning new measurement.</p>
44.392	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground and in a collar of stone, with brass cap mkd. as described in the field notes of the 2001-04 resurvey of the N. bdy. of T. 38 N., R. 31 E., executed concurrently under Group No. 802.</p> <p>N. 0°59'10" E., bet. secs. 33 and 34.</p> <p>Over hills, through sagebrush and native grasses.</p>
5.50	Dry wash, 20 lks. wide, drains E.
21.30	Trail road, bears NW. and SE.
32.90	Dry wash, 25 lks. wide, drains NE.
40.006	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T39N R31E 1/4 S33 S34</p> <p style="text-align: center;">2002</p>
72.00	Ravine, drains E.
80.012	<p>Point for the cor. of secs. 27, 28, 33 and 34, determined at record distance in latitude from the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described, and at record distance in departure from the cor. of secs. 26, 27, 34 and 35; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T39N R31E S28   S27 S33   S34</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 85°50'30" W., bet. secs. 27 and 34.</p> <p>Over hills, through sagebrush and native grasses.</p> <p>18.40 Trail road, bears NW. and SE.</p> <p>27.70 Louse Creek, 10 lks. wide, course S. 60° E.</p> <p>40.176 Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T39N R31E 1/4   S27 S34</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>80.352 The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 1, T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 12.</p> <p>N. 0°28'50" E., on the N-S center line of sec. 1.</p> <p>Over hills, through sagebrush and native grasses.</p> <p>25.00 Dry wash, 20 lks. wide, drains SW.</p> <p>29.50 Dry creek, 25 lks. wide, drains SW.</p> <p>37.70 Trail road, bears irregularly N. and SSE.</p> <p>45.960 Intersect the S. bdy. of sec. 36, T. 40 N., R. 31 E.</p> <p>Point for the 1/4 sec. cor. of sec. 1 only.</p>
--------	---

SUBDIVISION OF SECTION 1,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T40N R31E ----- 1/4 S 1 T39N R31E</p> <p style="text-align: center;">2002</p> <p>Set a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>From this point, the cor. of secs. 35 and 36 only, T. 40 N., R. 31 E., bears S. 89°45'40" W., 13.916 chs. dist., hereinbefore described.</p> <p>Continue measurement across sec. 36, T. 40 N., R. 31 E., on a blank line.</p> <p>50.00 Trout Creek Road, 30 lks. wide, bears N. 40° E. and S. 40° W.; saddle bears E. and W.</p> <p>78.006 The point for the Garside 1/4 sec. cor. of secs. 1 and 36, now an amended position, hereinbefore described.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 11, T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 0°55'50" E., parallel with the S 1/2 mile of the E. bdy. of sec. 11, on the N-S center line of sec. 11.</p> <p>Over hills, through sagebrush and native grasses.</p> <p>10.70 Dry wash, 10 lks. wide, drains S. 65° E.</p> <p>20.269 Point for the C-S 1/16 sec. cor. of sec. 11.</p> <p>POINT NOT MONUMENTED</p> <p>39.00 Ravine, drains SE.</p> <p>40.538 Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T39N R31E C 1/4 S11</p> <p style="text-align: center;">2002</p> <hr/>
--------	---

SUBDIVISION OF SECTION 11,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 11 and 12.</p> <p>N. 88°53'30" W., parallel with the E 1/2 mile of the S. bdy. of sec. 11, on the E-W center line of sec. 11.</p> <p>Over hills, through sagebrush and native grasses.</p>
1.60	Creek, 10 lks. wide, course S. 10° W.
2.20	Trout Creek Road, 30 lks. wide, bears N. 20° E. and S. 20° W.
12.50	Spur, slopes S.
20.244	Point for the C-E 1/16 sec. cor. of sec. 11.
	POINT NOT MONUMENTED
40.488	The center 1/4 sec. cor. of sec. 11.
	<hr/>
	<p>From the E 1/16 sec. cor. of secs. 11 and 14.</p> <p>N. 0°55'50" E., on the N-S center line of the SE1/4 of sec. 11.</p> <p>Over hills, through sagebrush and native grasses.</p>
1.40	Trout Creek Road, 30 lks. wide, bears N. 10° E. and S. 10° W.
20.269	Point for the SE 1/16 sec. cor. of sec. 11, at intersection with the E-W center line of the SE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SE 1/16 S11
	2002
	Set a steel fence post, 5 1/2 ft. long, alongside the stainless steel post.
	From this point, a point determined by John H. Milton III, Nevada Professional Land Surveyor No. 5271, in 1994, monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with a 1 in. plastic cap (mks. unreadable), as recorded in Humboldt County, Nevada, Book 340, Page 153, File No. 353669, bears S. 16°24'40" E., 0.106 chs. dist. This point is not utilized in this survey.
40.538	The point for the C-E 1/16 sec. cor. of sec. 11.
	<hr/>
	<p>From the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>N. 88°53'30" W., on the E-W center line of the SE1/4 of sec. 11.</p> <p>Over hills, through sagebrush and native grasses.</p>
7.80	Trout Creek, 10 lks. wide, course S. 45° W.

SUBDIVISION OF SECTION 11,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
13.40	Creek, 10 lks. wide, course S. 30° W.
14.80	Trout Creek Road, 30 lks. wide, bears N. 25° E. and S. 20° W.
20.246	The SE 1/16 sec. cor.
35.60	Ravine, drains SE.
40.492	The point for the C-S 1/16 sec. cor. of sec. 11.
<hr/> SUBDIVISION OF SECTION 13, T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>	
	From the 1/4 sec. cor. of secs. 13 and 24.
	N. 0°57'50" E., on the N-S center line of sec. 13.
	Over hills, through sagebrush and native grasses.
29.60	Dry wash, 20 lks. wide, drains SW.
43.402	Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T39N R31E C 1/4 S13  2002
61.30	Dry wash, 15 lks. wide, drains SW.
64.826	Point for the C-N 1/16 sec. cor. of sec. 13.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	C N 1/16   S13 C  2002
72.13	Barbed wire fence, bears N. 65° E. and S. 65° W.
76.60	Dry wash, 20 lks. wide, drains SW.
86.250	The 1/4 sec. cor. of secs. 12 and 13.
<hr/> From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.  S. 87°28'10" W., on the E-W center line of sec. 13. <hr/>	

SUBDIVISION OF SECTION 13,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over hills, through sagebrush and native grasses.
0.40	Dry wash, 10 lks. wide, drains SW.
19.80	Dry wash, 20 lks. wide, drains SW.
41.129	The center 1/4 sec. cor. of sec. 13.
57.30	Dry wash, 20 lks. wide, drains SW.
58.80	Dry wash, 25 lks. wide, drains S.
60.70	Trail road, bears NE. and SW.
81.825	The 1/4 sec. cor. of secs. 13 and 14.
	<hr/>
	From the N 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.
	S. 89°20'00" W., on the E-W center line of the NE1/4 of sec. 13.
	Over hills, through sagebrush and native grasses.
13.70	Dry wash, 20 lks. wide, drains SW.
37.90	Dry wash, 25 lks. wide, drains SW.
40.700	The C-N 1/16 sec. cor. of sec. 13.
	<hr/>
	SUBDIVISION OF SECTION 14, T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 2°11'30" E., on the N-S center line of sec. 14.
	Over hills, through sagebrush and native grasses.
89.036	The 1/4 sec. cor. of secs. 11 and 14.
	<hr/>
	SUBDIVISION OF SECTION 23, T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 0°56'20" E., on the N-S center line of sec. 23.
	Over hills, through sagebrush and native grasses.
28.10	Dry wash, 15 lks. wide, drains SE.
39.385	Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E-W center line.

SUBDIVISION OF SECTION 23,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, over a plastic-encased magnet, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T39N R31E C 1/4 S23 2002</p>
60.138	<p>Point for the C-N 1/16 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16   S23 C 2002</p> <p>Set a steel fence post, 5 1/2 ft. long, alongside the stainless steel post.</p>
80.891	<p>The 1/4 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 24.</p> <p>N. 86°53'40" W., on the E-W center line of sec. 23.</p> <p>Over hills, through sagebrush and native grasses.</p>
6.00	Dry wash, 15 lks. wide, drains SW.
12.50	Trail road, bears NE. and SW.
18.10	Trout Creek, 10 lks. wide, course S. 20° E.
19.30	Trout Creek Road, 30 lks. wide, bears N. 25° W. and S. 25° E.
21.054	<p>Point for the C-E 1/16 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S23 2002</p> <p>Set a steel fence post, 5 1/2 ft. long, alongside the stainless steel post.</p>
42.108	The center 1/4 sec. cor. of sec. 23.
52.10	Dry wash, 15 lks. wide, drains SE.
64.40	Dry wash, 20 lks. wide, drains SE.

SUBDIVISION OF SECTION 23,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
83.599	<p>The 1/4 sec. cor. of secs. 22 and 23.</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 23.</p> <p>N. 0°45'10" E., on the N-S center line of the NE1/4 of sec. 23.</p> <p>Over hills, through sagebrush and native grasses.</p>
20.615	<p>Point for the NE 1/16 sec. cor. of sec. 23, at intersection with the E-W center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S23</p> <p style="text-align: center;">2002</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 26°59' W., 0.348 chs. dist., with brass cap mkd. RM 23 FT TO COR 2002 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 65°25' W., 0.348 chs. dist., with brass cap mkd. RM NE 1/16 S23 23 FT TO COR 2002 and an arrow pointing to the cor.</p> <p>Set a steel fence post, 5 1/2 ft. long, alongside each of the stainless steel posts.</p> <p>Cor. is located in Trout Creek Road, 30 lks. wide, bears N. 10° W. and S. 10° E.</p>
25.00	Trout Creek, 10 lks. wide, course S. 20° E.
30.50	Trout Creek, 10 lks. wide, course S. 20° W.
35.40	Trout Creek, 10 lks. wide, course S. 5° E.
41.230	<p>The point for the E 1/16 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the point for the N 1/16 sec. cor. of secs. 23 and 24.</p> <p>N. 86°30'40" W., on the E-W center line of the NE1/4 of sec. 23.</p> <p>Over hills, through sagebrush and native grasses.</p>
5.40	Trail road, bears NE. and SW.
12.40	Ravine, drains SW.
20.10	Trout Creek, 10 lks. wide, course S. 10° E.

SUBDIVISION OF SECTION 23,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.992	The NE 1/16 sec. cor.
41.984	The C-N 1/16 sec. cor. of sec. 23.
	<hr/> From the E 1/16 sec. cor. of secs. 23 and 26. N. 0°44'50" E., on the N-S center line of the SE1/4 of sec. 23.
0.50	Dry wash, 15 lks. wide, drains SE.
40.170	The C-E 1/16 sec. cor. of sec. 23.
	<hr/> SUBDIVISION OF SECTION 24, T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/> From the 1/4 sec. cor. of secs. 24 and 25. N. 1°09'40" E., on the N-S center line of sec. 24. Over hills, through sagebrush and native grasses.
35.10	Dry wash, 10 lks. wide, drains W.
81.456	The 1/4 sec. cor. of secs. 13 and 24.
	<hr/> SUBDIVISION OF SECTION 25, T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/> From the 1/4 sec. cor. of secs. 25 and 36. N. 1°01'00" E., on the N-S center line of sec. 25. Over hills, through sagebrush and native grasses.
16.95	Barbed wire fence, bears N. 40° W. and S. 40° E.
81.807	The 1/4 sec. cor. of secs. 24 and 25.
	<hr/> SUBDIVISION OF SECTION 26, T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/> From the 1/4 sec. cor. of secs. 26 and 35. N. 0°33'20" E., on the N-S center line of sec. 26. Over hills, through sagebrush and native grasses.
8.30	Trail road, bears SE. and NW.
12.10	Clover Creek, 10 lks. wide, course S. 80° E.
41.169	Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E-W center line.

SUBDIVISION OF SECTION 26,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T39N R31E C 1/4 S26</p> <p style="text-align: center;">2002</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
83.20	Dry wash, 20 lks. wide, drains E.
84.214	The 1/4 sec. cor. of secs. 23 and 26.
<hr/>	
	<p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>N. 86°57'10" W., on the E-W center line of sec. 26. Over hills, through sagebrush and native grasses.</p>
6.20	Trout Creek, 10 lks. wide, course S. 5° W.
11.10	Trout Creek Road, 30 lks. wide, bears N. 10° W. and S. 10° E.
21.087	Point for the C-E 1/16 sec. cor. of sec. 26.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C <math>\frac{\quad}{S26}</math> C</p> <p style="text-align: center;">2002</p>
21.26	Barbed wire fence, bears N. and S.
42.174	The center 1/4 sec. cor. of sec. 26.
79.20	Clover Creek, 10 lks. wide, course SE.
82.70	Trail road, bears NW. and SE.
83.603	The 1/4 sec. cor. of secs. 26 and 27.
<hr/>	
	<p>From the C-E 1/16 sec. cor. of sec. 26.</p> <p>N. 0°41'40" E., on the N-S center line of the NE1/4 of sec. 26. Over hills, through sagebrush and native grasses.</p>
30.00	Dry wash, 20 lks. wide, drains SE.
42.240	The E 1/16 sec. cor. of secs. 23 and 26.
<hr/>	
	<p>From the E 1/16 sec. cor. of secs. 26 and 35.</p> <p>N. 0°46'00" E., on the N-S center line of the SE1/4 of sec. 26.</p>

SUBDIVISION OF SECTION 26,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over hills, through sagebrush and native grasses.
2.70	Clover Creek, 10 lks. wide, course S. 85° E.
6.00	Spur, slopes SE.
40.897	The C-E 1/16 sec. cor. of sec. 26.
<hr/> <p>SUBDIVISION OF SECTION 36, T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes the 2001-04 dependent resurvey of the N. bdy. of T. 38 N., R. 31 E., executed concurrently under Group No. 802, with a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>N. 1°15'30" E., on the N-S center line of sec. 36.</p> <p>Over hills, through sagebrush and native grasses.</p>
4.10	Dry wash, 20 lks. wide, drains SE.
8.50	Ditch, 10 lks. wide, 2 ft. deep, drains S. 50° E.
12.10	Trout Creek, 10 lks. wide, course S. 45° E.
19.255	Point for the C-S 1/16 sec. cor. of sec. 36.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} C \\ S\ 1/16\   \ S36 \\ C \end{array}</math> </p> <p style="text-align: center;">2002</p>
38.510	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} T39N\ R31E \\ C\ 1/4\ S36 \end{array}</math> </p> <p style="text-align: center;">2002</p>
49.60	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Trail road, bears NE. and SW.</p>

SUBDIVISION OF SECTION 36,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
59.118	Point for the C-N 1/16 sec. cor. of sec. 36.  POINT NOT MONUMENTED
71.70	Dry wash, 20 lks. wide, drains SW.
79.10	Dry wash, 15 lks. wide, drains SW.
79.726	The 1/4 sec. cor. of secs. 25 and 36. <hr/>
	From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp.  S. 83°54'40" W., on the E-W center line of sec. 36.  Over flats, through sagebrush and native grasses.
20.317	Point for the C-E 1/16 sec. cor. of sec. 36.  POINT NOT MONUMENTED
40.634	The center 1/4 sec. cor. of sec. 36.
49.90	Trail road, bears NE. and SW.
53.60	Trout Creek, 10 lks. wide, course S. 30° E.
58.80	Ditch, 10 lks. wide, 2 ft. deep, drains S. 25° E.
60.748	Point for the C-W 1/16 sec. cor. of sec. 36.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.  $\begin{array}{c} \text{W } 1/16 \\ \text{C } \frac{\quad}{\quad} \text{C} \\ \text{S36} \\ 2002 \end{array}$
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
61.00	Trout Creek Road, 30 lks. wide, bears N. 25° W. and S. 25° E.
69.00	Dry wash, 20 lks. wide, drains SE.
80.862	The 1/4 sec. cor. of secs. 35 and 36. <hr/>
	From the E 1/16 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 2001-04 dependent resurvey of the N. bdy. of T. 38 N., R. 31 E., executed concurrently under Group No. 802, with a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, N. of cor.  N. 1°08'40" E., on the N-S center line of the SE1/4 of sec. 36.  Over flats, through sagebrush and native grasses.

SUBDIVISION OF SECTION 36,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.839	<p>Point for the SE 1/16 sec. cor. of sec. 36, at intersection with the E-W center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S36</p> <p style="text-align: center;">2002</p>
39.678	<p>The point for the C-E 1/16 sec. cor. of sec. 36.</p> <hr/> <p>From the point for the S 1/16 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>S. 85°33'50" W., on the E-W center line of the SE1/4 of sec. 36.</p> <p>Over flats, through sagebrush and native grasses.</p>
20.293	The SE 1/16 sec. cor.
40.586	<p>The C-S 1/16 sec. cor. of sec. 36.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 1 and 36, on the S. Bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 2001-04 dependent resurvey of the N. bdy. of T. 38 N., R. 31 E., executed concurrently under Group No. 802, with a carsonite post, 5 ft. long, alongside the stainless steel post.</p> <p>N. 1°41'30" E., on the N-S center line of the SW1/4 of sec. 36.</p> <p>Over flats, through sagebrush and native grasses.</p>
28.60	Dry wash, 20 lks. wide, drains SE.
36.80	Trout Creek Road, 30 lks. wide, bears N. 25° W. and S. 25° E.
37.368	<p>The C-W 1/16 sec. cor. of sec. 36.</p> <hr/> <p>N. 1°15'00" E., on the N-S center line of the NW1/4 of sec. 36.</p> <p>Over flats, through sagebrush and native grasses.</p>
3.90	Ditch, 10 lks. wide, 2 ft. deep, drains S. 25° E.
14.40	Trout Creek, 10 lks. wide, course S. 25° E.
20.516	Point for the NW 1/16 sec. cor. of sec. 36, at intersection with the E-W center line of the NW1/4.

SUBDIVISION OF SECTION 36,  
T. 39 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S36</p> <p style="text-align: center;">2002</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>41.032 The point for the W 1/16 sec. cor. of secs. 25 and 36.</p> <hr/> <p>From the point for the C-N 1/16 sec. cor. of sec. 36.</p> <p>S. 83°39'10" W., on the E-W center line of the NW1/4 of sec. 36.</p> <p>Over flats, through sagebrush and native grasses.</p> <p>11.30 Dry wash, 20 lks. wide, drains SW.</p> <p>20.128 The NW 1/16 sec. cor.</p> <p>22.20 Trout Creek, 10 lks. wide, course S. 20° E.</p> <p>27.00 Ditch, 10 lks. wide, 2 ft. deep, drains S. 20° E.</p> <p>30.60 Trout Creek Road, 30 lks. wide, bears N. 25° W. and S. 25° E.</p> <p>40.256 The N 1/16 sec. cor. of secs. 35 and 36.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area encompassed in this survey is located in Humboldt County. The terrain varies from small mountains in the northern portion to flats and gentle hills in the southern portion. Trout Creek drains southerly through the township. The soil varies from sandy clay loam and rocky in the higher elevations to sandy and gravelly in the lower elevations. The vegetation consists of sagebrush, bitterbrush, rabbit brush, meadow grass and other native grasses.</p> <p>Access to the area is by way of a well maintained county road that extends northerly and southerly through the township.</p> <p>No mineral formations of consequence were observed, however, prospecting has occurred in the northeasterly portion of the township.</p> <hr/>
--------	---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Duane R. Garoutte	Cadastral Surveyor
Clay W. Morrow	Surveying Technician
Louis D. Campbell	Survey Aid
Jeremiah J. Lee	Survey Aid

CERTIFICATE OF SURVEY

I, Don R. Aschenbach, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing date of the 17th day of July, 2002, and Supplemental Special Instructions bearing date of the 12th day of November, 2002, I have dependently resurveyed a portion of the south boundary of Township 40 North, Range 31 East; and dependently resurveyed the east boundary, a portion of the north boundary and a portion of the subdivisional lines, and subdivided certain sections, Township 39 North, Range 31 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUN 24 2013

(Date)



(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary of Township 40 North, Range 31 East; and the dependent resurvey of the east boundary, a portion of the north boundary and a portion of the subdivisional lines, and the subdivision of certain sections, Township 39 North, Range 31 East, Mount Diablo Meridian, Nevada, executed by Don R. Aschenbach, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 25 2013

(Date)



(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in T. 39 N., R. 31 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~