

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

THE EIGHTH STANDARD PARALLEL NORTH, THROUGH RANGE 51 EAST

AND A PORTION OF RANGE 52 EAST,

THE CORRECTIVE DEPENDENT RESURVEY

OF A PORTION OF THE WEST BOUNDARY,

AND THE DEPENDENT RESURVEY

OF A PORTION OF THE SUBDIVISIONAL LINES

AND PORTIONS OF CERTAIN MINERAL SURVEYS,

TOWNSHIP 40 NORTH, RANGE 51 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Brett K. Jefferson, Professional Land Surveyor, Nevada  
Don R. Aschenbach, Cadastral Surveyor  
Bradley F. Dillon, Cadastral Surveyor  
Michael O. Jones, Cadastral Surveyor  
Mark G. Petrosine, Surveying Technician

Under Contract No. L06PC90210,  
Special Instructions dated June 2, 2009,  
and approved June 2, 2009,  
Supplemental Special Instructions dated December 17, 2009,  
and approved December 17, 2009,  
which provided for the surveys included under Group No. 876,  
and Assignment Instructions dated August 4, 2009,  
June 5, 2012, July 16, 2014 and October 1, 2019.

Survey commenced August 17, 2009  
Survey completed October 24, 2019

# INDEX DIAGRAM

TOWNSHIP 40 NORTH, RANGE 51 EAST, MOUNT DIABLO MERIDIAN, NEVADA

		31	32		33		34		35		36		31
		8	8		7		6		5		3		2
R50E	R51E											R51E	R52E
	10 6	60 5	48 4	39 3	29 2	20 1							
	59	59	47	38	28	19							
S 3	7	58 8	46 9	37 10	27 11	19 12							
	57	56	46	36	27	18							
	18	55 17	44 16	35 15	26 14	17 13							
		55	44	34	25	17							
	19	54 20	43 21	34 22	24 23	16 24							
	53	52	42	33	24	15							
	30	51 29	41 28	32 27	23 26	13 25							
	51	50	40	32	22	13							
	31	49 32	40 33	31 34	22	35	12 36						

- Mineral Survey No. 46, Office No. 1566 ..... PP. 62-64
- Mineral Survey No. 48, Office No. 1568 ..... PP. 65-66
- Mineral Survey No. 49, Office No. 1569 ..... PP. 67-68
- Mineral Survey No. 1817 ..... PP. 68-72
- Mineral Survey No. 4094 ..... P. 73

## TOWNSHIP 40 NORTH, RANGE 51 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The following field notes are those of the dependent resurvey of the Eighth Standard Parallel North, through Range 51 East and a portion of Range 52 East, the corrective dependent resurvey of a portion of the west boundary, and the dependent resurvey of a portion of the subdivisional lines and portions of certain mineral surveys, T. 40 N., R. 51 E., Mount Diablo Meridian, Nevada.

A portion of the north boundary (Eighth Standard Parallel North), the east boundary, a portion of the south boundary and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyors A.J. Hatch and J.H. Eaton in 1870-1871 under Contract No. 41. A portion of the north boundary (Eighth Standard Parallel North) was resurveyed and a portion of the north boundary (Eighth Standard Parallel North) was surveyed by U.S. Deputy Surveyor F. Bell in 1882 under Contract No. 147. The west boundary and a portion of the south boundary were surveyed by U.S. Deputy Surveyor T. K. Stewart in 1884 under Contract No. 170. A portion of the subdivisional lines were retraced and the remaining subdivisional lines were surveyed by U.S. Deputy Surveyors E.C. McClellan and E.L. Bridges in 1884 under Contract No. 171. A portion of the north boundary (Eighth Standard Parallel North) and the west boundary was dependently resurveyed by Cadastral Surveyors N.R. Forsyth, E.W. Sibley and R.A. Pratt in 1970-1974 under Group No. 473. A portion of the north boundary (Eighth Standard Parallel North), the south and east boundaries, the south one-half mile between sections 33 and 34 and certain mineral surveys were dependently resurveyed by Cadastral Surveyor J.A. Bastian in 1979-1981 under Group No. 574.

## HISTORY OF MINERAL SURVEYS PERTAINING TO RESURVEY

<u>Mineral Survey</u> (Office No.)	<u>Date</u>	<u>U.S. Mineral</u> <u>Surveyors</u>	<u>Cancellation Date</u> (If applicable)
M.S. 40 (1560)	1876	G.W. Garside	July 14, 1981
M.S. 41 (1561)	1877	C.C. Tracy	July 14, 1981
M.S. 42&38 (1562)	1877	C.C. Tracy	
M.S. 46 (1566)	1878	C.C. Tracy	
M.S. 48 (1568)	1885	R.M. Catlin	April 27, 1999
M.S. 49 (1569)	1885	R.M. Catlin	April 27, 1999
M.S. 50 (1570)	1885	E.C. McClellan	
M.S. 51 (1571)	1885	E.C. McClellan	
M.S. 1817	1898&	B.C. Jordan	
	(AM) 1899	F. Anderson	
M.S. 1875	1899	E.C. McClellan	
M.S. 4094	1912	E.A. Frissell	

Other mineral surveys not relevant to this survey are not included.

Before restoring the corners, the lines of the original surveys were retraced, and a diligent search made for any evidence of the original corners and other calls of the original field note record.

## TOWNSHIP 40 NORTH, RANGE 51 EAST, MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions for Group No. 876, dated June 2, 2009 and the Supplemental Special Instructions dated December 17, 2009.

Measurements were made with Trimble 4700, 5800 and R-8 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 1983 (CORS96) geographic position of the corner of sections 1, 2, 35 and 36, on the S. bdy. of the Tp., as determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) TUNG TUNGSTEN CORS ARP, BURN BURNS JUNCTION CORS ARP and LKN1 ELKO CORS ARP, in 2009, and carried forward by RTK observations is as follows:

Latitude: 41°18'47.940" N. Longitude: 116°11'58.725" W.

The 1987 mean magnetic declination is 16° E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "TUSCARORA, NEVADA" dated 1987.

---

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,  
THROUGH A PORTION OF RANGE 52 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of a Portion of the Survey Executed by  
U.S. Deputy Surveyors A.J. Hatch and J.H. Eaton in 1870,  
a Portion of the Resurvey Executed by  
U.S. Deputy Surveyor F. Bell in 1882  
and a Portion of the Dependent Resurvey executed by  
Cadastral Surveyor J.A. Bastian in 1979

---

Beginning at the standard 1/4 sec. cor. of sec. 31, T. 41 N., R. 52 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, in a mound of stone, 3 ft. diam., 1/2 ft. high, and a steel fence post alongside, with brass cap mkd. as described in the field notes of the dependent resurvey of the Eighth Standard Parallel North, through a portion of Range 52 East, executed under Group No. 574.

S. 89°32'50" W., on the S. bdy. of sec. 31.

1.00 Trail road, bears S. 15° E. and N. 15° W.

2.50 Base of mountains, bears SE. and NW.

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,  
THROUGH A PORTION OF RANGE 52 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
17.00	Spur, slopes NE.
27.339	The closing cor. of Tps. 40 N., Rs. 51 and 52 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Eighth Standard Parallel North, through a portion of Range 52 East, executed under Group No. 574, with a scattered mound of stone, S. of the cor.
30.50	Draw, drains NE.
40.255	The standard cor. of Tps. 41 N., Rs. 51 and 52 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the Eighth Standard Parallel North, through a portion of Range 52 East, executed under Group No. 574.
<hr/> <p>DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH, THROUGH RANGE 51 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyor F. Bell in 1882 and the Dependent Resurvey Executed by Cadastral Surveyors N.R Forsyth, E.W. Sibley and R.A. Pratt in 1970-1974</p> <hr/>	
	From the standard cor. of Tps. 41 N., Rs. 51 and 52 E., hereinbefore described.
	S. 89°58'40" W., on the S. bdy. of sec. 36.
7.326	The E 1/16 sec. cor. of sec. 1 only, T. 40 N., R. 51 E., hereinafter described.
11.70	Ridge, bears NE. and SW.
19.886	Point for the standard E 1/16 sec. cor. of sec. 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
<p>SC T41N R51E E 1/16 S36</p> <hr/>	
2009	

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 51 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
27.568	The 1/4 sec. cor. of sec. 1 only, T. 40 N., R. 51 E., hereinafter described.
37.30	Ravine, drains NE.
39.772	The standard 1/4 sec. cor. of sec. 36, monumented with a basalt stone, 11x10x3 ins., lying on top of an embedded mound of stone, 1 1/2 ft. diam., mkd. 1/4 on the bottom face, with a steel fence post alongside.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	SC T41N R51E 1/4 S36 <hr style="width: 10%; margin: auto;"/>
	2009
	Bury the mkd. stone and reset the steel fence post alongside the stainless steel post.
	<hr style="width: 30%; margin: auto;"/> N. 89°59'50" W., beginning new measurement.
19.811	Point for the standard W 1/16 sec. cor. of sec. 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	SC T41N R51E W 1/16 S36 <hr style="width: 10%; margin: auto;"/>
	2009
28.280	The closing cor. of secs. 1 and 2, T. 40 N., R. 51 E., hereinafter described.
38.60	Spur, slopes NE.
39.622	The standard cor. of secs. 35 and 36, determined at the center of an embedded mound of stone, 3 ft. diam., with a steel fence post set alongside. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 51 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">SC T41N R51E S35   S36 -----</p> <p style="text-align: center;">2009</p> <p>Build a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p> <hr/> <p>N. 89°54'30" W., on the S. bdy. of sec. 35.</p>
6.70	Southerly corner of rock foundation of cabin, 15 ft. square, bears NORTH, 1.80 chs. dist.
7.00	Spring branch in ravine, course NE.
20.439	Point for the standard E 1/16 sec. cor. of sec. 35.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">SC T41N R51E E 1/16 S35 -----</p> <p style="text-align: center;">2009</p>
28.657	The 1/4 sec. cor. of sec. 2 only, T. 40 N., R. 51 E., hereinafter described.
40.878	The standard 1/4 sec. cor. of sec. 35, determined at the center of an embedded mound of stone, 3 ft. diam. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">SC T41N R51E 1/4 S35 -----</p> <p style="text-align: center;">2009</p> <hr/>
	S. 89°21'40" W., beginning new measurement.
7.779	The W 1/16 sec. cor. of sec. 2 only, T. 40 N., R. 51 E., hereinafter described.
13.50	Ravine, drains N.

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 51 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
27.780	The closing cor. of secs. 2 and 3, T. 40 N., R. 51 E., hereinafter described.
29.50	Spur, slopes SW.
38.772	The standard cor. of secs. 34 and 35, monumented with a basalt stone, 10x10x8 ins., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, mkd. SC on the N. face.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           SC            T41N R51E            S34   S35            ————            2009         </div> Bury the mkd. stone alongside the stainless steel post.  <hr/> N. 89°23'40" W., on the S. bdy. of sec. 34.
27.195	The 1/4 sec. cor. of sec. 3 only, T. 40 N., R. 51 E., hereinafter described.
31.80	Ravine, drains NE.
38.002	Point for the standard 1/4 sec. cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           SC            T41N R51E            1/4 S34            ————            2009         </div>
65.382	The closing cor. of secs. 3 and 4, T. 40 N., R. 51 E., hereinafter described.
69.00	Ridge, bears N. and S.
76.004	Point for the standard cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 51 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	SC T41N R51E S33   S34 <hr style="width: 50px; margin: auto;"/> 2009
	N. 89°23'40" W., on the S. bdy. of sec. 33.
11.40	Cottonwood Creek, course N.
19.001	Point for the standard E 1/16 sec. cor. of sec. 33.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	SC T41N R51E E 1/16 S33 <hr style="width: 50px; margin: auto;"/> 2009
27.632	The 1/4 sec. cor. of sec. 4 only, T. 40 N., R. 51 E., hereinafter described.
38.002	The standard 1/4 sec. cor. of sec. 33, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 5 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the Eighth Standard Parallel North, through a portion of Range 51 East, executed under Group No. 473, with a steel fence post set alongside.  Add 2009 to brass cap and rebuild the mound of stone, 5 ft. base, to top.
	<hr style="width: 50%; margin: auto;"/> N. 89°39'40" W., beginning new measurement.
27.883	The closing cor. of secs. 4 and 5, T. 40 N., R. 51 E., hereinafter described.
32.50	Spur, slopes S.
39.026	Point for the standard cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 51 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">SC T41N R51E S32   S33 ----- 2009</p>
	N. 89°39'40" W., on the S. bdy. of sec. 32.
8.40	Head of ravine, drains NW.
27.864	The 1/4 sec. cor. of sec. 5 only, T. 40 N., R. 51 E., hereinafter described.
35.00	Ravine, drains SW.
39.026	Point for the standard 1/4 sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p>SC T41N R51E 1/4 S32 ----- 2009</p>
55.00	Spur, slopes S.
66.871	The closing cor. of secs. 5 and 6, T. 40 N., R. 51 E., hereinafter described.
78.052	The standard cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p>SC T41N R51E S31   S32 ----- 2009</p>
	N. 89°39'40" W., on the S. bdy. of sec. 31.
8.350	The E 1/16 sec. cor. of sec. 6 only, T. 40 N., R. 51 E., hereinafter described.
13.75	Creek, course N.
19.513	Point for the standard E 1/16 sec. cor. of sec. 31.

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 51 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">SC T41N R51E E 1/16 S31</p> <hr style="width: 10%; margin: auto;"/>
	2009
27.881	The 1/4 sec. cor. of sec. 6 only, T. 40 N., R. 51 E., hereinafter described.
36.00	Spur, slopes ENE.
39.026	Point for the standard 1/4 sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">SC T41N R51E 1/4 S31</p> <hr style="width: 10%; margin: auto;"/>
	2009
50.00	Ravine, drains ENE.
58.539	Point for the standard W 1/16 sec. cor. of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">SC T41N R51E W 1/16 S31</p> <hr style="width: 10%; margin: auto;"/>
	2009
62.25	Ravine, drains SE.
63.974	The closing cor. of Tps. 40 N., Rs. 50 and 51 E., hereinafter described.
78.052	The standard cor. of Tps. 41 N., Rs. 50 and 51 E., determined at the center of a toppled mound of stone, 6 ft. diam., with an iron post, 2 1/2 ins. diam., 28 ins. long, lying loose on top, with brass cap mkd. as described in the field notes of the dependent resurvey of the Eighth Standard Parallel North, through a portion of Range 51 East, executed under Group No. 473.

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 51 EAST,  
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Reset iron post, 6 ins. in the ground, to solid rock, and rebuild mound of stone, 4 ft. base, to top, around iron post.</p>
	<p>CORRECTIVE DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor T.K. Stewart in 1884 and Correction of a Portion of the Dependent Resurvey Executed by Cadastral Surveyors N.R. Forsyth, E.W. Sibley and R.A. Pratt in 1970-1974</p>
	<p>From the cor. of secs. 6 and 7, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 40 N., R. 51 E., executed under Group No. 473, with a mound of stone, 3 ft. diam., 2 ft. high, N. of cor.</p>
	<p>N. 12°41'30" E., on the W. bdy. of sec. 6.</p>
14.40	<p>Draw, drains NE.</p>
20.831	<p>Point for the S 1/16 sec. cor. of sec. 6 only.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S 1/16 S 6</p> <p style="text-align: center;">2009</p>
33.70	<p>Trail road on ridge, bears N. 70° E. and S. 70° W.</p>
41.662	<p>Point for the 1/4 sec. cor. of sec. 6 only, at proportionate distance, utilizing the original field notes; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E 1/4 S 6</p> <p style="text-align: center;">2009</p>

CORRECTIVE DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS															
	<p>From this point, the 1974 iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 40 N., R. 51 E., executed under Group No. 473, with a mound of stone, 3 ft. diam., 1 ft. high, E. of cor. bears N. 89°51'40" E., 1.120 chs. dist. This position was erroneously monumented, does not represent the best available evidence of the position of the original corner, and no longer functions as the 1/4 sec. cor. of sec. 6, T. 40 N., R. 51 E. Add the marks AM 2009 to the brass cap.</p>														
62.509	<p>Point for the N 1/16 sec. cor. of sec. 6 only, at proportionate distance utilizing the area relationships shown on the original plat.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td style="border-right: 1px solid black; padding: 2px;">T40N</td><td></td></tr> <tr><td style="border-right: 1px solid black; padding: 2px;">R51E</td><td></td></tr> <tr><td style="border-right: 1px solid black; padding: 2px;">N 1/16</td><td></td></tr> <tr><td style="border-right: 1px solid black; padding: 2px;">S 6</td><td></td></tr> </table> <p>2009</p> </div>	T40N		R51E		N 1/16		S 6							
T40N															
R51E															
N 1/16															
S 6															
63.50	Draw, drains NE.														
76.00	Spur, slopes E.														
80.40	Fence, bears E. and W.														
82.949	<p>The 1973 closing cor. of Tps. 40 N., Rs. 50 and 51 E., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 40 N., R. 51 E., executed under Group No. 473, with a mound of stone, 3 ft. diam., 1 ft. high, S. of cor. Add the marks AM to the brass cap and bury the iron pipe in place, 6 ins. below the ground.</p>														
82.974	<p>Intersect the Eighth Standard Parallel North.</p> <p>Point for the closing cor. of Tps. 40 N., Rs. 50 and 51 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td style="padding: 2px;">T41N</td><td style="padding: 2px;">R51E</td></tr> <tr><td style="padding: 2px;">S31</td><td></td></tr> <tr><td colspan="2" style="padding: 2px;">-----</td></tr> <tr><td style="padding: 2px;">S 3</td><td style="padding: 2px;">S 6</td></tr> <tr><td style="padding: 2px;">R50E</td><td style="padding: 2px;">R51E</td></tr> <tr><td colspan="2" style="padding: 2px;">CC</td></tr> <tr><td colspan="2" style="padding: 2px;">T40N</td></tr> </table> <p>2009</p> </div>	T41N	R51E	S31		-----		S 3	S 6	R50E	R51E	CC		T40N	
T41N	R51E														
S31															
-----															
S 3	S 6														
R50E	R51E														
CC															
T40N															

CORRECTIVE DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this point, the standard W 1/16 sec. cor. of sec. 31, T. 41 N., R. 51 E., hereinbefore described, bears S. 89°39'40" E., 5.435 chs. dist.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors A.J. Hatch and J.H. Eaton in 1871 and the Retracement and Survey Executed by U.S. Deputy Surveyors E.C. McClellan and E.L. Bridges in 1884</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the north boundary, T. 39 N., R. 51 E., executed under Group No. 574.</p> <p>N. 0°53'50" W., bet. secs. 35 and 36.</p>
20.80	Ravine, drains SE.
24.50	Trail road, bears S. 40° E. and N. 40° W.
25.60	Improved gravel road to Tuscarora, Nevada, 30 lks. wide, bears N. 75° E. and S. 75° W.
27.40	Trail road, bears S. 65° E. and N. 65° W.
41.00	Ravine, drains ENE.
41.731	<p>The 1/4 sec. cor. of secs. 35 and 36, monumented with the remains of wood fragments. These wood fragments correlate well with other original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E 1/4 S35 S36  2009</p>
	<p>N. 0°39'30" E., beginning new measurement.</p>
1.00	Trail road, bears N. 70° E. and S. 70° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
7.90	Trail road, bears N. 30° E. and S. 30° W.								
9.30	Ravine, drains E.								
24.60	Ravine, drains SE.								
29.80	Ravine, drains SE.								
40.723	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance, utilizing an old fence at the 1/4 sec. cor. of secs. 25 and 36 for the east control; there is no remaining evidence of the original corner.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T40N</td><td>R51E</td></tr> <tr><td>S26</td><td>S25</td></tr> <tr><td colspan="2" style="text-align: center;">— —</td></tr> <tr><td>S35</td><td>S36</td></tr> </table>	T40N	R51E	S26	S25	— —		S35	S36
T40N	R51E								
S26	S25								
— —									
S35	S36								
	2009								
	<hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the resurvey of the west boundary, T. 40 N., R. 52 E., executed under Group No. 574.</p>								
	N. 88°12'10" W., bet. secs. 25 and 36.								
39.906	Point for the 1/4 sec. cor. of secs. 25 and 36, determined latitudinally on line between the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp. and the cor. of secs. 25, 26, 35 and 36, and longitudinally at an old fence, bears N. 0°40' E. and S. 0°40' W.								
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T40N</td><td>R51E</td></tr> <tr><td>S25</td><td></td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td>S36</td><td></td></tr> </table>	T40N	R51E	S25		1/4	—	S36	
T40N	R51E								
S25									
1/4	—								
S36									
	2019								
64.40	Trail road, bears N. 30° E. and S. 30° W.								
80.620	The cor. of secs. 25, 26, 35 and 36.								
	<hr/> <p>N. 3°52'50" W., bet. secs. 25 and 26.</p>								
11.10	Draw, drains ESE.								
18.20	Fence, bears N. 88° E. and S. 88° W.								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.417	<p>Point for the S 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S 1/16 S26 S25</p> <p style="text-align: center;">2009</p>
29.20	Draw, drains E.
40.834	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E 1/4 S26 S25</p> <p style="text-align: center;">2009</p>
44.10	Draw, drains ESE.
61.231	<p>Point for the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E N 1/16 S26 S25</p> <p style="text-align: center;">2009</p>
54.00	Base of mountain.
72.70	Fence, bears S. 50° E. and N. 50° W.
81.628	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a granite stone, 14x9x7 ins., loosely set in an embedded mound of stone, 3 ft. diam., mkd. with 2 grooves on the S. face and 1 groove on the E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T40N R51E S23   S24 <hr style="width: 50%; margin: auto;"/> S26   S25  2009
	Bury the mkd. stone alongside the stainless steel post.
	<hr/> From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 40 N., R. 52 E., executed under Group No. 574.  S. 89°41'20" W., bet. secs. 24 and 25.
1.60	Trail road, bears S. 45° E. and N. 45° W.
11.00	Sixmile Canyon Creek, 15 lks. wide, course S.
18.70	Branch of Sixmile Canyon Creek, course S.
20.10	Trail road, bears N. 35° E. and S. 35° W.
35.50	Fence, bears S. 37° E. and N. 37° W.
39.782	The 1/4 sec. cor. of secs. 24 and 25, monumented with a basalt stone, 17x10x8 ins., firmly set in an embedded mound of stone, 3 ft. diam., faintly mkd. with illegible scribing on N. face, with a steel fence post alongside.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T40N R51E S24 1/4 — S25  2009
	Bury the mkd. stone alongside the stainless steel post.
	<hr/> N. 84°55'50" W., beginning new measurement.
9.20	Ridge, bears N. and S., on spur, slopes S.
25.10	Ravine, drains S.
46.807	The cor. of secs. 23, 24, 25 and 26.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 1°53'40" W., bet. secs. 23 and 24.
16.80	Ridge, bears E. and W.
20.190	Point for the S 1/16 sec. cor. of secs. 23 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T40N R51E S 1/16 S23 S24  2009
36.30	Sixmile Canyon Creek, 10 lks. wide, course NE.
40.380	The 1/4 sec. cor. of secs. 23 and 24, determined at the center of remnants of a wood post lying on top of an embedded mound of stone, 3 ft. diam.  At the corner point  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.  T40N R51E 1/4 S23 S24  2009
	N. 1°29'40" W., beginning new measurement.
6.90	Trail road, bears E. and W.
11.30	Trail road, bears S. 30° E. and N. 30° W.
14.10	Ravine, drains SE.
19.881	Point for the N 1/16 sec. cor. of secs. 23 and 24.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T40N R51E N 1/16 S23 S24  2009

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
39.762	<p>The cor. of secs. 13, 14, 23 and 24, monumented with a granite stone, 31x7x6 ins., loosely set, mkd. with 3 grooves on the S. face and 1 groove on the E. face, with an embedded mound of stone, 3 ft. diam., S. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" data-bbox="867 602 1013 716"> <tr> <td>T40N</td> <td>R51E</td> </tr> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> </table> <p>2009</p> </div> <p>Reset the mkd. stone alongside the stainless steel post.</p>	T40N	R51E	S14	S13	S23	S24		
T40N	R51E								
S14	S13								
S23	S24								
	<p>From the cor. of secs. 13 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 40 N., R. 52 E., executed under Group No. 574, with a mound of stone, 3 ft. diam., 1 ft. high, W. of cor.</p>								
	<p>N. 87°49'30" W., bet. secs. 13 and 24.</p>								
2.80	<p>Ravine, drains NE.</p>								
31.70	<p>Ravine, drains S.</p>								
44.321	<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1" data-bbox="867 1417 1013 1531"> <tr> <td>T40N</td> <td>R51E</td> </tr> <tr> <td></td> <td>S13</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S24</td> </tr> </table> <p>2009</p> </div>	T40N	R51E		S13	1/4	—		S24
T40N	R51E								
	S13								
1/4	—								
	S24								
64.70	<p>Ridge, bears SE. and NW.</p>								
88.642	<p>The cor. of secs. 13, 14, 23 and 24.</p>								
	<p>N. 4°00'00" E., bet. secs. 13 and 14.</p>								
22.30	<p>Top of ridge, bears SE. and NW.</p>								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
38.660	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E 1/4 S14   S13</p> <p style="text-align: center;">2019</p>
45.70	Trail road, bears SE. and NW.
58.40	Ridge, bears E. and NW.
77.320	<p>Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S11   S12 ----- S14   S13</p> <p style="text-align: center;">2019</p>
	<p>From the cor. of secs. 12 and 13, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 40 N., R. 52 E., executed under Group No. 574.</p> <p>N. 88°16'30" W., bet. secs. 12 and 13.</p>
1.20	Trail road, bears NE. and SW.
32.50	Ravine, drains NE.
41.302	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S12 1/4 — S13</p> <p style="text-align: center;">2019</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
82.604	The cor. of secs. 11, 12, 13 and 14.
	N. 0°58'10" E., bet. secs. 11 and 12.
21.50	Ravine, drains NE.
38.572	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T40N R51E 1/4 S11   S12 2019</p>
57.858	Point for the N 1/16 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T40N R51E N 1/16 S11   S12 2019</p>
72.70	Deep ravine, drains NE.
77.144	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T40N R51E S 2   S 1 ----- S11   S12 2019</p>
	<p>From the cor. of secs. 1 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 40 N., R. 52 E., executed under Group No. 574.</p>
	S. 89°25'30" W., bet. secs. 1 and 12.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
15.30	Top of knob, bears N. and S.
40.806	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, 1/2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S 1 1/4 — S12</p> <p style="text-align: center;">2019</p>
61.209	<p>Point for the W 1/16 sec. cor. of secs. 1 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S 1 W 1/16 — S12</p> <p style="text-align: center;">2019</p>
78.80	Deep ravine, drains NE.
81.612	The cor. of secs. 1, 2, 11 and 12.
	N. 0°17'10" E., bet. secs. 1 and 2.
7.80	Trail road, bears N. 70° E. and S. 70° W.
19.283	<p>Point for the S 1/16 sec. cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S 1/16 S 2   S 1</p> <p style="text-align: center;">2019</p>
38.566	Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance, utilizing the original field notes; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E 1/4 S 2   S 1</p> <p style="text-align: center;">2019</p> <p>Cor. is located on ridge, bears ENE. and WSW.</p> <p>76.660 Intersect the Eighth Standard Parallel North.</p> <p>Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T41N R51E S36 ----- S 2   S 1 T40N   R51E CC</p> <p style="text-align: center;">2009</p> <p>From this point, the standard cor. of secs. 35 and 36, T. 41 N., R. 51 E., hereinbefore described, bears N. 89°59'50" W., 11.342 chs. dist.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 1 only, is at midpoint in departure on the N. bdy. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T41N R51E ----- 1/4 S 1 T40N R51E</p> <p style="text-align: center;">2009</p> <p>From this point, the standard E 1/16 sec. cor. of sec. 36, T. 41 N., R. 51 E., hereinbefore described, bears N. 89°58'40" E., 7.682 chs. dist.</p> <hr/> <p>The point for the E 1/16 sec. cor. of sec. 1 only, is at midpoint in departure, bet. the closing cor. of Tps. 40 N., Rs. 51 and 52 E. and the 1/4 sec. cor. of sec. 1 only, on the N. bdy. of sec. 1.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS					
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T41N R51E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">E 1/16 S 1 T40N R51E</p> <p style="text-align: center;">2009</p> <p>From this point, the standard cor. of Tps. 41 N., Rs. 51 and 52 E., hereinbefore described, bears N. 89°58'40" E., 7.326 chs. dist.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivision lines, T. 40 N., R. 51 E., executed under Group No. 574, with a mound of stone, 2 1/2 ft. diam., 1 ft. high, W. of cor.</p> <p>N. 1°33'20" E., bet. secs. 34 and 35.</p>				
2.50	Ravine, drains SE.				
5.616	Intersect line 2-3, Mineral Survey No. 4094, Phoenix lode, at a point from which Cor. No. 1, Mineral Survey No. 4094, New Homesdale lode, on line 2-3, Mineral Survey No. 4094, Phoenix lode, hereinafter described, bears N. 62°08'10" W., 0.823 chs. dist.				
17.70	Ravine, drains SE.				
38.10	Ravine, drains SE.				
39.482	<p>The cor. of secs. 26, 27, 34 and 35, determined at the center of an embedded mound of stone, 1 1/2 ft. diam. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black;">S27</td> <td style="border-bottom: 1px solid black;">S26</td> </tr> <tr> <td style="border-right: 1px solid black;">S34</td> <td>S35</td> </tr> </table> <p style="text-align: center;">2009</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°37'40" W., bet. secs. 26 and 35.</p>	S27	S26	S34	S35
S27	S26				
S34	S35				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.50	Ravine, drains SE.
41.105	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.  T40N R51E S26 1/4 — S35  2009
74.65	Trail road, bears S. 40° E. and N. 40° W.
82.210	The cor. of secs. 26, 27, 34 and 35. <hr/>
	N. 2°45'50" W., bet. secs. 26 and 27.
8.25	Trail road on top of ridge, bears S. 45° E. and N. 45° W.
22.80	Ravine, drains SE.
27.90	Trail road, bears N. 45° E. and S. 45° W.
34.30	Abandoned mining ditch, drains SW.
40.517	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.  T40N R51E 1/4 S27 S26  2009
62.00	Trail road, bears SE. and NW.
63.10	Abandoned mining ditch, drains SE.
64.80	Trail road, bears SE. and NW.
65.70	Stream, 8 lks. wide, course ESE.
66.70	Abandoned mining ditch, drains W.
81.075	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S22   S23 ----- S27   S26</p> <p style="text-align: center;">2009</p>
	<hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°17'40" W., bet. secs. 23 and 26.</p>
40.291	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S23 1/4 — S26</p> <p style="text-align: center;">2009</p>
48.90	Trail road, bears N. 40° E. and S. 40° W.
54.60	Ravine, drains SE.
60.40	Abandoned mining ditch, drains SW.
80.582	The cor. of secs. 22, 23, 26 and 27.
	<hr/> <p>N. 1°01'00" W., bet. secs. 22 and 23.</p>
35.80	Ridge, bears E. and W.
40.496	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with a porphyry stone, 14x6x4 ins., lying on top of an embedded mound of stone, 2 ft. diam., mkd. 1/4 on bottom face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E 1/4 S22   S23</p> <p style="text-align: center;">2009</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°09'40" E., beginning new measurement.</p>								
24.10	Abandoned mining ditch, drains NE.								
27.40	Ravine, drains NE.								
29.60	Sixmile Canyon Creek, 10 lks. wide, course S. 80° E.								
30.40	Remnants of tunnel, bears EAST 0.50 chs. dist.								
31.60	Trail road, bears SE. and NW.								
39.754	<p>The cor. of secs. 14, 15, 22 and 23, monumented with a quartzite stone, 23x12x6 ins., lying on top of the ground, with 2 grooves on a face and 3 grooves on another face, with a mound of stone, 3 ft. diam., 1 ft. high, E. of the cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T40N</td><td>R51E</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S22</td><td>S23</td></tr> </table> <p style="text-align: center;">2009</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°22'40" W., bet. secs. 14 and 23.</p>	T40N	R51E	S15	S14	<hr/>		S22	S23
T40N	R51E								
S15	S14								
<hr/>									
S22	S23								
18.20	Trail road, bears N. and S.								
18.90	Ravine, drains S.								
39.400	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T40N</td><td>R51E</td></tr> <tr><td>S14</td><td></td></tr> <tr><td>1/4</td><td><hr/></td></tr> <tr><td>S23</td><td></td></tr> </table> <p style="text-align: center;">2009</p>	T40N	R51E	S14		1/4	<hr/>	S23	
T40N	R51E								
S14									
1/4	<hr/>								
S23									
59.100	Point for the W 1/16 sec. cor. of secs. 14 and 23.								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S14 W 1/16 — S23</p> <p style="text-align: center;">2009</p>
64.70	Trail road on ridge, bears N. and SE.
78.800	The cor. of secs. 14, 15, 22 and 23.
	<hr/> <p>N. 0°08'30" W., bet. secs. 14 and 15.</p>
20.00	Remnants of tunnel, bears EAST, 1.10 chs. dist.
24.40	Remnants of shaft, bears EAST, 0.10 chs. dist.
40.471	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with a limestone, 15x8x7 ins., firmly set in an embedded mound of stone, 3 ft. diam., mkd. 1/4 on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E 1/4 S15 S14</p> <p style="text-align: center;">2009</p>
	<p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 2°16'00" E., beginning new measurement.</p>
3.60	Trail road on ridge, bears S. 55° E. and N. 55° W.
14.00	Ravine, drains ENE.
25.00	Ravine, drains SE.
36.00	Trail road on ridge, bears S. 55° E. and N. 55° W.
38.336	<p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T40N R51E S10   S11 <hr style="width: 50%; margin: 0 auto;"/> S15   S14  2009
	<hr/> From the cor. of secs. 11, 12, 13 and 14. N. 89°27'20" W., bet. secs. 11 and 14.
41.378	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	T40N R51E S11 1/4 ——— S14  2019
46.60	Ridge, bears SE. and NW.
78.70	Ravine, drains SE.
82.756	The cor. of secs. 10, 11, 14 and 15.
	<hr/> N. 1°47'20" E., bet. secs. 10 and 11.
2.10	Ravine, drains SE.
10.90	Trail road on ridge, bears SE. and NW.
11.40	Fence, bears S. 70° E. and N. 70° W.
19.162	Point for the S 1/16 sec. cor. of secs. 10 and 11.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T40N R51E S 1/16 S10   S11  2010
30.70	Trail road on ridge, bears NE. and SW.
38.324	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E 1/4 S10   S11  2009</p>
76.648	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S 3   S 2 ----- S10   S11  2009</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°48'50" W., bet. secs. 2 and 11.</p>
1.80	Ridge, bears NE. and SW.
22.10	Ravine, drains NE.
40.825	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, pressed into a zinc-coated iron pipe, 1 in. diam., 24 ins. long, cemented into a drill hole, 1 in. diam., drilled 12 ins. deep into bedrock surface, 2 ins. below the surface of the ground, with a plastic-encased magnet deposited at bottom of drill hole, and in a mound of stone, 4 ft. base, to top, with brass tablet mkd.</p> <p style="text-align: center;">T40N R51E S 2 1/4 — S11  2019</p>
48.70	Trail road on ridge, bears NE. and SW.
57.10	Ravine, drains NE.
81.650	The cor. of secs. 2, 3, 10 and 11.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 1°31'10" E., bet. secs. 2 and 3.
19.160	Point for the S 1/16 sec. cor. of secs. 2 and 3.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.  T40N R51E S 1/16 S 3 S 2  2009
21.70	Ridge, bears ENE. and WSW.
38.320	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T40N R51E 1/4 S 3 S 2  2010
48.50	Ravine, drains NE.
57.480	Point for the N 1/16 sec. cor. of secs. 2 and 3.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T40N R51E N 1/16 S 3 S 2  2010
61.50	Spur, slopes SE.
76.180	Intersect the Eighth Standard Parallel North.  Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T41N R51E  
S35

S 3	S 2
T40N	R51E
CC	

2009

From this point, the standard cor. of secs. 34 and 35, T. 41 N., R. 51 E., hereinbefore described, bears S.  $89^{\circ}21'40''$  W., 10.992 chs. dist.

The point for the 1/4 sec. cor. of sec. 2 only, is at midpoint in departure, on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

T41N R51E

1/4 S 2
T40N R51E

2009

From this point, the standard E 1/16 sec. cor. of sec. 35, T. 41 N., R. 51 E., hereinbefore described, bears S.  $89^{\circ}54'30''$  E., 8.218 chs. dist.

The point for the W 1/16 sec. cor. of sec. 2 only, is at midpoint in departure, bet. the closing cor. of secs. 2 and 3 and the 1/4 sec. cor. of sec. 2 only, on the N. bdy. of sec. 2.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, over a plastic-encased magnet, with brass cap mkd.

T41N R51E

W 1/16 S 2
T40N R51E

2009

Cor. is located in a stable rockslide on a steep W. slope.

From this point, the standard 1/4 sec. cor. of sec. 35, T. 41 N., R. 51 E., hereinbefore described, bears N.  $89^{\circ}21'40''$  E., 7.779 chs. dist.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the north boundary, T. 39 N., R. 51 E., executed under Group No. 574.</p>
	<p>N. 0°07'00" E., bet. secs. 33 and 34.</p>
13.80	<p>Ravine, drains SE.</p>
19.00	<p>Trail road, bears S. 30° E. and N. 30° W.</p>
28.70	<p>Ravine, drains ESE.</p>
35.80	<p>Ridge, bears SE. and NW.</p>
40.350	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E 1/4 S33 S34  2009</p>
40.50	<p>Ravine, drains SE.</p>
47.907	<p>Intersect line 6-7, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, at a point from which Cor. No. 6, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, hereinafter described, bears N. 74°17'10" W., 1.335 chs. dist.</p>
52.600	<p>Intersect line 5-6, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, at a point from which Cor. No. 6, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, hereinafter described, bears S. 16°38'50" W., 4.521 chs. dist.</p>
60.525	<p>Point for the N 1/16 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the corner monumented in 1871.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E N 1/16 S33 S34  2014</p>
64.70	<p>Trail road on ridge, bears S. 60° E. and N. 60° W.</p>
73.70	<p>Ravine, drains SE.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
80.700	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T40N</td> <td>R51E</td> </tr> <tr> <td>S28</td> <td>S27</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S33</td> <td>S34</td> </tr> </table> <p style="text-align: center;">2009</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°38'20" W., bet. secs. 27 and 34.</p>	T40N	R51E	S28	S27			S33	S34
T40N	R51E								
S28	S27								
S33	S34								
1.60	Ravine, drains SE.								
10.20	Trail road on low spur, bears N. 45° E. and S. 45° W.								
20.00	Ravine, drains SE.								
26.40	Abandoned mining ditch, drains SW.								
40.751	<p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>T40N</td> <td>R51E</td> </tr> <tr> <td></td> <td>S27</td> </tr> <tr> <td>1/4</td> <td>—</td> </tr> <tr> <td></td> <td>S34</td> </tr> </table> <p style="text-align: center;">2009</p>	T40N	R51E		S27	1/4	—		S34
T40N	R51E								
	S27								
1/4	—								
	S34								
72.80	Trail road, bears S. 50° E. and N. 50° W.								
74.00	Stream, 5 lks. wide, course SE.								
81.502	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 2°09'30" W., bet. secs. 27 and 28.</p>								
7.90	Stream, 5 lks. wide, course SE.								
9.00	Trail road, bears S. 45° E. and N. 45° W.								
40.379	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T40N R51E 1/4 S28   S27  2010
52.40	Ridge, bears SE. and NW.
64.50	Ravine, drains ESE.
80.30	Trail road on ridge, bears E. and W.
80.758	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T40N R51E S21   S22 ----- S28   S27  2010
	From the cor. of secs. 22, 23, 26 and 27. S. 89°26'10" W., bet. secs. 22 and 27.
20.80	Trail road, bears SE. and NW.
21.30	Ravine, drains SE.
37.50	Trail road, bears SE. and NW.
40.310	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.  T40N R51E S22 1/4 ——— S27  2009
57.40	Trail on ridge, bears SE. and NW.
64.70	Trail on ridge, bears ENE. and WSW.
80.620	The cor. of secs. 21, 22, 27 and 28.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 0°12'20" E., bet. secs. 21 and 22.
14.40	Ravine, drains ESE.
31.60	Spur, slopes SE.
40.351	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           T40N R51E            1/4            S21   S22             2010         </div>
44.40	Spur, slopes NE.
80.10	Sixmile Canyon Creek, 8 lks. wide, course E.
80.702	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  <div style="text-align: center;">           T40N R51E            S16   S15  <hr style="width: 50%; margin: 0 auto;"/>           S21   S22             2009         </div>
	From the cor. of secs. 14, 15, 22 and 23.  S. 89°45'30" W., bet. secs. 15 and 22.
2.90	Ravine, drains SSW.
13.30	Sixmile Canyon Creek, 8 lks. wide, course SE.
16.00	Abandoned mining ditch, drains SE.
20.40	Ravine, drains NE.
39.850	Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T40N R51E S15 1/4 — S22</p> <p>2009</p> <p>Cor. is located on the right bank of Sixmile Canyon Creek, course E.</p>
40.00	Sixmile Canyon Creek, 8 lks. wide, course ENE.
59.775	Point for the W 1/16 sec. cor. of secs. 15 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p>T40N R51E S15 W 1/16 — S22</p> <p>2009</p>
79.700	The cor. of secs. 15, 16, 21 and 22.
	N. 0°03'10" W., bet. secs. 15 and 16.
20.175	Point for the S 1/16 sec. cor. of secs. 15 and 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	<p>T40N R51E S 1/16 S16 S15</p> <p>2010</p>
40.350	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	<p>T40N R51E 1/4 S16 S15</p> <p>2010</p>
50.40	Stream in Arthur Canyon, 4 lks. wide, course SE.
75.00	Trail road on ridge, bears S. 84° E. and N. 84° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
75.10	Fence, bears S. 84° E. and N. 84° W.								
80.700	<p>The cor. of secs. 9, 10, 15 and 16, determined at the center of an embedded mound of stone, 3 ft. diam. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T40N R51E</td></tr> <tr><td>S 9</td><td>S10</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S16</td><td>S15</td></tr> </table> <p style="text-align: center;">2009</p>	T40N R51E		S 9	S10	— —		S16	S15
T40N R51E									
S 9	S10								
— —									
S16	S15								
	<hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p>								
	N. 87°38'40" W., bet. secs. 10 and 15.								
3.50	Trail road, bears S. 55° E. and N. 50° W.								
14.50	Spur, slopes S.								
20.644	<p>Point for the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T40N R51E</td></tr> <tr><td colspan="2">S10</td></tr> <tr><td>E 1/16</td><td>—</td></tr> <tr><td colspan="2">S15</td></tr> </table> <p style="text-align: center;">2010</p>	T40N R51E		S10		E 1/16	—	S15	
T40N R51E									
S10									
E 1/16	—								
S15									
41.288	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with a limestone, 24x10x7 ins., firmly set in an embedded mound of stone, 3 ft. diam., mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>								

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T40N R51E S10 1/4 — S15</p> <p>2009</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>S. 89°50'20" W., beginning new measurement.</p>
18.80	Top of flat ridge, bears E. and W.
19.958	Point for the W 1/16 sec. cor. of secs. 10 and 15.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p>T40N R51E S10 W 1/16 — S15</p> <p>2009</p>
34.45	A spring, bears NORTH, 5.80 chs. dist.
34.50	Ravine, drains NNE.
39.916	The cor. of secs. 9, 10, 15 and 16.
	<hr/> <p>N. 1°35'50" E., bet. secs. 9 and 10.</p>
13.00	Ravine, drains NE.
19.018	Point for the S 1/16 sec. cor. of secs. 9 and 10.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<p>T40N R51E S 1/16 S 9 S10</p> <p>2010</p>
38.036	Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T40N R51E 1/4 S 9   S10</p> <p style="text-align: center;">2009</p>
40.00	Ridge, bears NE. and SW.
66.70	Ravine, drains NE.
76.072	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E S 4   S 3 ----- S 9   S10</p> <p style="text-align: center;">2010</p>
	<hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°17'20" W., bet. secs. 3 and 10.</p>
12.90	Ridge, bears N. and S.
20.358	<p>Point for the E 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E S 3 E 1/16 — S10</p> <p style="text-align: center;">2010</p>
32.75	Ravine, drains NE.
40.716	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E S 3 1/4 — S10</p> <p style="text-align: center;">2010</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
81.432	The cor. of secs. 3, 4, 9 and 10.
	N. 5°19'40" E., bet. secs. 3 and 4.
26.90	Ridge, bears E. and W.
38.186	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T40N R51E
	1/4
	S 4   S 3
	2010
50.50	Ridge, bears ENE. and WSW.
64.40	Ravine, drains ESE.
76.038	Intersect the Eighth Standard Parallel North.
	Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T41N R51E
	S34
	S 4   S 3
	T40N   R51E
	CC
	2009
	From this point, the standard cor. of secs. 33 and 34, T. 41 N., R. 51 E., hereinbefore described, bears N. 89°23'40" W., 10.622 chs. dist.
	The point for the 1/4 sec. cor. of sec. 3 only, is at midpoint in departure on the N. bdy. of sec. 3.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T41N R51E <hr style="width: 10%; margin: auto;"/>1/4 S3 T40N R51E</p> <p style="text-align: center;">2009</p> <p>From this point, the standard 1/4 sec. cor. of sec. 34, T. 41 N., R. 51 E., hereinbefore described, bears N. 89°23'40" W., 10.807 chs. dist.</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of the north boundary, T. 39 N., R. 51 E., executed under Group No. 574.</p> <p>N. 0°11'00" E., bet. secs. 32 and 33.</p>
28.10	Ridge, bears E. and W.
40.851	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E 1/4 S32 S33</p> <p style="text-align: center;">2009</p>
72.20	Ridge, bears SE. and NW.
81.702	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E S29 S28 <hr style="width: 10%; margin: auto;"/>S32 S33</p> <p style="text-align: center;">2009</p> <p>Cor. is located in the saddle of a major ridge, bears NNE. and SSW.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°54'30" W., bet. secs. 28 and 33.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.40	Ravine, drains SE.
26.40	Ravine, drains ENE.
36.50	Ravine, drains SE.
40.750	Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T40N R51E S28 1/4 — S33  2009
51.00	Ridge, bears SE. and NW.
81.500	The cor. of secs. 28, 29, 32 and 33. <hr/>
	N. 1°32'20" W., bet. secs. 28 and 29.
14.80	Top of ridge, bears N. and SSW: thence along ridge.
26.50	Leave ridge, bears NNE. and S.
40.866	Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.  T40N R51E 1/4 S29 S28  2009
	From this point, National Geodetic Survey control (formerly U.S. Coast and Geodetic Survey triangulation) station "Blitzen" bears N. 57°34'20" E., 11.382 chs. dist., monumented with a standard bronze disc, 3 1/2 ins. diam., firmly set in ledge rock, mkd. BLITZEN 1940 and a triangle.
61.299	Point for the N 1/16 sec. cor. of secs. 28 and 29.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T40N R51E N 1/16 S29 S28</p> <p style="text-align: center;">2009</p>
	<p>Cor. is located in trail road to Mt. Blitzen, bears E. and W.</p>
62.47	<p>Fence, bears S. 70° E. and N. 70° W.</p>
81.732	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E S20 S21 ----- S29 S28</p> <p style="text-align: center;">2009</p> <p>Set aspen post, 4 ins. diam., alongside the stainless steel post.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p>
	<p>N. 89°11'50" W., bet. secs. 21 and 28.</p>
17.00	<p>Trail road on ridge, bears SE. and NW.</p>
40.322	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E S21 1/4 ——— S28</p> <p style="text-align: center;">2009</p>
50.00	<p>Trail road, bears N. 70° E. and S. 20° W., on ridge, bears NE. and SW.</p>
60.483	<p>Point for the W 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T40N R51E S21 W 1/16 — S28  2009
80.644	The cor. of secs. 20, 21, 28 and 29. <hr/>
	N. 0°51'00" E., bet. secs. 20 and 21.
2.30	Spring, bears EAST, 1.00 chs. dist.
2.70	Spring, bears WEST, 1.70 chs. dist.
12.00	Stream, 5 lks. wide, course NE.
38.60	Ridge, bears E. and W.
40.856	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.  T40N R51E 1/4 S20 S21  2009
	Set an aspen post, 4 ins. diam., alongside the stainless steel post.
55.90	Sixmile Canyon Creek, 5 lks. wide, course ENE.
61.284	Point for the N 1/16 sec. cor. of secs. 20 and 21.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  T40N R51E N 1/16 S20 S21  2009
72.30	Ridge, bears SE. and NW.
81.712	The cor. of secs. 16, 17, 20 and 21, determined at the center of an embedded mound of stone, 3 ft. diam. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.  At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S17   S16 ----- S20   S21</p> <p style="text-align: center;">2009</p>
	<hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 88°28'10" W., bet. secs. 16 and 21.</p>
6.00	Ravine, drains SE.
19.932	Point for the E 1/16 sec. cor. of secs. 16 and 21.
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented in a drill hole in solid rock outcrop, with top mkd.</p> <p style="text-align: center;">T40N R51E S16 E 1/16 ——— S21</p> <p style="text-align: center;">2009</p>
39.864	Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S16 1/4 ——— S21</p> <p style="text-align: center;">2009</p>
42.50	Ravine, drains S.
58.20	Stream, 5 lks. wide, course SE.
79.728	The cor. of secs. 16, 17, 20 and 21.
	<hr/> <p>N. 1°09'50" E., bet. secs. 16 and 17.</p>
15.00	Stream, 5 lks. wide, course E.
15.80	Trail road, bears N. 55° E. and S. 55° W.
19.905	Point for the S 1/16 sec. cor. of secs. 16 and 17.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S 1/16 S17 S16</p> <p style="text-align: center;">2009</p>
25.20	Trail road, bears S. 20° E. and N. 20° W.
36.50	Trail road, bears N. 25° E. and S. 25° W.
39.810	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with a granite stone, 14x10x4 ins., firmly set in an embedded mound of stone, 3 ft. diam., mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E 1/4 S17 S16</p> <p style="text-align: center;">2009</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°46'00" W., beginning new measurement.</p>
7.00	Ridge, bears E. and W.
20.076	<p>Point for the N 1/16 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E N 1/16 S17 S16</p> <p style="text-align: center;">2009</p>
23.10	Ravine, near head of Arthur Canyon, drains E.
30.00	Trail road, bears E. and W.
40.152	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T40N R51E S 8   S 9 <hr style="width: 50%; margin: 0 auto;"/> S17   S16  2009  Set steel fence post alongside the stainless steel post.
	<hr/> From the cor. of secs. 9, 10, 15 and 16. N. 89°00'20" W., bet. secs. 9 and 16.
8.80	Trail road, bears N. and S.
15.20	Ridge, bears NE. and SW.
24.70	Ravine, drains S.
35.50	Top of knoll.
39.674	Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T40N R51E S 9 1/4 — S16  2009
41.60	Trail road, bears N. 35° E. and S. 35° W.
57.10	Ridge, bears SE. and NW.
79.348	The cor. of secs. 8, 9, 16 and 17.
	<hr/> N. 1°18'00" E., bet. secs. 8 and 9.
8.50	Spur, slopes SE.
20.079	Point for the S 1/16 sec. cor. of secs. 8 and 9.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T40N R51E S 1/16 S 8   S 9  2009

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
32.20	Ridge, bears E. and SW.
38.70	Ravine, drains ENE.
40.158	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E 1/4 S 8   S 9</p> <p style="text-align: center;">2009</p>
59.20	Ravine, drains E.
80.316	<p>The cor. of secs. 4, 5, 8 and 9, monumented with a granite stone, 11x7x6 ins., firmly set, no marks visible, with a deeply embedded mound of stone, 2 ft. diam., W. of cor. This stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.</p>
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S 5   S 4 ----- S 8   S 9</p> <p style="text-align: center;">2009</p>
	Bury the unmarked stone alongside the stainless steel post.
	<hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 81°54'00" W., bet. secs. 4 and 9.</p>
20.577	<p>Point for the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E S 4 E 1/16 — S 9</p> <p style="text-align: center;">2010</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
33.30	Trail road on ridge, bears N. 20° E. and S. 20° W.
41.154	The 1/4 sec. cor. of secs. 4 and 9, determined at the center of a deeply embedded mound of stone, 3 ft. diam. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T40N R51E S 4 1/4 — S 9</p>
	2009
	<hr style="width: 30%; margin: auto;"/> S. 89°45'20" W., beginning new measurement.
12.00	Ridge, bears NE. and SW.
15.50	Cottonwood Creek, 5 lks. wide, course N.
19.437	Point for the W 1/16 sec. cor. of secs. 4 and 9.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T40N R51E S 4 W 1/16 — S 9</p>
	2009
22.80	Trail road, bears SSE. and NNW.
38.874	The cor. of secs. 4, 5, 8 and 9.
	<hr style="width: 30%; margin: auto;"/> N. 8°10'10" E., bet. secs. 4 and 5.
27.30	Ravine, drains ENE.
27.45	Trail road, bears SE. and W.
35.876	Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T40N R51E 1/4 S 5   S 4</p> <p style="text-align: center;">2009</p>
71.483	<p>Intersect the Eighth Standard Parallel North.</p> <p>Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T41N R51E S33 ----- S 5   S 4 T40N   R51E CC</p> <p style="text-align: center;">2009</p> <p>From this point, the standard cor. of secs. 32 and 33, T. 41 N., R. 51 E., hereinbefore described, bears N. 89°39'40" W., 11.143 chs. dist.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 4 only, is at midpoint in departure on the N. bdy. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T41N R51E ----- 1/4 S 4 T40N R51E</p> <p style="text-align: center;">2009</p> <p>From this point, the standard E 1/16 sec. cor. of sec. 33, T. 41 N., R. 51 E., hereinbefore described, bears S. 89°23'40" E., 8.631 chs. dist.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the north boundary, T. 39 N., R. 51 E., executed under Group No. 574.</p> <p>N. 0°06'30" E., bet. secs. 31 and 32.</p>
36.00	<p>Ravine, drains SE.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.647	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E 1/4 S31 S32</p> <p style="text-align: center;">2009</p>
46.70	Ridge, bears SSE. and NNW.
81.294	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S30 S29 ----- S31 S32</p> <p style="text-align: center;">2009</p>
	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°08'20" W., bet. secs. 29 and 32.</p>
15.50	Cor. of fences extending N. 15° E. and N. 87° W., bears NORTH, 1.20 chs. dist.
30.00	Stream, 8 lks. wide, course SW.
30.80	Trail road, bears NE. and SW.
40.867	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S29 1/4 — S32</p> <p style="text-align: center;">2009</p>
50.00	Ridge, bears N. and S.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
62.20	Head of ravine, drains SW.
77.80	Ridge, bears NE. and SW.
81.734	The cor. of secs. 29, 30, 31 and 32.
	<hr/>
	S. 88°10'20" W., bet. secs. 30 and 31.
40.792	Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T40N R51E S30 1/4 — S31</p>
	<p style="text-align: center;">2009</p>
42.70	Ridge, bears NNE. and SSW.
61.188	Point for the W 1/16 sec. cor. of secs. 30 and 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T40N R51E S30 W 1/16 — S31</p>
	<p style="text-align: center;">2009</p>
67.30	McCann Creek, 10 lks. wide, course S.
67.90	Trail road, bears N. and S.
78.851	The cor. of secs. 30 and 31, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 40 N., R. 51 E., executed under Group No. 473, with a mound of stone, 3 ft. diam., 1 ft. high, E. of the cor.
	<hr/>
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°47'40" W., bet. secs. 29 and 30.
8.40	Ravine, drains WSW.
28.00	Ridge, bears E. and W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.651	Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T40N R51E 1/4 S30   S29
	2009
59.10	Stream, 4 lks. wide, course SW.
59.30	Trail road, bears N. 75° E. and S. 75° W.
78.40	Stream, 4 lks. wide, course SE.
79.50	Trail road, bears S. 35° E. and N. 35° W.
81.302	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T40N R51E S19   S20 ----- S30   S29
	2009
	From the cor. of secs. 20, 21, 28 and 29.
	S. 88°50'10" W., bet. secs. 20 and 29.
1.50	Spring, bears NORTH, 0.70 chs. dist.
7.20	Ravine, drains NE.
19.00	Trail road on flat ridge, bears S. 50° E. and N. 50° W.
38.22	Fence, bears N. 1° E. and S. 1° W., from which the cor. of fences extending N. 1° E., S. 1° W. and W., bears N. 1° E., 4.73 chs. dist.
40.326	Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T40N R51E S20 1/4 — S29</p> <p style="text-align: center;">2009</p>
49.40	Trail road, bears S. 50° E. and N. 50° W.
60.00	Ridge, bears SSE. and NNW.
60.489	<p>Point for the W 1/16 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S20 W 1/16 — S29</p> <p style="text-align: center;">2009</p> <p>Set a split cedar wood post alongside the stainless steel post.</p>
80.652	The cor. of secs. 19, 20, 29 and 30.
	S. 86°47'00" W., bet. secs. 19 and 30.
0.70	Trail road, bears S. 35° E. and N. 35° W.
1.30	Stream, 4 lks. wide, course SE.
40.302	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S19 1/4 — S30</p> <p style="text-align: center;">2009</p>
60.453	<p>Point for the W 1/16 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T40N R51E S19 W 1/16 ——— S30  2009
77.722	The cor. of secs. 19 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 40 N., R. 51 E., executed under Group No. 473, with a mound of stone, 3 ft. diam., 1 ft. high., S. of cor.
	<hr/> From the cor. of secs. 19, 20, 29 and 30.  N. 0°26'50" E., bet. secs. 19 and 20.
29.90	Trail road, bears NE. and SW.
40.649	Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T40N R51E 1/4 S19   S20  2009
52.00	Trail road on ridge, bears S. 30° E. and N. 30° W.
68.80	Head of Sixmile Canyon, drains E.
70.10	Cor. of fences extending N. and S. 39° E., bears EAST, 1.70 chs. dist.
73.90	Trail road in saddle, on curve from W. to N.
81.298	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T40N R51E S18   S17 ———   ——— S19   S20  2009

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From this point, the cor. of secs. 18 and 19, on the W. bdy. of the Tp., bears S. 85°27'40" W., 78.380 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 40 N., R. 51 E., executed under Group No. 473, with a mound of stone, 3 ft. diam., 1 ft. high, E. of cor.
	From the cor. of secs. 16, 17, 20 and 21.
	S. 88°33'30" W., bet. secs. 17 and 20.
20.306	Point for the E 1/16 sec. cor. of secs. 17 and 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T40N R51E S17 E 1/16 — S20  2009
31.60	Ridge, bears SE. and NW.
40.612	Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T40N R51E S17 1/4 — S20  2009
53.30	Ridge, bears NE. and SW.
61.10	Ravine, drains NNE.
79.20	Fence, bears N. and S.
79.50	Trail road, bears N. and S.
81.224	The cor. of secs. 17, 18, 19 and 20.
	N. 0°36'50" E., bet. secs. 17 and 18.
17.70	Trail road, bears S. 50° E. and N. 50° W.
20.50	Trail road, bears N. 30° E. and S. 30° W.
36.90	Stream, 4 lks. wide, course NE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.30	Ravine, drains E.
40.649	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E 1/4 S18   S17  2009</p>
	<p>Set a wood post, 4x6 ins., 60 ins. long, alongside the stainless steel post.</p> <p>Cor. is located WEST, 0.45 chs. dist. of trail road, bears S. 30° E. and N. 20° W.</p>
41.30	Trail road, bears S. 55° E. and N. 70° W.
53.70	Head of ravine, drains SE.
61.70	Ridge, bears NE. and SW.
75.60	Fence, bears S. 48° E. and N. 48° W.
76.20	Trail road, bears SE. and NW.
81.298	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E S 7   S 8 ----- S18   S17  2009</p>
	Set a steel fence post alongside the stainless steel post.
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°13'50" W., bet. secs. 8 and 17.</p>
12.70	Ridge, bears NE. and SW.
15.80	Trail road, bears NE. and SW.
19.826	Point for the E 1/16 sec. cor. of secs. 8 and 17.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S 8 E 1/16 — S17</p> <p style="text-align: center;">2009</p> <p>Build a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p>
31.50	Spring, bears SOUTH, 2.50 chs. dist.
39.652	<p>The 1/4 sec. cor. of secs. 8 and 17, determined at the center of a deeply embedded mound of stone, 3 ft. diam. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 11 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R51E S 8 1/4 — S17</p> <p style="text-align: center;">2009</p> <hr/> <p>S. 89°45'50" W., beginning new measurement.</p>
5.00	Flat ridge, bears SE. and NW.
18.90	Ravine, drains NNW.
29.70	Top of knoll.
40.929	The cor. of secs. 7, 8, 17 and 18.
	<hr/> <p>S. 84°20'20" W., bet. secs. 7 and 18.</p>
7.20	Fence, bears N. 62° W. and S. 62° E.
10.80	Trail road in saddle, bears N. 20° E. and S. 20° W.
40.00	Ridge, bears N. and S.
41.180	Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T40N R51E S 7 1/4 — S18</p> <p style="text-align: center;">2009</p>
62.70	Stream, 4 lks. wide, course NW.
63.20	Trail road, bears S. 30° E. and N. 30° W.
79.323	The cor. of secs. 7 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 40 N., R. 51 E., executed under Group No. 473.
	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 1°16'20" E., bet. secs. 7 and 8.</p>
7.40	Ridge, bears SE. and NW.
29.20	Ravine, drains NW.
40.657	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E 1/4 S 7   S 8</p> <p style="text-align: center;">2009</p>
52.00	Ridge, bears SE. and NW.
65.80	Ridge, bears NE. and SW.
81.314	The cor. of secs. 5, 6, 7 and 8, monumented with a wood post, 3 ins. square, 27 ins. long (Record, limestone 22x14x10), lying partially embedded on top of ground and tapered on one end, no marks visible. This wood post correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T40N R51E S 6   S 5 <hr style="width: 50%; margin: auto;"/>S 7   S 8</p> <p style="text-align: center;">2009</p> <p>Bury the wood post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9. N. 89°47'20" W., bet. secs. 5 and 8.</p>
8.50	Ridge, bears N. and S.
16.30	Ridge, bears SE. and NW.
40.286	Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T40N R51E S 5 1/4 — S 8</p> <p style="text-align: center;">2009</p>
46.80	Ridge, bears SE. and NW.
60.429	Point for the W 1/16 sec. cor. of secs. 5 and 8.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">T40N R51E S 5 W 1/16 — S 8</p> <p style="text-align: center;">2009</p>
62.30	Stream, 3 lks. wide, course N.
80.572	The cor. of secs. 5, 6, 7 and 8. <hr/>
	S. 83°14'00" W., bet. secs. 6 and 7.
4.90	Ridge, bears SE. and NW.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
28.80	Stream, 5 lks. wide, course N.
42.262	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E S 6 1/4 — S 7</p> <p style="text-align: center;">2009</p>
46.60	Ridge, bears SE. and NW.
58.60	Ravine, drains ESE.
74.00	Ridge, bears NNE. and SSW.
81.259	<p>The cor. of secs. 6 and 7, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 40 N., R. 51 E., executed under Group No. 473, with a mound of stone, 3 ft. diam., 1 ft. high, E. of cor.</p>
	<hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 10°09'20" E., bet. secs. 5 and 6.</p>
6.40	Head of ravine, drains NE.
20.60	Ridge, bears SE. and W.
36.108	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T40N R51E 1/4 S 6   S 5</p> <p style="text-align: center;">2009</p>
53.10	Stream, 5 lks. wide, course W.
54.162	<p>Point for the N 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T40N R51E N 1/16 S 6   S 5</p> <p style="text-align: center;">2009</p>
72.053	<p>Intersect the Eighth Standard Parallel North.</p> <p>Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T41N R51E S32 ----- S 6   S 5 T40N   R51E CC</p> <p style="text-align: center;">2009</p> <p>Build a mound of stone, 2 ft. base, 1 ft. high, S. of cor.</p> <p>From this point, the standard cor. of secs. 31 and 32, T. 41 N., R. 51 E., hereinbefore described, bears N. 89°39'40" W., 11.181 chs. dist.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 5 only, is at midpoint on the N. bdy. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T41N R51E ----- 1/4 S 5 T40N R51E</p> <p style="text-align: center;">2009</p> <p>From this point, the standard 1/4 sec. cor. of sec. 32, T. 41 N., R. 51 E., hereinbefore described, bears N. 89°39'40" W., 11.162 chs. dist.</p> <hr/> <p>The point for the 1/4 sec. cor. of sec. 6 only, is at proportionate distance on the N. bdy. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

T41N R51E

1/4 S 6

T40N R51E

2009

From this point, the standard E 1/16 sec. cor. of sec. 31, T. 41 N., R. 51 E., hereinbefore described, bears S. 89°39'40" E., 8.368 chs. dist.

The point for the E 1/16 sec. cor. of sec. 6 only, is at midpoint, bet. the closing cor. of secs. 5 and 6 and the 1/4 sec. cor. of sec. 6 only, on the N. bdy. of sec. 6.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., on exposed bedrock, over a plastic-encased magnet set into a 1 1/2 in. deep drill hole, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T41N R51E

E 1/16 S 6

T40N R51E

2009

Cor. is located on the S. edge of a trail, bears E. and W., and 70 lks. S. of a ravine, drains W.

From this point, the standard cor. of secs. 31 and 32, T. 41 N., R. 51 E., hereinbefore described, bears S. 89°39'40" E., 8.350 chs. dist.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 46 (1566),  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA



Reestablishment of the Survey Executed by  
U.S. Deputy Surveyor C.C. Tracy in 1878

All Alone lode



Beginning at the point for Cor. No. 1, Mineral Survey No. 46, All Alone lode, determined at record angle and distance from Cor. No. 2, Mineral Survey No. 46, All Alone lode; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 46 (1566),  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;">  <p>2010</p> </div> <p>Cor. is located on a gentle rolling E. slope, in an area covered with mining prospect holes and tailings, 70 lks. N. of a prospect hole, 30 ft. diam. and 12 ft. deep.</p> <p>Thence N. 58°23'40" W., on line 1-2, Mineral Survey No. 46, All Alone lode.</p>
16.970	<p>Cor. No. 2, Mineral Survey No. 46, All Alone lode, determined at the center of an embedded mound of earth and stone, 5 ft. diam. This mound of earth and stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;">  <p>2009</p> </div> <p>Cor. is located on a moderately steep SE. slope in an area covered with mining prospects and tailings.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence S. 31°36'20" W., on line 2-3, Mineral Survey No. 46, All Alone lode.</p>
7.379	<p>Point for Cor. No. 4, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, hereinafter described.</p> <p>Continue measurement on line 2-3, Mineral Survey No. 46, All Alone lode, now identical with line 4-3, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode.</p>
9.129	<p>Cor. No. 3, Mineral Survey No. 46, All Alone lode, identical with Cor. No. 3, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, determined at the center of an embedded mound of stone, 4 ft. diam., with a wooden post, 4 ins. diam., 5 ft. long, lying loose alongside, no marks visible. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 46 (1566),  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2009</p> <p>Cor. is located on a rolling brush covered SE. slope.</p>
	<p>Thence S. 58°23'40" E., on line 3-4, Mineral Survey No. 46, All Alone lode, identical in part with line 3-2, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode.</p>
7.338	<p>Cor. No. 2, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, on line 2-3 of cancelled Mineral Survey No. 49, May Queen lode, hereinafter described.</p> <p>Continue measurement on line 3-4, Mineral Survey No. 46, All Alone lode.</p>
16.970	<p>Point for Cor. No. 4, Mineral Survey No. 46, All Alone lode, determined at the intersection of the lines run parallel with the side line and the end line; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p style="text-align: center;">S34 T40N R51E</p> <p style="text-align: center;">2010</p> <p>Cor. is located in mine tailings on easterly slope and 90 lks. S. of a track road along the Tuscarora dump site.</p>
9.129	<p>Thence N. 31°36'20" E., on line 4-1, Mineral Survey No. 46, All Alone lode.</p> <p>Cor. No. 1, Mineral Survey No. 46, All Alone lode, and the point of beginning.</p>

DEPENDENT RESURVEY OF A PORTION OF  
 CANCELLED MINERAL SURVEY NO. 48 (1568),  
 T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of a Portion of the Survey Executed by  
 U.S. Deputy Surveyor R.M. Catlin in 1885

McVystal lode

From the point of intersection of line 2-3, cancelled Mineral Survey No. 48, McVystal lode with line 1-2 of Amended Mineral Survey No. 1817, Found Treasure No. 2 lode.

From this point of intersection, Cor. No. 1, Mineral Survey No. 1817, Found Treasure No. 2 lode, hereinafter described, bears S. 16°39'40" W., 0.206 chs. dist.

From this same point of intersection, the point for Cor. No. 2, cancelled Mineral Survey No. 48, McVystal lode, bears S. 84°43'50" E., 3.825 chs. dist., determined by the method of grant boundary adjustment between Cor. No. 3 and Cor. No. 6, both of cancelled Mineral Survey No. 48, McVystal lode; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

T40N R51E  
 S34

COR 2  
 MS 48  
 M

2010

Cor. is located on steep westerly slope of mine tailings 15 lks. W. of top of tailings.

From this point, Cor. No. 6, cancelled Mineral Survey No. 48, McVystal lode, bears S. 16°05'20" E., 10.924 chs. dist., determined at the center of an embedded mound of stone, 4 ft. diam., with a wood post, 3 ins. square, 32 ins. long, lying loose alongside, mkd. Cor McV.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.


MS 48  
 M  
 COR

6


S34  
 T40N R51E

2009

DEPENDENT RESURVEY OF A PORTION OF  
 CANCELLED MINERAL SURVEY NO. 48 (1568),  
 T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Cor. is located on a gentle SE. slope in moderate brush cover.</p> <p>A careful search was made for evidence of the intervening cor., and none was found.</p> <p>Thence N. 84°43'50" W., on a portion of line 2-3, cancelled Mineral Survey No. 48, McVystal lode.</p>
1.645	<p>Intersect line 3-4, cancelled Mineral Survey No. 49, May Queen lode, at a point from which Cor. No. 3, cancelled Mineral Survey No. 49, May Queen lode, hereinafter described, bears N. 48°57'10" W., 0.445 chs. dist.</p>
2.418	<p>Intersect line 8-1, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, at a point from which Cor. No. 8, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, hereinafter described, bears N. 79°52'00" W., 1.736 chs. dist.</p> <p>From this point of intersection, Cor. No. 3, cancelled Mineral Survey No. 48, McVystal lode, bears N. 84°43'50" W., 9.087 chs. dist., monumented with remnants of a wood post in the center of an embedded mound of stone, 4 ft. diam. The remnants and mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T40N R51E</p> <p>S34</p>  <p>3</p> <p>COR</p> <p>MS 48</p> <p>M</p> <p>2009</p> </div>
	<p>Cor. is located on a short, steep embankment, 30 lks. N. of a track road, bears SE. and NW., and 15 lks. S. of the base of mine tailings.</p>


DEPENDENT RESURVEY OF A PORTION OF  
 CANCELLED MINERAL SURVEY NO. 49 (1569),  
 T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by            U.S. Deputy Surveyor R.M. Catlin in 1885</p>
	<p style="text-align: center;">May Queen lode</p> <p>From Cor. No. 2, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, on line 3-4 of Mineral Survey No. 46, All Alone lode, also on line 2-3, cancelled Mineral Survey No. 49, May Queen lode, hereinafter described.</p> <p>Thence S. 42°05'20" W., on a portion of line 2-3, cancelled Mineral Survey No. 49, May Queen lode.</p> <p>4.699 Cor. No. 3, cancelled Mineral Survey No. 49, May Queen lode, determined at the center of an embedded mound of stone, 5 ft. diam., with a wood post, 4 ins. square, 46 ins. long, lying loose alongside, no marks visible. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p style="text-align: center;">2009</p>
	<p>Thence S. 48°57'10" E., on a portion of line 3-4, cancelled Mineral Survey No. 49, May Queen lode.</p>
0.445	<p>Intersect line 2-3, cancelled Mineral Survey No. 48, McVystal lode, at a point from which Cor. No. 2, cancelled Mineral Survey No. 48, McVystal lode, hereinafter described, bears S. 84°43'50" E., 5.470 chs. dist.</p>
0.573	<p>Intersect line 8-1, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, at a point from which Cor. No. 1, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, hereinafter described, bears S. 79°52'00" E., 1.506 chs. dist.</p> <p>From this point of intersection, Cor. No. 4, cancelled Mineral Survey No. 49, May Queen lode, bears S. 48°57'10" E., 18.432 chs. dist., monumented with an embedded mound of stone, 5 ft. diam. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF  
 CANCELLED MINERAL SURVEY NO. 49 (1569),  
 T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
 23 ins. in the ground, over a plastic-encased magnet, and in a  
 collar of stone, with brass cap mkd.



2014

DEPENDENT RESURVEY OF PORTIONS OF  
 AMENDED MINERAL SURVEY NO. 1817,  
 T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA


Reestablishment of Portions of the Survey Executed by  
 U.S. Deputy Mineral Surveyor B.C. Jordan in 1898  
 and Portions of the Amended Survey Executed by  
 U.S. Deputy Mineral Surveyor F. Anderson in 1899

Found Treasure No. 2 lode

From Cor. No. 1, Amended Mineral Survey No. 1817, Found Treasure  
 No. 2 lode, determined at the center of an embedded mound of  
 stone, 4 ft. diam., with a wood post, 3 ins. square, 36 ins.  
 long, lying loose alongside, mkd. COR 1 1817.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
 15 ins. in the ground, to bedrock, over a plastic-encased  
 magnet, and in a mound of stone, 5 ft. base, to top, with brass  
 cap mkd.



T40N R51E

2009

Cor. is located on a gentle, brushy SE. slope.

Thence N. 16°39'40" E., on line 1-2, Amended Mineral Survey  
 No. 1817, Found Treasure No. 2 lode.

0.206

Intersect line 2-3, cancelled Mineral Survey No. 48, McVystal  
 lode, at a point from which Cor. No. 2, cancelled Mineral Survey  
 No. 48, McVystal lode, hereinbefore described, bears  
 S. 84°43'50" E., 3.825 chs. dist.

DEPENDENT RESURVEY OF PORTIONS OF  
 AMENDED MINERAL SURVEY NO. 1817,  
 T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

4.309

Cor. No. 2, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, on line 3-4, Mineral Survey No. 46, All Alone lode, and also on line 2-3, cancelled Mineral Survey No. 49, May Queen lode, monumented with a portion of a wooden post, 3 ins. square, 6 ins. long, firmly set 6 ins. below ground, in an embedded mound of stone, 3 ft. diam. The wooden post and the mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

MS 46  
 AA  
 COR 2  
 MS 1817 / S34  
 FT NO 2 / T40N R51E

2010

Cor. is located on a rolling SE. slope in area covered with mining prospects and tailings, at the W. edge of a mining prospect hole, 5 ft. deep, 20 ft. diam.

From the point for Cor. No. 4, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, on line 2-3, Mineral Survey No. 46, All Alone lode, determined at proportionate distance between Cor. No. 2 and Cor. No. 3, both of Mineral Survey No. 46, All Alone lode; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

T40N R51E  
 S34  
 FT  
 NO 2 COR 4 / MS 46  
 MS 1817 / AA

2010

Cor. is located in a trench between two mine tailings piles.

Thence N. 73°53'50" W., on line 4-5, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode.

16.275

Cor. No. 5, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, monumented with a portion of a wooden post, 3 ins. square, 6 ins. long, firmly set 12 ins. below the ground, in an embedded mound of stone, 3 ft. diam.


DEPENDENT RESURVEY OF PORTIONS OF  
 AMENDED MINERAL SURVEY NO. 1817,  
 T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
 22 ins. in the ground, over a plastic-encased magnet, and in a  
 collar of stone, with brass cap mkd.

T40N R51E  
 S34



2010

Thence S. 16°38'50" W., on line 5-6, Amended Mineral Survey  
 No. 1817, Found Treasure No. 2 lode.

4.563 Intersect the line bet. secs. 33 and 34, at a point from which  
 the N 1/16 sec. cor. of secs. 33 and 34, hereinbefore described,  
 bears N. 0°07'00" E., 7.925 chs. dist.

9.084 Cor. No. 6, Amended Mineral Survey No. 1817, Found Treasure  
 No. 2 lode, determined at a defined discoloration of native  
 soil, 3 ins. diam., in an embedded mound of stone, 5 ft. diam.  
 The soil discoloration and mound of stone correlates well with  
 other original corners and is accepted as the best available  
 evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,  
 21 ins. in the ground, over a plastic-encased magnet, and in a  
 collar of stone, with brass cap mkd.

T40N MS 1817  
 R51E COR  
 S33 6 FT NO 2

2010

Cor. is located on steep SE. slope in moderate brush cover.

Thence S. 74°17'10" E., on line 6-7, Amended Mineral Survey  
 No. 1817, Found Treasure No. 2 lode.

1.335 Intersect the line bet. secs. 33 and 34, at a point from which  
 the 1/4 sec. cor. of secs. 33 and 34, hereinbefore described,  
 bears S. 0°07'00" W., 7.557 chs. dist.

DEPENDENT RESURVEY OF PORTIONS OF  
 AMENDED MINERAL SURVEY NO. 1817,  
 T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA


## CHAINS

5.435

Cor. No. 7, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, on the northerly side line of Irish Boy No. 2 lode, unsurveyed, determined at the center of an embedded mound of stone, 4 ft. diam., with a wooden post, 2x4 ins., 46 ins. long, lying loose alongside. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

MS 1817  
 FT NO 2  
 COR 7  
  
 S34  
 T40N R51E  
 2009


Thence S. 76°43'40" E., on line 7-8, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode.

13.405

Cor. No. 8, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, identical with the SE. cor., Irish Boy No. 2 lode, unsurveyed, determined at the center of an embedded mound of stone, 5 ft. diam., with a wooden post, 3x5 ins., 48 ins. long, no marks visible, lying loose alongside. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the position of the original corner.

At the corner point


Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

MS 1817  
 FT NO 2  
 COR 8  
  
 S34  
 T40N R51E  
 2009

Cor. is located on a gentle SE. slope in moderate brush cover.

Thence S. 79°52'00" E., on line 8-1, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode.

DEPENDENT RESURVEY OF PORTIONS OF  
 AMENDED MINERAL SURVEY NO. 1817,  
 T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.736	Intersect line 2-3, cancelled Mineral Survey No. 48, McVystal lode, at a point from which Cor. No. 2, cancelled Mineral Survey No. 48, McVystal lode, hereinbefore described, bears S. 84°43'50" E., 6.243 chs. dist.
2.616	Intersect line 3-4, cancelled Mineral Survey No. 49, May Queen lode, at a point from which Cor. No. 3, cancelled Mineral Survey No. 49, May Queen lode, hereinbefore described, bears N. 48°57'10" W., 0.573 chs. dist.
4.122	Cor. No. 1, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, and the point of beginning.
<hr/> Irish Boy No. 2 lode, unsurveyed	
From Cor. No. 7, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, on the northerly side line of Irish Boy No. 2 lode, unsurveyed, hereinbefore described.	
Thence N. 61°41'50" E., on a portion of the northerly side line, Irish Boy No. 2 lode, unsurveyed.	
9.820	The NE. cor. of Irish Boy No. 2 lode, unsurveyed, identical with original Cor. No. 8, Mineral Survey No. 1817, Found Treasure No. 2 lode, determined at the center of an embedded mound of stone, 5 ft. diam. This mound of stone correlates well with other original corners and is accepted as the best available evidence of the original corner.
At the corner point	
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone with brass cap mkd.	
	
Cor. is located on a moderate steep SE. slope in moderate brush cover.	
<hr/> Thence S. 29°38'30" E., on the easterly end line, Irish Boy No. 2 lode, unsurveyed.	
8.898	The SE. cor. of Irish Boy No. 2 lode, unsurveyed, identical with Cor. No. 8, Amended Mineral Survey No. 1817, Found Treasure No. 2 lode, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 4094,  
T. 40 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Mineral Surveyor E.A. Frissell in 1912 and a Portion of the Retracement and Remonumentation by Cadastral Surveyor J.A. Bastian in 1981</p> <hr/> <p style="text-align: center;">Phoenix lode</p> <p>From Cor. No. 2, Mineral Survey No. 4094, Phoenix lode, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 3 ft. diam., 6 ins. high, with brass cap mkd. as described in the field notes of the retracement and remonumentation of certain corners of Mineral Survey No. 4094, Phoenix lode, T. 40 N., R. 51 E., executed under Group No. 574.</p> <p>Thence N. 62°08'10" W., on a portion of line 2-3, Mineral Survey No. 4094, Phoenix lode.</p>
0.154	<p>Intersect line 3-4, Mineral Survey No. 1840, Comfort lode.</p> <p>From this point, Cor. No. 3, Mineral Survey No. 1840, Comfort lode, bears S. 0°46'00" E., 7.429 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the retracement and remonumentation of certain corners of Mineral Survey No. 1840, Blossom and Comfort lodes, T. 40 N., R. 51 E., executed under Group No. 574.</p> <p>From this same point, Cor. No. 4, Mineral Survey No. 1840, Comfort lode, bears N. 0°46'00" W., 4.249 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the retracement and remonumentation of certain corners of Mineral Survey No. 1840, Blossom and Comfort lodes, T. 40 N., R. 51 E., executed under Group No. 574.</p>
3.617	<p>Intersect the line bet. secs. 34 and 35, at a point from which the 1/4 sec. cor. of secs. 34 and 35, hereinbefore described, bears S. 1°33'20" W., 5.616 chs. dist.</p>
4.440	<p>Cor. No. 1, Mineral Survey No. 4094, New Homesdale lode, on line 2-3, Mineral Survey No. 4084, Phoenix lode, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the retracement and remonumentation of certain corners of Mineral Survey No. 4094, Phoenix lode, T. 40 N., R. 51 E., executed under Group No. 574.</p> <hr/>

TOWNSHIP 40 NORTH, RANGE 51 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

GENERAL DESCRIPTION

The area of this survey includes the town of Tuscarora, in the southeast portion of the township, and extends westerly over a portion of the Tuscarora Mountain Range into the McCann Creek and Big Cottonwood Canyon drainages. Elevation ranges between 5800 to 8200 feet. Most of the township is covered with moderate to dense sage and other mixed ground cover with the northern portion covered with low grasses replanted after a major range fire of several years ago. The western portion has numerous springs and live spring branches, scattered pockets of aspen and deep canyons with steep canyon slopes. A network of mostly 4-wheel drive trail roads exists throughout much of the township. Extensive abandoned mining activities are concentrated in and around Tuscarora and abandoned mine prospect sites are spread throughout the township.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Brock R. Clifford	Supervisory Cadastral Surveyor
John S. Parrish	Professional Land Surveyor
Brandon K. Grace	Cadastral Surveyor
Carl Davis	Surveying Technician
Chad M. Bartek	Surveying Technician
Justin T. Roberts	Surveying Technician

CERTIFICATE OF SURVEY

We, Brett K. Jefferson, Professional Land Surveyor, Nevada, Don R. Aschenbach, Bradley F. Dillon and Michael O. Jones, Cadastral Surveyors, and Mark G. Petrosine, Surveying Technician, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 2nd day of June, 2009, and Supplemental Special Instructions bearing date of the 17th day of December, 2009, We have dependently resurveyed the Eighth Standard Parallel North, through Range 51 East and a portion of Range 52 East, correctively dependently resurveyed a portion of the west boundary, and dependently resurveyed a portion of the subdivisional lines and portions of certain mineral surveys, Township 40 North, Range 51 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

FEB 24 2021

(Date)

*Brett K. Jefferson*

(Professional Land Surveyor)

MAR 29 2021

(Date)

*Mahmud O. Hammami*

/For Don R. Aschenbach

(Cadastral Surveyor)

MAR 15 2021

(Date)

*Bradley F. Dillon*

(Cadastral Surveyor)

MAR 29 2021

(Date)

*M O J*

(Cadastral Surveyor)

MAR 29 2021

(Date)

*Mark Petrosine*

(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Eighth Standard Parallel North, through Range 51 East and a portion of Range 52 East, the corrective dependent resurvey of a portion of the west boundary, and the dependent resurvey of a portion of the subdivisional lines and portions of certain mineral surveys, Township 40 North, Range 51 East, Mount Diablo Meridian, Nevada, executed by Brett K. Jefferson, Professional Land Surveyor, Nevada, Don R. Aschenbach, Bradley F. Dillon, and Michael O. Jones, Cadastral Surveyors, and Mark G. Petrosine, Surveying Technician, having been critically examined and found correct, are hereby approved.

MAR 29 2021

(Date)

*Mahmud O. Hammami*

(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in Township 40 North, Range 51 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~