

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

A PORTION OF THE 1873 MEANDER LINES OF SUMMIT LAKE,

AND A PORTION OF THE 1988-1991 MEANDER LINES OF SUMMIT LAKE,

AND

THE FURTHER SUBDIVISION OF SECTION 35,

AND

THE SUBDIVISION OF SECTION 36,

TOWNSHIP 42 NORTH, RANGE 25 EAST,

MOUNT DIABLO MERIDIAN, NEVADA

EXECUTED BY

Daniel A. Rash, Cadastral Surveyor  
Stephen J. Grimaldi, Cadastral Surveyor

Under Special Instructions dated and approved September 19, 2017,  
which provided for the surveys included under Group No. 975,  
and Assignment Instructions dated and approved September 19, 2017.

Survey commenced October 10, 2017

Survey completed September 10, 2018

INDEX DIAGRAM

TOWNSHIP 42 NORTH, RANGE 25 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25 6
31	32	33	34	35	5 36 2 5

Dependent Resurvey of a portion of the 1873  
 Meander Lines of Summit Lake ..... p. 7

Dependent Resurvey of a portion of the 1988-1991  
 Meander Lines of Summit Lake ..... p. 8

Further Subdivision of Section 35 ..... p. 8

Subdivision of Section 36 ..... pp. 9 - 12

## TOWNSHIP 42 NORTH, RANGE 25 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	The following field notes are those of the dependent resurvey of a portion of the south boundary, a portion of the east boundary, a portion of the subdivisional lines, a portion of the 1873 meander lines of Summit Lake and a portion of the 1988-1991 meander lines of Summit Lake, and the further subdivision of section 35, and the subdivision of section 36, Township 42 North, Range 25 East, Mount Diablo Meridian, Nevada.
1873	A portion of the east and south boundaries and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyor G.W. Garside under Contract No. 55.
1873	A portion of the north, south and east boundaries, a portion of the subdivisional lines, the meanders of Summit Lake and Camp McGarry Military Reservation were surveyed by U.S. Deputy Surveyor G.W. Garside under Contract No. 59.
1910	The west boundary of T. 41 N., R. 26 E. was resurveyed and the southeast township corner was remonumented by U.S. Transitman A.B. Rich under Group No. 3.
1917-18	A portion of the north boundary was dependently resurveyed and a portion surveyed by U.S. Transitsmen H.P. Purington and J.R. English and U.S. Surveyor H.W. Reppert under Group No. 52.
1946	A portion of the subdivisional lines were dependently resurveyed, and the west boundary, a portion of the south boundary and a portion of the subdivisional lines were surveyed by Cadastral Engineer J.W. Hardison under Group No. 342.
1964	Nevada Protraction Diagram No. 138 was approved for unsurveyed sections in T. 41 N., Rs. 23 1/2, 24 and 25 E. and T. 41 1/2 N., Rs. 23 1/2, 24 and 25 E.
1988-91	Portions of the south boundary, east boundary and subdivisional lines were dependently resurveyed, the 1873 meander lines of Summit Lake were dependently resurveyed and adjusted, section 35 was subdivided, and the 1988-1991 meander lines and an informative traverse of the 1988-1991 bank of a portion of Summit Lake was surveyed by Cadastral Surveyor R.A. Pratt under Group No. 655.
	Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the position of the original corners and other calls of the original field note record.
	In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.
	The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 2009 edition</u> , and the <u>Special Instructions for Group No. 975, dated September 19, 2017</u> .

TOWNSHIP 42 NORTH, RANGE 25 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Measurements were made with Trimble R-10 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) procedure and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents in chains for ground distances only are entered in the field notes.

The NAD 1983 (2011) (EPOCH:2010.0000) geographic position, of the following corners were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), and carried forward by RTK observations.

The southeast township cor. is as follows:

Latitude: 41°30'15.758" N. Longitude: 119°04'03.394" W.

The cor. of secs. 25, 26, 35 and 36, is as follows:

Latitude: 41°31'10.160" N. Longitude: 119°05'15.683" W.

The October 19, 2017 mean magnetic declination was determined to be 13°45' E., as obtained from the National Oceanic and Atmospheric Administration's National Centers For Environmental Information declination calculator.

---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

---

Reestablishment of a Portion of the Survey Executed by  
U.S. Deputy Surveyor G.W. Garside in 1873  
and a Portion of the Dependent Resurvey Executed by  
Cadastral Surveyor R.A. Pratt in 1988-1991

---

From the cor. of Tps. 41 N., 41 1/2 N. and 42 N., Rs. 25 and 26 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above a mound of stone, 4 1/2 ft. diam., 1 ft. high, with brass cap mkd.

T42N  
R25E | R26E  
S36 | S31  
S 1 | S 6  
R25E | R26E  
T41N  
1910

with steel fence post alongside.

Remark the brass cap to now read

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS																	
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T42N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td>S36</td><td>S 6</td></tr> <tr><td>T41 1/2N</td><td>T41N</td></tr> <tr><td>R25E</td><td>R26E</td></tr> <tr><td colspan="2">2017</td></tr> <tr><td colspan="2">1910</td></tr> </table>	T42N		R25E	R26E	S36	S31	S36	S 6	T41 1/2N	T41N	R25E	R26E	2017		1910	
T42N																	
R25E	R26E																
S36	S31																
S36	S 6																
T41 1/2N	T41N																
R25E	R26E																
2017																	
1910																	
	<p>Attach a BLM Land Survey Monument sign to existing fence post. S. 89°54'30" W., on the S. bdy. of sec. 36.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p>																
10.00	Barbed wire fence, bears N. and S. From this point the cor. of barbed wire fences bears N., 0.067 chs. dist., with fences extending E. and W.																
20.770	Point for the E 1/16 sec. cor. of sec. 36, T. 42 N., R. 25 E.  POINT NOT MONUMENTED																
27.10	Soldier Meadows Road, 30 lks. wide, bears N. 14° E., and S. 11° W.																
39.716	The N 1/4 sec. cor. of sec. 36, T. 41 1/2 N., R. 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of a portion of the subdivisional lines, T. 41 1/2 N., R. 25 E., executed under Group No. 655, with a juniper fence post, 6x7 ins. diam., firmly set, projecting 3 1/2 ft. above the ground, alongside.																
	Set a galvanized steel fence post, 6 ft. long, 2 ft. in the ground, alongside the stainless steel post with a BLM Land Survey Monument sign attached.																
41.540	The 1/4 sec. cor. of sec. 36, T. 42 N., R. 25 E., monumented with a stainless steel post, 3 ins. diam., firmly set, projecting 1 in. above a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd.																
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T42N</td><td>R25E</td></tr> <tr><td>1/4</td><td>S36</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td colspan="2">1988</td></tr> </table>	T42N	R25E	1/4	S36	<hr/>		1988									
T42N	R25E																
1/4	S36																
<hr/>																	
1988																	
	Remark the brass cap to now read																
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T42N</td><td>R25E</td></tr> <tr><td>1/4</td><td>S36</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>T41 1/2N</td><td>R25E</td></tr> <tr><td colspan="2">2017</td></tr> <tr><td colspan="2">1988</td></tr> </table>	T42N	R25E	1/4	S36	<hr/>		T41 1/2N	R25E	2017		1988					
T42N	R25E																
1/4	S36																
<hr/>																	
T41 1/2N	R25E																
2017																	
1988																	
	Set a galvanized steel fence post, 6 ft. long, 2 ft. in the ground, alongside the stainless steel post with a BLM Land Survey Monument sign attached.																

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S. 89°55'30" W., beginning new measurement.</p> <p>32.65 Barbed wire fence, bears N. and S. From this point the cor. of barbed wire fences bears N., 0.452 chs. dist., with fences extending E. and S.</p> <p>38.159 The closing cor. of secs. 35 and 36, T. 41 1/2 N., R. 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a mound of stone, 2 ft. diam., 1 1/2 ft. high., with brass cap mkd. as described in the field notes of the survey of a portion of the subdivisional lines, T. 41 1/2 N., R. 25 E., executed under Group No. 655.</p> <p>Set a galvanized steel fence post, 6 ft. long, 2 ft. in the ground, alongside the stainless steel post with a BLM Land Survey Monument sign attached.</p> <p>41.545 The cor. of secs. 35 and 36, T. 42 N., R. 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T42N R25E</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S35</td> <td style="padding: 0 5px;">S36</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center;">1988</td> </tr> </table> </p> <p>with the original basalt stone, 8x6x4 ins., plainly mkd. on the top face with 1 groove on a side, 5 grooves on the opposite side and 6 grooves on adjacent south side, lying alongside the stainless steel post, and with a mound of stone, 3 ft. diam., 1 ft. high, N. of cor.</p> <p>Remark the brass cap to now read</p> <p style="text-align: center;">T42N R25E</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S35</td> <td style="padding: 0 5px;">S36</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black; text-align: center;">S35</td> </tr> <tr> <td colspan="2" style="text-align: center;">T 41 1/2 N</td> </tr> <tr> <td colspan="2" style="text-align: center;">2017</td> </tr> <tr> <td colspan="2" style="text-align: center;">1988</td> </tr> </table> </p> <p>Set a galvanized steel fence post, 6 ft. long, 6 ins. in the ground, alongside the stainless steel post with a BLM Land Survey Monument sign attached.</p> <hr style="width: 60%; margin-left: auto; margin-right: auto;"/>	S35	S36	1988		S35	S36	S35		T 41 1/2 N		2017		1988	
S35	S36														
1988															
S35	S36														
S35															
T 41 1/2 N															
2017															
1988															

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1873 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1988-1991</p> <hr/> <p>From the cor. of Tps. 41 N., 41 1/2 N. and 42 N., Rs. 25 and 26 E., hereinbefore described.</p> <p>NORTH, bet. secs. 31 and 36.</p> <p>Over rolling land, through scattered sagebrush and native grass on the SW. side of Summit Lake.</p> <p>0.01 Barbed wire fence, bears E. and W.</p> <p>7.120 The 1988-1991 meander cor. of secs. 31 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a mound of stone, 2 1/2 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy., T. 42 N., R. 25 E., executed under Group No. 655.</p> <p>Set a galvanized steel fence post, 6 ft. long, 2 ft. in the ground, alongside the stainless steel post with a BLM Land Survey Monument sign attached.</p> <p>12.70 Enter water of Summit Lake.</p> <p>20.000 Point for the S 1/16 sec. cor. of secs. 31 and 36, falls in Summit Lake.</p> <p>33.100 The point for the 1873 meander cor. of secs. 31 and 36, falls in Summit Lake.</p>
	<p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1873 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1988-1991</p> <hr/> <p>From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°06'40" W., bet. secs. 35 and 36.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p> <p>41.537 The 1/4 sec. cor. of secs. 35 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 42 N., R. 25 E., executed under Group No. 655, with a steel fence post alongside, and with a mound of stone, 2 1/2 ft. diam., 1 ft. high, W. of cor.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Attach a BLM Land Survey Monument sign to the existing fence post.</p> <hr/> <p>N. 0°16'00" W., beginning new measurement.</p>
35.75	<p>Unimproved dirt two-track road, 18 lks. wide, bears S. 63° E. and N. 56° W.</p>
40.85	<p>Barbed wire fence, bears E. and W. From this point the cor. of barbed wire fences bears W., 1.482 chs. dist., with fences extending N. and E.</p>
42.040	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 42 N., R. 25 E., executed under Group No. 655, with a steel fence post alongside, and with a mound of stone, 2 1/2 ft. diam., 1 ft. high, W. of cor.</p> <p>Attach a BLM Land Survey Monument sign to the existing fence post.</p> <hr/> <p>From the 1873 meander cor. of secs. 25 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above a scattered mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 42 N., R. 25 E., executed under Group No. 655, with a steel fence post alongside.</p> <p>Set a galvanized steel fence post, 6 ft. long, 2 ft. in the ground, alongside the stainless steel post with a BLM Land Survey Monument sign attached and rebuild the mound of stone, 2 ft. base to top, around the stainless steel post.</p> <p>From this cor., a rebar, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, bears N. 34° E., 0.030 chs. dist., with a steel fence post alongside with a 4 ft. long PVC pipe slid over the top of the steel fence post.</p> <p>From this same cor., a U.S.C. &amp; G.S. Bench Mark, monumented with a brass tablet cemented in a drill hole, in a large boulder, with brass tablet mkd. Y66 1934, bears N. 17°48'30" W. 24.218 chs. dist.</p> <p>S. 89°59'40" W., bet. secs. 25 and 36.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p>
5.45	<p>Soldier Meadows Road, 30 lks. wide, bears S. 3° E. and N. 29° W.</p>
9.25	<p>Barbed wire fence, bears N. and S. From this point the cor. of barbed wire fences bears S., 2.007 chs. dist., with fences extending E. and W.</p>
20.483	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 42 N., R. 25 E., executed under Group No. 655, with a steel fence post alongside.</p>



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a galvanized steel fence post, 6 ft. long, 2 ft. in the ground, alongside the stainless steel post with a BLM Land Survey Monument sign attached.</p> <hr/> <p>S. 89°59'40" W., beginning new measurement.</p> <p>42.559 The cor. of secs. 25, 26, 35, and 36.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE 1873 MEANDER LINES OF SUMMIT LAKE, T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1873 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor R.A. Pratt in 1988-1991</p> <hr/> <p>From the point for the 1873 meander cor. of secs. 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>Thence, with the adjusted 1873 meanders of Summit Lake in sec. 36.</p> <p>N. 33°42'00" W., 12.530 chs.      At 10.075 chs., point for the special meander cor. at intersection with the E-W center line of sec. 36, hereinafter described.</p> <p>N. 23°56'00" W., 38.880 chs.      At 20.729 chs., point for the special meander cor. at intersection with the E-W center line of the NE 1/4 of sec. 36, hereinafter described.</p> <p>At 33.492 chs., point for the special meander cor. at intersection with the N-S center line of the NE 1/4 of sec. 36, hereinafter described.</p> <p>N. 28°46'00" E. 5.02 chs.      At 2.60 chs., barbed wire fence, bears E. and W.</p> <p>The 1873 meander cor. of secs. 25 and 36, hereinbefore described.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE 1988-1991  
MEANDER LINES OF SUMMIT LAKE,  
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of a Portion of the Survey Executed by  
Cadastral Surveyor R.A. Pratt in 1988-1991

From the 1988-1991 meander cor. of secs. 31 and 36, on the  
E. bdy. of the Tp., hereinbefore described.

Thence, with the 1988-1991 meanders of Summit Lake in sec. 36.

N. 49°29'00" W., 8.360 chs.

N. 28°30'00" W., 8.530 chs.

N. 2°26'00" E., 0.13 chs.

Point for the special meander  
cor. at intersection with the E-W  
center line of the SE1/4 of  
sec. 36, hereinafter described.

FURTHER SUBDIVISION OF SECTION 35,  
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

From the E 1/16 sec. cor. of sec. 35, on the S. bdy. of the Tp.,  
monumented with a stainless steel post, 2 1/2 ins. diam., firmly  
set, flush in a mound of stone, 4 ft. diam., 1 ft. high, with  
brass cap mkd.

E 1/16 35

1988

Remark the brass cap to now read

E 1/16 S35

2017

1988

Set a galvanized steel fence post, 6 ft. long, wedged in between  
large rocks, alongside the stainless steel post with a BLM Land  
Survey Monument sign attached.

N. 0°00'30" W., on the N-S center line of the SE1/4 of sec. 35.

Over rolling land, through scattered sagebrush and native grass.

41.504

The C-E 1/16 sec. cor. of sec. 35, monumented with a stainless  
steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins.  
above ground, with brass cap mkd. as described in the field  
notes of the survey of the subdivision of section 35, T. 42 N.,  
R. 25 E., executed under Group No. 655, with a mound of stone,  
2 ft. diam., 1 ft. high, W. of cor.

Set a galvanized steel fence post, 6 ft. long, 2 ft. in the  
ground, alongside the stainless steel post with a BLM Land  
Survey Monument sign attached.



SUBDIVISION OF SECTION 36,  
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of sec. 36, on the S. bdy. of the Tp. N. 0°30'40" E., on the N-S center line of sec. 36. Over rolling land, through scattered sagebrush and native grass.</p>
0.20	Barbed wire fence, bears E. and W.
20.760	Point for the C-S 1/16 sec. cor. of sec. 36.  POINT NOT MONUMENTED
41.520	<p>Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T42N R25E C 1/4 S36 2017</p> <p>Set a galvanized steel fence post, 6 ft. long, 2 ft. in the ground, alongside the stainless steel post with a BLM Land Survey Monument sign attached.</p>
62.526	<p>Point for the C-N 1/16 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16   S36 C 2017</p> <p>Set 2 galvanized steel fence posts, 6 ft. long, 2 ft. in the ground, N. and E., alongside the stainless steel post, with BLM Land Survey Monument sign attached.</p>
69.00	Unimproved dirt two-track road, 18 lks. wide, bears N. 83° E. and S. 83° W.
81.70	Barbed wire fence, bears E. and W.
83.532	The 1/4 sec. cor. of secs. 25 and 36. <hr/>
	<p>From the 1/4 sec. cor. of secs. 35 and 36. N. 89°57'00" E., on the E-W center line of sec. 36, on a weighted mean bearing. Over rolling land, through scattered sagebrush and native grass.</p>
41.992	The center 1/4 sec. cor. of sec. 36.
62.329	Point for the C-E 1/16 sec. cor. of sec. 36.


SUBDIVISION OF SECTION 36,  
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S36 2017</p>
63.40	<p>Set 2 galvanized steel fence posts, 6 ft. long, 2 ft. in the ground, N. and S., alongside the stainless steel post, with BLM Land Survey Monument sign attached.</p> <p>Soldier Meadows Road, 30 lks. wide, bears N. 34° E. and S. 26° W.</p>
77.566	<p>Intersect the 1988-1991 meander line of Summit Lake.</p> <p>Point for a special meander cor. on the E-W center line of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S / SMC C ——— C 36 2017</p>
	<p>Set a galvanized steel fence post, 6 ft. long, 2 ft. in the ground, alongside the stainless steel post with a BLM Survey Monument sign attached.</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 36.</p> <p>N. 0°30'40" E., on the N-S center line of the NE1/4 of sec. 36, parallel to the N-S center line of sec. 36.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p>
21.000	<p>Point for the NE 1/16 sec. cor. of sec. 36, at intersection with the E-W center line of the NE1/4 of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S36 2017</p>
23.40	<p>Set 2 galvanized steel fence posts, 6 ft. long, 2 ft. in the ground, S. and W., alongside the stainless steel post, with BLM Land Survey Monument sign attached.</p> <p>Soldier Meadows Road, 30 lks. wide, bears S. 6° E. and N. 6° W.</p>
32.670	<p>Intersect the adjusted 1873 meander line of Summit Lake.</p>

SUBDIVISION OF SECTION 36,  
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>Point for a special meander cor. on the N-S center line of the NE1/4 of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 36.</p> <p>N. 89°58'00" E., on the E-W center line of the NE1/4 of sec. 36, on a weighted mean bearing.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p> <p>20.335 The NE 1/16 sec. cor. of sec. 36.</p> <p>20.70 Soldier Meadows Road, 30 lks. wide, bears S. 6° E. and N. 6° W.</p> <p>25.616 Intersect the adjusted 1873 meander line of Summit Lake.</p> <p>Point for a special meander cor. on the E-W center line of the NE1/4 of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;">  </div> <hr/> <p>Set a galvanized steel fence post, 6 ft. long, 2 ft. in the ground, alongside the stainless steel post with a BLM Land Survey Monument sign attached.</p> <hr/> <p>From the point for the E 1/16 sec. cor. of sec. 36, on the S. bdy. of the Tp.</p> <p>N. 0°04'50" W., on the N-S center line of the SE1/4 of sec. 36.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p> <p>20.379 Point for the SE 1/16 sec. cor. of sec. 36, at intersection with the E-W center line of the SE1/4 of sec. 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>
---------------	--

SUBDIVISION OF SECTION 36,  
T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	SE 1/16 S36 2017
	Set 2 galvanized steel fence posts, 6 ft. long, 2 ft. in the ground, N. and E., alongside the stainless steel post, with BLM Land Survey Monument sign attached.
20.60	Unimproved dirt two-track road, 12 lks. wide, bears E. and W.
31.10	Soldier Meadows Road, 30 lks. wide, bears N. 32° E. and S. 32° W.
41.500	The C-E 1/16 sec. cor. of sec. 36.
	<hr/> From the point for the C-S 1/16 sec. cor. of sec. 36. S. 89°02'30" E., on the E-W center line of the SE1/4 of sec. 36. Over rolling land, through scattered sagebrush and native grass.
18.90	Soldier Meadows Road, 30 lks. wide, bears S. 18° E. and N. 18° W.
20.556	The SE 1/16 sec. cor. of sec. 36.
30.936	Intersect the 1988-1991 meander line of Summit Lake.
	Point for a special meander cor. on the E-W center line of the SE1/4 of sec. 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	
	Set a galvanized steel fence post, 6 ft. long, 2 ft. in the ground, alongside the stainless steel post with a BLM Land Survey Monument sign attached.
34.35	Enter water of a small bay of Summit Lake.
37.35	Leave water of a small bay of Summit Lake.
41.20	Enter water of Summit Lake.
41.357	The point for the S 1/16 sec. cor. of secs. 31 and 36.
	<hr/>

## T. 42 N., R. 25 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p data-bbox="764 310 1073 331" style="text-align: center;">GENERAL DESCRIPTION</p> <p data-bbox="446 359 1409 491">The land surveyed within Township 42 North, Range 25 East, ranges from about 5,800 to 6,200 ft. above sea level, and is nearly level to rolling. The soil varies from sandy clay, to gravelly and rocky. The vegetation consists of sagebrush, greasewood and bunchgrass.</p> <p data-bbox="446 520 1425 575">Tollhouse Canyon drains southeasterly through section 35, and Summit Lake extends into sections 24, 25 and 36.</p> <p data-bbox="446 600 1406 655">Access into the township is provided by three primary roads; Soldiers Meadows, Cedarville and Summit Lake Roads.</p> <p data-bbox="446 680 1377 735">No mineral formations of consequence were noted during the survey.</p>

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Christopher S. Bourgoine

Supervisory Range Technician



CERTIFICATE OF SURVEY

We, Daniel A. Rash and Stephen J. Grimaldi, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 19th day of September, 2017, we have dependently resurveyed a portion of the south boundary, a portion of the east boundary, a portion of the subdivisional lines, a portion of the 1873 meander lines of Summit Lake and a portion of the 1988-1991 meander lines of Summit Lake, and further subdivided section 35, and subdivided section 36, Township 42 North, Range 25 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

MAY 17 2019

(Date)

*Daniel A. Rash*  
Cadastral Surveyor

MAY 17 2019

(Date)

*Stephen J. Grimaldi*  
Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary, a portion of the east boundary, a portion of the subdivisional lines, a portion of the adjusted 1873 meander lines of Summit Lake and a portion of the 1988-1991 meander lines of Summit Lake, the further subdivision of section 35, and the subdivision of section 36, Township 42 North, Range 25 East, of the Mount Diablo Meridian, Nevada, executed by, Daniel A. Rash and Stephen J. Grimaldi, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

MAY 17 2019

(Date)

*Markham O. Hummer*  
(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 42 North, Range 25 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~