

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SOUTH BOUNDARY
AND A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SECTION 34,
TOWNSHIP 43 NORTH, RANGE 26 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Joseph J. Johnson, Cadastral Surveyor

Under Special Instructions dated August 19, 2014,

and approved August 19, 2014,

which provided for the surveys included under Group No. 936,

and Assignment Instructions dated August 19, 2014.

Survey commenced September 9, 2014

Survey completed August 26, 2016

INDEX DIAGRAM

TOWNSHIP 43 NORTH, RANGE 26 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
			7		
31	32	33	5 34 2	4 35	36

SUBDIVISION OF SECTION 34..... pp 8 - 12

TOWNSHIP 43 NORTH, RANGE 26 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary and a portion of the subdivisional lines and the subdivision of section 34, Township 43 North, Range 26 East, Mount Diablo Meridian, Nevada.

The south boundary was surveyed by U.S. Deputy Surveyor G.W. Garside in 1872 under Contract No. 55. The east boundary was surveyed by U.S. Deputy Surveyors G.W. Garside and C.S. Prebble in 1873 under Contract No. 61. The south and east boundaries were dependently and independently resurveyed by U.S. Surveyor H.W. Reppert and U.S. Transitman H.P. Purlington in 1917 under Group No. 52. The west and north boundaries and the subdivisional lines were surveyed by U.S. Surveyor H.W. Reppert and U.S. Transitman H.P. Purlington in 1917 under Group No. 52.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the position of the original corners and other calls of the original field note record.

In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 936, dated August 19, 2014.

Measurements were made with Trimble R-8 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method. The direction of each line is with reference to the true meridian. All bearings are mean bearings and the distances are reported as horizontal measurement at a mean ground elevation of 5,800 feet above sea level.

The NAD 1983 (2011) (EPOCH:2010.0000) geographic position, of the following corners were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operation Reference Stations (CORS) AJ6962 SHLD SHELDON REFUGE CORS ARP, DK6484 MODB MODOC PLATEAU CORS ARP, DN7467 P731 LILJUNIPERCN2007 CORS ARP, and carried forward by RTK observations.

The 1/4 sec. cor. of sec. 3, on the S. bdy. of the Tp., is as follows:

Latitude: 41°35'46.648" N. Longitude: 118°59'39.933" W.

The cor. of secs. 27, 28, 33 and 34, is as follows:

Latitude: 41°36'33.963" N. Longitude: 119°00'30.774" W.

The mean magnetic declination is 16 1/2° E, as shown on U.S.G.S. 7 1/2 minute quadrangle map "SUMMIT LAKE, NEVADA" dated 1990.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS			
	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.W. Garside in 1872 and a Portion of the Dependent and Independent Resurveys Executed by U.S. Surveyor H.W. Reppert and U.S. Transitman H.P. Purlington in 1917</p> <hr/> <p>Beginning at the cor. of secs. 33 and 34 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above a scattered mound of stone, 3 ft. base, 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy., T. 43 N., R. 26 E., executed under Group No. 52, with a mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <p>Rehabilitate mound around iron post, 3 1/2 ft. base, 1 ft. high, leave mound to west in place.</p> <p>Cor. is located 28 lks. S. of a barbed wire fence, bears E. and W.</p> <p>S. 89°52'40" E., bet. secs. 4 and 34.</p> <p>Across rolling land, covered with sagebrush and bunchgrass, and along S. side of barbed wire fence.</p>		
3.813	<p>The cor. of secs. 3 and 4, T. 42 N., R. 26 E., monumented with a basalt stone, 12x8x4 ins., loosely set, with 3 faint notches on the W. edge, with an iron post, 2 ins. diam., firmly set alongside, flush with the top of a mound of stone, 2 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the independent resurvey of a portion of the S. bdy., T. 43 N., R. 26 E., executed under Group No. 52, with a mound of stone, 3 ft. base, 1 ft. high, S. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T43N R26E</p> <p>S34</p> <hr style="width: 50px; margin: 0 auto;"/> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> </table> <p>T42N R26E</p> <p>2014</p> </div> <p>Bury mkd. stone and invert iron post alongside stainless steel post.</p>	S 4	S 3
S 4	S 3		
13.20	<p>S. 89°59'10" E., bet. secs. 3 and 34.</p> <p>Top of rise.</p>		
14.540	<p>Point for the 80 1/16 sec. cor. of sec. 3 only, T. 42 N., R. 26 E.</p>		

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">————— 80 1/16 S 3 2014</p>
	<p>Cor. is located 34 lks. S. of a barbed wire fence, bears E. and W.</p>
16.166	<p>Point for the W 1/16 sec. cor. of sec. 34 only.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">————— W 1/16 S34 2014</p>
	<p>Cor. is located 32 lks. S. of a barbed wire fence, bears E. and W.</p> <p>From this point, a position determined as the W 1/16 sec. cor. of sec. 34 by John H. Milton, Nevada Professional Land Surveyor No. 5271, in 2001, monumented with a rebar, 5/8 ins. diam., firmly set, projecting 5 ins. above the ground, with plastic cap lying loose alongside, mkd. JOHN H MILTON PLS 5271, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587, bears N. 1° E., 0.015 chs. dist. This position was determined using improper control and is not utilized during the course of this survey.</p> <p>From this same point, an unrecorded rebar, 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with no mks., bears N. 64°38' W., 0.029 chs. dist. This position is not utilized during the course of this survey.</p>
21.30	<p>From this point, the E. end of a barbed wire fence, extending W., bears N., 0.18 chs. dist., at the top of a basalt bench, bears N. and S.</p>
21.35	<p>From this point, the S. end of a barbed wire fence, extending N., bears N., 0.01 chs. dist., at the base of a basalt bench, bears N. and S.</p>
36.144	<p>The 1/4 sec. cor. of sec. 34 only, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd. as described in the independent resurvey of a portion of the S. bdy., T. 43 N., R. 26 E., executed under Group No. 52, with a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p>
	<p>Remark cap as shown</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T43N R26E 1/4 S34</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">T42N</p> <p style="text-align: center;">1917 2014</p>
18.395	<p>Cor. is located 2 lks. S. of a barbed wire fence, bears E. and W.</p> <hr style="width: 50%; margin: auto;"/> <p>N. 89°53'30" E., beginning new measurement.</p> <p>The 1/4 sec. cor. of sec. 3, T. 42 N., R. 26 E., monumented with an iron post, 1 in. diam., loosely set and leaning, projecting 11 ins. above a mound of stone, 5 ft. base, 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the independent resurvey of a portion of the S. bdy., T. 43 N., R. 26 E., executed under Group No. 52.</p> <p>Straighten iron post in place and rehabilitate mound.</p>
	<hr style="width: 80%; margin: auto;"/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr style="width: 80%; margin: auto;"/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Surveyor H.W. Reppert and U.S. Transitman H.P. Purlington in 1917</p> <hr style="width: 80%; margin: auto;"/> <p>From the 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., loosely set and leaning, with the base in place, projecting 20 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines, T. 43 N., R. 26 E., executed under Group No. 52, with a scattered mound of stone, 5 ft. base, 1 ft. high, E. of cor. (Record: W.)</p> <p>Straighten iron post in place and rehabilitate mound.</p> <p>Rebuild witness mound in place, 4 ft. base, 2 ft. high.</p> <p>N. 0°05'00" E., bet. secs. 34 and 35.</p> <p>Across rolling land, covered with sagebrush, scattered bitterbrush, and bunchgrass, posting the bdy. of the Sheldon National Wildlife Refuge with steel sign posts.</p> <p>10.90 Basalt bench, bears NNE. and SSW., descend.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 20.006</p> <p>0.40</p> <p>2.40</p> <p>4.30</p> <p>19.988</p>	<p>The N 1/16 sec. cor. of secs. 34 and 35, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, in 2001, monumented with a rebar, 5/8 ins. diam., 24 ins. long, firmly set, projecting 3 ins. above ground, with damaged plastic cap, the mks. TON remaining, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S34 S35</p> <p style="text-align: center;">2016</p> <p>Deposit rebar inside stainless steel post.</p> <hr/> <p>N. 0°05'00" E., beginning new measurement.</p> <p>Graded dirt road, 25 lks. wide, bears NE. and SW.</p> <p>Powerline, bears N. 43° E. and S. 43° W.</p> <p>Dirt road, 10 lks. wide, bears SSE. and NNW.</p> <p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines, T. 43 N., R. 26 E., executed under Group No. 52, with a mound of stone, 5 ft. base, 1 1/2 ft. high, W. of cor.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the survey of the subdivisional lines, T. 43 N., R. 26 E., executed under Group No. 52, with a mound of stone, 4 ft. base, 2 1/2 ft. high, W. of cor.</p> <p>Cor. is located on edge of basalt rim rock, bears NE. and SW.</p> <p>N. 0°08'30" W., bet. secs. 33 and 34, posting the bdy. of the Sheldon National Wildlife Refuge with steel sign posts.</p> <p>Across rolling land, covered with low sagebrush and bunchgrass.</p>
--	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS 9.995</p>	<p>The S-N 1/64 sec. cor. of secs. 33 and 34, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 ins. diam., 24 ins. long, firmly set, projecting 6 ins. above ground, with damaged illegible plastic cap, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S-N 1/64 S33 S34 2016</p> <p>Deposit rebar inside stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°09'30" W., beginning new measurement.</p>
<p>10.016</p>	<p>The N 1/16 sec. cor. of secs. 33 and 34, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 ins. diam., 24 ins. long, firmly set, projecting 5 ins. above ground, with damaged illegible plastic cap, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S33 S34 2016</p> <p>Deposit rebar inside stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°03'30" W., beginning new measurement.</p>
<p>9.991</p>	<p>The N-N 1/64 sec. cor. of secs. 33 and 34, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 ins. diam., 24 ins. long, firmly set, projecting 6 ins. above ground, with damaged illegible plastic cap, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N-N 1/64 S33 S34</p> <p style="text-align: center;">2016</p> <p>Bury rebar alongside stainless steel post.</p> <hr/> <p>N. 0°09'30" W., beginning new measurement.</p>
10.014	<p>The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., loosely set and leaning, the base still in place, projecting 20 ins. above a scattered mound of stone, 3 ft. base, 1 ft. high, with a brass cap mkd. as described in the field notes of the survey of the subdivisional lines, T. 43 N., R. 26 E., executed under Group No. 52, with a mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p> <p>Straighten iron post in place and rehabilitate mound, 4 ft. base, 1 1/2 ft. high.</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°56'50" W., bet. secs. 27 and 34.</p> <p>Across rolling land, covered with sagebrush, scattered bitterbrush and bunchgrass, with some rabbit brush in draws, posting the bdy. of the Sheldon National Wildlife Refuge with steel sign posts.</p>
6.00	<p>Descend into draw.</p>
20.040	<p>The E 1/16 sec. cor. of secs. 27 and 34, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 ins. diam., 24 ins. long, firmly set, projecting 6 ins. above ground, with damaged illegible plastic cap, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S27 E 1/16 — S34 2016
	Deposit rebar inside stainless steel post.

	S. 89°56'50" W., beginning new measurement.
0.90	Dirt road, 10 lks. wide, in bottom of draw, bears NNE. and SSE.
10.20	Dry stream bed, drains N.
20.040	The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with a brass cap mkd. as described in the field notes of the survey of the subdivisional lines, T. 43 N., R. 26 E., executed under Group No. 52, with a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.

	S. 89°57'40" W., beginning new measurement.
9.20	Rim rock, bears N. and S.
22.00	Rim rock, bears N. and S.
25.00	Summit, thence descend.
40.062	The cor. of secs. 27, 28, 33 and 34.

	SUBDIVISION OF SECTION 34, T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

	From the 1/4 sec. cor. of sec. 34, on the S. bdy. of the Tp.
	N. 0°04'50" W., on the N-S center line of sec. 34.
	Across rolling land, covered with sagebrush, scattered bitterbrush and bunchgrass, posting the bdy. of the Sheldon National Wildlife Refuge with steel sign posts.
8.50	Graded dirt road, 20 lks. wide, bears NE. and SW.
10.00	Powerline, bears N. 36° E. and S. 36° W.
12.607	The C-S 1/16 sec. cor. of sec. 34, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 ins. diam., 24 ins. long, firmly set, projecting 12 ins. above ground, with damaged plastic cap, the mks. JOHN PLS 52 remaining, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587. This is accepted as a careful and faithful determination of the position of the corner.

SUBDIVISION OF SECTION 34,
T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S34 C</p> <p style="text-align: center;">2016</p> <p>Deposit rebar inside stainless steel post.</p> <hr/> <p>N. 0°04'50" W., beginning new measurement.</p> <p>20.035 The center 1/4 sec. cor. of sec. 34, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 ins. diam., 24 ins. long, firmly set, projecting 12 ins. above ground, with damaged plastic cap, the mks. JOHN PLS 52 remaining, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T43N R26E C 1/4 S34</p> <p style="text-align: center;">2014</p> <p>Deposit rebar inside stainless steel post.</p> <p>Discontinue posting the bdy. of the Sheldon National Wildlife Refuge with steel sign posts.</p> <hr/> <p>N. 0°02'40" W., beginning new measurement.</p> <p>10.010 The C-S-N 1/64 sec. cor. of sec. 34, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 ins. diam., firmly set, projecting 6 ins. above ground, with damaged plastic cap, the mks. PLS 527 remaining, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587. This is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 0°04'50" W., beginning new measurement.</p>
---------------	--

SUBDIVISION OF SECTION 34,
T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.997	<p>The C-N 1/16 sec. cor. of sec. 34, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 ins. diam., firmly set, projecting 5 ins. above ground, with damaged illegible plastic cap, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587. This is accepted as a careful and faithful determination of the position of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03'20" W., beginning new measurement.</p>
10.002	<p>The C-N-N 1/64 sec. cor. of sec. 34, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 ins. diam., firmly set, projecting 6 ins. above ground, with damaged plastic cap, the mks. MILTON remaining, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587. This is accepted as a careful and faithful determination of the position of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01'40" W., beginning new measurement.</p>
9.996	<p>The 1/4 sec. cor. of secs. 27 and 34.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>S. 89°56'00" W., on the E-W center line of sec. 34.</p> <p>Across rolling land, covered with sagebrush, scattered bitterbrush and bunchgrass, posting the bdy. of the Sheldon National Wildlife Refuge with steel sign posts.</p>
12.20	<p>Graded dirt road, 25 lks. wide, bears NNE. and SSW.</p>
19.982	<p>The C-E 1/16 sec. cor. of sec. 34, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 ins. diam., 24 ins. long, firmly set, projecting 4 ins. above ground, with damaged plastic cap, the mks. PLS remaining, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>E 1/16</p> <p>C——C</p> <p>S34</p> <p>2016</p> </div> <p>Deposit rebar inside stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/>

SUBDIVISION OF SECTION 34,
T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S. 89°56'00" W., beginning new measurement.</p>
0.60	Powerline, bears N. 43° E. and S. 43° W.
20.007	<p>The center 1/4 sec. cor. of sec. 34.</p> <p>Discontinue posting the bdy. of the Sheldon National Wildlife Refuge with steel sign posts.</p> <hr/> <p>S. 89°56'40" W., beginning new measurement.</p>
7.40	Cross flat top ridge, 1.50 chs. wide, bears NE. and SW. This ridge separates 2 draws draining NE. This point is 2.00 chs. SW. of the North end of the ridge.
19.994	<p>The C-W 1/16 sec. cor. of sec. 34, determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 ins. diam., 24 ins. long, loosely set and leaning, the base undisturbed, projecting 12 ins. above a mound of stone, 2 1/2 ft. base, 1/2 ft. high, with plastic cap mkd. JOHN H. MILTON PLS 5271, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>W 1/16</p> <p>C———C</p> <p>S34</p> <p>2014</p> </div> <p>Deposit rebar inside stainless steel post.</p> <hr/> <p>S. 89°56'40" W., beginning new measurement.</p> <p>Begin posting the bdy. of the Sheldon National Wildlife Refuge with steel sign posts.</p>
20.018	<p>The 1/4 sec. cor. of secs. 33 and 34.</p> <hr/> <p>From the W 1/16 sec. cor. of sec. 34, on the S. bdy. of the Tp. N. 0°06'30" W., on the N-S center line of the SW1/4 of sec. 34.</p> <p>Across rolling land, covered with sagebrush, scattered bitterbrush and bunchgrass, posting the bdy. of the Sheldon National Wildlife Refuge with steel sign posts.</p>

SUBDIVISION OF SECTION 34,
T. 43 N., R. 26 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
12.591	From this point, a position determined by John H. Milton, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 ins. diam., firmly set, projecting 7 ins. above ground, as recorded in the Office of the Recorder, Humboldt County, Nevada, Document No. 2001 587, bears WEST, 0.011 chs. dist.
32.617	The C-W 1/16 sec. cor. of sec. 34.
<hr/>	
GENERAL DESCRIPTION	
The area resurveyed within T. 43 N., R. 26 E., is about 6 miles northeast of Summit Lake, Nevada. Access to the area is by Summit Lake Road. The terrain consists mainly of rolling hills and volcanic ledges. The vegetation is sagebrush and native grasses. No water was encountered during the course of this survey. No remains of the Stanley Ranch were found.	
<hr/>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Mark G. Petrosine

Surveying Technician

CERTIFICATE OF SURVEY

I, Joseph J. Johnson, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 19th day of August, 2014, I have dependently resurveyed a portion of the south boundary and a portion of the subdivisional lines and subdivided section 34, Township 43 North, Range 26 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

SEP 28 2016

(Date)



(Cadastral Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary and a portion of the subdivisional lines and the subdivision of section 34, Township 43 North, Range 26 East, of the Mount Diablo Meridian, Nevada, executed by Joseph J. Johnson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

SEP 28 2016

(Date)



(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 43 North, Range 26 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~