

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE SURVEY OF

A PORTION OF THE SOUTH BOUNDARY AND
A PORTION OF THE SUBDIVISIONAL LINES,
THE SUBDIVISION OF SECTIONS 18 AND 19,
AND THE DEPENDENT RESURVEY OF A PORTION OF
HOMESTEAD ENTRY SURVEY NO. 167,
TOWNSHIP 45 NORTH, RANGE 54 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Steven W. Bell, Land Surveyor (U.S.F.S.)

Under Special Instructions dated May 4, 2018,
and approved May 4, 2018,
and Amended Special Instructions dated October 24, 2019,
and approved October 24, 2019,
which provided for the surveys included under Group No. 984,
and Assignment Instructions dated May 4, 2018.

Survey commenced June 5, 2018

Survey completed June 11, 2020

INDEX DIAGRAM

TOWNSHIP 45 NORTH, RANGE 54 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
8 18 7	17	16	15	14	13
5 19 4 3	20	21	22	23	24
30	29	28	27	26	25
31 2	32	33	34	35	36

Subdivision of Section 18..... pp 9 -13
 Subdivision of Section 19..... pp 13-17
 Dependent Resurvey of Homestead Entry Survey No. 167..... pp 17-21

TOWNSHIP 45 NORTH, RANGE 54 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the survey of a portion of the south boundary and a portion of the subdivisional lines, the subdivision of sections 18 and 19, and the dependent resurvey of a portion of Homestead Entry Survey No. 167, Township 45 North, Range 54 East, Mount Diablo Meridian, Nevada.

The north boundary (Ninth Standard Parallel North) was surveyed by U.S. Deputy Surveyor D.C. Scully in 1896, under contract No. 209. The east boundary was surveyed by U.S. Deputy Surveyors L.H. Taylor and W.A. Kiddie in 1902, under Contract No. 232. Homestead Entry Survey No. 167 was surveyed by Forest Examiner W.B. Rice in 1918. The west boundary was surveyed by U.S. Surveyor C.S. Swanholm in 1920-1921, under Group No. 73. Nevada Protraction Diagram No. 135, Unit No. 3, for Tps. 44 and 45 N., R. 54 E. was approved in 1963. The dependent resurvey of a portion of the west boundary was executed concurrently under Group No. 982.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the position of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions dated May 4, 2018 and the Amended Special Instructions dated October 24, 2019, for Group No. 984.

Measurements were made with Trimble R-8 Global Navigation Satellite System (GNSS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 1983 (2011) (EPOCH:2010.0000) geographic position, of the following corners were determined from GNSS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) DP9275 P018 PHARMACY OR2008 CORS ARP, DL7761 P739 MCDERMITT OR2008 CORS ARP and AH8524 BURNS BURNS_JUNCTION_CORS ARP, and carried forward by RTK observations.

The cor. of Tps. 44 and 45 N., Rs. 53 and 54 E., is as follows:

Latitude: 41°44'43.665" N. Longitude: 115°56'52.119" W.

The cor. of secs. 7, 8, 17 and 18, is as follows:

Latitude: 41°48'12.258" N. Longitude: 115°55'42.424" W.

SURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS																	
	<p>From the cor. of Tps. 44 and 45 N., Rs. 53 and 54 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p>																
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T45N</td></tr> <tr><td>R53E</td><td>R54E</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td>R53E</td><td>R54E</td></tr> <tr><td colspan="2">T44N</td></tr> <tr><td colspan="2">1920</td></tr> </table>	T45N		R53E	R54E	S36	S31	— —		S 1	S 6	R53E	R54E	T44N		1920	
T45N																	
R53E	R54E																
S36	S31																
— —																	
S 1	S 6																
R53E	R54E																
T44N																	
1920																	
	<p>with a mound of stone, 3 ft. diam., 1 ft. high, S. of cor. East, bet. secs. 6 and 31.</p> <p>Over rolling terrain.</p>																
1.00	Barbed wire fence, bears N. and S.																
35.30	Wash, drains SW.																
40.000	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>																
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T45N R54E</td></tr> <tr><td colspan="2">S31</td></tr> <tr><td>1/4</td><td>—</td></tr> <tr><td colspan="2">S 6</td></tr> <tr><td colspan="2">T44N</td></tr> <tr><td colspan="2">2018</td></tr> </table>	T45N R54E		S31		1/4	—	S 6		T44N		2018					
T45N R54E																	
S31																	
1/4	—																
S 6																	
T44N																	
2018																	
	<p>Set an aluminum sign post alongside stainless steel post.</p>																
75.40	Sharp ledge bears N. and S., desc. steep E. slope.																
80.000	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>																
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T45N R54E</td></tr> <tr><td>S31</td><td>S32</td></tr> <tr><td colspan="2">— —</td></tr> <tr><td>S 6</td><td>S 5</td></tr> <tr><td colspan="2">T44N</td></tr> <tr><td colspan="2">2018</td></tr> </table>	T45N R54E		S31	S32	— —		S 6	S 5	T44N		2018					
T45N R54E																	
S31	S32																
— —																	
S 6	S 5																
T44N																	
2018																	

SURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
	<p>Set an aluminum sign post alongside stainless steel post.</p> <p>Land, rolling terrain Soil, rocky and clay loam Undergrowth is recently burned</p> <hr/> <p style="text-align: center;">SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Beginning at the point for the cor. of secs. 19, 20, 29 and 30, determined at 160.000 chs. dist. from the cor. of secs 5, 6, 31 and 32, hereinbefore described, and parallel with the W. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">T45N R54E</td> </tr> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black;">S19</td> <td style="border-bottom: 1px solid black;">S20</td> </tr> <tr> <td style="border-right: 1px solid black;">S30</td> <td>S29</td> </tr> </table> <p>2018</p> </div> <p>Set an aluminum sign post alongside stainless steel post.</p> <p>From this point, the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described, bears S. 0°00'50" W., 160.000 chs. dist.</p> <p>S. 89°53'10" W., bet. secs. 19 and 30.</p> <p>Over mountainous terrain through light undergrowth.</p>	T45N R54E		S19	S20	S30	S29
T45N R54E							
S19	S20						
S30	S29						
39.992	<p>Point for the 1/4 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td colspan="2">T45N R54E</td> </tr> <tr> <td colspan="2">S19</td> </tr> <tr> <td style="border-right: 1px solid black;">1/4</td> <td style="border-bottom: 1px solid black;">S30</td> </tr> </table> <p>2018</p> </div>	T45N R54E		S19		1/4	S30
T45N R54E							
S19							
1/4	S30						
43.15	<p>Set an aluminum sign post alongside stainless steel post.</p> <p>Barbed wire fence, bears S. 5° E. and N. 5° W.</p>						
47.233	<p>Intersect line 6-7 of H.E.S. No. 167, at a point from which Cor. No. 7, H.E.S. No. 167, hereinafter described, bears S. 1°42'20" E., 11.975 chs. dist.</p>						

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
53.60	Right bank of the Owyhee River, bears NE. and SW., thence across river, course NE.
54.30	Left bank of the Owyhee River, bears NE. and SW.
54.50	Enter cultivated field, edge bears NE. and SW.
55.10	Leave cultivated field, edge bears N. and S.
55.15	Barbed wire fence, bears N. and S.
55.40	Irrigation ditch, drains N.
55.90	Nevada State Route No. 225, asphalt surfaced, 35 lks. wide, bears N. and S.
56.80	Barbed wire fence, bears N. 5° E. and S. 5° W.
57.121	Intersect line 2-3 of H.E.S. No. 167, at a point from which Cor. No. 2, H.E.S. No. 167, hereinafter described, bears S. 18°17'00" E., 14.181 chs. dist.
64.30	Power line, bears S. 30° E. and N. 30° W.
79.00	Gravel road, County Road No. 729, 30 lks. wide, bears NE. and SW.
79.984	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, flush with a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the survey of the E. bdy. of T. 45 N., R. 53 E., executed under Group No. 73.
	Land, mountainous terrain Soil, rocky and clay loam, valley bottoms, fertile loam Undergrowth is sage and native grasses, valley floor, hay and willows
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°00'50" E., bet. secs. 19 and 20.
	Over rolling terrain through light undergrowth.
4.30	Trail road, 15 lks. wide, bears S. 25° E. and N. 25° W.
8.40	Wash, drains NE.
10.20	Spur, slopes SE.
11.10	Draw, drains W.
40.000	Point for the 1/4 sec. cor. of secs. 19 and 20. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T45N R54E 1/4 S19 S20</p> <p style="text-align: center;">2018</p> <p>Set an aluminum sign post alongside stainless steel post.</p>
43.10	Draw, drains W.
73.30	Draw, drains SW.
80.000	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T45N R54E S18 S17 ----- S19 S20</p> <p style="text-align: center;">2018</p> <p>Set an aluminum sign post alongside stainless steel post.</p> <p>Land, rolling terrain Soil, rocky and clay loam Undergrowth is sage and native grasses</p> <hr/> <p>S. 89°46'00" W., bet. secs. 18 and 19.</p> <p>Over mountainous terrain, through dense sage brush.</p>
0.15	Trail road, 15 lks. wide, bears N. 10° E. and S. 10° W.
18.15	Trail road, 15 lks. wide, bears N. 5° E. and S. 5° W.
39.984	<p>Point for the 1/4 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T45N R54E S18 1/4 ----- S19</p> <p style="text-align: center;">2018</p> <p>Set an aluminum sign post alongside stainless steel post.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.55	Barbed wire fence, bears N. 25° E. and S. 25° W.
59.976	Point for the W 1/16 sec. cor. of secs. 18 and 19. POINT NOT MONUMENTED
62.475	Point for the E-E-W-W 1/1024 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. 1/1024 2019 Set an aluminum sign post alongside stainless steel post.
62.65	Barbed wire fence, N. 20° W., 0.37 chs. dist. of fence corner with fences extending S. 70° W. and N. 20° W.
64.974	Point for the E-W-W 1/256 sec. cor. of secs. 18 and 19. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. S18 E-W-W 1/256 S19 2018 Set an aluminum sign post alongside stainless steel post.
67.05	Trail road, 15 lks. wide, bears S. 5° E. and N. 5° W.
68.00	Chain link fence, 4 ft. high, bears S. 25° E. and N. 25° W.
68.35	Intersect the SE. corner of a wood frame building, 59 x 25 ft., the long side bears S. 65° W.
70.95	Trail road, 15 lks. wide, bears N. 55° E. and S. 55° W.
77.55	Barbed wire fence, bears S. 40° E. and N. 40° W.
78.50	Trail road, 15 lks. wide, bears S. 30° E. and N. 30° W.
79.968	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 45 N., R. 53 E., executed concurrently under Group No. 982.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Land, mountainous and rolling terrain Soil, rocky and clay loam Undergrowth is sage, bitter brush, and native grasses</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20. N. 0°00'50" E., bet. secs. 17 and 18. Over rolling land through light undergrowth.</p>
0.75	Trail road, 15 lks. wide, bears NNE. and SSW.
40.000	<p>Point for the 1/4 sec. cor. of secs. 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T45N R54E 1/4 S18 S17 2018</p>
	Set an aluminum sign post alongside stainless steel post.
44.05	Barbed wire fence, bears N. 80° E. and S. 80° W.
79.70	Top of road cut, bears E. and W.
79.85	Edge of dirt road, bears E. and W.
80.000	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of dirt road, deposit plastic-encased magnet alongside, with brass cap mkd.</p> <p style="text-align: center;">T45N R54E S 7 S 8 ----- S18 S17 2018</p>
	<p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic encased magnet, for a reference monument, on S. side of road, bears S. 45°00' E., 45.5 lks. dist., with brass cap mkd. RM T45N R54E S17 30.0 FT TO COR 2018 and an arrow pointing to the cor.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic encased magnet, for a reference monument, on S. side of road, bears S. 45°00' W., 45.5 lks. dist., with brass cap mkd. RM T45N R54E S18 30.0 FT TO COR 2018 and an arrow pointing to the cor.</p> <p>Cor. located in Forest Service Road No. 930, 30 lks. wide, bears S. 85° E. and N. 85° W.</p> <p>Land, rolling Soil, rocky and clay loam Undergrowth is sage, bitter brush, and native grasses</p> <hr/> <p>S. 89°40'50" W., bet. secs. 7 and 18.</p> <p>Over dirt road bed.</p>
3.05	Leave dirt road bed, edge bears S. 85° E. and N. 85° W. Enter rolling land through light undergrowth.
13.30	Trail road, 15 lks. wide, bears SSE. and NNW.
26.30	Spur, slopes N.
28.10	Draw, drains N.
35.10	Ridge, bears N. and S.
39.951	Point for the 1/4 sec. cor. of secs. 7 and 18.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T45N R54E S 7 1/4 ——— S18 2018</p>
	Set an aluminum sign post alongside stainless steel post.
55.90	Dirt road, 30 lks. wide, bears N. 45° E. and S. 45° W.
58.90	Dry creek bed, 30 lks. wide, course SW.
79.902	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above a mound of stone, 4 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 45 N., R. 53 E., executed concurrently under Group No. 982.</p> <p>Set an aluminum sign post alongside iron post.</p>

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Land, rolling terrain Soil, rocky and clay loam Undergrowth is sage and native grasses</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 18, T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 18 and 19. N. 0°01'30" E., on the N-S center line of sec. 18. Over rolling terrain through medium undergrowth.</p>
1.25	Barbed wire fence, bears N. 25° E. and S. 25° W.
19.994	Point for the C-S 1/16 sec. cor. of sec. 18. POINT NOT MONUMENTED
25.00	Trail road, 15 lks. wide, bears E. and W.
39.988	Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E-W center line of sec. 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T45N R54E C 1/4 S18 2018
51.95	Set an aluminum sign post alongside stainless steel post. Barbed wire fence, bears S. 80° E. and N. 80° W.
79.942	The 1/4 sec. cor. of secs. 7 and 18. <hr/>
	<p>From the 1/4 sec. cor. of secs. 17 and 18. S. 89°44'50" W., on the E-W center line of sec. 18.</p>
9.45	Trail road, 15 lks. wide, bears S. 25° E. and N. 25° W.
21.60	Barbed wire fence, bears S. 80° E. and N. 80° W.
27.15	Barbed wire fence, bears S. 10° E. and N. 10° W.
39.964	The center 1/4 sec. cor. of sec. 18.
59.948	Point for the C-W 1/16 sec. cor. of sec. 18. POINT NOT MONUMENTED

SUBDIVISION OF SECTION 18,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
68.65	Barbed wire fence, bears N. 15° E. and S. 15° W.
77.90	Dirt road, 30 lks. wide, bears N. 25° E. and S. 25° W.
78.90	Barbed wire fence, bears S. and NW.
79.80	Draw, drains SW.
79.932	The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 45 N., R. 53 E., executed concurrently under Group No. 982, with a mound of stone, 3 ft. diam., 1/2 ft. high, W. of the cor.
	From the point for the W 1/16 sec. cor. of secs. 18 and 19. N. 0°01'40" E., on the N-S center line of the SW1/4 of sec. 18.
9.996	Point for the C-S-SW 1/64 sec. cor. of sec. 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. S18 C-S-SW 1/64 2018 Set an aluminum sign post alongside stainless steel post.
14.994	Point for the C-N-S-SW 1/256 sec. cor. of sec. 18. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. S18 C-N-S-SW 1/256 2020 Set an aluminum sign post alongside stainless steel post.
19.992	Point for the SW 1/16 sec. cor. of sec. 18, at intersection with the E-W center line of the SW1/4 of sec. 18. POINT NOT MONUMENTED
24.05	Trail road, 15 lks. wide, bears E. and W.

SUBDIVISION OF SECTION 18,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.981	<p>The point for the C-W 1/16 sec. cor. of sec. 18.</p> <hr/> <p>From the point for the C-S 1/16 sec. cor. of sec. 18. S. 89°45'20" W., on the E-W center line of the SW1/4 of sec. 18.</p>
17.486	<p>Point for the C-W-W-E-SW 1/1024 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">1/1024 2018</p> <p>Set an aluminum sign post alongside stainless steel post.</p>
19.984	<p>The point for the SW 1/16 sec. cor. of sec. 18.</p>
26.75	<p>Trail road, 15 lks. wide, bears NE. and SW.</p>
33.50	<p>Barbed wire fence, bears S. 10° E. and N. 10° W.</p>
34.972	<p>Point for the C-W-W-SW 1/256 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S18 C-W-W-SW 1/256 2018</p> <p>Set an aluminum sign post alongside stainless steel post.</p>
36.85	<p>Chain link fence, 4 ft. tall, bears N. 15° E. and S. 15° W.</p>
37.10	<p>Intersect the east side of a wood frame building, 99 x 29 ft., the SE. corner bears S. 5° E., 8 lks. dist., the long side bears N. 5° W.</p>
38.20	<p>Gravel road, 15 lks. wide, bears S. and NW.</p>
38.55	<p>Gravel road, 15 lks. wide, bears NE. and S.</p>
39.968	<p>The point for the S 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., as determined by the dependent resurvey of a portion of the E. bdy. of T. 45 N., R. 53 E., executed concurrently under Group No. 982.</p> <hr/> <p>From the C-N-S-SW 1/256 sec. cor. of sec. 18.</p>

SUBDIVISION OF SECTION 18,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	N. 89°45'30" E., on a portion of the computed E-W center line of the NW1/4SE1/4SW1/4 of sec. 18.
2.498	Point for C-W-NW-SE-SW 1/1024 sec. cor. of sec. 18, at its computed position. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. 1/1024 2018 Set an aluminum sign post alongside stainless steel post.
	N. 0°01'40" E., on the computed N-S center line of the NW1/4NW1/4SE1/4SW1/4 of sec. 18.
4.998	The C-W-W-E-SW 1/1024 sec. cor. of sec. 18. From the E-E-W-W 1/1024 sec. cor. of sec. 18 and 19.
	N. 0°01'40" E., on the computed N-S center line of the SE1/4SE1/4SW1/4SW1/4 of sec. 18.
4.998	Point for the C-E-SE-SW-SW 1/1024 sec. cor. of sec. 18, at its computed position. POINT NOT MONUMENTED
	N. 0°01'40" E., on the computed N-S center line of the NE1/4SE1/4SW1/4SW1/4 of sec. 18.
4.998	Point for the C-E-E-SW-SW 1/1024 sec. cor. of sec. 18, at its computed position. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. 1/1024 2018 Set an aluminum sign post alongside stainless steel post.
	N. 89°45'40" E., on a portion of the computed E-W center line of the SW1/4SW1/4 of sec. 18.
2.498	The C-S-SW 1/64 sec. cor. of sec. 18.

SUBDIVISION OF SECTION 18,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-W-W-SW 1/256 sec. cor. of sec. 18.</p> <p>N. 0°01'40" E., on a portion of the computed N-S center line of the SW1/4NW1/4SW1/4 of sec. 18.</p> <p>1.30 Barbed wire fence, bears S. 80° E. and N. 80° W.</p> <p>4.998 Point for the SW-NW-SW 1/256 sec. cor. of sec. 18, at intersection with the computed E-W center line of the SW1/4NW1/4SW1/4 of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S18 SW-NW-SW 1/256</p> <p style="text-align: center;">2018</p> <p>Set an aluminum sign post alongside stainless steel post.</p> <hr/> <p>S. 89°45'10" W., on a portion of the computed E-W center line of the SW1/4NW1/4SW1/4 of sec. 18.</p> <p>4.996 The point for the S-N-S 1/256 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush with a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 45 N., R. 53 E., executed concurrently under Group No. 982.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 19, T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 30.</p> <p>N. 0°01'10" E., on the N-S center line of sec. 19.</p> <p>35.90 Draw, drains W.</p> <p>39.964 Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E-W center line of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., over chiseled X in solid rock, with a plastic-encased magnet at base, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
--------	--

SUBDIVISION OF SECTION 19,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T45N R54E C 1/4 S19
	2018
	Set an aluminum sign post alongside stainless steel post.
45.40	Ridge, bears NE. and SW.
54.40	Draw, drains SW.
59.940	Point for the C-N 1/16 sec. cor. of sec. 19.
	POINT NOT MONUMENTED
79.916	The 1/4 sec. cor. of secs. 18 and 19.
	<hr/>
	From the 1/4 sec. cor. of secs. 19 and 20.
	S. 89°50'10" W., on the E-W center line of sec. 19.
15.40	Trail road, 15 lks. wide, bears NE. and SW.
15.70	Draw, drains SW.
39.984	The center 1/4 sec. cor. of sec. 19.
48.30	Draw, drains NW.
51.15	Barbed wire fence, bears S. 20° E. and N. 20° W.
51.276	Intersect line 5-6 of H.E.S. No. 167, at a point from which Cor. No. 6 of H.E.S. No. 167, hereinafter described, bears S. 17°22'10" E., 10.552 chs. dist.
56.80	Right bank of the Owyhee River, bears NE. and SW., thence across river, course NE.
57.45	Left bank of the Owyhee River, bears NE. and SW.
59.977	Point for the C-W 1/16 sec. cor. of sec. 19.
	POINT NOT MONUMENTED
65.746	Intersect line 3-4 of H.E.S. No. 167, at a point from which Cor. No. 3 of H.E.S. No. 167, hereinafter described, bears S. 14°03'00" W., 8.107 chs. dist.
65.75	Barbed wire fence, bears N. 15° E. and S. 15° W.
66.85	Power line, bears N. 15° E. and S. 15° W.
67.75	Nevada State Route No. 255, asphalt surfaced, 35 lks. wide, bears NNE. and SSW.
72.95	Barbed wire fence, bears N. 20° E. and S. 20° W.

SUBDIVISION OF SECTION 19,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
79.970	The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 45 N., R. 53 E., executed concurrently under Group No. 982, with a mound of stone, 3 ft. diam., 1 ft. high, SE. of the cor.

	From the point for the C-W 1/16 sec. cor. of sec. 19.
	N. 0°01'20" E., on the N-S center line of the NW1/4 of sec. 19.
3.45	Left bank of the Owyhee River, bears SSE. and NNW., thence across river, course NNW.
9.021	Intersect line 4-5 of H.E.S. No. 167, at a point from which Cor. No. 4 of H.E.S. No. 167, hereinafter described, bears S. 73°39'00" W., 3.949 chs. dist.
10.15	Right bank of the Owyhee River, bears SE. and NW.
13.95	Right bank of the Owyhee River, bears NE. and SW., thence across river, course NE.
14.65	Left bank of the Owyhee River, bears NE. and SW.
19.964	Point for the NW 1/16 sec. cor. of sec. 19, at intersection with the E-W center line of the NW1/4.
	POINT NOT MONUMENTED
23.25	Trail road, bears E. and W.
27.45	Left bank of the Owyhee River, bears SE. and NW., thence across river, course NW.
28.40	Right bank of Owyhee River, bears SE. and NW.
39.928	The point for the W 1/16 sec. cor. of secs. 18 and 19.

	From the point for the C-N 1/16 sec. cor. of sec. 19.
	S. 89°48'00" W., on the E-W center line of the NW1/4 of sec. 19.
11.80	Right bank of the Owyhee River, bears SE. and NW., thence across river, course NW.
13.45	Left bank of the Owyhee River, bears SE. and NW.
19.990	The point for the NW 1/16 sec. cor. of sec. 19.
25.30	Barbed wire fence, bears S. 45° E. and N. 45° W.
27.25	Power line, bears S. 75° E. and N. 75° W.
30.30	Nevada State Route No. 225, asphalt surfaced, 35 lks. wide, bears SE. and WNW.

SUBDIVISION OF SECTION 19,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.980	<p>The point for the N 1/16 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., as determined by the dependent resurvey of a portion of the E. bdy. of T. 45 N., R. 53 E., executed concurrently under Group No. 982.</p> <hr/> <p>From the E-W-W 1/256 sec. cor. of secs. 18 and 19.</p> <p>S. 0°01'20" W., on the computed N-S center line of the NE1/4NW1/4NW1/4 of sec. 19.</p>
1.15	Barbed wire fence, bears N. 70° E. and S. 70° W.
7.35	Barbed wire fence, bears SE. and NW.
9.452	<p>Point selected for the witness cor. to the C-E-NW-NW 1/256 sec. cor. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC S19 C-E-NW-NW 1/256 ↓ 2018</p> </div> <p>Set an aluminum sign post alongside stainless steel post.</p>
9.65	Right bank of the Owyhee River, bears SE. and NW., thence across river, course NW.
9.982	True point for the C-E-NW-NW 1/256 sec. cor. of sec. 19, at its computed position, falls within the channel of the Owyhee River where it is impractical to establish a permanent monument.
0.85	<p>S. 89°47'00" W., on a portion of the computed E-W center line of the NW1/4NW1/4 of sec. 19.</p> <p>Left bank of the Owyhee River, bears SE. and NW.</p>
4.997	<p>Point for the NW-NW 1/64 sec. cor. of sec. 19, at intersection with the computed N-S center line of the NW1/4NW1/4 of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

SUBDIVISION OF SECTION 19,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	S19 NW-NW 1/64 2018
	Set an aluminum sign post alongside stainless steel post.
9.85	Left bank of the Owyhee River, bears NE. and SW., thence across river, course SW.
10.50	Right bank of the Owyhee River, bears NE. and S.
14.992	The N-N 1/64 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 45 N., R. 53 E., executed concurrently under Group No. 982.
<hr/> DEPENDENT RESURVEY OF A PORTION OF HOMESTEAD ENTRY SURVEY NO. 167, T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>	
Reestablishment of a Portion of the Survey Executed by Forest Examiner, W.B. Rice, in 1918 <hr/>	
	From Cor. No. 1 of H.E.S. No. 167, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the field notes of the survey of Homestead Entry Survey No. 167.
	Set an aluminum sign post alongside iron post.
	Thence N. 28°15'00" W., on line 1-2 of H.E.S. No. 167.
5.40	Power line, bears S. 55° E. and N. 55° W.
7.80	Barbed wire fence, bears S. 60° E. and N. 60° W.
9.25	Nevada State Route No. 225, asphalt surfaced, 35 lks. wide, bears SE. and NW.
10.90	Barbed wire fence cor., fence extends S. 55° E. and N. 28° W. Thence along fence line.
13.00	Barbed wire fence cor., fence extends S. 28° E. and N. 85° W.
13.90	Van Duzer Creek, 40 lks. wide, course irregularly NE.
15.05	Edge of cultivated field, bears NE. and SW.

DEPENDENT RESURVEY OF A PORTION OF
HOMESTEAD ENTRY SURVEY NO. 167,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
16.698	<p>Point for Cor. No. 2 of H.E.S. No. 167, determined by Grant Boundary proportion; the monument set in the 1918 survey of H.E.S. No. 167, an iron post, 2 ins. diam., firmly set in a rotated position, projecting 12 ins. above the ground, bears N. 72°14'20" W., 1.706 chs. dist., with brass cap mkd. as described in the field notes of the survey of H.E.S. No. 167. Record information for Nevada State Route No. 225 right-of-way plans entitled, "Plans for R/W Acquisition Forest Highway 18, Nevada Forest Highway System Humboldt National Forest Elko County Nevada, dated October 14, 1976, with Highway Easement Deed, filed in Elko County Recorder's Office, File No. 103755, Book 244, Pages 195-210, together with the relationship to controlling corners of this survey, including a direct record tie to H.E.S. No. 71, indicates that this monument was moved from its 1918 position and therefore is not utilized in this dependent resurvey. Add the marks 2019 AM, and remove the marks made in the 1918 survey.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;"> T45N \ HES R54E \ 2 167 S30 \ </p>
	2018
	<p>From this cor., Cor. No. 12 of H.E.S. No. 71, monumented with a lava stone, 21x9x7 ins., loosely set, plainly mkd. 12 HES 71 on SW. face, bears S. 60°34' W., 8.937 chs. dist. (Record, S. 60°25' W., 8.91 chs.), from which the remaining original bearing object</p> <p style="padding-left: 40px;">A basalt boulder, 4x4x2 ft. above ground, mkd. X HES BR, bears N. 21°00' E., 5.6 lks. dist. (Record N. 42°49' E., 5 lks. dist.).</p>
	Thence N. 18°17'00" W., on line 2-3 of H.E.S. No. 167.
0.80	Irrigation ditch, drains N.
8.00	Barbed wire fence, bears N. 5° E. and S. 5° W.
10.85	Nevada State Route No. 225, asphalt surfaced, 35 lks. wide, bears N. 5° E. and S. 5° W.
13.45	Barbed wire fence, bears N. 5° E. and S. 5° W.
14.181	Intersect the line bet. secs. 19 and 30, at a point from which the 1/4 sec. cor. of secs. 19 and 30, hereinbefore described, bears N. 89°53'10" E., 17.129 chs. dist.
25.70	Dirt road, 12 lks. wide, bears NE. and SW.
34.60	Gravel road, County Road No. 729, 30 lks. wide, bears N. and S.

DEPENDENT RESURVEY OF A PORTION OF
HOMESTEAD ENTRY SURVEY NO. 167,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
37.90	Barbed wire fence, bears S. 35° E. and N. 35° W.
41.15	Power line, bears N. 65° E. and S. 65° W.
42.10	Edge of gravel parking area, bears SE. and NW.
44.10	Edge of gravel parking area, bears SSE. and NNW.
47.943	Point for Cor. No. 3 of H.E.S. No. 167, determined by Grant Boundary proportion; there is no remaining evidence of the original corner. Point falls on an asphalt entry to Nevada State Highway No. 225. Drive a magnetic nail, 6 ins. long, mkd. MAG, flush with the asphalt from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic encased magnet and in a mound of stone, 3 ft. base to top, for a reference monument, on W. side of Nevada State Highway No. 225, bears S. 30°00' W., 45.5 lks. dist., with brass cap mkd. RM COR 3 HES 167 30.0 FT TO COR 2018 and an arrow pointing to the cor. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic encased magnet and in a mound of stone, 3 ft. base to top, for a reference monument, on W. side of Nevada State Highway No. 225, bears N. 60°00' W., 90.9 lks. dist., with brass cap mkd. RM COR 3 HES 167 60.0 FT TO COR 2018 and an arrow pointing to the cor.

	Thence N. 14°03'00" E., on line 3-4 of H.E.S. No. 167.
0.45	Nevada State Route No. 225, asphalt surfaced, 35 lks. wide, bears SSE. and NNW.
1.20	Power line, bears E. and W.
2.10	Barbed wire fence cor., fences extend NNE., SSE., and WNW. Thence along fence line.
8.107	Intersect the E-W center line of sec. 19, at a point from which the 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., hereinbefore described, bears S. 89°50'10" W., 14.224 chs. dist.
16.15	Fence cor., barbed wire fences extend N. 85° E. and S. 15° W.
16.278	Point for Cor. No. 4 of H.E.S. No. 167, determined by Grant Boundary proportion; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF
 HOMESTEAD ENTRY SURVEY NO. 167,
 T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T45N R54E S19 / 4 \ HES 167 2018</p>
	<p>Set an aluminum sign post alongside stainless steel post.</p> <hr/> <p>Thence N. 73°39'00" E., on line 4-5 of H.E.S. No. 167.</p>
3.75	Left bank of the Owyhee River, bears NE. and SW., thence across river, course NE.
3.949	Intersect the N-S center line of the NW1/4 of sec. 19, at a point from which the point for the C-W 1/16 sec. cor. of sec. 19, hereinbefore described, bears S. 0°01'20" W., 9.021 chs. dist.
4.40	Right bank of the Owyhee River, bears NE. and SW.
9.565	Cor. No. 5 of H.E.S. No. 167, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. as described in the field notes of the survey of Homestead Entry Survey No. 167, with the faint outline of the remaining NE. pit, and with a mound of stone, 3 ft. diam., 1/2 ft. high, SW. of cor., with an iron steel fencepost alongside iron post.
	<p>Set an aluminum sign post alongside iron post.</p> <hr/> <p>Thence S. 17°22'10" E., on line 5-6 of H.E.S. No. 167.</p>
1.75	Barbed wire fence, N. 50° E., 0.65 chs. dist. of fence cor., with fences extending N. 50° E., S. 20° E., and S. 85° W.
9.75	Barbed wire fence, bears S. 20° E. and N. 20° W.
11.082	Intersect the E-W center line of sec. 19, at a point from which the center 1/4 sec. cor. of sec. 19, hereinbefore described, bears N. 89°50'10" E., 11.292 chs. dist.
21.634	Cor. No. 6 of H.E.S. No. 167, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, with brass cap mkd. as described in the field notes of the survey of Homestead Entry Survey No. 167, and with a mound of stone, 4 ft. diam., 1 1/2 ft. high, W. of cor.
	<p>Build a mound of stone, 3 ft. base, 18 ins. high, around iron post.</p> <p>Set an aluminum sign post alongside iron post.</p> <hr/> <p>Thence S. 1°42'20" E., on line 6-7 of H.E.S. No. 167.</p>

DEPENDENT RESURVEY OF A PORTION OF
HOMESTEAD ENTRY SURVEY NO. 167,
T. 45 N., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
3.80	Right bank of the Owyhee River, bears SE. and NW., thence across river, course NW.
4.60	Left bank of the Owyhee River, bears SE. and NW. Across cultivated field.
7.60	Left bank of the Owyhee River, bears NNE. and SSW., thence across river, course NNE.
11.80	Right bank of the Owyhee River, bears NNE. and SSW.
29.888	Intersect the line bet. secs. 19 and 30, at a point from which the 1/4 sec. cor. of secs. 19 and 30, hereinbefore described, bears N. 89°53'10" E., 7.241 chs. dist.
41.863	Cor. No. 7 of H.E.S. No. 167, monumented with an iron post, 2 ins. diam., firmly set, projecting 22 ins. above ground, with brass cap mkd. as described in the field notes of the survey of Homestead Entry Survey No. 167, and with a mound of stone, 3 ft. diam., 1 ft. high, W. of cor.
	Set an aluminum sign post alongside iron post.
	GENERAL DESCRIPTION
	The lands included in this survey are located in Elko County, Nevada, roughly 70 miles north of the community of Elko, Nevada. The land is generally rolling to mountainous with elevations ranging from 5600 to 6300 ft. above sea level. The vegetation consists of sagebrush, bitterbrush, and grasses on upland slopes, and willows and some hay fields along the Owyhee River. Soils vary from clay loam and rocky in the higher elevations to loam in the bottom lands. Access is provided by several trail roads feeding into Nevada State Route No. 225 which runs through the area.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS


Ethan B. Baker	Survey Technician (U.S.F.S.)
Michael G. Riley	Land Surveyor (U.S.F.S.)
Eric S. Greenwood	GIS Specialist (U.S.F.S.)

CERTIFICATE OF SURVEY

I, Steven W. Bell, Land Surveyor (U.S.F.S.), HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of May, 2018, and amended special instructions bearing date of the 24th day of October, 2019, I have surveyed a portion of the south boundary and a portion of the subdivisional lines, subdivided sections 18 and 19, and dependently resurveyed a portion of Homestead Entry Survey No. 167, Township 45 North, Range 54 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

SEP 10 2020

(Date)



(Land Surveyor)


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the survey of a portion of the south boundary and a portion of the subdivisional lines, the subdivision of sections 18 and 19, and the dependent resurvey of a portion of Homestead Entry Survey No. 167, Township 45 North, Range 54 East, of the Mount Diablo Meridian, Nevada, executed by Steven W. Bell, Land Surveyor (U.S.F.S.), having been critically examined and found correct, are hereby approved.

SEP 10 2020

(Date)



(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 45 North, Range 54 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~