

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SOUTH BOUNDARY,
A PORTION OF THE SUBDIVISIONAL LINES,
AND MINERAL SURVEY NO. 37B,

AND

THE SUBDIVISION OF SECTION 32,
TOWNSHIP 45 NORTH, RANGE 56 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Justin V. Haddon, Cadastral Surveyor

Brandon G. Courtright, Cadastral Surveyor

Under Special Instructions dated, August 16, 2016

and approved, August 16, 2016

which provided for the surveys included under Group No. 964,

and Assignment Instructions dated, August 16, 2016.

Survey commenced August 25th, 2016

Survey completed October 26th, 2016

INDEX DIAGRAM

TOWNSHIP 45 NORTH, RANGE 56 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	5 6 32 4 2	33	34	35	36

SUBDIVISION OF SECTION 32 pp 10 - 21
 METES-AND-BOUNDS SURVEY pp 12 - 14

MINERAL SURVEY INDEX

M.S. No. 37B, Office No. 1632 pp 8 - 9

TOWNSHIP 45 NORTH, RANGE 56 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those providing for the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines, and Mineral Survey No. 37B, and the subdivision of section 32, Township 45 North, Range 56 East, Mount Diablo Meridian, Nevada.

Mineral Survey No. 37A and B were surveyed by U.S. Deputy Mineral Surveyor R.M. Catlin in 1884. The south and east boundaries, and the subdivisional lines were surveyed by U.S. Deputy Surveyor G.A. Bellinger in 1904 under contract No. 243. The north boundary of T. 44 N., R. 56 E. was retraced by U.S. Deputy Surveyor G.S. Nickerson in 1906 under contract No. 247. Certain original corner points in Tps. 44 and 45 N., R. 56 E. were remonumented by Cadastral Surveyor W.L. Jepson in 1967 under Group No. 393. A portion of the south boundary, a portion of the subdivisional lines, and Mineral Survey No. 37A and B were dependently resurveyed by Cadastral Surveyor D.R. Garoutte in 1977 under Group No. 550.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 964, dated August 16, 2016.

Measurements were made with Trimble R8 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 1983 (2011) (Epoch:2010.0000) geographic position, of the following corners were determined by GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) DP9275 P018 PHARMACY_OR2008 CORS ARP, DL7761 P739 MCDERMITT_OR2008 CORS ARP and DL7692 GOSH GOSH_BRGN_UT1996 CORS ARP, and carried forward by RTK observations.

The corner of sections 4, 5, 32 and 33, on the S. bdy. of the Tp., is as follows:

Latitude: 41°44'35.337" N. Longitude: 115°40'22.496" W.

The corner of sections 29, 30, 31 and 32, is as follows:

Latitude: 41°45'27.326" N. Longitude: 115°41'31.816" W.

TOWNSHIP 45 NORTH, RANGE 56 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The August 25, 2016, mean magnetic declination was determined to be 12°59'E., as obtained from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.A. Bellinger in 1904 and a Portion of the Retracement Executed by U.S. Deputy Surveyor G.S. Nickerson in 1906</p> <hr/> <p>Beginning at the cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above a mound of stone, 4 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the remonumentation of certain section corners, T. 45 N., R. 56 E., executed under Group No. 393.</p> <p>N. 89°51'50" W., bet. secs. 5 and 32.</p> <p>4.991 The E-E-E 1/256 sec. cor. of secs. 5 and 32, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2012, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 ins. diam., firmly set, projecting 4 ins. above the ground, with a USFS aluminum cap mkd. T45N R56E E-E-E 1/256 S32 S5 2012, as shown on an unrecorded Record of Survey. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>From this cor., a position determined by person(s) unknown, bears S. 89°26'40" E., 0.182 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground. This position was not utilized during the course of this survey.</p> <p>From this same cor., a position determined by Alan S. Boyack, Nevada Professional Land Surveyor No. 2455, in 1975, bears S. 84°38'10" W., 0.028 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above an embedded mound of stone, 2 ft. diam., as recorded in Elko County, Nevada, Parcel Map, File No. 92396, with a steel fence post firmly set alongside. This position was not utilized during the course of this survey.</p> <hr/> <p>N. 89°51'50" W., beginning new measurement.</p> <p>3.25 Barbed wire fence, bears N. 65° E. and S. 65° W.</p> <p>5.44 Dirt road, 12 lks. wide, bears N. 80° E. and S. 80° W.</p> <p>8.66 Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.974	Point for the E 1/16 sec. cor. of secs. 5 and 32, occupied by a plastic pipe, 3 1/2 ins. diam., loosely set in a mound of stone, 3 ft. diam., 1/2 ft. high.
	POINT NOT MONUMENTED
15.77	Spur, slopes S. 60° W.
19.80	Trail road, 15 lks. wide, bears S. 50° E. and N. 50° W.
20.19	Hog wire fence, bears N. and S.
21.52	Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.
22.51	Martin Creek, 12 lks. wide, course S. 30° E.
24.70	Trail road, 12 lks. wide, bears N. 20° E. and S. 20° W.
29.948	<p>The W-W-E 1/256 sec. cor. of secs. 5 and 32, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2011, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, projecting 5 ins. above the ground, with a USFS aluminum cap mkd. T45N R56E W-W-E 1/256 S32 S5 T44N 2011, as shown on an unrecorded Record of Survey. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>From this cor., a position determined by person(s) unknown, bears N. 72°55'30" E., 1.357 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above the ground. This position was not utilized during the course of this survey.</p> <p>From this same cor., a position determined by Alan S. Boyack, Nevada Professional Land Surveyor No. 2455, in 1975, bears S. 84°24'50" W., 0.036 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above an embedded mound of stone, 2 ft. diam., as recorded in Elko County, Nevada, Parcel Map, File No. 92396. This position was not utilized during the course of this survey.</p> <p>From this same corner, a cor. of fences bears N. 81°06'10" W., 4.246 chs. dist., with barbed wire fences extending N. 5° E. and E.</p> <hr/> <p>N. 89°51'50" W., beginning new measurement.</p>
4.991	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the remonumentation of certain section corners, T. 45 N., R. 56 E., executed under Group No. 393, with a mound of stone, 2 ft. diam., 1 ft. high, N. of cor.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor G.A. Bellinger in 1904, and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor D.R. Garoutte in 1977</p> <hr/>
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 0°03'00" E., bet. secs. 32 and 33.</p>
1.10	Barbed wire fence, bears E. and W.
3.38	Trail road, 12 lks. wide, bears N. 60° E. and S. 60° W.
9.39	Spur, slopes S. 60° W.
19.906	Point for the S 1/16 sec. cor. of secs. 32 and 33.
	POINT NOT MONUMENTED
39.812	<p>The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, flush in a mound of stone, 3 ft. diam., 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the remonumentation of certain section corners, T. 45 N., R. 56 E., executed under Group No. 393.</p> <hr/>
	<p>N. 0°28'00" E., beginning new measurement.</p>
17.540	Intersect line 4-1, Mineral Survey No. 37B, Mardis millsite, at a point from which Cor. No. 4, hereinafter described, bears S. 54°13'10" W., 0.889 chs. dist.
18.22	Trail road, 15 lks. wide, bears N. 40° E. and S. 40° W.
19.958	<p>The N 1/16 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 45 N., R. 56 E., executed under Group No. 550.</p> <hr/>
	<p>N. 0°28'00" E., beginning new measurement.</p>
2.96	Barbed wire fence, bears S. 70° E. and N. 70° W.
4.702	Intersect line 1-2, Mineral Survey No. 37B, Mardis millsite, at a point, hereinafter described, from which Cor. No. 2, hereinafter described, bears N. 47°38'30" W., 2.022 chs. dist.
4.91	Martin Creek, 1 ch. wide, course S. 40° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.979	<p>The N-N 1/64 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 45 N., R. 56 E., executed under Group No. 550.</p> <hr/> <p>N. 0°28'00" E., beginning new measurement.</p>
3.80	<p>Trail road, 12 lks. wide, bears S. 55° E. and N. 55° W.</p>
9.979	<p>The cor. of secs. 28, 29, 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above a mound of stone, 2 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the remonumentation of certain section corners, T. 45 N., R. 56 E., executed under Group No. 393.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 31 and 32, perpetuated by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2011, for the U.S. Forest Service, monumented with an aluminum post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. diam., 1 ft. high, with a USFS aluminum cap mkd. T45N R56E 1/4 S31 S32 2011, as recorded in Elko County, Nevada, Record of Survey No. 3008, Document No. 655557. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>From this cor., a position determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, bears N. 76°17'30" W., 0.027 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set in the same mound of stone, with damaged plastic cap, no legible marks, as shown on an unrecorded Record of Survey. This position was determined at the center of the mound of stone, not the marked stoned recovered by Bell, and is not utilized during the course of this survey.</p> <p>N. 0°18'00" E., bet. secs. 31 and 32.</p>
6.03	<p>Dry canal, 12 lks. wide, 4 ft. deep, bears N. 15° E. and S. 15° W.</p>
19.895	<p>Point for the N 1/16 sec. cor. of secs 31 and 32.</p> <p>POINT NOT MONUMENTED</p>
28.53	<p>Spur, slopes N. 70° E.</p>
38.88	<p>Dry canal, 12 lks. wide, 4 ft. deep, bears N. 60° E. and S. 60° W.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS							
39.790	<p>The cor. of secs. 29, 30, 31 and 32, perpetuated by Thomas C. Ballew, Nevada Professional Land Surveyor No. 5072, monumented with a rebar, 1/2 in. diam., 18 ins. long, firmly set beneath a mound of stone, 2 ft. diam., 1/2 ft. high, with plastic cap mkd. PLS 5072, as shown on an unrecorded Record of Survey. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T45N R56E</td> </tr> <tr> <td style="border-right: 1px solid black; border-bottom: 1px solid black; padding: 2px 5px;">S30</td> <td style="border-bottom: 1px solid black; padding: 2px 5px;">S29</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S31</td> <td style="padding: 2px 5px;">S32</td> </tr> </table> <p>2016</p> </div> <p>Insert rebar inside stainless steel post.</p> <p>From this cor., a position perpetuated by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2011, for the U.S. Forest Service, bears N. 22°44'00" W., 0.013 chs. dist., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the same mound of stone, with USFS aluminum cap mkd. T45N R56E S30 S29 S31 S32 2011, as recorded in Elko County, Nevada, Record of Survey 3008, Document No. 655557. This position by Bell perpetuated the disturbed position of the mkd. stone, not the original undisturbed location of the mkd. stone recovered and monumented by Thomas C. Ballew, and is not utilized during the course of this survey, mark AM on cap and leave in place.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°52'00" W., bet. secs. 29 and 32.</p>	T45N R56E		S30	S29	S31	S32
T45N R56E							
S30	S29						
S31	S32						
7.59	Trail road, 12 lks. wide, bears S. 30° E. and N. 30° W.						
9.32	Creek, 8 lks. wide, courses S. 10° E.						
10.013	<p>The E-E 1/64 sec. cor. of secs. 29 and 32, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2011, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, projecting 2 ins. above the ground, with a USFS aluminum cap mkd. T45N R56E E-E 1/64 S29 S32 2011, as recorded in Elko County, Nevada, Record of Survey No. 3008, Document No. 655557. This is accepted as a careful and faithful determination of the position of the corner.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>S. 89°52'00" W., beginning new measurement.</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.013	Point for the E 1/16 sec. cor. of secs. 29 and 32.
	POINT NOT MONUMENTED
14.67	Barbed wire fence, bears S. 40° E. and N. 40° W.
22.24	Dry creek bed, 8 lks. wide, course S. 10° E.
25.02	Barbed wire fence, bears S. 25° E. and N. 25° W.
25.50	Dirt road, 15 lks. wide, bears S. 25° E. and N. 25° W.
26.04	Barbed wire fence, bears S. 25° E. and N. 25° W.
30.039	<p>The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above a mound of stone, 3 ft. diam., 1/2 ft. high, with brass cap mkd. as described in the field notes of the remonumentation of certain section corners, T. 45 N., R. 56 E., executed under Group No. 393, with a steel fence post loosely set alongside, and an aluminum sign post set alongside.</p> <hr/> <p>N. 89°49'10" W., beginning new measurement.</p>
19.968	<p>The W 1/16 sec. cor. of secs. 29 and 32, determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set, flush with the ground, with plastic cap mkd. PLS 6203, with a steel fence post firmly set alongside, as shown on an unrecorded Record of Survey. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>S29</p> <p>W 1/16 —</p> <p>S32</p> <p>2016</p> </div> <p>Insert rebar inside stainless steel post.</p> <hr/> <p>N. 89°49'10" W., beginning new measurement.</p>
10.02	Dry canal, 12 lks. wide, 4 ft. deep, bears S. 20° E. and N. 20° W.
18.25	Dry canal, 12 lks. wide, 4 ft. deep, bears N 60° E. and S. 60° W.
19.968	The cor. of secs. 29, 30, 31 and 32.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 37B,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by U.S. Deputy Mineral Surveyor R.M Catlin in 1884 and the Dependent Resurvey Executed by Cadastral Surveyor D.R. Garoutte in 1977</p> <hr/> <p>Mardis millsite</p> <p>From Cor. No. 1, Mineral Survey No. 37B, Mardis millsite, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap marked as described in the field notes of the dependent resurvey of Mineral Survey No. 37B, Mardis Millsite, T. 45 N., R. 56 E., executed under Group No. 550, with an iron post, 2 ins. diam., firmly set alongside, flush with the ground, with no visible marks on plate, with a steel fence post and an aluminum sign post firmly set alongside.</p> <p>Thence N. 47°38'30" W., on line 1-2, Mineral Survey No. 37B, Mardis millsite.</p>
0.85	Trail road, 15 lks. wide, bears N. 70° E. and S. 70° W.
1.70	Barbed wire fence, bears N. 40° E. and S. 40° W.
1.78	Barbed wire fence, bears S. 70° E. and N. 70° W.
5.868	<p>Intersect the line bet. secs. 32 and 33, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2011, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, projecting 18 ins. above the ground, with USFS aluminum cap mkd. T45N R56E LOT 37B S32 S33 2-1 2011, with aluminum sign post alongside, as recorded in Elko County, Nevada, Record of Survey 3008, Document No. 655557, at a point from which the N 1/16 sec. cor. of secs. 32 and 33, hereinbefore described, bears S. 0°28'00" W., 4.702 chs. dist.</p>
6.57	Martin Creek, 1 ch. wide, course S. 40° W.
7.890	<p>Cor. No. 2, Mineral Survey No. 37B, Mardis millsite, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above an embedded mound of stone, 2 1/2 ft. diam., with brass cap mkd. as described in the field notes of the dependent resurvey of Mineral Survey No. 37B, Mardis Millsite, T. 45 N., R. 56 E., executed under Group No. 550, with an iron post, 2 ins. diam., firmly set alongside, projecting 6 ins. above the ground, with no visible marks on plate, with a steel fence post and an aluminum sign post firmly set alongside.</p> <hr/> <p>Thence S. 54°20'50" W., on line 2-3, Mineral Survey No. 37B, Mardis millsite.</p>

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 37B,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
6.322	<p>Cor. No. 3, Mineral Survey No. 37B, Mardis millsite, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of Mineral Survey No. 37B, Mardis Millsite, T. 45 N., R. 56 E., executed under Group No. 550, with an iron post, 2 ins. diam., firmly set alongside, projecting 9 ins. above the ground, with no visible marks on plate, and a mound of stone, 3 ft. diam., 1/2 ft. high, E. of cor., with a steel fence post and an aluminum sign post firmly set alongside.</p>
	<hr/> <p>Thence S. 47°44'20" E., on line 3-4, Mineral Survey No. 37B, Mardis millsite.</p>
2.07	<p>Barbed wire fence, bears N. 35° E. and S. 35° W.</p>
3.539	<p>Intersect the E-W center line of the NE1/4 of sec. 32, at a point from which the N 1/16 sec. cor. of secs. 32 and 33, hereinbefore described, bears N. 89°59'20" E., 3.974 chs. dist.</p>
3.88	<p>Martin Creek, 2 chs. wide, course S. 45° W.</p>
7.64	<p>Barbed wire fence, bears N. 40° E. and S. 40° W.</p>
7.75	<p>Trail road, 15 lks. wide, N. 40° E. and S. 40°W.</p>
7.907	<p>Cor. No. 4, Mineral Survey No. 37B, Mardis Millsite, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of Mineral Survey No. 37B, Mardis Millsite, T. 45 N., R. 56 E., executed under Group No. 550, with an iron post, 2 ins. diam., firmly set flush with the ground, with no visible marks on plate, with a steel fence post and an aluminum sign post firmly set alongside.</p>
	<hr/> <p>Thence N. 54°13'10" E., on line 4-1, Mineral Survey No. 37B, Mardis Millsite.</p>
0.889	<p>Intersect the line bet. secs. 32 and 33, at a point from which the N 1/16 sec. cor. of secs. 32 and 33, hereinbefore described, bears N. 0°28'00" E., 2.418 chs. dist.</p>
5.025	<p>A position determined as a point at the intersection with the E-W center line of the NW 1/4 of sec. 3 by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2011, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, projecting 6 ins. above the ground, with USFS aluminum cap mkd. T45N R56E LOT 37B 4-1 S33 N-N 2011, with aluminum sign post alongside, as recorded in Elko County, Nevada, Record of Survey No. 3008, Document No. 655557.</p>
6.305	<p>Cor. No. 1, Mineral Survey No. 37B, Mardis millsite and point of beginning.</p> <hr/>

SUBDIVISION OF SECTION 32,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.
	N. 0°09'50" E., on the N-S center line of sec. 32.
19.898	Point for the C-S 1/16 sec. cor. of sec. 32.
	POINT NOT MONUMENTED
31.57	Barbed wire fence, bears S. 65° E. and N. 65° W.
39.796	Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T45N R56E C 1/4 S32
	2016
44.62	Barbed wire fence, bears N. 65° E. and S. 65° W.
59.668	Point for the C-N 1/16 sec. cor. of sec. 32.
	POINT NOT MONUMENTED
72.63	Barbed wire fence, bears N. 15° E. and S. 15° W.
74.572	Point for the C-N-N-N 1/256 sec. cor. of sec. 32, occupied by a rebar, 5/8 in. diam., 18 ins. long, bent over and flush with the ground, as determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, and shown on an unrecorded Record of Survey.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	S32 C-N-N-N 1/256
	2016
	Bury rebar alongside stainless steel post.
79.540	The 1/4 sec. cor. of secs. 29 and 32.
	From the 1/4 sec. cor. of secs. 32 and 33.
	N. 89°53'20" W., on the E-W center line of sec. 32.
12.05	Martin Creek, 9 lks. wide, course S. 45° W.

SUBDIVISION OF SECTION 32,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
13.00	Trail road, 15 lks. wide, bears N. 20° E. and S. 20° W.
13.37	Barbed wire fence, bears N. 20° E. and S. 20° W.
19.923	Point for the C-E 1/16 sec. cor. of sec. 32.
	POINT NOT MONUMENTED
25.62	Barbed wire fence, bears N. and S.
26.13	Dirt road, 15 lks. wide, bears N. and S.
26.50	Barbed wire fence, bears N. and S.
39.846	The center 1/4 sec. cor. of sec. 32.
48.81	Barbed wire fence, bears N. 15° E. and S. 15° W.
49.855	Point for the C-E-W 1/64 sec. cor. of sec. 32
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S32 C-E-W 1/64 2016
	From this point, a position determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, bears N. 58°51'04" W., 0.007 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the ground, as shown on an unrecorded Record of Survey. This position was not utilized during the course of this survey.
59.864	Point for the C-W 1/16 sec. cor. of sec. 32
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	W 1/16 C—C S32 2016
	From this point, a position determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, bears N. 67°22'38" W., 0.014 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, flush with the ground, with plastic cap mkd. PLS 6203, as shown on an unrecorded Record of Survey, with a steel fence post loosely set alongside. This position was not utilized during the course of this survey.

SUBDIVISION OF SECTION 32,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
68.78	Dry canal, 12 lks. wide, 4 ft. deep, bears N. 80° E. and S. 80° W.
79.882	The 1/4 sec. cor. of secs. 31 and 32.
	<hr/>
	From the point for the C-E 1/16 sec. cor. of sec. 32.
	N. 0°19'00" E., on the N-S center line of the NE1/4 of sec. 32.
19.915	Point for the NE 1/16 sec. cor. of sec. 32, at intersection with the E-W center line of the NE1/4.
	POINT NOT MONUMENTED
34.62	Barbed wire fence, bears S. 45° E. and N. 45° W.
39.830	The point for the E 1/16 sec. cor. of secs. 29 and 32.
	<hr/>
	From the N 1/16 sec. cor. of secs. 32 and 33.
	S. 89°59'20" W., on the E-W center line of the NE1/4 of sec. 32.
3.61	Martin Creek, 2 chs. wide, course S. 45° W.
3.974	Intersect line 3-4, Mineral Survey No. 37B, Mardis millsite, at a point from which Cor. No. 3, hereinbefore described, bears N. 47°44'20" W., 3.539 chs. dist.
4.85	Barbed wire fence, bears S. 45° E. and N. 45° W.
19.975	The point for the NE 1/16 sec. cor. of sec. 32.
28.00	Barbed wire fence, bears S. 10° E. and N. 10° W.
28.47	Dirt road, 15 lks. wide, bears S. 10° E. and N. 10° W.
29.25	Dry creek bed, 4 lks. wide, course S.
39.950	The point for the C-N 1/16 sec. cor. of sec. 32.
	<hr/>
	From the N-N 1/64 sec. cor. of secs. 32 and 33.
	S. 89°55'40" W., on the E-W center line of the NE1/4NE1/4 of sec. 32.
3.34	Creek, 8 lks. wide, course S.

SUBDIVISION OF SECTION 32,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.000	<p>The NE-NE 1/64 sec. cor. of sec. 32, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2011, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, projecting 6 ins. above the ground, with USFS aluminum cap mkd. T45N R56E NE-NE 1/64 2011, as recorded in Elko County, Nevada, Record of Survey No. 3008, Document No. 655557. This is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 0°23'30" E., on the N-S center line of the NE1/4NE1/4 of sec. 32.</p>
9.968	<p>The E-E 1/64 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the point for the E 1/16 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0°06'20" E., on the N-S center line of the SE1/4 of sec. 32.</p>
14.985	<p>From this point, a position determined by Alan S. Boyack, Nevada Professional Land Surveyor No. 2455, in 1975, bears WEST, 5.517 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 5 ins. above the ground, as recorded in Elko County, Nevada, Parcel Map, File No. 92396. This position was not utilized during the course of this survey.</p>
19.902	<p>Point for the SE 1/16 sec. cor. of sec. 32, at intersection with the E-W center line of the SE1/4.</p> <p>POINT NOT MONUMENTED</p>
24.877	<p>The C-S-N-SE 1/256 sec. cor. of sec. 32, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2011, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, projecting 3 ins. above the ground, with a USFS aluminum cap mkd. T45N R56E C-S-N-SE 1/256 S32 2011, as shown on an unrecorded Record of Survey, with aluminum sign post alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>From this cor., a position determined by Alan S. Boyack, Nevada Professional Land Surveyor No. 2455, in 1975, bears N. 33°53'20" E., 0.113 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with a steel fence post firmly set alongside, as recorded in Elko County, Nevada, Parcel Map, File No. 92396. This position was not utilized during the course of this survey.</p> <p>From this same corner, a cor. of fences bears N. 72°29'30" E., 0.281 chs. dist., with barbed wire fences extending N. and W.</p> <hr/> <p>N. 0°06'20" E., beginning new measurement.</p>
0.07	<p>Barbed wire fence, bears E. and W.</p>

SUBDIVISION OF SECTION 32,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
4.78	Dirt road, 20 lks. wide, bears N. 45° E. and S. 45° W.
4.975	The C-N-SE 1/64 sec. cor. of sec. 32, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2011, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, 6 ins. below the surface of the ground, with a USFS aluminum cap mkd. T45N R56E C-N-SE 1/64 S32 2011, as shown on an unrecorded Record of Survey. This is accepted as a careful and faithful determination of the position of the corner. _____
	N. 0°06'20" E., beginning new measurement.
9.950	The point for the C-E 1/16 sec. cor. of sec. 32. _____
	From the point for the S 1/16 sec. cor. of secs. 32 and 33. N. 89°52'30" W., on the E-W center line of the SE1/4 of sec. 32.
4.986	Point for the C-E-E-SE 1/256 sec. cor. of sec. 32. POINT NOT MONUMENTED
9.898	From this point, a position determined by Alan S. Boyack, Nevada Professional Land Surveyor No. 2455, in 1975, bears NORTH, 0.082 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, bent over, projecting 2 ins. above the ground, as recorded in Elko County, Nevada, Parcel Map, File No. 92396. This position was not utilized during the course of this survey.
14.906	From this point, a position determined by Alan S. Boyack, Nevada Professional Land Surveyor No. 2455, in 1975, bears NORTH, 0.078 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, as recorded in Elko County, Nevada, Parcel Map, File No. 92396, with a steel fence post firmly set alongside. This position was not utilized during the course of this survey.
19.944	The point for the SE 1/16 sec. cor. of sec. 32.
34.902	Point for the C-W-W-SE 1/256 sec. cor. of sec. 32. POINT NOT MONUMENTED
39.888	The point for the C-S 1/16 sec. cor. of sec. 32. _____
	From the point for the C-E-E-SE 1/256 sec. cor. of sec. 32. N. 0°03'50" E., on the N-S center line of the SE1/4NE1/4SE1/4 of sec. 32.

SUBDIVISION OF SECTION 32,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.952	<p>The C-E-NE-SE 1/256 sec. cor. of sec. 32, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2012, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, projecting 3 ins. above the ground, with a USFS aluminum cap mkd. T45N R56E C-E-NE-SE 1/256 S32 PLS 19225 2012, as shown on an unrecorded Record of Survey, with aluminum sign post alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>From this cor., a position determined by person(s) unknown, bears N. 72°23'20" E., 0.389 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 8 ins. above the ground, and in a cor. of fences, with barbed wire fences extending S. and W. This position was not utilized during the course of this survey.</p> <hr/> <p>N. 89°52'50" W., on the E-W center line of the NE1/4SE1/4 of sec. 32.</p>
4.59	Dirt road, 15 lks. wide, bears S. 10° E. and N. 10° W.
4.983	<p>The NE-SE 1/64 sec. cor. of sec. 32, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2012, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, projecting 4 ins. above the ground, with a USFS aluminum cap mkd. T45N R56E NE-SE 1/64 S32 PLS 19225 2012, as shown on an unrecorded Record of Survey, with aluminum sign post alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>From this cor., a position determined by person(s) unknown, bears N. 52°23'10" E., 0.444 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, flush with the ground. This position was not utilized during the course of this survey.</p> <hr/> <p>N. 0°04'40" E., on the N-S center line of the NE1/4SE1/4 of sec. 32.</p>
0.82	Dirt road, 15 lks. wide, bears S. 35° E. and N. 35° W.
4.976	<p>The C-N-NE-SE 1/256 sec. cor. of sec. 32, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2012, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, projecting 2 ins. above the ground, with a USFS aluminum cap mkd. T45N R56E C-N-NE-SE 1/256 S32 PLS 19225 2012, as shown on an unrecorded Record of Survey, with aluminum sign post alongside. This is accepted as a careful and faithful determination of the position of the corner.</p>

SUBDIVISION OF SECTION 32,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this cor., a position determined by person(s) unknown, bears N. 70°53'00" E., 0.401 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 7 ins. above the ground, and in a cor. of fences, with barbed wire fences extending S. and W. This position was not utilized during the course of this survey.</p> <hr/> <p>N. 89°53'00" W., on the E-W center line of the NW1/4NE1/4SE1/4 of sec. 32.</p>
4.62	Barbed wire fence, bears N. and S.
4.982	<p>The NW-NE-SE 1/256 sec. cor. of sec. 32, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2012, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, projecting 2 ins. above the ground, with a USFS aluminum cap mkd. NW-NE-SE 1/256 S32 PLS 19225 2012, as shown on an unrecorded Record of Survey, with aluminum sign post alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>From this corner, a cor. of fences bears N. 72°09'00" E., 0.394 chs. dist., with barbed wire fences extending E. and S.</p> <hr/> <p>S. 0°05'30" W., on the N-S center line of the NW1/4NE1/4SE1/4 of sec. 32.</p>
4.86	Barbed wire fence, bears E. and W.
4.976	<p>The C-W-NE-SE 1/256 sec. cor. of sec. 32, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2012, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, projecting 4 ins. above the ground, with a USFS aluminum cap mkd. C-W-NE-SE 1/256 S32 2011, as shown on an unrecorded Record of Survey, with aluminum sign post alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>From this cor., a position determined by Alan S. Boyack, Nevada Professional Land Surveyor No. 2455, in 1975, bears N. 46°19'40" E., 0.171 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above the ground, with a steel fence post firmly set alongside, as recorded in Elko County, Nevada, Parcel Map, File No. 92396. This position was not utilized during the course of this survey.</p> <p>From this same cor., a position determined by person(s) unknown, bears N. 71°16'40" E., 0.341 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 8 ins. above the ground, and in a cor. of fences, with barbed wire fences extending N. and W. This position was not utilized during the course of this survey.</p> <hr/> <p>N. 89°52'50" W., on the E-W center line of the NE1/4SE1/4 of sec. 32.</p>

SUBDIVISION OF SECTION 32,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
3.94	Barbed wire fence, bears N. 60° E. and S. 70° W.
4.78	Dirt road, 20 lks. wide, bears N. 45° E. and S. 45° W.
4.983	The C-N-SE 1/64 sec. cor. of sec. 32.
	<hr/>
	From the E-E-E 1/256 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.
	N. 0°03'50" E., on the computed N-S center line of the SE1/4SE1/4SE1/4 of sec. 32.
0.86	Cor. of fences, with barbed wire fences extending N., N. 65° E. and S. 65° W.
1.41	Trail road, 12 lks. wide, bears N. 75° E. and S. 75° W.
7.51	Barbed wire fence, bears E. and W.
8.90	Spur, slopes W.
9.952	Point for the C-E-SE-SE 1/256 sec. cor. of sec. 32, at its computed position.
	POINT NOT MONUMENTED
	<hr/>
	N. 0°03'50" E., on the computed N-S center line of the NE1/4SE1/4SE1/4 of sec. 32.
5.04	Barbed wire fence, bears E. and W.
9.952	The point for the C-E-E-SE 1/256 sec. cor. of sec. 32.
	<hr/>
	From the W-W-E 1/256 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.
	N. 0°09'00" E., on the computed N-S center line of the SW1/4SW1/4SE1/4 of sec. 32.
0.67	Barbed wire fence, bears E. and W.
9.949	Point for the C-W-SW-SE 1/256 sec. cor. of sec. 32, at its computed position.
	POINT NOT MONUMENTED
	<hr/>
	N. 0°09'00" E., on the computed N-S center line of the NW1/4SW1/4SE1/4 of sec. 32.
9.949	The point for the C-W-W-SE 1/256 sec. cor. of sec. 32.
	<hr/>
	From the C-S-N-SE 1/256 sec. cor. of sec. 32.

SUBDIVISION OF SECTION 32,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 89°52'40" W., on the computed E-W center line of the SE1/4NW1/4SE1/4 of sec. 32.</p> <p>4.82 Barbed wire fence, bears N. 50° E. and S. 50° W.</p> <p>4.967 From this point, a position determined by Alan S. Boyack, Nevada Professional Land Surveyor No. 2455, in 1975, bears NORTH, 0.090 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 5 ins. above the ground, with steel fence post firmly set alongside, as recorded in Elko County, Nevada, Parcel Map, File No. 92396. This position was not utilized during the course of this survey.</p> <p>5.381 From this point, a position determined by Alan S. Boyack, Nevada Professional Land Surveyor No. 2455, in 1975, bears SOUTH, 0.453 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, bent over, projecting 6 ins. above the ground, as recorded in Elko County, Nevada, Parcel Map, File No. 92396. This position was not utilized during the course of this survey.</p> <p>6.08 Dirt road, 20 lks. wide, bears N. and S.</p> <p>6.48 Barbed wire fence, bears N. and S.</p> <p>9.970 Point for the C-S-NW-SE 1/256 sec. cor. of sec. 32, at its computed position.</p> <p>POINT NOT MONUMENTED</p> <hr/> <p>N. 89°52'40" W., on a portion of the computed E-W centerline of the SW1/4NW1/4SE1/4 of sec. 32.</p> <p>4.985 The SW-NW-SE 1/256 sec. cor. of sec. 32, determined by Steven W. Bell, Nevada Professional Land Surveyor No. 19225, in 2011, for the U.S. Forest Service, monumented with an aluminum drive rod, 3/4 in. diam., firmly set, projecting 5 ins. above the ground, with a USFS aluminum cap mkd. SW-NW-SE 1/256 S32 2011, as shown on an unrecorded Record of Survey, with aluminum sign post alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>From this cor., a position determined Alan S. Boyack, Nevada Professional Land Surveyor No. 2455, in 1975, bears N. 2°51'20" W., 0.081 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 5 ins. above the ground, with two steel fence posts firmly set alongside, as recorded in Elko County, Nevada, Parcel Map, File No. 92396. This position was not utilized during the course of this survey.</p> <p>From this same corner, a cor. of fences bears N. 88°31'40" E., 8.371 chs. dist., with barbed wire fence extending N. 65° W.</p> <p>From this same corner, a cor. of fences bears N. 70°34'30" W., 2.901 chs. dist., with barbed wire fences extending S. 5° W. and N. 15° W.</p>
--------	---

SUBDIVISION OF SECTION 32,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From this same corner, a cor. of fences bears N. 32°29'20" W., 7.369 chs. dist., with barbed wire fences extending S. 65° E. and S. 15° E.</p> <hr/>
4.975	<p>S. 0°09'00" W., on a portion of the computed N-S center line of the SW1/4NW1/4SE1/4 of sec. 32.</p> <p>The point for the C-W-W-SE 1/256 sec. cor. of sec. 32.</p> <hr/>
19.884	<p>From the C-W 1/16 sec. cor. of sec. 32.</p> <p>N. 0°14'00" E., on the N-S center line of the NW1/4 of sec. 32.</p> <p>Point for the NW 1/16 sec. cor. of sec. 32, at intersection with the E-W center line of the NW1/4.</p> <p>POINT NOT MONUMENTED</p>
39.768	<p>The W 1/16 sec. cor. of secs. 29 and 32.</p> <hr/>
3.47	<p>From the point for the C-N 1/16 sec. cor. of sec. 32</p> <p>N. 89°51'10" W., on the E-W center line of the NW1/4 of sec. 32.</p> <p>Barbed wire fence, bears N. 15° E. and S. 15° W.</p>
4.998	<p>Point for the C-E-E-NW 1/256 sec. cor. of sec. 32.</p> <p>POINT NOT MONUMENTED</p>
19.993	<p>The point for the NW 1/16 sec. cor. of sec. 32.</p>
22.39	<p>Dry canal, 6 ft. wide, 2 ft. deep, bears N. 10° E. and S. 10° W.</p>
33.23	<p>Dry canal, 10 ft. wide, 4 ft. deep, bears N. and S.</p>
39.986	<p>The point for the N 1/16 sec. cor. of secs. 31 and 32.</p> <hr/>
9.938	<p>From the point for the C-E-E-NW 1/256 sec. cor. of sec. 32.</p> <p>N. 0°10'50" E., on the computed N-S center line of the SE1/4NE1/4NW1/4 of sec. 32.</p> <p>The C-E-NE-NW 1/256 sec. cor. of sec. 32, at its computed position.</p> <p>POINT NOT MONUMENTED</p> <hr/>
	<p>N. 0°10'50" E., on a portion of the computed N-S center line of the NE1/4NE1/4NW1/4 of sec. 32.</p>

SUBDIVISION OF SECTION 32,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
4.969	<p>Point for the NE-NE-NW 1/256 sec. cor. of sec. 32, occupied by a rebar, 5/8 in. diam., 18 ins. long, firmly set, projecting 2 ins. above the ground, with damaged plastic cap, no legible marks, determined by Robert E. Morley, Professional Land Surveyor No. 6203, and shown on an unrecorded Record of Survey, with a steel fence post firmly set alongside.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S32 NE-NE-NW 1/256 2016</p> <p>Insert rebar inside stainless steel post, leave steel fence post lying loose alongside.</p> <hr/> <p>S. 89°49'40" E., on a portion of the computed E-W center line of the NE1/4NE1/4NW1/4 of sec. 32.</p>
4.994	<p>The C-N-N-N 1/256 sec. cor. of sec. 32.</p> <hr/> <p>From the C-E-W 1/64 sec. cor. of sec. 32.</p> <p>N. 0°11'50" E., on a portion of the computed N-S center line of the SE1/4NW1/4 of sec. 32.</p>
14.908	<p>Point for the C-N-SE-NW 1/256 sec. cor. of sec. 32, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S32 C-N-SE-NW 1/256 2016</p> <p>From this point, a position determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, bears N. 56°16'50" W., 0.004 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, with plastic cap mkd. PLS 6203, as shown on an unrecorded Record of Survey, with a steel fence post lying loose alongside. This position was determined using improper control at the 1/4 sec. cor. of secs. 31 and 32 and is not utilized during the course of this survey.</p> <hr/>

SUBDIVISION OF SECTION 32,
T. 45 N., R. 56 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>5.000</p>	<p>S. 89°51'40" E., on a portion of the computed E-W center line of the NE1/4SE1/4NW1/4 of sec. 32.</p> <p>The NE-SE-NW 1/256 sec. cor. of sec. 32, at its computed position.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S32 NE-SE-NW 1/256</p> <p style="text-align: center;">2016</p> <p>Point is located 10 ft. northwesterly from a barbed wire fence, extending N. 15° E. and S. 15° W.</p> <p>From this point, a position determined by Robert E. Morley, Nevada Professional Land Surveyor No. 6203, bears N. 23°08'40" W., 0.004 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with plastic cap mkd. PLS 6203, as shown on an unrecorded Record of Survey, with a steel fence post lying loose alongside. This position was determined using improper control at the 1/4 sec. cor. of secs. 31 and 32 and is not utilized during the course of this survey.</p>
<p>4.969</p>	<p>N. 0°10'50" E., on a portion of the computed N-S center line of the NE1/4SE1/4NW1/4 of sec. 32.</p> <p>The point for the C-E-E-NW 1/256 sec. cor. of sec. 32.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in this survey are located in Elko County, Nevada, roughly 65 miles north of the community of Elko, Nevada. The area is generally rolling, at an average elevation of 7000 ft. above sea level. The vegetation consists of sagebrush and grasses, with some areas of wetlands. Access is gained by way of Gold Creek Rd., which can be accessed off Nevada State Route 225.</p>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Robert W. Femling

Cadastral Surveyor

Lucas T. Beauchamp

Student Trainee

CERTIFICATE OF SURVEY

We, Justin V. Haddon and Brandon G. Courtright, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of August, 2016, we have dependently resurveyed a portion of the south boundary, a portion of the subdivisional lines, Mineral Survey No. 37B, and subdivided section 32, Township 45 North, Range 56 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

MAR 29 2017

(Date)

Justin V. Haddon

(Cadastral Surveyor)

MAR 29 2017

(Date)

Brandon G. Courtright

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the south boundary, a portion the subdivisional lines, Mineral Survey No. 37B, and the subdivision of section 32, Township 45 North, Range 56 East, Mount Diablo Meridian, Nevada, executed by Justin V. Haddon and Brandon G. Courtright, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

MAR 29 2017

(Date)

Michael S. Hammering

(Chief Cadastral Surveyor for Nevada)

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above described surveys in Township 45 North, Range 56 East, Mount Diablo Meridian, Nevada, is a true copy of the original field notes.

(Date)

(Chief Cadastral Surveyor for Nevada)