

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE IDAHO-NEVADA STATE LINE, FROM MILE POST 104 TO MILE POST 111,

THE SOUTH BOUNDARY,

A PORTION OF THE EAST BOUNDARY,

THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION-OF-SECTION LINES OF CERTAIN SECTIONS,

AND THE FURTHER SUBDIVISION OF CERTAIN SECTIONS

AND THE METES-AND-BOUNDS SURVEY OF LOT 3 IN SECTION 26,

TOWNSHIP 47 NORTH, RANGE 52 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Daniel R. Ontiveros, Cadastral Surveyor
Clay W. Morrow, Surveying Technician

Under Special Instructions dated October 21, 2004,
and approved October 21, 2004,
which provided for the surveys included under Group No. 821,
and Assignment Instructions dated October 21, 2004.

Survey commenced June 17, 2005
Survey completed April 9, 2008

INDEX DIAGRAM

TOWNSHIP 47 NORTH, RANGE 52 EAST, MOUNT DIABLO MERIDIAN, NEVADA

MP 111	Idaho 7		MP 110	7	MP 109	5	MP 108	4	MP 107	3	MP 106	2	MP 105	2	Idaho	MP 104
Nevada	31	6 115	116	5 113	89	4 88	73	3 71	53	2 52	38	1	21	Nevada		
	29	7 109	111	8 108	86	9 85	69	10 67	50	11 49	37	12				
	27	18 104	105	17 102	83	16 82	65	15 63	47	14 46	36	13				
	25	19 99	100	20 97	81	21 79	60	22 58	44	23 43	36	24				
	24	30 94	95	29 92	77	28 76	57	27 55	41	26 40	34	25 34				
	22	31 18	90	32 17	73	33 14	53	34 11	38	35 10	32	36 8	20			

Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 2 ... pp. 117-119.
 Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 3 ... pp. 119-121.
 Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 4 ... pp. 121-123.
 Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 5 ... pp. 123-125.
 Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 6 ... pp. 126-127.
 Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 7 ... pp. 128-132.
 Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 8 ... pp. 133-137.
 Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 9 ... pp. 137-141.
 Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 10 .. pp. 141-146.

- Continued on next page -

Index Continued

Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 11 ..	pp. 146-148.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 14 ..	pp. 149-150.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 15 ..	pp. 150-155.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 16 ..	pp. 155-160.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 17 ..	pp. 160-165.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 18 ..	pp. 165-169.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 19 ..	pp. 170-172.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 20 ..	pp. 172-177.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 21 ..	pp. 177-181.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 22 ..	pp. 181-185.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 23 ..	pp. 185-189.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 26 ..	pp. 189-193.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 27 ..	pp. 193-198.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 28 ..	pp. 198-203.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 29 ..	pp. 203-206.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 30 ..	pp. 206-208.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 31 ..	pp. 208-210.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 32 ..	pp. 211-213.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 33 ..	pp. 213-217.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 34 ..	pp. 218-221.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 35 ..	pp. 221-226.
Dep. Resurvey of the Subdivision-of-Section Lines of Sec. 36 ..	pp. 226-227.
Further Subdivision of Sec. 2	p. 227.
Further Subdivision of Sec. 7	pp. 227-229.
Further Subdivision of Sec. 8	pp. 229-230.
Further Subdivision of Sec. 9	pp. 230-232.
Further Subdivision of Sec. 10	pp. 232-233.
Further Subdivision of Sec. 11	pp. 233-235.
Further Subdivision of Sec. 14	pp. 235-237.
Further Subdivision of Sec. 15	pp. 237-238.
Further Subdivision of Sec. 16	pp. 239-240.
Further Subdivision of Sec. 17	pp. 240-241.
Further Subdivision of Sec. 18	pp. 242-243.
Further Subdivision of Sec. 19	pp. 243-246.
Further Subdivision of Sec. 20	pp. 246-247.
Further Subdivision of Sec. 21	pp. 248-249.
Further Subdivision of Sec. 22	pp. 249-251.
Further Subdivision of Sec. 23	pp. 251-252.
Further Subdivision of Sec. 26	pp. 252-254.
Further Subdivision of Sec. 27	pp. 254-256.
Further Subdivision of Sec. 28	pp. 256-258.
Further Subdivision of Sec. 29	pp. 258-261.
Further Subdivision of Sec. 30	pp. 261-264.
Further Subdivision of Sec. 31	pp. 264-266.
Further Subdivision of Sec. 32	pp. 266-269.
Further Subdivision of Sec. 33	pp. 269-271.
Further Subdivision of Sec. 34	pp. 271-272.
Further Subdivision of Sec. 35	pp. 273-274.
Further Subdivision of Sec. 36	p. 274.
The Metes-and-Bounds Survey of Lot 3, in Section 26.....	pp. 275-276.

TOWNSHIP 47 NORTH, RANGE 52 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field note are those of the dependent resurvey of a portion of the Idaho-Nevada State Line, from Mile Post 104 to Mile Post 111, the south boundary, a portion of the east boundary, the west boundary, a portion of the subdivisional lines and the subdivision-of-section lines of certain sections, and the further subdivision of certain sections and the metes-and-bounds survey of Lot 3 in section 26, Township 47 North, Range 52 East, Mount Diablo Meridian, Nevada.

The state line between Idaho and Nevada was surveyed by U.S. Astronomer and Surveyor D.G. Major under Contract of September 7, 1872. A portion of the state line between Idaho and Nevada, was dependently resurveyed and the south, east and west boundaries, the subdivisional lines and a portion of the subdivision of certain sections were surveyed by U.S. Surveyor F.E. Joy in 1911 under Instructions dated April 27, 1911. Lots 1, 2 and 3, section 26, were created by supplemental plat accepted February 8, 1957. A portion of the state line between Idaho and Nevada was dependently resurveyed by Cadastral Surveyor W.D. Kimmel in 2004-2005, under Group No. 1184, Idaho.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the complete survey.

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 821, dated October 21, 2004.

Measurements were made with Trimble 5700 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in theses field notes.

The NAD 1983 (1999) geographic position of the corner of Townships 46 and 47 North, Ranges 52 and 53 East, as determined by a tie made to Federal Base Network Control Station H 318, located in sec. 19, is as follows:

Latitude: 41°55'21.471" N.

Longitude: 116°04'23.659" W.

The 1971 mean magnetic declination is 17 1/2° E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "OWYHEE, NEV.-IDAHO", dated 1971.

DEPENDENT RESURVEY OF A PORTION OF THE
IDAHO-NEVADA STATE LINE, FROM MILE POST 104 TO MILE POST 111

CHAINS	<p style="text-align: center;">Retracement of a Portion of the Survey Executed by U.S. Astronomer and Surveyor D.G. Major in 1873, a Portion of the Dependent Resurvey Executed by U.S. Surveyor F.E. Joy in 1911 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor W.D. Kimmel in 2004-05</p> <hr/> <p>Beginning at the 104 Mile Post, monumented with a basalt stone, 28x20x5 ins., firmly set in a mound of stone, 6 ft. base, 3 ft. high, mkd. I 42 L on the N. face and N 104 on the S. face.</p> <p>N. 89°28'40" W., on the 105th mile.</p> <p>35.408 Point for the closing cor. of Tps. 47 N., Rs. 52 and 53 E., hereinafter described.</p> <p>65.868 From this point, the closing cor. of secs. 26 and 27, T. 16 S., R. 3 E., Boise Meridian, Idaho, bears SOUTH, 0.131 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. T16S R3E S26 S27 CC 1912. Cor. is located below the top of bluff, at base of small cliff, 30 ft. high, on west slope of steep rocky mountain.</p> <p>80.738 True point for the 105 Mile Post, at proportionate distance; falls in unstable rock slide area, where it is impractical to establish a permanent monument.</p> <hr/> <p>N. 89°28'40" W., on the 106th mile.</p> <p>20.184 The witness cor. to the 105 Mile Post, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Group No. 1184, Idaho.</p> <hr/> <p>N. 89°55'00" W., beginning new measurement.</p> <p>14.267 Point for the closing cor. of secs. 1 and 2, hereinafter described.</p> <p>34.406 Point for the E 1/16 sec. cor., on the N. bdy. of sec. 2, hereinafter described.</p> <p>44.928 The closing cor. of secs. 27 and 28, on the S. bdy. of T. 16 S., R. 3 E., Boise Meridian, Idaho, monumented with a rebar, 3/4 in. diam., firmly set in drill hole in boulder, projecting 10 ins. above the ground and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 16 S., R. 3 E., executed under Group No. 1184, Idaho.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE
IDAHO-NEVADA STATE LINE, FROM MILE POST 104 TO MILE POST 111

CHAINS	
54.545	Point for the closing 1/4 sec. cor. on the N. and S. center line of sec. 2, hereinafter described.
58.311	The 106 Mile Post, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground and in a mound of stone, 3 ft. base, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Group No. 1184, Idaho.
	<hr/>
	N. 89°50'50" W., on the 107th mile.
6.10	Fence, bears N. and S.; enter meadow.
6.631	The E 1/16 sec. cor. of sec. 28, on the S. bdy. of T. 16 S., R. 3 E., Boise Meridian, Idaho, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Group No. 1184, Idaho.
13.110	From this point, a steel fence post of unknown origin, firmly set, projecting 2 ft. above the ground, bears SOUTH, 0.014 chs. dist.
16.291	Point for the closing cor. on the N. and S. center line of the W1/2 of sec. 2, hereinafter described.
16.340	From this point, a mound of stone, 5 ft. diam., 1 ft. high, bears SOUTH, 0.06 chs. dist. This mound of stone was not utilized during the course of this survey.
26.645	The closing cor. of the N. and S. center line of sec. 28, on the S. bdy. of T. 16 S., R. 3 E., Boise Meridian, Idaho, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Group No. 1184, Idaho.
36.418	Point for the closing cor. of secs. 2 and 3, hereinafter described.
46.659	The closing cor. of the N. and S. center line of the SW1/4 of sec. 28, on the S. bdy. of T. 16 S., R. 3 E., Boise Meridian, Idaho, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Group No. 1184, Idaho.
	Cor. is located in fence, bears N. and S.

DEPENDENT RESURVEY OF A PORTION OF THE
IDAHO-NEVADA STATE LINE, FROM MILE POST 104 TO MILE POST 111

CHAINS	
56.374	Point for the closing cor. on the N. and S. center line of the E1/2 of sec. 3, hereinafter described.
66.673	The closing cor. of sec. 28 and 29, on the S. bdy. of T. 16 S., R. 3 E., Boise Meridian, Idaho, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 16 S., R. 3 E., Boise Meridian, Idaho, executed under Group No. 1184, Idaho.
76.280	Point for the closing cor. on the N. and S. center line of sec. 3, hereinafter described.
80.985	The 107 Mile Post, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Group No. 1184, Idaho, with steel fence post alongside.
	<hr/> N. 89°52'50" W., on the 108th mile.
0.296	From this point, a position established by Donald J. Watts, Idaho Professional Land Surveyor No. 1923, bears SOUTH, 0.028 chs. dist., monumented with a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above the ground, with a plastic cap mkd. PELS 1923.
5.638	The E 1/16 sec. cor. of sec. 29, on the S. bdy. of T. 16 S., R. 3 E., Boise Idaho Meridian, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Group No. 1184, Idaho.
15.268	Point for the closing cor. on the N. and S. center line of the W1/2 of sec. 3, hereinafter described.
25.588	The closing cor. of the N. and S. center line of sec. 29, on the S. bdy. of T. 16 S., R. 3 E., Boise Meridian, Idaho, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the subdivision of section 29, executed under Group No. 1184, Idaho.
35.253	Point for the closing cor. of secs. 3 and 4, hereinafter described.

DEPENDENT RESURVEY OF A PORTION OF THE
IDAHO-NEVADA STATE LINE, FROM MILE POST 104 TO MILE POST 111

CHAINS	
42.20	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.
45.593	<p>The W 1/16 sec. cor. of sec. 29, on the S. bdy. of T. 16 S., R. 3 E., Boise Meridian, Idaho, determined at the intersection of record distances to the 2004 reference monuments, as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Group No. 1184, Idaho, point falls in a landscaped lawn, from which the 2004-05 accessories</p> <p>A rebar, 3/4 in. diam., firmly set, projecting 4 ins. above the ground, bears N. 25°02' E., 173.4 lks. dist., with aluminum cap mkd. RM T16S R3E W 1/16 S29 114.4 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A rebar, 3/4 in. diam., firmly set, projecting 4 ins. above the ground, bears N. 69°17' E., 151.6 lks. dist., with aluminum cap mkd. RM T16S R3E W 1/16 S29 100.0 FT TO COR 2004 and an arrow pointing to the corner.</p>
55.262	Point for the closing cor. on the N. and S. center line of the E1/2 of sec. 4, hereinafter described.
65.598	The closing cor. of secs. 29 and 30, on the S. bdy. of T. 16 S., R. 3 E., Boise Meridian, Idaho, monumented with an aluminum post, 2 1/2 ins. diam., set flush with the surface of the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 16 S., R. 3 E., executed under Group No. 1184, Idaho.
75.216	The closing cor. on the N. and S. center line of sec. 4, hereinafter described.
80.918	The 108 Mile Post, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Group No. 1184, Idaho.
4.642	<p>N. 89°53'10" W., on the 109th mile.</p> <p>The closing cor. of the N. and S. center line of the SE1/4 of sec. 30, on the S. bdy. of T. 16 S., R. 3 E., Boise Meridian, Idaho, monumented with a rebar, 3/4 in. diam., set flush with the surface of the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the subdivision of section 30, executed under Group No. 1184, Idaho, from which the 2004-2005 accessory</p>

DEPENDENT RESURVEY OF A PORTION OF THE
IDAHO-NEVADA STATE LINE, FROM MILE POST 104 TO MILE POST 111

CHAINS	<p>An aluminum post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, bears N. 44°29' E., 10.4 lks. dist., with aluminum cap mkd. RM T16S R3E CC S30 EE (with lines in the shape of an inverted "T" connecting the letters E) 6.8 FT TO COR. 2004 with an arrow pointing to the cor.</p>
14.322	The closing cor. on the N. and S. center line of the W1/2 of sec. 4, hereinafter described.
17.00	Owyhee River, 2 chs. wide, course NNW.
24.662	<p>The closing cor. of the N. and S. center line of sec. 30, on the S. bdy. of T. 16 S., R. 3 E., Boise Meridian, Idaho, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivision of section 30, executed under Group No. 1184, Idaho.</p> <p>Cor. is located in fence, bears N. and S., 19 lks. N. of the cor. of fences extending N. and W.</p>
34.307	Point for the closing cor. of secs. 4 and 5, hereinafter described.
44.609	<p>The closing cor. of the N. and S. center line of the SW1/4 of sec. 30, on the S. bdy. of T. 16 S., R. 3 E., Boise Meridian, Idaho, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivision of section 30, executed under Group No. 1184, Idaho.</p> <p>Cor. is located 3.5 lks. S. of the cor. fences extending N., S., E. and W.</p>
54.253	Point for the closing cor. on the N. and S. center line of the E1/2 of sec. 5, hereinafter described.
54.30	Fence, bears N. and S., 4.7 lks. S. of the cor. of fences extending N., E. and W.
67.359	<p>The closing cor. of Tps. 16 S., Rs. 2 and 3 E., Boise Meridian, Idaho, monumented with an iron post, 3 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary, T. 16 S., R. 3 E., executed under Group No. 1184, Idaho. Add the marks 2004 to the brass cap.</p> <p>Cor. is located 10 lks. S. of a fence, bears E. and W.</p>
74.269	Point for the closing cor. on the N. and S. center line of sec. 5, hereinafter described.

DEPENDENT RESURVEY OF A PORTION OF THE
IDAHO-NEVADA STATE LINE, FROM MILE POST 104 TO MILE POST 111

CHAINS	
80.857	<p>The 109 Mile Post, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Group No. 1184, Idaho.</p> <hr/> <p>S. 89°41'10" W., on the 110th mile.</p>
6.478	<p>From this point, the disturbed monument for the 1912 closing E 1/16 cor. of sec. 25, on the S. bdy. of T. 16 S., R. 2 E., Boise Meridian, Idaho, bears NORTH, 0.032 chs. dist., being the remains of the 1912 iron post, 20 ins. long, 1 in. diam., with cap missing, found wired to a wooden fence corner post of fences extending N. and W., the 1912 position undeterminable.</p>
13.400	<p>Point for the closing cor. on the N. and S. center line of the W1/2 of sec. 5, hereinafter described.</p>
33.388	<p>Point for the closing cor. of sec. 5 and 6, hereinafter described.</p>
53.378	<p>Point for the closing cor. on the N. and S. center line of the E1/2 of sec. 6, hereinafter described.</p>
73.357	<p>Point for the closing 1/4 sec. cor. on the N. and S. center line of sec. 6, hereinafter described.</p>
80.954	<p>The 110 Mile Post, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Instructions dated April 27, 1911.</p> <hr/> <p>S. 89°50'30" W., on the 111th mile.</p>
5.546	<p>From this point, the closing E 1/16 sec. cor. of sec. 26, on the S. bdy. of T. 16 S., R. 2 E., Boise Idaho Meridian, bears SOUTH, 0.032 chs. dist., monumented with an iron post, 1 in. diam., projecting 18 ins. above the ground, bent and overgrown on SE. side by base of a cottonwood, 36 ins. diam., with cap mkd. 1/16 S26 191. Accepted base of iron post as the best available evidence of the position of the 1911-12 monument.</p>
12.475	<p>Point for the closing cor. on the N. and S. center line of the W1/2 of sec. 6, hereinafter described.</p>
31.406	<p>The closing cor. of Tps. 47 N., Rs. 51 and 52 E., hereinafter described.</p>

DEPENDENT RESURVEY OF A PORTION OF THE
IDAHO-NEVADA STATE LINE, FROM MILE POST 104 TO MILE POST 111

CHAINS	
65.558	<p>From this point, the closing cor. of secs. 26 and 27, T. 16 S., R. 2 E., Boise Meridian, bears SOUTH, 0.006 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 2 ft. above the ground, at the cor. of fences extending E, W. and N., with brass cap mkd. CC T16S R2E IDA S26 S27 1912, with a mound of stone, 5 ft. diam., 3 ft. high, E. of corner.</p>
71.372	<p>From this point, the 1/4 sec. cor. for sec. 1 only, on the N. bdy. of sec. 1, T. 47 N., R. 51 E., Mount Diablo Meridian, bears SOUTH, 0.073 chs. dist., monumented with a bent iron post, 1 in. diam., projecting 15 ins. above the ground, leaning southerly, with brass cap mkd. 1/4 CC S1 10 NEV 191. Cor. is located 10 lks. E. of the cor. of fences extending E., W. and S.</p>
80.702	<p>The 111 Mile Post, monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Instructions dated April 27, 1911.</p>
	<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/>
	<p>From the cor. of Tps. 46 and 47 N., Rs. 52 and 53 E., monumented with an iron post, 3 ins. diam., set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 46 N., R. 52 E., executed under Instructions dated April 27, 1911.</p>
	<p>S. 89°56'30" W., bet. secs. 1 and 36.</p>
26.00	<p>Owyhee River, 2 chs. wide, course NW.</p>
39.650	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented with a rusted iron post, 1 in. diam., 36 ins. long, bent at base, loosely set in a mound of stone, with brass cap mkd. as described in the field notes of the survey of the north boundary of T. 46 N., R. 52 E., executed under Instructions dated April 27, 1911.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T47N R52E S36 1/4 <u> </u> S 1 T46N</p> <p style="text-align: center;">2004</p> <p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 89°47'20" W., beginning new measurement.</p>
20.075	<p>Point for the W 1/16 sec. cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E S36 W 1/16 <u> </u> S 1 T46N</p> <p style="text-align: center;">2005</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
40.150	<p>The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 31 ins. in the ground, bent at base, with brass cap mkd. as described in the field notes of the survey of the north boundary of T. 46 N., R. 52 E., under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E S35 S36 <u> </u> <u> </u> S 2 S 1 T46N</p> <p style="text-align: center;">2005</p> <p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr/>

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°51'50" W., bet. secs. 2 and 35.
19.98	Cor. of fences extending N., E. and W.
20.010	<p>Point for the 1/16 sec. cor. No. 1, bet. secs. 2 and 35 (E1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the E 1/16 sec. cor. of secs. 2 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T47N R52E S35 E 1/16 <u> </u> S 2 T46N 2006 </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
40.020	<p>Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T47N R52E S35 1/4 <u> </u> S 2 T46N 2006 </div>
60.030	<p>The 1/16 sec. cor. No. 2, bet. secs. 2 and 35 (W1/2), monumented with remains of the 1911 iron post, 20 ins. long, 1 in. diam., 4 ins. below the surface of the ground, with brass cap missing. This point will now be referred to as the W 1/16 sec. cor. of secs. 2 and 35.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T47N R52E S35 W 1/16 $\frac{\quad}{\quad}$ S 2 T46N</p> <p style="text-align: center;">2005</p> <p>Bury the remains of iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on N. side of bladed road, bears W. and S.</p> <hr/> <p>N. 89°41'30" W., beginning new measurement.</p>
20.012	<p>The cor. of secs. 2, 3, 34 and 35, monumented with a rebar of unknown origin, 18 ins. long, 5/8 in. diam., firmly set flush with the asphalt surface. This rebar is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 4 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">T47N R52E S34 S35 $\frac{\quad}{\quad}$ $\frac{\quad}{\quad}$ S 3 S 2 T46N</p> <p style="text-align: center;">2006</p> <p>Bury the rebar alongside the copper coated steel stake.</p> <p>Cor. is located at the intersection of roads extending N., S., E. and W.</p> <hr/> <p>N. 89°57'20" W., bet. secs. 3 and 34.</p> <p>Along asphalt-surfaced road.</p>
20.017	<p>Point for the 1/16 sec. cor. No. 1, bet. secs. 3 and 34 (E1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the E 1/16 sec. cor. of secs. 3 and 34.</p>

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">T47N R52E S34 E 1/16 $\frac{\quad}{\quad}$ S 3 T46N</p> <p style="text-align: center;">2006</p>
40.034	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with a rebar of unknown origin, 18 ins. long, 5/8 in. diam., firmly set 2 ins. below the asphalt surface; there is no remaining evidence of the original corner. This rebar is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">T47N R52E S34 1/4 $\frac{\quad}{\quad}$ S 3 T46N</p> <p style="text-align: center;">2006</p> <p>Bury the rebar alongside the copper coated steel stake.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°57'20" W., beginning new measurement.</p> <p>Along improved gravel road.</p>
20.017	<p>The 1/16 sec. cor. No. 2, bet. secs. 3 and 34 (W1/2), monumented with an iron post, 36 ins. long, 1 in. diam., set 8 ins. below the surface of a gravel road, with brass cap mkd. as described in the field notes of the survey of the north boundary, T. 46 N., R. 52 E., executed under Instructions dated April 27, 1911. This point will now be referred to as the W 1/16 sec. cor. of secs. 3 and 34.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T47N R52E S34 W 1/16 $\frac{\quad}{\quad}$ S 3 T46N</p> <p style="text-align: center;">2004</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a fence bearing E. and W., for a reference monument, bears N. 58°03' E., 48.2 lks. dist, with brass cap mkd. RM W 1/16 S34 31.8 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a fence bearing E. and W., for a reference monument, bears S. 39°34' E., 36.2 lks. dist, with brass cap mkd. RM W 1/16 S3 23.9 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>Bury the iron post alongside the stainless steel post.</p> <hr/> <p>N. 89°56'00" W., beginning new measurement.</p> <p>20.035 The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 36 ins. long, 1 in. diam, set 22 ins. below the surface of an improved gravel road, with brass cap mkd. as described in the field notes of the survey of the north boundary, T. 46 N., R. 52 E., executed under Instructions dated April 27, 1911, and a rebar, 18 ins. long, 5/8 in. diam., set atop the iron post by John T. Eddy, Nevada Professional Land Surveyor No. 5016, 4 ins. below the surface of the improved gravel road, with plastic cap mkd. JUB PLS 5016.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the improved gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E S33 S34 $\frac{\quad}{\quad}$ S 4 S 3 T46N</p> <p style="text-align: center;">2004</p>
--------	---

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a fence bearing E. and W., for a reference monument, bears S. 31°39' W., 34.1 lks. dist., with brass cap mkd. RM T46N R52E S4 22.5 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, 1.5 lks. W. of the cor. fences extending N. and W., for a reference monument, bears N. 50°02' W., 35.5 lks. dist., with brass cap mkd. RM T47N R52E S33 23.4 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Insert the rebar inside the stainless steel post and reset the iron post, inverted, alongside.</p> <hr/> <p>N. 89°52'50" W., bet. secs. 4 and 33.</p> <p>Along improved gravel road.</p>
20.018	<p>The 1/16 sec. cor. No. 1, bet. secs. 4 and 33 (E1/2), monumented with the remains of the 1911 iron post, 18 ins. long, 1 in. diam., 2 ins. below the surface of an improved gravel road, with brass cap missing. This point will now be referred to as the E 1/16 sec. cor. of secs. 4 and 33.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the improved gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <p>S33</p> <p>E 1/16 $\frac{\quad}{\quad}$</p> <p>S 4</p> <p>T46N</p> <p>2004</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing NW. and SE., for a reference monument, bears N. 60°49' E., 55.6 lks. dist., with brass cap mkd. RM E 1/16 S33 36.7 FT TO COR 2004 and an arrow pointing to the corner.</p>

CHAINS

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 8°48' E., 70.6 lks. dist., with brass cap mkd. RM E 1/16 S4 46.6 FT TO COR 2004 and an arrow pointing to the corner.

Bury the iron post alongside the stainless steel post.

N. 89°53'00" W., beginning new measurement.

Leave gravel road, continue over bladed dirt road.

20.017

The 1/4 sec. cor. of secs. 4 and 33, monumented with a rusted iron post, 36 ins. long, 1 in. diam., 2 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the survey of the north boundary of T. 46 N., R. 52 E., executed under Instructions dated April 27, 1911.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.

T47N R52E
S33
1/4
S 4
T46N

2004

Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.

Corner is located on N. side of bladed dirt road.

N. 89°53'20" W., beginning new measurement.

20.026

The 1/16 sec. cor. No. 2, bet. secs. 4 and 33 (W1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 21 ins. in the ground, with the exposed portion of the iron post bent flush with the ground, with brass cap mkd. as described in the field notes of the survey of the north boundary of T. 46 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 4 and 33.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <p>S33</p> <p>W 1/16 <u> </u></p> <p>S 4</p> <p>T46N</p> <p>2004</p> </div> <p>Reset the iron post, inverted, alongside the stainless steel post.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>N. 89°53'40" W., beginning new measurement.</p> <p>20.007 The cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of a bladed dirt road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <table border="1" style="margin: auto;"> <tr> <td>S32</td> <td>S33</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> </table> <p>T46N</p> <p>2007</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at the cor. of fences extending N. and E., for a reference monument, bears N. 41°49' E., 42.9 lks. dist., with brass cap mkd. RM T47N R52E S33 28.3 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 43°26' W., 43.6 lks. dist., with brass cap mkd. RM T47N R52E S32 28.8 FT TO COR 2004 and an arrow pointing to the corner.</p> <hr style="width: 60%; margin: 20px auto;"/>	S32	S33	S 5	S 4
S32	S33				
S 5	S 4				

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 89°53'40" W., bet. secs. 5 and 32.</p> <p>Over rolling land.</p>
20.007	<p>Point for the E 1/16 sec. cor. of secs. 5 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <p>S32</p> <p>E 1/16 $\frac{\quad}{\quad}$</p> <p>S 5</p> <p>T46N</p> <p>2004</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
40.014	<p>The 1/4 sec. cor. of 5 and 32, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 26 ins. in the ground, with the exposed portion of the iron post bent flush with the ground, with brass cap mkd. as described in the field notes of the survey of the north boundary of T. 46 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <p>S32</p> <p>1/4 $\frac{\quad}{\quad}$</p> <p>S 5</p> <p>T46N</p> <p>2004</p> </div> <p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°54'30" W., beginning new measurement.</p>
0.30	Canal road, bears NW. and SE.
20.009	Point for the W 1/16 sec. cor. of secs. 5 and 32.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E S32 W 1/16 <u> </u> S 5 T46N</p> <p style="text-align: center;">2005</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
22.50	Improved gravel road, bears NE. and SW.
38.85	Improved gravel road, 25 ft. wide, bears NE. and SW.
40.018	<p>The cor. of secs. 5, 6, 31 and 32, monumented with a rusted iron post, 36 ins. long, 1 in. diam., firmly set, projecting 21 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the north boundary, T. 46 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E S31 S32 S 6 S 5 T46N</p> <p style="text-align: center;">2004</p> <p>Reset the iron post, inverted, alongside the stainless steel post.</p> <hr/> <p>N. 89°55'30" W., bet. secs. 6 and 31.</p> <p>Over rolling land.</p>
20.012	<p>Point for the E 1/16 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T47N R52E S31 E 1/16 $\frac{\quad}{\quad}$ S 6 T46N</p> <p style="text-align: center;">2005</p>
40.024	<p>The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 21 ins. in the ground, with the exposed portion of the iron post bent at base, with brass cap mkd. as described in the field notes of the survey of the north boundary, T. 46 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E S31 1/4 $\frac{\quad}{\quad}$ S 6 T46N</p> <p style="text-align: center;">2004</p> <p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending S. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°56'30" W., beginning new measurement.</p>
20.004	<p>Point for the W 1/16 sec. cor. of secs. 6 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E S31 W 1/16 $\frac{\quad}{\quad}$ S 6 T46N</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Cor. is located 1 lk. S. of a fence, bears E. and W.
39.548	<p>The cor. of Tps. 46 and 47 N., Rs. 51 and 52 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 46 N., R. 51 E., executed under Instructions dated April 27, 1911.</p> <p>Set a steel sign post, 6 ft. long, alongside the cor.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the cor. of Tps. 46 and 47 N., Rs. 52 and 53 E., hereinbefore described.</p> <p>N. 0°01'00" W., bet. secs. 31 and 36.</p> <p>Across bottom land.</p>
14.70	Nevada State Route 51, asphalt-surfaced, bears E. and W.; continue along base of mountains, ascend.
39.880	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E R53E 1/4 S36 S31 2006</p>
79.760	<p>Cor. is located at the corner of fence remnants extending N., S. and E.</p> <p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the east boundary, T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, with a mound of stone, 2 ft. base, 10 ins. high, W. of cor.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

MEMORANDUM

The original notes describe the cor. of secs. 1, 6, 7 and 12 as an iron post and do not mention a witness corner. However, a chiseled "X", was found marking the corner point and an iron post with additional scribe marks indicating it is mkd. for a witness corner was found south of the corner point.

From the true point for the cor. of secs. 1, 6, 7 and 12, monumented with a chiseled "X" on top of igneous boulder in place, 3 ft. base, projecting 9 ins. above the ground.

At the corner point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, in concreted drill hole, with brass cap mkd.

T47N	
R52E	R53E
S 1	S 6
<hr/>	
S12	S 7

2006

From this cor., the witness cor. to the cor. of secs. 1, 6, 7 and 12, bears S. 0°02'40" E., 0.055 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor., with brass cap mkd.

S 1	S 6
R52E	T47N
<hr/>	
S12	S 7
<hr/>	
W C	5 L N
1911	
.....	

N. 0°02'40" W., bet. secs. 1 and 6.

Over rolling, table land.

13.629

The original closing cor. of Tps. 47 N., Rs. 52 and 53 E., monumented with an iron post, 3 ins. diam., loosely set, projecting 28 ins. above the ground, in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as the amended closing cor. of Tps. 47 N., Rs. 52 and 53 E. Add the marks AM 2006 to the brass cap and bury in place.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
13.773	<p>Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. of Tps. 47 N., Rs. 52 and 53 E.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \overline{S\ 1\ S\ 6} \\ C\ C \\ R52E\ R53E \\ T47N \\ 2006 \end{array}$ </div> <p>From this point, the 104 Mile Post bears S. 89°28'40" E., 35.408 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the cor. of Tps. 46 and 47 N., Rs. 51 and 52 E., hereinbefore described.</p> <p>N. 0°02'00" W., bet. secs. 31 and 36.</p> <p>Over rolling land.</p>
19.982	<p>Point for the S 1/16 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} T47N \\ R51E\ R52E \\ S\ 1/16 \\ S36\ S31 \\ 2004 \end{array}$ </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
39.964	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R51E R52E 1/4 S36 S31 2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>59.946 Point for the N 1/16 sec. cor. of secs. 31 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R51E R52E N 1/16 S36 S31 2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>79.928 The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 24 ins. in the ground, with the exposed portion of the iron post bent at base, with brass cap mkd. as described in the field notes of the survey of east boundary of T. 47 N., R. 51 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R51E R52E S25 S30 ----- S36 S31 2004</p> <p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
--------	--

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°01'00" E., bet. secs. 25 and 30.
	Over rolling land.
19.974	Point for the S 1/16 sec. cor. of secs. 25 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">T47N R51E R52E S 1/16 S25 S30</p>
	2004
	Set a steel sign post, 6 ft. long, alongside the stainless steel post.
39.948	The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 12 ins. in the ground, with exposed portion of the iron post bent flush with the ground, with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 47 N., R. 51 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p style="text-align: center;">T47N R51E R52E 1/4 S25 S30</p>
	2004
	Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.
	Cor. is located 2 lks. W. of a fence, bears N. and S.
	<p style="text-align: center;">_____</p>
	N. 0°03'10" W., beginning new measurement.
20.005	Point for the N 1/16 sec. cor. of secs. 25 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="889 275 1036 394"> <p>T47N R51E R52E N 1/16 S25 S30</p> </div> <div data-bbox="930 426 995 451">2004</div> <div data-bbox="456 487 1477 543">Set a steel sign post, 6 ft. long, alongside the stainless steel post.</div> <div data-bbox="456 577 1299 604">Cor. is located 2 lks. W. of a fence, bears N. and S.</div> <div data-bbox="310 638 1477 842"> <p>40.010 Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance. The 1911 corner monument, an iron post, 36 ins. long, 1 in. diam., with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 47 N., R. 51 E., executed under Instructions dated April 27, 1911, was found laying loose on the ground, the original position undeterminable.</p> </div> <div data-bbox="456 877 1477 966">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div data-bbox="889 999 1036 1127"> <p>T47N R51E R52E S24 S19 S25 S30</p> </div> <div data-bbox="930 1157 995 1182">2004</div> <div data-bbox="456 1218 1461 1274">Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</div> <div data-bbox="456 1308 1331 1335">Cor. is located 4.5 lks. W. of a fence, bears N. and S.</div> <hr/> <div data-bbox="456 1398 1044 1425">N. 0°03'10" W., bet. secs. 19 and 24.</div> <div data-bbox="456 1459 743 1486">Over rolling land.</div> <div data-bbox="310 1520 1253 1547"> <p>20.005 Point for the S 1/16 sec. cor. of secs. 19 and 24.</p> </div> <div data-bbox="456 1581 1477 1669">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div data-bbox="889 1703 1036 1822"> <p>T47N R51E R52E S 1/16 S24 S19</p> </div> <div data-bbox="930 1852 995 1877">2004</div>
--------	---

CHAINS	
	<p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 7 lks. W. of a fence, bears N. and S.</p>
40.010	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 47 N., R. 51 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R51E R52E 1/4 S24 S19</p> <p style="text-align: center;">2004</p> <p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 7.5 lks. W. of a fence, bears N. and S.</p> <hr/> <p>N. 0°02'00" W., beginning new measurement.</p>
19.989	<p>Point for the N 1/16 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R51E R52E N 1/16 S24 S19</p> <p style="text-align: center;">2007</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 7 lks. W. of a fence, bears N. and S.</p> <p>From this cor., Federal Base Network Control Station H 318, bears S. 83°37'20" E., 8.785 chs. dist., monumented with a standard metal disk mkd. H 318 1951, set in a concrete post, 12 ins. diam., projecting 5 ins. above the surface of the ground with two steel fence posts set alongside.</p>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.978	<p>The point for the cor. of secs. 13, 18, 19, and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of a bladed gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R51E R52E S13 S18 S24 S19</p> <p>2004</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 50°40' E., 68.5 lks. dist., with brass cap mkd. RM T47N R52E S18 45.2 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears S. 53°52' E., 64.7 lks. dist., with brass cap mkd. RM T47N R52E S19 42.7 FT TO COR 2004 and an arrow pointing to the corner.</p> <hr/> <p>N. 0°02'00" W., bet. secs. 13 and 18.</p> <p>Along bladed gravel road.</p>
19.989	<p>Point for the 1/16 sec. cor. No. 12, bet. secs. 13 and 18 (S1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the S 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of a bladed gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R51E R52E S 1/16 S13 S18</p> <p>2004</p> </div>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 47°21' E., 72.0 lks. dist., with brass cap mkd. RM S 1/16 S18 47.5 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears S. 59°15' E., 62.0 lks. dist., with brass cap mkd. RM S 1/16 S18 40.9 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>39.978 The 1/4 sec. cor. of secs. 13 and 18, monumented with a rusted iron post, 36 ins. long, 1 in. diam., set 4 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 47 N., R. 51 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R51E R52E 1/4 S13 S18 2007</p> </div> <p>Reset the iron post, inverted, alongside the stainless steel post.</p> <p>Cor. is located 3 lks. W. of the cor. of fences extending N., E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02'00" W., beginning new measurement.</p> <p>Across cultivated field.</p> <p>19.989 Point for the 1/16 sec. cor. No. 6, bet. secs. 13 and 18 (N1/2), at proportionate distance. The 1911 iron post, 36 ins. long, 1 in. diam., with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 47 N., R. 51 E., executed under the Instructions dated April 27, 1911, was found laying loose on the ground, the original position undeterminable. This point will now be referred to as the N 1/16 sec. cor. of secs. 13 and 18.</p>
--------	--

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R51E R52E N 1/16 S13 S18</p> <p style="text-align: center;">2004</p> <p>Reset the iron post, inverted, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., S. and E.</p>
34.50	Slough, drains irregularly NW.
39.978	<p>The cor. of secs. 7, 12, 13 and 18, monumented with remains of the bottom portion of the 1911 iron post, 18 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with the top portion of the iron post, 12 ins. long, wired to a nearby fence corner, with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 47 N., R. 51 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R51E R52E S12 S 7 S13 S18</p> <p style="text-align: center;">2004</p> <p>Bury top and bottom portions of the iron post alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending E., W. and S.</p> <hr/> <p>N. 0°02'10" W., bet. secs. 7 and 12.</p> <p>Across cultivated field.</p>
19.98	Fence, bears E. and W.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.992	<p>Point for the 1/16 sec. cor. No. 12, bet. secs. 7 and 12 (S1/2), at proportionate distance. The disturbed remains of the 1911 iron post was found 12 ins. below the surface of the ground, laying horizontally, with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 47 N., R. 51 E., executed under Instructions dated April 27, 1911, the original position undeterminable. This point will now be referred to as the S 1/16 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R51E R52E S 1/16 S12 S 7 2004</p> <p>Bury the remains of the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
39.984	<p>The 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R51E R52E 1/4 S12 S 7 2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on N. side of field access road, bears E. and W.</p>
59.976	<p>The 1/16 sec. cor. No. 6 bet. secs. 7 and 12 (N1/2), monumented with a rebar of unknown origin, 18 ins. long, 5/8 in. diam., firmly set, projecting 4 ins. above the ground. This rebar is accepted as best available evidence of the position of the original corner. This cor. will now be referred to as the N 1/16 sec. cor. of secs. 7 and 12.</p>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R51E R52E N 1/16 S12 S 7</p> <p>2004</p> </div> <p>Bury the rebar and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02'10" W., beginning new measurement.</p> <p>Leave cultivated fields enter rolling land.</p>
19.992	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 47 N., R. 51 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R51E R52E S 1 S 6 <hr style="width: 50%; margin: 0 auto;"/>S12 S 7</p> <p>2004</p> </div> <p>Reset the iron post, inverted, alongside the stainless steel post.</p> <p>Cor. is located in fence, bears N. and S.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 0°03'00" W., bet. secs. 1 and 6.</p> <p>Over rolling land.</p>
4.80	<p>Asphalt-surfaced road, bears NW. and SE.</p>

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
13.404	<p>Intersect the Idaho-Nevada State Line.</p> <p>The closing cor. of secs. 1 and 6, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above the ground, in a collar of stone, with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 47 N., R. 51 E., executed under Instructions dated April 27, 1911. Add the marks 2006 to the brass cap.</p> <p>From this corner, the 111 Mile Post, hereinbefore described, bears S. 89°50'30" W., 49.296 chs. dist.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02'00" W., bet. secs. 35 and 36.</p> <p>Across cultivated field.</p>
13.00	Owyhee River, 2 chs. wide, course NW.; enter rolling land.
14.90	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, on curve bearing S. 60° E. and N. 60° W.
19.997	<p>Point for the 1/16 sec. cor. No. 12, bet. secs. 35 and 36 (S1/2) at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the S 1/16 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S35 S36</p> <p style="text-align: center;">2005</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.994	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S35 S36 2005</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 80 lks. E. of Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 1 1/2° W. and S. 1 1/2° E.</p>
59.991	<p>The 1/16 sec. cor. No. 6, bet. secs. 35 and 36 (N1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 18 ins. above the ground, in a mound of stone, 1 1/2 ft. base, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the N 1/16 sec. cor. of secs. 35 and 36.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S35 S36 2004</p> <p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
	<p>N. 0°02'40" E., beginning new measurement.</p>
20.023	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a rebar of unknown origin, 18 ins. long, 3/4 in. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 4 ft. base. This rebar has been locally recognized and utilized by various Professional Land Surveyors and is accepted as the best available evidence of the position of the original corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <table border="1" style="margin: auto;"> <tr> <td>S26</td><td>S25</td></tr> <tr> <td>S35</td><td>S36</td></tr> </table> <p>2006</p> </div> <p>Bury the rebar inside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89°46'50" W., bet. secs. 25 and 36.</p> <p>Over mountainous land, along S. slope.</p> <p>40.118 True point for the 1/4 sec. cor. of secs. 25 and 36, at record distance. This point falls on rocky outcrop where it is impractical to establish a permanent monument.</p> <p>40.408 The witness cor. to the 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <hr/> <p>N. 89°41'40" W., beginning new measurement.</p> <p>Descend W. slope.</p> <p>39.373 The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0°01'50" W., bet. secs. 25 and 26.</p> <p>Along base of mountains.</p> <p>19.962 The 1/16 sec. cor. No. 12, bet. secs. 25 and 26 (S1/2), monumented with a steel fence post of unknown origin, 3 ft. long, firmly set in a mound of stone, 3 ft. base, 2 ft. high. This steel fence post is harmoniously related to surrounding corners and is accepted as the best available evidence of the position of the original corner. The cor. will now be referred to as the S 1/16 sec. cor. of secs. 25 and 26.</p>	S26	S25	S35	S36
S26	S25				
S35	S36				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S26 S25</p> <p style="text-align: center;">2006</p> <p>Reset the steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°03'20" W., beginning new measurement.</p>
19.224	Record position for the witness cor. to the 1/4 sec. cor. of secs. 25 and 26; there is no remaining evidence of the original witness corner. The witness cor. serves no further function.
19.974	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., over a chiseled cross(X) on a rock outcrop, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S26 S25</p> <p style="text-align: center;">2006</p>
39.948	<p>Point for the 1/16 sec. cor. No. 6, bet. secs. 25 and 26 (N1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S26 S25</p> <p style="text-align: center;">2006</p>
59.922	<p>The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, and in a collar of stone, 2 ft. base, 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°06'40" W., bet. secs. 23 and 24.</p> <p>Over mountainous land.</p>
19.968	<p>Point for the S 1/16 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S23 S24</p> <p style="text-align: center;">2006</p>
39.876	<p>The witness cor. to the 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., loosely set in a mound of stone, projecting 2 ft. above the mound, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Rehabilitate the mound of stone, 4 ft. base, to top and add the marks T47N R52E W C 2008 to brass cap.</p> <hr/> <p>N. 0°00'30" W., beginning new measurement.</p>
0.060	<p>True point for the 1/4 sec. cor. of secs. 23 and 24, determined at record distance from the witness cor.; falls in rock slide, where it is impracticable to establish a permanent monument.</p>
40.119	<p>The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, firmly set, projecting 15 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor. Add the marks 2008 to the brass cap. Rebuild the mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <hr/> <p>N. 0°08'30" W., bet. secs. 13 and 14.</p> <p>Over mountainous land.</p>
39.987	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., loosely set, projecting 24 ins. above the ground, and in a scattered mound of stone, 2 ft. base, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor. Rebuild the scattered mound of stone, 4 ft. base, to top and add the marks T47N R52E 2008 to the brass cap.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°01'30" W., beginning new measurement.
19.987	<p>Point for the N 1/16 sec. cor. of secs. 13 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S14 S13</p> <p style="text-align: center;">2006</p>
39.974	<p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 1 in. diam., loosely set, projecting 24 ins. above the ground, in a scattered mound of stone, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor. Rebuild the scattered mound of stone, 4 ft. base, to top and add the marks 2008 to the brass cap.</p> <hr/> <p>N. 0°03'00" W., bet. secs. 11 and 12.</p> <p>Over mountainous land.</p>
20.051	<p>Point for the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S11 S12</p> <p style="text-align: center;">2006</p>
40.102	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., loosely set, projecting 18 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, with a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p> <hr/> <p>N. 0°04'10" W., beginning new measurement.</p>
19.944	<p>Point for the N 1/16 sec. cor. of secs. 11 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>N 1/16 S11 S12</p> <p>2006</p>
39.888	<p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 36 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R 52 E., executed under Instructions dated April 27, 1911.</p> <hr/> <p>N. 0°06'10" W., bet. secs. 1 and 2.</p> <p>Over mountainous land.</p>
13.957	<p>The original closing cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor. This cor. will now function as the amended closing cor. of secs. 1 and 2. Add the marks AM 2006 to the brass cap and bury in place.</p>
13.994	<p>Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. of secs. 1 and 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <hr style="width: 50%; margin: 0 auto;"/> <p>S 2 S 1 C C T47N R52E</p> <p>2006</p> </div> <p>From this point, the witness cor. to the 105 Mile Post, hereinbefore described, bears S. 89°55'00" E., 14.267 chs. dist.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°02'00" W., bet. secs. 34 and 35.</p> <p>Along asphalt-surfaced road.</p>
19.928	<p>Point for the 1/16 sec. cor. No. 12, bet. secs. 34 and 35 (S1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the S 1/16 sec. cor. of secs. 34 and 35.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">S 1/16 S34 S35</p> <p style="text-align: center;">2007</p> <p>39.856 The 1/4 sec. cor. of secs. 34 and 35, monumented with a rebar of unknown origin, 18 ins. long, 5/8 in. diam., firmly set 4 ins. below the asphalt-surfaced road. This rebar is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 3 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S34 S35</p> <p style="text-align: center;">2006</p> <p>Bury the rebar alongside the copper coated steel stake.</p> <hr/> <p>N. 0°05'30" E., beginning new measurement.</p> <p>20.020 Point for the 1/16 sec. cor. No. 6, bet. secs. 34 and 35 (N1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the N 1/16 sec. cor. of secs. 34 and 35.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">N 1/16 S34 S35</p> <p style="text-align: center;">2007</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.040	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a rebar of unknown origin, 24 ins. long, 1/2 in. diam., firmly set 4 ins. below the surface, at the intersection of asphalt-surfaced roads extending E., W. and S. This rebar has been locally utilized and accepted by various Professional Land Surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 5 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"><div>T47N R52E</div><div>S27 S26</div><div>S34 S35</div><div>2006</div></div> <p>Bury the rebar alongside the copper coated steel stake.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°54'20" W., bet. secs. 26 and 35.</p>
10.40	<p>Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 14 1/4° W. and S. 14 1/4° E; thence along asphalt-surfaced road, bears W.</p>
19.990	<p>Point for the 1/16 sec. cor. No. 1, bet. secs. 26 and 35 (E1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the E 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"><div>E 1/16</div><div>S26</div><div>S35</div><div>2006</div></div>
34.50	<p>Bridge over the Owyhee River, 2 chs. wide, river courses NNW.</p>
35.980	<p>Record position for the witness cor. to the 1/4 sec. cor. of secs. 26 and 35; there is no remaining evidence of the original corner. The witness cor. serves no further function.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.980	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 4 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <p>S26</p> <p>1/4 $\frac{\quad}{\quad}$</p> <p>S35</p> <p>2006</p> </div>
59.970	<p>Point for the 1/16 sec. cor. No. 2, bet. secs. 26 and 35 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>S26</p> <p>W 1/16 $\frac{\quad}{\quad}$</p> <p>S35</p> <p>2007</p> </div>
79.960	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>N. 0°08'50" W., bet. secs. 26 and 27.</p> <p>Across cultivated field.</p>
19.944	<p>Point for the 1/16 sec. cor. No. 12, bet. secs. 26 and 27 (S1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the S 1/16 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16</p> <p>S27 S26</p> <p>2006</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Cor. is located on S. side of irrigation ditch, drains W., and 30 lks. W. of fence, bears N. and S.
39.10	Fence, bears E. and W.
39.888	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T47N R52E 1/4 S27 S26 2006
	Cor. is located on the S. side of an access road, bears E. and W.
40.60	Fence, bears E. and W.
59.832	Point for the 1/16 sec. cor. No. 6, bet. secs. 26 and 27 (N1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the N 1/16 sec. cor. of secs. 26 and 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. N 1/16 S27 S26 2006
	Cor. is located S. 62 3/4° W., 25 lks. dist. of the cor. of fences extending N., S., E. and W.
59.95	Fence, bears E. and W.
74.10	Improved gravel road, bears NW. and SE.
77.30	Owyhee River, 2 chs. wide, course NW.
79.776	The cor. of secs. 22, 23, 26 and 27, monumented with a steel drill rod of unknown origin, 20 ins. long, 2 ins. diam., firmly set 6 ins. below the ground. This steel drill rod correlates well with other existing corners and is accepted as the best available evidence of the position of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <table> <tr> <td>S22</td><td>S23</td></tr> <tr> <td>S27</td><td>S26</td></tr> </table> <p>2004</p> </div> <p>Bury the steel drill rod alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°11'00" W., bet. secs. 23 and 26.</p> <p>Over mountainous land.</p>	S22	S23	S27	S26
S22	S23				
S27	S26				
20.642	<p>The 1/16 sec. cor. No. 1, bet. secs. 23 and 26 (E1/2), monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, and in a mound of stone, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the E 1/16 sec. cor. of secs. 23 and 26.</p> <hr/> <p>N. 89°41'40" W., beginning new measurement.</p>				
10.90	<p>Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 27 3/4° W. and S. 27 3/4° E.; thence along improved gravel road.</p>				
19.50	<p>Canal, 6 lks. wide, course N.</p>				
19.70	<p>Southerly edge of an improved gravel road, bears E. and W.</p>				
19.814	<p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <table> <tr> <td>1/4</td><td>S23</td></tr> <tr> <td></td><td>S26</td></tr> </table> <p>2006</p> </div>	1/4	S23		S26
1/4	S23				
	S26				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.628	<p>Point for the 1/16 sec. cor. No. 2, bet. secs. 23 and 26 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S23} \\ \text{W 1/16 } \frac{\text{S23}}{\text{S26}} \\ \text{S26} \end{array}$ <p>2006</p> </div> <p>Cor. is located on S. shoulder of an improved gravel road, bears E. and W.</p>
59.442	<p>The cor. of secs. 22, 23, 26 and 27.</p> <hr/> <p>N. 0°05'40" W., bet. secs. 22 and 23.</p> <p>Along improved gravel road.</p>
20.025	<p>Point for the 1/16 sec. cor. No. 12, bet. secs. 22 and 23 (S1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of an improved gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S 1/16} \\ \text{S22} \text{S23} \end{array}$ <p>2006</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, 1 lk. W. of a fence bearing N. and S., for a reference monument, bears S. 56°43' E., 90.8 lks. dist., with brass cap mkd. RM S 1/16 S23 59.9 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, 1 lk. E. of a fence bearing N. and S., for a reference monument, bears S. 46°23' W., 62.9 lks. dist., with brass cap mkd. RM S 1/16 S22 41.5 FT TO COR 2006 and an arrow pointing to the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.050	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of an improved gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S22 S23 2006</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, 3 lks. W. of a fence bearing N. and S., for a reference monument, bears N. 44°24' E., 97.1 lks. dist., with brass cap mkd. RM 1/4 S23 64.1 FT TO COR 2006 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, 1 lk. E. of a fence bearing N. and S., for a reference monument, bears N. 36°06' W., 79.4 lks. dist., with brass cap mkd. RM 1/4 S22 52.4 FT TO COR 2006 and an arrow pointing to the corner.</p>
60.075	<p>Point for the 1/16 sec. cor. No. 6, bet. secs. 22 and 23 (N1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of an improved gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S22 S23 2006</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, 1 lk. W. of a fence bearing N. and S., for a reference monument, bears S. 55°27' E., 81.8 lks. dist., with brass cap mkd. RM N 1/16 S23 54.0 FT TO COR 2006 and an arrow pointing to the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, 1 lk. E. of a fence bearing N. and S., for a reference monument, bears S. 54°13' W., 64.7 lks. dist., with brass cap mkd. RM N 1/16 S22 42.7 FT TO COR 2006 and an arrow pointing to the corner.</p>						
80.100	<p>Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of an improved gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T47N</td><td>R52E</td></tr> <tr><td>S15</td><td>S14</td></tr> <tr><td>S22</td><td>S23</td></tr> </table> <p>2006</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, 1 lk. N. of the cor. of fences extending E. and S., for a reference monument, bears S. 48°31' E., 86.7 lks. dist., with brass cap mkd. RM T47N R52E S23 57.2 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 22 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a collar of stone, 1 lk. N. of a fence bearing E. and W., for a reference monument, bears S. 58°24' W., 109.1 lks. dist., with brass cap mkd. RM T47N R52E S22 72.0 FT TO COR 2006 and an arrow pointing to the corner.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°54'20" W., bet. secs. 14 and 23.</p> <p>Over mountainous land.</p>	T47N	R52E	S15	S14	S22	S23
T47N	R52E						
S15	S14						
S22	S23						
40.056	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>T47N R52E S14 1/4 $\frac{\quad}{\quad}$ S23</p> <p>2006</p>
60.084	<p>Point for the 1/16 sec. cor. No. 2, bet. secs. 14 and 23 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p>W 1/16 $\frac{S14}{S23}$</p> <p>2006</p> <p>Cor. is located at the cor. of fences extending S. and W.</p>
67.50	Canal, 50 lks. wide, 5 ft. deep, drains N.
73.70	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 26 3/4° W. and S. 26 3/4° E.
80.112	<p>The cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 0°04'10" W., bet. secs. 14 and 15.</p> <p>Over gently rolling land.</p>
11.70	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.
20.02	Cor. of fences extending S., E. and NE.
20.025	<p>The 1/16 sec. cor. No. 12, bet. secs. 14 and 15 (S1/2), perpetuated by Donald J. Watts, Idaho Professional Engineer and Land Surveyor No. 1923, monumented with a rebar, 30 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with plastic cap, 1 in. diam., mkd. PELS 1923, as shown on an unrecorded plat titled Duck Valley Reservation, Employee Housing Tracts in Sections 14 and 15, dated October 12, 1994. This is accepted as a careful and faithful perpetuation of the position of the original corner. This cor. will now be referred to as the S 1/16 sec. cor. of secs. 14 and 15.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S15 S14</p> <p style="text-align: center;">2006</p> <p>Bury the rebar alongside the stainless steel post.</p> <hr/> <p>N. 0°14'40" W., beginning new measurement.</p> <p>19.977 The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <hr/> <p>N. 0°12'40" W., beginning new measurement.</p> <p>20.069 The 1/16 sec. cor. No. 6, bet. secs. 14 and 15 (N1/2), monumented with the remains of the 1911 iron post, 18 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with the top portion and brass cap missing. This cor. will now be referred to as the N 1/16 sec. cor. of secs. 14 and 15.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S15 S14</p> <p style="text-align: center;">2004</p> <p>Bury the remains of the iron post alongside the stainless steel post.</p> <hr/> <p>N. 0°13'00" W., beginning new measurement.</p> <p>19.964 The cor. of secs. 10, 11, 14 and 15, determined by Donald J. Watts, Idaho Professional Engineer and Land Surveyor No. 1923, monumented with a rebar, 30 ins. long, 5/8 in. diam., firmly set flush with the surface of the ground, with a plastic cap, 1 in. diam., mkd. PELS 1923, as shown on an unrecorded plat of the Reynold Teller survey. This is accepted as a careful and faithful determination of the position of the original corner.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <table border="1" style="margin: auto;"> <tr> <td>S10</td><td>S11</td></tr> <tr> <td>S15</td><td>S14</td></tr> </table> <p>2005</p> </div> <p>Bury the rebar alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N. and E.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°51'10" W., bet. secs. 11 and 14.</p> <p>Over mountainous land.</p> <p>20.059 Point for the E 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16 $\frac{S11}{S14}$</p> <p>2006</p> </div> <p>40.118 Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <table border="1" style="margin: auto;"> <tr> <td>1/4</td><td>$\frac{S11}{S14}$</td></tr> </table> <p>2007</p> </div> <p>60.177 Point for the 1/16 sec. cor. No. 2, bet. secs. 11 and 14 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 11 and 14.</p>	S10	S11	S15	S14	1/4	$\frac{S11}{S14}$
S10	S11						
S15	S14						
1/4	$\frac{S11}{S14}$						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{r} S11 \\ W\ 1/16 \quad \hline S14 \end{array}$ </p> <p style="text-align: center;">2005</p>
80.236	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°14'20" W., bet. secs. 10 and 11.</p> <p>Over gently rolling land.</p>
19.983	<p>The 1/16 sec. cor. No. 12, bet. secs. 10 and 11 (S1/2), monumented with a bent iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the original corner position. This cor. will now be referred to as the S 1/16 sec. cor. of secs. 10 and 11.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{r} S\ 1/16 \\ S10 \mid S11 \end{array}$ </p> <p style="text-align: center;">2004</p> <p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 4.5 lks. E. of a fence, bears N. and S.</p> <hr/> <p>N. 0°13'10" W., beginning new measurement.</p>
19.995	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S10 S11 2004</p> <p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 1.5 lks. E. of a fence, bears N. and S.</p> <hr/> <p>N. 0°11'50" W., beginning new measurement.</p> <p>19.997 Point for the 1/16 sec. cor. No. 6, bet. secs. 10 and 11 (N1/2), at proportionate distance; the 1911 monument, an iron post, 36 ins. long, 1 in. diam., with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, was found laying loose on the ground, the original position undeterminable. This point will now be referred to as the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S10 S11 2005</p> <p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>39.994 The cor. of secs. 2, 3, 10 and 11, monumented with a rusted iron post firmly set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="894 281 1039 380"> <p>T47N R52E $\frac{S\ 3}{S10} \mid \frac{S\ 2}{S11}$</p> </div> <div data-bbox="935 407 998 432">2004</div> <div data-bbox="459 468 1414 527"> <p>Reset the iron post, inverted, alongside the stainless steel post.</p> </div> <hr/> <div data-bbox="459 590 1078 615"> <p>From the cor. of secs. 1, 2, 11 and 12.</p> </div> <div data-bbox="459 648 1045 674"> <p>N. 89°54'10" W., bet. secs. 2 and 11.</p> </div> <div data-bbox="315 709 1235 735"> <p>20.158 Point for the E 1/16 sec. cor. of secs. 2 and 11.</p> </div> <div data-bbox="459 770 1479 856"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> </div> <div data-bbox="829 892 992 961"> <p>E 1/16 $\frac{S\ 2}{S11}$</p> </div> <div data-bbox="935 993 998 1018">2006</div> <div data-bbox="315 1054 1468 1203"> <p>40.316 The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Add the marks T47N R52E 2008 to the brass cap.</p> </div> <hr/> <div data-bbox="459 1266 1143 1291"> <p>N. 89°49'30" W., beginning new measurement.</p> </div> <div data-bbox="459 1327 776 1352"> <p>Across pasture land.</p> </div> <div data-bbox="315 1388 1479 1501"> <p>20.058 Point for the 1/16 sec. cor. No. 2, bet. secs. 2 and 11 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 2 and 11.</p> </div> <div data-bbox="459 1537 1419 1623"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="826 1659 992 1728"> <p>W 1/16 $\frac{S\ 2}{S11}$</p> </div> <div data-bbox="935 1759 998 1785">2006</div> <div data-bbox="315 1820 998 1845"> <p>40.116 The cor. of secs. 2, 3, 10 and 11.</p> </div> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°15'20" W., bet. secs. 2 and 3.
13.965	<p>Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \hline S\ 3 \mid S\ 2 \\ C\ C \\ T47N\ R52E \\ 2006 \end{array}$ </div> <p>From this point, Mile Post No. 106 bears S. 89°50'50" E., 36.418 chs. dist., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°03'10" W., bet. secs. 33 and 34.</p> <p>Along improved gravel road.</p>
20.016	<p>The 1/16 sec. cor. No. 12, bet. secs. 33 and 34 (S1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 12 ins. below the surface of an improved gravel road, with illegible marks on the brass cap. This cor. will now be referred to as the S 1/16 sec. cor. of secs. 33 and 34.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the improved gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} S\ 1/16 \\ S33 \mid S34 \\ 2004 \end{array}$ </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 44°29' E., 49.2 lks. dist., with brass cap mkd. RM S 1/16 S34 32.5 FT TO COR 2004 and an arrow pointing to the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 41°30' W., 45.6 lks. dist., with brass cap mkd. RM S 1/16 S33 30.1 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Reset the iron post, inverted, alongside the stainless steel post.</p> <hr/> <p>N. 0°05'20" W., beginning new measurement.</p>
19.979	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of an improved gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S33 S34 2004</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at the cor. of fences extending S. and E., for a reference monument, bears S. 43°09' E., 49.6 lks. dist., with brass cap mkd. RM 1/4 S34 32.7 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at the cor. of fences extending S. and W., for a reference monument, bears S. 40°06' W., 47.1 lks. dist., with brass cap mkd. RM S1/4 S33 31.1 FT TO COR 2004 and an arrow pointing to the corner.</p>
39.958	<p>The 1/16 sec. cor. No. 6, bet. secs. 33 and 34 (N1/2), monumented with a bent iron post, 36 ins. long, 1 in. diam., firmly set 10 ins. below the surface of an improved gravel road, with brass cap mkd. as described in the field notes of the survey of T 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted vertical position of the iron post as the best available evidence of the original corner position. This cor. will now be referred to as the N 1/16 sec. cor. of secs. 33 and 34.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the gravel road, over plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S33 S34</p> <p style="text-align: center;">2004</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 53°36' E., 64.1 lks. dist., with brass cap mkd. RM N 1/16 S34 42.3 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 48°34' W., 39.6 lks. dist., with brass cap mkd. RM N 1/16 S33 26.1 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Reset the iron post, inverted, alongside the stainless steel post.</p> <hr/> <p>N. 0°06'10" W., beginning new measurement.</p> <p>20.010 The cor. of secs. 27, 28, 33 and 34, determined at the intersection of asphalt-surfaced roads extending N., E. and W., and an improved gravel road extending S. This position correlates well with existing corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">T47N R52E S28 S27 S33 S34</p> <p style="text-align: center;">2006</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°53'20" W., bet. secs. 27 and 34. Along asphalt-surfaced road.
20.056	Point for the 1/16 sec. cor. No. 1, bet. secs. 27 and 34 (E1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the E 1/16 sec. cor. of secs. 27 and 34. Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd. <div style="text-align: center;"> $\begin{array}{r} \text{S27} \\ \text{E } 1/16 \frac{\quad}{\quad} \\ \text{S34} \end{array}$ </div> <div style="text-align: center;">2007</div>
40.112	Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 5 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd. <div style="text-align: center;"> $\begin{array}{r} \text{T47N R52E} \\ \text{S27} \\ 1/4 \frac{\quad}{\quad} \\ \text{S34} \end{array}$ </div> <div style="text-align: center;">2007</div>
60.168	Point for the 1/16 sec. cor. No. 2, bet. secs. 27 and 34 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 27 and 34. Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd. <div style="text-align: center;"> $\begin{array}{r} \text{S27} \\ \text{W } 1/16 \frac{\quad}{\quad} \\ \text{S34} \end{array}$ </div> <div style="text-align: center;">2007</div>
80.224	The cor. of secs. 27, 28, 33 and 34. <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°03'50" W., bet. secs. 27 and 28. Along asphalt-surfaced road.
20.002	Point for the 1/16 sec. cor. No. 12, bet. secs. 27 and 28 (S1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the S 1/16 sec. cor. of secs. 27 and 28. Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd. S 1/16 S28 S27 2007
40.004	Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd. T47N R52E 1/4 S28 S27 2006
60.006	Point for the 1/16 sec. cor. No. 6, bet. secs. 27 and 28 (N1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the N 1/16 sec. cor. of secs. 27 and 28. Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd. N 1/16 S28 S27 2007
80.008	The cor. of secs. 21, 22, 27 and 28, monumented with a rebar of unknown origin, 18 ins. long, 5/8 in. diam., firmly set 3 ins. below the surface of the asphalt. This rebar is accepted as the best available evidence of the position of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 4 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div><div>T47N R52E</div><div><div>S21</div><div>S22</div></div><div><div>S28</div><div>S27</div></div></div> <p>2006</p> <p>Bury the rebar alongside the copper coated steel stake.</p> <p>Cor. is located at the intersection of asphalt-surfaced roads extending S. and W., and an improved gravel road extending E.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89°34'00" W., bet. secs. 22 and 27.</p> <p>Along improved gravel road.</p> <p>2.80 Owyhee River, 2 chs. wide, course NW.</p> <p>9.50 Improved gravel road, parallels Owyhee River.</p> <p>19.864 The 1/16 sec. cor. No. 1, bet. secs. 22 and 27 (E1/2), monumented with a rusted iron post, 36 ins. long, 1 in. diam., firmly set 10 ins. below the surface of the gravel road, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, with and a rebar, 30 ins. long, 5/8 in. diam., set alongside. This cor. will now be referred to as the E 1/16 sec. cor. of secs. 22 and 27.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div><div>E 1/16</div><div><div>S22</div><div>S27</div></div></div> <p>2005</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 31°19' E., 68.9 lks. dist., with brass cap mkd. RM E 1/16 S22 45.5 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 36°24' E., 73.0 lks. dist., with brass cap mkd. RM E 1/16 S27 48.2 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>Reset the iron post, inverted, and deposit the rebar alongside the stainless steel post.</p> <hr/> <p>N. 89°47'30" W., beginning new measurement.</p>
20.067	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <p>S22</p> <p>1/4 <u> </u></p> <p>S27</p> <p>2005</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 36°20' E., 75.8 lks. dist., with brass cap mkd. RM 1/4 S22 50.0 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 26°17' E., 65.6 lks. dist., with brass cap mkd. RM 1/4 S27 43.3 FT TO COR 2005 and an arrow pointing to the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, a rebar of unknown origin, 5/8 in. diam., firmly set and bent, with plastic cap unreadable, bears S. 76°26' W., 0.012 chs. dist. This rebar was disturbed and not utilized during the course of this survey.</p>
40.134	<p>The 1/16 sec. cor. No. 2, bet. secs. 22 and 27 (W1/2), monumented with a rusted iron post, 36 ins. long, 1 in. diam., firmly set 12 ins. below the surface of a gravel road, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the W 1/16 sec. cor. of secs. 22 and 27.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} S22 \\ W\ 1/16 \quad \frac{\quad}{\quad} \\ S27 \end{array}$ <p>2005</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 37°48' E., 79.1 lks. dist., with brass cap mkd. RM W 1/16 S22 52.2 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 37°58' E., 70.8 lks. dist., with brass cap mkd. RM W 1/16 S27 46.7 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>Reset the iron post, inverted, alongside the stainless steel post.</p> <hr style="width: 20%; margin-left: 0;"/> <p>N. 89°43'50" W., beginning new measurement.</p>
20.089	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr style="width: 80%; margin-left: 0;"/> <p>N. 0°06'20" W., bet. secs. 21 and 22.</p> <p>Along gravel drive way.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.869	<p>The 1/16 sec. cor. No. 12, bet. secs. 21 and 22 (N1/2), determined at the cor. of fences extending N. and E. This position correlates well with existing corners and is accepted as the best available evidence of the position of the original corner. This cor. will now be referred to as the S 1/16 sec. cor. of secs. 21 and 22.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16 S21 S22</p> <p>2006</p> <hr style="width: 30%; margin: 10px auto;"/> </div> <p>N. 0°00'10" E., beginning new measurement.</p> <p>Enter pasture land.</p>
20.005	<p>Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E 1/4 S21 S22</p> <p>2006</p> </div> <p>Cor. is located on the south edge of a canal, drains W.</p>
20.19	Fence, bears E. and W.
40.010	<p>The 1/16 sec. cor. No. 6, bet. secs. 21 and 22 (N1/2), occupied by a railroad tie of unknown origin, 10x10 ins., firmly set, projecting 4 ft. above the ground, at the cor. of fences extending N., S., E. and W., with the remains of the 1911 iron post, 12 ins. long, 1 in. diam., with brass cap missing, wired to the railroad tie. This position correlates well with existing corners and is accepted as the best available evidence of the position of the original corner. This cor. will now be referred to as the N 1/16 sec. cor. of secs. 21 and 22.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 87°17' E., 15.2 lks. dist., with brass cap mkd. XRM N 1/16 S22 10.0 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears S. 7°32' E., 15.2 lks. dist., with brass cap mkd. RM N 1/16 S22 10.0 FT TO COR 2006 and an arrow pointing to the corner.</p> <hr/> <p>N. 0°10'00" W., beginning new measurement.</p>						
18.924	Record position for witness cor. to the cor. of secs. 15, 16, 21 and 22; there is no remaining evidence of the original corner. The witness cor. serves no further function.						
19.93	Gravel road, bears E. and W.						
20.024	<p>True point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of an improved gravel road bearing E. and W., with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T47N</td><td>R52E</td></tr> <tr><td>S16</td><td>S15</td></tr> <tr><td>S21</td><td>S22</td></tr> </table> <p>2006</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, on the N. shoulder of the gravel road, for a reference monument, bears N. 40°11' E., 47.7 lks. dist., with brass cap mkd. RM T47N R52E S15 31.5 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, on the N. shoulder of the gravel road, for a reference monument, bears N. 50°56' W., 54.7 lks. dist., with brass cap mkd. RM T47N R52E S16 36.1 FT TO COR 2006 and an arrow pointing to the corner.</p> <hr/>	T47N	R52E	S16	S15	S21	S22
T47N	R52E						
S16	S15						
S21	S22						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°57'40" W., bet. secs. 15 and 22.</p> <p>Along improved gravel road.</p> <p>20.048 Point for the 1/16 sec. cor. No. 1, bet. secs. 15 and 22 (E1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the E 1/16 sec. cor. of secs. 15 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S15} \\ \text{E 1/16} \quad \hline \text{S22} \end{array}$ <p>2006</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 51°35' E., 79.1 lks. dist., with brass cap mkd. RM E 1/16 S22 52.2 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 46°27' W., 71.8 lks. dist., with brass cap mkd. RM E 1/16 S22 47.4 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>40.096 Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{T47N R52E} \\ \text{S15} \\ \text{1/4} \quad \hline \text{S22} \end{array}$ <p>2006</p> </div> <p>from which</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 38°16' E., 59.2 lks. dist., with brass cap mkd. RM 1/4 S22 39.1 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 42°33' W., 63.9 lks. dist., with brass cap mkd. RM 1/4 S22 42.2 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>60.144 The 1/16 sec. cor. No. 2, bet. secs. 15 and 22 (W1/2), monumented with a bent iron post, 36 ins. long, 1 in. diam., firmly set, 18 ins. below the surface of a gravel road, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner. This cor. will now be referred to as the W 1/16 sec. cor. of secs. 15 and 22.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>W 1/16 $\frac{S15}{S22}$</p> <p>2005</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 39°01' E., 53.5 lks. dist., with brass cap mkd. XRM W 1/16 S22 35.3 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 51°30' W., 66.4 lks. dist., with brass cap mkd. RM W 1/16 S22 43.8 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>Cor. is located 60 lks. S. of canals extending E., W. and N., drains W.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°19'30" W., beginning new measurement.
13.20	Owyhee River, 2 chs. wide, course NW.
16.50	Intersection of improved gravel roads extending E., SE., W. and NW.
19.891	The cor. of secs. 15, 16, 21 and 22.
	N. 0°31'40" W., bet. secs. 15 and 16.
	Over gently rolling land.
5.00	Improved gravel road, bears NW. and SE.
8.00	Owyhee River, 2 chs. wide, course NW.; enter cultivated land.
10.00	Dirt road, bears NE. and SW.
19.98	Fence, bears E. and W.
20.024	The 1/16 sec. cor. No. 12, bet. secs. 15 and 16 (S1/2), monumented with remains of the 1911 iron post, 30 ins. long, 1 in. diam., firmly set 20 ins. in the ground, with brass cap missing. This cor. will now be referred to as the S 1/16 sec. cor. of secs. 15 and 16.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	S 1/16 S16 S15
	2006
	Reset the iron post, inverted, alongside the stainless steel post.
	Cor. is located N. 65° W., 10 lks. dist., of the cor. fences extending E., W. and N.
	N. 0°05'20" W., beginning new measurement.
19.999	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>T47N R52E 1/4 S16 S15 2006</p> <p>Cor. is located on the N. shoulder of a field access road.</p>
39.88	Fence, bears E. and W.
39.998	<p>Point for the 1/16 sec. cor. No. 6, bet. secs. 15 and 16 (N1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the N 1/16 sec. cor. of secs. 15 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, in an irrigation ditch, 10 lks. wide and 3 ft. deep, drains N., with brass cap mkd.</p> <p>N 1/16 S16 S15 2006</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at the cor. of fences extending E., W. and S., for a reference monument, bears S. 50°35' E., 19.1 lks. dist., with brass cap mkd. RM N 1/16 S15 12.6 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 47°52' W., 17.6 lks. dist., with brass cap mkd. RM N 1/16 S16 11.6 FT TO COR 2006 and an arrow pointing to the corner.</p>
59.59	Fence, bears E. and W.
59.997	<p>The cor. of secs. 9, 10, 15 and 16, monumented with a rebar of unknown origin, 12 ins. long, 1/2 in. diam., set 6 ins. below the surface of the gravel road. This rebar is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of an improved gravel road, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="889 275 1036 373"> <p>T47N R52E S 9 S10 S16 S15</p> </div> <div data-bbox="930 401 995 426">2006</div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 50°04' E., 62.9 lks. dist., with brass cap mkd. RM T47N R52E S10 41.5 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 32°13' W., 47.6 lks. dist., with brass cap mkd. RM T47N R52E S9 31.4 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>Bury the rebar alongside the stainless steel post.</p> <p>Cor. is located S. 32° W., 49 lks. dist. of the cor. of fences extending N., E. and W.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°52'20" W., bet. secs. 10 and 15.</p> <p>Through housing subdivision.</p> <div data-bbox="310 1308 407 1333">20.008</div> <div data-bbox="456 1308 1474 1423"> <p>Point for the 1/16 sec. cor. No. 1, bet. secs. 10 and 15 (E1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="824 1577 990 1650"> <p>E 1/16 $\frac{S10}{S15}$</p> </div> <div data-bbox="930 1680 995 1705">2006</div> </div> <div data-bbox="310 1740 391 1766">36.35</div> <div data-bbox="456 1740 1430 1829"> <p>Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.; thence along bladed gravel road.</p> </div>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.016	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of a gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <p>S10</p> <p>1/4 <u> </u></p> <p>S15</p> <p>2006</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 48°48' E., 63.6 lks. dist., with brass cap mkd. RM 1/4 S10 42.0 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 46°21' W., 60.3 lks. dist., with brass cap mkd. RM 1/4 S10 39.8 FT TO COR 2006 and an arrow pointing to the corner.</p>
60.024	<p>Point for the 1/16 sec. cor. No. 2, bet. secs. 10 and 15 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S10</p> <p>W 1/16 <u> </u></p> <p>S15</p> <p>2006</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 53°45' E., 79.2 lks. dist., with brass cap mkd. RM W 1/16 S15 52.3 FT TO COR 2006 and an arrow pointing to the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 46°55' W., 73.3 lks. dist., with brass cap mkd. RM S 1/16 S15 48.4 FT TO COR 2006 and an arrow pointing to the corner.</p>
80.032	<p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p>N. 0°16'40" W., bet. secs. 9 and 10.</p> <p>Along bladed dirt road.</p>
0.42	Fence, bears E. and W.
19.94	Fence, bears E. and W.
19.999	<p>Point for the 1/16 sec. cor. No. 12, bet. secs. 9 and 10 (S1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the S 1/16 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, in an irrigation ditch, 6 lks. wide, 1 ft. deep, drains N., with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 9 S10</p> <p style="text-align: center;">2006</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, on the E. berm of an irrigation ditch bearing N. and S., for a reference monument, bears S. 35°52' E., 27.4 lks. dist., with brass cap mkd. RM S 1/16 S10 18.1 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 79°29' W., 23.9 lks. dist., with brass cap mkd. RM S 1/16 S9 15.8 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>Cor. is located N. 77°05' W., 30 lks. dist., of the cor. of fences extending N., S., E. and W.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.998	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with a rebar of unknown origin, 20 ins. long, 5/8 in. diam., firmly set 4 ins. below the asphalt surface, at intersection of roads extending S., E. and W. This rebar correlates well with existing corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S 9 S10 2006</p> <p>Bury the rebar alongside the copper coated steel stake.</p> <hr/> <p>N. 0°05'40" W., beginning new measurement.</p> <p>Enter pasture land.</p>
20.086	<p>The 1/16 sec. cor. No. 6, bet. secs. 9 and 10 (N1/2), determined by Donald J. Watts, Idaho Professional Land Surveyor No. 1923, monumented with a rebar, 24 ins. long, 1/2 in. diam., firmly set, projecting 2 ins. above the ground, with plastic cap, 1 1/2 ins. diam., mkd. PELS 1923, as shown on an unrecorded home site survey plat, dated 1997. This rebar has been locally recognized and is accepted as a careful and faithful determination of the position of the original corner. This cor. will now be referred to as the N 1/16 sec. cor. of secs. 9 and 10.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 9 S10 2006</p> <p>Bury the rebar alongside the stainless steel post.</p> <p>Cor. is located S. 25° E., 16 lks. dist. of the cor. of fences extending N. and E.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°04'50" E., beginning new measurement.</p> <p>Enter gently rolling land.</p>				
0.15	Fence, bears E. and W.				
19.859	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a rebar of unknown origin, 30 ins. long, 5/8 in. diam., firmly set 2 ins. below the surface of the ground. This rebar has been locally recognized and utilized by various professional land surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <table> <tr> <td>S 4</td><td>S 3</td></tr> <tr> <td>S 9</td><td>S10</td></tr> </table> <p>2006</p> </div> <p>Bury the rebar and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°48'00" W., bet. secs. 3 and 10.</p> <p>Over gently rolling land.</p>	S 4	S 3	S 9	S10
S 4	S 3				
S 9	S10				
19.949	<p>The 1/16 sec. cor. No. 1, bet. secs. 3 and 10 (N1/2), monumented with a bent iron post, 36 ins. long, 1 in. diam., loosely set, projecting 28 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner. This cor. will now be referred to as the E 1/16 sec. cor. of secs. 3 and 10.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td>E 1/16</td><td>S 3</td></tr> <tr> <td></td><td>S10</td></tr> </table> <p>2004</p> </div>	E 1/16	S 3		S10
E 1/16	S 3				
	S10				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
	<hr/>
	<p>N. 89°58'30" W., beginning new measurement.</p>
19.984	<p>The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T47N R52E S 3 1/4 <u> </u> S10</p>
	<p style="text-align: center;">2004</p>
	<p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
	<hr/>
	<p>N. 89°53'30" W., beginning new measurement.</p>
19.993	<p>The 1/16 sec. cor. No. 2, bet. secs. 3 and 10 (W1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the W 1/16 sec. cor. of secs. 3 and 10.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">S 3 W 1/16 <u> </u> S10</p>
	<p style="text-align: center;">2004</p>
	<p>Reset the iron post, inverted, and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
	<hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°54'30" W., beginning new measurement.
19.08	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.
19.990	The cor. of secs. 3, 4, 9 and 10.
	N. 0°07'30" E., bet. secs. 3 and 4.
	Over gently rolling land.
1.20	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.
14.009	Intersect the Idaho-Nevada State Line.
	Point for the closing cor. of secs. 3 and 4. This point falls in the lobby of the Headquarters of the Shoshone Paiute Tribes.
	POINT NOT MONUMENTED
	From this point, the original closing cor. of secs. 3 and 4 bears N. 0°07'30" E., 0.034 chs. dist., monumented with an iron post, 1 in. diam., firmly set flush in the carpeted floor of the lobby of the Headquarters of the Shoshone-Paiute Tribes, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as the amended closing cor. for secs. 3 and 4. Remove existing markings and add the marks AM 2008 to the brass cap.
	From this same point, the 107 Mile Post, hereinbefore described, bears S. 89°52'50" E., 35.253 chs. dist.
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°10'10" W., bet. secs. 32 and 33.
	Along bladed dirt road.
19.996	The 1/16 sec. cor. No. 12, bet. secs. 32 and 33 (S1/2), monumented with remains of the 1911 iron post, 20 ins. long, 1 in. diam., firmly set 6 ins. below the surface of a dirt road, with brass cap missing. This cor. will now be referred to as the S 1/16 sec. cor. of secs. 32 and 33.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the dirt road, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">S 1/16 S32 S33</p> <p style="text-align: center;">2004</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 38°54' E., 46.7 lks. dist., with brass cap mkd. RM S 1/16 S33 30.8 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 34°27' W., 48.3 lks. dist., with brass cap mkd. RM S 1/16 S32 31.9 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Bury the remains of iron post alongside the stainless steel post.</p> <hr/> <p>N. 0°07'10" W., beginning new measurement.</p> <p>19.986 The 1/4 sec. cor. of secs. 32 and 33, monumented with a bent iron post, 36 ins. long, 1 in. diam., firmly set 12 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted vertical position of the iron post as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S32 S33</p> <p style="text-align: center;">2004</p> <p>Bury the iron post alongside the stainless steel post.</p> <p>Cor. is located on the W. berm of canal, 20 lks. wide, 2 ft. deep, drains N.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°17'30" E., beginning new measurement.
19.974	<p>Point for the 1/16 sec. cor. No. 6, bet. secs. 32 and 33 (N1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the N 1/16 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16 S32 S33</p> <p>2005</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 56 lks. E. of a canal, 20 lks. wide, 2 ft. deep, drains N., and 20 lks. W. of an access road, parallels canal.</p>
39.948	<p>The cor. of secs. 28, 29, 32 and 33, monumented with a rusted iron pin of unknown origin, 6 ins. long, 1/4 in. diam., firmly set 24 ins. below the surface of a road. This iron pin correlates well with the position shown on a State of Nevada Department of Highways plat titled "Map Showing the Location of Access Road, Flight Strip and Material Bury to be Acquired from the Shoshone Piute Tribe", dated 1942 and is accepted as the best available evidence of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of the road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E S29 S28 S32 S33</p> <p>2005</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 57°14' W., 132.9 lks. dist., with brass cap mkd. RM T47N R52E S32 87.7 FT TO COR 2005 and an arrow pointing to the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing NW. and SE., for a reference monument, bears N. 42°12' W., 82.7 lks. dist., with brass cap mkd. RM T47N R52E S29 54.6 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>Bury the iron pin alongside the stainless steel post.</p> <p>From this cor., a rebar of unknown origin, 5/8 in. diam., firmly set 4 ins. below the surface of the road, bears N. 85°59' W., 21.5 lks. dist. This rebar was not utilized during the course of this survey.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°55'30" W., bet. secs. 28 and 33.</p> <p>Along asphalt-surfaced road.</p> <p>19.957 Point for the 1/16 sec. cor. No. 1, bet. secs. 28 and 33 (E1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the E 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 4 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S28} \\ \text{E } 1/16 \text{ ---} \\ \text{S33} \end{array}$ <p>2007</p> </div> <p>39.914 Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 4 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{T47N R52E} \\ \text{S28} \\ 1/4 \text{ ---} \\ \text{S33} \end{array}$ <p>2007</p> </div>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
59.871	<p>Point for the 1/16 sec. cor. No. 2, bet. secs. 28 and 33 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 4 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S28} \\ \text{W 1/16} \quad \hline \text{S33} \end{array}$ <p>2007</p> </div>
79.828	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>N. 0°04'00" W., bet. secs. 28 and 29.</p> <p>Across pasture land.</p>
20.001	<p>The 1/16 sec. cor. No. 12, bet. secs. 28 and 29 (S1/2), determined at the cor. of fences extending N., S. and E. This position correlates well with existing corners and is accepted as best available evidence of the position of the original corner. This cor. will now be referred to as the S 1/16 sec. cor. of secs. 28 and 29.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S 1/16} \\ \text{S29} \mid \text{S28} \end{array}$ <p>2005</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 7.5 lks. E. of a canal, 7.5 lks. wide, 1 ft. deep, drains N.</p>
19.962	<p>N. 0°10'40" W., beginning new measurement.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S29 S28</p> <p style="text-align: center;">2005</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 12 lks. E. of a canal, 4.5 lks. wide, 1 ft. deep, drains N.</p> <p>39.924 The 1/16 sec. cor. No. 6, bet. secs. 28 and 29 (N1/2), monumented with remains of the 1911 iron post, 12 ins. long, 1 in. diam., firmly set 10 ins. below the surface of the ground, with brass cap missing. This point will now be referred to as the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S29 S28</p> <p style="text-align: center;">2005</p> <p>Bury the remains of the iron post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°22'40" W., beginning new measurement.</p> <p>20.001 The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 2 ins. below the surface of an improved gravel road, with brass cap illegible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E S20 S21 S29 S28</p> <p style="text-align: center;">2004</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at the cor. of fences extending S. and W., for a reference monument, bears S. 48°56' W., 82.3 lks. dist., with brass cap mkd. RM T47N R52E S29 54.3 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 28°20' W., 103.6 lks. dist., with brass cap mkd. RM T47N R52E S20 68.4 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>Bury the iron post alongside the stainless steel post.</p> <p>Cor. is located in a gravel road, bears E. and W.</p>
20.050	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>S. 89°43'30" W., bet. secs. 21 and 28.</p> <p>Along asphalt-surfaced road.</p> <p>Point for the 1/16 sec. cor. No. 1, bet. secs. 21 and 28 (E1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the E 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S21} \\ \text{E 1/16 } \frac{\quad}{\text{S28}} \\ \hline 2007 \end{array}$ </div>
40.100	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate distance; the remains of the 1911 iron post was found laying loose nearby, the original position undeterminable. Remove and destroy the 1911 iron post.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T47N R52E S21 1/4 $\frac{\quad}{\quad}$ S28 2007</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 32°18' W., 58.3 lks. dist., with brass cap mkd. RM 1/4 S28 38.5 FT TO COR 2007 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 47°17' W., 56.8 lks. dist., with brass cap mkd. RM 1/4 S21 37.5 FT TO COR 2007 and an arrow pointing to the corner.</p>
60.150	<p>The 1/16 sec. cor. No. 2, bet. secs. 21 and 28 (W1/2), monumented with the remains of the 1911 iron post, 16 ins. long, 1 in. diam., firmly set 12 ins. below the surface of the road, with brass cap missing. This corner will now be referred to as the W 1/16 sec. cor. of secs. 21 and 28.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{\quad}{\quad}$ S21 S28 2004</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 32°19' W., 63.5 lks. dist., with brass cap mkd. RM W 1/16 S28 41.9 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 35°49' W., 58.6 lks. dist., with brass cap mkd. RM W 1/16 S21 38.7 FT TO COR 2004 and an arrow pointing to the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury remains of the iron post alongside the stainless steel post.</p> <hr/> <p>N. 89°06'10" W., beginning new measurement.</p>
19.854	<p>The cor. of secs. 20, 21, 28 and 29.</p> <hr/> <p>N. 0°20'10" W., bet. secs. 20 and 21.</p>
0.91	Fence, bears E. and W.
19.90	Fence, bears E. and W.
19.995	<p>Point for the 1/16 sec. cor. No. 12, bet. secs. 20 and 21 (S1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the S 1/16 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S20 S21</p> <p style="text-align: center;">2004</p>
39.990	<p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>The 1/4 sec. cor. of secs. 20 and 21, monumented with remains of the 1911 iron post, 15 ins. long, 1 in. diam., firmly set, projecting 1 in. above the ground, with the top portion of the iron post laying alongside and brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S20 S21</p> <p style="text-align: center;">2004</p> <p>Bury the top and bottom portions of the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°17'30" W., beginning new measurement.
12.90	Asphalt-surfaced road, bears NW. and SE.
19.988	Point for the 1/16 sec. cor. No. 6, bet. secs. 20 and 21 (N1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the N 1/16 sec. cor. of secs. 20 and 21. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> N 1/16 S20 S21 2006 </div> Cor. is located at the cor. of fences extending N. and E.
39.976	The cor. of secs. 16, 17, 20 and 21, monumented with a rebar of unknown origin, 18 ins. long, 1/2 in. diam., firmly set, projecting 4 ins. above the ground, at the cor. of fences extending S. and W. This rebar correlates well with existing corners and is accepted as the best available evidence of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T47N R52E S17 S16 S20 S21 2006 </div> Insert the rebar inside the stainless steel post.
	From the cor. of secs. 15, 16, 21 and 22. S. 89°17'30" W., bet. secs. 16 and 21. Along improved dirt road.
19.871	Point for the 1/16 sec. cor. No. 1, bet. secs. 16 and 21 (E1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the E 1/16 sec. cor. of secs. 16 and 21.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{E } 1/16 \quad \frac{\text{S16}}{\text{S21}} \\ 2006 \end{array}$ <p>Cor. is located on S. shoulder of a gravel road, bears E. and W.</p>
39.742	<p>The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap erroneously marked 1/16 S21 1911. Remove the marks 1/16 and add the marks T47N R52E 1/4 S16 2007 and a horizontal line to the brass cap.</p> <hr/> <p>N. 89°11'20" W., beginning new measurement.</p>
20.297	<p>Point for the 1/16 sec. cor. No. 2, bet. secs. 16 and 21 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 16 and 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{W } 1/16 \quad \frac{\text{S16}}{\text{S21}} \\ 2006 \end{array}$ <p>Cor. is located S. 47° W., 77 lks. dist., of a gravel road, curves SE. and W.</p>
40.594	<p>The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°10'50" E., bet. secs. 16 and 17.</p> <p>Along E. side of bladed gravel road.</p>
19.999	<p>Point for the 1/16 sec. cor. No. 12, bet. secs. 16 and 17 (S1/2), at proportionate distance, the 1911 iron post, 36 ins. long, 1 in. diam., with brass cap unreadable, was found laying loose nearby. This point will now be referred to as the S 1/16 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S 1/16 S17 S16</p> <p>2006</p> <p>Remove and destroy the iron post.</p>
39.998	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with brass cap mkd. as described in the field notes of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>T47N R52E 1/4 S17 S16</p> <p>2005</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°07'40" W., beginning new measurement.</p>
19.978	<p>Point for the 1/16 sec. cor. No. 6, bet. secs. 16 and 17 (N1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the N 1/16 sec. cor. of secs. 16 and 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>N 1/16 S17 S16</p> <p>2006</p> <p>Cor. is located on E. shoulder of bladed gravel road, bears N. and S.</p>
39.956	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a rebar of unknown origin, 20 ins. long, 5/8 in. diam., firmly set flush with the surface of the ground, with the 1911 iron post, 1 in. diam., laying loose nearby. This rebar correlates well with existing corners and is accepted as the best available evidence of the position of the original corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r l} \text{T47N R52E} & \\ \hline \text{S } 8 & \text{S } 9 \\ \hline \text{S17} & \text{S16} \end{array}$ <p>2006</p> </div> <p>Bury the rebar and iron post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°59'20" W., bet. secs. 9 and 16.</p> <p>Along N. side of bladed dirt road, bears E. and W.</p> <p>19.998 Point for the 1/16 sec. cor. No. 1, bet. secs. 9 and 16 (E1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the E 1/16 sec. cor. of secs. 9 and 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r l} \text{S } 9 & \\ \hline \text{E } 1/16 & \text{S16} \end{array}$ <p>2006</p> </div> <p>Cor. is located on W. shoulder of gravel road, bears N. and S.</p> <p>39.996 Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r l} \text{T47N R52E} & \\ \hline \text{S } 9 & \\ \hline \text{1/4} & \text{S16} \end{array}$ <p>2006</p> </div> <p>Cor. is located at the cor. of fences extending E., W. and N.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
46.00	Owyhee River, 2 chs. wide, course NNW.
47.80	Improved gravel road, bears NNW. and SSE.
59.98	Fence, bears N. and S.
59.994	Point for the 1/16 sec. cor. No. 2, bet. secs. 9 and 16 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 9 and 16. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{r} S \ 9 \\ W \ 1/16 \ \hline S16 \end{array}$ 2006 </div>
	Cor. is located on N. side of canal, 30 lks. wide, 5 ft. deep, drains W.
79.992	The cor. of secs. 8, 9, 16 and 17. <hr/>
	N. 0°08'10" W., bet. secs. 8 and 9. Along E. side of bladed gravel road.
19.978	Point for the 1/16 sec. cor. No. 12, bet. secs. 8 and 9 (S1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the S 1/16 sec. cor. of secs. 8 and 9. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{r} S \ 1/16 \\ S \ 8 S \ 9 \end{array}$ 2006 </div>
39.956	The 1/4 sec. cor. of secs. 8 and 9, monumented with a PK nail of unknown origin, at the intersection of an asphalt-surfaced road extending E. and W. and a bladed gravel road extending S. This PK nail correlates well with existing corners and is accepted as the best available evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 4 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S 8 S 9 2006</p> <p>Bury the PK nail alongside the copper coated steel stake.</p> <hr/> <p>N. 0°00'50" W., beginning new measurement.</p> <p>Enter cultivated fields.</p>
20.024	<p>The 1/16 sec. cor. No. 6, bet. secs. 8 and 9 (N1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of T. 47 N., R. 52 E., executed under Instructions dated April, 27, 1911. This cor. will now be referred to as the N 1/16 sec. cor. of secs. 8 and 9.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 8 S 9 2005</p> <p>Bury the iron post alongside the stainless steel post.</p> <p>Cor. is located at the intersection of fences extending N., S., E. and W.</p> <hr/> <p>N. 0°02'20" W., beginning new measurement.</p>
20.016	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of a dirt driveway, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="889 279 1036 378"> <p>T47N R52E S 5 S 4 S 8 S 9</p> </div> <div data-bbox="932 407 997 432">2006</div> <hr/> <div data-bbox="456 499 1057 525">From the cor. of secs. 3, 4, 9 and 10.</div> <div data-bbox="456 558 1027 583">N. 89°30'10" W., bet. secs. 4 and 9.</div> <div data-bbox="456 617 773 642">Across rolling land.</div> <div data-bbox="311 678 1479 974"> <p>19.983 The 1/16 sec. cor. No. 1, bet. secs. 4 and 9 (E1/2), perpetuated with a rebar of unknown origin, 20 ins. long, 1 in. diam., firmly set, projecting 5 ins. above the ground, with the remains of the 1911 iron post, 4 ins. long, 1 in. diam., wired to the rebar, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This rebar is accepted as a careful and faithful perpetuation of the position of the original corner. This cor. will now be referred to as the E 1/16 sec. cor. of secs. 4 and 9.</p> </div> <div data-bbox="456 1010 761 1035">At the corner point</div> <div data-bbox="456 1068 1479 1157">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div data-bbox="829 1190 992 1262"> <p>E 1/16 $\frac{S\ 4}{S\ 9}$</p> </div> <div data-bbox="932 1291 997 1316">2006</div> <div data-bbox="456 1352 1479 1377">Bury the rebar and iron post alongside the stainless steel post.</div> <div data-bbox="456 1411 1333 1436">Cor. is located 1.5 lks. S. of a fence, bears E. and W.</div> <hr/> <div data-bbox="456 1505 1141 1530">S. 89°47'30" W., beginning new measurement.</div> <div data-bbox="456 1564 837 1589">Enter cultivated fields.</div> <div data-bbox="311 1625 1479 1833"> <p>19.882 The 1/4 sec. cor. of secs. 4 and 9, determined at the cor. of fences extending N., E. and W., with an iron post, 36 ins. long, 1 in. diam., with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, wired to the fence corner. This is accepted as the best available evidence of the position of the original corner.</p> </div>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{T47N R52E} \\ \text{S } 4 \\ 1/4 \frac{\quad}{\text{S } 9} \end{array}$ <p>2006</p> <p>Bury the iron post alongside the stainless steel post.</p> <hr/> <p>S. 89°57'00" W., beginning new measurement.</p>
20.012	<p>Point for the 1/16 sec. cor. No. 2, bet. secs. 4 and 9 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{S } 4 \\ \text{W } 1/16 \frac{\quad}{\text{S } 9} \end{array}$ <p>2006</p>
20.50	Owyhee River, 1 ch. wide, course NNW.
40.024	The cor. of secs. 4, 5, 8 and 9.
	<hr/> <p>N. 0°14'00" W., bet. secs. 4 and 5.</p>
14.103	<p>Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. of secs. 4 and 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{S } 5 \mid \text{S } 4 \\ \text{C } \text{C} \\ \text{T47N R52E} \end{array}$ <p>2006</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this cor., the original closing cor. of secs. 4 and 5 bears N. 0°14'00" W., 0.007 chs. dist., monumented with an iron post, 1 in. diam., firmly set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as the amended closing cor. of secs. 4 and 5. Add the marks AM 2006 to the brass cap and drive the 1911 iron post 4 ins. below the surface of the ground.</p> <p>From this same cor., the 108 Mile Post, hereinbefore described, bears S. 89°53'10" E., 34.307 chs. dist.</p> <p>Cor. is located on S. side of hay field, on N. berm of irrigation ditch, 8 lks. wide, drains W.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°00'50" W., bet. secs. 31 and 32.</p> <p>Over rolling land; generally along fence.</p> <p>20.009 Point for the S 1/16 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S31 S32 2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N. and E.</p> <p>40.018 The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T47N R52E 1/4 S31 S32</p> <p style="text-align: center;">2004</p> <p>Bury the iron post alongside the stainless steel post.</p> <p>Cor. is located in a fence, bears N. and S.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0°08'00" W., beginning new measurement.</p> <p>2.00 Canal, 50 lks. wide, 5 ft. deep, drains W.</p> <p>19.947 Point for the N 1/16 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S31 S32</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>39.894 The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 18 ins. below the surface of an improved gravel road, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, with an iron rod of unknown origin, 12 ins. long, 2 ins. square, set atop the iron post.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the gravel road, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E S30 S29 S31 S32</p> <p style="text-align: center;">2004</p> <p>from which</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at the cor. of fences extending N. and E., for a reference monument, bears N. 25°19' E., 77.9 lks. dist., with brass cap mkd. RM T47N R52E S29 51.4 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at the cor. of fences extending N. and W., for a reference monument, bears N. 23°16' W., 68.0 lks. dist., with brass cap mkd. RM T47N R52E S30 44.9 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Insert the iron rod inside the stainless steel post and deposit iron post alongside.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°52'50" W., bet. secs. 29 and 32.</p> <p>Along improved gravel road.</p> <p>20.107 Point for the E 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of a gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16 $\frac{S29}{S32}$</p> <p>2005</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 25°26' E., 65.4 lks. dist., with brass cap mkd. RM E 1/16 S29 43.2 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 29°26' E., 65.9 lks. dist., with brass cap mkd. RM E 1/16 S32 43.5 FT TO COR 2005 and an arrow pointing to the corner.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.214	<p>The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 2 ins. below the surface of a gravel road, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <p>S29</p> <p>1/4 $\frac{\quad}{\quad}$</p> <p>S32</p> <p>2004</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 35°19' W., 74.2 lks. dist., with brass cap mkd. RM 1/4 S32 49.0 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing NE. and SW., for a reference monument, bears N. 44°17' W., 129.1 lks. dist., with brass cap mkd. RM 1/4 S29 85.2 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Bury the iron post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°57'00" W., beginning new measurement.</p>
20.002	<p>Point for the W 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of a gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S29</p> <p>W 1/16 $\frac{\quad}{\quad}$</p> <p>S32</p> <p>2004</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	from which
	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 37°37' E., 73.8 lks. dist., with brass cap mkd. RM W 1/16 S29 48.7 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 43°28' E., 82.9 lks. dist., with brass cap mkd. RM W 1/16 S32 54.7 FT TO COR 2004 and an arrow pointing to the corner.</p>
40.004	The cor. of secs. 29, 30, 31 and 32.
	<hr/> <p>N. 89°48'10" W., bet. secs. 30 and 31.</p> <p>Along improved gravel road.</p>
20.010	Point for the E 1/16 sec. cor. of secs. 30 and 31.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of a gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>S30</p> <p>E 1/16 $\frac{\quad}{\quad}$</p> <p>S31</p> <p>2004</p> </div>
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 41°44' W., 79.7 lks. dist., with brass cap mkd. RM E 1/16 S31 52.6 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 31°13' W., 70.9 lks. dist., with brass cap mkd. RM E 1/16 S30 46.8 FT TO COR 2004 and an arrow pointing to the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Leave gravel road; enter gently rolling land.
40.020	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above the ground, at the cor. of fences extending S. and E., with brass cap mkd. as described in the field notes of the survey of T 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Add the marks T47N R52E 2004 to the brass cap.</p> <hr/> <p>S. 89°57'30" W., beginning new measurement.</p>
19.926	<p>Point for the W 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S30} \\ \text{W } 1/16 \text{ } \hline \text{S31} \end{array}$ <p>2004</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
39.474	<p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°10'20" W., bet. secs. 29 and 30.</p> <p>Along improved gravel road.</p>
20.017	<p>Point for the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S } 1/16 \\ \text{S30} \text{S29} \end{array}$ <p>2004</p> </div> <p>from which</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears S. 43°36' E., 42.1 lks. dist., with brass cap mkd. RM S 1/16 S29 27.8 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears S. 41°07' W., 39.1 lks. dist., with brass cap mkd. RM S 1/16 S30 25.8 FT TO COR 2004 and an arrow pointing to the corner.</p>
40.034	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, firmly set 12 ins. below the surface of a gravel road, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <p>1/4</p> <p>S30 S29</p> <p>2004</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at the cor. of fences extending S. and E., for a reference monument, bears S. 58°34' E., 70.2 lks. dist., with brass cap mkd. RM 1/4 S29 46.3 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears S. 31°44' W., 55.3 lks. dist., with brass cap mkd. RM 1/4 S30 36.5 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Bury the iron post alongside the stainless steel post.</p> <p>Cor. is located at intersection of gravel roads, on curve S. and E.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°07'30" W., beginning new measurement.
	Enter gently rolling land.
19.989	Point for the N 1/16 sec. cor. of secs. 29 and 30.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, over a plastic-encased magnet, with brass
	cap mkd.
	<div style="text-align: center;"> N 1/16 S30 S29 </div>
	<div style="text-align: center;">2004</div>
	Set a steel sign post, 6 ft. long, alongside the stainless steel
	post.
39.978	The cor. of secs. 19, 20, 29 and 30, monumented with an iron
	post, 36 ins. long, 1 in. diam., firmly set, projecting 15 ins.
	above the ground, with brass cap mkd. as described in the field
	notes of the survey of T. 47 N., R. 52 E., executed under
	Instructions dated April 27, 1911.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, over a plastic-encased magnet, with brass
	cap mkd.
	<div style="text-align: center;"> T47N R52E S19 S20 S30 S29 </div>
	<div style="text-align: center;">2004</div>
	Reset the iron post, inverted, alongside the stainless steel
	post.
	<hr/>
	From the cor. of secs. 20, 21, 28 and 29.
	N. 89°53'50" W., bet. secs. 20 and 29.
	Across pasture and cultivated fields.
20.142	The 1/16 sec. cor. No. 1, bet. secs. 20 and 29 (E1/2),
	monumented with an iron post, 36 ins. long, 1 in. diam., firmly
	set, projecting 9 ins. above the ground, with brass cap mkd.
	as described in the field notes of the survey of T. 47 N.,
	R. 52 E., executed under Instructions dated April 27, 1911.
	This cor. will now be referred to as the E 1/16 sec. cor. of
	secs. 20 and 29.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: right;"> $\begin{array}{r} S20 \\ E\ 1/16 \quad \hline S29 \end{array}$ </div> <p style="text-align: right;">2004</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 1.5 lks. N. of the cor. of fences extending S., E. and W.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 89°49'30" W., beginning new measurement.</p>
20.004	<p>The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 36 ins. long, 1 in. diam., loosely set and bent, projecting 18 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: right;"> $\begin{array}{r} T47N\ R52E \\ S20 \\ 1/4 \quad \hline S29 \end{array}$ </div> <p style="text-align: right;">2004</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 89°50'30" W., beginning new measurement.</p>
19.991	<p>Point for the 1/16 sec. cor. No. 2, bet. secs. 20 and 29 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the W 1/16 sec. cor. of secs. 20 and 29.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S20} \\ \text{W } 1/16 \text{ } \hline \text{S29} \end{array}$ <p>2004</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Leave pasture and cultivated fields; thence across gently rolling land.</p> <p>39.982 The cor. of secs. 19, 20, 29 and 30.</p> <hr/> <p>N. 89°57'10" W., bet. secs. 19 and 30.</p> <p>Across gently rolling land.</p> <p>19.980 Point for the E 1/16 sec. cor. of secs. 19 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S19} \\ \text{E } 1/16 \text{ } \hline \text{S30} \end{array}$ <p>2004</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 30 lks. N. of the cor. of fences extending E., W. and S.</p> <p>39.960 The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Add the marks T47N R52E and 2005 to the brass cap and set a steel sign post, 6 ft. long, alongside the iron post.</p> <p>Cor. is located 30 lks. N. of fence, bears E. and W.</p> <hr/>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°58'20" W., beginning new measurement.
19.956	Point for the W 1/16 sec. cor. of secs. 19 and 30. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">W 1/16 $\frac{S19}{S30}$ 2004</div> Set a steel sign post, 6 ft. long, alongside the stainless steel post. Cor. is located 29 lks. N. of a fence, bears E. and W.
31.50	Center of airport runway, bears N. and S.
39.29	Fence, bears N. and S.
39.334	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., hereinbefore described.
	<hr/> From the cor. of secs. 19, 20, 29 and 30. N. 0°06'00" W., bet. secs. 19 and 20. Across rolling land.
20.008	The 1/16 sec. cor. No. 12, bet. secs. 19 and 20 (S1/2), monumented with a rebar of unknown origin, 18 ins. long, 1/2 in. diam., firmly set 2 ins. below the surface of the ground. This rebar correlates well with existing corners and is accepted as the best available evidence of the original corner. This cor. will now be referred to as the S 1/16 sec. cor. of secs. 19 and 20. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">S 1/16 S19 S20 2004</div> Bury the rebar and set a steel sign post, 6 ft. long, alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Cor. is located 30 lks. W. of a fence, bears N. and S.</p> <p>From this point, a rebar of unknown origin, 3/4 in. diam., firmly set, projecting 12 ins. above the ground, bears S. 28°03' E., 0.014 chs. dist. This rebar could not reconciled with proper procedures and was not utilized during the course of this survey.</p> <hr/> <p>N. 0°06'00" W., beginning new measurement.</p>
20.008	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 36 ins. long, 1 in. diam., the top 18 ins. bent parallel to the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S19 S20 2004</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 0°01'10" W., beginning new measurement.</p> <p>Entering slough, covered in thick willows.</p>
19.987	<p>True point for the 1/16 sec. cor. No. 6, bet. secs. 19 and 20 (N1/2), at proportionate distance; there is no remaining evidence of the original corner. This point falls in flooded slough area with beaver ponds, where it is impractical to establish a permanent monument. This point will now be referred to as the N 1/16 sec. cor. of secs. 19 and 20.</p> <p>From the true point, a point selected for the witness N 1/16 sec. cor. of secs. 19 and 20 bears S. 89°54'00" E., 1.636 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="885 279 1019 415" data-label="Diagram"> </div> <p data-bbox="930 445 993 472">2004</p> <p data-bbox="456 506 1446 590">Witness cor. is located in a fence, bears S. 64° E. and N. 64° W., 9.5 lks. NW. of the cor. of fences extending E. and N. 64° W.</p> <p data-bbox="313 625 407 653">39.974</p> <p data-bbox="456 625 1446 835">The cor. of secs. 17, 18, 19 and 20, monumented with remains of the 1911 iron post, 20 ins. long, 1 in. diam., firmly set flush with the surface of the ground, at the cor. of fences extending N., S., E. and W., with the brass cap broken off and laying alongside, mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p data-bbox="456 867 760 894">At the corner point</p> <p data-bbox="456 926 1479 1010">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="894 1045 1036 1150" data-label="Diagram"> </div> <p data-bbox="930 1176 993 1203">2004</p> <p data-bbox="456 1234 1463 1297">Bury the remains of the iron post alongside the stainless steel post.</p> <hr/> <p data-bbox="456 1356 1122 1383">From the cor. of secs. 16, 17, 20, and 21.</p> <p data-bbox="456 1415 1057 1442">N. 89°47'20" W., bet. secs. 17 and 20.</p> <p data-bbox="456 1474 854 1501">Over gently rolling land.</p> <p data-bbox="313 1537 407 1564">19.940</p> <p data-bbox="456 1537 1479 1652">Point for the 1/16 sec. cor. No. 1, bet. secs. 17 and 20 (E1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the E 1/16 sec. cor. of secs. 17 and 20.</p> <p data-bbox="456 1684 1479 1768">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: right;"> S17 E 1/16 $\frac{\quad}{\quad}$ S20 2006 </div> <p>From this point, a rebar of unknown origin, 1/2 in. diam., firmly set 2 ins. below the surface of the ground, bears N. 69°26' E., 0.093 chs. dist. This rebar could not reconciled with proper procedures and was not utilized during the course of this survey.</p> <p>25.00 Asphalt-surfaced road, bears NW. and SE.</p> <p>39.880 The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 2 ins. below the surface of dirt road, with brass cap mkd. as described in the field noted of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. below the surface of the dirt road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: right;"> T47N R52E S17 1/4 $\frac{\quad}{\quad}$ S20 2004 </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 64°47' E., 43.0 lks. dist., with brass cap mkd. RM 1/4 S20 28.4 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears S. 30°11' W., 58.6 lks. dist., with brass cap mkd. RM 1/4 S20 38.7 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Bury the iron post alongside the stainless steel post.</p> <p>Cor. is located at the intersection of dirt roads extending S., E. and W.</p> <hr style="width: 20%; margin-left: auto; margin-right: 0;"/>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°49'40" W., beginning new measurement.
19.958	<p>The 1/16 sec. cor. No. 2, bet. secs. 17 and 20 (W1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, with brass cap broken off and laying loose alongside and unreadable. This cor. will now be referred as the W 1/16 sec. cor. of secs. 17 and 20.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{W } 1/16 \quad \frac{\text{S17}}{\text{S20}} \\ 2004 \end{array}$ </div> <p>Bury the iron post and brass cap alongside the stainless steel post.</p> <p>Cor. is located in a fence, bears E. and W.</p> <hr/> <p>N. 89°55'10" W., beginning new measurement.</p> <p>Enter cultivated fields.</p>
19.918	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>S. 89°59'10" W., bet. secs. 18 and 19.</p> <p>Across hay fields.</p>
20.016	<p>Point for the 1/16 sec. cor. No. 1, bet. secs. 18 and 19 (E1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the E 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{E } 1/16 \quad \frac{\text{S18}}{\text{S19}} \\ 2004 \end{array}$ </div> <p>Cor. is located in a fence, bears E. and W.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.03	Cor. of fences extending N., S. and E.
40.032	<p>The 1/4 sec. cor. of secs. 18 and 19., monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 2 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <p>S18</p> <p>1/4 <u> </u></p> <p>S19</p> <p>2004</p> </div> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located in a fence, bears N. and S.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 89°57'40" W., beginning new measurement.</p>
19.984	<p>The 1/16 sec. cor. No. 2, bet. secs. 18 and 19 (W1/2), monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred as the W 1/16 sec. cor. of secs. 18 and 19. Add the marks W and 2008 to the brass cap.</p> <p>Cor. is located at the corner of corral fences extending N. and W.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 89°52'10" W., beginning new measurement.</p>
18.71	Fence, bears N. and S.
19.236	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°08'50" W., bet. secs. 17 and 18.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Across cultivated field.
19.988	<p>The 1/16 sec. cor. No. 12, bet. secs. 17 and 18 (S1/2), monumented with the remains of the 1911 iron post, 26 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with the top portion of the iron post and the brass cap laying alongside the iron post mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the S 1/16 sec. cor. of secs. 17 and 18.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S18 S17</p> <p style="text-align: center;">2004</p> <p>Bury the top and bottom remains of the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located in a fence, bears N. and S.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 0°04'30" W., beginning new measurement.</p>
0.03	<p>Cor. of fences extending N., S. and W.</p> <p>Enter gently rolling land.</p>
19.36	Fence, bears E. and W.
19.940	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, firmly set 8 ins. below the surface of an improved gravel road, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S18 S17</p> <p style="text-align: center;">2004</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 31°46' E., 65.9 lks. dist., with brass cap mkd. RM 1/4 S17 43.5 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at the cor. of fences extending S., E. and W., for a reference monument, bears S. 36°31' W., 75.6 lks. dist., with brass cap mkd. RM 1/4 S18 49.9 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Bury iron post alongside the stainless steel post at corner point.</p> <p>Cor. is located in an improved gravel road, bears E. and W.</p> <hr/> <p>N. 0°04'20" W., beginning new measurement.</p> <p>20.046 The 1/16 sec. cor. No. 6, bet. secs. 17 and 18 (N1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the N 1/16 sec. cor. of secs. 17 and 18.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16 S18 S17</p> <p>2004</p> </div> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., E. and W.</p> <hr/> <p>N. 0°14'20" W., beginning new measurement.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS					
19.906	<p>The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <table border="1" style="margin: auto;"> <tr> <td>S 7</td><td>S 8</td></tr> <tr> <td>S18</td><td>S17</td></tr> </table> <p>2004</p> </div> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>S. 89°59'20" W., bet. secs. 8 and 17.</p> <p>Across pasture land.</p>	S 7	S 8	S18	S17
S 7	S 8				
S18	S17				
19.978	<p>The 1/16 sec. cor. No. 1, bet. secs. 8 and 17 (E1/2), monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as the E 1/16 sec. cor. of secs. 8 and 17. Add the marks E and 2008 to the brass cap.</p> <p>Cor. is located at the cor. of fences extending N., S. and E.</p> <hr/> <p>N. 89°48'40" W., beginning new measurement.</p>				
19.987	<p>The 1/4 sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <table border="1" style="margin: auto;"> <tr> <td>S 8</td><td></td></tr> <tr> <td>1/4</td><td>S17</td></tr> </table> <p>2006</p> </div>	S 8		1/4	S17
S 8					
1/4	S17				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Cor. is located on E. side of irrigation ditch, 5 lks. wide, 2 ft. deep, drains N.</p> <p>Enter rolling land.</p>
39.974	<p>The 1/16 sec. cor. No. 2, bet. secs. 8 and 17 (W1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the W 1/16 sec. cor. of secs. 8 and 17.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} S\ 8 \\ W\ 1/16\ \hline S17 \end{array}$ <p>2005</p> </div> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., S., E. and W.</p> <hr/> <p>N. 89°54'20" W., beginning new measurement.</p>
17.10	Asphalt-surfaced road, bears NW. and SE.
20.009	<p>The cor. of secs. 7, 8, 17 and 18.</p> <hr/> <p>N. 89°50'50" W., bet. secs. 7 and 18.</p> <p>Across abandoned field.</p>
0.13	From this point, the cor. of fences extending S. and NW., bears S., 57 lks. dist.
0.33	Cor. of fences extending SE. and W.
19.973	<p>The 1/16 sec. cor. No. 1, bet. secs. 7 and 18 (E1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the E 1/16 sec. cor. of secs. 7 and 18.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{S } 7 \\ \text{E } 1/16 \quad \hline \text{S18} \end{array}$ <p>2004</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the intersection of fences extending N., E. and W.</p> <hr/> <p>N. 89°55'50" W., beginning new measurement.</p>
20.001	<p>The 1/4 sec. cor. of secs. 7 and 18, reestablished by Donald J. Watts, Idaho Professional Engineer and Land Surveyor No. 1923, monumented with a rebar, 30 ins. long, 5/8 in. diam., firmly set flush with the surface of the ground, with plastic cap, 1 in. diam., mkd. AB PELS 1923, as shown on the unrecorded Ron Howard Survey - Tract 1113 plat, Duck Valley Reservation. This position is harmoniously related to surrounding corners and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} \text{T47N R52E} \\ \text{S } 7 \\ 1/4 \quad \hline \text{S18} \end{array}$ <p>2004</p> <p>Bury the rebar alongside the stainless steel post.</p> <hr/> <p>N. 89°55'50" W., beginning new measurement,</p>
20.001	<p>Point for the 1/16 sec. cor. No. 2, bet. secs. 7 and 18, at proportionate distance; the bottom portion the 1911 iron post, 10 ins. long, 1 in. diam., was found laying loose nearby, the position undeterminable. This point will now be referred to as the W 1/16 sec. cor. of secs. 7 and 18.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{r} S\ 7 \\ W\ 1/16\ \hline S18 \end{array}$ </p> <p style="text-align: center;">2004</p> <p>Bury remaining portion of the iron post alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending S., E. and W.</p> <p>39.122 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°01'30" W., bet. secs. 7 and 8.</p> <p>20.047 The 1/16 sec. cor. No. 12, bet. secs. 7 and 8 (S1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 6 ins. below the asphalt surface, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred as the S 1/16 sec. cor. of secs. 7 and 8.</p> <p>At the corner point</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 4 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;"> $\begin{array}{r} S\ 1/16 \\ S\ 7\ S\ 8 \end{array}$ </p> <p style="text-align: center;">2006</p> <p>Bury the iron post alongside the cooper coated steel stake.</p> <p>Cor. is located in asphalt-surfaced road, bears N. and S.</p> <hr/> <p>N. 0°10'10" W., beginning new measurement.</p> <p>Along asphalt-surfaced road.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.040	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with a rebar of unknown origin, 30 ins. long, 1/2 in. diam., firmly set 3 ins. below the surface, at the intersection of asphalt-surfaced roads extending S., E. and W. and a dirt bladed road extending N. This rebar has been locally recognized and utilized by local surveyors and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 4 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">T47N R52E 1/4 S 7 S 8 2006</p> <p>Bury rebar alongside the copper coated steel stake.</p> <hr/> <p>N. 0°07'10" W., beginning new measurement.</p> <p>Along bladed dirt road.</p>
19.954	<p>Point for the 1/16 sec. cor. No. 6, bet. secs. 7 and 8 (N1/2), at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred as the N 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of a dirt road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 7 S 8 2005</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 38°25' E., 40.8 lks. dist., with brass cap mkd. RM N 1/16 S8 26.9 FT TO COR 2005 and an arrow pointing to the corner.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 42°45' W., 42.3 lks. dist., with brass cap mkd. RM N 1/16 S7 27.9 FT TO COR 2005 and an arrow pointing to the corner.</p>				
39.908	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of the road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <table border="1" style="margin: auto;"> <tr> <td>S 6</td><td>S 5</td></tr> <tr> <td>S 7</td><td>S 8</td></tr> </table> <p>2005</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 42°13' E., 45.0 lks. dist., with brass cap mkd. RM T47N R52E S5 29.7 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 53°15' W., 41.7 lks. dist., with brass cap mkd. RM T47N R52E S6 27.5 FT TO COR 2005 and an arrow pointing to the corner.</p>	S 6	S 5	S 7	S 8
S 6	S 5				
S 7	S 8				
20.012	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>N. 89°56'30" W., bet. secs. 5 and 8.</p> <p>The 1/16 sec. cor. No. 1, bet. secs. 5 and 8 (E1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the E 1/16 sec. cor. of secs. 5 and 8.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p>				

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	$\begin{array}{r} S\ 5 \\ E\ 1/16 \quad \hline S\ 8 \end{array}$ <p>2005</p> <p>Bury iron post alongside the stainless steel post.</p> <p>Cor. is located in a fence, bears N. and S.</p> <hr/> <p>N. 89°52'00" W., beginning new measurement.</p>
19.96	Fence, bears N.
19.990	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} T47N\ R52E \\ S\ 5 \\ 1/4 \quad \hline S\ 8 \end{array}$ <p>2005</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
39.400	<p>Point selected for the witness W 1/16 sec. cor. of secs. 5 and 8, occupied by a rebar of unknown origin, 26 ins. long, 1 in. diam., firmly set flush with the surface of the ground.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} W\ C \\ S\ 5 \\ W\ 1/16 \quad \longleftarrow \hline S\ 8 \end{array}$ <p>2005</p> <p>Cor. is located at the cor. of fences extending N., S. and E.</p>
39.980	<p>True point for the 1/16 sec. cor. No. 2, bet. secs. 5 and 8 (W1/2), at proportionate distance; there is no remaining evidence of the original corner. This point falls in a canal, 75 lks. wide, 15 ft. deep, drains N., where it is impractical to set a permanent monument. This point will now be referred to as the W 1/16 sec. cor. of secs. 5 and 8.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
59.67	Fence, bears N. and S.
59.970	The cor. of secs. 5, 6, 7 and 8.
	<hr/>
	S. 89°54'20" W., bet. secs. 6 and 7.
0.34	Fence, bears N. and S.
19.990	The 1/16 sec. cor. No. 1, bet. secs. 6 and 7 (E1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 2 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, with an iron rod, 24 ins. long, 1 in. diam., set alongside. This cor. will now be referred to as the E 1/16 sec. cor. of secs. 6 and 7.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{r} \text{S } 6 \\ \text{E } 1/16 \quad \hline \text{S } 7 \end{array}$
	2005
	Bury the iron post and iron rod alongside the stainless steel post.
	Cor. is located at the cor. of fences extending N., S. and W.
	<hr/>
	N. 89°49'40" W., beginning new measurement.
20.001	The 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 18 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{r} \text{T47N R52E} \\ \text{S } 6 \\ 1/4 \quad \hline \text{S } 7 \end{array}$
	2005

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending E., W. and S.</p> <hr/> <p>N. 89°55'40" W., beginning new measurement.</p> <p>20.037 The 1/16 sec. cor. No. 2, bet. secs. 6 and 7 (W1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the W 1/16 sec. cor. of secs. 6 and 7.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S } 6 \\ \text{W } 1/16 \quad \frac{\quad}{\quad} \\ \text{S } 7 \end{array}$ <p>2005</p> </div> <p>Bury the iron post alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., S., E. and W.</p> <hr/> <p>N. 89°51'20" W., beginning new measurement.</p> <p>15.95 Asphalt-surfaced road, bears NW. and SE.</p> <p>18.954 The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°03'40" W., bet. secs. 5 and 6.</p> <p>13.852 Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the road, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

S 6 | S 5
C C
T47N R52E

2005

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., 9 lks. W. of the cor. of fences extending S. and E., for a reference monument, bears S. 63°50' E., 48.3 lks. dist., with brass cap mkd. RM T47N R52E S5 31.9 FT TO COR 2005 and an arrow pointing to the corner.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., 60 lks. S. of the cor. of fences extending S. and W., for a reference monument, bears S. 29°34' W., 59.8 lks. dist., with brass cap mkd. RM T47N R52E S6 39.5 FT TO COR 2005 and an arrow pointing to the corner.

From this cor., the original closing cor. of secs. 5 and 6 bears N. 0°03'40" W., 0.075 chs. dist., monumented with an iron post, 1 in. diam., firmly set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as an amended closing cor. of secs. 5 and 6. Add the marks AM 2005 to the brass cap and drive the 1911 iron post 12 ins. below the surface of the ground.

From this same cor., the 109 Mile Post bears S. 89°41'10" E., 33.388 chs. dist., hereinbefore described.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 2,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
U.S. Surveyor F.E. Joy in 1911

From the 1/4 sec. cor. of secs. 2 and 11.

N. 0°02'00" E., on the N. and S. center line of sec. 2.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 2,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
13.979	<p>The original closing 1/4 sec. cor. of sec. 2, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 18 ins. in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as the amended closing 1/4 cor. of sec. 2. Add the marks AM 2006 to the brass cap and bury in place.</p>
13.985	<p>Intersect the Idaho-Nevada State Line.</p> <p>The point for the closing cor. on the N. and S. center line of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base, with brass cap mkd.</p> $\begin{array}{c} C \\ \hline C \quad C \quad S \quad 2 \\ C \end{array}$ <p style="text-align: center;">2008</p> <p>From this point, the 106 Mile Post bears N. 89°55'00" W., 3.766 chs. dist.</p> <hr/> <p>The point for the E 1/16 sec. cor. of sec. 2, is at midpoint in departure bet. the closing cor. on the N. and S. center line of sec. 2 and the closing cor. of secs. 1 and 2, on the N. bdy. of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> $\begin{array}{c} \hline E \quad 1/16 \quad S \quad 2 \\ 2006 \end{array}$ <p>From this point, the closing cor. of secs. 1 and 2, bears S. 89°55'00" E., 20.139 chs. dist., hereinbefore described.</p> <hr/> <p>From the W 1/16 sec. cor. of 2 and 11.</p> <p>N. 0°01'40" E., on the N. and S. center line of the W1/2 of sec. 2.</p>
13.972	<p>Intersect the Idaho-Nevada State Line.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 2,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Point for the closing 1/16 sec. cor. No. 2, on the N. bdy. of sec. 2 (W1/2), at proportionate distance. This point will now function as the closing cor. on the N. and S. center line of the W1/2 of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> $\begin{array}{c} W \\ \hline C \quad C \quad \quad S \quad 2 \\ \hline W \end{array}$ <p style="text-align: center;">2006</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, S. of cor.</p> <p>From this point, the 106 Mile Post bears S. 89°50'50" E., 16.291 chs. dist.</p> <p>From this same point, the 1911 iron post, 36 ins. long, 1 in. diam., bent and laying loose, bears N. 30°48' E., 0.900 chs. dist., with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This monument has been disturbed and is not accepted as the position of the original corner. Remove and destroy the 1911 iron post.</p>
	<p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 3, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 3 and 10.</p> <p>N. 0°17'10" W., on the N. and S. center line of the E1/2 of sec. 3.</p> <p>13.939 The original closing 1/16 sec. cor. No. 1, sec. 3 (E1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as the amended closing 1/16 sec. cor. No. 1 of sec. 3. Add the marks AM 2006 to the brass cap and reset the iron post, inverted, in place.</p> <p>13.949 Intersect the Idaho-Nevada State Line.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 3,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Point for the closing cor. on the N. and S. center line of the E1/2 of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} E \\ \hline C \ C \ S \ 3 \\ E \end{array}$ </div> <p style="text-align: center;">2006</p> <p>From this point, the 107 Mile Post bears N. 89°50'50" W., 24.611 chs. dist.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 0°01'40" E., on the N. and S. center line of sec. 3.</p> <p>13.966 The original closing 1/4 sec. cor. of sec. 3, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, with a steel fence post, 5 ft. long, set alongside. This cor. will now function as the amended closing 1/4 sec. cor. of sec. 3. Add the marks AM 2006 to the brass cap and bury in place.</p> <p>13.993 Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. on the N. and S. center line of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ \hline C \ C \ S \ 3 \\ C \end{array}$ </div> <p style="text-align: center;">2006</p> <p>From this point, the 107 Mile Post bears N. 89°50'50" W., 4.705 chs. dist.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 3 and 10.</p> <p>N. 0°06'30" E., on the N. and S. center line of the W1/2 of sec. 3.</p>
--------	---

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 3,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
13.984	<p>The original closing 1/16 sec. cor. No. 2, sec. 3 (W1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as the amended closing 1/16 No. 2 sec. cor. of sec. 3. Add the marks AM 2006 to the brass cap and bury in place.</p>
13.999	<p>Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. on the N. and S. center line of the W1/2 of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} W \\ \hline C \ C \ S \ 3 \\ W \end{array}$ <p>2006</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>From this point, the 107 Mile Post bears S. 89°52'50" E., 15.268 chs. dist.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 4, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>N. 0°00'20" E., on the N. and S. center line of the E1/2 of sec. 4.</p>
0.015	Fence, bears E. and W.
13.875	<p>Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. on the N. and S. center line of the E1/2 of sec. 4, point falls in a private yard, under aspen trees.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 4,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a copper coated stake, 20 ins. long, 9/16 in. diam., flush with the surface of the ground, with a brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> $\begin{array}{c} E \\ \hline C \ C \ S \ 4 \\ \hline E \end{array}$ <p>2007</p> </div> <p>From this point, the original closing 1/16 sec. cor. No. 1, sec. 4 (E1/2), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 27 ins. above the ground, bears N. 0°00'20" E., 0.020 chs. dist., with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as the amended closing 1/16 sec. cor. No. 1 of sec. 4. Remove and destroy the 1911 iron post.</p> <p>From this same point, the 108 Mile Post bears N. 89°52'50" W., 25.656 chs. dist.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0°17'00" W., on the N. and S. center line of sec. 4.</p> <p>13.939 The original closing 1/4 sec. cor. of sec. 4, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 9 ins. above the ground, with the top 8 ins. bent over, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner. This cor. will now function as the amended closing 1/4 sec. cor. of sec. 4. Add the marks AM 2006 to the brass cap and bury in place.</p> <p>13.989 Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. on the N. and S. center line of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ \hline C \ C \ S \ 4 \\ \hline C \end{array}$ <p>2007</p> </div>
--------	---

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 4,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, the 108 Mile Post bears N. $89^{\circ}52'50''$ W., 5.702 chs. dist.</p> <hr/> <p>From the W $1/16$ sec. cor. of secs. 4 and 9.</p> <p>N. $0^{\circ}20'10''$ W., on the N. and S. center line of the W$1/2$ of sec. 4.</p> <p>14.046 Intersect the Idaho-Nevada State Line.</p> <p>The closing $1/16$ sec. cor. No. 2, on the N. bdy. of sec. 4 (W$1/2$), monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the closing cor. on the N. and S. center line of the W$1/2$ of sec. 4.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 $1/2$ ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} W \\ \hline C \ C \ S \ 4 \\ W \end{array}$ <p>2007</p> </div> <p>Add the marks AM 2007 to the 1911 brass cap and bury iron post alongside the stainless steel post.</p> <p>From this cor., the 108 Mile Post bears S. $89^{\circ}53'10''$ E., 14.322 chs. dist.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 5, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the E $1/16$ sec. cor. of secs. 5 and 8.</p> <p>N. $0^{\circ}02'00''$ E., on the N. and S. center line of the E$1/2$ of sec. 5.</p>
--------	--

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 5,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
14.122	<p>Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. on the N. and S. center line of the E1/2 of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} E \\ \hline C \ C \ S \ 5 \\ E \end{array}$ <p style="text-align: center;">2007</p> <p>From this point, the original closing 1/16 sec. cor. No. 1, sec. 5 (E1/2), bears N. 0°02'00" E., 0.047 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above the ground, in a fence bearing E. and W., with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as the amended closing 1/16 sec. cor. No. 1 of sec. 5. Add the marks AM 2007 and bury the iron post 4 ins. below the ground.</p> <p>From this same point, the 109 Mile Post bears N. 89°53'10" W., 26.604 chs. dist.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 0°04'20" W., on the N. and S. center line of sec. 5.</p>
0.42	<p>Fence, bears E. and W., 3 lks. W. of the cor. of fences extending E., W. and S. and 12 lks. E. of the cor. of fences extending N. and E.</p>
14.116	<p>Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. of sec. 5, on the N. and S. center line of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{r} C \\ \hline C \ C \ S \ 5 \\ C \end{array}$ <p style="text-align: center;">2006</p>

<p>CHAINS</p>	<div data-bbox="456 275 1463 541"> <p>From this point, the original closing 1/4 sec. cor. of sec. 5 bears N. 0°04'20" W., 0.042 chs. dist., monumented with an iron post, 1 in. diam., firmly set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as the amended closing 1/4 sec. cor. of sec. 5. Add the marks AM 2006 to the brass cap and drive the iron post 4 ins. below the surface of the ground.</p> </div> <div data-bbox="456 575 1440 634"> <p>From this same point, the 109 Mile Post bears N. 89°53'10" W., 6.588 chs. dist.</p> </div> <hr/> <div data-bbox="456 697 1138 722"> <p>From the W 1/16 sec. cor. of secs. 5 and 8.</p> </div> <div data-bbox="456 758 1396 812"> <p>N. 0°03'50" W., on the N. and S. center line of the W1/2 of sec. 5.</p> </div> <div data-bbox="311 848 1058 873"> <p>14.009 Intersect the Idaho-Nevada State Line.</p> </div> <div data-bbox="456 909 1446 963"> <p>Point for the closing cor. on the N. and S. center line of the W1/2 of sec. 5, at proportionate distance.</p> </div> <div data-bbox="456 997 1479 1085"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="904 1092 1021 1180"> $\begin{array}{c} W \\ \hline C \quad C S \quad 5 \\ W \end{array}$ </div> <div data-bbox="930 1218 995 1243"> <p>2008</p> </div> <div data-bbox="456 1278 1188 1302"> <p>Cor. falls on E. bank of canal bears S. and W.</p> </div> <div data-bbox="456 1337 1463 1575"> <p>From this point, the original iron post for the closing 1/16 sec. cor. No. 2, on the N. bdy. of sec. 5 (W1/2), 36 ins. long, 1 in. diam., bears N. 89°31'10" E., 0.627 chs. dist., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This monument has been displaced by canal construction, remove and destroy the iron post.</p> </div> <div data-bbox="456 1608 1440 1665"> <p>From this same point, the 109 Mile Post bears N. 89°41'10" E., 13.400 chs. dist.</p> </div> <hr/>
---------------	--

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 6,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/>
13.776	<p>From the E 1/16 sec. cor. of secs. 6 and 7.</p> <p>N. 0°03'50" W., on the N. and S. center line of the E1/2 of sec. 6.</p> <p>Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. on the N. and S. center line of the E1/2 of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} E \\ \hline C \quad C S \quad 6 \\ E \end{array}$ <p>2007</p> </div> <p>Cor. is located in fence, bears N. and S.</p> <p>From this point, the original closing 1/16 sec. cor. No. 1, sec. 6 (E1/2) bears N. 0°03'50" W., 0.090 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as the amended closing 1/16 sec. cor. No. 1 of sec. 6 (E1/2). Add the marks AM 2006 to the brass cap and drive the iron post 4 ins. below the surface of the ground.</p> <p>From this same point, the 110 Mile Post bears S. 89°41'10" W., 27.576 chs. dist.</p>
13.606	<p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N. 0°00'10" E., on the N. and S. center line of sec. 6.</p> <p>Intersect the Idaho-Nevada State Line.</p> <p>Point for the closing cor. on the N. and S. center line of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 6,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="893 273 1023 367" data-label="Equation-Block"> $\begin{array}{r} C \\ \hline C \ C \ S \ 6 \\ C \end{array}$ </div> <div data-bbox="925 399 990 430" data-label="Text"> <p style="text-align: center;">2007</p> </div> <div data-bbox="446 462 1461 735" data-label="Text"> <p>From this point, the original closing 1/4 sec. cor., sec. 6, bears N. 0°00'10" E., 0.018 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as the amended closing 1/4 sec. cor. on the N. and S. center line of sec. 6. Add the marks AM 2005 to the brass cap and drive the iron post 4 ins. below the surface of the ground.</p> </div> <div data-bbox="446 756 1445 829" data-label="Text"> <p>From this same point, the 110 Mile Post bears S. 89°41'10" W., 7.597 chs. dist.</p> </div> <hr/> <div data-bbox="446 882 1136 913" data-label="Text"> <p>From the W 1/16 sec. cor. of secs. 6 and 7.</p> </div> <div data-bbox="446 934 1396 1008" data-label="Text"> <p>N. 0°08'40" W., on the N. and S. center line of the W1/2 of sec. 6.</p> </div> <div data-bbox="300 1029 1055 1060" data-label="Text"> <p>13.504 Intersect the Idaho-Nevada State Line.</p> </div> <div data-bbox="446 1092 1477 1281" data-label="Text"> <p>The closing 1/16 sec. cor. No. 2, on the N. bdy. of sec. 6 (W1/2), monumented with remains of the bottom portion the 1911 iron post, 10 ins. long, 1 in. diam., firmly set 12 ins. below the surface of the ground. This cor. will now be referred to as the closing cor. on the N. and S. center line of the W1/2 of sec. 6.</p> </div> <div data-bbox="446 1302 763 1333" data-label="Text"> <p>At the corner point</p> </div> <div data-bbox="446 1354 1477 1459" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="893 1480 1023 1585" data-label="Equation-Block"> $\begin{array}{r} W \\ \hline C \ C \ S \ 6 \\ W \end{array}$ </div> <div data-bbox="925 1606 998 1648" data-label="Text"> <p style="text-align: center;">2006</p> </div> <div data-bbox="446 1669 1461 1743" data-label="Text"> <p>Bury the remains of the iron post alongside the stainless steel post.</p> </div> <div data-bbox="446 1764 1347 1837" data-label="Text"> <p>From this cor., the 110 Mile Post bears N. 89°50'30" E., 12.475 chs. dist.</p> </div>
--------	---

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 7,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/>
	<p>From the S 1/16 sec. cor. of secs. 7 and 8.</p> <p>N. 89°38'20" W., on the 1/16 section line through the S1/2 of sec. 7.</p>
0.29	Cor. of fences extending N., S. and W.
0.605	<p>A witness corner established by Donald J. Watts, Idaho Professional Engineer and Land Surveyor No. 1923, as shown on the unrecorded Christopher & Shelly Harney Survey Homesite plat, Duck Valley Reservation, monumented with a rebar, 1/2 in. diam., firmly set in a fence bearing E. and W., with plastic cap mkd. PELS 1923.</p>
20.002	<p>The 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 7, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the SE 1/16 sec. cor. of sec. 7. Add the marks SE and 2005 to the brass cap and set a steel sign post, 6 ft. long, alongside.</p> <p>Cor. is located at the cor. of fences extending S., E. and W.</p> <hr/> <p>S. 89°41'20" W., beginning new measurement.</p>
20.013	<p>The 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 7, monumented with and iron post, 36 ins. long, 1 in. diam., firmly set, projecting 8 ins. above the ground, bent slightly to the E., with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner. This cor. will now be referred to as the C-S 1/16 sec. cor. of sec. 7.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>S 1/16 S 7</p> <p>C</p> <p>2005</p> </div>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 7,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N. and E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°54'50" W., beginning new measurement.</p>
19.972	<p>The 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 7, monumented with a rebar of unknown origin, 18 ins. long, 5/8 in. diam., firmly set, projecting 2 ins. above the ground. This rebar is accepted as the best available evidence of the position of the original corner. This cor. will now be referred to as the SW 1/16 sec. cor. of sec. 7.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 7</p> <p style="text-align: center;">2006</p> <p>Insert the rebar inside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., S., and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°56'00" W., beginning new measurement.</p>
19.108	<p>The S 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 7 and 8.</p> <p>N. 89°56'10" W., on the E. and W. center line of sec. 7.</p> <p>Along asphalt-surfaced road.</p>
20.001	<p>Point for the 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 7, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-E 1/16 sec. cor. of sec. 7.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 7,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 7 \end{array}$ </div>
	<div style="text-align: center;">2007</div>
40.002	<p>The center 1/4 of sec. cor. of sec. 7, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 24 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{T47N R52E} \\ \text{C } 1/4 \text{ S } 7 \end{array}$ </div> <div style="text-align: center;">2005</div> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 41°47' E., 76.7 lks. dist., with brass cap mkd. RM C 1/4 S7 50.6 FT TO COR 2005 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at the cor. of fences extending S. and W., for a reference monument, bears S. 39°40' W., 72.6 lks. dist., with brass cap mkd. RM C 1/4 S7 47.9 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>Bury the iron post alongside the stainless steel post.</p> <hr style="width: 20%; margin-left: 0;"/> <p>S. 89°58'10" W., beginning new measurement.</p>
20.021	<p>Point for the 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 7, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-W 1/16 sec. cor. of sec. 7.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 7,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 7 \end{array}$ <p>2005</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>From this point, a rebar of unknown origin, 5/8 in. diam., firmly set 2 ins. below the surface of the ground, bears N. 89°59' E., 0.105 chs. dist. This rebar cannot be reconciled with proper procedures, is not harmoniously related to surrounding accepted corners and is not utilized during the course of this survey.</p> <p>39.041 The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 7 and 8.</p> <p>N. 89°59'20" W., on the 1/16 section line through the N1/2 of sec. 7.</p> <p>20.025 Point for the 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 7, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NE 1/16 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\text{NE } 1/16 \text{ S } 7$ <p>2005</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located in a fence, bears N. and S., 7.5 lks. N. of the cor. of fences extending N. and W. and 4.5 lks. S. of the cor. of fences extending N. and E.</p> <p>40.035 Cor. of fences extending N., E. and W.</p>
--------	--

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 7,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.050	<p>The 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 7, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-N 1/16 sec. cor. of sec. 7.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \mid S\ 7 \\ C \end{array}$ <p>2005</p> </div> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°55'20" W., beginning new measurement.</p>
19.00	Asphalt-surfaced road, bears NW. and SE.
20.000	<p>Point for the 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 7, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NW 1/16 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $NW\ 1/16\ S\ 7$ <p>2005</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>From this point, a rebar of unknown origin, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, at the cor. of fences extending S., W. and NW., bears N. 77°01' E., 0.328 chs. dist. This rebar cannot be reconciled with proper procedures, is not harmoniously related to surrounding accepted corners and is not utilized during the course of this survey.</p>
38.960	<p>The N 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 50%; margin: 10px auto;"/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 8,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/>
	<p>From the S 1/16 sec. cor. of secs. 8 and 9.</p> <p>S. 89°59'40" W., on the 1/16 section line through the S1/2 of sec. 8.</p> <p>19.975 The 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 8, monumented with an iron post, firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the SE 1/16 sec. cor. of sec. 8.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 8</p> <p style="text-align: center;">2006</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., S., E. and W.</p> <hr/> <p>N. 89°53'40" W., beginning new measurement.</p>
19.923	<p>The 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 8, monumented with remains of the 1911 iron post, 15 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with the brass cap laying alongside, unreadable. This cor. will now be referred to as the C-S 1/16 sec. cor. of sec. 8.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> C S 1/16 S 8 C </p> <p style="text-align: center;">2006</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 8,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Bury the remains of the iron post and brass cap and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending E., W. and N.</p> <hr/> <p>N. 89°43'30" W., beginning new measurement.</p>
20.040	<p>The 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 8, determined at the cor. of fences extending N. and E. This position correlates well with existing corners and is accepted as the best available evidence of the position of the original corner. The remains of the 1911 iron post, 24 ins. long, 1 in. diam., was found laying loose nearby, the original position undeterminable. This cor. will now be referred to as the SW 1/16 sec. cor. of sec. 8.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 8</p> <p style="text-align: center;">2006</p> <p>Bury the remains of the iron post alongside the stainless steel post.</p> <hr/> <p>N. 89°43'00" W., beginning new measurement.</p>
19.73	Cor. of fences extending N., S. and E.
19.980	The S 1/16 sec. cor. of secs. 7 and 8.
	<hr/> <p>From the 1/4 sec. cor. of secs. 8 and 9.</p> <p>N. 89°47'30" W., on the E. and W. center line of sec. 8.</p> <p>Along asphalt-surfaced road.</p>
19.982	<p>Point for the 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 8, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-E 1/16 sec. cor. of sec. 8.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p>


DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 8,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 8 \end{array}$ <p style="text-align: center;">2007</p>
39.964	<p>Point for the center 1/4 sec. cor. of sec. 8, at proportionate distance; there is no remaining evidence of the original corner. Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> $\begin{array}{c} \text{T47N R52E} \\ \text{C } 1/4 \text{ S } 8 \end{array}$ <p style="text-align: center;">2007</p>
59.676	<p>Record position for the witness cor. to the 1/16 sec. cor. No. 8, bet. the NW and SW quarters; there is no remaining evidence of the original corner. The witness cor. serves no further function.</p>
59.946	<p>Point for the 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 8, at proportionate distance. This point will now be referred to as the C-W 1/16 sec. cor. of sec. 8.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 8 \end{array}$ <p style="text-align: center;">2007</p>
79.928	<p>The 1/4 sec. cor. of secs. 7 and 8.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 8 and 9.</p> <p>N. 89°51'50" W., on the 1/16 section line through the N1/2 of sec. 8.</p>
19.971	<p>The 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 8, monumented with the remains of the 1911 iron post, 12 ins. long, 1 in. diam., firmly set 6 ins. below the surface of the ground, with the top portion of the iron post laying alongside, the brass cap unreadable. This cor. will now be referred to as the NE 1/16 sec. cor. of sec. 8.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 8,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 8</p> <p style="text-align: center;">2005</p> <p>Bury the top and bottom portions of the iron post alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., S., E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°50'00" W., beginning new measurement.</p>
19.996	<p>Point for the 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 8, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-N 1/16 sec. cor. of sec. 8.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of a road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16\ \ S\ 8 \\ C \end{array}$ </p> <p style="text-align: center;">2005</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 54°09' E., 57.1 lks. dist., with brass cap mkd. RM CN 1/16 S8 37.7 FT TO COR 2005 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 41°42' W., 36.4 lks. dist., with brass cap mkd. RM CN 1/16 S8 24.0 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>Cor. is located in an access road, bears N. and S.</p>
39.386	<p>Point selected for the witness NW 1/16 sec. cor. of sec. 8.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 8,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C</p> <p>NW 1/16 S 8</p>  <p>2005</p> </div> <p>Cor. is located in a fence, bears N. and S., 4 lks. N. of the cor. of fences extending N., S., E. and W.</p> <p>39.992 True point for the 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 8, at proportionate distance; there is no remaining evidence of the original corner. This point falls in a major canal, 100 lks. wide, 15 ft. deep, drains N., where it is impractical to establish a permanent monument. This point will now be referred to as the NW 1/16 sec. cor. of sec. 8.</p> <p>59.988 The N 1/16 sec. cor. of secs. 7 and 8.</p> <hr/> <p style="text-align: center;">THE DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 9, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 9 and 10.</p> <p>S. 89°59'50" W., on the 1/16 section line through the S1/2 of sec. 9.</p> <p>19.985 Point for the 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 9, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SE 1/16 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>SE 1/16 S 9</p> <p>2006</p> </div> <p>Cor. is located 6 lks. E. of fence, bears N. and S.</p>
--------	---

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 9,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.970	<p>Point for the 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 9, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-S 1/16 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \mid S\ 9 \\ C \end{array}$ <p>2006</p> </div> <p>from which a local monument</p> <p>A brass tablet, 3 1/2 ins. diam., firmly set flush in a concrete head wall of an irrigation ditch, drains N., bears N. 54°09' W., 22.4 lks. dist., with brass cap mkd. US INDIAN IRRIGATION SERVICE BENCHMARK ELEV.</p> <p>from which a new accessory</p> <p>A brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, concreted flush in a drill hole on the head wall of an irrigation ditch, drains N., for a reference monument, bears S. 69°44' W., 19.4 lks. dist., with brass cap mkd. RM CS 1/16 S9 12.8 FT TO COR 2006 and an arrow pointing to the corner.</p>
50.00	Owyhee River, 2 chs. wide, course NW.
52.50	Improved gravel road, bears NW. and SE.
59.661	<p>Point selected for the witness SW 1/16 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} W\ C \\ \leftarrow SW\ 1/16\ S\ 9 \end{array}$ <p>2006</p> </div> <p>Cor. is located in a canal road, bears NW. and SE.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 9,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
59.955	True point for the 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 9, at proportionate distance; there is no remaining evidence of the original corner. Point falls in a major canal, 30 lks. wide, 10 ft. deep, drains NW., where it is impractical to establish a permanent monument. This point will now be referred to as the SW 1/16 sec. cor. of sec. 9.
79.940	<p>The S 1/16 sec. cor. of secs. 8 and 9.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>S. 89°58'50" W., on the E. and W. center line of sec. 9.</p> <p>Along asphalt-surfaced road.</p>
19.971	<p>Point for the 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 9, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-E 1/16 sec. cor. of sec. 9.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p>
	<div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 9 \end{array}$ <p>2007</p> </div>
39.942	<p>Point for the center 1/4 sec. cor. of sec. 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p>
	<div style="text-align: center;"> <p>T47N R52E</p> <p>C 1/4 S 9</p> <p>2007</p> </div>
55.10	Bridge over Owyhee River, 2 chs. wide, course NW.
59.913	Point for the 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 9, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-W 1/16 sec. cor. of sec. 9.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 9,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> $\begin{array}{c} W \ 1/16 \\ C \text{-----} C \\ S \ 9 \end{array}$ <p>2007</p> </div> <p>79.884 The 1/4 sec. cor. of secs. 8 and 9.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 9 and 10.</p> <p>S. 89°56'30" W., on the 1/16 section line through the N1/2 of sec. 9.</p> <p>19.709 The witness cor. to the 1/16 sec. cor. No. 5, monumented with an iron post, 1 in. diam., firmly set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now function as an angle point. Remove the WC and add the marks AP 2006 to the brass cap.</p> <p>Cor. is located at the cor. of fences extending S. and E.</p> <hr/> <p>S. 89°53'50" W., beginning new measurement.</p> <p>0.300 Point for the 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 9, at proportionate distance. This point will now be referred to as the NE 1/16 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>NE 1/16 S 9</p> <p>2006</p> </div> <p>20.250 Point for the 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 9, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-N 1/16 sec. cor. of sec. 9.</p>
--------	--

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 9,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 9 C</p> <p style="text-align: center;">2006</p>
38.10	Owyhee River, 2 chs. wide, course NW.
40.200	<p>The 1/16 sec. cor. No. 3, in the center of the NW 1/4 of sec. 9, monumented with an iron post, firmly set 2 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the NW 1/16 sec. cor. of sec. 9.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 9</p> <p style="text-align: center;">2006</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel poet.</p> <hr/> <p>N. 89°59'30" W., beginning new measurement.</p>
19.942	<p>The N 1/16 sec. cor. of secs. 8 and 9.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 10, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 10 and 11.</p> <p>N. 89°48'30" W., on the 1/16 section line through the S1/2 of sec. 10.</p>
0.04	Fence, bears N. and W.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 10,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.045	<p>The 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 10, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911, witnessed with a steel fence post, 5 ft. long, E. of cor. This cor. will now be referred to as the SE 1/16 sec. cor. of sec. 10.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 10</p> <p style="text-align: center;">2005</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°53'30" W., beginning new measurement.</p>
20.004	<p>The 1/16 sec. cor. of No. 10, bet. the SE and SW quarters of sec. 10, monumented with an iron post, 36 ins. diam., 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-S 1/16 sec. cor. of sec. 10.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> C S 1/16 S10 C </p> <p style="text-align: center;">2005</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°58'10" W., beginning new measurement.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 10,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
7.00	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.
20.036	<p>The 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 10, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the SW 1/16 sec. cor. of sec. 10.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S10</p> <p style="text-align: center;">2005</p> <p>Bury the iron post alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending S., E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°46'30" W., beginning new measurement.</p>
19.66	Fence, bears N. and S.
19.956	<p>The S 1/16 sec. cor. of secs. 9 and 10.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>N. 89°51'30" W., on the E. and W. center line of sec. 10.</p> <p>Along asphalt-surfaced road.</p>
20.015	<p>Point for the 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 10, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-E 1/16 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S10</p> <p style="text-align: center;">2007</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 10,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.030	<p>Point for the center 1/4 sec. cor. of sec. 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">T47N R52E C 1/4 S10</p> <p style="text-align: center;">2007</p>
57.80	<p>Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.</p>
60.045	<p>Point for the 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 10, at proportionate distance; there is no remaining evidence of the original corner. This cor. will now be referred to as the C-W 1/16 sec. cor. of sec. 10.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">W 1/16 C ——— C S10</p> <p style="text-align: center;">2007</p>
80.060	<p>The 1/4 sec. cor. of secs. 9 and 10.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>N. 89°48'00" W., on the 1/16 section line through the N1/2 of sec. 10.</p>
0.45	<p>Canal, 9 lks. wide, course N.</p>
19.968	<p>The 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 10, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the NE 1/16 sec. cor. of sec. 10.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 10,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S10</p> <p style="text-align: center;">2005</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 89°47'30" W., beginning new measurement.</p>
19.984	<p>The 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 10, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-N 1/16 sec. cor. of sec. 10.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S10 C</p> <p style="text-align: center;">2005</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 86°27'20" W., beginning new measurement.</p>
20.126	<p>The 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 10, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the NW 1/16 sec. cor. of sec. 10. Remove the mark 3 and add the marks NW 2007 to the brass cap.</p> <hr/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 10,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 86°51'00" W., beginning new measurement.
8.90	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.
20.009	The N 1/16 sec. cor. of secs. 9 and 10.
<p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 11, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/>	
	From the 1/4 sec. cor. of secs. 11 and 14.
	N. 0°01'30" W., on the N. and S. center line of sec. 11.
20.011	The 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 11, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-S 1/16 sec. cor. of sec. 11. Add the marks S 2008 and a vertical line, with the letter C stamped at each end of the line, to the brass cap.
	Set a steel sign post, 6 ft. long, alongside the iron post.
	N. 0°14'40" W., beginning new measurement.
20.065	The center 1/4 sec. cor. of sec. 11, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, 2 1/2 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Add the marks T47N R52E 2008 to the brass cap.
	Set a steel sign post, 6 ft. long, alongside the iron post.
	N. 0°20'20" W., beginning new measurement.
19.943	The 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 11, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-N 1/16 sec. cor. of sec. 11. Add the marks C 2008 and a vertical line, with the letter C stamped at each end of the line, to the brass cap.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 11,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a steel sign post, 6 ft. long, alongside the iron post.
	<hr/>
	N. 0°13'30" W., beginning new measurement.
19.934	The 1/4 sec. cor. of secs. 2 and 11.
	<hr/>
	From the 1/4 sec. cor. of secs. 11 and 12.
	N. 89°53'20" W., on the E. and W. center line of sec. 11.
20.087	Point for the C-E 1/16 sec. cor. of sec. 11.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid bedrock, over a plastic-encased magnet, in a mound of stone, 4 ft. base, with brass cap mkd.
	<div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S11} \end{array}$ </div>
	2007
40.174	The center 1/4 sec. cor. of sec. 11.
	<hr/>
	S. 89°58'50" W., beginning new measurement.
20.069	The 1/16 sec. cor. No. 8, bet. the SW and NW quarters of sec. 11, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 10 ins. above the ground, slightly bent, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911 with a steel fence post, 3 ft. long, set alongside. This cor. will now be referred to as the C-W 1/16 sec. cor. of sec. 11.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, with brass cap mkd.
	<div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S11} \end{array}$ </div>
	2006
	Bury the iron post and steel fence post and set a steel sign post, 6 ft. long, alongside the stainless steel post.
	<hr/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 11,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°57'50" W., beginning new measurement.
20.110	<p>The 1/4 sec. cor. of secs. 10 and 11</p> <hr/> <p>From the C-S 1/16 sec. cor. of sec. 11.</p> <p>N. 89°53'30" W., on the E. and W. center line of the SW1/4 of sec. 11.</p>
20.095	<p>Point for the 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 11, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SW 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S11</p> <p style="text-align: center;">2006</p>
40.190	<p>The S 1/16 sec. cor. of secs. 10 and 11.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 11.</p> <p>N. 89°54'50" W., on the E. and W. center line of the NW1/4 of sec. 11.</p>
20.064	<p>Point for the 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 11, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NW 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S11</p> <p style="text-align: center;">2006</p>
40.128	<p>The N 1/16 sec. cor. of secs. 10 and 11.</p> <hr/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 14,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/>
<p>19.995</p>	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0°06'30" W., on the N. and S. center line of sec. 14.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>S 1/16 S14</p> <p>C</p> <p>2006</p> </div>
<p>39.990</p>	<p>The center 1/4 sec. cor. of sec. 14, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, 4 ft. base, 3 ft. high, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <hr/> <p>N. 0°09'40" W., beginning new measurement.</p>
<p>20.004</p>	<p>Point for the C-N 1/16 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base, with brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>N 1/16 S14</p> <p>C</p> <p>2007</p> </div>
<p>40.008</p>	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>N. 89°54'00" W., on the E. and W. center line of sec. 14.</p> <p>20.014 Point for the C-E 1/16 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 14,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;">E 1/16 C———C S14</div>
	<div style="text-align: center;">2006</div>
40.028	<p>The center 1/4 sec. cor. of sec. 14.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>N. 89°53'20" W., beginning new measurement.</p>
20.043	<p>Point for the C-W 1/16 sec. cor. of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, with brass cap mkd.</p> <div style="text-align: center;">W 1/16 C———C S14</div> <div style="text-align: center;">2008</div>
40.086	<p>The 1/4 sec. cor. of secs. 14 and 15.</p> <hr/>
<p>DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 15, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/>	
	<p>From the S 1/16 sec. cor. of secs. 14 and 15.</p> <p>N. 89°55'50" W., on the 1/16 section line through the S1/2 of sec. 15.</p>
4.15	<p>Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.</p>
20.027	<p>Point for the 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 15, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SE 1/16 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 15,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	SE 1/16 S15
	2006
	Cor. is located 1.5 lks. E. of fence, bears N. and S.
40.054	<p>The 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 15, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-S 1/16 sec. cor. of sec. 15. Add the marks CS 2006 and a vertical line, with the letter C stamped at each end of the line, to the brass cap.</p> <p>Set a steel sign post, 6 ft. long, alongside the iron post.</p> <p>Cor. is located at the cor. of fences extending E., W. and S.</p> <hr/> <p>N. 89°47'50" W., beginning new measurement.</p>
19.90	Cor. of fences extending N., S., E. and W.
20.067	<p>Point for the 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 15, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SW 1/16 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	SW 1/16 S15
	2006
	Cor. is located in a fence, bears E. and W.
40.134	<p>The S 1/16 sec. cor. of secs. 15 and 16.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>S. 89°50'50" W., on the E. and W. center line of sec. 15.</p>
14.80	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.; thence along a gravel road.
20.059	<p>Point for the 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 15, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-E 1/16 sec. cor. of sec. 15.</p>



DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 15,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S15} \end{array}$ <p>2006</p> </div> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 51°55' E., 62.4 lks. dist., with brass cap mkd. RM CE 1/16 S15 41.2 FT TO COR 2006 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 41°07' W., 29.6 lks. dist., with brass cap mkd. RM CE 1/16 S15 19.5 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>40.118 The center 1/4 sec. cor. of sec. 15, monumented with an iron pipe of unknown origin, 15 ins. long, 1 in. diam., firmly set 6 ins. below the surface of the ground, on S. shoulder of the gravel road. This iron pipe is accepted as careful and faithful determination of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E C 1/4 S15</p> <p>2006</p> </div> <p>Bury the iron pipe alongside the stainless steel post.</p> <p>Cor. is located on the S. edge of a dirt road, bears E. and W., S. 9° W., 53 lks. of the cor. of fences extending E., W. and N., and N. 18° W., 31 lks. dist. of the cor. of fences extending E., W. and S.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 89°32'30" W., beginning new measurement.</p>
--------	---


DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 15,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.006	<p>Point for the 1/16 sec. cor. No. 8, bet. NW and SW quarters of sec. 15, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-W 1/16 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of a gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{---} \text{C} \\ \text{S15} \end{array}$ <p>2006</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 42°03' E., 58.3 lks. dist., with brass cap mkd. RM CW 1/16 S15 38.5 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 26°04' W., 47.0 lks. dist., with brass cap mkd. RM CW 1/16 S15 31.0 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>Cor. is located in a dirt road, bears E. and W., S. 20° E., 55 lks. of the cor. of fences extending E., W. and N., and N. 39 1/4° W., 57 lks. of the cor. of fences extending E., W. and S.</p>
40.012	<p>The 1/4 sec. cor. of secs. 15 and 16.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 14 and 15.</p> <p>S. 89°59'00" W., on the 1/16 section line through the N1/2 of sec. 15.</p>
20.021	<p>The 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 15, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the NE 1/16 sec. cor. of sec. 15.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 15,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S15</p> <p style="text-align: center;">2004</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°51'30" W., beginning new measurement.</p> <p>5.60 Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.</p> <p>20.020 True point for the 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 15, at proportionate distance; there is no remaining evidence of the original corner. Point falls in a canal, 75 lks. wide, 5 ft. deep, drains W., where it is impractical to establish a permanent monument. This point will now be referred to as the C-N 1/16 sec. cor. of sec. 15.</p> <p>From the true point, the point selected for the witness C-N 1/16 sec. cor. of sec. 15 bears S. 0°12' E., 0.266 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;">  </div> <p style="text-align: center;">2006</p> <p>Cor. is located 1 lk. E. of fence, bears N. and S.</p> <p>39.887 Point selected for the witness NW 1/16 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;">  </div> <p style="text-align: center;">2006</p>
--------	---

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 15,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Cor. is located 9 lks. N. of a fence, bears E. and W.
40.040	True point for the 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 15, at proportionate distance; there is no remaining evidence of the original corner. Point falls in canal, 75 lks. wide, 4 ft. deep, bears S., E., and W., drains W., where it is impractical to establish a permanent monument. This point will now be referred to as the NW 1/16 sec. cor. of sec. 15.
60.060	The N 1/16 sec. cor. of secs. 15 and 16.
<p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 16, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 15 and 16.</p> <p>N. 89°58'10" W., on the 1/16 section line through the S1/2 of sec. 16.</p>	
10.10	Owyhee River, 2 chs. wide, course NW.
12.30	Improved gravel road, parallels Owyhee River.
19.717	Point selected for the witness SE 1/16 sec. cor. of sec. 16.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<p>WC</p> <p>SE 1/16 S16</p>  <p>2006</p>
19.977	True point for the 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 16, at proportionate distance; there is no remaining evidence of the original corner. Point falls in canal, 90 lks. wide, drains N., where it is impractical to establish a permanent monument. This point will now be referred to as the SE 1/16 sec. cor. of sec. 16.
39.65	Canal, drains NE.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 16,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.954	<p>The 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 16, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 12 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-S 1/16 sec. cor. of sec. 16.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> C S 1/16 S16 C </div> <p style="text-align: center;">2005</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°56'50" W., beginning new measurement.</p>
0.50	Fence, bears NW. and SE.
20.061	<p>Point for the 1/16 sec. cor. No. 9, in the center of the SW 1/4 of sec. 16, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SW 1/16 sec. cor. of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> SW 1/16 S16 2006 </div>
40.122	<p>The S 1/16 sec. cor. of secs. 16 and 17.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 15 and 16.</p> <p>N. 89°56'30" W., on the E. and W. center line of sec. 16.</p>
19.998	<p>Point for the 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 16, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-E 1/16 sec. cor. of sec. 16.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 16,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of a dirt road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} E\ 1/16 \\ \hline C \quad S16 \quad C \end{array}$ <p>2006</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, 3 ft. SW. from a railroad tie, 6 ft. long, 8x8 ins. squared, for a reference monument, bears N. 69°15' E., 64.5 lks. dist., with brass cap mkd. RM CE 1/16 S16 42.6 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at end of fence extending E., for a reference monument, bears S. 31°21' E., 63.2 lks. dist., with brass cap mkd. RM CE 1/16 S16 41.7 FT TO COR 2006 and an arrow pointing to the corner.</p> <p>Cor. is located at the intersection of dirt roads extending N., S. and W.</p> <p>27.20 Owyhee River, 2 chs. wide, course NW.</p> <p>29.45 Improved gravel road, bears NW. and SE.</p> <p>39.25 Canal, 75 lks. wide, drains NNW.</p> <p>39.996 The center 1/4 sec. cor. of sec. 16, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 2 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E C 1/4 S16</p> <p>2005</p> </div>
--------	---

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 16,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p data-bbox="456 275 1365 331">Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr data-bbox="703 352 1230 359"/> <p data-bbox="456 394 1143 422">N. 89°59'30" W., beginning new measurement.</p> <p data-bbox="313 457 1419 663">19.967 The 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 16, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-W 1/16 sec. cor. of sec. 16.</p> <p data-bbox="456 699 764 726">At the corner point</p> <p data-bbox="456 758 1479 842">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="899 877 1032 947" style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{---} \text{C} \\ \text{S } 16 \end{array}$ </div> <p data-bbox="932 982 1000 1010" style="text-align: center;">2005</p> <p data-bbox="456 1041 1365 1098">Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p data-bbox="456 1129 1430 1157">Cor. is located at the cor. of fences extending N., S. and E.</p> <hr data-bbox="703 1178 1230 1184"/> <p data-bbox="456 1220 1143 1247">N. 89°57'20" W., beginning new measurement.</p> <p data-bbox="313 1283 1049 1310">20.013 The 1/4 sec. cor. of secs. 16 and 17.</p> <hr data-bbox="456 1331 1479 1337"/> <p data-bbox="456 1373 1175 1400">From the N 1/16 sec. cor. of secs. 15 and 16.</p> <p data-bbox="456 1432 1435 1493">N. 89°58'50" W., on the 1/16 section line through the N1/2 of sec. 16.</p> <p data-bbox="313 1524 1451 1640">20.038 Point for the 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 16, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NE 1/16 sec. cor. of sec. 16.</p> <p data-bbox="456 1671 1468 1761">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of a dirt road, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="878 1797 1057 1824" style="text-align: center;">NE 1/16 S16</div> <p data-bbox="932 1856 1000 1883" style="text-align: center;">2006</p>
--------	--

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 16,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>from which a local monument</p> <p>A brass tablet, 3 1/2 ins. diam., firmly set flush in a concrete head wall of an irrigation ditch, bears N. 54°01' W., 23.1 lks. dist., with brass cap mkd. US INDIAN IRRIGATION SERVICE BENCHMARK ELEV.</p> <p>from which a new accessory</p> <p>A brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, concreted flush in a drill hole on concrete head wall of an irrigation ditch, for a reference monument, bears S. 41°46' W., 30.8 lks. dist., with brass cap mkd. RM NE 1/16 S16 20.3 FT TO COR 2006 and an arrow pointing to the corner.</p>
40.076	<p>True point for the 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 16, at proportionate distance; there is no remaining evidence of the original corner. Point falls in the Owyhee River, 2 chs. wide, course NNW., where it is impractical to establish a permanent monument. This point will now be referred to as the C-N 1/16 sec. cor. of sec. 16.</p>
40.744	<p>Point selected for the witness C-N 1/16 sec. cor. of sec. 16.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="857 1150 1052 1312" data-label="Diagram"> </div> <p style="text-align: center;">2006</p>
42.50	<p>Improved gravel road, bears NW. and SE.</p>
60.114	<p>The 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 16, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the NW 1/16 sec. cor. of sec. 16.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 16,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="873 275 1052 300" style="text-align: center;">NW 1/16 S16</div> <div data-bbox="932 333 997 359" style="text-align: center;">2005</div> <div data-bbox="456 394 1362 453">Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</div> <div data-bbox="456 487 1109 512">Cor. is located in fence, bears E. and W.</div> <hr style="width: 30%; margin: 10px auto;"/> <div data-bbox="456 577 1141 602">N. 89°57'00" W., beginning new measurement.</div> <div data-bbox="329 636 1125 661">0.075 Cor. of fences extending N., S., E. and W.</div> <div data-bbox="313 695 1092 720">19.872 The N 1/16 sec. cor. of secs. 16 and 17.</div> <hr style="width: 80%; margin: 20px auto;"/> <div data-bbox="578 789 1362 873" style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 17, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</div> <hr style="width: 80%; margin: 10px auto;"/> <div data-bbox="643 938 1299 995" style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</div> <hr style="width: 30%; margin: 10px auto;"/> <div data-bbox="456 1060 1174 1085">From the S 1/16 sec. cor. of secs. 16 and 17.</div> <div data-bbox="456 1119 1430 1178">N. 89°56'50" W., on the 1/16 section line through the S1/2 of sec. 17.</div> <div data-bbox="313 1211 1482 1478"> 19.906 The 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 17, at the cor. of fences extending N., S. and E., with an iron post, 36 ins. long, 1 in. diam., wired to the W. side of wood post, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911 and is accepted as the best available evidence of the position of original corner. This cor. will now be referred to as the SE1/16 sec. cor. of sec. 17. At the corner point </div> <div data-bbox="456 1512 1482 1598">Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</div> <div data-bbox="878 1631 1055 1656" style="text-align: center;">SE 1/16 S17</div> <div data-bbox="932 1690 1000 1715" style="text-align: center;">2006</div> <div data-bbox="456 1751 1317 1776">Bury the iron post alongside the stainless steel post.</div> <hr style="width: 30%; margin: 10px auto;"/>
--------	---

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 17,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°50'20" W., beginning new measurement.
20.000	<p>Point for the 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 17, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-S 1/16 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> C S 1/16 S17 C </div> <p style="text-align: center;">2006</p>
22.50	Asphalt-surfaced road, bears NW. and SE.
24.00	Canal, 75 lks., wide, 10 ft. deep, parallels asphalt-surfaced road, drains NW.
40.000	<p>The 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 17, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the SW 1/16 cor. of sec. 17.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> SW 1/16 S17 2004 </div> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°44'10" W., beginning new measurement.</p>
19.959	<p>The S 1/16 sec. cor. of secs. 17 and 18.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 16 and 17.</p> <p>N. 89°54'30" W., on the E. and W. center line of sec. 17.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 17,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.952	<p>The 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 17, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-E 1/16 sec. cor. of sec. 17.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S17} \end{array}$ <p>2005</p> </div> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°51'10" W., beginning new measurement.</p>
0.03	Fence, bears N. and S.
19.981	<p>Point for the center 1/4 sec. cor. of sec. 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{T47N R52E} \\ \text{C } 1/4 \text{ S17} \end{array}$ <p>2005</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 48°02' E., 62.1 lks. dist., with brass cap mkd. RM C 1/4 S17 41.0 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 44°06' W., 61.4 lks. dist., with brass cap mkd. RM C 1/4 S17 40.5 FT TO COR 2005 and an arrow pointing to the corner.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 17,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
37.00	Asphalt-surfaced road, bears NW. and SE.
37.75	Canal, 75 lks. wide, 10 ft. deep, parallels asphalt-surfaced road, drains NW; thence along improved gravel road.
39.962	<p>The 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 17, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 4 ins. below the surface of an improved gravel road, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-W 1/16 sec. cor. of sec. 17.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S17} \end{array}$ <p>2004</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 34°22' W., 70.3 lks. dist., with brass cap mkd. RM CW 1/16 S17 46.4 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears N. 45°14' W., 60.4 lks. dist., with brass cap mkd. RM CW 1/16 S17 39.9 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Bury the iron post alongside the stainless steel post.</p> <hr style="width: 20%; margin-left: 0;"/> <p>N. 89°55'10" W., beginning new measurement.</p>
20.034	<p>The 1/4 sec. cor. of secs. 17 and 18.</p> <hr style="width: 80%; margin-left: 0;"/> <p>From the N 1/16 sec. cor. of secs. 16 and 17.</p> <p>N. 89°49'20" W., on the 1/16 section line through the N1/2 of sec. 17.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 17,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.007	<p>Point for the 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 17, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NE 1/16 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S17</p> <p style="text-align: center;">2006</p> <p>Cor. is located in fence, bears E. and W.</p>
20.04	Cor. of fences extending N., S., E. and W.
40.014	<p>Point for the 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 17, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-N 1/16 sec. cor. of sec. 17.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S17 C</p> <p style="text-align: center;">2006</p> <p>Cor. is located on E. side of small irrigation ditch, 5 lks. wide, 1 ft. deep, drains N.</p>
57.50	Asphalt-surfaced road, bears NW. and SE.
58.50	Canal, 75 lks. wide, 10 ft. deep, parallels asphalt-surfaced road, drains NW.
60.021	<p>The 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 17, monumented with a bent iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted vertical position of iron post as the best available evidence of the position of the original corner. This cor. will now be referred to as the NW 1/16 sec. cor. of sec. 17. Add the marks NW 2008 to the brass cap.</p>

CHAINS	<p>Set a steel sign post, 6 ft. long, alongside the iron post.</p> <p>Cor. is located at the cor. of fences extending E., W., and S.</p> <hr/> <p>N. 89°52'10" W., beginning new measurement.</p>
19.908	<p>The N 1/16 sec. cor. of sec. 17 and 18.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 18, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 17 and 18.</p> <p>S. 89°57'50" W., on the 1/16 section line through the S1/2 of sec. 18.</p>
20.001	<p>The 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 18, monumented with the remains of the 1911 iron post, 18 ins. long, 1 in. diam., firmly set, projecting 2 ins. above the ground, with the top portion and brass cap missing. This cor. will now be referred to as the SE 1/16 sec. cor. of sec. 18.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S18</p> <p style="text-align: center;">2004</p> <p>Bury the remains of the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located in fence, bears N. and S., 3 lks. S. of the cor. of fences extending S. and E.</p> <hr/> <p>N. 89°58'00" W., beginning new measurement.</p>
10.50	<p>Thacker Slough, 50 lks. wide, 5 ft. deep, course NW.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 18,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.011	<p>The 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 18, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 1 in. below the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-S 1/16 sec. cor. of sec. 18.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16\ \ S18 \\ C \end{array}$ <p>2004</p> </div> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°55'40" W., beginning new measurement.</p>
20.003	<p>Point for the 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 18, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SW 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} SW\ 1/16\ S18 \\ 2004 \end{array}$ </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
38.66	Fence, bears N. and S.
39.195	<p>The S 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>N. 89°59'20" W., on the E. and W. center line of sec. 18.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 18,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Along bladed dirt road.
19.992	<p>The 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 18, monumented with a bent iron post, 36 ins. long, 1 in. diam., firmly set, projecting 20 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted vertical position of iron post as the best available evidence of the position of the original corner. This cor. will now be referred to as the C-E 1/16 sec. cor. of sec. 18.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S18} \end{array}$ <p>2004</p> </div> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on S. shoulder of gravel road, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°54'00" W., beginning new measurement.</p>
20.013	<p>Point for the center 1/4 sec. cor. of sec. 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of a gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{T47N R52E} \\ \text{C } 1/4 \text{ S18} \end{array}$ <p>2004</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 32°47' E., 27.3 lks. dist., with brass cap mkd. RM C 1/4 S18 18.0 FT TO COR 2004 and an arrow pointing to the corner.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 18,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 52°29' W., 37.3 lks. dist., with brass cap mkd. RM C 1/4 S18 24.6 FT TO COR 2004 and an arrow pointing to the corner.</p>
40.026	<p>The 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 18, monumented with the remains of the 1911 iron post, 24 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with the top portion of the 1911 iron post wired to a nearby wooden post at the cor. of fences extending E., W. and N., with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-W 1/16 sec. cor. of sec. 18.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S18} \end{array}$ <p>2004</p> </div> <p>Bury the top and bottom portions of the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 3 lks. SE. of the cor. of fences extending E., W. and N.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°55'50" W., beginning new measurement.</p>
19.14	Cor. of fences extending N., E. and W.
19.171	The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.
20.003	<p>From the N 1/16 sec. cor. of secs. 17 and 18.</p> <p>S. 89°53'10" W., on the 1/16 section line through the N1/2 of sec. 18.</p> <p>The 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 18, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the NE 1/16 sec. cor. of sec. 18.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 18,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S18</p> <p style="text-align: center;">2004</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located in a fence, bears N. and S., 5 lks. S. of the cor. of fences extending N., S., E. and W.</p> <hr/> <p>N. 89°55'10" W., beginning new measurement.</p> <p>19.992 Point for the 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 18, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-N 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S18 C</p> <p style="text-align: center;">2004</p> <p>Cor. is located 4 lks. W. of fence, bears N. and S.</p> <p>39.984 Point for the 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 18, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NW 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S18</p> <p style="text-align: center;">2004</p> <p>Cor. is located at the cor. of fences extending N., S. and E.</p> <p>59.166 The N 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.</p> <hr/>
--------	--

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 19,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/>
	<p>From 1/4 sec. cor. of secs. 19 and 30.</p> <p>N. 0°04'00" W., on the N. and S. center line of sec. 19.</p>
19.988	<p>Point for the C-S 1/16 sec. cor. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>C S 1/16 S19 C</p> <p>2004</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
39.976	<p>The center 1/4 sec. cor. of sec. 19, monumented with an iron post, firmly set, projecting 17 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E C 1/4 S19</p> <p>2004</p> </div> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr/>
19.987	<p>N. 0°10'00" W., beginning new measurement.</p> <p>Point for the C-N 1/16 sec. cor. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 19,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">C N 1/16 S19 C</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
20.10	Fence, bears E. and W., 1 lk. E. of the cor. of fences extending E., W. and N., thence along fence.
39.974	The 1/4 sec. cor. of secs. 18 and 19.
	<hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20.</p> <p>S. 89°59'20" W., on the E. and W. center line of sec. 19.</p>
19.966	<p>Point for the C-E 1/16 sec. cor. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S19</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 15 lks. N. of a dirt road, 15 lks. wide, bears E. and W.</p>
39.932	The center 1/4 sec. cor. of sec. 19.
	<hr/> <p>N. 89°55'30" W., beginning new measurement.</p>
19.979	<p>Point for the C-W 1/16 sec. cor. of sec. 19.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ——— C S19</p> <p style="text-align: center;">2004</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 19,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a steel sign post, 6 ft. long, alongside the stainless steel post.
31.50	Center of airport runway, bears N. and S.
39.24	Fence, bears N. and S.
39.319	The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp.
<p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 20, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p>	
	From the S 1/16 sec. cor. of secs. 20 and 21.
	N. 89°50'30" W., on the 1/16 section line through the S1/2 of sec. 20.
20.010	Point for the 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 20, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SE 1/16 sec. cor. of sec. 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SE 1/16 S20
	2004
	Set a steel sign post, 6 ft. long, alongside the stainless steel post.
	Cor. is located in an abandoned fence, bears N. and S.
40.020	Point for the 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 20, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-S 1/16 sec. cor. of sec. 20.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 20,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \mid S20 \\ C \end{array}$ </div> <div style="text-align: center;">2004</div> <p>Cor. is located in an abandoned fence, bears E. and W., in thick willows.</p> <p>60.030 Point for the 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 20, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SW 1/16 sec. cor. of sec. 20.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">SW 1/16 S20</div> <div style="text-align: center;">2004</div> <p>Cor. is located at the cor. of fences extending N., S. and E.</p> <p>79.74 Fence, bears N. and S.</p> <p>80.040 The S 1/16 sec. cor. of secs. 19 and 20.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 21.</p> <p>N. 89°41'50" W., on the E. and W. center line of sec. 20.</p> <p>19.987 The 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 20, monumented with the 1911 iron post, bent to the E., 36 ins. long, 1 in. diam., projecting 18 ins. above the ground, with brass cap missing. Accepted base of iron post as the best available evidence of the position of the original corner. This cor. will now be referred to as the C-E 1/16 sec. cor. of sec. 20.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} E\ 1/16 \\ C \text{ --- } C \\ S20 \end{array}$ </div> <div style="text-align: center;">2004</div>
--------	---

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 20,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
	<p>Cor. is located 30 lks. N. of a fence, bears E. and W. and 29 lks. S. of a fence, bears E. and W.</p>
	<p>S. 89°56'40" W., beginning new measurement.</p>
20.028	<p>The center 1/4 sec. cor. of sec. 20, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with brass cap mkd. as described in the field notes of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T47N R52E C 1/4 S20</p>
	<p style="text-align: center;">2004</p>
	<p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
	<p>N. 89°46'10" W., beginning new measurement.</p>
0.30	<p>Cor. of fences extending N., S. and E.</p>
19.932	<p>The 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 20, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-W 1/16 sec. cor. of sec. 20.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">W 1/16 C ——— C S20</p>
	<p style="text-align: center;">2004</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 20,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located in fence, bears E. and W.</p> <hr/> <p>N. 89°48'10" W., beginning new measurement.</p>
20.007	<p>The 1/4 sec. cor. of secs. 19 and 20.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 20 and 21.</p> <p>N. 89°44'00" W., on the 1/16 section line through the N1/2 of sec. 20.</p>
6.50	Road, asphalt-surfaced, bears NW. and SE.
8.00	Canal, 75 lks. wide, 10 ft. deep, parallels asphalt-surfaced road, drains NW.
20.013	<p>The 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 20, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 20 ins. above the ground, with brass cap mkd. as described in the field notes of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the NE 1/16 sec. cor. of sec. 20.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S20</p> <p style="text-align: center;">2004</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N. and W.</p> <hr/> <p>N. 89°55'20" W., beginning new measurement.</p>
19.60	Fence, bears N. and S., 1 lk. S. of the cor. of fences extending N., S. and E.
19.883	<p>The 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 20, monumented with an iron post, firmly set flush with the surface of a dirt road, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-N 1/16 sec. cor. of sec. 20.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 20,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the dirt road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16\ S20 \\ C \end{array}$ <p>2004</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 48°45' E., 37.9 lks. dist., with brass cap mkd. RM CN 1/16 S20 25.0 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 41°17' W., 43.6 lks. dist., with brass cap mkd. RM CN 1/16 S20 28.8 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Bury the iron post alongside the stainless steel post.</p> <p>Cor. is located in dirt road, bears N. and S.</p> <hr style="width: 20%; margin-left: 0;"/> <p>N. 89°46'50" W., beginning new measurement.</p> <p>0.30 Cor. of fences extending N., S. and W., thence along fence.</p> <p>20.053 The 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 20, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the NW 1/16 sec. cor. of sec. 20.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>NW 1/16 S20</p> <p>2004</p> </div>
--------	---

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 20,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., E. and W.</p> <hr/> <p>N. 89°53'30" W., beginning new measurement.</p>
19.906	<p>The true point for the N 1/16 sec. cor. of secs. 19 and 20.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 21, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 21 and 22.</p> <p>N. 89°47'30" W., on the 1/16 section line through the S1/2 of sec. 21.</p>
19.981	<p>The 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 21, monumented with the remains of the 1911 iron post, 20 ins. long, 1 in. diam., firmly set flush with the surface of the ground, the top portion of the iron post found laying loose nearby, with the brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the SE 1/16 sec. cor. of sec. 21.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S21</p> <p style="text-align: center;">2006</p> <p>Bury the top and bottom portions of the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., E. and W.</p> <hr/> <p>N. 89°53'30" W., beginning new measurement.</p>


DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 21,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.055	<p>The 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 21, reestablished by Donald J. Watts, Idaho Professional Land Surveyor No. 1923, monumented with a PK nail set in center of asphalt-surfaced road. This position is accepted as a careful and faithful reestablishment of the position of the original corner. This cor. will now be referred to as the C-S 1/16 sec. cor. of sec. 21.</p> <p>At the corner point</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \mid S21 \\ C \end{array}$ <p>2007</p> <hr style="width: 20%; margin: auto;"/> </div> <p>N. 89°56'50" W., beginning new measurement.</p>
20.021	<p>Point for the 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 21, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SW 1/16 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased, with brass cap mkd.</p> <div style="text-align: center;"> <p>SW 1/16 S21</p> <p>2006</p> </div>
20.25	<p>Fence, bears N. and S., 4.5 lks. S. of the cor. of fences extending E., W. and S.</p>
40.042	<p>The S 1/16 sec. cor. of secs. 20 and 21.</p> <hr style="width: 80%; margin: 10px auto;"/>
	<p>From the 1/4 sec. cor. of secs. 21 and 22.</p> <p>S. 89°57'10" W., on the E. and W. center line of sec. 21.</p>
20.058	<p>Point for the 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 21, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-E 1/16 sec. cor. of sec. 21.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 21,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} E \ 1/16 \\ C \text{---} C \\ S21 \end{array}$ <p>2006</p> </div>
40.116	<p>The center 1/4 sec. cor. of sec. 21, monumented with a rebar of unknown origin, 24 ins. long, 1/2 in. diam., firmly set 5 ins. below the asphalt surface, at the intersection of the projection of asphalt-surfaced roads curving S. and W. This position is harmoniously related to surrounding accepted corners, has been adopted by adjacent landowners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>T47N R52E C 1/4 S21</p> <p>2007</p> </div> <p>Remove and dispose of rebar and set a steel sign post, 6 ft. long, alongside the copper coated steel stake.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°45'30" W., beginning new measurement.</p>
20.037	<p>Point for the 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 21, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-W 1/16 sec. cor. of sec. 21.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> $\begin{array}{c} W \ 1/16 \\ C \text{---} C \\ S21 \end{array}$ <p>2007</p> </div>
40.074	<p>The 1/4 sec. cor. of secs. 20 and 21.</p> <hr/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 21,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>From the N 1/16 sec. cor. of secs. 21 and 22.</p> <p>N. 89°54'50" W., on the 1/16 section line through the N1/2 of sec. 21.</p>
19.406	<p>Point selected for the witness NE 1/16 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C</p> <p>NE 1/16 S21</p>  <p>2006</p> </div> <p>Cor. is located 9 lks. S. of fence, bears E. and W.</p>
20.072	<p>True point for the 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 21, at proportionate distance; there is no remaining evidence of the original corner. Point falls in canal, 1.00 chs. wide, 10 ft. deep, drains N., where it is impractical to establish a permanent monument. This cor. will now be referred to as the NE 1/16 sec. cor. of sec. 21.</p>
40.144	<p>Point for the 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 21, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-N 1/16 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>N 1/16 S21</p> <p>C</p> <p>2006</p> </div> <p>Cor. is located 14 lks. S. of fence, bears E. and W.</p> <p>From this point, a reference position established by Donald J. Watts, Idaho Professional Land Surveyor No. 1923, monumented with a rebar, 1/2 in. diam., firmly set, projecting 2 ns. above the ground, with plastic cap mkd. PELS 1923, 1.5 ks. N. of the cor. of fences extending E., W. and S., bears N. 89°10' E., 1.002 chs. dist.</p>
59.20	<p>Improved gravel road, bears N. and S.</p>
59.969	<p>Point selected for the witness NW 1/16 sec. cor. of sec. 21.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 21,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">W C NW 1/16 S21 ← 2006</p>
60.216	<p>True point for the 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 21, at proportionate distance; there is no remaining evidence of the original corner. Point falls in canal, 1.00 chs. wide, 10 ft. deep, drains N., where it is impractical to establish a permanent monument. This point will now be referred to as the NW 1/16 sec. cor. of sec. 21.</p>
80.288	<p>The N 1/16 sec. cor. of secs. 20 and 21.</p>
	<p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 22, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p>
	<p>From the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>S. 89°58'50" W., on the 1/16 section line through the S1/2 of sec. 22.</p>
0.46	<p>Fence, bears N. and S.</p>
19.907	<p>The 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 22, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the SE 1/16 sec. cor. of sec. 22.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">SE 1/16 S22 2005</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 22,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 5 lks. N. of a fence, bears E. and W.</p> <hr/> <p>N. 89°46'10" W., beginning new measurement.</p>
9.50	Owyhee River, 2 chs. wide, course NW.
19.91	Fence, bears N. and S.
20.060	<p>Point for the 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 22, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-S 1/16 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>C S 1/16 S22 C</p> <p>2006</p> </div> <p>Cor. is located on N. berm of canal, drains W., 45 lks. N. of a fence, bears E. and W. and 3 lks. N. of fence, bears E. and W.</p>
32.50	Improved gravel road, bears NW. and SE.
40.120	<p>Point for the 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 22, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SW 1/16 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>SW 1/16 S22</p> <p>2006</p> </div> <p>Cor. is located on E. berm of canal, 75 lks. wide, 10 ft. deep, drains NNW.</p>
60.180	<p>The S 1/16 sec. cor. of sec. 21 and 22.</p> <hr/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 22,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the 1/4 sec. cor. of secs. 22 and 23.
	N. 89°50'50" W., on the E. and W. center line of sec. 22.
0.48	Fence, bears N. and S.
20.012	Point for the 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 22, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-E 1/16 sec. cor. of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S22} \end{array}$
	2006
	Cor. is located on the S. berm of an irrigation ditch, 6 lks. wide, 1 ft. deep, drains W.
20.05	Fence, bears N. and S.
40.024	Point for the center 1/4 sec. cor. of sec. 22, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	$\begin{array}{c} \text{T47N R52E} \\ \text{C } 1/4 \text{ S22} \end{array}$
	2006
	Cor. is located 30 lks. N. of fence, bears E. and W.
41.40	Owyhee River, 2 chs. wide, course NW.
45.00	Improved gravel road, parallels Owyhee River.
60.036	Point for the 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 22, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-W 1/16 sec. cor. of sec. 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 22,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> $\begin{array}{c} W \ 1/16 \\ C \text{-----} C \\ S22 \end{array}$ </div> <div style="text-align: center;">2006</div> <p>Cor. is located on the S. berm of an irrigation ditch, drains W.</p>
60.05	Fence, bears N. and S.
80.048	The 1/4 sec. cor. of secs. 21 and 22.
	<hr/> <p>From the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>N. 89°52'10" W., on the 1/16 section line through the N1/2 of sec. 22.</p>
0.53	Fence, bears N. and S.
20.007	<p>The 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 22, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NE 1/16 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">NE 1/16 S22</div> <div style="text-align: center;">2006</div> <p>Cor. is located 30 lks. S. of the cor. of fences extending E., W. and S.</p>
40.014	<p>Point for the 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 22, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-N 1/16 sec. cor. of sec. 22.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N \ 1/16 \mid S22 \\ C \end{array}$ </div> <div style="text-align: center;">2006</div> <p>Cor. is located on the N. berm of an irrigation ditch, 6 lks. wide, 1 ft. deep, drains W.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 22,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
57.00	Owyhee River, 2 chs. wide, course NW.
59.50	Improved gravel road, parallels Owyhee River.
60.021	Point for the 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 22, at proportionate distance. This point will now be referred to as the NW 1/16 sec. cor. of sec. 22. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd. NW 1/16 S22 2006 Cor. is located on the W. shoulder of an improved gravel road, parallels Owyhee River.
64.062	The witness cor. to the 1/16 sec. cor. No. 3, sec. 22, monumented with an iron post, firmly set, projecting 24 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This witness cor. will now function as an Angle Point. Remove the WC and add the marks AP 2006 to the brass cap. Cor. is located in a fence, bears E. and W. _____ N. 89°49'20" W., beginning new measurement.
15.947	The N 1/16 sec. cor. of secs. 21 and 22. _____ DEPENDENT RESURVEY OF THE SUBDIVISION-OF SECTION LINES OF SECTION 23, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA _____ Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911 _____ From the 1/4 sec. cor. of secs. 23 and 26. N. 0°32'40" E., on the N. and S. center line of sec. 23.
2.60	Canal, 6 lks. wide, drains NW.
14.20	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 33° W. and S. 33° E.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 23,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.109	<p>Point for the 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 23, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-S 1/16 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \mid S23 \\ C \end{array}$ <p>2006</p> </div> <p>From this point, a rebar of unknown origin, 1/2 in. diam., firmly set, projecting 3 ins. above the ground, bears N. 60°15' E., 0.239 chs. dist. This position cannot be reconciled with proper procedures and is not utilized during the course of this survey.</p>
40.218	<p>The center 1/4 sec. cor. of sec. 23, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Add the marks T47N R52E 2008 to the brass cap.</p> <p>Set a steel sign post, 6 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°15'10" W., beginning new measurement.</p>
19.969	<p>The 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 23, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-N 1/16 sec. cor. of sec. 23. Add the marks N 2008 and a vertical line, with the letter C stamped at each end of the line, to the brass cap.</p> <p>Set a steel sign post, 6 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02'00" E., beginning new measurement.</p>
20.062	<p>The 1/4 sec. cor. of secs. 14 and 23.</p> <hr style="width: 50%; margin: 10px auto;"/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 23,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the true point for the 1/4 sec. cor. of secs. 23 and 24. N. 89°52'10" W., on the E. and W. center line of sec. 23.
19.994	Point for the C-E 1/16 sec. cor. of sec. 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., in a rock slide, over a plastic-encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{---} \text{C} \\ \text{S23} \end{array}$ <p>2006</p> </div>
39.988	The center 1/4 sec. cor. of sec. 23. <div style="text-align: center;"> <hr style="width: 20%; margin: 0 auto;"/> </div> N. 89°56'00" W., beginning new measurement.
16.70	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 30° W. and S. 30° E.
20.036	Point for the 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 23, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-W 1/16 sec. cor. of sec. 23. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{---} \text{C} \\ \text{S23} \end{array}$ <p>2006</p> </div> Cor. is located on S. berm of irrigation ditch, 10 lks. wide, drains W.
39.36	Fence, bears N. and S.
40.072	The 1/4 sec. cor. of secs. 22 and 23. <div style="text-align: center;"> <hr style="width: 20%; margin: 0 auto;"/> </div> From the C-S 1/16 sec. cor. of sec. 23. N. 89°29'10" W., on the 1/16 section line through the SW1/4 of sec. 23.
4.10	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 23 1/4° W. and S. 23 1/4° E.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 23,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.741	<p>The 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 23, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 24 ins. below the surface of an irrigation berm, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the SW 1/16 sec. cor. of sec. 23.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S23</p> <p style="text-align: center;">2006</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on S. berm of irrigation ditch, 6 lks. wide, drains W.</p> <hr/> <p>S. 89°51'40" W., beginning new measurement.</p>
19.34	Fence, bears N. and S.
20.109	<p>The S 1/16 sec. cor. of sec. 22 and 23.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 23.</p> <p>N. 89°51'10" W., on the 1/16th line through the NW1/4 of sec. 23.</p>
20.007	<p>Point for the 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 23, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NW 1/16 sec. cor. of sec. 23.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S23</p> <p style="text-align: center;">2006</p>
25.20	<p>Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 26 3/4° W. and S. 26 3/4° E.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 23,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.63	Fence, bears N. and S.
40.014	The N 1/16 sec. cor. of secs. 22 and 23.
<p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 26, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
<p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p>	
	From the S 1/16 sec. cor. of secs. 25 and 26.
	N. 89°59'10" W., on the 1/16 section line through the S1/2 of sec. 26.
14.00	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 15° W. and S. 15° E.
14.959	Angle Point No. 4, Lot 3, sec. 26, hereinafter described.
19.959	Point for the 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 26, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SE 1/16 sec. cor. of sec. 26.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SE 1/16 S26
	2005
	Cor. is located in a fence, bears E. and W.
27.535	Angle Point No. 3, Lot 3, sec. 26, hereinafter described.
38.90	Owyhee River, 2 chs. wide, course NNW.
39.918	The 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 26, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 12 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-S 1/16 sec. cor. of sec. 26.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 26,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \mid S26 \\ C \end{array}$ <p>2005</p> </div> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located on the W. bank of the Owyhee River, course NNW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°51'00" W., beginning new measurement.</p>
0.90	Improved gravel road, bears NNW. and SSE.
20.038	<p>True point for the 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 26, at proportionate distance; there is no remaining evidence of the original corner. This point falls in irrigation ditch, 30 lks. wide, 3 ft. deep, drains W., where it is impractical to establish a permanent monument. This point will now be referred to as the SW 1/16 sec. cor. of sec. 26.</p> <p>From the true point, a point selected for the witness SW 1/16 sec. cor. of sec. 26 bears S. 83°40'00" E., 0.087 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} W\ C \\ \leftarrow SW\ 1/16\ S26 \end{array}$ <p>2006</p> </div>
39.78	Fence, bears N. and S.
40.076	The S 1/16 sec. cor. of secs. 26 and 27.
	<hr style="width: 50%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>N. 89°56'20" W., on the E. and W. center line of sec. 26.</p>
18.40	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 15° W. and S. 15° E.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 26,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.006	<p>Point for the 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 26, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-E 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S26} \end{array}$ <p>2006</p> </div>
39.012	<p>Record position for the witness cor. to the center 1/4 sec. cor. of sec. 26; there is no remaining evidence of the original corner. The witness cor. serves no further function.</p>
40.012	<p>Point for the center 1/4 sec. cor. of sec. 26, at proportionate distance.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{T47N R52E} \\ \text{C } 1/4 \text{ S26} \end{array}$ <p>2006</p> </div>
42.20	<p>Owyhee River, 2 chs. wide, course NNW.</p>
44.50	<p>Improved gravel road, parallels Owyhee River; thence along bladed dirt road, bears E. and W.</p>
60.018	<p>Point for the 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 26, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-W 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S26} \end{array}$ <p>2006</p> </div>
80.024	<p>The 1/4 sec. cor. of secs. 26 and 27</p> <hr/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 26,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>S. 89°58'50" W., on the 1/16 section line through the N1/2 of sec. 26.</p>
19.965	<p>Point for the 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 26, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NE 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S26</p> <p style="text-align: center;">2006</p>
23.60	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 15° W. and S. 15° E.
39.930	<p>Point for the 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 26, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-N 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S26 C</p> <p style="text-align: center;">2006</p> <p>Cor. is located 7.5 lks. N. of a fence, bears E. and W.</p>
56.90	Owyhee River, 2 chs. wide, course NW.
52.00	Improved gravel road, parallels Owyhee River.
59.895	<p>The 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 26, monumented with the remains of the 1911 iron post, 36 ins. long, 1 in. diam., firmly set 12 ins. below the surface of the ground, with brass cap missing. This cor. will now be referred to as the NW 1/16 sec. cor. of sec. 26.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 26,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">NW 1/16 S26</p> <p style="text-align: center;">2005</p> <p>Bury the remains of the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 6 lks. N. of fence, bears E. and W., and 15 lks. S. of irrigation ditch, 15 lks. wide, 4 ft. deep, drains W.</p> <hr/> <p>N. 89°47'40" W., beginning new measurement.</p> <p>19.94 Fence, bears N. and S.</p> <p>20.159 The N 1/16 sec. cor. of secs. 26 and 27.</p>
	<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 27, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 26 and 27.</p> <p>N. 89°50'30" W., on the 1/16 section line through the S1/2 of sec. 27.</p> <p>20.024 Point for the 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 27, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SE 1/16 sec. cor. of sec. 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S27</p> <p style="text-align: center;">2006</p> <p>20.18 Fence, bears N. and S.</p> <p>39.78 From this point, the cor. of fences extending S. and E., bears S. at 4 lks. dist.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 27,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.048	<p>The 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 27, monumented with the remains of the 1911 iron post, 18 ins. long, 1 in. diam., firmly set 10 ins. below the surface of a gravel road, with brass cap missing, and a rebar of unknown origin, 18 ins. long, 5/8 in. diam., set alongside. This cor. will now be referred to as the C-S 1/16 sec. cor. of sec. 27.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \mid S27 \\ C \end{array}$ <p>2005</p> </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears S. 43°01' E., 35.8 lks. dist., with brass cap mkd. RM CS 1/16 S27 23.6 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears S. 51°18' W., 43.6 lks. dist., with brass cap mkd. RM CS 1/16 S27 28.8 FT TO COR 2005 and an arrow pointing to the corner.</p> <p>Bury the remains of the iron post and the rebar alongside the stainless steel post.</p> <p>Cor. is located in a gravel road, bears N. and S.</p> <hr style="width: 20%; margin-left: 0;"/> <p>N. 89°45'20" W., beginning new measurement.</p>
0.36	Fence, bears N. and S., 1 lk. S. of the cor. of fences extending S. and W.
20.108	<p>The 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 27, monumented with a slightly bent iron post, 36 ins. long, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the SW 1/16 sec. cor. of sec. 27.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 27,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S27</p> <p style="text-align: center;">2006</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 89°57'00" W., beginning new measurement.</p> <p>0.075 Cor. of fences extending N., S. and E.</p> <p>20.035 The S 1/16 sec. cor. of secs. 27 and 28.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>N. 89°51'10" W., on the E. and W. center line of sec. 27.</p> <p>Along dirt road.</p> <p>20.151 The 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 27, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set 10 ins. below the surface of a dirt road, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-E 1/16 sec. cor. of sec. 27.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the dirt road, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{E 1/16} \\ \text{C} \text{---} \text{C} \\ \text{S27} \end{array}$ </p> <p style="text-align: center;">2005</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 43°34' E., 20.5 lks. dist., with brass cap mkd. RM CE 1/16 S27 13.5 FT TO COR 2005 and an arrow pointing to the corner.</p>
--------	--

CHAINS

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 50°51' W., 23.0 lks. dist., with brass cap mkd. RM CE 1/16 S27 15.2 FT TO COR 2005 and an arrow pointing to the corner.

Bury the iron post alongside the stainless steel post.

Cor. is located in a dirt road, bears E. and W., 38 lks. S. of the intersection of canals, each 30 lks. wide, extending E., W. and N., drains W. and N.

N. 89°46'30" W., beginning new measurement.

20.012

The center 1/4 sec. cor. of sec. 27, monumented with the remains of the 1911 iron post, 36 ins. long, 1 in. diam., firmly set 6 ins. below the surface of a gravel road, with brass cap missing.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below the surface of the gravel road, over a plastic-encased magnet, with brass cap mkd.

T47N R52E
C 1/4 S27

2005

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at the cor. of fences extending N., E. and W., for a reference monument, bears N. 25°14' E., 48.8 lks. dist., with brass cap mkd. RM C 1/4 S27 32.2 FT TO COR 2005 and an arrow pointing to the corner.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing NW. and SE., for a reference monument, bears S. 44°50' E., 108.9 lks. dist., with brass cap mkd. RM C 1/4 S27 71.9 FT TO COR 2005 and an arrow pointing to the corner.

Bury the remains of the iron post alongside the stainless steel post.

Cor. is located in a gravel road, bears E. and W.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 27,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°47'40" W., beginning new measurement.
19.95	Fence, bears N. and S.
19.996	Point for the 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 27, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-W 1/16 sec. cor. of sec. 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{---} \text{C} \\ \text{S27} \end{array}$ <p>2006</p> </div> <p>Cor. is located 1.5 lks. N. and 4.5 lks. W. of the cor. of fences extending E., W. and N.</p>
39.992	The 1/4 sec. cor. of secs. of secs. 27 and 28. <hr/>
	From the N 1/16 sec. cor. of sec. 26 and 27. N. 89°45'40" W., on the 1/16 section line through the N1/2 of sec. 27.
19.91	Fence, bears N. and S.
20.031	Point for the 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 27, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NE 1/16 sec. cor. of sec. 27. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> <p>NE 1/16 S27</p> <p>2006</p> </div> <p>Cor. is located in the bottom of a drain, 18 lks. wide, 4.5 lks. N. and 12 lks. W. of the cor. of fences extending N., E. and W.</p>
39.95	Fence, bears N. and S.
40.062	Point for the 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 27, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-N 1/16 sec. cor. of sec. 27.


DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 27,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S27 C</p> <p style="text-align: center;">2006</p> <p>Cor. is located 19.5 lks. N. and 10.5 lks. W. of the cor. of fences extending N., S., E. and W.</p> <p>60.093 Point for the 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 27, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NW 1/16 sec. cor. of sec. 27.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S27</p> <p style="text-align: center;">2006</p> <p>Cor. is located at the cor. of fences extending N., S., E. and W.</p> <p>80.124 The N 1/16 sec. cor. of secs. 27 and 28.</p>
	<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 28, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 27 and 28.</p> <p>S. 89°55'20" W., on the 1/16 section line through the S1/2 of sec. 28.</p> <p>20.023 The 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 28, monumented with a slightly bent iron post, 36 ins. long, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field noted of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the SE 1/16 sec. cor. of sec. 28.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 28,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S28</p> <p style="text-align: center;">2005</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., S., E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°52'30" W., beginning new measurement.</p> <p>19.70 Fence, bears N. and S.</p> <p>19.934 True point for the 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 28, at proportionate distance; there is no remaining evidence of the original corner. Point falls in canal, 1.50 chs. wide, 15 ft. deep, drains W., where it is impractical to set a permanent monument. This point will now be referred to as the C-S 1/16 sec. cor. of sec. 28.</p> <p>True point is located 28 lks. N. and 23 lks. W. of the cor. of fences extending N., S., E. and W.</p> <p>From the true point, the point selected for the witness C-S 1/16 sec. cor. of sec. 28 bears S. 0°05'00" E., 0.283 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encases magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C</p> <p>C</p> <p>↑</p> <p>S 1/16 S28</p> <p>C</p> <p style="margin-top: 10px;">2005</p> </div> <p>Witness cor. is located in fence, bears E. and W.</p> <p>39.868 True point for the 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 28, at proportionate distance; there is no remaining evidence of the original corner. Point falls in canal, 1.50 chs. wide, 15 ft. deep, drains W., where it is impractical to set a permanent monument. This point will now be referred to as the SW 1/16 sec. cor. of sec. 28.</p>
--------	---

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 28,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the true point, the point selected for the witness SW 1/16 sec. cor. of sec. 28, bears S. 21°59'50" E., 0.375 chs. dist.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C</p> <p>SW 1/16 S28</p>  <p>2005</p> </div>
59.802	<p>The S 1/16 sec. cor. of secs. 28 and 29.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28.</p> <p>S. 89°51'00" W., on the E. and W. center line of sec. 28.</p>
19.992	<p>The 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 28, monumented with the remains of the 1911 iron post, 24 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with the top 12 ins. of the iron post laying alongside, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-E 1/16 sec. cor. of sec. 28.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16</p> <p>C — C</p> <p>S28</p> <p>2005</p> </div> <p>Bury the remains of the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 17.5 lks. N. of the cor. of fences extending S., E. and W. and 34 lks. S. of the cor. of fences extending N., E. and W.</p> <hr/> <p>N. 89°55'20" W., beginning new measurement.</p>
20.088	<p>The center 1/4 sec. cor. of sec. 28, monumented with the remains of the 1911 iron post, 18 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with brass cap missing.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 28,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T47N R52E C 1/4 S28</p> <p style="text-align: center;">2005</p> <p>Bury the remains of the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post. Cor. is located 3 lks. E. of fence, extends W., and S. 4° W., 28 ks. of the cor. of fences extending N., E. and W., and N. 9° W., 21.5 lks. of the cor. of fences extending S. and E.</p> <hr/> <p>N. 89°48'00" W., beginning new measurement.</p>
19.991	<p>The 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 28, monumented with the 1911 iron post, 36 ins. long, 1 in. diam., firmly set flush with the surface of the ground, with brass cap missing. This cor. will now be referred to as the C-W 1/16 sec. cor. of sec. 28.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C — C S28</p> <p style="text-align: center;">2005</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 15 lks. N. of fence, bears E. and W. and S. 3° W., 25 lks. dist. of the cor. of fences extending N., E. and W.</p> <hr/> <p>N. 89°56'50" W., beginning new measurement.</p>
19.790	<p>The 1/4 sec. cor. of secs. 28 and 29.</p> <hr/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 28,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the N 1/16 sec. cor. of secs. 27 and 28.</p>
	<p>S. 89°52'30" W., on the 1/16 section line through the N1/2 of sec. 28.</p> <p>20.075 The 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 28, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the NE 1/16 sec. cor. of sec. 28.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S28</p> <p style="text-align: center;">2005</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., S., E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°54'40" W., beginning new measurement.</p>
20.012	<p>The 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 28, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-N 1/16 sec. cor. of sec. 28.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S28 C</p> <p style="text-align: center;">2005</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 28,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending E., W. and S.</p> <hr/> <p>N. 89°56'50" W., beginning new measurement.</p> <p>19.906 The 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 28, determined by John T. Eddy, Nevada Professional Land Surveyor No. 5016, monumented with a rebar, 18 ins. long, 5/8 in. diam., projecting 4 ins. above the ground, with plastic cap, 1 1/2 ins. diam., mkd. JUB PLS 5016, as shown on an unrecorded combination boundary and topography map, filed with the Duck Valley Housing Authority. This position is accepted as a careful and faithful determination of the position of the original corner. This cor. will now be referred to as the NW 1/16 sec. cor. of sec. 28.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S28</p> <p style="text-align: center;">2005</p> <p>Bury the rebar and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 89°57'00" W., beginning new measurement.</p> <p>19.904 The N 1/16 sec. cor. of secs. 28 and 29.</p>
	<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 29, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 32.</p> <p>N. 0°09'00" W., on the N. and S. center line of sec. 29.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 29,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Along bladed dirt road.
19.986	<p>Point for the C-S 1/16 sec. cor. of sec. 29.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the dirt road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> C S 1/16 S29 C </div> <p style="text-align: center;">2004</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 39°10' E., 57.4 lks. dist., with brass cap mkd. RM CS 1/16 S29 37.9 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears N. 49°15' W., 53.0 lks. dist., with brass cap mkd. RM CS 1/16 S29 35.0 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
39.972	<p>The center 1/4 sec. cor. of sec. 29, monumented with a bent iron post, 36 ins. long, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T47N R52E C 1/4 S29 </div> <p style="text-align: center;">2004</p> <p>Bury the iron post alongside the stainless steel post.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 29,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°09'50" W., beginning new measurement.
0.015	Cor. of fences extending N. and E.
19.984	Point for the C-N 1/16 sec. cor. of sec. 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> C N 1/16 S29 C </div> 2004 Set a steel sign post, 6 ft. long, alongside the stainless steel post. Cor. is located on the projection of fences extending S. and E., 7.5 lks. W. of a canal, 10 lks. wide, 1 ft. deep, drains N.
39.968	The 1/4 sec. cor. of secs. 20 and 29. <hr/>
	From the 1/4 sec. cor. of secs. 28 and 29. N. 89°52'10" W., on the E. and W. center line of sec. 29.
0.12	Canal, 4.5 lks. wide, 1 ft. deep, drains N.
20.115	Point for the C-E 1/16 sec. cor. of sec. 29. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> E 1/16 C ——— C S29 </div> 2005
40.15	Canal, 10 lks. wide, 1 ft. deep, drains N.
40.230	The center 1/4 sec. cor. of sec. 29. <hr/>
	N. 89°51'30" W., beginning new measurement.
20.007	Point for the C-W 1/16 sec. cor. of sec. 29.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 29,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the road, over a plastic-encased magnet, with brass cap mkd.</p> $\begin{array}{c} W \ 1/16 \\ C \text{---} C \\ S29 \end{array}$ <p>2004</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 36°09' E., 38.9 lks. dist., with brass cap mkd. RM CW 1/16 S29 25.7 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing E. and W., for a reference monument, bears S. 55°28' W., 50.8 lks. dist., with brass cap mkd. RM CW 1/16 S29 33.5 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>39.41 Fence, bears N. and S.</p> <p>40.014 The 1/4 sec. cor. of secs. 29 and 30.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 30, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 0°04'50" W., on the N. and S. center line of sec. 30.</p> <p>12.40 Gravel road, bears NW. and SE.</p> <p>19.969 Point for the C-S 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 30,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">C S 1/16 S30 C</p> <p style="text-align: center;">2004</p> <p>Cor. is located 2 lks. W. of the cor. of fences extending N., S. and E.</p>
39.938	<p>The center 1/4 sec. cor. of sec. 30, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Add the marks T47N R52E 2004 to the brass cap.</p> <p>Set a steel sign post, 6 ft. long, alongside the iron post.</p> <p>Cor. is located at the cor. of fences extending N., S., E. and W.</p> <hr/> <p>N. 0°08'40" W., beginning new measurement.</p>
19.984	<p>Point for the C-N 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S30 C</p> <p style="text-align: center;">2004</p>
39.67	Fence, bears E. and W.
39.968	<p>The 1/4 sec. cor. of secs. 19 and 30.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>N. 89°56'20" W., on the E. and W. center line of sec. 30.</p>
0.29	Fence, bears N. and S.
19.976	<p>Point for the C-E 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 30,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">E 1/16 C ——— C S30</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located in fence, bears E. and W.</p>
20.25	Cor. of fences extending N., S., E. and W.
39.952	The center 1/4 sec. cor. of sec. 30.
	<hr/> <p>S. 89°58'10" W., beginning new measurement.</p>
19.981	<p>Point for the C-W 1/16 sec. cor. of sec. 30.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ——— C S30</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 2 lks. N. of a fence, bears E. and W.</p>
31.50	Center of airport runway, bears N. and S.
39.38	Fence, bears N. and S.
39.402	The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.
	<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 31, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the 1/4 sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.</p> <p>N. 0°04'40" W., on the N. and S. center line of sec. 31.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 31,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.993	Point for the C-S 1/16 sec. cor. of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, over a plastic-encased magnet, with brass
	cap mkd.
	<div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \mid S31 \\ C \end{array}$ </div>
	2004
	Set a steel sign post, 6 ft. long, alongside the stainless steel
	post.
39.986	The center 1/4 sec. cor. of sec. 31, monumented with a bent iron
	post, 36 ins. long, 1 in. diam., firmly set, projecting 20 ins.
	above the ground, with brass cap mkd. as described in the field
	notes of the survey of T. 47 N., R. 52 E., executed under
	Instructions dated April 27, 1911. Accepted base of iron post
	as the best available evidence of the position of the original
	corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, over a plastic-encased magnet, with brass
	cap mkd.
	<div style="text-align: center;"> T47N R52E C 1/4 S31 </div>
	2004
	Bury the iron post and set a steel sign post, 6 ft. long,
	alongside the stainless steel post.
	From this cor., a rebar of unknown origin, 5/8 in. diam., firmly
	set, projecting 6 ins. above the ground, bears N. 1°27' E.,
	0.072 chs. dist. This position cannot be reconciled with proper
	procedures and is not utilized during the course of this survey.
	<hr/>
	N. 0°04'40" W., beginning new measurement.
20.005	Point for the C-N 1/16 sec. cor. of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam.,
	24 ins. in the ground, over a plastic-encased magnet, with brass
	cap mkd.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 31,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<div style="text-align: center;"> $\begin{array}{c} C \\ N \ 1/16 \ S31 \\ C \end{array}$ </div>
	2004
	Set a steel sign post, 6 ft. long, alongside the stainless steel post.
40.010	The 1/4 sec. cor. of secs. 30 and 31.
	<hr/> <p>From the 1/4 sec. cor. of secs. 31 and 32.</p> <p>N. 89°58'20" W., on the E. and W. center line of sec. 31.</p>
20.031	Point for the C-E 1/16 sec. cor. of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> $\begin{array}{c} E \ 1/16 \\ C \ \hline S31 \\ C \end{array}$ </div>
	2004
	Set a steel sign post, 6 ft. long, alongside the stainless steel post.
40.062	The center 1/4 sec. cor. of sec. 31.
	<hr/> <p>N. 89°58'20" W., beginning new measurement.</p>
19.945	Point for the C-W 1/16 sec. cor. of sec. 31.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> $\begin{array}{c} W \ 1/16 \\ C \ \hline S31 \\ C \end{array}$ </div>
	2004
	Set a steel sign post, 6 ft. long, alongside the stainless steel post.
39.511	The 1/4 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp.
	<hr/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 32,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0°08'10" W., on the N. and S. center line of sec. 32.</p>
19.97	Fence, bears E. and W., 3 lks. E. of the cor. of fences extending N., E. and W.
19.998	<p>Point for the C-S 1/16 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>C S 1/16 S32 C</p> <p>2004</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
38.50	Improved gravel road, 25 ft. wide, bears NE. and SW.
39.996	<p>The center 1/4 sec. cor. of sec. 32, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R52E C 1/4 S32</p> <p>2004</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 1 lk. W. of fence, bears N. and S.</p> <hr/> <p>N. 0°01'00" W., beginning new measurement.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 32,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.971	<p>Point for the C-N 1/16 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \mid S32 \\ C \end{array}$ <p>2004</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., S. and W.</p>
39.942	<p>The 1/4 sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>N. 89°52'20" W., on the E. and W. center line of sec. 32.</p>
0.31	Fence, bears N. and S.
20.001	<p>Point for the C-E 1/16 sec. cor. of sec. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} E\ 1/16 \\ C \text{ --- } C \\ S32 \end{array}$ <p>2004</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
38.50	Improved gravel road, 25 ft. wide, bears NE. and SW.
39.99	Fence, bears N. and S.
40.002	<p>The center 1/4 sec. cor. of sec. 32.</p> <hr/> <p>N. 89°52'40" W., beginning new measurement.</p>
19.964	Point for the C-W 1/16 sec. cor. of sec. 32.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 32,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} W \ 1/16 \\ \hline C \quad \quad C \\ S32 \end{array}$ <p>2004</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
39.928	The 1/4 sec. cor. of secs. 31 and 32.
	<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 33, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 33 and 34.</p> <p>N. 89°55'30" W., on the 1/16 section line through the S1/2 of sec. 33.</p>
0.30	Fence, bears N. and S.
19.856	<p>Point selected for the witness SE 1/16 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} W \ C \\ \hline \leftarrow SE \ 1/16 \ S33 \end{array}$ <p>2005</p> </div> <p>Cor. is located on the E. berm of canal. 30 lks. wide, 3 ft. deep, drains N. and 9 lks. N. of a fence, bears E. and W.</p>
20.036	<p>True point for the 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 33, at proportionate distance; there is no remaining evidence of the original corner. This point falls in a canal, 30 lks. wide, 3 ft. deep, drains N., where it is impractical to establish a permanent monument. This point will now be referred to as the SE 1/16 sec. cor. of sec. 33.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 33,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.072	<p>The 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 33, monumented with an iron post, firmly set, projecting 14 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-S 1/16 sec. cor. of sec. 33.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16\ S33 \\ C \end{array}$ <p>2004</p> </div> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 2 lks. S. of fence, bears E. and W.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89°52'40" W., beginning new measurement.</p>
0.15	<p>Fence, bears N. and S., 2 lks. S. of the cor. of fences extending N., S. and E.</p>
20.015	<p>Point for the 1/16 sec. cor. No. 9, in the center of the SW 1/4 of sec. 33, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SW 1/16 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>SW 1/16 S33</p> <p>2004</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 1.5 lks. N. of fence, bears E. and W.</p>
40.030	<p>The S 1/16 sec. cor. of secs. 32 and 33.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 33 and 34.</p> <p>S. 89°52'50" W., on the E. and W. center line of sec. 33.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 33,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.098	<p>Point for the 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 33, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-E 1/16 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S33} \end{array}$ </div> <p style="text-align: center;">2004</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, in a fence bearing N. and S., for a reference monument, bears S. 46°22' W., 27.9 lks. dist., with brass cap mkd. RM CE 1/16 S33 18.4 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, at the cor. of fences extending N., S. and W., for a reference monument, bears N. 41°56' W., 29.6 lks. dist., with brass cap mkd. RM CE 1/16 S33 19.5 FT TO COR 2004 and an arrow pointing to the corner.</p>
20.30	Fence, bears N. and S.
40.196	<p>The center 1/4 sec. cor. of sec. 33, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T 47 N., R. 52 E., executed under Instructions dated April 27, 1911.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{T47N R52E} \\ \text{C } 1/4 \text{ S33} \end{array}$ </div> <p style="text-align: center;">2005</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 33,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the iron post alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending S., W. and NE.</p> <hr/> <p>N. 89°40'10" W., beginning new measurement.</p>
19.956	<p>Point for the 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 33, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-W 1/16 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{---} \text{C} \\ \text{S33} \end{array}$ <p>2005</p> </div> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 15 lks. N. of fence, bears E. and W.</p>
39.60	Fence, extends N. and S.
39.912	The 1/4 sec. cor. of secs. 32 and 33.
	<hr/> <p>From the N 1/16 sec. cor. of secs. 33 and 34.</p> <p>N. 89°55'20" W., on the 1/16 section line through the N1/2 of sec. 33.</p>
0.30	Fence, bears N. and S.
19.783	<p>Point selected for the witness NE 1/16 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{W C} \\ \text{NE } 1/16 \text{ S33} \\ \leftarrow \end{array}$ <p>2005</p> </div>
20.025	<p>True point for the 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 33, at proportionate distance; there is no remaining evidence of the original corner. Point falls in canal, drains N., 50 lks. wide, 5 ft. deep, where it is impractical to establish a permanent monument. This point will now be referred to as the NE 1/16 sec. cor. of sec. 33.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 33,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.050	<p>The 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 33, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the C-N 1/16 sec. cor. of sec. 33.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> C N 1/16 S33 C </div> <p style="text-align: center;">2005</p> <p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located in marsh area, 2 lks. N. of fence, bears E. and W.</p> <hr style="width: 30%; margin-left: auto; margin-right: auto;"/> <p>N. 89°52'40" W., beginning new measurement.</p>
19.960	<p>Point for the 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 33, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NW 1/16 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> NW 1/16 S33 </div> <p style="text-align: center;">2005</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 2 lks. N. of fence, bears E. and W.</p>
39.72	Access road, bears N. and S.
39.920	<p>The N 1/16 sec. cor. of sec. 32 and 33.</p> <hr/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 34,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/>
	<p>From the S 1/16 sec. cor. of secs. 34 and 35.</p> <p>N. 89°55'00" W., on the 1/16 section line through the S1/2 of sec. 34.</p> <p>20.015 Point for the 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 34, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SE 1/16 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S34</p> <p style="text-align: center;">2006</p>
20.06	Cor. of fences extending S. and W.
40.030	<p>Point for the 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 34, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-S 1/16 sec. cor. of sec. 34.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">C S 1/16 S34 C</p> <p style="text-align: center;">2007</p>
60.045	<p>The 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 34, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the SW 1/16 sec. cor. of sec. 34. Add the marks SW 2006 to the brass cap.</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located at the cor. of fences extending N., S., E. and W.</p> <hr/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 34,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°48'10" W., beginning new measurement.
19.70	Fence, bears N. and S.
20.043	The S 1/16 sec. cor. of secs. 33 and 34.
	<hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>N. 89°51'10" W., on the E. and W. center line of sec. 34.</p>
20.025	<p>Point for the 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 34, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-E 1/16 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16 C ——— C S34</p> <p>2006</p> </div> <p>Cor. is located at the cor. of fences extending N., S., E. and W.</p>
40.050	<p>The center 1/4 sec. cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 4 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>T47N R52E C 1/4 S34</p> <p>2006</p> </div>
60.075	<p>True point for the 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 34, at proportionate distance; there is no remaining evidence of the original corner. Point falls in canal, 50 lks. wide, 5 ft. deep, drains N., where it is impractical to establish a permanent monument. This point will now be referred to as the C-W 1/16 sec. cor. of sec. 34.</p>
60.227	Point selected for the witness C-W 1/16 sec. cor. of sec. 34.

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 34,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C W 1/16 C ————— C → S34</p> <p>2006</p> </div>
80.100	<p>The 1/4 sec. cor. of secs. 33 and 34.</p> <hr/> <p>From the N 1/16 sec. cor. of sec. 34 and 35.</p> <p>N. 89°55'10" W., on the 1/16 section line through the N1/2 of sec. 34.</p>
20.009	<p>The 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 34, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, with the top 15 ins. bent flush with the surface of the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Accepted base of iron post as the best available evidence of the position of the original corner. This cor. will now be referred to as the NE 1/16 sec. cor. of sec. 34.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>NE 1/16 S34</p> <p>2006</p> </div> <p>Reset the iron post, inverted, alongside the stainless steel post.</p> <hr/> <p>N. 89°52'10" W., beginning new measurement.</p>
0.03	<p>Fence, bears N. and S., 7.5 lks. S. of the cor. of fences extending N., S. and E.</p>
20.051	<p>Point for the 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 34, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-N 1/16 sec. cor. of sec. 34.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 34,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., 6 ins. below the top of a survey monument well, a plastic vinyl-coated pipe, 12 ins. long, 6 ins. diam., with an aluminum lid, 7 ins. diam., set flush with the surface of the asphalt, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">C N 1/16 S34 C</p> <p style="text-align: center;">2007</p>
40.102	True point for the 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 34, at proportionate distance; there is no remaining evidence of the original corner. Point falls in canal, 30 lks. wide, 3 ft. deep, drains N., where it is impractical to establish a permanent monument. This point will now be referred to as the NW 1/16 sec. cor. of sec. 34.
40.19	Fence, bears N. and S., 1.5 lks. N. of the cor. of fences extending N., E. and W.
40.279	<p>Point selected for the witness NW 1/16 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W C NW 1/16 S34 →</p> <p style="text-align: center;">2006</p> <p>Cor. is located 1.5 lks. N. of fence, bears E. and W.</p>
59.64	Fence, bears N. and S.
60.153	The N 1/16 sec. cor. of secs. 33 and 34.
<p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 35, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 35 and 36.</p> <p>N. 89°55'30" W., on the 1/16 section line through the S1/2 of sec. 35.</p>	

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 35,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.70	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. $3\frac{3}{4}^{\circ}$ E. and S. $3\frac{3}{4}^{\circ}$ W.
7.00	Owyhee River, 2 chs. wide, course N.
19.80	Canal, 15 lks. wide, 3 ft. deep, drains N.
20.019	Point for the 1/16 sec. cor. No. 11, in the center of the SE1/4 of sec. 35, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the SE 1/16 sec. cor. of sec. 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. SE 1/16 S35 2006 Cor. is located 7.5 lks. N. of fence, bears E. and W.
40.038	Point for the 1/16 sec. cor. No. 10, bet. the SE and SW quarters of sec. 35, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-S 1/16 sec. cor. of sec. 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of a dirt road, over a plastic-encased magnet, with brass cap mkd. C S 1/16 S35 C 2006 Cor. is located at the S. end of a dirt road, bears N.
60.057	The 1/16 sec. cor. No. 9, in the center of the SW1/4 of sec. 35, monumented with an iron post, 36 ins. long, 1 in. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. This cor. will now be referred to as the SW 1/16 sec. cor. of sec. 35. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.


DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 35,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	SW 1/16 S35
	2005
	<p>Bury the iron post and set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located SE., 3 lks. dist. of the cor. of fences extending N., S. and E.</p>
	<hr/> <p>N. 89°42'10" W., beginning new measurement.</p>
19.978	<p>The S 1/16 sec. cor. of secs. 34 and 35.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 35 and 36.</p> <p>N. 89°55'10" W., on the E. and W. center line of sec. 35.</p>
0.80	<p>Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 1 1/2° W and S. 1 1/2° E.</p>
9.00	<p>Owyhee River, 2 chs. wide, course NW.</p>
20.008	<p>True point for the 1/16 sec. cor. No. 7, bet. the NE and SE quarters of sec. 35, at proportionate distance; there is no remaining evidence of the original corner. Point falls in canal, 30 lks. wide, 4 ft. deep, drains N., where it is impractical to establish a permanent monument. This point will now be referred to as the C-E 1/16 sec. cor. of sec. 35.</p>
20.150	<p>Point selected for the witness C-E 1/16 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="889 1423 1084 1528" style="text-align: center;"> <p>W C</p> <p>E 1/16</p> <p>C ————— C →</p> <p>S35</p> </div>
	2006
	<p>Cor. is located SE., 10 lks. dist., of the cor. of fences extending S., E. and W.</p>
40.016	<p>Point for the center 1/4 sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of a bladed dirt road, over a plastic-encased magnet, with brass cap mkd.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 35,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T47N R52E C 1/4 S35</p> <p style="text-align: center;">2006</p>
	<p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, 2 lks. W. of a fence bearing N. and S., for a reference monument, bears S. 46°03' E., 52.9 lks. dist., with brass cap mkd. RM C 1/4 S35 34.9 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, 2 lks. E. of a fence bearing N. and S., for a reference monument, bears S. 50°33' W., 23.6 lks. dist., with brass cap mkd. RM C 1/4 S35 15.6 FT TO COR 2004 and an arrow pointing to the corner.</p> <p>Cor. is located in a dirt road, bears N. and S.</p>
60.024	<p>Point for the 1/16 sec. cor. No. 8, bet. the NW and SW quarters of sec. 35, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the C-W 1/16 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ——— C S35</p> <p style="text-align: center;">2006</p> <p>Cor. is located NW., 20 lks. dist., of the cor. of fences extending N., E. and W.</p>
80.032	<p>The 1/4 sec. cor. of secs. 34 and 35.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 35 and 36.</p> <p>N. 89°53'20" W., on the 1/16 section line through the N1/2 of sec. 35.</p>
4.90	<p>Nevada State Route No. 225, asphalt-surfaced, 45 lks. wide, bears N. 16 1/4° W. and S. 16 1/4° E.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 35,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.973	<p>True point for the 1/16 sec. cor. No. 5, in the center of the NE1/4 of sec. 35, at proportionate distance; there is no remaining evidence of the original corner. Point falls in the Owyhee River, 2 chs. wide, course NW., where it is impractical to establish a permanent monument. This point will now be referred to as the NE 1/16 sec. cor. of sec. 35.</p>
21.151	<p>Point selected for the witness NE 1/16 sec. cor. of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C</p> <p>NE 1/16 S35</p>  <p>2006</p> </div>
39.946	<p>The 1/16 sec. cor. No. 4, bet. the NE and NW quarters of sec. 35, monumented with the remains of the 1911 iron post, 20 ins. long, 1 in. diam., firmly set flush with the surface of a gravel road, with brass cap missing, witnessed by a rebar, 18 ins. long, 5/8 in. diam., set alongside. This point will now be referred to as the C-N 1/16 sec. cor. of sec. 35.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of a gravel road, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>N 1/16 S35</p> <p>C</p> <p>2006</p> </div> <p>Bury the iron post and rebar alongside the stainless steel post.</p> <p>Cor. is located on W. shoulder of bladed gravel road, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°55'00" W., beginning new measurement.</p>
20.018	<p>Point for the 1/16 sec. cor. No. 3, in the center of the NW1/4 of sec. 35, at proportionate distance; there is no remaining evidence of the original corner. This point will now be referred to as the NW 1/16 sec. cor. of sec. 35.</p>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 35,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S35</p> <p style="text-align: center;">2006</p>
40.036	<p>The N 1/16 sec. cor. of secs. 34 and 35.</p>
	<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 36, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp.</p> <p>N. 0°17'40" W., on the N. and S. center line of sec. 36.</p>
10.50	<p>Owyhee River, 2 chs. wide, course NW.</p>
20.015	<p>Point for the C-S 1/16 sec. cor. of sec. 35.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S36 C</p> <p style="text-align: center;">2006</p>
21.00	<p>Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears E. and W.; begin ascent.</p>
40.030	<p>The center 1/4 sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 47 N., R. 52 E., executed under Instructions dated April 27, 1911. Add the marks T47N R52E 2005 to the brass cap.</p> <hr/> <p>N. 0°25'10" W., beginning new measurement.</p>
39.925	<p>The true point for the 1/4 sec. cor. of secs. 25 and 36.</p> <hr/>

DEPENDENT RESURVEY OF THE
SUBDIVISION-OF-SECTION LINES OF SECTION 36,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp.
	N. 89°50'40" W., on the E. and W. center line of sec. 36.
39.840	The center 1/4 sec. cor. of sec. 36. <hr/>
	N. 89°50'10" W., beginning new measurement.
19.982	Point for the C-W 1/16 sec. cor. of sec. 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over plastic-encased magnet, in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	$\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S36} \\ 2006 \end{array}$
39.964	The 1/4 sec. cor. of secs. 35 and 36. <hr/>
	<p>FURTHER SUBDIVISION OF SECTION 2, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	From the E 1/16 sec. cor. of secs. 2 and 11.
	N. 0°02'50" W., on the N. and S. center line of the E1/2 of sec. 2.
13.990	The E 1/16 sec. cor., on the N. bdy. of sec. 2. <hr/>
	<p>FURTHER SUBDIVISION OF SECTION 7, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	From the 1/4 sec. cor. of secs. 7 and 18.
	N. 0°08'50" W., on the N. and S. center line of sec. 7.
19.987	The C-S 1/16 sec. cor. of sec. 7. <hr/>
	N. 0°08'20" W., beginning new measurement.
20.068	The center 1/4 sec. cor. of sec. 7. <hr/>

FURTHER SUBDIVISION OF SECTION 7,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°16'00" W., beginning new measurement.
19.917	The C-N 1/16 sec. cor. of sec. 7. <hr/>
	N. 0°03'40" E., beginning new measurement.
19.973	The 1/4 sec. cor. of secs. 6 and 7. <hr/>
	From the C-E 1/16 sec. cor. of sec. 7.
	N. 0°11'40" W., on the N. and S. center line of the NE1/4 of sec. 7.
19.936	The NE 1/16 sec. cor. of sec. 7. <hr/>
	N. 0°01'20" W., beginning new measurement.
19.917	The E 1/16 sec. cor. of secs. 6 and 7. <hr/>
	From the E 1/16 sec. cor. of secs. 7 and 18.
	N. 0°06'30" W., on the N. and S. center line of the SE1/4 of sec. 7.
20.120	The SE 1/16 sec. cor. of sec. 7. <hr/>
	N. 0°10'10" W., beginning new measurement.
19.937	The C-E 1/16 sec. cor. of sec. 7. <hr/>
	From the W 1/16 sec. cor. of secs. 7 and 18.
	N. 0°04'10" W., on the N. and S. center line of the SW1/4 of sec. 7.
19.993	The SW 1/16 sec. cor. of sec. 7. <hr/>
	N. 0°17'00" W., beginning new measurement.
20.026	The C-W 1/16 sec. cor. of secs. 7. <hr/>
	N. 0°12'30" W., on the N. and S. center line of the NW1/4 of sec. 7.
19.956	The NW 1/16 sec. cor. of sec. 7. <hr/>

FURTHER SUBDIVISION OF SECTION 7,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°03'00" W., beginning new measurement.
1.20	Asphalt-surfaced road, bears NW. and SE.
19.971	The W 1/16 sec. cor. of secs. 6 and 7.
<hr/>	
FURTHER SUBDIVISION OF SECTION 8, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA	
<hr/>	
	From the 1/4 sec. cor. of secs. 8 and 17.
	N. 0°03'00" E., on the N. and S. center line of sec. 8.
19.950	The C-S 1/16 sec. cor. of sec. 8.
<hr/>	
	N. 0°19'30" W., beginning new measurement.
20.090	The center 1/4 sec. cor. of sec. 8.
<hr/>	
	N. 0°01'50" W., beginning new measurement.
19.983	The C-N 1/16 sec. cor. of sec. 8.
<hr/>	
	N. 0°08'50" W., beginning new measurement.
19.60	From this point, the cor. of fences extending S. and E., bears E., 3 lks. dist.
19.978	The 1/4 sec. cor. of secs. 5 and 8.
<hr/>	
	From the C-E 1/16 sec. cor. of sec. 8.
	N. 0°00'50" E., on the N. and S. center line of the NE1/4 of sec. 8.
19.998	The NE 1/16 sec. cor. of sec. 8.
<hr/>	
	N. 0°09'40" W., beginning new measurement.
19.76	Cor. of fences extending N., S. and E.
19.93	Cor. of fences extending N., S. and W.
19.989	The E 1/16 sec. cor. of secs. 5 and 8.
<hr/>	

FURTHER SUBDIVISION OF SECTION 8,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the E 1/16 sec. cor. of secs. 8 and 17. N. 0°07'50" W., on the N. and S. center line of the SE1/4 of sec. 8.
19.980	The SE 1/16 sec. cor. of sec. 8. <hr/>
	N. 0°09'20" W., beginning new measurement.
20.053	The C-E 1/16 sec. cor. of sec. 8. <hr/>
	From the W 1/16 sec. cor. of secs. 8 and 17. N. 0°06'20" W., on the N. and S. center line of the SW1/4 of sec. 8.
19.981	The SW 1/16 sec. cor. of sec. 8. <hr/>
	N. 0°09'30" W., beginning new measurement.
20.066	The C-W 1/16 sec. cor. of sec. 8. <hr/>
	N. 0°04'30" W., on the N. and S. center line of the NW1/4 of sec. 8.
19.969	The true point for the NW 1/16 sec. cor. of sec. 8. <hr/>
	N. 0°08'00" W., beginning new measurement.
19.966	The true point for the W 1/16 sec. cor. of secs. 5 and 8. <hr/>
	FURTHER SUBDIVISION OF SECTION 9, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 9 and 16. N. 0°12'20" W., on the N. and S. center line of sec. 9.
19.988	The C-S 1/16 sec. cor. of sec. 9. <hr/>
	N. 0°12'20" W., beginning new measurement.
19.988	The center 1/4 sec. cor. of sec. 9. <hr/>

FURTHER SUBDIVISION OF SECTION 9,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°09'00" W., beginning new measurement.
20.043	The C-N 1/16 sec. cor. of sec. 9. <hr/>
	N. 0°20'40" E., beginning new measurement.
20.018	The 1/4 sec. cor. of secs. 4 and 9. <hr/>
	From the C-E 1/16 sec. cor. of sec. 9.
	N. 0°12'20" W., on the N. and S. center line of the NE1/4 of sec. 9.
20.073	The NE 1/16 sec. cor. of sec. 9. <hr/>
	N. 0°09'00" E., beginning new measurement.
20.053	The E 1/16 sec. cor. of secs. 4 and 9. <hr/>
	From the E 1/16 sec. cor. of secs. 9 and 16.
	N. 0°14'30" W., on the N. and S. center line of the SE1/4 of sec. 9.
19.994	The SE 1/16 sec. cor. of sec. 9. <hr/>
	N. 0°14'30" W., beginning new measurement.
19.994	The C-E 1/16 sec. cor. of sec. 9. <hr/>
	From the W 1/16 sec. cor. of secs. 9 and 16.
	N. 0°10'10" W., on the N. and S. center line of the SW1/4 of sec. 9.
19.983	The true point for the SW 1/16 sec. cor. of sec. 9. <hr/>
	N. 0°10'10" W., beginning new measurement.
19.983	The C-W 1/16 sec. cor. of sec. 9. <hr/>

FURTHER SUBDIVISION OF SECTION 9,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°05'40" W., on the N. and S. center line of the NW1/4 of sec. 9.
20.014	The NW 1/16 sec. cor. of sec. 9. _____
	N. 0°09'50" E., beginning new measurement.
20.036	The W 1/16 sec. cor. of secs. 4 and 9. _____
FURTHER SUBDIVISION OF SECTION 10, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA	
	From the 1/4 sec. cor. of secs. 10 and 15.
	N. 0°20'30" W., on the N. and S. center line of sec. 10.
6.80	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28° W. and S. 28° E.
19.999	The C-S 1/16 sec. cor. of sec. 10. _____
	N. 0°10'00" W., beginning new measurement.
19.989	The center 1/4 sec. cor. of sec. 10. _____
	N. 0°01'10" E., beginning new measurement.
20.040	The C-N 1/16 sec. cor. of sec. 10. _____
	N. 0°09'00" W., beginning new measurement.
19.934	The 1/4 sec. cor. of secs. 3 and 10. _____
	From the C-E 1/16 sec. cor. of sec. 10.
	N. 0°03'50" W., on the N. and S. center line of the NE1/4 of sec. 10.
20.017	The NE 1/16 sec. cor. of sec. 10. _____
	N. 0°08'50" W., beginning new measurement.
19.997	The E 1/16 sec. cor. of secs. 3 and 10. _____

FURTHER SUBDIVISION OF SECTION 10,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the E 1/16 sec. cor. of secs. 10 and 15. N. 0°21'00" W., on the N. and S. center line of the SE1/4 of sec. 10.
20.006	The SE 1/16 sec. cor. of sec. 10. <hr/>
	N. 0°08'00" W., beginning new measurement.
19.978	The C-E 1/16 sec. cor. of sec. 10. <hr/>
	From the W 1/16 sec. cor. of secs. 10 and 15. N. 0°25'30" W., on the N. and S. center line of the SW1/4 of sec. 10.
19.966	The SW 1/16 sec. cor. of sec. 10. <hr/>
	N. 0°06'20" W., beginning new measurement.
20.028	The C-W 1/16 sec. cor. of sec. 10. <hr/>
	N. 0°11'00" W., on the N. and S. center line of the NW1/4 of sec. 10.
3.90	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.
21.235	The NW 1/16 sec. cor. of sec. 10. <hr/>
	N. 0°07'30" E., beginning new measurement.
13.60	Owyhee River, 2 chs. wide, course NW.
18.727	The W 1/16 sec. cor. of secs. 3 and 10. <hr/>
FURTHER SUBDIVISION OF SECTION 11, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA	
	From the C-E 1/16 sec. cor. of sec. 11. N. 0°10'30" W., on the N. and S. center line of the NE1/4 of sec. 11.
19.943	Point for the NE 1/16 sec. cor. of sec. 11, at intersection with the E. and W. center line of the NE1/4.

FURTHER SUBDIVISION OF SECTION 11,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">NE 1/16 S11</p> <p style="text-align: center;">2006</p>
39.882	<p>The E 1/16 sec. cor. of secs. 2 and 11.</p> <hr/>
	<p>From the N 1/16 sec. cor. of sec. 11 and 12.</p> <p>N. 89°53'20" W., on the E. and W. center line of the NE1/4 of sec. 11.</p>
20.122	<p>The NE 1/16 sec. cor. of sec. 11.</p>
40.264	<p>The C-N 1/16 sec. cor. of sec. 11.</p> <hr/>
	<p>From the E 1/16 sec. cor. of sec. 11 and 14.</p> <p>N. 0°05'30" W., on the N. and S. center line of the SE1/4 of sec. 11.</p>
20.031	<p>Point for the SE 1/16 sec. cor. of sec. 11, at intersection of with the E. and W. center line of the SE1/4.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">SE 1/16 S11</p> <p style="text-align: center;">2006</p>
40.088	<p>The C-E 1/16 sec. cor. of sec. 11.</p> <hr/>
	<p>From the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>N. 89°54'30" W., on the E. and W. center line of the SE1/4 of sec. 11.</p>
20.073	<p>The SE 1/16 sec. cor. of sec. 11.</p>
40.107	<p>The C-S 1/16 sec. cor. of sec. 11.</p> <hr/>

FURTHER SUBDIVISION OF SECTION 11,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the W 1/16 sec. cor. of sec. 11 and 14.
	N. 0°07'50" W., on the N. and S. center line of the SW1/4 of sec. 11.
19.997	The SW 1/16 sec. cor. of sec. 11.
	N. 0°10'20" W., beginning new measurement.
20.020	The C-W 1/16 sec. cor. of sec. 11.
	N. 0°19'30" W., on the N. and S. center line of the NW1/4 of sec. 11.
19.979	The NW 1/16 sec. cor. of sec. 11.
	N. 0°12'40" W., beginning new measurement.
19.966	The W 1/16 sec. cor. of secs. 2 and 11.
<p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 14, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	From the C-E 1/16 sec. cor. of sec. 14.
	N. 0°05'40" W., on the N. and S. center line of the NE1/4 of sec. 14.
19.995	Point for the NE 1/16 sec. cor. of sec. 14, at intersection with the E. and W. center line of the NE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	NE 1/16 S14
	2006
39.990	The E 1/16 sec. cor. of secs. 11 and 14.
	From the N 1/16 sec. cor. of secs. 13 and 14.
	N. 89°52'40" W., on the E. and W. center line of the NE1/4 of sec. 14.

FURTHER SUBDIVISION OF SECTION 14,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.036	The NE 1/16 sec. cor. of sec. 14.
40.072	The C-N 1/16 sec. cor. of sec. 14.
	<hr/>
	From the W 1/16 sec. cor. of secs. 14 and 23.
	N. 0°08'00" W., on the N. and S. center line of the SW1/4 of sec. 14.
20.010	Point for the SW 1/16 sec. cor. of sec. 14, at intersection with the E. and W. center line of the SW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	SW 1/16 S14
	2006
39.996	The C-W 1/16 sec. cor. of sec. 14.
	<hr/>
	From the C-S 1/16 sec. cor. of sec. 14.
	N. 89°51'50" W., on the E. and W. center line of the SW1/4 of sec. 14.
20.035	The SW 1/16 sec. cor. of sec. 14.
40.040	The S 1/16 sec. cor. of secs. 14 and 15.
	<hr/>
	From the C-W 1/16 sec. cor. of sec. 14.
	N. 0°11'20" W., on the N. and S. center line of the NW1/4 of sec. 14.
20.036	Point for the NW 1/16 sec. cor. of sec. 14, at intersection with the E. and W. center line of the NW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, with brass cap mkd.
	NW 1/16 S14
	2006
40.019	The W 1/16 sec. cor. of secs. 11 and 14.
	<hr/>

FURTHER SUBDIVISION OF SECTION 14,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the C-N 1/16 sec. cor. of sec. 14.
	N. 89°47'50" W., on the E. and W. center line of the NW1/4 of sec. 14.
20.050	The NW 1/16 sec. cor. of sec. 14.
40.100	The N 1/16 sec. cor. of secs. 14 and 15.
<hr/>	
FURTHER SUBDIVISION OF SECTION 15, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA	
<hr/>	
	From the 1/4 sec. cor. of secs. 15 and 22.
	N. 0°02'30" E., on the N. and S. center line of sec. 15.
20.101	The C-S 1/16 sec. cor. of sec. 15.
<hr/>	
	N. 0°26'20" W., beginning new measurement.
19.50	Fence, bears E. and W., 9 lks. W. of the cor. of fences extending S., E. and W.
19.822	The center 1/4 sec. cor. of sec. 15.
<hr/>	
	N. 0°00'10" E., beginning new measurement.
0.50	Fence, bears E. and W., 8 lks. W. of the cor. of fences extending N., E. and W.
20.221	The true point for the C-N 1/16 sec. cor. of sec. 15.
<hr/>	
	N. 0°09'10" W., beginning new measurement.
20.009	The 1/4 sec. cor. of secs. 10 and 15.
<hr/>	
	From the C-E 1/16 sec. cor. of sec. 15.
	N. 0°06'20" W., on the N. and S. center line of the NE1/4 of sec. 15.
6.30	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 28 1/4° W. and S. 28 1/4° E.
20.117	The NE 1/16 sec. cor. of sec. 15.
<hr/>	

FURTHER SUBDIVISION OF SECTION 15,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°11'00" W., beginning new measurement.
20.014	The E 1/16 sec. cor. of secs. 10 and 15.
	From the E 1/16 sec. cor. of secs. 15 and 22.
	N. 0°00'50" W., on the N. and S. center line of the SE1/4 of sec. 15.
20.00	Fence, bears E. and W., 2 lks. E. of the cor. of fences extending N., S., E. and W.
20.063	The SE 1/16 sec. cor. of sec. 15.
	N. 0°20'30" W., beginning new measurement.
19.899	The C-E 1/16 sec. cor. of sec. 15.
	From the W 1/16 sec. cor. of secs. 15 and 22.
	N. 0°01'00" W., on the N. and S. center line of the SW1/4 of sec. 15.
0.60	Intersection of canals extending N., E. and W., drains W., thence along canal.
20.187	The SW 1/16 sec. cor. of sec. 15.
	N. 0°15'50" W., beginning new measurement.
19.45	Fence, bears E. and W., 36 lks. W. of the cor. of fences extending E., W. and S.
19.910	The C-W 1/16 sec. cor. of sec. 15.
	N. 0°02'40" W., on the N. and S. center line of the NW1/4 of sec. 15.
0.55	Fence, bears E. and W., 19 lks. E. of the corner. of fences extending E., W. and N.
20.110	The true point for the NW 1/16 sec. cor. of sec. 15.
	N. 0°07'20" W., beginning new measurement.
20.004	The W 1/16 sec. cor. of secs. 10 and 15.

FURTHER SUBDIVISION OF SECTION 16,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the 1/4 sec. cor. of secs. 16 and 21.
	N. 1°07'10" W., on the N. and S. center line of sec. 16.
20.540	The C-S 1/16 sec. cor. of sec. 16.
	N. 0°13'20" W., beginning new measurement.
20.018	The center 1/4 sec. cor. of sec. 16.
	N. 0°19'10" W., beginning new measurement.
13.70	Improved gravel road, bears NW. and SE.
19.30	Owyhee River, 2 chs. wide, course NW.
19.977	The true point for the C-N 1/16 sec. cor. of sec. 16.
	N. 0°07'40" E., beginning new measurement.
19.989	The 1/4 sec. cor. of secs. 9 and 16.
	From the C-E 1/16 sec. cor. of sec. 16.
	N. 0°12'20" W., on the N. and S. center line of the NE1/4 of sec. 16.
19.988	The NE 1/16 sec. cor. of sec. 16.
	N. 0°01'10" E., beginning new measurement.
19.994	The E 1/16 sec. cor. of secs. 9 and 16.
	From the E 1/16 sec. cor. of secs. 16 and 21.
	N. 0°49'40" W., on the N. and S. center line of the SE1/4 of sec. 16.
20.282	The true point for the SE 1/16 sec. cor. of sec. 16.
	N. 0°09'20" W., beginning new measurement.
8.90	Improved gravel road, bears NW. and SE.
11.50	Owyhee River, 2 chs. wide, course NW.
20.009	The C-E 1/16 sec. cor. of sec. 16.

FURTHER SUBDIVISION OF SECTION 16,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the W 1/16 sec. cor. of secs. 16 and 21. N. 0°28'40" W., on the N. and S. center line of the SW1/4 of sec. 16.
20.268	The SW 1/16 sec. cor. of sec. 16. <hr/>
	N. 0°02'50" E., beginning new measurement.
20.002	The C-W 1/16 sec. cor. of sec. 16. <hr/>
	N. 0°31'50" W., on the N. and S. center line of the NW1/4 of sec. 16.
19.976	The NW 1/16 sec. cor. of sec. 16. <hr/>
	N. 0°14'20" E., beginning new measurement.
19.992	The W 1/16 sec. cor. of secs. 9 and 16. <hr/>
FURTHER SUBDIVISION OF SECTION 17, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA	
	From the 1/4 sec. cor. of secs. 17 and 20. N. 0°06'00" E., on the N. and S. center line of sec. 17.
0.40	Gravel road, bears E. and W.
16.10	Asphalt-surfaced road, bears NW. and SE.
19.928	The C-S 1/16 sec. cor. of sec. 17. <hr/>
	N. 0°06'00" E., beginning new measurement.
20.008	The center 1/4 sec. cor. of sec. 17. <hr/>
	N. 0°21'40" W., beginning new measurement.
20.018	The C-N 1/16 sec. cor. of sec. 17. <hr/>
	N. 0°00'10" E., beginning new measurement.
19.915	The 1/4 sec. cor. of secs. 8 and 17. <hr/>

FURTHER SUBDIVISION OF SECTION 17,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the C-E 1/16 sec. cor. of sec. 17.
	N. 0°17'10" W., on the N. and S. center line of the NE1/4 of sec. 17.
20.008	The NE 1/16 sec. cor. of sec. 17.
	N. 0°02'50" W., beginning new measurement.
19.911	The E 1/16 sec. cor. of secs. 8 and 17.
	From the E 1/16 sec. cor. of secs. 17 and 20.
	N. 0°16'30" E., on the N. and S. center line of the SE1/4 of sec. 17.
19.943	The SE 1/16 sec. cor. of sec. 17.
	N. 0°02'50" E., beginning new measurement.
20.013	The C-E 1/16 sec. cor. of sec. 17.
	From the W 1/16 sec. cor. of secs. 17 and 20.
	N. 0°01'40" W., on the N. and S. center line of the SW1/4 of sec. 17.
19.924	The SW 1/16 sec. cor. of sec. 17.
	N. 0°09'10" E., beginning new measurement.
20.003	The C-W 1/16 sec. cor. of sec. 17.
	N. 0°26'10" W., on the N. and S. center line of the NW1/4 of sec. 17.
20.029	The NW 1/16 sec. cor. of sec. 17.
	N. 0°03'20" E., beginning new measurement.
4.00	Asphalt-surfaced road, nears NW. and SE.
19.918	The W 1/16 sec. cor. of secs. 8 and 17.

FURTHER SUBDIVISION OF SECTION 18,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the 1/4 sec. cor. of secs. 18 and 19.
	N. 0°06'00" W., on the N. and S. center line of sec. 18.
19.997	The C-S 1/16 sec. cor. of sec. 18.
	N. 0°03'40" W., beginning new measurement.
19.980	The center 1/4 sec. cor. of sec. 18.
	N. 0°03'10" W., beginning new measurement.
19.994	The C-N 1/16 sec. cor. of sec. 18.
	N. 0°10'50" W., beginning new measurement.
19.995	The 1/4 sec. cor. of secs. 7 and 18.
	From the C-E 1/16 sec. cor. of sec. 18.
	N. 0°06'30" W., on the N. and S. center line of the NE1/4 of sec. 18.
20.002	The NE 1/16 sec. cor. of sec. 18.
	N. 0°09'10" W., beginning new measurement.
0.05	Cor. of fences extending N., S., E. and W.
19.998	The E 1/16 sec. cor. of secs. 7 and 18.
	From the E 1/16 sec. cor. of secs. 18 and 19.
	N. 0°06'40" W., on the N. and S. center line of the SE1/4 of sec. 18.
19.980	The SE 1/16 sec. cor. of sec. 18.
	N. 0°03'00" W., beginning new measurement.
0.03	Cor. of fences extending S. and E.
19.956	The C-E 1/16 sec. cor. of sec. 18.

FURTHER SUBDIVISION OF SECTION 18,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the W 1/16 sec. cor. of secs. 18 and 19.</p> <p>N. 0°09'20" W., on the N. and S. center line of the SW1/4 of sec. 18.</p>
20.009	<p>The SW 1/16 sec. cor. of sec. 18.</p> <hr/> <p>N. 0°05'30" W., beginning new measurement.</p>
19.990	<p>The C-W 1/16 sec. cor. of sec. 18.</p> <hr/> <p>N. 0°00'10" E., on the N. and S. center line of the NW1/4 of sec. 18.</p>
19.987	<p>The NW 1/16 sec. cor. of sec. 18.</p> <hr/> <p>N. 0°12'30" W., beginning new measurement.</p>
19.992	<p>The W 1/16 sec. cor. of secs. 7 and 18.</p> <hr/> <p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 19, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 19.</p> <p>N. 0°05'40" W., on the N. and S. center line of the NE1/4 of sec. 19.</p>
19.987	<p>Point for the NE 1/16 sec. cor. of sec. 19, at intersection with the E. and W. center line of the NE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S19</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located in a fence, bears E. and W., 10 lks. W. of the cor. of fences extending N., E. and W.</p>
39.974	<p>The E 1/16 sec. cor. of secs. 18 and 19.</p> <hr/>

FURTHER SUBDIVISION OF SECTION 19,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the true point for the N 1/16 sec. cor. of secs. 19 and 20.</p> <p>S. 89°59'10" W., on the E. and W. center line of the NE1/4 of sec. 19.</p>
19.991	The NE 1/16 sec. cor. of sec. 19.
20.09	Cor. of fences extending N., E. and W.
39.982	The C-N 1/16 sec. cor. of sec. 19.
	<hr/> <p>From the E 1/16 sec. cor. of secs. 19 and 30.</p> <p>N. 0°05'00" W., on the N. and S. center line of the SE1/4 of sec. 19.</p>
19.999	<p>Point for the SE 1/16 sec. cor. of sec. 19, at intersection with the E. and W. center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S19</p> <p style="text-align: center;">2004</p> <p>From this cor., a rebar of unknown origin, 1/2 in. diam., firmly set, projecting 3 ins. above the ground, bears N. 21°02' W., 0.05 chs. dist. This rebar cannot be reconciled with proper procedures and was not utilized during the course of this survey.</p>
39.85	Dirt road, 15 lks. wide, bears E. and W.
39.998	The C-E 1/16 sec. cor. of sec. 19.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 19 and 20.</p> <p>N. 89°59'00" W., on the E. and W. center line of the SE1/4 of sec. 19.</p>
19.973	The SE 1/16 sec. cor. of sec. 19.
39.946	The C-S 1/16 sec. cor. of sec. 19.
	<hr/> <p>From the W 1/16 sec. cor. of secs. 19 and 30.</p> <p>N. 0°06'10" W., on the N. and S. center line of the SW1/4 of sec. 19.</p>

FURTHER SUBDIVISION OF SECTION 19,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.997	<p>Point for the SW 1/16 sec. cor. of sec. 19, at intersection with the E. and W. center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S19</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
39.994	<p>The C-W 1/16 sec. cor. of sec. 19.</p> <hr/> <p>From the C-S 1/16 sec. cor. of sec. 19.</p> <p>N. 89°56'50" W., on the E. and W center line of the SW1/4 of sec. 19.</p>
19.968	<p>The SW 1/16 sec. cor. of sec. 19.</p>
31.50	<p>Center of airport runway, bears N. and S.</p>
39.26	<p>Fence, bears N. and S.</p>
39.326	<p>The S 1/16 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 19.</p> <p>N. 0°10'40" W., on the N. and S. center line of the NW1/4 of sec. 19.</p>
19.988	<p>Point for the NW 1/16 sec. cor. of sec. 19, at intersection with the E. and W. center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S19</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>

FURTHER SUBDIVISION OF SECTION 19,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.19	Fence, bears E. and W.
39.959	The W 1/16 sec. cor. of secs. 18 and 19.
	<hr/>
	From the C-N 1/16 sec. cor. of sec. 19.
	N. 89°55'10" W., on the E. and W. center line of the NW1/4 of sec. 19.
19.982	The NW 1/16 sec. cor. of sec. 19.
39.19	Fence, bears N. and S.
39.269	The N 1/16 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp.
	<hr/>
	SUBDIVISION OF SECTION 20, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the 1/4 sec. cor. of secs. 20 and 29.
	N. 0°01'00" E., on the N. and S. center line of sec. 20.
20.008	The C-S 1/16 sec. cor. of sec. 20.
	<hr/>
	N. 0°19'40" W., beginning new measurement.
19.970	The center 1/4 sec. cor. of sec. 20.
	<hr/>
	N. 0°02'40" E., beginning new measurement.
20.022	The C-N 1/16 sec. cor. of sec. 20.
	<hr/>
	N. 0°15'10" W., beginning new measurement.
19.83	Fence, bears E. and W.
20.014	The 1/4 sec. cor. of secs. 17 and 20.
	<hr/>
	From the C-E 1/16 sec. cor. of sec. 20.
	N. 0°22'00" W., on the N. and S. center line of the NE1/4 of sec. 20.

FURTHER SUBDIVISION OF SECTION 20,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.30	Fence, bears E. and W.
19.976	The NE 1/16 sec. cor. of sec. 20. <hr/>
	N. 0°05'10" W., beginning new measurement.
14.50	Asphalt-surface road, bears NW. and SE.
19.968	The E 1/16 sec. cor. of secs. 17 and 20. <hr/>
	From the E 1/16 sec. cor. of secs. 20 and 29.
	N. 0°02'20" E., on the N. and S. center line of the SE1/4 of sec. 20.
20.013	The SE 1/16 sec. cor. of sec. 20. <hr/>
	N. 0°16'20" W., beginning new measurement.
19.75	Fence, bears E. and W.
20.045	The C-E 1/16 sec. cor. of sec. 20. <hr/>
	From the W 1/16 sec. cor. of secs. 20 and 29.
	N. 0°02'30" W., on the N. and S. center line of the SW1/4 of sec. 20.
20.008	The SW 1/16 sec. cor. of sec. 20. <hr/>
	N. 0°06'20" W., beginning new measurement.
19.995	The C-W 1/16 sec. cor. of sec. 20. <hr/>
	N. 0°18'20" W., on the N. and S. center line of the NW1/4 of sec. 20.
20.019	The NW 1/16 sec. cor. of sec. 20. <hr/>
	N. 0°01'00" E., beginning new measurement.
19.997	The W 1/16 sec. cor. of secs. 17 and 20. <hr/>

FURTHER SUBDIVISION OF SECTION 21,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the 1/4 sec. cor. of secs. 21 and 28.
	N. 0°04'10" E., on the N. and S. center line of sec. 21.
20.172	The C-S 1/16 sec. cor. of sec. 21. _____
	N. 0°14'20" W., beginning new measurement.
19.862	The center 1/4 sec. cor. of sec. 21. _____
	N. 0°04'50" W., beginning new measurement.
19.95	Fence, bears E. and W.
20.097	The C-N 1/16 sec. cor. of sec. 21. _____
	N. 1°01'00" E., beginning new measurement.
19.476	The 1/4 sec. cor. of secs. 16 and 21. _____
	From the C-E 1/16 sec. cor. of sec. 21.
	N. 0°02'20" W., on the N. and S. center line of the NE1/4 of sec. 21.
20.051	The true point for the NE 1/16 sec. cor. of sec. 21. _____
	N. 0°25'00" E., beginning new measurement.
19.749	The E 1/16 sec. cor. of secs. 16 and 21. _____
	From the E 1/16 sec. cor. of secs. 21 and 28.
	N. 0°05'20" E., on the N. and S. center line of the SE1/4 of sec. 21.
20.038	The SE 1/16 sec. cor. of sec. 21. _____
	N. 0°13'30" W., beginning new measurement.
19.916	The C-E 1/16 sec. cor. of sec. 21. _____

FURTHER SUBDIVISION OF SECTION 21,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the W 1/16 sec. cor. of secs. 21 and 28. N. 0°09'00" E., on the N. and S. center line of the SW1/4 of sec. 21.
20.287	The SW 1/16 sec. cor. of sec. 21. <hr/>
	N. 0°17'20" W., beginning new measurement.
19.928	The C-W 1/16 sec. cor. of sec. 21. <hr/>
	N. 0°11'10" W., on the N. and S. center line of the NW1/4 of sec. 21.
20.043	The true point for the NW 1/16 sec. cor. of sec. 21. <hr/>
	N. 0°21'10" E., beginning new measurement.
19.731	The W 1/16 sec. cor. of secs. 16 and 21. <hr/>
FURTHER SUBDIVISION OF SECTION 22, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA	
	From the 1/4 sec. cor. of secs. 22 and 27. N. 0°12'20" W., on the N. and S. center line of sec. 22.
0.61	Fence, bears E. and W.
19.876	The C-S 1/16 sec. cor. of sec. 22. <hr/>
	N. 0°15'50" W., beginning new measurement.
14.10	Improved gravel road, bears NW and SE.
17.60	Owyhee River, 2 chs. wide, course NW.
19.76	Fence, bears E. and W.
20.059	The center 1/4 sec. cor. of sec. 22. <hr/>
	N. 0°04'20" W., beginning new measurement.
19.70	Fence, bears E. and W., 5 lks. E. of the cor. of fences extending N. and E.

FURTHER SUBDIVISION OF SECTION 22,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.80	From this point, the cor. of fences extending S. and E., bears W. at 5 lks. dist.
20.008	The C-N 1/16 sec. cor. of sec. 22. <hr/>
	N. 0°19'50" W., beginning new measurement.
19.44	Fence, bears E. and W.
19.907	The 1/4 sec. cor. of secs. 15 and 22. <hr/>
	From the C-E 1/16 sec. cor. of sec. 22.
	N. 0°05'00" W., on the N. and S. center line of the NE1/4 of sec. 22.
0.10	Irrigation Ditch, 6 lks. wide, 1 ft. deep, drains W
19.72	Cor. of fences extending E., W. and S.
20.017	The NE 1/16 sec. cor. of sec. 22. <hr/>
	N. 0°12'40" W., beginning new measurement.
19.47	Fence, bears E. and W.
19.966	The E 1/16 sec. cor. of secs. 15 and 22. <hr/>
	From the E 1/16 sec. cor. of secs. 22 and 27.
	N. 0°13'20" W., on the N. and S. center line of the SE1/4 of sec. 22.
0.59	Fence, bears E. and W.
8.00	Improved gravel road, bears NW. and SE.
10.30	Owyhee River, 2 chs. wide, course NW.
19.80	Fence, bears E. and W.
19.868	The SE 1/16 sec. cor. of sec. 22. <hr/>
	N. 0°23'50" W., beginning new measurement.
20.086	The C-E 1/16 sec. cor. of sec. 22. <hr/>

FURTHER SUBDIVISION OF SECTION 22,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the W 1/16 sec. cor. of secs. 22 and 27.
	N. 0°11'10" W., on the N. and S. center line of the SW1/4 of sec. 22.
0.56	Fence, bears E. and W.
19.75	Cor. of fences extending E., W. and S.
19.883	The SW 1/16 sec. cor. of sec. 22.
	<hr/>
	N. 0°07'50" W., beginning new measurement.
0.27	Fence, bears E. and W., 3 lks. E. of the cor. of fences extending N. and E.
20.032	The C-W 1/16 sec. cor. of sec. 22.
	<hr/>
	N. 0°03'50" W., on the N. and S. center line of the NW1/4 of sec. 22.
20.000	The NW 1/16 sec. cor. of sec. 22.
	<hr/>
	N. 0°27'00" W., beginning new measurement.
3.80	Owyhee River, 2 chs. wide, course NW.
19.43	Fence, bears E. and W.
19.848	The W 1/16 sec. cor. of secs. 15 and 22.
	<hr/>
	FURTHER SUBDIVISION OF SECTION 23, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the E 1/16 sec. cor. of secs. 23 and 26.
	N. 0°48'10" E., on the N. and S. center line of the SE1/4 of sec. 23.
20.239	Point for the SE 1/16 sec. cor. of sec. 23, at intersection with the E. and W. center line of the SE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, in a collar of stone, 2 ft. base, with brass cap mkd.

FURTHER SUBDIVISION OF SECTION 23,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	SE 1/16 S23
	2006
40.279	The C-E 1/16 sec. cor. of sec. 23.
	<hr/> <p data-bbox="430 495 1494 537">From the S 1/16 sec. cor. of secs. 23 and 24.</p> <p data-bbox="430 537 1494 621">S. 89°55'50" W., on the E. and W. center line of the SE1/4 of sec. 23.</p>
20.315	The SE 1/16 sec. cor. of sec. 23.
40.221	The C-S 1/16 sec. cor. of sec. 23.
	<hr/> <p data-bbox="430 747 1494 789">From the W 1/16 sec. cor. of secs. 23 and 26.</p> <p data-bbox="430 789 1494 873">N. 0°44'50" E., on the N. and S. center line of the SW1/4 of sec. 23.</p>
20.181	The SW 1/16 sec. cor. of sec. 23.
	<hr/> <p data-bbox="430 957 1494 999">N. 0°18'00" W., beginning new measurement.</p>
0.20	Irrigation ditch, 10 lks. wide, 2 ft. deep, drains W.
19.954	The C-W 1/16 sec. cor. of sec. 23.
	<hr/> <p data-bbox="430 1125 1494 1209">N. 0°10'20" W., on the N. and S. center line of the NW1/4 of sec. 23.</p>
0.20	Irrigation ditch, 10 lks. wide, 2 ft. deep, drains W.
7.00	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 23° W., and S. 28° E.
19.998	The NW 1/16 sec. cor. of sec. 23.
	<hr/> <p data-bbox="430 1377 1494 1419">N. 0°01'50" W., beginning new measurement.</p>
20.043	The W 1/16 sec. cor. of secs. 14 and 23.
	<hr/> <p data-bbox="430 1503 1494 1545" style="text-align: center;">FURTHER SUBDIVISION OF SECTION 26, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p data-bbox="430 1545 1494 1587">From the 1/4 sec. cor. of secs. 26 and 35.</p> <p data-bbox="430 1587 1494 1629">N. 0°08'30" E., on the N. and S. center line of sec. 26.</p>

FURTHER SUBDIVISION OF SECTION 26,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
13.70	Improved gravel road, bears NW. and SE.
19.904	The C-S 1/16 sec. cor. of sec. 26. <hr/>
	N. 0°19'50" W., beginning new measurement.
5.80	Owyhee River, 2 chs. wide, course NW.
20.008	The center 1/4 sec. cor. of sec. 26. <hr/>
	N. 0°10'40" E., beginning new measurement.
19.84	Fence, bears E. and W.
19.919	The C-N 1/16 sec. cor. of sec. 26. <hr/>
	N. 1°34'40" W., beginning new measurement.
19.806	The 1/4 sec. cor. of secs. 23 and 26. <hr/>
	From the C-E 1/16 sec. cor. of sec. 26.
	N. 0°03'40" E., on the N. and S. center line of the NE1/4 of sec. 26.
5.60	Nevada State Route 225, asphalt-surfaced, 45 lks. wide, bears N. 15° W. and. S. 15° E.
19.947	The NE 1/16 sec. cor. of sec. 26. <hr/>
	N. 2°01'20" W., beginning new measurement.
19.699	The E 1/16 sec. cor. of secs. 23 and 26. <hr/>
	From the E 1/16 sec. cor. of secs. 26 and 35.
	N. 0°03'10" E., on the N. and S. center line of the SE1/4 of sec. 26.
19.934	The SE 1/16 sec. cor. of sec. 26. <hr/>
	N. 0°11'20" W., beginning new measurement.

FURTHER SUBDIVISION OF SECTION 26,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
4.047	Intersect line 1-2 of Lot 3, Sec. 26, from which Angle Point No. 1 bears S. 89°59'40" E., 4.495 chs. dist., hereinafter described.
19.990	The C-E 1/16 sec. cor. of sec. 26. <hr/>
	From the W 1/16 sec. cor. of secs. 26 and 35. N. 0°00'20" W., on the N. and S. center line of the SW1/4 of sec. 26.
19.925	The true point for the SW 1/16 sec. cor. of sec. 26. <hr/>
	N. 0°14'10" W., beginning new measurement.
19.975	The C-W 1/16 sec. cor. of sec. 26. <hr/>
	N. 0°17'40" E., on the N. and S. center line of the NW1/4 of sec. 26.
19.83	Fence, bears E. and W.
19.892	The NW 1/16 sec. cor. of sec. 26. <hr/>
	N. 1°08'20" W., beginning new measurement.
0.15	Irrigation ditch, 15 lks. wide, 4 ft. deep, drains W.
4.50	Improved gravel road, bears NW. and SE.
5.80	Owyhee River, 2 chs. wide, course NW.
19.915	The W 1/16 sec. cor. of secs. 23 and 26. <hr/>
	FURTHER SUBDIVISION OF SECTION 27, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>
	From the 1/4 sec. cor. of secs. 27 and 34. N. 0°01'50" E., on the N. and S. center line of sec. 27.
19.977	The C-S 1/16 sec. cor. of sec. 27. <hr/>

FURTHER SUBDIVISION OF SECTION 27,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°29'10" W., beginning new measurement.
19.964	The center 1/4 sec. cor. of sec. 27. <hr/>
	N. 0°08'20" E., beginning new measurement.
19.78	Fence, bears E. and W.
19.980	The C-N 1/16 sec. cor. of sec. 27. <hr/>
	N. 0°13'00" E., beginning new measurement.
19.39	Fence, bears E. and W.
20.001	The 1/4 sec. cor. of secs. 22 and 27. <hr/>
	From the C-E 1/16 sec. cor. of sec. 27.
	N. 0°11'40" E., on the N. and S. center line of the NE1/4 of sec. 27.
0.38	Intersection of canals, each 30 lks. wide, extending E., W. and N., drains W. and N.
0.54	Fence, bears E. and W., 7 lks. E. of the cor. of fences extending N. and W. and on projection of fence extending E.
19.93	Fence, bears E. and W.
19.975	The NE 1/16 sec. cor. of sec. 27. <hr/>
	N. 0°19'40" E., beginning new measurement.
19.42	Fence, bears E. and W.
20.011	The E 1/16 sec. cor. of secs. 22 and 27. <hr/>
	From the E 1/16 sec. cor. of secs. 27 and 34.
	N. 0°03'30" W., on the N. and S. center line of the SE1/4 of sec. 27.
19.960	The SE 1/16 sec. cor. of sec. 27. <hr/>
	N. 0°31'10" W., beginning new measurement.

FURTHER SUBDIVISION OF SECTION 27,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.78	Fence, bears E. and W., 2 lks. W. of the cor. of fences extending E., W. and S.
19.940	The C-E 1/16 sec. cor. of sec. 27. <hr/>
	From the W 1/16 sec. cor. of secs. 27 and 34. N. 0°07'10" W., on the N. and S. center line of the SW1/4 of sec. 27.
20.01	Fence, bears E. and W.
20.024	The SW 1/16 sec. cor. of sec. 27. <hr/>
	N. 0°10'20" W., beginning new measurement.
19.949	The C-W 1/16 sec. cor. of sec. 27. <hr/>
	N. 0°02'20" E., on the N. and S. center line of the NW1/4 of sec. 27.
19.991	The NW 1/16 sec. cor. of sec. 27. <hr/>
	N. 0°06'30" E., beginning new measurement.
19.37	Fence, bears E. and W.
19.991	The W 1/16 sec. cor. of secs. 22 and 27. <hr/>
FURTHER SUBDIVISION OF SECTION 28, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>	
	From the 1/4 sec. cor. of secs. 28 and 33. N. 0°11'30" W., on the N. and S. center line of sec. 28.
19.68	Fence, bears E. and W.
19.966	The true point for the C-S 1/16 sec. cor. of sec. 28. <hr/>
	N. 0°25'20" W., beginning new measurement.
19.962	The center 1/4 sec. cor. of sec. 28. <hr/>

FURTHER SUBDIVISION OF SECTION 28,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°05'10" W., beginning new measurement.
0.28	Fence, bears E. and W., 2 lks. W. of the cor. of fences extending N., E. and W.
20.015	The C-N 1/16 sec. cor. of sec. 28. <hr/>
	N. 0°06'40" W., beginning new measurement.
19.821	The 1/4 sec. cor. of secs. 21 and 28. <hr/>
	From the C-E 1/16 sec. cor. of sec. 28.
	N. 0°17'20" W., on the N. and S. center line of the NE1/4 of sec. 28.
0.34	Cor. of fences extending N., E. and W.
20.009	The NE 1/16 sec. cor. of sec. 28. <hr/>
	N. 0°00'20" E., beginning new measurement.
19.949	The E 1/16 sec. cor. of secs. 21 and 28. <hr/>
	From the E 1/16 sec. cor. of secs. 28 and 33.
	N. 0°15'20" W., on the N. and S. center line of the SE1/4 of sec. 28.
19.949	The SE 1/16 sec. cor. of sec. 28. <hr/>
	N. 0°00'30" E., beginning new measurement.
19.80	Cor. of fences extending S., E. and W.
19.979	The C-E 1/16 sec. cor. of sec. 28. <hr/>
	From the W 1/16 sec. cor. of secs. 28 and 33.
	N. 0°07'50" W., on the N. and S. center line of the SW1/4 of sec. 28.
19.984	The true point for the SW 1/16 sec. cor. of sec. 28. <hr/>

FURTHER SUBDIVISION OF SECTION 28,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°36'10" W., beginning new measurement.
19.84	Fence, bears E. and W.
19.986	The C-W 1/16 sec. cor. of sec. 28.
	<hr/>
	N. 0°10'10" E., on the N. and S. center line of the NW1/4 of sec. 28.
0.25	Fence, bears E. and W., 1.5 lks. W. of the cor. of fences extending N., E. and W.
19.965	The NW 1/16 sec. cor. of sec. 28.
	<hr/>
	N. 0°32'00" W., beginning new measurement.
19.708	The W 1/16 sec. cor. of secs. 21 and 28.
	<hr/>
	FURTHER SUBDIVISION OF SECTION 29, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the C-E 1/16 sec. cor. of sec. 29.
	N. 0°19'10" W., on the N. and S. center line of the NE1/4 of sec. 29.
19.94	Fence, bears E. and W., 10.5 lks. E. of the cor. of fences extending N., S., E. and W.
19.974	Point for the NE 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the NE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NE 1/16 S29
	2005
	Set a steel sign post, 6 ft. long, alongside the stainless steel post.
39.94	Cor. of fences extending S., E. and W.
39.954	The E 1/16 sec. cor. of secs. 20 and 29.
	<hr/>

FURTHER SUBDIVISION OF SECTION 29,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>N. 89°50'20" W., on the E. and W. center line of the NE1/4 of sec. 29.</p>
20.163	The NE 1/16 sec. cor. of sec. 29.
20.27	Fence, bears N. and S., 3 lks. N. of the cor. of fences extending N., S., E. and W.
40.222	The C-N 1/16 sec. cor. of sec. 29.
	<hr/> <p>From the E 1/16 sec. cor. of 29 and 32.</p> <p>N. 0°08'10" W., on the N. and S. center line of the SE1/4 of sec. 29.</p>
0.59	Fence, bears E. and W.
19.994	<p>Point for the SE 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S29</p> <p style="text-align: center;">2005</p>
39.968	The C-E 1/16 sec. cor. of sec. 29.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 28 and 29.</p> <p>N. 89°54'10" W., on the E. and W. center line of the SE1/4 of sec. 29.</p>
0.07	Canal, 7.5 lks. wide, 1 ft. deep, drains N.
20.130	The SE 1/16 sec. cor. of sec. 29.
40.241	The C-S 1/16 sec. cor. of sec. 29.
	<hr/> <p>From the W 1/16 sec. cor. of secs. 29 and 32.</p> <p>N. 0°09'40" W., on the N. and S. center line of the SW1/4 of sec. 29.</p>
0.59	Fence, bears E. and W.

FURTHER SUBDIVISION OF SECTION 29,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.002	<p>Point for the SW 1/16 sec. cor. of sec. 16, at intersection with the E. and W. center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S29</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
40.004	<p>The C-W 1/16 sec. cor. of sec. 29.</p> <hr/> <p>From the C-S 1/16 sec. cor. of sec. 29.</p> <p>N. 89°54'10" W., on the E. and W. center line of the SW1/4 of sec. 29.</p>
19.97	Fence, bears N. and S.
20.004	The SW 1/16 sec. cor. of sec. 29.
39.72	Fence, bears N. and S.
40.008	<p>The S 1/16 sec. cor. of secs. 29 and 30.</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 29.</p> <p>N. 0°08'40" W., on the N. and S. center line of the NW1/4 of sec. 29.</p>
19.986	<p>Point for the NW 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S29</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p> <p>Cor. is located 1.5 lks. W. of fence, bears N. and S.</p>
39.972	<p>The W 1/16 sec. cor. of secs. 20 and 29.</p> <hr/>

FURTHER SUBDIVISION OF SECTION 29,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the C-N 1/16 sec. cor. of sec. 29.
	N. 89°51'00" W., on the E. and W. center line of the NW1/4 of sec. 29.
19.98	Fence, bears N. and S.
19.999	The NW 1/16 sec. cor. of sec. 29.
39.998	The N 1/16 sec. cor. of secs. 29 and 30.
<hr/>	
FURTHER SUBDIVISION OF SECTION 30, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA	
<hr/>	
	From the C-E 1/16 sec. cor. of sec. 30.
	N. 0°08'00" W., on the N. and S. center line of the NE1/4 of sec. 30.
19.987	Point for the NE 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the NE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NE 1/16 S30
	2004
	Set a steel sign post, 6 ft. long, alongside the stainless steel post.
20.04	Fence, bears E. and W., 28 lks. E. of the cor. of fences extending N., S., E. and W.
39.67	Cor. of fences extending S., E. and W.
39.974	The E 1/16 sec. cor. of secs. 19 and 30.
<hr/>	
	From the N 1/16 sec. cor. of secs. 29 and 30.
	N. 89°56'50" W., on the E. and W. center line of the NE1/4 of sec. 30.
19.978	The NE 1/16 sec. cor. of sec. 30.
20.25	Fence, bears N. and S., 5 lks. S. of the cor. of fences extending N., S., E. and W.
39.956	The C-N 1/16 sec. cor. of sec. 30.
<hr/>	

FURTHER SUBDIVISION OF SECTION 30,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the E 1/16 sec. cor. of secs. 30 and 31.</p> <p>N. 0°07'30" W., on the N. and S. center line of the SE1/4 of sec. 30.</p>
0.61	Fence, bears E. and W.
19.993	<p>Point for the SE 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S30</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
20.05	Fence, bears E. and W.
39.986	The C-E 1/16 sec. cor. of sec. 30.
<hr/>	
	<p>From the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>N. 89°52'20" W., on the E. and W. center line of the SE1/4 of sec. 30.</p>
0.29	Fence, bears N. and S.
19.993	The SE 1/16 sec. cor. of sec. 30.
39.97	Cor. of fences extending N., S. and E.
39.986	The C-S 1/16 sec. cor. of sec. 30.
<hr/>	
	<p>From the W 1/16 sec. cor. of secs. 30 and 31.</p> <p>N. 0°09'40" W., on the N. and S. center line of the SW1/4 of sec. 30.</p>
19.972	<p>Point for the SW 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S30</p> <p style="text-align: center;">2004</p>

FURTHER SUBDIVISION OF SECTION 30,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.21	Fence, bears ESE. and WNW.
30.20	Gravel road, bears NW. and SE.
39.92	Fence, bears E. and W.
39.944	The C-W 1/16 sec. cor. of sec. 30.
	<hr/>
	From the C-S 1/16 sec. cor. of sec. 30.
	S. 89°57'50" W., on the E. and W. center line of the SW1/4 of sec. 30.
8.50	Gravel road, bears NW. and SE.
19.954	The SW 1/16 sec. cor. of sec. 30.
39.42	Fence, bears N. and S.
39.439	The S 1/16 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.
	<hr/>
	From the C-W 1/16 sec. cor. of sec. 30.
	N. 0°06'40" W., on the N. and S. center line of the NW1/4 of sec. 30.
19.995	Point for the NW 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the NW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NW 1/16 S30
	2004
	Set a steel sign post, 6 ft. long, alongside the stainless steel post.
39.70	Fence, bears E. and W.
39.990	The W 1/16 sec. cor. of secs. 19 and 30.
	<hr/>
	From the C-N 1/16 sec. cor. of sec. 30.
	WEST, on the E. and W. center line of the NW1/4 of sec. 30.

FURTHER SUBDIVISION OF SECTION 30,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.969	The NW 1/16 sec. cor. of sec. 30.
31.50	Center of airport runway, bears N. and S.
39.08	Fence, bears E. and W.
39.369	The N 1/16 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.
<hr/>	
FURTHER SUBDIVISION OF SECTION 31, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA	
<hr/>	
	From the C-E 1/16 sec. cor. of sec. 31.
	N. 0°06'20" W., on the N. and S. center line of the NE1/4 of sec. 31.
19.976	Point for the NE 1/16 sec. cor. of sec. 31, at intersection with the E. and W. center line of the NE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NE 1/16 S31
	2004
	Set a steel sign post, 6 ft. long, alongside the stainless steel post.
39.36	Fence, bears E. and W.
39.952	The E 1/16 sec. cor. of secs. 30 and 31.
<hr/>	
	From the N 1/16 sec. cor. of secs. 31 and 32.
	N. 89°53'10" W., on the E. and W. center line of the NE1/4 of sec. 31.
20.021	The NE 1/16 sec. cor. of sec. 31.
40.042	The C-N 1/16 sec. cor. of sec. 31.
<hr/>	
	From the E 1/16 cor. of secs. 6 and 31, on the S. bdy. of the Tp.
	N. 0°02'50" W., on the N. and S. center line of the SE1/4 of sec. 31.

FURTHER SUBDIVISION OF SECTION 31,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.002	<p>Point for the SE 1/16 sec. cor. of sec. 31, at intersection with the E. and W. center line of the SE1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S31</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
40.004	<p>The C-E 1/16 sec. cor. of sec. 31.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 31 and 32.</p> <p>N. 89°56'50" W., on the E. and W. center line of the SE1/4 of sec. 31.</p>
20.022	<p>The SE 1/16 sec. cor. of sec. 31.</p>
40.044	<p>The C-S 1/16 sec. cor. of sec. 31.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.</p> <p>N. 0°00'10" E., on the N. and S. center line of the SW1/4 of sec. 31.</p>
0.01	<p>Fence, bears E. and W.</p>
19.988	<p>Point for the SW 1/16 sec. cor. of sec. 31, at intersection with the E. and W. center line of the SW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S31</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
39.975	<p>The C-W 1/16 sec. cor. of sec. 31.</p> <hr/>

FURTHER SUBDIVISION OF SECTION 31,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-S 1/16 sec. cor. of sec. 31.</p> <p>N. 89°57'30" W., on the E. and W. center line of the SW1/4 of sec. 31.</p>
19.974	The SW 1/16 sec. cor. of sec. 31.
39.530	The S 1/16 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp.
	<hr/> <p>From the C-W 1/16 sec. cor. of sec. 31.</p> <p>N. 0°03'20" W., on the N. and S. center line of the NW1/4 of sec. 31.</p>
19.993	<p>Point for the NW 1/16 sec. cor. of sec. 31, at intersection with the E. and W. center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S31</p> <p style="text-align: center;">2004</p> <p>Set a steel sign post, 6 ft. long, 1 ft., S. of the cor.</p>
39.986	The W 1/16 sec. cor. of secs. 30 and 31.
	<hr/> <p>From the C-N 1/16 sec. cor. of sec. 31.</p> <p>S. 89°59'30" W., on the E. and W. center line of the NW1/4 of sec. 31.</p>
19.936	The NW 1/16 sec. cor. of sec. 31.
39.493	The N 1/16 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp.
	<hr/> <p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 32, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 32.</p> <p>N. 0°08'10" E., on the N. and S. center line of the NE1/4 of sec. 32.</p>
19.20	Improved gravel road, 25 lks. wide, bears NE. and SW.

FURTHER SUBDIVISION OF SECTION 32,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.972	Point for the NE 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the NE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	NE 1/16 S32
	2005
	Cor. is located 4.5 lks. E. of the cor. of fences extending NE., SW. and W.
39.37	Fence, bears E. and W.
39.944	The E 1/16 sec. cor. of secs. 29 and 32.
	From the N 1/16 sec. cor. of secs. 32 and 33.
	N. 89°52'40" W., on the E. and W. center line of the NE1/4 of sec. 32.
0.56	Canal, 20 lks. wide, 2 ft. deep, drains N.
19.40	Improved gravel road, 25 ft. wide, bears NE. and SW.
20.054	The NE 1/16 sec. cor. of sec. 32.
20.09	Cor. of fences extending NE., SW. and W.
40.108	The C-N 1/16 sec. cor. of sec. 32.
	From the E 1/16 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.
	N. 0°08'20" W., on the N. and S. center line of the SE1/4 of sec. 32.
19.98	Fence, bears E. and W.
19.998	Point for the SE 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the SE1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SE 1/16 S32
	2004

FURTHER SUBDIVISION OF SECTION 32,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a steel sign post, 6 ft. long, alongside the stainless steel post.
39.990	The C-E 1/16 sec. cor. of sec. 32.
	From the S 1/16 sec. cor. of secs. 32 and 33.
	N. 89°53'20" W., on the E. and W. center line of the SE1/4 of sec. 32.
19.996	The SE 1/16 sec. cor. of sec. 32.
40.000	The C-S 1/16 sec. cor. of sec. 32.
	From the W 1/16 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.
	N. 0°04'30" W., on the N. and S. center line of the SW1/4 of sec. 32.
17.70	Improved gravel road, 25 ft. wide, bears NE. and SW.
19.94	Fence, bears E. and W.
20.004	Point for the SW 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the SW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SW 1/16 S32
	2004
	Set a steel sign post, 6 ft. long, alongside the stainless steel post.
40.008	The C-W 1/16 sec. cor. of sec. 32.
	From the C-S 1/16 sec. cor. of sec. 32.
	N. 89°53'40" W., on the E. and W. center line of the SW1/4 of sec. 32.
0.03	Fence, bears N. and S., 3 lks. N. of the cor. of fences extending N., E. and W.
17.70	Improved gravel road, 25 ft. wide, bears NE. and SW.
19.986	The SW 1/16 sec. cor. of sec. 32.

FURTHER SUBDIVISION OF SECTION 32,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.972	The S 1/16 sec. cor. of secs. 31 and 32.
	<hr/> <p>From the C-W 1/16 sec. cor. of sec. 32.</p> <p>N. 0°04'30" W., on the N. and S. center line of the NW1/4 of sec. 32.</p>
19.959	<p>Point for the NW 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the NW1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">NW 1/16 S32</p> <p style="text-align: center;">2004</p>
	<p>Set a steel sign post, 6 ft. long, alongside the stainless steel post.</p>
19.99	Fence, bears E. and W., 7 lks. W. of the cor. of fences extending N., E. and W.
39.31	Fence, bears E. and W.
39.918	The W 1/16 sec. cor. of secs. 29 and 32.
	<hr/> <p>From the C-N 1/16 sec. cor. of sec. 32.</p> <p>N. 89°54'50" W., on the E. and W. center line of the NW1/4 of sec. 32.</p>
19.983	The NW 1/16 sec. cor. of sec. 32.
39.966	The N 1/16 sec. cor. of secs. 31 and 32.
	<hr/> <p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 33, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp.</p> <p>N. 0°10'00" W., on the N. and S. center line of sec. 33.</p>
19.987	The C-S 1/16 sec. cor. of sec. 33.

FURTHER SUBDIVISION OF SECTION 33,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°27'30" W., beginning new measurement.
19.843	The center 1/4 sec. cor. of sec. 33. <hr/>
	N. 0°19'20" E., beginning new measurement.
20.10	Fence, bears E. and W.
20.119	The C-N 1/16 sec. cor. of sec. 33. <hr/>
	N. 0°16'50" E., beginning new measurement.
20.007	The 1/4 sec. cor. of secs. 28 and 33. <hr/>
	From the C-E 1/16 sec. cor. of sec. 33.
	N. 0°07'00" E., on the N. and S. center line of the NE1/4 of sec. 33.
20.049	The true point for the NE 1/16 sec. cor. of sec. 33. <hr/>
	N. 0°05'20" E., beginning new measurement.
0.07	Fence, bears E. and W., 3 lks. E. of the cor. of fences extending N., S. and E.
20.008	The E 1/16 sec. cor. of secs. 28 and 33. <hr/>
	From the E 1/16 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp.
	N. 0°06'30" W., on the N. and S. center line of the SE1/4 of sec. 33.
20.001	The true point for the SE 1/16 sec. cor. of sec. 33. <hr/>
	N. 0°16'20" W., beginning new measurement.
19.911	The C-E 1/16 sec. cor. of sec. 33. <hr/>
	From the W 1/16 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp.
	N. 0°08'20" W., on the N. and S. center line of the SW1/4 of sec. 33.

FURTHER SUBDIVISION OF SECTION 33,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.97	Fence, bears E. and W.
19.990	The SW 1/16 sec. cor. of sec. 33. <hr/>
	N. 0°17'20" W., beginning new measurement.
19.76	Fence, bears E. and W.
19.915	The C-W 1/16 sec. cor. of sec. 33. <hr/>
	N. 0°18'20" E., on the N. and S. center line of the NW1/4 of sec. 33.
20.03	Fence, bears E. and W.
20.046	The NW 1/16 sec. cor. of sec. 33. <hr/>
	N. 0°17'10" E., beginning new measurement.
19.991	The W 1/16 sec. cor. of secs. 28 and 33. <hr/>
FURTHER SUBDIVISION OF SECTION 34, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA	
	From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp.
	N. 0°01'50" W., on the N. and S. center line of sec. 34.
19.956	The C-S 1/16 sec. cor. of sec. 34. <hr/>
	N. 0°06'10" W., beginning new measurement.
19.974	The center 1/4 sec. cor. of sec. 34. <hr/>
	N. 0°03'40" E., beginning new measurement.
19.991	The C-N 1/16 sec. cor. of sec. 34. <hr/>
	N. 0°03'50" W., beginning new measurement.
20.024	The 1/4 sec. cor. of secs. 27 and 34. <hr/>

FURTHER SUBDIVISION OF SECTION 34,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the C-E 1/16 sec. cor. of sec. 34.
	N. 0°08'10" E., on the N. and S. center line of the NE1/4 of sec. 34.
19.997	The NE 1/16 sec. cor. of sec. 34.
	N. 0°02'40" W., beginning new measurement.
20.030	The E 1/16 sec. cor. of secs. 27 and 34.
	From the E 1/16 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp.
	N. 0°01'50" W., on the N. and S. center line of the SE1/4 of sec. 34.
19.942	The SE 1/16 sec. cor. of sec. 34.
	N. 0°04'00" W., beginning new measurement.
19.951	The C-E 1/16 sec. cor. of sec. 34.
	From the W 1/16 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp.
	N. 0°01'40" W., on the N. and S. center line of the SW1/4 of sec. 34.
0.25	Fence, bears E. and W.
19.970	The SW 1/16 sec. cor. of sec. 34.
	N. 0°08'10" W., beginning new measurement.
19.996	The true point for the C-W 1/16 sec. cor. of sec. 34.
	N. 0°00'50" W., on the N. and S. center line of the NW1/4 of sec. 34.
19.985	The true point for the NW 1/16 sec. cor. of sec. 34.
	N. 0°05'00" W., beginning new measurement.
20.017	The W 1/16 sec. cor. of secs. 27 and 34.

FURTHER SUBDIVISION OF SECTION 35,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.
	N. 0°05'40" W., on the N. and S. center line of sec. 35.
19.953	The C-S 1/16 sec. cor. of sec. 35.
	N. 0°01'30" E., beginning new measurement.
20.002	The center 1/4 sec. cor. of sec. 35.
	N. 0°09'20" E., beginning new measurement.
20.018	The C-N 1/16 sec. cor. of sec. 35.
	N. 0°03'30" W., beginning new measurement.
20.011	The 1/4 sec. cor. of secs. 26 and 35.
	From the true point for the C-E 1/16 sec. cor. of sec. 35.
	N. 0°03'40" E., on the N. and S. center line of the NE1/4 of sec. 35.
20.008	The true point for the NE 1/16 sec. cor. of sec. 35.
	N. 0°00'20" W., beginning new measurement.
20.017	The E 1/16 sec. cor. of secs. 26 and 35.
	From the E 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.
	N. 0°03'50" W., on the N. and S. center line of the SE1/4 of sec. 35.
19.90	Fence, bears E. and W.
19.975	The SE 1/16 sec. cor. of sec. 35.
	N. 0°00'20" W., beginning new measurement.
20.000	The true point for the C-E 1/16 sec. cor. of sec. 35.
	From the W 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.

FURTHER SUBDIVISION OF SECTION 35,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°07'30" W., on the N. and S. center line of the SW1/4 of sec. 35.
19.932	The SW 1/16 sec. cor. of sec. 35. <hr/>
	N. 0°03'20" E., beginning new measurement.
20.004	The C-W 1/16 sec. cor. of sec. 35. <hr/>
	N. 0°07'30" E., on the N. and S. center line of the NW1/4 of sec. 35.
20.019	The NW 1/16 sec. cor. of sec. 35. <hr/>
	N. 0°01'00" E., beginning new measurement.
20.016	The W 1/16 sec. cor. of secs. 26 and 35. <hr/>
FURTHER SUBDIVISION OF SECTION 36, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA	
	From the W 1/16 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp.
	N. 0°09'50" W., on the N. and S. center line of the SW1/4 of sec. 36.
20.006	Point for the SW 1/16 sec. cor. of sec. 36, at intersection with the E. and W. center line of the SW1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, over a plastic-encased magnet, in a mound of stone, 3 ft. base, to top, with brass cap mkd. SW 1/16 S36 2005
40.012	The C-W 1/16 sec. cor. of sec. 36. <hr/>
	From the C-S 1/16 sec. cor. of sec. 36.
	N. 89°48'50" W., on the E. and W. center line of the SW1/4 of sec. 36.
20.028	The SW 1/16 sec. cor. of sec. 36.
40.056	The S 1/16 sec. cor. of secs. 35 and 36. <hr/>

METES-AND-BOUNDS SURVEY OF LOT 3 IN SECTION 26,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The boundary of Lot No. 3 was based on the supplemental plat dated February 8, 1957 and the patent issued May 15, 1957.</p> <p>Beginning at the point for Angle Point No. 1, Lot 3, determined at record angle and distance from Angle Point No. 4, Lot 3.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam. flush with the surface of the ground, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <div style="display: inline-block; vertical-align: middle;"> <div style="border: 1px solid black; padding: 2px; text-align: center;">AP1 LOT 3</div> <div style="margin-left: 10px;">S26</div> </div> <p>2006</p> </div> <p>Thence N. 89°59'40" W., on line 1-2, Lot 3.</p> <p>4.495 Intersect the N. and S. center line of the SE1/4 of sec. 26, from which the SE 1/16 sec. cor. of sec. 26 bears S. 0°11'20" E., 4.047 chs. dist., hereinbefore described.</p> <p>12.062 Point for Angle Point No. 2, Lot 3, determined at record angle and distance from Angle Point No. 3, Lot 3.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., flush with the surface of the ground, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> <p>T47N R52E</p> <div style="display: inline-block; vertical-align: middle;"> <div style="border: 1px solid black; padding: 2px; text-align: center;">AP2 LOT 3</div> <div style="margin-left: 10px;">S26</div> </div> <p>2005</p> </div> <hr style="width: 30%; margin: 10px auto;"/> <p>Thence S. 0°04'10" E., on line 2-3, Lot 3.</p> <p>4.045 Point for Angle Point No. 3, Lot 3, determined at record distance from the SE 1/16 sec. cor. of sec. 26, and on the E-W center line of the SE1/4 of sec. 26, identical with line 3-4 of Lot 3.</p> <p>Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., flush with the surface of the ground, with brass cap, 1 1/2 ins. diam., mkd.</p> <div style="text-align: center;"> <div style="display: inline-block; vertical-align: middle;"> <div style="border: 1px solid black; padding: 2px; text-align: center;">LOT 3 AP3</div> <div style="margin-left: 10px;">S26</div> </div> <div style="margin-left: 10px;"> <p>T47N R52E</p> <p>2006</p> </div> </div> <hr style="width: 30%; margin: 10px auto;"/>
--------	---

METES-AND-BOUNDS SURVEY OF LOT 3 IN SECTION 26,
T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence S. 89°59'10" E., on line 3-4, Lot 3, on a portion of the E-W center line of the SE1/4 of sec. 26.
7.576	The SE 1/16 sec. cor. of sec. 26, hereinbefore described.
12.576	Point for Angle Point No. 4, Lot 3, determined at record distance from the SE1/16 sec. cor. of sec. 26. Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., flush in the ground, with brass cap, 1 1/2 ins. diam., mkd. <div style="text-align: center;"> <div style="display: inline-block; border: 1px solid black; padding: 2px;"> LOT 3 AP4 </div> <div style="display: inline-block; vertical-align: middle; padding: 0 10px;">S26</div> </div> <div style="text-align: center; margin-top: 10px;"> T47N R52E 2006 </div>
	Thence N. 7°18'10" W., on line 4-1, Lot 3.
4.080	Angle Point No. 1, Lot 3, and the point of beginning.
GENERAL DESCRIPTION	
<p>The area contained in this survey ranges from mountainous, rolling to nearly level terrain in the bottom lands, all within the Duck Valley Indian Reservation. The town of Owyhee is located in section 26. Members of the Shoshone-Paiute Tribes have residences and ranches in the area, using the land for growing hay and for grazing cattle and horses. The reservation headquarters is located in section 3, straddling the Idaho-Nevada State Line.</p> <p>Nevada State Route 225 enters in section 36, traveling northwesterly and leaving the township in section 4, at the Idaho-Nevada State Line. The land is drained by numerous canals, sloughs and the Owyhee River, which enters the township in section 36 and flows northwesterly, leaving the township in section 4, on the Idaho-Nevada State Line.</p>	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Don R. Aschenbach	Cadastral Surveyor
Lance A. Barney	Cadastral Surveyor
Richard A. Harrison	Surveying Technician
Mark G. Petrosine	Surveying Technician
Steven E. Dagitz	Student Trainee (Land Surveyor)
Kane M. Hellebust	Student Trainee (Land Surveyor)
Michelle E. Martin	Supervisory Range Technician
Derrick J. Rader	Supervisory Range Technician

CERTIFICATE OF SURVEY

We, Daniel R. Ontiveros, Cadastral Surveyor and Clay W. Morrow, Surveying Technician, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing date of the 21st day of October, 2004, we have dependently resurveyed a portion of the Idaho-Nevada State Line, from Mile Post 104 to Mile Post 111, the south boundary, a portion of the east boundary, the west boundary, a portion of the subdivisional lines, and the subdivision-of-section lines of certain sections, and further subdivided certain sections and surveyed by metes and bounds Lot 3 in section 26, Township 47 North, Range 52 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 25, 2008

(Date)

Daniel R. Ontiveros
/For/ Daniel R. Ontiveros
(Cadastral Surveyor)

September 22, 2008

(Date)

Clay W. Morrow
(Surveying Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the Idaho-Nevada State Line, from Mile Post 104 to Mile Post 111, the south boundary, a portion of the east boundary, the west boundary, a portion of the subdivisional lines, and the subdivision-of-section lines of certain sections, and the further subdivision of certain sections and the metes-and-bound survey of Lot 3 in section 26, Township 47 North, Range 52 East, Mount Diablo Meridian, Nevada, executed by Daniel R. Ontiveros, Cadastral Surveyor and Clay W. Morrow, Surveying Technician, having been critically examined and found correct, are hereby approved.

September 25, 2008

(Date)

Daniel R. Ontiveros
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 47 N., R. 52 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~