

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE NORTH BOUNDARY

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTION 1,

TOWNSHIP 4 SOUTH, RANGE 60 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Joseph J. Johnson, Cadastral Surveyor

Under Special Instructions dated December 18, 2013,

and approved December 18, 2013,

and Supplemental Special Instructions dated May 22, 2015,

and approved May 22, 2015,

which provided for the surveys included under Group No. 929,

and Assignment Instructions dated December 17, 2013.

Survey commenced January 2, 2014

Survey completed May 26, 2015

INDEX DIAGRAM

TOWNSHIP 4 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

				6	4
6	5	4	3	2	1 3 8
7	8	9	10	11	12 2
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 1 pp. 8 - 11.

TOWNSHIP 4 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the east boundary, a portion of the north boundary and a portion of the subdivisional lines, and the subdivision of section 1, Township 4 South, Range 60 East, Mount Diablo Meridian, Nevada.

The south boundary was surveyed by U.S. Deputy Surveyor E.B. Monroe in 1869 under contract No. 31. The east, west and north boundaries were surveyed by U.S. Deputy Surveyor E.B. Monroe in 1870 under contract No. 34. The subdivisional lines were surveyed by U.S. Deputy Surveyor E.B. Monroe in 1870 under Contract No. 35. A portion of the north boundary was dependently resurveyed by Cartographic Aid D.A. Cannon, supervised by Cadastral Surveyor R.C. Yundt in 1958 under Group No. 353. A portion of the First Standard Parallel South (south boundary) was dependently resurveyed by Cadastral Surveyor E.W. Sibley in 1964 under Group No. 422. A portion of the north boundary was dependently resurveyed by Cadastral Surveyors L.A. Barney and J.J. Johnson in 2012-2015 under Group No. 914. During the course of work performed under Group No. 914, retracements revealed that the original 1/4 sec. cor. of secs. 1 and 36, Tps. 3 and 4 S., R. 60 E., set by U.S. Deputy Surveyor Monroe was not recovered in the Cannon and Yundt resurvey. The original Monroe corner was found approximately 2 chains NE of the alleged Cannon-Yundt recovery, resulting in an overlap between the survey by Monroe and the resurvey by Cannon-Yundt from the cor. of Tps. 3 and 4 S., Rgs. 60 and 61 E., and the cor. of secs. 1 and 2, Tps. 3 and 4 S., R. 60 E.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 929, dated December 18, 2013 and Supplemental Special Instructions dated May 22, 2015.

Measurements were made with Trimble R-8 Global Positioning System (GPS) receivers using the real-time kinematic method. The direction of each line is with reference to the true meridian. All bearings are mean bearings and the distances are reported as horizontal measurement at a mean ground elevation of 4000 feet above sea level.

The NAD 1983 (2011) (Epoch:2010.0000) geographic position, of the following corners were determined by GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS), ECHO CORS ARP, CARLTON SQUARE 2 CORS ARP and PIOCHE CORS ARP, and carried forward by RTK observations is as follows.

TOWNSHIP 4 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The 1/4 sec. cor. of sec. 2, on the N. bdy. of the Tp., is as follows:

Latitude: 37°38'07.708" N. Longitude: 115°13'05.406" W.

The cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp. is as follows:

Latitude: 37°36'21.848" N. Longitude: 115°11'27.132" W.

The mean magnetic declination is 15 1/2° E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "Fossil Peak, Nev." dated 1970.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed by
U.S. Deputy Surveyor E.B. Monroe in 1870

Beginning at the cor. of secs. 7, 12, 13 and 18, monumented with a limestone, 12x12x6 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 4 notches on the S. edge and 2 notches on the N. edge.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

T4S	
R60E	R61E
S12	S 7

S13	S18

2015

Bury mkd. stone in mound of stone.

N. 0°06'50" E., bet. secs. 7 and 12.

13.00 Ridge, bears ENE. and WSW.

19.70 Hiko Canyon Rd., 18 lks. wide, bears NE. and S.

41.358 Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T4S R60E R61E 1/4 S12 S 7 2015</p>
78.90	Ravine, drains SE.
82.716	The cor. of secs. 1, 6, 7 and 12, monumented with an unmkd. stone, 16x10x10 ins., loosely set in a mound of stone, 3 ft. base, 1 ft. high.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T4S R60E R61E S 1 S 6 ----- S12 S 7 2015</p>
	Bury the unmkd. stone in mound of stone.
	N. 0°32'50" E., bet. secs. 1 and 6.
22.50	Summit of mountains, bears NE. and SW.
32.90	Spur, slopes W.
38.40	Ravine, drains W.
39.840	The 1/4 sec. cor. of secs. 1 and 6, determined at the center of a mound of stone, 4 ft. base, 1 ft. high. This is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">T4S R60E R61E 1/4 S 1 S 6 2015</p> <hr/>
	<p>N. 0°28'20" E., beginning new measurement.</p>
3.60	Ravine, drains SW.
18.60	Spur, slopes W.
28.60	Ravine, drains WNW.
34.36	Spur, slopes WNW.
39.508	<p>The cor. of Tps. 3 and 4 S., Rs. 60 and 61 E., monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy. of T. 4 S., R. 60 E., executed under Group No. 353.</p> <hr/>
	<p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.B. Monroe in 1870</p> <hr/>
	<p>From the cor. of Tps. 3 and 4 S., Rs. 60 and 61 E., hereinbefore described.</p>
	<p>S. 89°53'40" W., on the N. bdy. of sec. 1.</p>
	<p>Descend over mountainous land.</p>
11.90	Ravine, 10 lks. wide, drains SW.
20.00	Spur, slopes WSW.
40.110	<p>The closing 1/4 sec. cor. of sec. 36, T. 3 S., R. 60 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the subdivision of section 36, T. 3 S., R. 60 E., executed concurrently under this same Group.</p>
	<p>From this cor., the 1958 Cannon-Yundt 1/4 sec. cor. of sec. 36, now an amended monument, bears S. 0°02'00" W., 1.561 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 3 S., R. 60 E., executed concurrently under this same Group.</p>

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS													
40.521	<p>The original 1/4 sec. cor. of secs. 1 and 36, monumented with a limestone, 18x12x3 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 1/4 on the W. face. This cor. now refers to sec. 1 only.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T3S R60E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1/4 S 1 T4S R60E</p> <p style="text-align: center;">2014</p> <p>Bury the mkd. stone in mound of stone.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°25'50" W., beginning new measurement.</p>												
19.575	<p>Intersect the N-S center line of the SW1/4 of sec. 36, T. 3 S., R. 60 E.</p> <p>Point for a closing cor. of secs. 1 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">T3S</td><td style="padding-left: 5px;">R60E</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">T3S</td><td style="padding-left: 5px;">S36 C</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S36</td><td style="padding-left: 5px;">R60E</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">R60E</td><td style="padding-left: 5px;">S 1 C</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding-left: 5px;">T4S</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding-left: 5px;">R60E</td></tr> </table> <p style="text-align: center;">2015</p> <p>From this point, the W 1/16 sec. cor. of sec. 36 only, T. 3 S., R. 60 E., bears S. 0°02'00" W., 0.843 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the subdivision of section 36, T. 3 S., R. 60 E., executed concurrently under this same Group.</p> <p>Continue measurement across sec. 36, T. 3 S., R. 60 E., on a blank line.</p>	T3S	R60E	T3S	S36 C	S36	R60E	R60E	S 1 C		T4S		R60E
T3S	R60E												
T3S	S36 C												
S36	R60E												
R60E	S 1 C												
	T4S												
	R60E												
20.121	<p>Point for the W 1/16 sec. cor. of sec. 1 only.</p>												

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.														
	<hr style="width: 10%; margin: auto;"/> W 1/16 S 1														
	2014														
	Continue measurement on the N. bdy. of sec. 1.														
21.70	Base of steep descent.														
28.00	Enter nearly level farmland.														
39.562	Intersect the line bet. secs. 35 and 36, T. 3 S., R. 60 E. Point for a closing cor. of secs. 1 and 35.														
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.														
	<table border="1" style="margin: auto;"> <tr><td></td><td>T3S</td></tr> <tr><td></td><td>R60E</td></tr> <tr><td>C</td><td>S35</td></tr> <tr><td colspan="2"><hr style="width: 10%; margin: auto;"/></td></tr> <tr><td>C</td><td>S 1</td></tr> <tr><td></td><td>T4S</td></tr> <tr><td></td><td>R60E</td></tr> </table>		T3S		R60E	C	S35	<hr style="width: 10%; margin: auto;"/>		C	S 1		T4S		R60E
	T3S														
	R60E														
C	S35														
<hr style="width: 10%; margin: auto;"/>															
C	S 1														
	T4S														
	R60E														
	2015														
	From this point, the SW cor. of sec. 36, T. 3 S., R. 60 E., bears S. 0°02'10" W., 0.028 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set 16 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 3 S., R. 60 E., executed concurrently under this same Group.														
40.242	The cor. of secs. 1 and 2, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set 20 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy. of T. 4 S., R. 60 E., executed under Group No. 914.														
	<hr style="width: 10%; margin: auto;"/> S. 89°49'50" W., on the N. bdy. of sec. 2.														
	Over farmland.														
17.50	Leave farmland.														
19.278	Point for the E 1/16 sec. cor. of sec. 35 only, T. 3 S., R. 60 E.														

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;"><u>E 1/16 S35</u></p> <p style="text-align: center;">2014</p> <p>19.90 Power line, bears N. 20° E. and S. 20° W.</p> <p>19.944 The E 1/16 sec. cor. of sec. 2 only, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy. of T. 4 S., R. 60 E., executed under Group No. 914.</p> <hr/> <p>S. 89°49'50" W., beginning new measurement.</p> <p>0.60 Gravel road, 30 lks. wide, bears N. 15° E. and S. 15° W.</p> <p>1.240 Angle Point No. 2, of a metes-and-bounds survey in sec. 2, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy. of T. 4 S., R. 60 E., executed under Group No. 914.</p> <hr/> <p>S. 89°49'50" W., beginning new measurement.</p> <p>0.90 Ascend through scattered sagebrush.</p> <p>10.25 Fence, parallels Nevada State Route 318.</p> <p>13.55 Nevada State Route 318, 50 lks. wide, bears N. 20° E. and S. 20° W.</p> <p>16.85 Fence, parallels Nevada State Route 318.</p> <p>18.053 The 1/4 sec. cor. of sec. 35, T. 3 S., R. 60 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion on the N. bdy. of T. 4 S., R. 60 E., executed under Group No. 914.</p> <p>18.722 The 1/4 sec. cor. of sec. 2, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy. of T. 4 S., R. 60 E., executed under Group No. 353, with the original limestone, 12x6 ins., projecting 11 ins. above the ground, alongside, no marks visible.</p> <hr/>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.B. Monroe in 1870
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°11'00" W., bet. secs. 1 and 12.</p>
2.90	Ravine, 10 lks. wide, drains SE.
26.60	Summit of mountains, bears N. and S.
40.020	<p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R60E S 1 1/4 — S12</p> <p style="text-align: center;">2015</p>
60.030	<p>Point for the W 1/16 sec. cor. of secs. 1 and 12.</p> <p>POINT NOT MONUMENTED</p>
80.040	<p>The cor. of secs. 1, 2, 11 and 12, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 4 S., R. 60 E., executed under Group No. 914.</p>
<p>SUBDIVISION OF SECTION 1, T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>From the 1/4 sec. cor. of secs. 1 and 12.</p> <p>N. 0°08'20" E., on the N-S center line of sec. 1.</p>
20.084	<p>Point for the C-S 1/16 sec. cor. of sec. 1.</p> <p>POINT NOT MONUMENTED</p>
40.168	<p>Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to solid rock, over a chiseled x and plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

SUBDIVISION OF SECTION 1,
T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T4S R60E C 1/4 S 1 2015
79.843	The N 1/4 sec. cor. of sec. 1, hereinbefore described. <hr/>
	From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp. S. 89°39'20" W., on the E-W center line of sec. 1.
40.296	The center 1/4 sec. cor. of sec. 1.
60.361	Point for the C-W 1/16 sec. cor. of sec. 1. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. W 1/16 C———C S 1 2015
	From this point, a position determined as the C-W 1/16 sec. cor. of sec. 1, by Lenard D. Smith, Nevada Professional Land Surveyor No. 12751, in 2003, bears N. 89°02'00" W., 0.167 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with an aluminum cap mkd. L. SMITH CW 1/16 PLS 12751, as recorded in Lincoln County, Nevada, Plat Book B, Page 498, File No. 120449. This position was based on the 1958 Cannon-Yundt 1/4 sec. cor. of sec. 1 and is not utilized during the course of this survey.
80.426	The 1/4 sec. cor. of secs. 1 and 2, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 4 S., R. 60 E., executed under Group No. 914. <hr/>
	From the point for the W 1/16 sec. cor. of secs. 1 and 12. N. 0°03'10" E., on the N-S center line of the SW1/4 of sec. 1.
20.166	Point for the SW 1/16 sec. cor. of sec. 1, at intersection with the E-W center line of the SW1/4. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

SUBDIVISION OF SECTION 1,
T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">SW 1/16 S 1</p> <p style="text-align: center;">2015</p>
	<p>From this point, a position determined as the SW 1/16 sec. cor. of sec. 1, by Lenard D. Smith, Nevada Professional Land Surveyor No. 12751, in 2003, bears S. 86°30'10" W., 0.087 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with an aluminum cap mkd. L. SMITH SW 1/16 PLS 12751, as recorded in Lincoln County, Nevada, Plat Book B, Page 498, File No. 120449. This position was based on the 1958 Cannon-Yundt 1/4 sec. cor. of sec. 1 and is not utilized during the course of this survey.</p>
40.332	<p>The C-W 1/16 sec. cor. of sec. 1.</p> <hr/>
	<p>From the point for the C-S 1/16 sec. cor. of sec. 1.</p> <p>S. 89°25'10" W., on the E-W center line of the SW1/4 of sec. 1.</p>
20.037	<p>The SW 1/16 sec. cor. of sec. 1.</p>
40.074	<p>The S 1/16 sec. cor. of secs. 1 and 2, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set 10 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 4 S., R. 60 E., executed under Group No. 914.</p> <hr/>
	<p>From the C-W 1/16 sec. cor. of sec. 1.</p> <p>N. 0°03'10" E., on the N-S center line of the NW1/4 of sec. 1.</p>
19.667	<p>From this point, a position determined as the NW 1/16 sec. cor. of sec. 1, by Lenard D. Smith, Nevada Professional Land Surveyor No. 12751, in 2003, bears WEST 0.246 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with an aluminum cap mkd. L. SMITH NW 1/16 PLS 12751, as recorded in Lincoln County, Nevada, Plat Book B, Page 498, File No. 120449. This position was based on the 1958 Cannon-Yundt 1/4 sec. cor. of sec. 1 and is not utilized during the course of this survey.</p>
39.174	<p>Intersect the S. bdy. of sec. 36, T. 3 S., R. 60 E.</p> <p>Point for a closing cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, to solid rock, over a chiseled x and plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>

SUBDIVISION OF SECTION 1,
T. 4 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p>	<div data-bbox="917 283 1031 472" data-label="Diagram"> </div> <div data-bbox="885 514 950 541" data-label="Text"><p>2015</p></div> <div data-bbox="430 567 1453 756" data-label="Text"> <p>From this point, the W 1/16 sec. cor. of sec. 36 only, T. 3 S., R. 60 E., bears S. 87°05'50" E., 0.547 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 3 S., R. 60 E., executed concurrently under this same Group.</p> </div> <div data-bbox="284 777 1429 808" data-label="Text"> <p>39.995 The W 1/16 sec. cor. of sec. 1 only, on the N. bdy. of the Tp.</p> </div> <hr/> <div data-bbox="795 861 1104 892" data-label="Section-Header"><p>GENERAL DESCRIPTION</p></div> <div data-bbox="430 913 1469 1165" data-label="Text"> <p>The area surveyed lies in the northerly extremes of the Pahrnagat Valley. The terrain varies from mountainous in the east portion to nearly level in the central portion with the remaining terrain being gently rolling. The elevation ranges from about 3,900 to 5,200 ft. above sea level. The soil varies from sandy clay loam and rocky on the higher elevations to clay loam on the bottom land. The native vegetation is primarily sagebrush. A portion of the bottom lands are currently irrigated croplands.</p> </div> <div data-bbox="430 1186 1469 1291" data-label="Text"> <p>The surveyed area is located approximately two miles northeast of the community of Hiko, Nevada. This historical community was once the county seat of Lincoln County. Today all that remains are a cemetery, a stone building and a small number of homes.</p> </div>
---------------	--

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Brandon G. Courtright

Cadastral Surveyor

Robert H. Thompson

Principal Analyst

CERTIFICATE OF SURVEY

I, Joseph J. Johnson, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 18th day of December, 2013, and Supplemental Special Instructions bearing date of the 22nd day of May, 2015, I have dependently resurveyed of a portion of the east boundary, a portion of the north boundary and a portion of the subdivisional lines, and subdivided section 1, Township 4 South, Range 60 East, Mount Diablo Meridian, Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

JUN 02 2015

(Date)

Joe J. Johnson

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the east boundary, a portion of the north boundary and a portion of the subdivisional lines, and the subdivision of section 1, Township 4 South, Range 60 East, Mount Diablo Meridian, Nevada, executed by Joseph J. Johnson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 02 2015

(Date)

Michael O. Harrington

(Chief Cadastral Surveyor for Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 4 S., R. 60 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor for Nevada)~~