

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

THE DEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 41 EAST,

AND

THE DEPENDENT RESURVEY OF PORTIONS OF THE SOUTH AND EAST BOUNDARIES,
A PORTION OF THE SUBDIVISIONAL LINES,
AND A PORTION OF THE SUBDIVISION OF SECTION 36,

THE SUBDIVISION OF SECTION 35,

AND

THE FURTHER SUBDIVISION OF SECTION 36,

TOWNSHIP 5 SOUTH, RANGE 40 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Richard A. Zaninovich, Cadastral Surveyor

Craig L. Wanless, Cadastral Surveyor

Under Special Instructions dated August 27, 2001, approved August 27, 2001,
Supplemental Special Instructions dated August 12, 2003, approved
August 12, 2003, and Supplemental Special Instructions dated June 6, 2005,
and approved June 6, 2005, which provided for the surveys included under
Group No. 804, and Assignment Instructions dated August 28, 2001
and July 9, 2003.

Survey commenced September 18, 2001

Survey completed June 15, 2005

INDEX DIAGRAM

TOWNSHIP 5 SOUTH, RANGE 40 EAST, MOUNT DIABLO MERIDIAN, NEVADA

						31
						2
6	5	4	3	2	1	
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
				13	10	
30	29	28	27	12 26	9 25	5
				12	8	
				9		
31	32	33	34	10 35	7 36	
			4	3		

Dependent Resurvey of a Portion of the Subdivision of
 Section 36..... p. 14.
 Subdivision of Section 35 pp. 14 - 17.
 Further Subdivision of Section 36 p. 17.

TOWNSHIP 5 SOUTH, RANGE 40 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of the First Standard Parallel South, through a portion of Range 41 East, and the dependent resurvey of portions of the south and east boundaries, a portion of the subdivisional lines, and a portion of the subdivision of section 36, the subdivision of section 35, and the further subdivision of section 36, Township 5 South, Range 40 East, Mount Diablo Meridian, Nevada.

The north, (First Standard Parallel South through ranges 40 and 41 east), south, east, and west boundaries and subdivisional lines were surveyed by U.S. Deputy Surveyor N.L. Berdan in 1882 under Contract No. 154. The north, south, east and west boundaries of section 36 were dependently resurveyed, section 36 was subdivided, and Lida Townsite was surveyed by U.S. Cadastral Engineer J.C. Thoma and U.S. Transitman L.R. Mercer in 1918 under Group No. 60. The west one-half mile of the east and west center line of section 36 was dependently resurveyed and Tract 37 in section 36 was surveyed by Cadastral Surveyor L.E. Bland in 1968 under Group No. 460. During the course of this resurvey a double set of corners were found for the corner of sections 25, 26, 35 and 36.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, Special Instructions dated August 27, 2001, the Supplemental Special Instructions dated August 12, 2003, and Supplemental Special Instructions dated June 6, 2005, for Group No. 804, Nevada.

The directions and distances of the lines of this survey were obtained by Trimble 5700 Global Positioning System (GPS) receivers using the real time kinematic method and refer to the true meridian, based on geodetic methods.

The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

Geodetic control was derived from Global Positioning System (GPS) static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing the Continuously Operating Reference Stations (CORS) MINARET SUMMIT, MAMMOTH LAKES AND DYER.

The geographic position of the corner of sections 1, 2, 35 and 36, on the south boundary of the township, NAD 83 (1999) is as follows:

Latitude: 37°27'11.925" N. Longitude: 117°30'09.733" W.

The 1980 mean magnetic declination is 15° East, as shown on the U.S.G.S. quadrangle map "MAGRUDER MTN., NEV." provisional edition dated 1987.

310

DEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 41 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor N.L. Berdan in 1882</p> <hr/> <p>From the stan. 1/4 sec. cor. of sec. 31, T. 4 S., R. 41 E., monumented with a granite stone, 16x10x4 ins., (Record, basalt, 13x8x7 ins.), firmly set, projecting 8 ins. above the ground, in a mound of stone, 2 ft. diam., 6 ins. high, mkd. SC on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> SC T4S R41E <u>1/4 S31</u> </div> <p style="text-align: center;">2003</p> <p>Deposit the original corner monument alongside the stainless steel post.</p> <p>Cor. is S., 0.70 chs. dist., from a dirt road, 15 lks. wide, bears NW and SE.</p> <p>S. 89°20'20" W., on the S. bdy. of sec. 31.</p> <p>36.018 The closing cor. of Tps. 5 S., Rs. 40 and 41 E., hereinafter described.</p> <p>40.356 The stan. cor. of Tps. 4 S., Rs. 40 and 41 E., monumented with a basalt stone, 15x9x6 ins., firmly set, projecting 10 ins. above the ground, in a mound of stone, 2 ft. diam., 6 ins. high, dimly mkd. SC on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> SC T4S R40E R41E <u>S36 S31</u> </div> <p style="text-align: center;">2003</p> <p>Deposit the original corner monument alongside the stainless steel post.</p> <hr/>
--------	---

311

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor N.L. Berdan in 1882</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with a basalt stone, 21x11x5 ins., loosely set, in a mound of stone, 3 ft. diam., 8 ins. high, mkd. with 5 grooves on one face and 1 groove on opposite face, alongside of which is an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T5S</td><td>R40E</td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td></td><td>3 LT</td></tr> <tr><td>S 2</td><td>S 1</td></tr> <tr><td></td><td>T6S</td></tr> </table> <p>1918</p> </div> <p>At the corner point</p> <p>Reset the iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground, and in a mound of stone, 3 ft. base, to top, add marks 2003 to the brass cap.</p> <p>Deposit the original corner monument alongside the iron post.</p> <p>N. 89°03'50" W., bet. secs. 2 and 35.</p> <p>Over nearly level land.</p>	T5S	R40E	S35	S36		3 LT	S 2	S 1		T6S
T5S	R40E										
S35	S36										
	3 LT										
S 2	S 1										
	T6S										
15.00	<p>Nevada State Route No. 266, asphalt surface, 60 lks. wide, on a curve bearing WSW and ENE.</p>										
40.350	<p>The 1/4 sec. cor. of secs. 2 and 35, monumented with a granite stone, (Record, basalt), 13x7x6 ins., firmly set, projecting 6 ins. above the ground, in a mound of stone, 3 ft. diam., 6 ins. high, mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T5S</td><td>R40E</td></tr> <tr><td></td><td>S35</td></tr> <tr><td>1/4</td><td></td></tr> <tr><td></td><td>S 2</td></tr> <tr><td></td><td>T6S</td></tr> </table> <p>2003</p> </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <hr/>	T5S	R40E		S35	1/4			S 2		T6S
T5S	R40E										
	S35										
1/4											
	S 2										
	T6S										

312

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S. 89°53'50" W., beginning new measurement.</p> <p>Over rolling land.</p>						
11.00	Bottom of desc.; asc. over SE. slope.						
39.10	Ravine, drains SE.; continue over rolling land.						
39.441	<p>The cor. of secs. 2, 3, 34 and 35, monumented with a basalt stone, 20x8x6 ins., (Record, 11x9x8 ins.), firmly set, projecting 6 ins. above the ground, mkd. with 2 grooves on E. face and 4 grooves on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R40E</p> <table style="margin: auto;"> <tr> <td>S34</td><td>S35</td></tr> <tr> <td>S 3</td><td>S 2</td></tr> <tr> <td colspan="2">T6S</td></tr> </table> <p>2003</p> </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <hr/> <p>S. 89°20'00" W., bet. secs. 3 and 34.</p> <p>Over rolling land.</p>	S34	S35	S 3	S 2	T6S	
S34	S35						
S 3	S 2						
T6S							
40.139	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with a limestone, (Record, basalt), 18x10x8 ins., firmly set, projecting 8 ins. above the ground, in a mound of stone, 2 ft. diam., 6 ins. high, mkd. 1/4 on N. face, from which the original bearing tree</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 60° E., 40 lks. dist., with scribe marks BT visible on partially opened blaze. (Record, pine, N. 45° E., 31 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R40E</p> <table style="margin: auto;"> <tr> <td>1/4</td><td>S34</td></tr> <tr> <td></td><td>S 3</td></tr> <tr> <td></td><td>T6S</td></tr> </table> <p>2001</p> </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <hr/>	1/4	S34		S 3		T6S
1/4	S34						
	S 3						
	T6S						

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 89°31'40" W., beginning new measurement.</p> <p>Over rolling land.</p> <p>39.861 The cor. of secs. 3, 4, 33 and 34, monumented with a quartz stone, (Record, basalt), 15x8x7 ins., firmly set, projecting 8 ins. above the ground, mkd. with 3 grooves on E. and 3 grooves on W. faces.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T5S</td><td>R40E</td></tr> <tr><td>S33</td><td>S34</td></tr> <tr><td>S 4</td><td>S 3</td></tr> </table> <p>T6S</p> <p>2003</p> </div> <p>There are no remains of the original bearing trees.</p> <p>Deposit the original corner monument alongside the stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor N.L. Berdan in 1882</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a granite stone, 12x10x6 ins., (1882 Record, 18x12x6 ins.), firmly set, projecting 6 ins. above the ground, mkd. with 5 notches on N. edge and 1 notch on S. edge, alongside of which is an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 3 ft. base, 8 ins. high, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T5S</td><td></td></tr> <tr><td>R40E</td><td>R41E</td></tr> <tr><td>S25</td><td>S30</td></tr> <tr><td>S36</td><td>S31</td></tr> </table> <p>1918</p> </div> <p>At the corner point</p> <p>Reset the iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground, and in a mound of stone, 2 ft. base, to top, add marks 2003 to the brass cap.</p>	T5S	R40E	S33	S34	S 4	S 3	T5S		R40E	R41E	S25	S30	S36	S31
T5S	R40E														
S33	S34														
S 4	S 3														
T5S															
R40E	R41E														
S25	S30														
S36	S31														

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the original corner monument alongside the iron post.</p>
	<p>N. 1°00'40" W., bet. secs. 25 and 30.</p>
	<p>Over nearly level land.</p>
41.497	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T 5 S 1/4 R40E R41E S25 S30</p>
	<p style="text-align: center;">2003</p>
	<p>Over rolling land.</p>
82.994	<p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T5S R40E R41E S24 S19 S25 S30</p>
	<p style="text-align: center;">2003</p>
	<p>From this corner, the closing cor. of Tps. 5 S., Rs. 40 and 41 E., on the First Standard Parallel South, bears</p>
	<p>N. 1°00'40" W., 331.976 chs. dist., monumented with a basalt stone, 14x10x6 ins., firmly set, projecting 6 ins. above the ground, mkd. with 6 grooves on E. and W. faces and 6 notches on S. edge, alongside of which is a rebar, 5/8 in. diam., set by person(s) unknown, firmly set, projecting 4 ins. above the ground, in a mound of stone, 2 ft. base, 6 ins. high.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T4S R41E S31 S1 S6 R40E R41E T5S CC</p>
	<p style="text-align: center;">2003</p>

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Deposit the original corner monument alongside and rebar inside of the stainless steel post.</p> <p>This control line was fully retraced and a careful search was made for intervening corners, none of which were found.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor N.L. Berdan in 1882 and a Portion of the Dependent Resurvey Executed by U.S. Cadastral Engineer J.C. Thoma and U.S. Transittman L.R. Mercer in 1918</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 1°07'30" E., bet. secs. 35 and 36.</p> <p>Over nearly level land.</p> <p>5.80 Nevada State Route No. 266, asphalt surface, 60 lks. wide, bears N. 65° E. and S. 65° W.</p> <p>25.00 Graveled road, 20 lks. wide, bears N. 70 1/4° W., and S. 70 1/4° E.</p> <p>40.005 The 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 3 1/2 ft. base, 8 ins. high, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} 1/4 \\ S35 \left \begin{array}{l} S36 \\ 2LT \end{array} \right. \end{array}$ <p>1918</p> </div> <p>This cor. now refers to the 1/4 sec. cor. of sec. 36 only. Remark the brass cap as follows:</p> <div style="text-align: center;"> $\begin{array}{r} 1/4 \\ S36 \\ 2LT \end{array}$ <p>1918 2005</p> </div> <p>A 5 ft. steel fence post is set alongside the iron post.</p> <hr/>
--------	--

316

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 1°09'20" E., beginning new measurement.
	Over nearly level land.
6.768	The 1/4 sec. cor. of sec. 35 only, hereinafter described.
20.012	Point for the N 1/16 sec. cor. of sec. 36 only.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	<div style="text-align: center;"> $\begin{array}{c} \text{N } 1/16 \\ \text{S36} \end{array}$ </div>
	2005
	Over nearly level land.
29.10	Dirt road, 15 lks. wide, bears N. 40° W. and S. 40° E.
40.024	The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 2 ft. diam., 8 ins. high, with brass cap mkd.
	<div style="text-align: center;"> $\begin{array}{c} \text{T5N R40E} \\ \text{S26} \mid \text{S25} \\ \hline \text{S35} \mid \text{S36} \end{array}$ </div>
	1918
	This cor. now refers to the cor. of secs. 25, 35 and 36 only. Remark the brass cap as follows:
	<div style="text-align: center;"> $\begin{array}{c} \text{T5N R40E} \\ \text{S35} \mid \text{S25} \\ \hline \text{S36} \end{array}$ </div>
	1918
	2005
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> $\begin{array}{c} \text{S25} \\ 1/4 \mid \hline \text{S36} \end{array}$ </div>
	1918
	A mound of stone, 3 ft. base, 6 ins. high is North of cor.

317

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 89°42'20" W., bet. secs. 25 and 36. Over nearly level land.
39.734	The cor. of secs. 25, 35 and 36 only. <hr/>
	N. 0°55'40" E., bet. secs. 25 and 35. Ascend over gradual S. slope.
3.00	Dirt road, 15 lks. wide, bears N. 45° E. and S. 45° W.
13.516	The cor. of secs. 25, 26, 35 and 36, monumented with a granite stone, 12x12x12 ins., firmly set, projecting 8 ins. above the ground, mkd. with 1 groove on S. face and 1 groove on E. face. This corner now refers to the cor. of secs. 25, 26 and 35 only. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">T5S R40E S26 S35 S25 <hr/></div> 2005 Deposit the original corner monument alongside the stainless steel post. <hr/>
	N. 0°06'50" W., bet. secs. 25 and 26. Over rolling land.
39.828	The 1/4 sec. cor. of secs. 25 and 26, monumented with a lava stone, 14x14x5 ins., firmly set, projecting 6 ins. above the ground, mkd. 1/4 on W. face. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;">T5S R40E 1/4 S26 S25 <hr/></div> 2002 Deposit the original corner monument alongside the stainless steel post. <hr/>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>N. 0°11'10" E., beginning new measurement.</p> <p>Over rolling land.</p>				
40.305	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a quartz stone, 16x12x10 ins., firmly set, projecting 10 ins. above the ground, mkd. with 2 grooves on S. face. (Record, basaltic)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. long, 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R40E</p> <table> <tr> <td>S23</td><td>S24</td></tr> <tr> <td>S26</td><td>S25</td></tr> </table> <p>2002</p> </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 81°53'20" W., bet. secs. 24 and 25.</p> <p>Over rolling land.</p>	S23	S24	S26	S25
S23	S24				
S26	S25				
39.304	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R40E</p> <table> <tr> <td>1/4</td><td>S24</td></tr> <tr> <td></td><td>S25</td></tr> </table> <p>2003</p> </div> <p>Over rolling land.</p>	1/4	S24		S25
1/4	S24				
	S25				
78.608	<p>The cor. of secs. 23, 24, 25 and 26.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°01'10" E., bet. secs. 34 and 35.</p> <p>Over rolling land.</p>				
46.390	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original cor.</p>				

319

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T5S R40E 1/4 S34 S35 2003</p> <p>The corner is W., 1.30 chs. dist., from fence line, bears N. and S.</p> <p>From this corner, a point established by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, bears S. 0°45'20" W., 6.574 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, in a collar of stone, with plastic cap mkd. BOUNDY PLS 2518. (Survey not recorded in Esmeralda County Courthouse.)</p> <p>From the rebar, intersection of fence lines bears E., 1.00 chs. dist., fences extending N. and E.</p> <p>Over rolling land.</p>
69.585	<p>Point for the N 1/16 sec. cor. of secs. 34 and 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S34 S35 2003</p> <p>From this corner, a point established by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, bears S. 0°20'30" W., 9.776 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, in a collar of stone, with plastic cap mkd. BOUNDY PLS 2518. (Survey not recorded in Esmeralda County Courthouse.)</p> <p>From the rebar, intersection of fence lines bears S. 45° E., 0.30 chs. dist., fences extending E. and irregularly S.</p>
92.780	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a granite stone, 8x8x8 ins., firmly set, projecting 8 ins. above the ground, mkd. with 1 groove on S. face and 2 grooves on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R40E S27 S26 S34 S35 2002</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>There are no remains of the original bearing trees.</p> <p>Deposit the original corner monument alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 25, 26 and 35 only.</p> <p>S. 89°46'30" W., bet. secs. 26 and 35.</p> <p>Over nearly level land.</p>
10.45	Dirt road, 15 lks. wide, bears N. 23° W. and S. 23° E.
40.634	<p>The 1/4 sec. cor. of secs. 26 and 35, monumented with a basalt stone, 18x16x8 ins., (Record, 9x9x7 ins.), firmly set, projecting 10 ins. above the ground, mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R40E</p> <p>S26</p> <p>1/4 <u> </u></p> <p>S35</p> <p>2002</p> </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <hr/> <p>N. 89°59'40" W., beginning new measurement.</p> <p>Over rolling land.</p>
20.457	Point for the W 1/16 sec. cor. of secs. 26 and 35; not monumented.
21.10	<p>Dirt road, 15 lks. wide, bears N. 1° E. and S. 1° W.</p> <p>Over rolling land.</p>
40.914	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>N. 0°18'00" W., bet. secs. 26 and 27.</p> <p>Over nearly level land.</p>
40.262	The 1/4 sec. cor. of secs. 26 and 27, monumented with a basalt stone, 10x9x8 ins., firmly set, projecting 6 ins. above the ground, in a collar of stone, mkd. 1/4 on W. face.

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> T5S R40E 1/4 S27 S26 2002 </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <hr/> <p>N. 0°00'30" E., beginning new measurement.</p> <p>Over rolling land.</p> <p>3.90 Dirt road, 15 lks. wide, bears N. 50° W. and S. 50° E.</p> <p>40.077 The cor. of secs. 22, 23, 26 and 27, monumented with a sandstone, 15x10x6 ins., (Record, basalt), firmly set, projecting 10 ins. above the ground, mkd. with 2 grooves on S. face and 2 grooves on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> T5S R40E S22 S23 S27 S26 2003 </div> <p>Deposit the original corner monument alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°57'50" W., bet. secs. 23 and 26.</p> <p>Over rolling land; through pine timber.</p> <p>40.894 Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> T5S R40E S23 1/4 ——— S26 2003 </div>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Ascend over NE. slope.
47.00	Spur, slopes NE.; desc. over NW. slope.
81.788	The cor. of secs. 22, 23, 26 and 27.
	<hr/>
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 36, T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	Reestablishment of a Portion of the Subdivision of Section 36 Executed by U.S. Cadastral Engineer J.C. Thoma and U.S. Transitman L.R. Mercer in 1918
	<hr/>
	From the center 1/4 sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above the ground, in a collar of stone, with brass cap mkd.
	1/4 S36 LT1
	1918
	N. 0°51'10" E., on the N. and S. center line of sec. 36.
	Over nearly level land.
19.910	Point for the center N 1/16 sec. cor. of sec. 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	N 1/16 S36 C
	2003
	Set a carsonite post alongside the stainless steel post.
	Over nearly level land.
39.820	The 1/4 sec. cor. of secs. 25 and 36.
	<hr/>
	SUBDIVISION OF SECTION 35, T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA
	<hr/>
	From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.
	N. 0°56'00" E., on the N. and S. center line of sec. 35.
	Over nearly level land.

323

SUBDIVISION OF SECTION 35,
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
27.00	From this point, the W. end of an airstrip bears E., 0.90 chs. dist., extending S. 55° E.
38.30	Graveled road, 20 lks. wide, bears N. 60° W. and S. 60° E.
43.65	Dirt road, 15 lks. wide. bears N. 50° E. and S. 50° W.
46.219	Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T5S R40E C 1/4 S35 2005 Set a carsonite post alongside the stainless steel post. Over nearly level land.
69.470	Point for the C-N 1/16 sec. cor. of sec. 35; not monumented.
92.721	The 1/4 sec. cor. of secs. 26 and 35. <hr/> Point for the 1/4 sec. cor. of sec. 35 only, determined at midpoint latitudinally bet. the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., and the cor. of secs. 25, 26 and 35 only, and on the W. bdy. of sec. 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet and in a collar of stone, with brass cap mkd. T5S R40E 1/4 S35 2005 N. 89°50'50" W., on the E. and W. center line of sec. 35. Over nearly level land.
38.30	Dirt road, 15 lks. wide, bears N. 50° E. and S. 50° W.
40.508	The center 1/4 sec. cor. of sec. 35.
52.90	Graveled road, 25 lks. wide, bears N. 40° W. and S. 40° E. Over rolling land.
60.596	Point for the C-W 1/16 sec. cor. of sec. 35. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

324

SUBDIVISION OF SECTION 35,
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div style="text-align: center;"> $\begin{array}{c} \text{W } 1/16 \\ \text{C} \quad \text{---} \quad \text{C} \\ \text{S35} \end{array}$ <p>2005</p> </div> <p>The corner is E., 25 lks. dist., from fence line, bears N. and S.</p> <p>From this corner, a point established by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, bears S. 1°44'20" W., 6.570 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with plastic cap mkd. BOUNDY PLS 2518. (Survey not recorded in Esmeralda County Courthouse.)</p> <p>The rebar is E., 2 lks. dist., from the intersection of fence lines, extending N. and W.</p> <p>From this same corner, the SE corner of a brick ranch house, 75x95 ft., the long side bears S. 89°10' W., bears N. 49°18' W., 9.38 chs. dist.</p> <p>Over rolling land.</p>
80.684	<p>The 1/4 sec. cor. of secs. 34 and 35.</p>
	<hr/> <p>From the C-W 1/16 sec. cor. of sec. 35.</p> <p>N. 0°28'40" E., on the N. and S. center line of the NW1/4 of sec. 35.</p> <p>Over rolling hills.</p>
3.30	<p>Graveled driveway, 20 lks. wide, bears N. 80° W. and S. 80° E.</p>
14.80	<p>Graveled road, 20 lks. wide, bears N. 30° W. and S. 30° E.</p>
23.223	<p>Point for the NW 1/16 sec. cor. of sec. 35, at intersection with the E. and W. center line of the NW1/4.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>
	<div style="text-align: center;">NW 1/16 S35</div>
	<div style="text-align: center;">2005</div>
	<p>Set a carsonite post alongside the stainless steel post.</p> <p>From this corner, a point established by Wallace T. Boundy, Nevada Professional Land Surveyor No. 2518, bears S. 1°58'10" W., 9.797 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 6 ins. above the ground, in a collar of stone, with plastic cap mkd. BOUNDY PLS 2518. (Survey not recorded in Esmeralda County Courthouse.)</p>

SUBDIVISION OF SECTION 35,
T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The rebar is E., 1 lk. dist. from the intersection of fence lines, extending S. and W.</p> <p>Over rolling land.</p>
46.446	<p>The point for the W 1/16 sec. cor. of secs. 26 and 35.</p> <hr/> <p>From the point for the C-N 1/16 sec. cor. of sec. 35.</p> <p>N. 89°55'20" W., on the E. and W. center line of the NW1/4 of sec. 35.</p> <p>Over rolling land.</p>
20.273	<p>The NW 1/16 sec. cor. of sec. 35.</p> <p>Over rolling land.</p>
24.30	<p>Graveled road, 25 lks. wide, bears N. 10° W. and S. 10° E.</p>
40.546	<p>The N 1/16 sec. cor. of secs. 34 and 35.</p> <hr/> <p style="text-align: center;">FURTHER SUBDIVISION OF SECTION 36, T. 5 S., R. 40 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 36.</p> <p>N. 89°51'00" W., on the E. and W. center line of the NW1/4 of sec. 36.</p> <p>Over nearly level land.</p>
39.843	<p>The N 1/16 sec. cor. of sec. 36 only.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in this survey are located in Esmeralda County, about 23 miles southwest of the community of Goldfield, Nevada. The area can be reached from Goldfield by traveling southerly on U.S. Highway No. 95, thence westerly on Nevada State Route No. 266. Numerous graveled and dirt roads provide access to the area.</p> <p>The terrain varies from nearly level to mountainous. The elevation ranges from about 6100 feet to about 7400 feet above sea level. The townsite of Lida is situated in section 36. The soil is sandy clay loam and gravel. The vegetation consists of pine, cacti, sagebrush and native grass.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Michael A. Derby	Surveying Technician
Jeremiah J. Lee	Surveying Technician
Clay W. Morrow	Surveying Technician
Matthew Norman	Surveying Technician

CERTIFICATE OF SURVEY

We, Richard A. Zaninovich and Craig L. Wanless, Cadastral Surveyors, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing date of the 27th day of August, 2001, the Supplemental Special Instructions bearing date of the 12th day of August, 2003, and Supplemental Special Instructions bearing date of the 6th day of June, 2005, we have dependently resurveyed the First Standard Parallel South, through a portion of Range 41 East, and dependently resurveyed portions of the south and east boundaries, a portion of the subdivisional lines, and a portion of the subdivision of section 36, subdivided section 35, and further subdivided section 36, Township 5 South, Range 40 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by us and under our direction. Said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 21, 2005
(Date)

David D. Morlan
/ For Richard A. Zaninovich
(Cadastral Surveyor)

June 30, 2005
(Date)

Craig Wanless
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the First Standard Parallel South, through a portion of Range 41 East, and the dependent resurvey of portions of the south and east boundaries, a portion of the subdivisional lines, and a portion of the subdivision of section 36, the subdivision of section 35, and the further subdivision of section 36, Township 5 South, Range 40 East, of the Mount Diablo Meridian, Nevada, executed by Richard A. Zaninovich and Craig L. Wanless, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

July 21, 2005
(Date)

David D. Morlan
(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in T. 5 S., R. 40 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~