

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 61 EAST,
A PORTION OF THE EAST BOUNDARY,
A PORTION OF THE SUBDIVISIONAL LINES,
AND A PORTION OF THE MEANDERS OF LOWER PAHRANAGAT LAKE,
THE SUBDIVISION OF CERTAIN SECTIONS,
AND THE METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
TOWNSHIP 8 SOUTH, RANGE 61 EAST,
OF THE MOUNT DIABLO MERIDIAN,
IN THE STATE OF NEVADA

EXECUTED BY

Kane M. Hellebust, Cadastral Surveyor

Under Special Instructions dated March 1, 2010,
and approved March 1, 2010,
which provided for the surveys included under Group No. 893,
and Assignment Instructions dated March 1, 2010.

Survey commenced April 17, 2010

Survey completed October 5, 2011

INDEX DIAGRAM

TOWNSHIP 8 SOUTH, RANGE 61 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	27 2 26	19 1
7	8	9	10 29	25 11 24	19 12 18
18	17	16	15	22 14 20	15 13 14
19	20	21	22	23	12 24 11 6
30	29	28	27	26	10 25 5 8
31	32	33	34	35	7 36 3 2

DEPENDENT RESURVEY OF A PORTION OF THE ORIGINAL MEANDERS OF LOWER
PAHRANAGAT LAKE.....PP 30 - 31
SUBDIVISION OF SECTION 2pp 31 - 34
SUBDIVISION OF SECTION 11pp 34 - 40
SUBDIVISION OF SECTION 13pp 40 - 42
SUBDIVISION OF SECTION 14pp 43 - 46
SUBDIVISION OF SECTION 24pp 46 - 52
SUBDIVISION OF SECTION 25pp 52 - 54
METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES THROUGH PORTIONS
OF SECTIONS 2, 11, 14, 24 AND 25.....pp 55 - 75

TOWNSHIP 8 SOUTH, RANGE 61 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The following field notes are those of the dependent resurvey of the Second Standard Parallel South, through a portion of Range 61 East, a portion of the east boundary, a portion of the subdivisional lines, and a portion of the meanders of Lower Pahranaagat Lake, the subdivision of certain sections, and the metes-and-bounds surveys of certain parcel boundaries through portions of sections 2, 11, 14, 24 and 25, Township 8 South, Range 61 East, Mount Diablo Meridian, Nevada.</p> <p>The south boundary (Second Standard Parallel South) was surveyed by U.S. Deputy Surveyor E.B. Monroe in 1869 under Contract No. 31. The north, east and west boundaries, a portion of the subdivisional lines and the meander lines of Lower Pahranaagat Lake were surveyed by U.S. Deputy Surveyor E.B. Monroe in 1870 under Contract No. 34. A portion of the south boundary (Second Standard Parallel South) was retraced and resurveyed by U.S. Transistmen H.G. Mason and E.R. Bunbury in 1916 under Group No. 49. The east boundary was dependently resurveyed by Cadastral Engineers D.R. Averill and E.A. Taylor in 1952-53 under Group No. 355. The original standard 1/4 section corner of section 33, on the south boundary (Second Standard Parallel South), was remonumented by Cadastral Surveyor E.W. Sibley in 1965 under Group No. 430. A portion of the south boundary (Second Standard Parallel South) was independently resurveyed by Cadastral Surveyor R.K. Baugh in 1978 under Group No. 548. A portion of the south boundary (Second Standard Parallel South) was dependently resurveyed by Cadastral Surveyor D.R. Aschenbach in 2009-10 under Group No. 877.</p> <p>A dependent resurvey of a portion of the north boundary was executed currently under T. 7 S., R. 61 E. of this same group.</p> <p>Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners and other calls of the original field note record.</p> <p>The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 2009</u>, and the Special Instructions for Group No. 893, dated March 1, 2010.</p> <p>Measurements were made with Trimble R8 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.</p> <p>The NAD 1983 (CORS 96) (2002) geographic position of the following corners were determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuous Operating Reference Stations (CORS) RAIL RAILROAD VALLEY CORS ARP, NVCA CARLTON SQUARE 2 CORS ARP and ECHO ECHO_BRGN_NV1999 CORS ARP and carried forward by RTK observations.</p>
--------	---

TOWNSHIP 8 SOUTH, RANGE 61 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The corner of Tps. 8 S., Rs. 61 and 62 E., is as follows:</p> <p style="padding-left: 40px;">Latitude: 37°12'09.297" N. Longitude: 115°05'05.331" W.</p> <p>The corner of sections 2, 3, 34 and 35, on the N. bdy. of the Tp., is as follows:</p> <p style="padding-left: 40px;">Latitude: 37°17'20.359" N. Longitude: 115°07'10.634" W.</p> <p>The February 17, 2011 mean magnetic declination was determined to be 12°40' E., as obtained from the National Oceanic and Atmospheric Administration's National Geophysical Data Center declination calculator.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL SOUTH, THROUGH A PORTION OF RANGE 61 EAST, MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Deputy Surveyor E.B. Monroe in 1869</p> <hr/> <p>Beginning at the standard 1/4 sec. cor. of sec. 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base, to top, with cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel South, through a portion of Range 61 East, executed under Group No. 877.</p> <p>Corner is located 19 lks. S. of a barbed wire fence, bears E. and W.</p> <p>S. 89°50'30" W., on the S. bdy. of sec. 36.</p> <p>Over gently rolling land, through scattered undergrowth, along fence.</p> <p>20.40 Base of steep hill, bears S. 20° W. and W.</p> <p>25.70 Ravine, drains N. 65° E., ascend a SE slope.</p> <p>29.90 Ravine, drains S. 45° E., ascend a NE slope.</p> <p>40.449 The standard cor. of secs. 35 and 36, monumented with a trachyte stone, 18x14x10 ins., firmly set, projecting 8 ins. above a mound of stone, 3 ft. base, 1 1/2 ft. high, plainly mkd. with 1 notch on E. edge and 5 notches on W. edge, with a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
--------	--

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 61 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>SC T8S R61E <u>S35 S36</u></p> <p>2010</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Corner is located 40 lks. S. of a barbed wire fence, bears E. and W.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.B. Monroe in 1870, and a Portion of the Dependent Resurvey Executed by Cadastral Engineers D.R. Averill and E.A. Taylor in 1952</p> <hr/> <p><u>MEMORANDUM</u></p> <p>The dependent resurvey of the east boundary, executed by Cadastral Engineers D.R. Averill and E.A. Taylor in 1952, created theoretical positions within Lower Pahranaagat Lake for the corner of sections 25, 30, 31 and 36 and the 1/4 section corner of sections 25 and 30. These theoretical positions were not established during the original survey by U.S. Deputy Surveyor E.B. Monroe in 1870, do not serve as useful points of control for the lottings shown on the plats approved and accepted within Townships 8 South, Ranges 61 and 62 East and are eliminated by this resurvey.</p> <hr/> <p>From the standard cor. of Tps. 8 S., Rs. 61 and 62 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above an embedded collar of stone, 2 ft. base, with brass cap mkd. as described in the field notes of the retracement and resurvey of the Second Standard Parallel South through Range 62 E., executed under Group No. 49, with a trachyte stone firmly set alongside the iron post, and a mound of stone, 3 ft. base, 1 ft. high, N. of cor.</p> <p>Corner is located 1 1/2 lks. N. of a barbed wire fence, bears E. and W.</p> <p>N. 0°08'30" E., bet. secs. 31 and 36.</p> <p>Over gently rolling land, through scattered undergrowth, along fence.</p> <p>24.00 Trail road, 15 lks. wide, in the bottom of a draw, drains NE.</p> <p>31.00 Low flat spur, slopes E.</p> <p>32.40 Trail road, bears S. 75° E. and N. 75° W.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.030	<p>The 1/4 sec. cor. of secs. 31 and 36, perpetuated by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with the top of an embedded mound of stone, 3 ft. base, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE 1/4 S36 S31 R61E R62E T8S 1963, with a trachyte stone, 14x12x6 ins., buried alongside the concrete post, plainly mkd. 1/4 on a face, with a steel fence post firmly set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S 1/4 R61E R62E S36 S31</p> <p>2010</p> </div> <p>Bury the concrete post and mkd. stone and reset the steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°04'40" E., beginning new measurement.</p>
6.40	Draw, drains N. 65° E.
20.044	<p>Point for the N 1/16 sec. cor. of secs. 31 and 36; there is no remaining evidence of monument set by the Bureau of Sport Fisheries and Wildlife.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16 S36 S31</p> <p>2010</p> </div>
24.00	Trail road, 15 lks. wide, bears E. and W.
30.50	SW. shore of Lower Pahranaagat Lake, meanders S. 45° E. and N. 45° W.
31.069	<p>The meander cor. of secs. 31 and 36, monumented with an unmkd. trachyte stone, 24x8x6 ins., lying loose in the center of a scattered mound of stone. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div data-bbox="873 380 1027 583" data-label="Diagram"> <pre> T8S MC R61E R62E S36 S31 2010 </pre> </div> <p>Bury the unmkd. stone alongside the stainless steel post.</p> <p>from which I add</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 0°29'20" W., 177.3 lks. dist., with brass cap mkd. RM MC T8SR61E S36 117.0 FT TO COR 2010 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 89°28'30" W., 136.4 lks. dist., with brass cap mkd. RM MC T8SR61E S36 90.0 FT TO COR 2010 and an arrow pointing to the corner.</p> <p>Point is located at the line of ordinary high water on the SE. shore of Lower Pahrnagat Lake, bears SE. and NW.</p> <hr/> <p>N. 0°31'20" E., across the waters of Lower Pahrnagat Lake.</p> <p>56.326 Point for the meander cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="867 1419 1027 1623" data-label="Diagram"> <pre> T8S R61E R62E S25 S30 MC 2010 </pre> </div> <p>Set a steel fence post alongside the stainless steel post and raise a mound of stone, 2 1/2 ft. base, 1 ft. high, N. of cor.</p> <p>Point is located at the line of ordinary high water on the NE. shore of Lower Pahrnagat Lake, bears SE. and NW.</p> <hr/> <p>N. 0°31'20" E., bet. secs. 25 and 30. Over gently rolling land, through scattered undergrowth.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.70	Improved gravel road, 30 lks. wide, bears S. 65° E. and N. 65° W.
3.357	The witness point, at the intersection of the southwesterly line of Parcel No. 1317 F, with the line bet. secs. 25 and 30, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the metes-and-bounds survey of certain parcels through sections 30, 31 and 32, T. 8 S., R. 62 E., executed concurrently under this same group.
5.60	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 40° E. and N. 40° W.
10.140	The witness point, at intersection of the northeasterly line of Parcel No. 1317 F with the line bet. secs. 25 and 30 monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the metes-and-bounds survey of certain parcels through sections 30, 31 and 32, T. 8 S., R. 62 E., executed concurrently under this same group.
15.10	Large draw, drains SW.
29.20	Large draw, drains S. 15° W.
30.887	The cor. of secs. 19, 24, 25 and 30, monumented with an iron post, 2 ins. diam., firmly set 2 ins. below the surface of the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 8 S., R. 61 E., executed under Group No. 355, with a deeply embedded mound of stone, W. of cor.
	N. 0°29'50" E., bet. secs. 19 and 24.
	Over gently rolling land, through scattered undergrowth.
16.90	Top of draw, 30 ft., high, bears N. 20° E. and S. 20° W.
19.603	Point for the S 1/16 sec. cor. of sec. 24 only.
	POINT NOT MONUMENTED
26.90	Draw, drains S. 35° W.
35.70	Draw, drains S. 30° W.
39.206	The 1/4 sec. cor. of sec. 24 only, monumented with an iron post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 10 ins. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 8 S., R. 61 E., executed under Group No. 355, with a trachyte stone firmly set on the E. side of the iron post, and a mound of stone, 3 1/2 ft. base, 2 ft. high, W. of cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.B. Monroe in 1870</p>
	<p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°32'50" E., bet. secs. 35 and 36.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
1.00	Draw, drains E.
12.40	Draw, drains S. 80° E.
27.40	Draw, drains N. 40° E.
35.00	Spur, bears S. 60° E. and N. 60° W.
39.018	<p>The 1/4 sec. cor. of secs. 35 and 36, monumented with a trachyte stone, 22x9x7 ins., firmly set, projecting 16 ins. above an embedded mound of stone, 3 ft. base, 6 ins. high, plainly mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8S R61E 1/4 S35 S36</p> <p style="text-align: center;">2010</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Corner is located in a deep draw, drains S. 65° E.</p>
	<p>N. 0°07'20" E., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
9.10	Spur, bears S. 40° E. and N. 40° W.
27.50	Draw, drains S. 65° E.
35.00	Spur, bears S. 60° E. and N. 60° W.
38.748	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a trachyte stone, 20x8x6 ins., firmly set, projecting 10 ins. above a mound of stone, 3 ft. base, 1 ft. high, plainly mkd. with 1 notch on the. E. edge and 1 notch on the S. edge.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R61E S26 S25 S35 S36</p> <p>2010</p> </div> <p>Bury the mkd. stone and set a steel fence post alongside the stainless steel post.</p> <hr/> <p>S. 89°32'20" E., bet. secs. 25 and 36.</p> <p>Over gently rolling land, through scattered undergrowth.</p> <p>24.80 Draw, drains N. 35° E.</p> <p>37.00 Ravine, drains N. 20° E.</p> <p>40.040 The 1/4 sec. cor. of secs. 25 and 36, perpetuated by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with the top of a mound of stone, 3 ft. base, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE 1/4 S25 S36 T8S R61E 1963, with a trachyte stone, 16x10x6 ins., buried alongside the concrete post, plainly mkd. with a 1/4 on a face, with a steel fence post, firmly set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R61E S25 1/4 — S36</p> <p>2010</p> </div> <p>Bury the concrete post and the mkd. stone and reset the steel fence post alongside the stainless steel post.</p> <hr/> <p>EAST, beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
10.00	Draw, drains N. 15° E.
20.000	Point for the E 1/16 sec. cor. of secs. 25 and 36. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">$\begin{array}{c} S25 \\ E\ 1/16 \text{ ---} \\ S36 \end{array}$ 2010 Corner is located in a barbed wire fence, with fences extending S. 45° E. and N. 45° W.</div>
24.50	Trail road, bears S. 40° E. and N. 40° W.
27.60	Trail road, bears NE. and SW.
31.90	Trail road, bears N. and S.
36.70	Top of a small rocky ledge, bears S. 40° E. and N. 40° W.
37.500	Point for the meander cor. of secs. 25 and 36, at record bearing and distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. <div style="text-align: center;">$\begin{array}{c} T8S\ R61E \\ S25 \\ \text{---} \quad \diagup \quad MC \\ S36 \end{array}$ 2010 from which A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 10 ins. in the ground to solid rock, over a plastic- encased magnet, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. 19°52'00" W., 97.6 lks. dist., with brass cap mkd. RM MC T8SRE61E S36 64.4 FT TO COR 2010 and an arrow pointing to the corner. A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 4 ins. in the ground to solid rock, over a plastic- encased magnet, and in a mound of stone, 4 ft. base, to top, for a reference monument, bears N. 69°04'50" W., 126.9 lks. dist., with brass cap mkd. RM MC T8SR61E S25 83.8 FT TO COR 2010 and an arrow pointing to the corner.</div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Point is located at the line of ordinary high water on the SE. shore of Lower Pahranaagat Lake, bears S. 30° E. and N. 30° W.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 0°21'50" E., bet. secs. 25 and 26.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
13.50	Draw, drains N. 60° E.
21.60	Draw, drains N. 70° E.
32.70	Draw, drains N. 55° E.
33.80	Draw, drains S. 50° E.
39.255	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with a trachyte stone, 24x7x6 ins., firmly set, projecting 12 ins. above a mound of stone, 2 1/2 ft. base, 1 ft. high, plainly mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8S R61E 1/4 S26 S25 2010</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°21'10" E., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
6.60	Draw, drains S. 65° E.
19.50	Top of rocky ridge, bears S. 60° E. and N. 60° W.
19.948	<p>The N 1/16 sec. cor. of secs. 25 and 26, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with the top of a mound of stone, 3 ft. base, 1 ft. high, with a standard brass tablet firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE N 1/16 S26 S25 1963, with a steel fence post firmly set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S26 S25</p> <p style="text-align: center;">2010</p> <p>Bury the concrete post and reset the steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 0°21'10" E., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
17.70	Leave rolling land, enter wide draw, drains E.
19.948	<p>The cor. of secs. 23, 24, 25 and 26, perpetuated by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with the surface of the ground, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE T8S R61E S23 S24 S26 S25 1963, with a trachyte stone, 12x8x6 ins., plainly mkd. with 2 notches on one edge and 1 notch on an adjoining edge, buried alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8S R61E S23 S24 S26 S25</p> <p style="text-align: center;">2010</p> <p>Bury the concrete post and the mkd. stone and set a steel fence post alongside the stainless steel post.</p> <p>Corner is located in a barbed wire fence, bears S. 45° E. and N. 45° W.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 88°53'30" W., bet. secs. 24 and 25.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
6.10	Spur, bears N. 40° E. and S. 40° W.
10.50	Draw, drains S. 20° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
17.40	Spur, bears S. 10° E. and N. 10° W.
20.178	Point for the E 1/16 sec. cor. of secs. 24 and 25; there is no remaining evidence of the monument set by the Bureau of Sport Fisheries and Wildlife. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 1/2 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> S24 E 1/16 — S25 2010 </div>
	Set a steel fence post alongside the stainless steel post.
22.30	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 41°33'00" E. and N. 41°33'00" W.
23.443	The point for a witness point, at intersection of the westerly line of Parcel No. 1317 G, identical with the intersection of the westerly line of Parcel No. 1318 A, hereinafter described. Thence over bottom lands, edge bears S. 40° E. and N. 40° W., through grasses and tulles.
40.10	Pahranagat Creek, 25 lks. wide, 2 ft. deep, course S. 20° E.
40.356	Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;"> T8S R61E S24 1/4 — S25 2010 </div>
48.90	Leave bottom lands, edge bears SE. and NW., enter gently rolling land, through scattered undergrowth.
58.10	Trail road, 15 lks. wide, bears S. and N. 25° W.
80.712	The cor. of secs. 23, 24, 25 and 26. <hr/>
	N. 1°00'30" E., bet. secs. 23 and 24. Over gently rolling land, through scattered undergrowth.
19.10	Trail road, 20 lks. wide, bears S. 85° E. and N. 85° W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.40	Enter marsh, edge bears S. 85° E. and N. 85° W.
40.722	<p>Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T8S R61E 1/4 S23 S24 2010</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, N. of cor.</p> <p>From this point, United States Coast and Geodetic Survey bench mark "C 312" bears N. 26°28'30" E., 12.243 chs. dist., monumented with a standard brass cap, 3 1/2 ins. diam., firmly set flush with the top of a concrete base, 6x6 ins., projecting 3 ins. above the ground, with top mkd. C312 1941.</p>
61.083	<p>Point for the N 1/16 sec. cor. of secs. 23 and 24.</p> <p>POINT NOT MONUMENTED</p>
65.50	Leave marsh, edge bears S. 20° E. and N. 20° W., enter gently rolling land, through scattered undergrowth.
69.20	Improved gravel road, 30 lks. wide, bears S. 20° E. and N. 20° W.
81.444	<p>The cor. of secs. 13, 14, 23 and 24, perpetuated by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with a mound of stone, 3 ft. base, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE T8S R61E S14 S13 S23 S24 1963, with a trachyte stone, 18x9x8 ins., firmly set alongside the concrete post, projecting 1 in. above the mound of stone, plainly mkd. with 3 notches on S. edge and 1 notch on E. edge, with a steel fence post firmly set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8S R61E S14 S13 S23 S24 2010</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the concrete post and the mkd. stone and reset the steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 6 ins. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 8 S., R. 61 E., executed under Group No. 355.</p> <p>N. 89°51'40" W., bet. secs. 13 and 24.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
7.00	Deep draw, drains S. 45° W.
40.004	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with a trachyte stone, 15x10x10 ins., firmly set, projecting 7 ins. above the surface of the ground (Record, in a mound of stone), plainly mkd. 1/4 on S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R61E</p> <p>S13</p> <p>1/4 —</p> <p>S24</p> <p>2010</p> </div> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 88°53'10" W., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
9.10	Draw, drains S. 40° W.
20.168	<p>Point for the W 1/16 sec. cor. of secs. 13 and 24.</p> <p>POINT NOT MONUMENTED</p> <p>Point is located on the northerly edge of a deep draw, drains W.</p>
30.252	<p>The W-W 1/64 sec. cor. of secs. 13 and 24, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a galvanized iron pipe, 1 1/2 ins. diam., 3 ft. long, firmly set, projecting 2 ft. above the ground, with a steel fence post firmly set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p>S13 W-W 1/64 S24</p> <p>2010</p> <p>Reset the galvanized iron pipe and steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 88°53'10" W., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
4.60	<p>U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 20° E. and N. 20° W.</p>
5.042	<p>Point for the W-W-W 1/256 sec. cor. of secs. 13 and 24; there is no remaining evidence of the monument set by the Bureau of Sport Fisheries and Wildlife.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>S13 W-W-W 1/256 S24</p> <p>2010</p>
10.084	<p>Set a steel fence post alongside the stainless steel post.</p> <p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 1°04'40" E., bet. secs. 13 and 14.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
6.854	<p>A wooden post, 4x4 ins., 5 ft. long, firmly set, projecting 2 1/2 ft. above the ground, mkd. with faded black and white paint.</p>
10.024	<p>The S-S 1/64 sec. cor. of secs. 13 and 14, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded survey plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a galvanized iron pipe, 1 1/2 ins. diam., 3 ft. long, firmly set, projecting 1 ft. above a mound of stone, 2 1/2 ft. base, 1 ft. high, with a steel fence post firmly set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p>S-S 1/64 S14 S13</p> <p>2010</p> <p>Reset the galvanized iron pipe and steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 1°04'40" E., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
1.419	The point for a witness point, at intersection of the westerly line of Parcel No. 1317 I with the line bet. secs. 13 and 14, hereinafter described.
5.70	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 18° E. and N. 18°12'00" W.
10.024	Point for the S 1/16 sec. cor. of secs. 13 and 14.
	POINT NOT MONUMENTED
15.187	The point for a witness point, intersection of the easterly line of Parcel No. 1317 I with the line bet. secs. 13 and 14, hereinafter described.
30.072	<p>The 1/4 sec. cor. of secs. 13 and 14, perpetuated by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with the top of a mound of stone, 3 ft. base, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE 1/4 S14 S13 T8S R61E 1963, with a trachyte stone, 12x6x4 ins., firmly set alongside the concrete post, projecting 8 ins. above the mound of stone, plainly mkd. 1/4 on a face, with a steel fence post firmly set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p>T8S R61E 1/4 S14 S13</p> <p>2010</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Bury the mkd. stone and reset the concrete post and steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 1°02'40" E., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
10.00	Deep draw, drains S. 15° W.
20.134	<p>The N 1/16 sec. cor. of secs. 13 and 14, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded survey plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with the top of a mound of stone, 3 ft. base, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE N 1/16 S14 S13 1963, with a steel fence post firmly set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16 S14 S13</p> <p>2010</p> </div> <p>Bury the concrete post and reset the steel fence post alongside the stainless steel post.</p> <p>From this corner, a wood post, 7x3 ins., firmly set, projecting 3 ft. above the ground, mkd. with faded black and white paint, bears N. 28°52'40" W., 0.058 chs. dist.</p> <hr/> <p>N. 1°02'40" E., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
14.60	Draw, drains W.
20.134	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a trachyte stone, 12x10x10 ins., loosely set, projecting 10 ins. above a mound of stone, 3 ft. base, 1 ft. high, plainly mkd. with 1 notch on E. edge and 4 notches on S. edge, with a wooden post, 7x3 ins., 4 ft. long, lying loose alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="889 268 1019 367"> <p>T8S R61E S11 S12 — — S14 S13</p> </div> <div data-bbox="922 401 987 426">2010</div> <div data-bbox="435 457 1380 510"> <p>Bury the mkd. stone and reset the wooden post alongside the stainless steel post.</p> <hr/> </div> <div data-bbox="435 569 1461 726"> <p>From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 6 ins. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 8 S., R. 61 E., executed under Group No. 355.</p> </div> <div data-bbox="435 751 1040 779"> <p>N. 89°07'30" W., bet. secs. 12 and 13.</p> </div> <div data-bbox="435 806 1326 833"> <p>Over gently rolling land, through scattered undergrowth.</p> </div> <div data-bbox="289 858 862 886"> <p>28.00 Deep draw, drains S. 40° W.</p> </div> <div data-bbox="289 911 1461 1016"> <p>40.169 The 1/4 sec. cor. of secs. 12 and 13, monumented with a trachyte stone, 12x12x9 ins., firmly set, projecting 8 ins. above an embedded mound of stone, 3 ft. base, 4 ins. high, plainly mkd. 1/4 on N. face.</p> </div> <div data-bbox="435 1043 740 1071"> <p>At the corner point</p> </div> <div data-bbox="435 1098 1442 1203"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> </div> <div data-bbox="889 1234 1019 1348"> <p>T8S R61E S12 1/4 — S13</p> </div> <div data-bbox="922 1381 987 1407">2010</div> <div data-bbox="435 1434 1308 1461"> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> </div> <div data-bbox="435 1518 1118 1545"> <p>N. 89°07'00" W., beginning new measurement.</p> </div> <div data-bbox="435 1572 1323 1600"> <p>Over gently rolling land, through scattered undergrowth.</p> </div> <div data-bbox="289 1625 750 1652"> <p>11.50 Deep draw, drains S.</p> </div> <div data-bbox="289 1677 766 1705"> <p>13.30 Spur, bears N. and S.</p> </div> <div data-bbox="289 1730 750 1757"> <p>15.80 Deep draw, drains S.</p> </div> <div data-bbox="289 1782 1005 1810"> <p>40.082 The cor. of secs. 11, 12, 13 and 14.</p> <hr/> </div>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 2°32'10" E., bet. secs. 11 and 12. Over gently rolling land, through scattered undergrowth.
4.00	Deep draw, drains S. 45° W.
19.436	Point for the S 1/16 sec. cor. of secs. 11 and 12. POINT NOT MONUMENTED Point is located on a rocky ridge, bears S. 30° E. and N. 30° W.
31.80	Draw, drains N. 60° W.
38.30	Draw, drains S. 45° W.
38.872	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd. T8S R61E 1/4 S11 S12 2010
52.00	Draw, drains W.
66.60	Draw, drains SW.
77.744	The cor. of secs. 1, 2, 11 and 12, monumented with a trachyte stone, 18x10x10 ins., loosely set, projecting 14 ins. above the center of a mound of stone, 3 ft. base, 1 ft. high, plainly mkd. with 1 notch on E. edge and 5 notches on S. edge. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T8S R61E S 2 S 1 S11 S12 2010 Bury the mkd. stone alongside the stainless steel post.
	N. 0°08'10" E., bet. secs. 1 and 2. Over gently rolling land, through scattered undergrowth.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
1.50	Enter nearly level flood plain, edge bears N. 60° E. and S. 60° W.
12.00	Improved gravel road, 30 lks. wide, bears N. 70° E. and S. 70° W.
19.80	Enter gently rolling land, edge bears E. and W.; through scattered undergrowth.
40.417	The 1/4 sec. cor. of secs. 1 and 2, monumented with a trachyte stone, 12x8x8 ins., firmly set, projecting 6 ins. above an embedded mound of stone, 3 ft. base, 4 ins. high, plainly mkd. 1/4 on the W. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T8S R61E 1/4 S 2 S 1
	2010
	Bury the mkd. stone alongside the stainless steel post.
	Corner is located 12 lks. W. of the center of a small draw, drains S. 15° E.
	<hr/>
	N. 0°06'50" E., beginning new measurement.
	Over gently rolling land, through scattered undergrowth.
0.70	Draw, drains S. 15° E.
4.60	Ridge, bears S. 30° E. and N. 30° W.
10.70	Draw, drains W.
20.70	Draw, drains S. 60° W.
23.00	Spur, bears N. 60° E. and S. 60° W.
25.60	Draw, drains S. 40° W.
39.816	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 7 S., R. 61 E., executed concurrently under this same group.
	<hr/>
	From the cor. of secs. 13, 14, 23 and 24.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°56'40" W., bet. secs. 14 and 23. Over gently rolling land, through scattered undergrowth.
4.20	Improved gravel road, 30 lks. wide, bears S. 15° E. and N. 15° W.
6.90	Abandoned trail road, 15 lks. wide, bears S. 30° E. and N. 25° W.
7.10	Enter marsh, edge bears S. 35° E. and N. 75° W.; through grasses and tulles.
10.50	Gravel road, 20 lks. wide, bears N. 60° E. and S. 60° W.
28.40	Abandoned trail road, 15 lks. wide, bears N. 30° E. and S. 30° W.
40.188	Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd. T8S R61E S14 1/4 — S23 2010 Set a steel fence post alongside the stainless steel post. From this point, the corner of barbed wire fences extending N. 20° E. and S. 65° W., bears N. 45°17' W., 2.02 chs. dist.
44.70	Barbed wire fence, bears N. 65° E. and S. 65° W.
60.282	Point for the W 1/16 sec. cor. of secs. 14 and 23; there is no remaining evidence of the monument set by the Bureau of Sport Fisheries and Wildlife. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd. S14 W 1/16 — S23 2010
66.90	Trail road, 15 lks. wide, bears S. 15° E. and N. 15° W.
70.329	Point for the W-W 1/64 sec. cor. of secs. 14 and 23; there is no remaining evidence of the monument set by the Bureau of Sport Fisheries and Wildlife.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S14 W-W 1/64 S23 2010</p> <p>Thence over gently rolling land, through scattered undergrowth.</p>
80.376	<p>The cor. of secs. 14, 15, 22 and 23, monumented with a trachyte stone, 15x9x8 ins., firmly set, projecting 8 ins. above a mound of stone, 3 ft. base, 1 ft. high, plainly mkd. with 3 notches on E. edge and 2 notches on S. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8S R61E S15 S14 S22 S23 2010</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p>N. 0°12'00" E., bet. secs. 14 and 15.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
20.092	<p>Point for the S 1/16 sec. cor. of secs. 14 and 15; there is no remaining evidence of the monument set by the Bureau of Sport Fisheries and Wildlife.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S15 S14 2010</p> <p>Point is located in a small draw, drains E.</p>
38.40	<p>Trail road, 15 lks. wide, bears S. 15° E. and N. 15° W.</p>
40.184	<p>The 1/4 sec. cor. of secs. 14 and 15, perpetuated by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set,</p>

CHAINS

29.436

N. 4°31'10" E., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Over gently rolling land, through scattered undergrowth.						
9.812	<p>The cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the position of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <table> <tr> <td>T8S</td><td>R61E</td></tr> <tr> <td>S10</td><td>S11</td></tr> <tr> <td>S15</td><td>S14</td></tr> </table> <p>2010</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°10'50" W., bet. secs. 11 and 14.</p> <p>Over gently rolling land, through scattered undergrowth.</p>	T8S	R61E	S10	S11	S15	S14
T8S	R61E						
S10	S11						
S15	S14						
4.90	Draw, drains W.						
19.656	<p>Point for the E 1/16 sec. cor. of secs. 11 and 14; there is no remaining evidence of the monument set by the Bureau of Sport Fisheries and Wildlife.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of a trail road, over a plastic-encased magnet, with brass cap mkd.</p> <table> <tr> <td>E 1/16</td><td>S11</td></tr> <tr> <td></td><td>S14</td></tr> </table> <p>2010</p> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, for a reference monument, bears N. 12°01'50" E., 71.2 lks. dist., with brass cap mkd. RM E 1/16 S11 47.0 FT TO COR 2010 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, for a reference monument, bears S. 78°41'10" E., 37.7 lks. dist., with brass cap mkd. RM E 1/16 S14 24.9 FT TO COR 2010 and an arrow pointing to the corner.</p> <p>Point is located on the northerly edge of a trail road, 15 lks. wide, bears N. 25° E. and S. 25° W.</p>	E 1/16	S11		S14		
E 1/16	S11						
	S14						

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
22.60	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 20° E. and N. 20° W.
25.60	Improved gravel road, 30 lks. wide, bears S. 20° E. and N. 20° W.
26.250	The point for a witness point and intersection of the westerly line of Parcel No. 1317 J, with the line bet. secs. 11 and 14, hereinafter described.
28.10	Enter bottom lands, edge bears S. 65° E. and N. 65° W., through grasses and tulles.
39.312	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">T8S R61E S11 1/4 — S14 2010</div>
	Set a steel fence post alongside the stainless steel post.
57.90	Pahranagat Creek, 2 ft. deep, 15 lks. wide, drains S.
78.624	The cor. of secs. 10, 11, 14 and 15. <hr/>
	N. 1°27'20" E., bet. secs. 10 and 11. Over bottom lands, through grasses and tulles.
39.136	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the position of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. <div style="text-align: center;">T8S R61E 1/4 S10 S11 2010</div>
	Set a steel fence post alongside the stainless steel post.
58.704	Point for the N 1/16 sec. cor. of secs. 10 and 11. POINT NOT MONUMENTED

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
65.50	Improved gravel road, 30 lks. wide, bears N. 30° E. and S. 25° W.
	Thence over gently rolling land, through scattered undergrowth.
78.272	The cor. of secs. 2, 3, 10 and 11, monumented with a trachyte stone, 12x8x6 ins., firmly set, projecting 8 ins. above a mound of stone, 3 ft. base, 6 ins. high, plainly mkd. with 2 notches on E. edge and 5 notches on S. edge.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;"> T8S R61E S 3 S 2 S10 S11 2010 </div>
	Bury the mkd. stone alongside the stainless steel post.
	From this corner, the U.S. Fish & Wildlife Service GPS control point "CP 3" bears N. 66°04'40" W., 21.486 chs. dist., monumented with a standard brass tablet, firmly cemented flush with the top of a large stone, mkd. U.S.F.W.S. CP3.
	From the cor. of secs. 1, 2, 11 and 12.
	S. 89°35'50" W., bet. secs. 2 and 11.
	Over gently rolling land, through scattered undergrowth.
13.90	Enter nearly level flood plain, edge bears N. 85° E. and S. 85° W.
18.20	Trail road, 15 lks. wide, bears N. 70° E. and S. 70° W.
40.094	The 1/4 sec. cor. of secs. 2 and 11, perpetuated by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with a collar of stone, 2 ft. base, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE 1/4 S2 S11 T8SR61E 1963, with a trachyte stone, 21x11x8 ins. (Record, 12x8x6 ins.), plainly mkd. 1/4 on a face, loosely set alongside the concrete post and a steel fence post firmly set alongside.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	T8S R61E S 2 1/4 — S11 2010
	Bury the concrete post and the mkd. stone and reset the steel fence post alongside the stainless steel post.
	S. 89°37'30" W., beginning new measurement.
	Over flood plain, nearly level, through scattered undergrowth.
17.60	Improved gravel road, 30 lks. wide, bears N. 65° E. and S. 65° W.
19.980	Point for the W 1/16 sec. cor. of secs. 2 and 11.
	POINT NOT MONUMENTED
22.842	The point for a witness point, at intersection of the easterly line of Parcel No. 1317 M with the line bet. secs. 2 and 11, hereinafter described.
23.90	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 26°33'30" E. and N. 26°33'40" W.
24.530	The point for a witness point, at intersection of the westerly line of Parcel No. 1317 M with the line bet. secs. 2 and 11, hereinafter described.
31.30	Improved gravel road, 30 lks. wide, bears N. 40° E. and S. 40° W.
	Thence over gently rolling land, edge bears N. 40° E. and S. 40° W.; through scattered undergrowth, grasses and tulles.
39.960	The cor. of secs. 2, 3, 10 and 11.
	N. 0°03'00" W., bet. secs. 2 and 3.
	Over gently rolling land, through scattered undergrowth.
20.194	Point for the S 1/16 sec. cor. of secs. 2 and 3.
	POINT NOT MONUMENTED
23.00	Enter bottom lands, edge bears N. 65° E. and S. 65° W.; through grasses and scattered undergrowth.
32.80	Gravel road, 25 lks. wide, bears E. and W.
39.80	Enter Pahranagat Creek, in a earthen ditch, 15 lks. wide, 5 ft. deep, course N. and S. 5° E.
40.388	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the position of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T8S R61E 1/4 S 3 S 2</p> <p style="text-align: center;">2010</p> <p>Point is located in Pahrnagat Creek, in a earthen ditch, 15 lks. wide, 5 ft. deep, course N. and S.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 45°18'20" W., 159.9 lks. dist., with brass cap mkd. RM T8SR61E 1/4 S3 105.5 FT TO COR 2010 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 44°51'00" W., 159.2 lks. dist., with brass cap mkd. RM T8SR61E 1/4 S3 105.1 FT TO COR 2010 and an arrow pointing to the corner.</p>
52.80	<p>Leave Pahrnagat Creek, in a earthen ditch, bears S. and N. 25° W.</p> <p>Thence over bottom lands, through grasses and scattered undergrowth.</p>
69.10	<p>Earthen dam, 20 lks. wide, 5 ft. high, bears N. 70° E. and S. 70° W.</p>
69.20	<p>Enter Upper Pahrnagat Lake, edge bears N. 70° E. and S. 70° W.</p> <p>Thence across the waters of Upper Pahrnagat Lake.</p>
81.109	<p>True point for the cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 7 S., R. 61 E., executed concurrently under this same group.</p> <hr/> <p>From cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°08'00" W., bet. secs. 10 and 15.</p> <p>Over bottom lands, grasses and scattered brush.</p>
5.20	<p>Enter gently rolling land, edge bears S. 15° E. and N. 15° W.; through scattered undergrowth.</p>
7.80	<p>Trail road, 15 lks. wide, bears S. 15° E. and N. 15° W.</p>
9.880	<p>Point for the E-E 1/64 sec. cor. of secs. 10 and 15; there is no remaining evidence of the monument set by the Bureau of Sport Fisheries and Wildlife.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S10 E-E 1/64 S15 2010</p> <p>19.760 Point for the E 1/16 sec. cor. of secs. 10 and 15; there is no remaining evidence of the monument set by the Bureau of Sport Fisheries and Wildlife.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S10 E 1/16 — S15 2010</p> <p>39.520 The 1/4 sec. cor. of secs. 10 and 15, monumented with a trachyte stone, 10x10x6 ins., firmly set, projecting 8 ins. above a mound of stone, 3 ft. base, 1 ft. high, plainly mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T8S R61E S10 1/4 — S15 2010</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE ORIGINAL MEANDERS OF LOWER PAHRANAGAT LAKE, T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.B. Monroe in 1870</p> <hr/> <p style="text-align: center;">MEMORANDUM</p> <p>The following meander lines are of the lake area formerly called Pahrnagat Lake and now known as Lower Pahrnagat Lake.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE
ORIGINAL MEANDERS OF LOWER PAHRANAGAT LAKE,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>The Compass Rule Adjustment was the mathematical solution used for meander course restoration.</p> <hr/> <p>From the meander cor. of secs. 25 and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>Thence with the adjusted meanders of Lower Pahranaagat Lake in sec. 25, at the line of ordinary high water.</p> <p>S. 74°07'50" W., 4.610 chs.</p> <p>S. 76°07'40" W., 9.017 chs.</p> <p>N. 2°01'40" W., 17.878 chs.</p> <p>S. 66°09'00" W., 25.575 chs. At 6.842 chs., point for a special meander cor. at intersection with the N-S center line of the NE1/4 of sec. 25, hereinafter described.</p> <p>S. 50°42'30" W., 18.081 chs. At 4.066 chs., point for a special meander cor. at intersection with the N-S center line of sec. 25, hereinafter described.</p> <p>S. 11°24'30" E., 3.020 chs.</p> <p>S. 19°36'20" E., 7.044 chs.</p> <p>S. 66°08'20" E., 3.509 chs.</p> <p>S. 54°40'30" E., 7.026 chs. At 5.447 chs., point for a special meander cor., at the intersection with the N-S center line of sec. 25, hereinafter described.</p> <p>S. 78°07'00" E., 6.007 chs.</p> <p>S. 80°06'50" E., 7.507 chs.</p> <p>S. 1°43'30" E., 16.813 chs.</p> <p>S. 32°31'40" E., 8.045 chs.</p> <p>N. 82°38'00" E., 8.490 chs.</p> <p>N. 37°28'30" E., 5.668 chs.</p> <p>S. 42°43'30" E., 4.622 chs.</p> <p>S. 36°30'30" E., 4.725 chs. The meander cor. of secs. 25 and 36, hereinbefore described.</p>
--------	--

DEPENDENT RESURVEY OF A PORTION OF THE
ORIGINAL MEANDERS OF LOWER PAHRANAGAT LAKE,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>S. 24°56'10" E., 6.816 chs. At end of course, the meander cor. at intersection with the line bet. secs. 31 and 36, hereinbefore described.</p> <hr/> <p>SUBDIVISION OF SECTION 2, T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 11. N. 0°03'40" E., on the N-S center line of sec. 2. Over nearly level flood plain, through scattered undergrowth.</p> <p>2.00 Gravel road, 30 lks. wide, bears E. and W.</p> <p>13.40 Enter gently rolling land, edge bears N. 60° E. and S. 60° W.; through scattered undergrowth.</p> <p>20.207 Point for the C-S 1/16 sec. cor. of sec. 2. POINT NOT MONUMENTED</p> <p>31.70 Draw, drains S. 60° W.</p> <p>40.414 Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T8S R61E C 1/4 S 2 2010 From this point, a position determined by the Bureau of Sport Fisheries and Wildlife for the center 1/4 sec. cor. of sec. 2, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., firmly set, projecting 7 ins. above the ground, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE C 1/4 S2 1963, bears S. 0°02'40" W., 2.799 chs. dist. This position does not correlate with the dimensions on the unrecorded plat within acceptable limits and is not utilized during the course of this survey.</p> <p>58.10 Spur, bears S. 65° E. and N. 65° W.</p>
--------	--

SUBDIVISION OF SECTION 2,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.754	<p>The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 7 S., R. 61 E., executed concurrently under this same group.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 1 and 2.</p> <p>S. 89°35'30" W., on the E-W center line of sec. 2.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
20.30	Draw, drains S.
35.20	Draw, drains S.
40.141	The center 1/4 sec. cor. of sec. 2.
60.159	Point for the C-W 1/16 sec. cor. of sec. 2.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">W 1/16 C ——— C S2</p> <p style="text-align: center;">2010</p>
	<p>From this point, a position determined by the Bureau of Sport Fisheries and Wildlife for the C-W 1/16 sec. cor. of sec. 2, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., firmly set, projecting 2 ins. above the ground, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE W 1/16 C-C S2 1963, bears S. 0°13'20" E., 2.060 chs. dist. This position does not correlate with the dimensions on the unrecorded plat within acceptable limits and is not utilized during the course of this survey.</p>
71.50	Enter bottom lands, edge bears S. 10° E. and N. 10° W.
74.30	Asphalt surfaced road, 30 lks. wide, bears N. 10° E. and S. 10° W.
77.972	The point for a witness point, at intersection of the easterly line of Parcel No. 1317 L with the E-W center line of sec. 2, hereinafter described.
78.70	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, curves N. and S. 5° E.

SUBDIVISION OF SECTION 2,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
79.790	The point for a witness point, at intersection of the westerly line of Parcel No. 1317 L with the E-W center line of sec. 2, hereinafter described.
80.177	The 1/4 sec. cor. of secs. 2 and 3.
	From the point for the W 1/16 sec. cor. of secs. 2 and 11.
	N. 0°00'20" E., on the N-S center line of the SW1/4 of sec. 2. Over nearly level flood plain, through scattered undergrowth.
20.201	Point for the SW 1/16 sec. cor. of sec. 2, at intersection with the E-W center line of the SW1/4.
	POINT NOT MONUMENTED
30.60	Base of volcanic hill, slopes N. 30° E.
40.401	The C-W 1/16 sec. cor. of sec. 2.
	From the point for the C-S 1/16 sec. cor. of sec. 2.
	S. 89°36'30" W., on the E-W center line of the SW1/4 of sec. 2. Over gently rolling land, through scattered undergrowth.
14.10	Spur, bears N. 40° E. and S. 40° W.
16.00	Enter nearly level flood plain, edge bears N. 40° E. and S. 40° W.; through scattered undergrowth.
20.000	The point for the SW 1/16 sec. cor. of sec. 2.
21.20	Base of round hill.
31.40	Enter bottom lands, edge bears S. 30° E. and N. 30° W.; through scattered undergrowth.
32.928	The point for a witness point, at intersection of the easterly line of Parcel No. 1317 M with the E-W center line of the SW1/4 of sec. 2, hereinafter described.
33.772	The point for a witness point, at intersection of the southerly line of Parcel No. 1317 L with the E-W center line of the SW1/4 of sec. 2, said point being on the N. bdy. of Parcel No. 1317 M and on the computed center line of U.S. Highway No. 93., hereinafter described.
	Point is located on U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 26°33'40" E. and N. 26°33'40" W.
34.616	The intersection of the westerly line of Parcel No. 1317 M, with the E-W center line of the SW1/4 of sec. 2, hereinafter described.
34.785	The point for the witness point, at intersection of the westerly line of Parcel No. 1317 L with the E-W center line of the SW1/4 of sec. 2, hereinafter described.

SUBDIVISION OF SECTION 2,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
35.50	Pahranagat Creek, in a earthen ditch, 20 lks. wide, 2 ft. deep, course S. 20° E.
36.30	Trail road, 15 lks. wide, bears S. 20° E. and N. 20° W.
38.30	Enter rolling hills, edge bears S. 20° E. and N. 20° W.; through scattered undergrowth.
40.000	The point for the S 1/16 sec. cor. of secs. 2 and 3.
	From the C-W 1/16 sec. cor. of sec. 2.
	N. 0°00'20" E., on the N-S center line of the NW1/4 of sec. 2.
	Over a gently rolling volcanic hill, through scattered undergrowth.
10.70	Spur, bears N. 45° E. and S. 45° W.
30.90	Top of rocky cliff, 40 ft. high, bears E. and W.
	Thence over nearly level flood plain, drains S. 75° W.
38.00	Spur, bears N. 65° E. and S. 65° W.
40.532	The W 1/16 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., projecting 18 ins. above the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 7 S., R. 61 E., executed concurrently under this same group.
	From this point, United States Geological Survey triangulation station "Lake" bears S. 17°05'10" E., 21.834 chs. dist., monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, with a standard brass disk, 3 ins. diam., firmly attached to the top of the rebar, with top mkd. LAKE 1969 and a triangle.
	SUBDIVISION OF SECTION 11, T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 11 and 14.
	N. 1°56'50" E., on the N-S center line of sec. 11.
	Over bottom lands, through grasses.
19.502	Point for the C-S 1/16 sec. cor. of sec. 11.
	POINT NOT MONUMENTED
24.70	Enter gently rolling land, edge bears S. 25° E. and N. 25° W., through scattered undergrowth.

SUBDIVISION OF SECTION 11,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
27.102	The point for a witness point, at intersection of the westerly line of Parcel No. 1317 K with the N-S center line of sec. 11, hereinafter described.
29.253	<p>The C-N-S 1/64 sec. cor. of sec. 11, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a slight indentation in the ground, at the corroded end of a galvanized iron pipe, 1 1/2 ins. diam., 3 ft. long, lying loose on the surface of the ground. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S11 C-N-S 1/64</p> <p style="text-align: center;">2010</p> <p>Reset the galvanized iron pipe and set a steel fence post alongside the stainless steel post.</p> <p>From this corner, a wooden post, 7x2 ins., firmly set, projecting 3 ft. above the ground, coated with faded white and black paint, bears N. 37°32'30" W., 0.588 chs. dist.</p> <hr style="width: 20%; margin-left: 0;"/> <p>N. 1°56'50" E., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
3.90	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 27° E. and N. 26°33'30" W.
9.751	<p>Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8N R61E C 1/4 S11</p> <p style="text-align: center;">2010</p> <p>A wooden post, 7x2 ins., 4 ft. long, coated with faded white and black paint, was found lying loose nearby, original position indeterminable. Reset the wooden post alongside the stainless steel post.</p>
10.549	The point for a witness point, at intersection of the easterly line of Parcel No. 1317 K with the N-S center line of sec. 11, hereinafter described.

SUBDIVISION OF SECTION 11,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
29.246	Point for the C-N 1/16 sec. cor. of sec. 11. POINT NOT MONUMENTED
48.741	The 1/4 sec. cor. of secs. 2 and 11. <hr/>
	From the 1/4 sec. cor. of secs. 11 and 12. S. 89°23'50" W., on the E-W center line of sec. 11. Over gently rolling land, through scattered undergrowth.
19.852	Point for the C-E 1/16 sec. cor. of sec. 11. POINT NOT MONUMENTED
28.40	Large draw, drains S.
29.778	Point for the C-W-E 1/64 sec. cor. of sec. 11. POINT NOT MONUMENTED
39.704	The center 1/4 sec. cor. of sec. 11.
42.80	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 26°33'30" E. and N. 26°33'30" W.
46.021	The point for a witness point, at intersection of the westerly line of Parcel No. 1317 K with the E-W center line of sec. 11, hereinafter described.
53.50	Enter bottom lands, edge bears N. 35° E. and S. 15° W.; through grasses and tulles.
59.522	Point for the C-W 1/16 sec. cor. of sec. 11. POINT NOT MONUMENTED
79.340	The 1/4 sec. cor. of secs. 10 and 11. <hr/>
	From the E 1/16 sec. cor. of secs. 11 and 14. N. 2°14'30" E., on the N-S center line of the SE1/4 of sec. 11. Over gently rolling land, through scattered undergrowth.
1.135	The point for a witness point and Point of Curvature, at intersection of the easterly line of Parcel No. 1317 J, with the N-S center line of the SE1/4 of sec. 11, hereinafter described.
15.00	Draw, drains S. 45° W.

SUBDIVISION OF SECTION 11,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
19.469	<p>The SE 1/16 sec. cor. of sec. 11, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with the top of a mound of stone, 3 ft. base, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE SE 1/16 S11 1963, with a steel fence post, firmly set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S11</p> <p style="text-align: center;">2010</p> <p>Bury the concrete post and reset the steel fence post alongside the stainless steel post.</p> <p>From this corner, a wooden post, 7x2 ins., firmly set, projecting 3 ft. above the ground, bears S. 46°10'40" E., 0.104 chs. dist.</p> <p>From this same corner, a wooden post, 7x2 ins., firmly set, projecting 3 ft. above the ground, bears S. 89°47'50" W., 0.040 chs. dist.</p> <hr/> <p>N. 2°14'30" E., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
9.734	<p>Point for the C-N-SE 1/64 sec. cor. of sec. 11.</p>
	<p>POINT NOT MONUMENTED</p>
10.80	<p>Large draw, drains W.</p>
19.468	<p>Point for the C-E 1/16 sec. cor. of sec. 11.</p> <hr/>
	<p>From the point for the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>S. 89°17'20" W., on the E-W center line of the SE1/4 of sec. 11.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
19.754	<p>The SE 1/16 cor. of sec. 11.</p> <hr/> <p>S. 89°17'20" W., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>

SUBDIVISION OF SECTION 11,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
8.990	The point for a witness point, at intersection of the easterly line of Parcel No. 1317 J with the E-W center line of the SE1/4 of sec. 11, hereinafter described.
9.877	<p>The C-W-SE 1/64 cor. of sec. 11, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a galvanized iron pipe, 1 1/2 ins. diam., 3 ft. long, firmly set, projecting 1 1/2 ft. above a collar of stone, 2 ft. base, 1/2 ft. high, with a steel fence post set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S11 C-W-SE 1/64</p> <p style="text-align: center;">2010</p> <p>Reset the galvanized iron pipe and steel fence post alongside the stainless steel post.</p> <p>From this corner, a Nevada Department of Transportation right-of-way monument, bears N. 7°59'40" W., 0.069 chs. dist., monumented with a concrete post, 6x6 ins., firmly set, projecting 6 ins. above the ground, mkd. with an N cast into a face.</p> <hr/> <p>S. 89°17'20" W., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
2.50	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 26°33'30" E. and N. 27° W.
3.30	Improved gravel road, 40 lks. wide, bears S. 27° E. and N. 27° W.
3.926	The point for a witness point, at intersection of the westerly line of Parcel No. 1317 J with the E-W center line of the SE1/4 of sec. 11, hereinafter described.
9.877	<p>The point for the C-S 1/16 sec. cor. of sec. 11.</p> <hr/> <p>From the C-W-SE 1/64 cor. of sec. 11.</p> <p>N. 2°05'40" E., on the N-S center line of the NW1/4 of the SE1/4 of sec. 11.</p> <p>Over gently rolling land, through scattered undergrowth.</p>

SUBDIVISION OF SECTION 11,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
9.742	<p>Point for the NW-SE 1/64 sec. cor. of sec. 11, at intersection with the E-W center line of the NW1/4 of the SE1/4; there is no remaining evidence of the monument set by the Bureau of Sport Fisheries and Wildlife.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S11 NW-SE 1/64</p> <p style="text-align: center;">2010</p> <p>Set a steel fence post alongside the stainless steel post.</p>
19.484	<p>The point for the C-W-E 1/64 sec. cor. of sec. 11</p> <hr/> <p>From the point for the C-N-SE 1/64 cor. of sec. 11.</p> <p>S. 89°20'40" W., on the E-W center line of the NW1/4 of the SE1/4 of sec. 11.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
9.901	The NW-SE 1/64 sec. cor. of sec. 11.
17.60	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 27° E. and N. 27° W.
19.802	The C-N-S 1/64 sec. cor. of sec. 11.
	<hr/> <p>From the point for the C-W 1/16 sec. cor. of sec. 11.</p> <p>N. 1°42'00" E., on the N-S center line of the NW1/4 of sec. 11.</p> <p>Over bottom lands, through grasses.</p>
11.80	Enter gently rolling land, edge bears N. 35° E. and W.; through scattered undergrowth.
19.532	Point for the NW 1/16 sec. cor. of sec. 11, at intersection with the E-W center line of the NW1/4.
	POINT NOT MONUMENTED
30.439	The point for a witness point, at intersection of the westerly line of Parcel No. 1317 M with the N-S center line of the NW1/4 of sec. 11, hereinafter described.
31.60	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 27° E. and N. 26°33'30" W.
33.639	The point for a witness point, at intersection of the easterly line of Parcel No. 1317 M with the N-S center line of the NW1/4 of sec. 11, hereinafter described.

SUBDIVISION OF SECTION 11,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.064	The point for the W 1/16 sec. cor. of secs. 2 and 11.
	<hr/> <p>From the point for the C-N 1/16 sec. cor. of sec. 11. S. 89°30'50" W., on the E-W center line of the NW1/4 of sec. 11. Over gently rolling land, through scattered undergrowth.</p>
9.933	The point for a witness point, at intersection of the easterly line of Parcel No. 1317 K with the E-W center line of the NW1/4 of sec. 11, hereinafter described.
13.50	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 26°33'30" E. and N. 27° W.
16.680	The point for a witness point, at intersection of the westerly line of Parcel No. 1317 K with the E-W center line of the NW1/4 of sec. 11, hereinafter described.
19.899	The point for the NW 1/16 sec. cor. of sec. 11.
23.70	Enter bottom lands, edge bears N. 25° E. and S. 25° W.; through grasses.
39.798	The point for the N 1/16 sec. cor. of secs. 10 and 11.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 13, T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24. N. 0°53'10" E., on the N-S center line of sec. 13. Over gently rolling land, through scattered undergrowth.</p>
4.60	Draw, drains N. 75° W.
6.30	Draw, drains S. 60° W.
16.80	Large draw, drains S. 75° W.
20.190	Point for the C-S 1/16 sec. cor. of sec. 13. POINT NOT MONUMENTED
32.70	Large draw, drains N. 85° W.
36.60	Draw, drains W.
40.380	Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.

SUBDIVISION OF SECTION 13,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T8S R61E C 1/4 S13 2010</p>
61.20	Draw, drains S. 30° W.
66.40	Large draw, drains S. 75° W.
74.50	Spur, bears N. 45° E. and S. 45° W.
79.00	Draw, drains S. 35° W.
80.528	The 1/4 sec. cor. of secs. 12 and 13.
	<hr/> <p>From the 1/4 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set flush with the top of a mound of stone, 3 ft. base, 1 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 8 S., R. 61 E., executed under Group No. 355.</p> <p>Corner is located in a large draw, drains W.</p> <p>N. 89°17'20" W., on the E-W center line of sec. 13.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
11.00	Draw, drains S. 35° W.
27.00	Large draw, drains S. 45° W.
40.080	The center 1/4 sec. cor. of sec. 13.
44.60	Draw, drains S. 40° W.
60.178	Point for the C-W 1/16 sec. cor. of sec. 13.
	POINT NOT MONUMENTED
	Point is located in a large draw, drains S. 80° W.
80.276	The 1/4 sec. cor. of secs. 13 and 14.
	<hr/> <p>From the point for the W 1/16 sec. cor. of secs. 13 and 24.</p> <p>N. 0°59'00" E., on the N-S center line of the SW1/4 of sec. 13.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
13.20	Large draw, drains S. 70° W.
20.120	Point for the SW 1/16 sec. cor. of sec. 13, at intersection with the E-W center line of the SW1/4.
	POINT NOT MONUMENTED
23.40	Large draw, drains W.

SUBDIVISION OF SECTION 13,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
40.238	<p>The point for the C-W 1/16 sec. cor. of sec. 13.</p> <hr/> <p>From the point for the C-S 1/16 sec. cor. of sec. 13. N. 89°05'20" W., on the E-W center line of the SW1/4 of sec. 13. Over gently rolling land, through scattered undergrowth.</p>
20.132	The point for the SW 1/16 sec. cor. of sec. 13.
29.70	Draw, drains S. 45° W.
40.264	<p>The point for the S 1/16 sec. cor. of secs. 13 and 14.</p> <hr/> <p>From the W-W-W 1/256 sec. cor. of secs. 13 and 24. N. 1°03'20" E., on the computed N-S center line of the SW1/4 of the SW1/4 of the SW1/4 of sec. 13. Over gently rolling land, through scattered undergrowth.</p>
1.30	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 20° E. and N. 20° W.
10.033	<p>The C-W-SW-SW 1/256 sec. cor. of sec. 13, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a galvanized iron pipe, 1 1/2 ins. diam., 3 ft. long, firmly set, projecting 8 ins. above a collar of stone, 2 ft. base, 1/2 ft. high, with a steel fence post set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S13 C-W-SW-SW 1/256 2010</p> <p>Reset the galvanized iron pipe and steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 88°59'10" W., on a portion of the computed E-W center line of the SW1/4 of the SW1/4 of sec. 13.</p>
2.90	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 20° E. and N. 20° W.
5.037	The S-S 1/64 sec. cor. of secs. 13 and 14.

SUBDIVISION OF SECTION 14,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 1°41'40" E., on the N-S center line of sec. 14.</p> <p>Over bottom lands, through grasses and tulles.</p>
40.154	<p>Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T8S R61E C 1/4 S14</p> <p style="text-align: center;">2010</p>
60.009	<p>Point for the C-N 1/16 sec. cor. of sec. 14.</p> <p>POINT NOT MONUMENTED</p>
79.864	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>N. 89°59'20" W., on the E-W center line of sec. 14.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
5.173	<p>The point for a witness point, at intersection of the easterly line of Parcel No. 1317 I with the E-W center line of sec. 14, hereinafter described.</p> <p>Point is located in a large draw, drains S. 45° W.</p>
8.40	<p>U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 18°12'00" E. and N. 18°12'00" W.</p>
9.958	<p>The point for a witness point, at intersection of the westerly line of Parcel No. 1317 I with the E-W center line of sec. 14, hereinafter described.</p>
12.40	<p>Spur, bears N. 45° E. and S. 45° W.</p>
13.60	<p>Improved gravel road, 30 lks. wide, bears N. 20° E. and S. 20° W.</p>
14.20	<p>Enter bottom lands, edge bears N. 20° E. and S. 20° W.; through grasses and tulles.</p>
19.876	<p>Point for the C-E 1/16 sec. cor. of sec. 14.</p> <p>POINT NOT MONUMENTED</p>
39.752	<p>The center 1/4 sec. cor. of sec. 14.</p>
53.80	<p>Pahrnagat Creek, 20 lks. wide, 2 ft. deep, course S.</p>

SUBDIVISION OF SECTION 14,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
80.983	<p>The 1/4 sec. cor. of secs. 14 and 15.</p> <hr/> <p>From the point for the C-E 1/16 sec. cor. of sec. 14. N. 1°22'00" E., on the N-S center line of the NE1/4 of sec. 14. Over bottom lands, through grasses and tulles.</p>
19.995	<p>Point for the NE 1/16 sec. cor. of sec. 14, at intersection with the E-W center line of the NE1/4.</p> <p>POINT NOT MONUMENTED</p>
21.40	<p>Enter gently rolling land, edge bears S. 45° E. and N. 55° W.; through scattered undergrowth.</p>
22.663	<p>The point for a witness point, at intersection of the westerly line of Parcel No. 1317 J with the N-S center line of the NE1/4 of sec. 14, hereinafter described.</p>
24.20	<p>Improved gravel road, 30 lks. wide, bears S. 25° E. and N. 20° W.</p>
24.994	<p>The C-S-N-NE 1/256 sec. cor. of sec. 14, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a galvanized iron pipe, 1 1/2 ins. diam., 3 ft. long, firmly set, projecting 1 ft. above a collar of stone, 2 ft. base, 1/2 ft. high, with a steel fence post set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S14 C-S-N-NE 1/256 2010</p> <p>Reset the galvanized iron pipe and steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 1°22'00" E., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
7.50	<p>U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 20° E. and N. 20° W.</p>
14.997	<p>The E 1/16 sec. cor. of secs. 11 and 14.</p> <hr/>

SUBDIVISION OF SECTION 14,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the N 1/16 sec. cor. of secs. 13 and 14.</p> <p>S. 89°35'50" W., on the E-W center line of the NE1/4 of sec. 14.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
12.132	The point for a witness point, at intersection of the easterly line of Parcel No. 1317 I with the E-W center line of the NE1/4 of sec. 14, hereinafter described.
14.826	<p>Point for the C-W-E-NE 1/256 sec. cor. of sec. 14; there is no remaining evidence of the monument set by the Bureau of Sport Fisheries and Wildlife.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">S14 C-W-E-NE 1/256 2010</p> <p>from which I add</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 37°34'30" E., 122.6 lks. dist., with brass cap mkd. RM C-W-E-NE 1/256 S14 80.9 FT TO COR 2010 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 51°44'30" E., 126.4 lks. dist., with brass cap mkd. RM C-W-E-NE 1/256 S14 83.4 FT TO COR 2010 and an arrow pointing to the corner.</p>
15.40	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 18°12'00" E. and N. 18° W.
16.906	The point for a witness point, at intersection of the westerly line of Parcel No. 1317 I with the E-W center line of the NE1/4 of sec. 14, hereinafter described.
17.40	Improved gravel road, 30 lks. wide, bears S. 30° E. and N. 30° W.
18.00	Enter bottom lands, edge bears S. 30° E. and N. 30° W.; through grasses and tulles.
19.768	The point for the NE 1/16 sec. cor. of sec. 14.
39.534	The point for the C-N 1/16 sec. cor. of sec. 14.

SUBDIVISION OF SECTION 14,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-W-E-NE 1/256 sec. cor. of sec. 14.</p> <p>N. 1°17'10" E., on a portion of the computed N-S center line of the SW1/4 of the NE1/4 of the NE1/4 of sec. 14.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
5.007	<p>The SW-NE-NE 1/256 sec. cor. of sec. 14, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a galvanized iron pipe, 1 1/2 ins. diam., 3 ft. long, firmly set, projecting 1 ft. above the ground, with a steel fence post set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S14 SW-NE-NE 1/256 2010</p> <p>Reset the galvanized iron pipe and steel fence post alongside the stainless steel post.</p> <hr/> <p>S. 89°29'40" W., on a portion of the computed E-W center line of the SW1/4 of the NE1/4 of the NE1/4 of sec. 14.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
2.40	<p>U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, curves S. 18° E. and N. 18° W.</p>
4.935	<p>The C-S-N-NE 1/256 sec. cor. of sec. 14.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 24, T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 1°01'00" E., on the N-S center line of sec. 24.</p> <p>Over bottom lands, through grasses and tulles.</p>
0.40	<p>Pahranagat Creek, 25 lks. wide, 2 ft. deep, course S. 35° E.</p>
7.20	<p>Trail road, 15 lks. wide, bears S. 55° E. and N. 55° W.; enter gently rolling land through scattered undergrowth.</p>
17.50	<p>Abandoned asphalt surfaced road, 30 lks. wide, bears S. 55° E. and N. 55° W.</p>

SUBDIVISION OF SECTION 24,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
18.129	The point for a witness point, at intersection of the westerly line of Parcel No. 1317 H with the N-S center line of sec. 24, hereinafter described.
19.025	The point for a witness point, at intersection of the westerly line of Parcel No. 1318 A with the N-S center line of sec. 24, hereinafter described.
19.331	<p>Point selected for the witness C-S 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC C S1/16 ↑ S24 C</p> <p>2010</p> </div> <p>From this point, a rebar, 5/8 in. diam., encased in concrete, 3 ins. diam., 18 ins. long, was found lying loose on the surface of the ground, original position indeterminable, with a steel fence post, 4 ft. long, laying loose, 1 in. below the surface of the ground. Reset the concrete encased rebar and the steel fence post alongside the stainless steel post.</p>
19.983	True point for the C-S 1/16 sec. cor. of sec. 24.
20.30	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 41°33'10" E. and N. 41°33'10" W.
24.848	The point for a witness point, at intersection of the easterly line of Parcel No. 1317 H with the N-S center line of sec. 24, hereinafter described.
30.30	Gravel road, 25 lks. wide, bears N. 70° E. and S. 70° W.
39.967	<p>The center 1/4 sec. cor. of sec. 24, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with the top of a collar of stone, 2 ft. base, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE C 1/4 S24 1963, with a steel fence post set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p>

SUBDIVISION OF SECTION 24,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">T8S R61E C 1/4 S24</p> <p style="text-align: center;">2010</p> <p>Bury the concrete post and reset the steel fence post alongside the stainless steel post.</p> <hr/> <p>N. 1°01'00" E., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
19.957	<p>Point for the C-N 1/16 sec. cor. of sec. 24.</p> <p>POINT NOT MONUMENTED</p>
39.914	<p>The 1/4 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the 1/4 sec. cor. of sec. 24 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89°58'00" W., on the E-W center line of sec. 24.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
19.987	<p>Point for the C-E 1/16 sec. cor. of sec. 24.</p> <p>POINT NOT MONUMENTED</p>
28.20	<p>Large draw, S. 30° W.</p>
39.974	<p>The center 1/4 sec. cor. of sec. 24.</p> <hr/> <p>S. 89°58'00" W., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
12.50	<p>Trail road, 15 lks. wide, bears S. 60° E. and N. 60° W.; located in the bottom of a deep draw, drains N. 60° W.</p>
13.363	<p>The point for a witness point, at intersection of the easterly line of Parcel No. 1317 H with the E-W center line of sec. 24, hereinafter described.</p>
17.30	<p>U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, curves S. 35° E. and N. 30° W.</p>
18.965	<p>The point for a witness point, at intersection of the westerly line of Parcel No. 1317 H with the E-W center line of sec. 24, hereinafter described.</p>
20.169	<p>Point for the C-W 1/16 sec. cor. of sec. 24; there is no remaining evidence of the monument set by the Bureau of Sport Fisheries and Wildlife.</p>

SUBDIVISION OF SECTION 24,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>W 1/16</p> <p>C ——— C</p> <p>S24</p> <p>2010</p> </div> <p>Set a steel fence post alongside the stainless steel post.</p>
23.50	Deep draw, drains S. 40° W.
26.90	Spur, bears N. 45° E. and S. 45° W.
28.70	Improved gravel road, 30 lks. wide, bears S. 40° E. and N. 35° W.
37.50	Enter bottom lands, edge bears S. 20° E. and N. 20° W.; through grasses.
40.338	The 1/4 sec. cor. of secs. 23 and 24.
	<hr/> <p>From the E 1/16 sec. cor. of secs. 24 and 25.</p> <p>N. 0°45'30" E., on the N-S center line of the SE1/4 of sec. 24.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
2.161	The point for a witness point, at intersection of the easterly line of Parcel No. 1318 A with the N-S center line of the SE1/4 of sec. 24, hereinafter described.
7.10	Spur, bears S. 50° E. and N. 50° W.
17.20	Large draw, drains S. 50° W.
19.793	<p>The SE 1/16 sec. cor. of sec. 24, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with the top of a collar of stone, 2 ft. base, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE SE1/16 S24 1963, with a steel fence post set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p>

SUBDIVISION OF SECTION 24,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	SE 1/16 S24
	2010
	Bury the concrete post and reset the steel fence post alongside the stainless steel post.
	<hr/>
	N. 0°45'30" E., beginning new measurement.
	Over gently rolling land, through scattered undergrowth.
1.90	Draw, drains S. 70° W.
11.60	Draw, drains S. 60° W.
19.793	The point for the C-E 1/16 sec. cor. of sec. 24.
	<hr/>
	From the point for the S 1/16 sec. cor. of sec. 24 only, on the E. bdy. of the Tp., hereinbefore described.
	S. 89°25'40" W., on the E-W center line of the SE1/4 of sec. 24.
	Over gently rolling land, through scattered undergrowth.
6.50	Draw, drains S. 20° W.
20.082	The SE 1/16 sec. cor. of sec. 24.
	<hr/>
	S. 89°25'40" W., beginning new measurement.
	Over gently rolling land, through scattered undergrowth.
4.10	Trail road, 15 lks. wide, bears N. 40° E. and S. 40° W.
11.90	Spur, bears N. and S.
15.722	The point for a witness point, at intersection of the easterly line of Parcel No. 1318 A with the E-W center line of the SE1/4 of sec. 24, hereinafter described.
19.70	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 41°33'10" E. and N. 42° W.
20.082	The true point for the C-S 1/16 sec. cor. of sec. 24.
	<hr/>
	From the C-W 1/16 sec. cor. of sec. 24.
	N. 1°00'50" E., on the N-S center line of the NW1/4 of sec. 24.
	Over gently rolling land, through scattered undergrowth.
4.30	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 35° E. and N. 30° W.

SUBDIVISION OF SECTION 24,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
20.159	<p>The NW 1/16 sec. cor. of sec. 24, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with the top of a mound of stone, 3 ft. base, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE NW1/16 S24 1963, with a steel fence post alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S24</p> <p style="text-align: center;">2010</p> <p>Bury the concrete post and reset the steel fence post alongside the stainless steel post.</p>
	<hr/>
	<p>N. 1°00'50" E., beginning new measurement.</p>
	<p>Over gently rolling land, through scattered undergrowth.</p>
7.10	<p>Draw, drains S. 80° W.</p>
9.50	<p>Draw, drains S. 40° W.</p>
20.158	<p>The point for the W 1/16 sec. cor. of secs. 13 and 24.</p>
	<hr/>
	<p>From the point for the C-N 1/16 sec. cor. of sec. 24.</p>
	<p>N. 89°27'40" W., on the E-W center line of the NW1/4 of sec. 24.</p>
	<p>Over gently rolling land, through scattered undergrowth.</p>
9.90	<p>Trail road, bears N. 30° E. and S. 30° W.</p>
20.167	<p>The NW 1/16 sec. cor. of sec. 24.</p>
	<hr/>
	<p>N. 89°27'40" W., on beginning new measurement.</p>
	<p>Over gently rolling land, through scattered undergrowth.</p>
7.60	<p>U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 20° E. and N. 20° W.</p>
10.083	<p>Point for the C-W-NW 1/64 sec. cor. of sec. 24; there is no remaining evidence of the monument set by the Bureau of Sport Fisheries and Wildlife.</p>


SUBDIVISION OF SECTION 24,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S24 C-W-NW 1/64</p> <p style="text-align: center;">2010</p> <p>Set a steel fence post alongside the stainless steel post.</p>
17.40	Improved gravel road, 30 lks. wide, bears S. 20° E. and N. 20° W.
18.20	Enter bottom lands, edge bears S. 10° W. and N. 20° W.; through grasses.
20.166	The point for the N 1/16 sec. cor. of secs. 23 and 24.
	<hr/> <p>From the C-W-NW 1/64 sec. cor. of sec. 24.</p> <p>N. 1°00'30" E., on the N-S center line of the NW1/4 of the NW1/4 of sec. 24.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
7.20	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 20° E. and N. 20° W.
20.261	The W-W 1/64 sec. cor. of secs. 13 and 24.
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 25, T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 0°34'40" E., on the N-S center line of sec. 25.</p> <p>Over bottom lands, through grasses and tules.</p>
12.50	Ravine, drains N. 30° E.
20.000	<p>The C-S 1/16 sec. cor. of sec. 25, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with the top of a mound of stone, 2 1/2 ft. base, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE C S1/16 S25 1963, with a steel fence post set alongside. This is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p>

SUBDIVISION OF SECTION 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S \ 1/16 \quad \quad S25 \\ C \end{array}$ <p>2010</p> <p>Bury the concrete post and reset the steel fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°34'40" E., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p> <p>7.80 Enter bottom lands, edge bears S. 25° E. and N. 25° W.; through grasses and tulles.</p> <p>8.634 Point for a special meander cor. on the N-S center line of sec. 25, at intersection with the adjusted record meander line of Lower Pahrnagat Lake and at the line of ordinary high water.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} SMC \\ C \\ \diagdown \quad \quad \diagup \\ S \ 25 \\ C \end{array}$ <p>2010</p> <p>Thence on a blank line across the waters of Lower Pahrnagat Lake.</p> <p>31.675 Point for a special meander cor. on the N-S center line of sec. 25, at intersection with the adjusted record meander line of Lower Pahrnagat Lake and at the line of ordinary high water.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S \ 25 \\ C \\ SMC \end{array}$ <p>2010</p> </div> </div></div>
--------	--

SUBDIVISION OF SECTION 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence continue on the N-S center line of sec. 25.
32.20	Enter bottom lands, edge bears E. and W., through grasses and tulles.
60.254	The 1/4 sec. cor. of secs. 24 and 25.
	<hr/> <p>From the E 1/16 sec. cor. of secs. 24 and 25.</p> <p>S. 0°33'40" W., on the N-S center line of the NE1/4 of sec. 25, on a weighted mean bearing.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
2.40	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 42° E. and N. 41°33'00" W.
3.705	The point for a witness point, at intersection of the westerly line of Parcel No. 1317 G with the N-S center line of the NE1/4 of sec. 25, hereinafter described.
9.10	Enter bottom lands, edge bears S. 60° E. and N. 20° W.; through grasses.
18.819	<p>Point for a special meander cor. on the N-S center line of the NE1/4 of sec. 25., at intersection with the adjusted record meander line of Lower Pahranaagat Lake and at the line of ordinary high water.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>2010</p> <hr/>

METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

MEMORANDUM


The lands acquired by the United States of America from the Buckhorn Investment Company, Grantor, are described in the Warranty Deed dated August 6, 1963 and recorded in the official records of Lincoln County, Nevada on August 22, 1963, under Document No. 49677, in Book M-1 of Real Estate Deeds on page 178. Within this township the warranty deed excluded parcel Nos. 1317 G, 1317 H, 1317 I, 1317 J, 1317 K, 1317 L and 1317 M as described in the deed from Buckhorn Investment Company of Nevada to the State of Nevada, dated March 21, 1962, and recorded in the Official Records of Lincoln County, Nevada, on April 2, 1962, under Document No. 39269, in Book L-1 of Real Estate Deeds on Pages 484 to 487. Also excluded was Parcel No. 1318A, as described in the deed from Floyd R. Lamb and Eleanor Lamb, husband and wife, to the State of Nevada on March 20, 1962, and recorded in the Official Records of Lincoln County, Nevada, on April 2, 1962, under Document No. 39271, in Book L-1 of Real Estate Deeds on Pages 487. The following metes-and-bounds surveys are referenced to the excluded parcels and describe those portions of the deeded lines that define the boundaries in common with adjoining Federal interest.

Application Nevada 050551, supplement to application Nevada 050551 and application Nevada 058197, all prepared by the State of Nevada, Department of Highways and approved by the Department of Interior on May 24, 1933, March 26, 1959 and April 19, 1962, respectively, accompanied by supporting highway plans and property schedules supplied by the Nevada Department of Transportation were referenced during the execution of these surveys to determine the limits of the rights-of-ways described within the conveyance documents.

PARCEL NO. 1317 G

From the point for a witness point, at intersection of the westerly line of Parcel No. 1317 G with the N-S center line of the NE1/4 of sec. 25.



Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.



2010

From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 194+10.65 POT DIST 60.45 ANGLE 90, bears S. 61°09'50" E., 5.438 chs. dist.

METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this same point, United States Coast and Geodetic Survey bench mark "B 312" bears S. 33°20'10" E., 2.897 chs. dist., monumented with a standard brass cap, 3 1/2 ins. diam., set in a concrete post, 6x6 ins., firmly set, projecting 3 ins. above the ground, with top mkd. B312 1941.</p> <p>N. 41°33'00" W., on the westerly line of Parcel No. 1317 G, through the NW1/4 of the NE1/4 of sec. 25.</p> <p>4.867 Point for a witness point, at intersection of the westerly line of Parcel No. 1317 G with the line bet. secs. 24 and 25, identical with the intersection of the westerly boundary of Parcel No. 1318 A, with the line bet. secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP T8SR61E</p>  <p>2010</p> </div>
	<div style="text-align: center;"> <p><u>PARCEL NO. 1318 A</u></p> </div> <p>From the point for a witness point, at intersection of the easterly line of Parcel No. 1318 A with the N-S center line of the SE1/4 of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP E S 24 E</p>  <p>2010</p> </div> <p>N. 41°33'10" W., on the easterly line of Parcel No. 1318 A, through the SW1/4 of the SE1/4 of sec. 24.</p> <p>23.349 Point for a witness point, at intersection of the easterly line of Parcel No. 1318 A with the E-W center line of the SE1/4 of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="889 262 1036 420"> <p>WP S S ——— S \ 24 / 2010</p> </div>
	<p>From the point for a witness point, at intersection of the westerly line of Parcel No. 1318 A with the line bet. secs. 24 and 25, identical with the intersection of the westerly line of Parcel No. 1317 G with the line bet. secs. 24 and 25, hereinbefore described.</p>
	<p>N. 41°33'10" W., on the westerly line of Parcel No. 1318 A, through the SW1/4 of the SE1/4 of sec. 24.</p>
24.573	<p>Nevada Department of Transportation right-of-way monument, a wooden post, 4x4 ins., firmly set, projecting 4 ft. above the ground, mkd. R/W with faded black and white paint.</p>
24.982	<p>Point for a witness point, at intersection of the westerly line of Parcel No. 1318 A with the N-S center line of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<div data-bbox="922 1012 1003 1222"> <p>WP C S ——— C \ 24 / 2010</p> </div>
	<p style="text-align: center;"><u>PARCEL NO. 1317 H</u></p> <p>From the point for a witness point, at intersection of the easterly line of Parcel No. 1317 H with the N-S center line of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div data-bbox="901 1554 987 1785"> <p>WP C S ——— C \ 24 / 2010</p> </div> <p>N. 41°33'10" W., on the easterly line of Parcel No. 1317 H, through the E1/2 of the SW1/4 of sec. 24.</p>

METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

14.310

Point for a witness point and a Point of Curvature established by the Nevada Department of Transportation, monumented with the remains of a wooden post, 4x4 ins., with the bottom portion, 2 1/2 ft. long, firmly set, 6 ins. below the surface of the ground and the top portion, 3 ft. long, lying on the surface of the ground nearby and mkd. illegibly with faded black and white paint.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

WP

S24

2010

Buried the bottom portion of the wooden post alongside the stainless steel post and reset the top portion of the wooden post alongside.

From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 229+47.22 PC DIST 39.35 ANGLE 90, bears S. 48°26'50" W., 2.434 chs. dist.

From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 229+47.22 PC DIST 115.20 ANGLE 90, bears S. 48°26'50" W., 1.284 chs. dist.

Thence along the arc of a circular curve to the right having a radius of 4800.00 ft.; the long chord of said arc bears N. 39°18'45" W., 5.686 chs. dist., continuing on the easterly line of Parcel No. 1317 H.

5.687

Point for a witness point, at intersection of the easterly line of Parcel No. 1317 H with the E-W center line of sec. 24.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

WP

S

C—C

24

2010

METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the point for a witness point, at intersection of the westerly line of Parcel No. 1317 H with the N-S center line of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="909 472 998 640"> </div> <p>2010</p> <p>N. 41°33'10" W., on the westerly line of Parcel No. 1317 H, through the E1/2 of the SW1/4 of sec. 24.</p> <p>19.258 Point for a witness point and Point of Curvature established by the Nevada Department of Transportation, monumented with the bottom portion of a wooden post, 4x4 ins., 2 ft. long, firmly set 6 ins. below the surface of the ground, with the top portion of the post, 4x4 ins., 3 ft. long, laying loose alongside, mkd. with faded white paint.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="885 1144 982 1312"> </div> <p>2010</p> <p>Bury the bottom portion of the wooden post alongside the stainless steel post and reset the top portion of the wooden post alongside.</p> <hr/> <p>Thence along the arc of a circular curve to the right having a radius of 5100.00 ft.; the long chord of said arc bears N. 38°03'40" W., 9.412 chs. dist., continuing on the westerly line of Parcel No. 1317 H.</p> <p>9.418 Point for a witness point, at intersection of the westerly line of Parcel No. 1317 H with the E-W center line of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="889 262 1039 441"> <p>WP S C — C 24 2010</p> </div> <hr/> <div data-bbox="820 499 1096 531"> <p>PARCEL NO. 1317 I</p> </div> <div data-bbox="435 556 1437 636"> <p>From the point for a witness point, at intersection of the easterly line of Parcel No. 1317 I with the line bet. secs. 13 and 14.</p> </div> <div data-bbox="435 661 1469 741"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="893 766 1015 982"> <p>WP T8SR61E S14 S13 2010</p> </div> <div data-bbox="435 1008 1372 1066"> <p>N. 18°12'00" W., on the easterly line of Parcel No. 1317 I, through the E1/2 of the SE1/4 of sec. 14.</p> </div> <div data-bbox="289 1087 1453 1146"> <p>15.666 Point for a witness point, at intersection of the easterly line of Parcel No. 1317 I with the E-W center line of sec. 14.</p> </div> <div data-bbox="435 1171 1469 1251"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="885 1276 1031 1455"> <p>WP S C — C 14 2010</p> </div> <div data-bbox="435 1486 1453 1545"> <p>Thence continue N. 18°12'00" W., on the easterly line of Parcel No. 1317 I, through the SE1/4 of the NE1/4 of sec. 14.</p> </div> <div data-bbox="289 1566 1453 1646"> <p>36.767 Point for a witness point, at intersection of the easterly line of Parcel No. 1317 I with the E-W center line of the NE1/4 of sec. 14.</p> </div> <div data-bbox="435 1671 1469 1751"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div>
--------	---

METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="889 268 1036 386" data-label="Diagram"> </div> <div data-bbox="922 415 987 441" data-label="Text"> <p>2010</p> </div> <div data-bbox="435 474 1461 579" data-label="Text"> <p>From this point, a Nevada Department of Transportation right-of-way monument, a concrete post, 6x6 ins., firmly set flush with the surface of the ground, mkd. with an N cast into a face, bears S. 74°26'30" W., 1.668 chs. dist.</p> </div> <hr/> <div data-bbox="435 638 1429 718" data-label="Text"> <p>From the point for a witness point, at intersection of the westerly line of Parcel No. 1317 I with the line bet. secs. 13 and 14.</p> </div> <div data-bbox="435 743 1461 823" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="893 852 1010 1003" data-label="Diagram"> </div> <div data-bbox="922 1033 987 1058" data-label="Text"> <p>2010</p> </div> <div data-bbox="435 1087 1377 1146" data-label="Text"> <p>N. 18°12'00" W., on the westerly line of Parcel No. 1317 I, through the E1/2 of the SE1/4 of sec. 14.</p> </div> <div data-bbox="289 1167 1461 1327" data-label="Text"> <p>10.995 From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 279+64.69 POT DIST 39.65 ANGLE 90, bears N. 71°48'00" E., 0.919 chs. dist.</p> </div> <div data-bbox="435 1352 1445 1516" data-label="Text"> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 279+64.69 POT DIST 57.35 ANGLE 90, bears N. 71°48'00" E., 2.384 chs. dist.</p> </div> <div data-bbox="289 1537 1445 1591" data-label="Text"> <p>30.159 Point for a witness point, at intersection of the westerly line of Parcel No. 1317 I with the E-W center line of sec. 14.</p> </div> <div data-bbox="435 1617 1458 1696" data-label="Text"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="883 1701 1029 1814" data-label="Diagram"> </div> <div data-bbox="922 1848 987 1873" data-label="Text"> <p>2010</p> </div>
--------	--



METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Thence continue N. 18°12'00" W., on the westerly line of Parcel No. 1317 I, through the SE1/4 of the NE1/4 of sec. 14.</p>
51.224	<p>Point for a witness point, at intersection of the westerly line of Parcel No. 1317 I with the E-W center line of the NE1/4 of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="885 556 1031 714" style="text-align: center;"> </div> <hr/> <p style="text-align: center;"><u>PARCEL NO. 1317 J</u></p> <p>From a point for a witness point, at intersection of the easterly line of Parcel No. 1317 J with the N-S center line of the SE1/4 of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="901 1039 990 1249" style="text-align: center;"> </div>
15.120	<p>Thence along an arc of a circular curve to the left having a radius of 10,200.00 ft.; the long chord of said arc bears N. 23°45'20" W., 15.114 chs. dist., on a portion of the easterly line of Parcel No. 1317 J, through the SW1/4 of the SE1/4 of sec. 11.</p> <p>Point for a witness point and a Point of Tangency established by the Nevada Department of Transportation, monumented with a wooden post, 4x4 ins., 6 ft. long, firmly set, projecting 4 ft. above the ground, no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="909 1701 1031 1879" style="text-align: center;"> </div>




METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reset the wooden post alongside the stainless steel post.</p> <p>From this point, a Nevada Department of Transportation highway station, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 329+60.06 PT DIST 45.60 ANGLE 90, bears S. 63°26'30" W., 2.343 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 329+60.06 PT DIST 60.70 ANGLE 90, bears S. 63°26'30" W., 3.953 chs. dist.</p>
4.893	<p>Thence N. 26°33'30" W., continuing on a portion of the easterly line of Parcel No. 1317 J.</p> <p>Point for a witness point, at intersection of the easterly line of Parcel No. 1317 J with the E-W center line of the SE1/4 of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="860 903 1055 1092"> <p>2010</p> </div>
5.141	<p>From a point for a witness point, at intersection of the westerly line of Parcel No. 1317 J with the N-S center line of the NE1/4 of sec. 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="909 1344 1006 1596"> <p>2010</p> </div> <p>Thence along an arc of a circular curve to the right having a radius of 2050.00 ft.; the long chord of said arc bears N. 23°08'50" W., 5.135 chs. dist., on the westerly line of Parcel No. 1317 J, through the NW1/4 of the NE1/4 of sec. 14.</p> <p>Point for a witness point and a Point of Tangency established by the Nevada Department of Transportation, monumented with a concrete post, 6x6 ins., firmly set, projecting 1 ft. above the ground, mkd. with an N cast into a face.</p>




METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Thence N. 18°24'20" W., continuing on the westerly line of Parcel No. 1317 J.
4.840	<p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 315+01.50 PC DIST 57.55 ANGLE 90, bears N. 71°35'40" E., 2.934 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 315+01.50 PC DIST 82.05 ANGLE 90, bears N. 71°35'40" E., 5.049 chs. dist.</p>
13.180	<p>Point for a witness point, at intersection of the westerly line of Parcel No. 1317 J with the line bet. secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p>  <p>2010</p> </div>
33.601	<p>Thence continue N. 18°24'20" W., on the westerly line of Parcel No. 1317 J, through the SW1/4 of the SE1/4 of sec. 11.</p> <p>Point for a witness point, at intersection of the westerly line of Parcel No. 1317 J with the E-W center line of the SE1/4 of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP</p>  <p>2010</p> </div> <hr/> <p style="text-align: center;"><u>PARCEL NO. 1317 K</u></p> <p>From the point for a witness point, at intersection of the easterly line of Parcel No. 1317 K with the N-S center line sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	
1.283	<p>N. 26°33'30" W., on the easterly line of Parcel No. 1317 K, through the SE1/4 of the NW1/4 of sec. 11.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 348+54.55 POT DIST 54.80 ANGLE 90, bears S. 63°26'30" W., 2.202 chs. dist.</p>
20.797	<p>Point for a witness point, at intersection of the easterly line of Parcel No. 1317 K with the E-W center line of the NW1/4 of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> 
	<p>From the point for a witness point, at intersection of the westerly line of Parcel No. 1317 K with the N-S center line of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p>  <p>From this point, a Nevada Department of Transportation right-of-way monument, a concrete post, 6x6 ins., firmly set, projecting 1 1/2 ft. above the ground, mkd. with an N cast into a face, bears N. 62°28'50" E., 6.058 chs. dist.</p> <p>N. 26°33'30" W., on the westerly line of Parcel No. 1317 K, through the NE1/4 of the SW1/4 of sec. 11</p>



METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
0.099	A Nevada Department of Transportation right-of-way monument, a concrete post, 6x6 ins., firmly set, projecting 8 ins. above the ground, mkd. with an N cast into a face.
13.224	<p>Point for a witness point, at intersection of the westerly line of Parcel No. 1317 K with the E-W center line of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p>  <p>Continue N. 26°33'30" W., on the westerly line of Parcel No. 1317 K, through the SE1/4 of the NW1/4 of sec. 11.</p>
34.922	<p>Point for a witness point, at intersection of the westerly line of Parcel No. 1317 K with the E-W center line of the NW1/4 of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> 
	<p style="text-align: center;"><u>PARCEL NO. 1317 M</u></p> <p>From the point for a witness point, at intersection of the easterly line of Parcel No. 1317 M with the N-S center line of the NW1/4 of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> 




METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 368+85.05 POT DIST 51.90 ANGLE 90, bears S. 26°43'00" E., 5.548 chs. dist. (Calculated, 50.90 ft.)</p> <p>N. 26°33'30" W., on the easterly line of Parcel No. 1317 M, through the NW1/4 of the NW1/4 of sec. 11.</p>
6.041	<p>Point for a witness point, at intersection of the easterly line of Parcel No. 1317 M with the line bet. secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="906 720 1019 892" data-label="Diagram"> <p>2010</p> </div> <p>Continue N. 26°33'40" W., on the easterly line of Parcel No. 1317 M, through SW1/4 of the SW1/4 of sec. 2.</p>
28.547	<p>Point for a witness point, at intersection of the easterly line of Parcel No. 1317 M with the E-W center line of the SW1/4 of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="873 1224 1052 1396" data-label="Diagram"> <p>2010</p> </div>
	<p>From the point for a witness point, at intersection of the westerly line of Parcel No. 1317 M with the N-S center line of the NW1/4 of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>



METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="889 264 1019 443"> <p>WP W S 11 W</p>  </div> <div data-bbox="922 474 987 499">2010</div> <div data-bbox="435 531 1377 583"> <p>N. 26°33'30" W., on the westerly line of Parcel No. 1317 M, through the NW1/4 of the NW1/4 of sec. 11.</p> </div> <div data-bbox="305 611 1458 663"> <p>9.605 Point for a witness point, at intersection of the westerly line of Parcel No. 1317 M with the line bet. secs. 2 and 11.</p> </div> <div data-bbox="435 688 1458 768"> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> </div> <div data-bbox="889 800 1019 957"> <p>WP T8S R61E S 2 S11</p>  </div> <div data-bbox="922 978 987 1003">2010</div> <div data-bbox="435 1035 1393 1087"> <p>Thence continuing N. 26°33'40" W., on the westerly line of Parcel No. 1317 M, through the SW1/4 of the SW1/4 of sec. 2.</p> </div> <div data-bbox="289 1115 1458 1192"> <p>31.738 Point for a witness point, at intersection of the westerly line of Parcel No. 1317 M with the southerly line of Parcel No. 1317 L, hereinafter described.</p> </div> <div data-bbox="289 1220 1458 1350"> <p>32.111 Intersect the westerly line of Parcel No. 1317 M with the E-W center line of the SW1/4 of sec. 2, established by the Nevada Department of Transportation, monumented with a wooden post, 4x4 ins., 6 ft. long, firmly set, projecting 4 ft. above the ground, no marks visible.</p> </div> <hr/> <div data-bbox="813 1413 1084 1438"> <p><u>PARCEL NO. 1317 L</u></p> </div> <div data-bbox="435 1465 1458 1591"> <p>From the point for a witness point, at intersection of the southerly line of Parcel No. 1317 L with the E-W center line of the SW1/4 of sec. 2, said point being on the N. bdy. of Parcel No. 1317 M and on the computed center line of U.S. Highway No. 93.</p> </div> <div data-bbox="435 1623 1312 1648"> <p>Set a PK nail, mkd. PK, flush with the asphalt surface.</p> </div> <div data-bbox="435 1675 1409 1728"> <p>Point is located in U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 26°33'40" E. and N. 26°33'40" W.</p> </div> <div data-bbox="435 1759 1409 1812"> <p>N. 63°26'20" E., on a portion of the southerly line of Parcel No. 1317 L, through the NW1/4 of the SW1/4 of sec. 2.</p> </div> <div data-bbox="305 1839 1458 1892"> <p>0.909 Point for a witness point and the southeast corner of Parcel No. 1317 L, in sec. 2.</p> </div>
--------	---

METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="909 367 1023 546"> <p>WP</p>  <p>2010</p> </div> <hr/> <p>Thence N. 26°33'40" W., on the easterly line of Parcel No. 1317 L, continuing through the NW1/4 of the SW1/4 of sec. 2.</p>
0.344	<p>Point for a witness point and Point of Curvature.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="909 850 1023 1029"> <p>WP</p>  <p>2010</p> </div> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 391+82.24 PC DIST 88.00 ANGLE 90, bears N. 63°26'20" E., 0.424 chs. dist.</p> <hr/> <p>Thence along the arc of a circular curve to the right having a radius of 2940.00 ft.; the long chord of said arc bears N. 13°34'50" W., 20.012 chs. dist., continuing on the easterly line of Parcel No. 1317 L, through the NW1/4 of the SW1/4 of sec. 2.</p>
20.184	<p>Point for a witness point, at intersection of the easterly line of Parcel No. 1317 L with the E-W center line of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="876 1617 1006 1827"> <p>WP</p>  <p>2010</p> </div>




METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Thence continuing along the arc of a circular curve to the right having a radius of 2940.00 ft.; the long chord of said arc bears N. 6°55'00" E., 11.654 chs. dist., on the easterly line of Parcel No. 1317 L through the W1/2 of the NW1/4 of sec. 2.</p>
31.872	<p>Point for a witness point and a Point of Tangency established by the Nevada Department of Transportation, monumented with a wooden post, 4x4 ins., 5 ft. long, firmly set, projecting 2 1/2 ft. above the ground, no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="909 672 1006 882"> <p>WP</p>  </div> <p>Reset the wooden post alongside the stainless steel post.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 413+28.78 PT DIST 83.25 ANGLE 90, bears S. 75°34'00" E., 0.353 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 413+28.78 PT DIST 120.10 ANGLE 90, bears S. 75°34'00" E., 0.912 chs. dist.</p> <hr/> <p>Thence N. 14°26'00" E., continuing on the easterly line of Parcel No. 1317 L, through the W1/2 of the NW1/4 of sec. 2.</p>
8.230	<p>Point for a witness point, at an angle point of Parcel No. 1317 L, in sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="909 1638 1006 1848"> <p>WP</p>  </div>



METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 40°06'40" E., continuing on the easterly line of Parcel No. 1317 L, through the W1/2 of the NW1/4 of sec. 2.
2.604	<p>Point for a witness point and an angle of Parcel No. 1317 L, in sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>
	<div data-bbox="885 556 1031 745" data-label="Diagram"> </div> <p>N. 14°26'00" E., continuing on the easterly line of Parcel No. 1317 L, through the W1/2 of the NW1/4 of sec. 2.</p>
9.341	<p>Point of Curvature, falls on a cliff face, 25 ft. high, edge bears N. 50° E. and S. 50° W., where it is impracticable to establish a permanent monument.</p> <p>From this point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 423+88.61 PC DIST 109.60 ANGLE 90, bears N. 75°34'00" W., 1.372 chs. dist.</p> <p>From this same point, a Nevada Department of Transportation highway station utilized to determine the centerline of the right-of-way of U.S. Highway No. 93, monumented with a standard Nevada Department of Transportation brass tablet, set in concrete, mkd. STA 423+88.61 PC DIST 57.95 ANGLE 90, bears N. 75°34'00" W., 2.153 chs. dist.</p> <p>Thence along an arc of a circular curve to the left having a radius of 5200.00 ft.; the long chord of said arc bears N. 9°14'20" W., 14.266 chs. dist., continuing on the easterly line of Parcel No. 1317 L, through the W1/2 of the NW1/4 of sec. 2.</p>
14.286	<p>Point for a witness point, at intersection of the easterly line of Parcel No. 1317 L with the line bet. secs. 2 and 35, on the N. bdy. of the Tp.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>



METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>WP T7SR61E S35  T8S 2010</p>
0.757	<p>From the point for a witness point, at intersection of the southerly line of Parcel No. 1317 L with the E-W center line of the SW1/4 of sec. 2, said point being on the N. bdy. of Parcel No. 1317 M and on the computed center line of U.S. Highway No. 93.</p> <p>Thence S. 63°26'20" W., on a portion of the southerly line of Parcel No. 1317 L, through the W1/2 of the SW1/4 of sec. 2.</p> <p>Point for a witness point, at intersection of the westerly line of Parcel No. 1317 M with the southerly line of Parcel No. 1317 L.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>WP  S 2 2010</p>
0.909	<p>Point for a witness point, at the southwest corner of Parcel No. 1317, in sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p>WP  S 2 2010</p>
0.344	<p>Thence N. 26°33'40" W., on the westerly line of Parcel No. 1317 L, continuing through the W1/2 of the SW1/4 of sec. 2.</p> <p>Point for a witness point and Point of Curvature.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p style="text-align: center;">WP S 2 2010</p> 
	<p>Thence along the arc of a circular curve to the right having a radius of 3060.00 ft.; the long chord of said arc bears N. 26°29'50" W., 0.103 chs. dist., continuing on the westerly line of Parcel No. 1317 L, through the W1/2 of the SW1/4 of sec. 2.</p>
0.103	<p>Intersect the westerly line of Parcel No. 1317 L, with the E-W center line of the SW1/4 of sec. 2.</p> <p>Thence continuing along the arc of a circular curve to the right having a radius of 3060.00 ft.; the long chord of said arc bears N. 13°30'50" W., 20.734 chs. dist., on the westerly line of Parcel No. 1317 L, through the W1/2 of the SW1/4 of sec. 2.</p>
21.014	<p>Point for a witness point, at intersection of the westerly line of Parcel No. 1317 L with the E-W center line of sec. 2.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">WP S C — C 2 2010</p> 
	<p>Thence continuing along the arc of a circular curve to the right having a radius of 3060.00 ft.; the long chord of said arc bears N. 6°55'10" E., 12.126 chs. dist., on the westerly line of Parcel No. 1317 L, through the W1/2 of the NW1/4 of sec. 2.</p>
33.174	<p>Point for a witness point and a Point of Tangency established by the Nevada Department of Transportation, monumented with a wooden post, 4x4 ins., 6 ft. long, firmly set, projecting 4 ft. above the ground, no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>

METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<div data-bbox="873 264 987 441"> <p>WP S 2  2010</p> </div> <p>Reset the wooden post alongside the stainless steel post.</p> <hr/> <p>N. 14°26'00" E., continuing on the westerly line of Parcel No. 1317 L, through the W1/2 of the NW1/4 of sec. 2.</p> <p>11.996 Point for a witness point and an angle point of Parcel No. 1317 L, established by the Nevada Department of Transportation, monumented with a wooden post, 4x4 ins., 6 ft. long, firmly set, projecting 4 ft. above the ground, no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="889 924 987 1100"> <p>WP S 2  2010</p> </div> <p>Reset the wooden post alongside the stainless steel post.</p> <hr/> <p>N. 4°37'20" W., continuing on the westerly line of Parcel No. 1317 L, through the W1/2 of the NW1/4 of sec. 2.</p> <p>0.049 Point for a witness point and a Point of Curvature established by the Nevada Department of Transportation, monumented with a concrete post, 6x6 ins., firmly set, projecting 1 in. above the ground, mkd. with an N cast into a face.</p> <hr/> <p>Thence along the arc of a circular curve to the right having a radius of 2050.00 ft.; the long chord of said arc bears N. 2°52'40" E., 8.108 chs. dist., continuing on the westerly line of Parcel No. 1317 L, through the W1/2 of the NW1/4 of sec. 2.</p> <p>8.132 Point for a witness point and Point of Tangency.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 2 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p>
--------	---

METES-AND-BOUNDS SURVEYS OF CERTAIN PARCEL BOUNDARIES
THROUGH PORTIONS OF SECTIONS 2, 11, 14, 24 AND 25,
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">WP S 2 (</p>
	<p style="text-align: center;">2010</p> <hr/>
	<p>Thence N. 10°22'40" E., continuing on the westerly line of Parcel No. 1317 L, through the W1/2 of the NW1/4 of sec. 2.</p>
0.90	<p>Upper Pahrnagat Lake, edge bears NE and SW.; thence across the surface of the water.</p>
5.326	<p>Point of Curvature, falls in Upper Pahrnagat Lake, where it is impracticable to establish a permanent monument.</p> <p>From this point, a Nevada Department of Transportation right-of-way monument, bears S. 79°37'20" E., 0.379 chs. dist., monumented with a concrete post, 6x6 ins., firmly set, projecting 2 ft. above the ground, mkd. with an N cast into a face.</p> <hr/>
	<p>Thence along the arc of a circular curve to the left having a radius of 950.00 ft.; the long chord of said arc bears N. 3°03'40" E., 3.670 chs. dist., continuing on the westerly line of Parcel No. 1317 L, through the W1/2 of the NW1/4 of sec. 2.</p>
3.680	<p>Intersect the westerly line of Parcel No. 1317 L, with the line bet. secs. 2 and 35, on the N. bdy. of the Tp.</p> <p>Point is located in Upper Pahrnagat Lake, where it is impracticable to establish a permanent monument.</p> <hr/>
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land surveyed and resurveyed within Township 8 South, Range 61 East, is situated about seven miles southeast of Alamo, Nevada. The average elevation is 3,200 ft. above sea level. The terrain varies from gently rolling in the eastern portion to nearly level bottom lands in the central portion, with the remaining terrain being gently rolling. The rolling portions of the terrain drains towards the central portion and the central portion drains to the southeast. The soil varies from rocky in the higher elevations to black loam in the bottom land. The vegetation consists of shadscale, sagebrush, native grasses and tulles.</p> <p>Access into the area is provided by U.S. Highway No. 93, the roads servicing the Pahrnagat National Wildlife Refuge and numerous trail roads. A portion of the Pahrnagat National Wildlife Refuge falls within the area. A portion of the Lower Pahrnagat Lake is located in the southeast portion of the township. No mineral formations of consequence were noted during the survey.</p> <hr/>

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Joseph J. Johnson	Cadastral Surveyor
Michelle E. Martin	Supervisory Range Technician
Matthew J. White	Supervisory Range Technician
Michael E. Swope	Student Trainee (Cadastral Surveyor)
Jonathan Grayson	Survey Technician
Michael C. Lambeth	Survey Technician
Clay W. Morrow	Survey Technician
Michael A. Sandoval	Survey Technician
Jose A. Serna	Survey Technician
Brandon K. Grace	Survey Aid

CERTIFICATE OF SURVEY

I, Kane M. Hellebust, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of March, 2010, I have dependently resurveyed the Second Standard Parallel South, through a portion of Range 61 East, a portion of the east boundary, a portion of the subdivisional lines, and a portion of the meanders of Lower Pahrnagat Lake, subdivided certain sections, and conducted metes-and-bounds surveys of certain parcel boundaries through portions of sections 2, 11, 14, 24 and 25, Township 8 South, Range 61 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 28, 2012

Date



Cadastral Surveyor


CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of the Second Standard Parallel South, through a portion of Range 61 East, a portion of the east boundary, a portion of the subdivisional lines, and a portion of the meanders of Lower Pahrnagat Lake, the subdivision of certain sections, and the metes-and-bounds surveys of certain parcel boundaries through portions of sections 2, 11, 14, 24 and 25, Township 8 South, Range 61 East, Mount Diablo Meridian, Nevada, executed by Kane M. Hellebust, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

March 2, 2012

Date



Chief Cadastral Surveyor for Nevada

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 8 S., R. 61 E., Mount Diablo Meridian, Nevada, is a true copy of the original field notes.~~

~~Date~~~~Chief Cadastral Surveyor for Nevada~~