

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Original

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE NORTH BOUNDARY

OF

TOWNSHIP 10 SOUTH, RANGE 62 EAST;

AND THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 22, 27 AND 34,

TOWNSHIP 9 SOUTH, RANGE 62 EAST,

OF THE MOUNT DIABLO MERIDIAN,

IN THE STATE OF NEVADA

EXECUTED BY

Don R. Aschenbach, Cadastral Surveyor

Under Special Instructions dated July 12, 2005,
and approved July 12, 2005,
which provided for the surveys included under Group No. 828,
and Assignment Instructions dated July 12, 2005.

Survey commenced July 15, 2005

Survey completed November 16, 2007

INDEX DIAGRAM

TOWNSHIP 9 SOUTH, RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15 6	14	13
19	20	21	22 5	4 23	24
30	29	28	27 5	4 26	25
31	32	33	34	35 3	36

			2	2	
--	--	--	---	---	--

Subdivision of Section 22 pp. 6 - 8.
 Subdivision of Section 27 pp. 8 - 9.
 Subdivision of Section 34 pp. 9 - 11.

TOWNSHIP 9 SOUTH, RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary of Township 10 South, Range 62 East; and the dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 22, 27 and 34, Township 9 South, Range 62 East, Mount Diablo Meridian, Nevada.

The north boundary (Second Standard Parallel South) was surveyed by U.S. Deputy Surveyor E.B. Monroe in 1869 under Contract No. 31.

A portion of the north boundary (Second Standard Parallel South) was dependently resurveyed, and the south boundary and a portion of the subdivisional lines were surveyed by U.S. Deputy Surveyors W.F. Benson and C.F. Putnam in 1881 under Contract No. 125.

The south boundary and the north boundary (Second Standard Parallel South) were dependently resurveyed and the east and west boundaries and subdivisional lines were surveyed by U.S. Transitsmen H.G. Manson and E.R. Bunbury in 1916-1917 under Group No. 49. The survey of the subdivisional lines superseded the survey of a portion of the subdivisional lines executed by W.F. Benson and C.F. Putnum in 1881.

The east four miles of the north boundary (Second Standard Parallel South) were dependently resurveyed by Cadastral Engineers D.R. Averill and E.A. Taylor and Assistant Cadastral Engineers C.A. Swiatek and J. Boggs in 1952 under Group No. 355.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 828 dated July 12, 2005.

Measurements were made with Trimble 5700 Global Positioning System (GPS) receivers using the real-time kinematic (RTK) method and refer to the true meridian based on geodetic methods. The mean bearings of the lines and horizontal equivalents of ground distances only are entered in the field notes.

The NAD 83 (CORS 96) geographic position of the 1/4 section corner of sec. 2, on the N. bdy. of T. 10 S., R. 62 E., determined from GPS static observations processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS) LVWD Las Vegas Valley CORS ARP, NVCS CARLTON SQUARE CORS ARP and ECHO ECHO CANYON S.P. CORS ARP, in 2005, and carried forward by RTK observations, is as follows:

Latitude: 37°06'56.418" N. Longitude: 115°00'21.072" W.

The mean magnetic declination is 15 1/2° E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "LOWER PAHRANAGAT LAKE, NEV.", dated 1969.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyors W.F. Benson and C.F. Putnam in 1881 and the Resurvey Executed by U.S. Transitmen H.G. Mason and E.R. Bunbury in 1916-1917</p> <hr/>
	<p>Beginning at the 1/4 sec. cor. of sec. 2 only, monumented with a porphyry stone, 18x10x8 ins., firmly set 4 ins. in the ground and in a small mound of stone, mkd. 1/4 on N. face, with a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, S. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;"> <u>T9S R62E</u> 1/4 S 2 T10S R62E 2007 </p> <p>Deposit the original stone alongside the stainless steel post. N. 89°29'20" W., on the N. bdy. of sec. 2.</p> <p>Ascend gradual SE. slope through creosote and scattered cacti.</p>
37.802	<p>The cor. of secs. 34 and 35, T. 9 S., R. 62 E., hereinafter described.</p>
40.868	<p>The cor. of secs. 2 and 3, monumented with a porphyry stone, 21x8x7 ins., firmly set in a small mound of stone, mkd. with 2 grooves on E. and 4 grooves on W. face, with a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;"> <u>T9S R62E</u> S34 <u>S 3 S 2</u> T10S R62E 2005 </p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr/> <p>N. 89°41'30" W., on the N. bdy. of sec. 3.</p> <p>Over rolling land through chaparral, Joshua and yucca, with very little grass.</p>
9.70	<p>Dry wash, 20 lks. wide, drains SE.</p>

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
16.900	The E 1/16 sec. cor. of sec. 34 only, T. 9 S., R. 62 E., hereinafter described.
17.00	Enter mountainous land.
26.30	Top of low ridge, bears SE. and NW.
32.40	Draw, drains SE.
36.866	The 1/4 sec. cor. of sec. 34 only, T. 9 S., R. 62 E., hereinafter described.
39.583	The 1/4 sec. cor. of sec. 3 only, monumented with a porphyry stone, 24x18x12 ins., firmly set in a mound of stone, 4 ft. base, 2 ft. high, mkd. 1/4 on N. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p>T9S R62E <hr style="width: 50px; margin: 0 auto;"/> 1/4 S 3 T10S R62E</p>
	2005
	Deposit the original stone alongside the stainless steel post.
	<hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>Reestablishment of the Survey Executed by U.S. Transitemen H.G. Mason and E.R. Bunbury in 1916-1917</p> <hr/>
	From the 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the subdivision of T. 9 S., R. 62 E., executed under Group No. 49, with a mound of stone, W. of cor.
	S. 0°01'50" W., bet. secs. 34 and 35.
	Over gently rolling land, through greasewood, yucca, and rabbit brush, with very little grass.
38.418	The cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the field notes of resurvey of the south boundary of T. 9 S., R. 62 E., executed under Group No. 49, with a mound of stone, N. of cor.
	From this cor., the cor. of secs. 2 and 3, T. 10 S., R. 62 E., bears N. 89°29'20" W., 3.066 chs. dist., hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the field notes of the subdivision of T. 9 S., R. 62 E., executed under Group No. 49, with a mound of stone, W. of cor.</p> <p>N. 0°18'00" E., bet. secs. 26 and 27.</p> <p>Over rolling land, through greasewood, yucca and rabbit brush, with very little grass.</p> <p>6.00 Dry wash, 30 lks. wide, drains E.</p> <p>14.60 Top of ridge, bears N. 15° W. and S. 50° E.</p> <p>28.00 Enter nearly level land.</p> <p>30.70 Dry wash, 20 lks. wide, drains SE.</p> <p>40.002 Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance. The only remaining evidence of the original corner are the remains of an iron post found nearby. The original position of the post is undeterminable.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T9S R62E 1/4 S27 S26</p> <p style="text-align: center;">2005</p> <p>Deposit the remains of the original post alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>80.004 The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the field notes of the subdivision of T. 9 S., R. 62 E., executed under Group No. 49, with a mound of stone, W. of cor.</p> <hr/> <p>N. 0°06'50" E., bet. secs. 22 and 23.</p> <p>Over nearly level rolling land, through greasewood, yucca, and rabbit brush, with very little grass.</p> <p>11.50 Pahranaagat Wash, 30 lks. wide, drains SE.</p> <p>25.40 Old highway, 40 lks. wide, bears SE. and NW.</p> <p>26.90 Underground fiber optic cable, bears SE. and NW.</p> <p>40.054 The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the subdivision of T. 9 S., R. 62 E., executed under Group No. 49, with a mound of stone, W. of cor.</p> <hr/>
--------	---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	N. 0°04'10" E., beginning new measurement.
1.20	Dry wash, 30 lks. wide, drains SW.
20.20	Dry wash, 20 lks. wide, drains W.
36.10	Dry wash, 30 lks. wide, drains SW.
39.978	The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. as described in the field notes of the subdivision of T. 9 S., R. 62 E., executed under Group No. 49, with a mound of stone, W. of cor.
	From the cor. of secs. 26, 27, 34 and 35.
	N. 89°58'40" W., bet. secs. 27 and 34.
	Over rolling land, through greasewood, yucca and rabbit brush, with very little grass.
4.90	Dry wash, 30 lks. wide, drains NE.
20.015	Point for the E 1/16 sec. cor. of secs. 27 and 34.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	E 1/16 $\frac{S27}{S34}$
	2005
40.030	The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the subdivision of T. 9 S., R. 62 E., executed under Group No. 49, with a mound of stone, N. of cor.
	From the cor. of secs. 22, 23, 26 and 27.
	S. 89°53'50" W., bet. secs. 22 and 27.
	Over rolling land, through greasewood, yucca and rabbit brush, with very little grass.
19.999	Point for the E 1/16 sec. cor. of secs. 22 and 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	E 1/16 $\frac{S22}{S27}$
	2005

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
23.80	Ridge, bears SE. and NW.
30.30	Dry wash, 40 lks. wide, drains SE.
39.998	The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the subdivision of T. 9 S., R. 62 E., executed under Group No. 49, with a mound of stone, N. of cor.
	From the cor. of secs. 14, 15, 22 and 23.
	S. 89°55'30" W., bet. secs. 15 and 22.
	Over rolling land, through greasewood, yucca and rabbit brush, with very little grass.
7.30	Underground fiber optic cable, bears SE. and NW.
7.50	Old highway, 40 lks. wide, bears SE. and NW.
13.70	Pahrnagat Wash, 30 lks. wide, drains SSE.
19.916	Point for the E 1/16 sec. cor. of secs. 15 and 22.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	$\begin{array}{r} \text{E } 1/16 \text{ } \frac{\text{S15}}{\text{S22}} \\ 2005 \end{array}$
20.00	Enter mountainous land.
39.832	The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the subdivision of T. 9 S., R. 62 E., executed under Group No. 49.
	<p>SUBDIVISION OF SECTION 22, T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	From the 1/4 sec. cor. of secs. 22 and 27.
	N. 0°12'20" E., on the N-S center line of sec. 22.
18.40	Dry wash, 20 lks. wide, drains E.
23.30	Dry wash, 20 lks. wide, drains SE.
40.013	Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E-W center line.

SUBDIVISION OF SECTION 22,
T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, flush in rock outcrop, with top mkd.</p> <p style="text-align: center;">T9S R62E C 1/4 S22</p> <p style="text-align: center;">2005</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p>
43.00	Ridge, bears SE. and NW.
58.60	Dry wash, 30 lks. wide, drains E.
69.20	Dry wash, 20 lks. wide, drains SE.
80.053	The 1/4 sec. cor. of secs. 15 and 22.
<hr/>	
	<p>From the 1/4 sec. cor. of secs. 22 and 23.</p> <p>S. 89°50'20" W., on the E-W center line of sec. 22.</p>
1.50	Dry wash, 30 lks. wide, drains SW.
2.50	Underground fiber optic line, bears SE. and NW.
3.00	Old highway, 40 lks. wide, bears SE. and NW.
14.40	Pahrana gat Wash, 30 lks. wide, drains SE.
19.965	Point for the C-E 1/16 sec. cor. of sec. 22.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S22</p> <p style="text-align: center;">2005</p>
30.00	Enter mountainous land.
38.80	Ridge, bears SE. and NW.
39.930	The center 1/4 sec. cor. of sec. 22.
66.20	Draw, drains SE.
79.745	The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the subdivision of T. 9 S., R. 62 E., executed under Group No. 49, with a mound of stone, W. of cor.
<hr/>	

SUBDIVISION OF SECTION 22,
T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	From the C-E 1/16 sec. cor. of sec. 22.
	N. 0°08'20" E., on the N-S center line of the NE1/4 of sec. 22.
16.40	Dry wash, 30 lks. wide, drains SE.
40.009	The E 1/16 sec. cor. of secs. 15 and 22.
<hr/>	
	From the E 1/16 sec. cor. of secs. 22 and 27.
	N. 0°09'40" E., on the N-S center line of the SE1/4 of sec. 22.
18.20	Dry wash, 30 lks. wide, drains E.
40.034	The C-E 1/16 sec. cor. of sec. 22.
<hr/>	
SUBDIVISION OF SECTION 27, T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA	
<hr/>	
	From the 1/4 sec. cor. of secs. 27 and 34.
	N. 0°19'00" E., on the N-S center line of sec. 27.
17.50	Spur, slopes E.
33.00	Dry wash, 30 lks. wide, drains E.
40.127	Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E-W center line.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	T9S R62E C 1/4 S27 2005
56.30	Ridge, bears E. and W.
79.919	The 1/4 sec. cor. of secs. 22 and 27.
<hr/>	
	From the 1/4 sec. cor. of secs. 26 and 27.
	N. 89°48'00" W., on the E-W center line of sec. 27.
7.10	Dry wash, 20 lks. wide, drains SE.
20.007	Point for the C-E 1/16 sec. cor. of sec. 27.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

SUBDIVISION OF SECTION 27,
T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S27} \end{array}$ <p style="text-align: center;">2005</p>
40.014	The center 1/4 sec. cor. of sec. 27.
50.00	Enter mountainous land.
71.00	Draw, drains SE.
80.007	The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the subdivision of T. 9 S., R. 62 E., executed under Group No. 49.
	<hr/> <p>From the C-E 1/16 sec. cor. of sec. 27.</p> <p>N. 0°18'30" E., on the N-S center line of the NE1/4 of sec. 27.</p>
31.40	Dry wash, 30 lks. wide, drains SE.
39.897	The E 1/16 sec. cor. of secs. 22 and 27.
	<hr/> <p>From the E 1/16 sec. cor. of secs. 27 and 34.</p> <p>N. 0°18'30" E., on the N-S center line of the SE1/4 of sec. 27.</p>
18.10	Dry wash, 30 lks. wide, drains SE.
36.00	Ridge, bears SE. and NW.
40.065	The C-E 1/16 sec. cor. of sec. 27.
	<hr/> <p>SUBDIVISION OF SECTION 34, T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>S. 0°02'40" E., on the N-S center line of sec. 34.</p>
24.60	Dry wash, 30 lks. wide, drains SE.
31.40	Dry wash, 20 lks. wide, drains NE.
40.081	Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E-W center line.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9S R62E C 1/4 S34</p> <p style="text-align: center;">2005</p>

SUBDIVISION OF SECTION 34,
T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
51.80	Dry wash, 30 lks. wide, drains NE.; enter mountainous land.
70.70	Draw, drains SE.
78.221	<p>The 1/4 sec. cor. of sec. 34 only, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the resurvey of the south boundary of T. 9 S., R. 62 E., executed under Group No. 49.</p> <p>From this cor., the 1/4 sec. cor. of sec. 3 only, T. 10 S., R. 62 E., bears N. 89°41'30" W., 2.717 chs. dist., hereinbefore described.</p> <hr/> <p>The point for the E 1/16 sec. cor. of sec. 34 only, T. 9 S., R. 62 E., is at midpoint bet. the cor. of secs. 34 and 35 and the 1/4 sec. cor. of sec. 34 only, on the S. bdy. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"><u>E 1/16 S34</u></p> <p style="text-align: center;">2005</p> <p>From this cor., the cor. of secs. 2 and 3, T. 10 S., R. 62 E., bears S. 89°41'30" E., 16.900 chs. dist., hereinbefore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>S. 89°55'30" W., on the E-W center line of sec. 34.</p>
19.989	<p>Point for the C-E 1/16 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">$\frac{E \ 1/16}{C \ \underline{\hspace{1cm}} \ C}$</p> <p style="text-align: center;">S34</p> <p style="text-align: center;">2005</p>
39.978	The center 1/4 sec. cor. of sec. 34.
61.90	Dry wash, 30 lks. wide, drains NE.
71.00	Enter mountainous land.
79.893	The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set in mound of stone, with brass cap mkd. as described in the field notes of the subdivision of T. 9 S., R. 62 E., executed under Group No. 49, with a mound of stone, W. of cor.

SUBDIVISION OF SECTION 34,
T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the C-E 1/16 sec. cor. of sec. 34.</p> <p>N. 0°00'20" W., on the N-S center line of the NE1/4 of sec. 34.</p> <p>6.10 Dry wash, 20 lks. wide, drains SE.</p> <p>16.70 Dry wash, 30 lks. wide, drains NE.</p> <p>20.20 Dry wash, 20 lks. wide, drains NE.</p> <p>40.047 The E 1/16 sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the E 1/16 sec. cor. of sec. 34 only, on the S. bdy. of the Tp.</p> <p>N. 0°00'20" W., on the N-S center line of the SE1/4 of sec. 34.</p> <p>17.20 Dry wash, 30 lks. wide, drains SE.</p> <p>38.279 The C-E 1/16 sec. cor. of sec. 34.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located in Lincoln County, Nevada, about 75 miles north of the City of Las Vegas, Nevada. The area drains southeasterly and the average elevation is about 3000 feet above sea level. Most of the area surveyed varies from rolling to nearly level land covered with greasewood, yucca and rabbit brush, with very little grass. No mineral formations of consequence were noted during the survey.</p> <hr/>
--------	---

UNITED STATES
DEPARTMENT OF INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Steven E. Dagitz	Land Surveyor (Student Trainee)
Derrick J. Rader	Supervisory Range Technician
Antwan R. Dickson	Surveying Technician
David J. Roderiques	Surveying Technician
David L. Schroeder	Survey Aid

CERTIFICATE OF SURVEY

I, Don R. Aschenbach, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of Special Instructions bearing date of the 12th day of July, 2005, I have dependently resurveyed a portion of the north boundary of Township 10 South, Range 62 East; and dependently resurveyed a portion of the subdivisional lines, and subdivided sections 22, 27 and 34, Township 9 South, Range 62 East, of the Mount Diablo Meridian, in the State of Nevada, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 21, 2008

(Date)

Don R. Aschenbach

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Reno, Nevada

The foregoing field notes of the dependent resurvey of a portion of the north boundary of Township 10 South, Range 62 East; and the dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 22, 27 and 34, Township 9 South, Range 62 East, Mount Diablo Meridian, Nevada, executed by Don R. Aschenbach, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

December 2, 2008

(Date)

David D. Morlan

(Chief Cadastral Surveyor, Nevada)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in T. 9 S., R. 62 E., M.D.M., Nevada, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor, Nevada)~~