

Resurvey of the East Boundary of Section 36

of
T. 27 S., R. 59 E.

chains

Thence, N. 0° 03' W., on true line bet. secs. 31 and 36. (N $\frac{1}{2}$)
 Over rolling descent, this scattering understory.

.86 Set an iron post 3 ft. long 1 in. diam., over a cross (X) marked on bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. sec. 36, only, with brass cap marked

1.00 A spur, slopes W.; descend 85 ft.
 13.00 Center of a wash, 3 chs. wide, course W. and SW.; ascend 390 ft. over a broken SE. slope.

39.84 The cor. of secs. 25, 30, 31 and 36, which is a granite stone 20x18x10 ins. above ground, set in a mound of stone 3 ft. base and 1 ft. high and marked with 5 notches on N.; 1 notch on S. sides.

At point for cor. of secs. 25, 30, 31 and 36, with brass cap marked

Set an iron post 3 ft. long 2 ins. diam., 15 ins. in the ground to bedrock, with the original stone corner set alongside, and in a mound of stone to top, for cor. of secs. 25, 30, 31 and 36, with brass cap marked

T 27 S
 R 59 E R 60 E
 S 25 S 30
 S 36 S 31
 1932

Land, mountainous.

Soil, gravelly, 3d rate and rocky, 4th rate.

Undergrowth, creosote brush, sage and cacti.

Resurvey of a Portion of the N. Bdy. of T. 27 S., R. 59 E.

From the cor. of Ts. 26 and 27 S., Rs. 58 and 59 E., hereinafter described.

East on a random line bet. secs. 6 and 31.

.38.74 A point 107 lks. N. of the orig. $\frac{1}{4}$ sec. cor.

79.90 A point 96 lks. N. of the cor. of secs. 5, 6, 31 and 32; a mesquite stake, 2 ins. sq., 2 ft. above a mound of earth 3 ft. base and 1 ft. high, with legible marks: SV on SE., and SVI on SW. sides.

At point for cor.

Set an iron post 3 ft. long 2 ins. diam., 26 ins. in the ground, with the original stake corner set alongside, for cor. of secs. 5, 6, 31 and 32, with brass cap marked

T 26 S R 59 E
 S 31 S 32
 S 6 S 5
 T 27 S
 1932

and raise a

mound of stone 3 ft. base and 1 $\frac{1}{2}$ ft. high west of cor.