

Resurvey of a Portion of the North Boundary

T. 27 S., R. 59 E.

chains
 ✓ Thence, S.89°50'W. on true line bet. secs. 6 and 31. (E½)
 Over rolling desert land, thru scattering undergrowth.
 Ascend 90 ft. over a general E. slope.
 23.00 Foot of hills, bears N. and S.; ascend 150 ft. over a rocky SE. slope.
 30.00 A rocky spur, slopes SW.; descend 65 ft. on SW. slope.
 40.60 A point 40.00 chs. in departure from the SE. cor. of sec. 6, hereinafter described.
 Set an iron post 3 ft. long 1 in. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, for ¼ sec. cor. sec. 6, only, with brass cap marked.
 41.16 The orig. ¼ sec. cor.; a limestone, 14x10x2 ins. above ground, set in a mound of stone 2 ft. base and 1 ft. high and marked ¼ on N. side. As this cor. now refers to sec. 31, only.
 At point for cor.
 Set an iron post 3 ft. long 1 in. diam., 4 ins. in the ground to bedrock, with the original stone corner set alongside, and in a mound of stone to top, for ¼ sec. cor. sec. 31, only, with brass cap marked
¼ S 31
 1932
 ✓ Thence, N.88°25'W., on true line bet. secs. 6 and 31. (W½)
 Ascend 67 ft. over broken SE. slope to
 11.25 Descend 35 ft. to
 16.25 A rocky ravine, course SW.; ascend 145 ft.
 20.70 A spur, slopes SW.; descend 75 ft.
 23.00 A ravine, course SW.; ascend 145 ft.
 31.30 A spur, slopes SW.; descend 200 ft. over rocky SW. slope.
 38.75 The cor. of Ts. 26 and 27 S., Rs. 58 and 59 E.; a limestone, 16x10x9 ins., set on bedrock in a mound of stone 2 ft. base and 1 ft. high and marked with 6 notches on N., S., E. and W. sides.
 At point for cor.
 Set an iron post 3 ft. long 3 ins. diam., over a cross (X) marked on bedrock, with the original stone corner set alongside, and in a mound of stone to top, for cor. of Ts. 26 and 27 S., Rs. 58 and 59 E., with brass cap mkd.

T 26 S
R 58 E R 59 E
S 36 S 31
S 1 S 6
T 27 S

1932