

To and Resurvey of a Portion of the Subdivisions of

11

.S 33 .R . Fractional T. 30 S., R. 62 E.

Chains.	
117.57	Record dist; find no trace of the original closing cor. of frac. secs. 21 and 22.
	Return to the temp. cor. of secs. 9, 10, 15 and 16.
	North on a random line bet. secs. 9 and 10.
40.00	Find no trace of the original $\frac{1}{4}$ sec. cor. Set temp. cor.
80.00	Find no trace of the original cor. of secs. 3, 4, 9 and 10. Set temp. cor. Continue line and measurement bet. secs. 3 and 4.
120.00	Find no trace of the original $\frac{1}{4}$ sec. cor.
156.64	Intersect N. bdy. of Tp., 1.79 chs. W. of the original cor. of secs. 3, 4, 33 and 34, which is a malpais stone, 22x12x10 ins., set in a mound of stone 3 ft. base, 2 ft. high, marked with 3 notches on E. and 3 notches on S. side.
	At point for cor. with the original stone alongside,
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 3, 4, 33, and 34, with brass cap mkd.
	T29S R62E S33 S34 S 4 S 3 T30S 1933
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	The original cor. of secs. 2, 3, 10, and 11, is a catclaw post, 2 ins. sq., 36 ins. long, set in a mound of stone 3 ft. base, 1 ft. high, with marks visible SXI on SE. side, other marks illegible.
	At point for cor. with old post alongside,
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 2, 3, 10, and 11, with brass cap mkd.
	T30S R62E S 3 S 2 S10 S11 1933
	raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.
	Thence
	West on a random line bet. secs. 3 and 10.
40.12	Record dist; find no trace of the original $\frac{1}{4}$ sec. cor.
80.81	A point 94 lks. N. of the temp. cor. of secs. 3, 4, 9 and 10. Continue line and measurement bet. secs. 4 and 9.
120.28	Record dist; find no trace of the original $\frac{1}{4}$ sec. cor.