

Resurvey of a Portion of the Subdivisions
of
T. 24 S., R. 56 E.

chains

1/4

S 6 | S 5

1932

Thence, north on a random line bet. secs. 5 and 6.

40.85 A point 5 lks. E. of the cor. of secs. 5, 6, 31 and 32, on N. bdy. of Tp., hereinafter described.

Return to the 1/4 sec. cor. secs. 5 and 6.

Thence, N.0°04'W., on true line bet. secs. 5 and 6. (W 1/2)

Over rolling hills and rolling washland, drains N.

Descend 25 ft. to

2.50 A spur, slopes NW.; descend 115 ft. over NE. slope, to

40.85 The cor. of secs. 5, 6, 31 and 32; a sandstone, 12x6x6 ins. set in a mound of earth and gravel, 4 ft. base and 1 ft. high; and marked with 5 notches on E., 1 notch on W. sides.

At point for cor.

Set an iron post 3 ft. long 2 ins. diam., 27 ins. in the ground, with the original stone cor. set alongside, for cor. of secs. 5, 6, 31 and 32, with brass cap mkd.

T 23 S R 56 E

S 31 | S 32

S 6 | S 5

T 24 S

1932

No suitable accessories available.

Land, rocky hills, rolling hills and rolling washland.

Soil, rocky, 4th rate; gravelly, 3d rate.

Undergrowth, creosote brush and cacti.

Resurvey of a Portion of the N. Bdy. of T. 24 S., R. 56 E.

Thence,

West on a random line bet. secs. 6 and 31.

40.08 A point 8 lks. N. of the orig. 1/4 sec. cor.

80.39 A point 55 lks. S. of the orig. cor. of Ts. 23 and 24 S., Rs. 55 and 56 E.

Return to the cor. of secs. 5, 6, 31 and 32, on N. bdy. of Tp.

Thence, S.89°53'W., on true line bet. secs. 6 and 31. (E 1/2)

Over rolling washland, thru scattering undergrowth.

Along a gentle N. slope, drains N. and NE.

40.08 The orig. 1/4 sec. cor.; a limestone, 10x8x4 ins.; set in a mound of stone 3 ft. base and 10 ins. high; and marked 1/4 on N. side.