

Resurvey of a Portion of the Subdivisions
of
T. 23 S., R. 55 E.

chains

chains

From this point the 2 mile cor. bet. monuments 116 and 117, on the state boundary, bears S. 46° 12' E., 14.47 chs. dist.; described in the field notes of the Portion of the California-Nevada State Boundary resurveyed under this group.

Land, rolling and level desert.

Soil, sandy, gravelly and rocky, 3d rate.

Undergrowth, creosote, sage, shadscale and cacti.

The orig. cor. of secs. 19, 24, 25 and 30, on E. bdy. of Tp. is a limestone, 4x2x2 ins., marked with a cross X on top and set in a mound of earth, witnessed by pits, N., S., E. and W., about 4 ft. dist. I reset this stone 12 ins. in the ground at exact point for cor., deposited charcoal around stone and raised a mound of stone and earth 1 1/2 ft. base and 1 ft. high west of corner.

Thence, west on a random line bet. secs. 24 and 25.

40.16 Record dist.; find no trace of 1/4 sec. cor.

80.12 A point 156 lks. N. of my temp. cor. of secs. 23, 24, 25 and 26.

Continue line and measurement bet. secs. 23 and 26.

120.32 Record dist.; find no trace of 1/4 sec. cor. Set temp. cor.

160.32 Record dist.; find no trace of cor. of secs. 22, 23, 26 and 27; set temp. cor.

Continue line and measurement bet. secs. 22 and 27.

200.32 Find no trace of orig. 1/4 sec. cor.

207.08 A point 2.43 chs. S. of the orig. clos. cor. of frac. secs. 22 and 27; hereinafter described.

From the temp. cor. of secs. 22, 23, 26 and 27.

North on a random line bet. secs. 22 and 23.

40.00 Find no trace of orig. 1/4 sec. cor.; set temp. cor.

81.54 A point 2.05 chs. W. of the orig. cor. of secs. 14, 15, 22 and 23; hereinafter described.

Return to the cor. of secs. 25, 26, 35 and 36.

Thence, N. 1° 19' W., on true line bet. secs. 25 and 26.

Ascend 30 ft. over a SW. slope, thru undergrowth.

4.50 Top of hills, bears NW. and SE.; descend 100 ft. on NE. slope.

35.00 A wash, course SE.; continue over nearly level land, drains SE.

40.01 Set an iron post 5 ft. long 1 in. diam., 30 ins. in the ground, with a stone, 6x4x3 ins., mkd. X, deposited at the base, for 1/4 sec. cor., with brass cap mkd.