Dependent Resurvey, East Boundary, T. 16 S., R. 14 E.

Chains

T 16 S
R 14 E | R 15 E
S 24 | S 19
S 25 | S 30
1955

Bury the original corner stone alongside the iron post and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, rolling and broken.
Soil, heavy clay; rocky.
Undergrowth, sage.

---

South, bet. secs. 25 and 30.

Desc. gradually over broken SE. slope.

30.30 Dry wash, course E.

40.10 The ¼ sec. cor. of secs. 25 and 30, which is monumented by a basaltic stone, 9x5x4 ins., loosely set in amall mound of stone, mkd. ¼ on W. face.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, with brass cap mkd.

¼
S 25 | S 30
1955

Bury the original corner stone alongside the iron post.
South, beginning new measurement.
Desc. gradually.

2.50 Dry wash, course N. 30° E.; asc. 100 ft. over NW. slope.

31.95 The closing cor. of Tps. 16 S., Rs. 14 and 15 E., on the Idaho-Nevada state line, which is monumented by a basaltic stone, 36x14x7 ins., firmly set in a mound of stone, mkd. CC and 5 grooves on N. and 6 grooves on E. face.

At the corner point

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with brass cap mkd.

CC
T 16 S
R 14 E | R 15 E
S 25 | S 30
NEV
1955

Bury the original corner stone alongside the iron post and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.