

North Boundary of T. 24 N., R. 23 E.

Chains

East bet. secs. 3 and 34.

Over mountainous land, gradually descending.

33.02 Intersect the E. bdy. of the Pyramid Lake Indian Reservation at a point from which the 31 M.P. hrs. N.11°40'E., 8.96 chs.

Set an iron post. 3 ins. dia., for C.C. of frac. Tps. 24 and 25 N., R. 23 E., with brass cap stamped

PL on E.
CC PLIR on W.
T 25 N R 23 E S 34 on NW.
T 24 N S 3 on SW,
1912 on S.
6 notches on N. and S. edges

Build a mound of stone 2 ft. base, 1½ ft. high, W. of cor.

Thence continue line over Public land.

39.00 Road, hrs. N. 10° E. and S. 10° W.

40.00 Set an iron post for ¼ sec. cor. bet. secs. 3 and 34, with brass cap stamped

¼ S 34 in N. half
S 3 1912 in S. half

Build a mound of stone 2 ft. base, 1½ ft. high, N. of cor.

49.07 To shore of Winnemucca Lake, hrs. N. and S.

Set an iron post, 1 inch. in diameter, for M.C. of frac. secs. 3 and 34, with brass cap stamped

MC in E.
T 25 N R 23 E S 34 in NW.
T 24 N S 3 in SW.
1912 in S.
6 notches on N. and S. edge

Build a mound of stone 2 ft. base, 1½ ft. high, W. of cor.

Land, mountainous and rolling, - grazing.
Soil, sandy and rocky, 3rd rate.
No timber.

May 15, 1912.

Guy P. Harrington,
U. S. Surveyor.