## Chains

Survey commenced May 13, 1912, by Earl G. Harrington, Transitman.

May 14, 1912. At 8h 00m A.M., 1 m t., I set off 39° 59° on the lat. arc, 18° 39½° N. on the decl. arc, and determine a meridian with the solar, at the cor. of Tps. 24 and 25 N., Rgs. 22 and 23 E., previously described.

Thence I run

West bet. secs. 1 and 36.

Over rough, mountainous land, ascending steep E. slope of ridge.

- 4.75 Drain, course S. 60° E.
- 15.00 Top of ascent. Ridge, brs. NW. and SE. Begin descent of SW. slope.
- 20.90 Bottom of descent. Dry drain, course S. 45° E. Begin ascent of E. slope.
- 40.00 Set an iron post for 2 sec cor. bet. secs. 1 and 36, with brass cap stamped

\$ \$ 36 in N. half S 1 1912 in S. half

Build a mound of stone 2 ft. base, la ft. high, N. of cor.

- 58.95 Top of ascent. Ridge, brs. N. and S. Begin descent of W. slope.
- 64.00 Drain, course S. 35° W.
- 65.10 Bottom of descent. Dry drain, course S. 45° E. Begin ascent of E. slope.
- 80.00 Set an iron post for the cor. of secs. 1, 2, 35 and 36, with brass cap stamped

T 25 N S 36 in NE. quadrant
R 22 E S 1 in SE. quadrant
T 24 N S 2 in SW. quadrant
S 35 in NW. quadrant
1912 in S.

1 notch on E. and 5 notches on W. edge

Build a mound of stone 2 ft. base, la ft. high, W. of cor.

Land, very rough and mountainous, - barren. Soil, stony, 3rd rate.
No timber.

May 14, 1912. At this cor. I set off 180 413' N. on the