

North Boundary of T. 24 N., R. 22 E.

Chains

$\frac{1}{4}$ S 34 in N. half
S 3 1912 in S. half

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

43.40 Top of rocky ridge. Begin descent of W. slope of rocky ridge.

48.10 To shore of Pyramid Lake, brs. N. 15° W. and S. 15° E.
Set an iron post for M.C. of frac. secs. 3 and 34, with brass cap stamped

M C in W.
T 25 N S 34 in NE.
T 24 N R 22 E S 3 in SE.
1912 in S.
6 notches on N. and S. edges

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

Fremont's
Pyramid brs. S. $16^{\circ} 32'$ W.

Land, rough and mountainous, - grazing.
Soil, sandy and rocky, 3rd rate.
No timber.

May 14, 1912.

Earl G. Harrington,
Transitman.

West Boundary of frac. T. 25 N., R. 23 E.

Survey commenced May 20, 1912, by Guy P. Harrington, U. S. Surveyor.

May 20, 1912. At 8h 00m a.m., l.m.t., I set off $39^{\circ} 59'$ on the lat. arc, $20^{\circ} 00\frac{1}{4}'$ N. on the decl. arc, and determine a meridian with the solar, at the cor. of Tps. 24 and 25 N., Rgs. 22 and 23 E., previously described.

Thence I run

North bet. secs. 31 and 36.

Over rough, mountainous land, ascending S. slope.

40.00 Set an iron post for $\frac{1}{4}$ sec. cor. bet. secs. 31 and 36, with brass cap stamped

$\frac{1}{4}$ S 36 in W. half
S 31 in E. half
1912 in S.