Chains

Survey commenced May 22, 1912, by Guy P. Harrington, U. S. Surveyor.

May 22, 1912. At 8h 00m A.M., l.m.t., I set off 40° 04½' on the lat. arc; 20° 25' N. on the decl. arc, and determine a meridian with the solar, at the cor. of Tps. 25 and 26 N., Rgs 22 and 23 E., previously described.

Thence I run

East bet. secs. 6 and 31.

Over very rough and mountainous land, ascending steep
   West slope.

4.10 Top of ascent. Ridge, brs. N. 10° E. and S. 10° W.

Thence along SW. slope of ridge.

40.00 Set an iron post for the ¼ sec. cor. bet. secs. 6 and 31,
   with brass cap stamped

     ¼ S 31 in N. half
       S 6 1912 in S. half

Build a mound of stone 2 ft. base, 1½ ft. high, N. of cor.

40.10 Top of ascent. Ridge, brs. N. 60° W. and S.

Begin descent of E. slope.

80.00 Set an iron post for the cor. of secs. 5, 6, 31 and 32,
   with brass cap stamped

     T 26 N S 32 in NE. quadrant
     R 23 E S 5 in SE. quadrant
     T 25 N S 6 in SW. quadrant
         S 31 in NW. quadrant
     1912 in S.
     5 notches on E. and 1 notch on W. edge

Build a mound of stone 2 ft. base, 1½ ft. high, W. of cor.

Land, very rough and mountainous, - barren and grazing.
Soil, rocky, 3rd rate.
No timber.

May 22, 1912. At this cor., I set off 20° 26¼' N. on the
decl. arc, and at 11h 56m 28s A.M., l.m.t., observe the
sun on the meridian; the resulting lat. is 40° 04½',
which is the correct lat.