

West Boundary of frac. T. 26 N., R. 23 E.

Chains.

40.00 Set an iron post for the $\frac{1}{4}$ sec. cor. bet. secs. 7 and 12,
with brass cap stamped

$\frac{1}{4}$ S 12 in W. half
S 7 in E. half
1912 in S.

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

41.00 Top of ascent. Ridge, brs. E. and W.

Begin descent over broken slope.

44.90 Draw, course N. 80° E.

58.60 Ridge, brs. N. 50° E. and S. 50° W.

79.95 Deep drain, course N. 60° E.

Spring on line.

Bottom of descent. Begin ascent.

80.00 Set an iron post for the cor. of secs. 1, 6, 7 and 12,
with brass cap stamped

T 26 N S 6 in NE. quadrant
R 23 E S 7 in SE. quadrant
S 12 in SW. quadrant
R 22 E S 1 in NW. quadrant
1912 in S.

5 notches on S. and 1 notch on N. edge

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rough and mountainous, - grazing.

Soil, rocky, 3rd rate.

Scattered juniper timber, full distance.

North bet. secs. 1 and 6.

Over rough, mountainous land, ascending broken slope.

16.00 Top of ascent. Ridge, brs. E. and W. Begin descent.

33.60 Bottom of descent. Drain, containing running water, 1 lk.
wide, course S. 40° E. Begin ascent.

40.00 Set an iron post for the $\frac{1}{4}$ sec. cor. bet. secs. 1 and 6,
with brass cap stamped

$\frac{1}{4}$ S 1 in W. half
S 6 in E. half
1912 in S.

Build a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.