

North Boundary of frac. T. 26 N., R. 23 E.

Chains

Survey commenced June 1, 1912, by Earl G. Harrington,
Transitman.

June 1, 1912. At 8h 00m A.M., l.m.t., I set off $40^{\circ} 09'$
on the lat. arc, $22^{\circ} 05'$ N. on the decl. arc, and deter-
mine a meridian with the solar, at the cor. of Tps. 26
and 27 N., Rgs. 22 and 23 E.

Thence I run

East bet. secs. 6 and 31.

Over rough, mountainous land, descending E. slope.

40.00 Set an iron post for $\frac{1}{4}$ sec. cor. bet. secs. 6 and 31, with
brass cap stamped

$\frac{1}{4}$ S 31 in N. half
S 6 1912 in S. half

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of
cor.

59.90 Bottom of descent. Dry drain, course N. 10° E.

Begin ascent.

74.50 Top of ascent. Ridge, brs. NE. and SW. Begin descent.

80.00 Set an iron post for the cor. of secs. 5, 6, 31 and 32,
with brass cap stamped

T 27 N S 32 in NE. quadrant
R 23 E S 5 in SE. quadrant
T 26 N S 6 in SW. quadrant
S 31 in NW. quadrant
1912 in S.
5 notches on E. and 1 notch on W. edge

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of
cor.

Land, rough and mountainous, - grazing.
Soil, rocky, 3rd rate.
Scattered juniper timber, full distance.

East bet. secs. 5 and 32.

Over mountainous land, descending.

7.15 Bottom of descent. Deep drain, course N. Begin ascent.

24.00 Top of ascent. Ridge, brs. NE. and SW. Begin descent.

40.00 Set an iron post for $\frac{1}{4}$ sec. cor. bet. secs. 5 and 32,
with brass cap stamped