

North Boundary of frac. T. 26 N., R. 23 E.

Chains

East bet. secs. 2 and 35.

Over rolling land, descending gradual slope towards
Winnemucca Lake.

25.75 Road, brs. N. and S.

26.50 To shore of Winnemucca Lake, brs. N. and S.

Set an iron post, 1 inch in dia., for M.C. of frac. secs.
2 and 35, with brass cap stamped

M C in E.
T 26 N S 2 in SW.
T 27 N R 23 E S 35 in NW.
1912 in S.
6 notches on N. and S. edge

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of
cor.

Land, nearly level, - grazing.
Soil, sandy, 3rd rate.
No timber.
Scattered sage brush, full distance.

June 1, 1912.

Earl G. Harrington,
Transitman.

West boundary of frac. T. 27 N., R. 23 E.

Survey commenced June 15, 1912, by Earl G. Harrington,
transitman.

June 15, 1912. At 8h 00m A.M., l.m.t., I set off $40^{\circ}09\frac{1}{2}'$
on the lat. arc; $23^{\circ}20'$ N. on the decl. arc, and deter-
mine a meridian with the solar at the cor. of Tps. 26
and 27 N., Rgs. 22 and 23 E.

Thence I run

North bet. secs. 31 and 36.

Over rough, mountainous land, along E. slope of ridge.

12.30 Low ridge, brs. E. and W. Begin descent.

22.30 Bottom of descent. Dry drain, course E. Begin ascent.

32.20 Head of draw, course E.

40.00 Set an iron post for $\frac{1}{4}$ sec. cor. bet. secs. 31 and 36,
with brass cap stamped