

## West Bdy. of T. 21 N. R. 24 E.

## Chains

West of and alongside rock set an iron post for W.C.  
with brass cap stamped

T 21 N S 6 in NE. quadrant  
R 24 E S 7 in SE. quadrant  
S 12 in SW. quadrant  
R 23 E S 1 in NW. quadrant  
W C in addition  
1 notch on N. and 5 on S. edges

Land, gently rolling.  
Soil, sandy loam, 1st rate.

From the cor. of secs. 1, 6, 7 and 12 I run

North on a random line bet. secs. 1 and 6.

20.00 Set temp. 1/16 sec. cor.

40.18 Falls 8 lks. W. of the  $\frac{1}{4}$  sec. cor. bet. secs. 1 and 6,  
which is a granite stone 12x8x6 ins. above ground, mkd.  
 $\frac{1}{4}$  on W. face and witnessed by a mound of stone to W.

Returning to the cor. of secs. 1, 6, 7 and 12 I run

N.  $0^{\circ} 07'$  E. on a true line bet. secs. 1 and 6.

Along gradual east slope.

20.09 Set an iron post for the 1/16 sec. cor. No. 12 bet. secs.  
1 and 6 (S.  $\frac{1}{4}$ ) with brass stamped

1/16 S 1 in W. half  
S 6 in E. half  
No 12 in S.

Build a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft.  
high, W. of cor.

40.18 The  $\frac{1}{4}$  sec. cor. bet. secs. 1 and 6.

West of and alongside stone set an iron post for W.C.  
with brass cap stamped

$\frac{1}{4}$  S 1 in W. half  
S 6 in E. half  
W C in addition

From this  $\frac{1}{4}$  sec. cor. I run

North on a random line bet. secs. 1 and 6 (N.  $\frac{1}{4}$ )

20.00 Set temp. 1/16 sec. cor.

40.20 Falls 5 lks. E. of cor. of Tps. 21 and 22 N. Rgs. 23 and  
24 E., which is a granite rock 14x10x8 ins. above  
ground, mkd. with 6 notches on N. S. E. and W. edges  
and witnessed by a mound of stone to S.