

North Bdy. of T. 21 N. R. 23 E.

Chains

Dig pits 18x18x12 ins., E. and W. of cor.,
3 ft. dist., raise a mound of earth $3\frac{1}{2}$ ft.
base, $1\frac{1}{2}$ ft. high, N. of cor.

80.06 The cor. of secs. 35 and 36.

West of and alongside the stone set an iron post for W.C.
with brass cap stamped

T 22 N. S 36 in NE. quadrant
R 23 E S 35 in NW. quadrant
1 notch on E. and 5 notches on W. edge

82.56 Set an iron post for C.C., 6.40 chs. S. $0^{\circ} 18'$ E. of the
NE. cor.
of sec. 2 with brass cap stamped

T 22 N S 35 in NE. quadrant
T 21 N R 23 E S 1 in SE. quadrant
C C in E. edge
and W C in addition

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.

Land, gentle east slope.
Soil, sandy and stony, 2nd rate.

From the NE. cor. of sec. 2, I run

West on a random line bet. secs. 2 and 35.

22.80 Intersect the C.C. of secs. 2 and 35 on the reservation
bdy., which is a volcanic rock 20x12x6 ins. above
ground, mkd. P.L.I.R. on E. C.C. on W. face and wit-
nessed by a mound of stone, W. of cor.

Returning to the NE. cor. of sec. 2, thence I run

West on a true line bet. secs. 2 and 35.

Ascending gradual east slope.

22.80 The C.C. of secs. 2 and 35 on the reservation bdy.,
West of and alongside the rock set an iron post for W.C.
with brass cap stamped

C C in E. edge
T 22 N S 35 in NE. quadrant
R 23 E S 2 in SE. quadrant
P L I R in middle
and W C in addition
6 notches on N. and 6 on S. edges

This cor. is 8.04 chs. N. $20^{\circ} 37'$ W. of the 131 $\frac{1}{2}$ M.P.

Land, gentle east slope.
Soil, sandy and stony, 2nd rate.

Guy P. Harrington,
U. S. Surveyor.