

## North bdy. of T. 23 N. R. 21 E.

## Chains

Survey commenced July 15, 1911.

From the cor. of Tps. 23 and 24 N., Rgs. 21 and 22 E.,

I run

West on a true line bet. secs. 1 and 36.

Over rolling land.

13.75 Wire fence, brs. N. 30° E. and S. 30° W. Joins fence from  
S. 70° E. Thence ascend sandy slope, bearing N. and S.

25.00 Top of ascent on sandy bench, brs. N. and S.

28.75 Road, brs. N. 10° E. and S. 10° W.

40.00 Set an iron post for  $\frac{1}{4}$  sec. cor. bet. secs. 1 and 36,  
with brass cap stamped

$\frac{1}{4}$  S 36 in N. half  
S 1 in S. half

Dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist.,  
and raise a mound of earth 3 $\frac{1}{2}$  ft. base, 1 $\frac{1}{2}$  ft. high,  
N. of cor.

80.00 Set an iron post for the cor. of secs. 1, 2, 35 and 36,  
with brass cap stamped

T 24 N S 36 in NE. quadrant  
R 21 E S 1 in SE. quadrant  
T 23 N S 2 in SW. quadrant  
S 35 in NW. quadrant  
1 notch on E. and 5 notches on W. edges

Dig pits 18x18x12 ins. in each sec. 5 $\frac{1}{2}$  ft. dist., and  
raise a mound of earth 4 ft. base, 2 ft. high, W. of cor.  
Land, rolling, - grazing.  
Soil, sandy 3rd rate.

From the cor. of secs. 1, 2, 35 and 36, I run

West on a true line bet. secs. 2 and 35.

Over gently rolling land.

40.00 Set an iron post for  $\frac{1}{4}$  sec. cor. bet. secs. 2 and 35,  
with brass cap stamped

$\frac{1}{4}$  S 35 in N. half  
S 2 in S. half

Dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist.,  
and raise a mound of earth 3 $\frac{1}{2}$  ft. base, 1 $\frac{1}{2}$  ft. high,  
N. of cor.

Thence steep ascent of mountain.