

North boundary of T. 23 N. R. 22 E.

Chains

Survey commenced July 14.

From the M.C. bet. secs. 4 and 5, T. 23 N. R. 22 E., on bank of Pyramid Lake, I offset W. 42.40 chs. - Thence N. $0^{\circ} 03' W.$ 20.45 chs. to bank of Pyramid Lake.

Set an iron post 3 ft. long, 3 ins. dia. 26 ins. in the ground, for M.C. of frac. secs. 5 and 32, on line bet. Tps. 23 and 24 N., R. 22 E., with brass cap stamped

T 23 N S 5 in SW. quadrant
T 24 N R 22 E S 32 in NW. quadrant
M C in E. half
6 notches on S. edge, and 6 on N. edge

Dig a pit 36x36x12 ins. 8 ft. W. of cor., and raise a mound of earth 4 ft. base, 2 ft. high, W. of cor.

Thence I run

West on a true line bet. secs. 5 and 32.

Over gently rolling land.

5.32 Road, brs. N. and S.

9.92 Road, brs. N. and S.

37.60 Set an iron post for cor. of secs. 5, 6, 31 and 32, with brass cap stamped

T 24 N S 32 in NE. quadrant
R 22 E S 5 in SE. quadrant
T 23 N S 6 in SW. quadrant
S 31 in NW. quadrant
5 notches on E. and 1 notch on W. edge

Dig pits 18x18x12 ins. in each sec. $5\frac{1}{2}$ ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, W. of cor,

Land, gently rolling, - grazing.
Soil, sandy, 2nd rate.

From the cor. of secs. 5, 6, 31 and 32, I run

West on a true line bet. secs. 6 and 31.

Ascending gentle NE. slope.

40.00 Set an iron post for $\frac{1}{4}$ sec. cor. bet. secs. 6 and 31, with brass cap stamped

$\frac{1}{4}$ S 31 in N. half
S 6 in S. half

Dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist., and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high,