

West bdy. of frac. T. 27 N. R. 21 E.

Sept. 2, 1911.

From the cor. of secs. 13, 18, 19 and 24, as described in subdivision notes of frac. T. 27 N. R. 20 E., I run South on a true line bet. secs. 19 and 24.

Over nearly level land.

2.00 Old road, brs. E. and W.

11.65 Bank of Pyramid Lake, brs. E. and W.

Set an iron post for meander cor. bet. secs. 19 and 24, with brass cap stamped

M C in S. half
T 27 N R 21 E S 19 in NE. quadrant
R 20 E S 24 in NW. quadrant
6 notches on E. and W. edges.

Dig a pit 36x36x12 ins. 8 ft. N. of cor., and raise a mound of earth 4 ft. base, 2 ft. high, N. of post.

Land, nearly level, - grazing.
Soil, sandy and stony, 3rd rate.

From the cor. of secs. 13, 18, 19 and 24, I run North on a true line bet. secs. 13 and 18.

Over nearly level land.

35.00 Begin gradual ascent along SW. slope.

40.00 Set an iron post for the 1/2 sec. cor. bet. secs. 13 and 18, with brass cap stamped

1/2 S 13 in W. half
S 18 in E. half

Build a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

55.50 Deep draw, drains S. 50° W.

Thence steep ascent of SW. slope.

65.50 Top of steep ascent.

Thence along W. slope.

80.00 Set an iron post for the cor. of secs. 7, 12, 13 and 18, with brass cap stamped

T 27 N S 7 in NE. quadrant
R 21 E S 18 in SE. quadrant
S 13 in SW. quadrant
R 20 E S 12 in NW. quadrant
4 notches on S. and 2 notches on N. edges

Build a mound of stone 2 ft. base, 1 1/2 ft. high, W. of cor.