

North bdy. of T. 27 N. R. 22 E.

Chains.

T 28 N S 35 in NE. quadrant
 R 22 E S 2 in SE. quadrant
 T 27 N S 3 in SW. quadrant
 S 34 in NW. quadrant
 2 notches on E. and 4 on W. edges

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous, - grazing.

Soil, stony, 3rd rate.

From the cor. of secs. 2, 3, 34 and 35, I run

East on a true line bet. secs. 2 and 35.

Continue ascent of SW. slope.

10.50 Top of ascent on SW. slope.

Thence descend NE. slope.

35.25 Bottom of descent in draw, drains S. 45° W.

Thence ascend steep rocky W. slope.

40.00 Set an iron post for the $\frac{1}{4}$ sec. cor. bet. secs. 2 and 35,
 with brass cap stamped

$\frac{1}{4}$ S 35 in N. half
 S 2 in S. half

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

68.90 Top of ascent on ridge, brs. N. and S.

Thence descend SE. slope.

80.00 Set an iron post for the cor. of secs. 1, 2, 35 and 36,
 with brass cap stamped

T 28 N S 36 in NE. quadrant
 R 22 E S 1 in SE. quadrant
 T 27 N S 2 in SW. quadrant
 S 35 in NW. quadrant
 1 notch on E. and 5 notches on W. edge

Build a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous, - grazing.

Soil, stony, 3rd rate.

From the cor. of secs. 1, 2, 35 and 36, I run

East on a true line bet. secs. 1 and 36.

Continuing descent.

21.00 Bottom of descent.

Small draw, drains S.