

North bdy. of T. 27 N. R. 23 E.

Chains

67.00 Top of ascent on ridge, brs. N. and S.

Thence descend SE. slope.

80.00 Set an iron post for the cor. of secs. 4, 5, 32 and 33,

with brass cap stamped

T 28 N S 33 in NE. quadrant

R 23 E S 4 in SE. quadrant

T 27 N S 5 in SW. quadrant

S 32 in NW. quadrant

4 notches on E. and 2 notches on W. edge

Build a mound of stone 2 ft. base, 1½ ft. high, W. of cor.

Land, mountainous, - grazing.

Soil, stony, 3rd rate.

From the cor. of secs. 4, 5, 32 and 33, I run

East on a true line bet. secs. 4 and 33.

Continuing descent.

19.53 Intersect the reservation bdy. 2.48 chs. S. 32° 04' E. of the
50 Mile Post.

Set an iron post 3 ft. long, 3 ins. dia., 26 ins. in the
ground, for the C.C. of Tps. 27 and 28 N., R. 23 E.,
with brass cap stamped

C C in W. edge

T 28 N R 23 E S 33 in NW. quadrant

T 27 N S 4 in SW. quadrant

P L I R in middle

6 notches on N. and S. edges

Build a mound of stone 4 ft. base, 2 ft. high, W. of cor.

Land, mountainous, - grazing.

Soil, stony, 3rd rate.

GUY P. HARRINGTON

U. S. Surveyor.