

North bdy. of T. 28 N., R. 20 E.

Chains

Dig pits 18x18x12 ins. E. and W. of cor., 3 ft. dist., and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

80.00 Set an iron post for the cor. of secs. 5, 6, 31 and 32, with brass cap stamped

T 29 N S 32 in NE. quadrant  
R 20 E S 5 in SE. quadrant  
T 28 N S 6 in SW. quadrant  
S 31 in NW. quadrant  
5 notches on E. and 1 notch on W. edge

Dig pits 18x18x12 ins. in each sec.  $5\frac{1}{2}$  ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, W. of cor.

Land, nearly level, barren desert.  
Soil, sandy and alkali, 3rd rate.

From the cor. of secs. 5, 6, 31 and 32, I run West bet. secs. 6 and 31.

40.00 Set an iron post for  $\frac{1}{4}$  sec. cor. bet. secs. 6 and 31, with brass cap stamped

$\frac{1}{4}$  S 31 in N. half  
S 6 in S. half

Dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist., and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

46.00 Road, brs. S.  $25^{\circ}$  W. and N.  $25^{\circ}$  E.

76.16 Intersect the E. bdy. of T. 28 N., R. 19 E., 8.35 chs.

South of the cor. of Tps. 28 and 29 N., Rg. 19 E.

Set an iron post 3 ft. long, 3 ins. dia., 26 ins. in the ground, for C.C. of Tps. 28 and 29 N., R. 20 E., with brass cap stamped

C C in E.  
T 29 N S 31 in NE. quadrant  
T 28 N R 20 E S 6 in SE. quadrant  
6 notches on N. and S. edges

Dig pits 30x24x12 ins. on each line N. and S. of cor. 4 ft., and E. of cor. 8 ft. dist., and raise a mound of earth 5 ft. base,  $2\frac{1}{2}$  ft. high, E. of cor.

Land, nearly level, barren desert.  
Soil, sandy and alkali, 3rd rate.

Guy P. Harrington

U. S. Surveyor.