

Subdivision of T. 29 N. R. 19 E.

Chains.

PLIR in middle
CC in N.
T 29 N S 14 in NE. quadrant
R 19 E S 15 in NW. quadrant
2 notches on E. and 4 on W. edges.

Dig a pit 30x24x12 ins. on line SE. of cor., 3 ft. dist.
and a pit 24x18x12 ins. N. of cor., 7 ft. dist., and
raise a mound of earth 4 ft. base, 2 ft. high, N. of cor.

Thence over gently rolling land, within the reservation, on same bearing, and new measurement.

24.66 Intersect N. bdy. of Reservation, 6.76 chs. S. 85° 12' E. of Station 9.

Set an iron post 26 ins. in the ground, for closing cor. of secs.

14 and 15, with brass cap stamped

PLIR in middle
CC in S.
T 29 N S 15 in SW. quadrant
R 19 E S 14 in SE. quadrant
2 notches on E. and 4 on W. edge.

Dig pits 24x18x12 ins. crosswise on each line E. and W. 3 ft.,
and S. of cor. 7 ft. dist., and raise a mound of earth 4 ft. base,
2 ft. high, S. of cor.

Land, gently rolling, grazing.
Soil, sandy, 3rd rate.

GENERAL DESCRIPTION

This township consists of desert land, devoid of vegetation. The soil is alkali, 3rd rate.

A small amount of grazing land is situated in sec. 14, 15, 23, 26, 35 and 36.

GUY P. HARRINGTON

U. S. Surveyor

List of Assistants:

Earl G. Harrington (Instrumentmen
Archie J. Strane)

Louis G. Hurst (Chainmen
William Cort)
Roy Simmonds (Chainmen
C. A. Simson)

Joe Flinchpaugh (Flagmen
Raymond R. Reed)

Warren Quigley (Axemen
Geo. A. Keller)

J. W. Rodgers (Moundsmen
Clifford Mc Laughlin)